

Guidelines for NLgov profile for CloudEvents

Project Notificatieservices



Logius Guide

Draft May 22, 2026

This version:

<https://logius-standaarden.github.io/CloudEvents-NL-Guidelines/>

Latest published version:

<https://gitdocumentatie.logius.nl/publicatie/notificatieservices/guidelines/>

Latest editor's draft:

<https://logius-standaarden.github.io/CloudEvents-NL-Guidelines/>

Previous version:

<https://gitdocumentatie.logius.nl/publicatie/notificatieservices/guidelines/0.3/>

Editors:

Gershon Jansen ([VNG Realisatie](#))

Ad Gerrits ([VNG Realisatie](#))

[Edwin Wisse](#) (Logius)

Author:

Ad Gerrits ([VNG Realisatie](#))

Participate:

[GitHub Logius-standaarden/CloudEvents-NL-Guidelines](#)

[All issues](#)

[File an issue](#)

[Commit history](#)

[Pull requests](#)

This document is also available in these non-normative format: [PDF](#)



This document is licensed under

[Creative Commons Attribution 4.0 International Public License](#)

Status of This Document

This is a draft that could be altered, removed or replaced by other documents. It is not a recommendation approved by TO.

Table of Contents

Status of This Document

Conformance

Abstract

1. Guideline for the use of the HTTP Protocol Binding for CloudEvents

- 1.1 Summary with points for attention
- 1.2 Recommendations
- 1.3 Examples
- 1.4 Normative References

2. Guideline for the use of the JSON Event Format for CloudEvents

- 2.1 Summary with points for attention
- 2.2 Recommendations
- 2.3 Examples
- 2.4 Normative References

3. Guideline for the use of the Webhook pattern for CloudEvents

- 3.1 Summary with points for attention
 - 3.1.1 Delivering notifications
 - 3.1.2 Authorization
 - 3.1.3 Abuse protection
- 3.2 Recommendations
- 3.3 Examples
- 3.4 Normative References

A. Index

- A.1 Terms defined by this specification
- A.2 Terms defined by reference

B. References

- B.1 Normative references
- B.2 Informative references

§ Conformance

As well as sections marked as non-normative, all authoring guidelines, diagrams, examples, and notes in this specification are non-normative. Everything else in this specification is normative.

The key words *MAY*, *MUST*, *MUST NOT*, *OPTIONAL*, *SHOULD*, and *SHOULD NOT* in this document are to be interpreted as described in [BCP 14 \[RFC2119\]](#) [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

Abstract

This document is provides guidelines for [[NLgov.CloudEvents](#)] for multiple transport protocols including HTTP, JSON event format and Webhooks. For each transport protocol, there are lists of things to keep in mind and examples on how to do so.

§1. Guideline for the use of the HTTP Protocol Binding for CloudEvents

The CloudEvents message format can be used when using different formats and protocols and patterns. In order to be able to use the NLgov profile for CloudEvents properly in practice, agreements must also be made when and in what way a certain format, protocol or pattern is used.

The Serverless Working Group has described how the HTTP protocol can be used in a standardized way in combination with the CloudEvents message format: [HTTP Protocol Binding for CloudEvents](#). The specification defines how the elements defined in the CloudEvents specification are to be used in HTTP 1.1 requests and response messages.

Similar to what happened in the NLgov profile for CloudEvents, this guideline makes recommendations about the use of the HTTP specification within the context of the Dutch government. These are intended to make use of the specification more unambiguous and to work towards standardisation in the long term.

§1.1 Summary with points for attention

- Events can be transferred with all standard or application-defined HTTP request methods that support payload body transfers. Events can be also be transferred in HTTP responses and with all HTTP status codes that permit payload body transfers.
- This specification defines three content modes for transferring events:
 - structured (required): HTTP message body contains both event data and metadata attributes; an appropriate event format is used ((non-batching) JSON is the only event format that *MUST* be supported);
 - batched (optional): HTTP message body contains event data and metadata attributes from multiple events; an appropriate event format is used.
 - binary (required): HTTP message body contains event data as-is; event attributes mapped to HTTP-headers; HTTP Content-Type header declares the media type.
- Received Content-Type header value is:
 - `application/cloudevents(+xxxx)`: structured mode (xxx denotes the used event format)
 - `application/cloudevents-batch`: batched mode
 - Otherwise: binary mode (Content-Type header declares the media type.)
- Structured content mode:
 - The HTTP message body *MUST* contain both event data and metadata attributes.
 - The HTTP Content-Type header *MUST* be set to the media type of an event format (E.g. `application/cloudevents+json; charset=UTF-8`)
 - The chosen event format defines how all attributes, and data, are represented in the HTTP message body.
 - Implementations *MAY* include the same HTTP headers as defined for the binary mode (E.g. `ce-id`).
- Batched content mode:
 - The HTTP message body *MUST* contain both event data and metadata attributes.
 - The HTTP Content-Type header *MUST* be set to the media type of an event format (E.g. `application/cloudevents-batch+json; charset=UTF-8`)
 - The chosen event format defines how a batch of events and all event attributes, and data, are represented.
 - All batched CloudEvents *MUST* have the same `specversion` attribute. Other attributes *MAY* differ, including the `datacontenttype` attribute. The batch *MAY* be empty.

- Binary content mode:
 - All CloudEvents context attributes, including extensions, *MUST* be mapped to HTTP headers with the same name as the attribute name but prefixed with `ce-`.
 - The value for each HTTP header is constructed as described in the [specification](#)

At the moment there are *no additional agreements* about the use of the specification within the Dutch government.

§1.2 Recommendations

- One *SHOULD* use the [HTTP Protocol Binding for CloudEvents](#).
- There are no agreements to deviate from the standard in any part.
- Given the fact that many organizations still have little experience with standardized exchange of events, we recommend a useful relatively simple mechanism that consumers are already familiar with:
 - One *SHOULD* use structured content mode.
 - One *SHOULD* use the JSON (non batched) event format
 - When using structured mode one *SHOULD NOT* depend on the usage of HTTP-headers that replicate context-attributes in the event.
- If the above advice is followed, when notifying via webhooks 1 message will contain JSON-structured data about 1 event that has occurred.

§1.3 Examples

Structured content mode: HTTP POST request with a JSON event format encoded event:

```
POST /myresource HTTP/1.1
Host: webhook.example.com
Content-Type: application/cloudevents+json; charset=utf-8
Content-Length: nnnn

{
  "specversion": "1.0",
  "type": "nl.overheid.zaken.zaakstatus-gewijzigd",
  "source": "urn:nld:oin:00000001823288444000:systeem:BRP-component",
  "id": "f3dce042-cd6e-4977-844d-05be8dce7cea",
  ... further attributes omitted ...
}
```

```
"data": {  
    ... application data ...  
}  
}
```

Batched content mode: HTTP POST request with two JSON event format encoded events:

```
[  
  {  
    "specversion": "1.0",  
    "type": "nl.overheid.zaken.zaakstatus-gewijzigd",  
    "source": "urn:nld:oin:00000001823288444000:systeem:BRP-component",  
    "id": "f3dce042-cd6e-4977-844d-05be8dce7cea",  
    ... further attributes omitted ...  
    "data": {  
      ... application data ...  
    }  
  },  
  {  
    "specversion": "1.0",  
    "type": "nl.overheid.zaken.zaakstatus-gewijzigd",  
    "source": "urn:nld:oin:00000001823288444000:systeem:BRP-component",  
    "id": "1ca55552-bc4a-4f5d-8cc8-8106e3e883c1",  
    ... further attributes omitted ...  
    "data": {  
      ... application data ...  
    }  
  }  
]
```

Binary content mode: HTTP POST request with context attributes mapped to HTTP-headers:

```
POST /myresource HTTP/1.1  
Host: webhook.example.com  
ce-specversion: 1.0  
ce-type: nl.overheid.zaken.zaakstatus-gewijzigd  
ce-id: f3dce042-cd6e-4977-844d-05be8dce7cea  
ce-source: urn:nld:oin:00000001823288444000:systeem:BRP-component  
... further attributes omitted ...  
Content-Type: application/json; charset=utf-8  
Content-Length: nnnn  
  
{  
    ... application data ...  
}
```

§1.4 Normative References

- [HTTP Protocol Binding for CloudEvents - Version 1.0.1](#)

§2. Guideline for the use of the JSON Event Format for CloudEvents

The CloudEvents message format can be used when using different formats and protocols and patterns. In order to be able to use the NLgov profile for CloudEvents properly in practice, agreements must also be made when and in what way a certain format, protocol or pattern is used.

The Serverless Working Group has described how the JavaScript Object Notation (JSON) Data Interchange Format can be used in a standardized way in combination with the CloudEvents message format: [JSON Event Format for CloudEvents](#).

Similar to what happened in the NLgov profile for CloudEvents, this guideline makes recommendations about the use of the JSON specification within the context of the Dutch government. These are intended to make use of the specification more unambiguous and to work towards standardisation in the long term.

The JSON Format for CloudEvents specification defines how events are expressed in JSON. The JSON syntax is not a specification of a complete data interchange. Meaningful data interchange requires agreement between a producer and consumer on the semantics attached to a particular use of the JSON syntax. What JSON does provide is the syntactic framework to which such semantics can be attached.

§2.1 Summary with points for attention

- Each CloudEvents event can be wholly represented as a JSON object and *MUST* use the media type `application/cloudevents+json`.
- The [CloudEvents JSONSchema](#) for the spec can be used to validate events in JSON.
- Unset attributes *MAY* be encoded to the JSON value of null. When decoding attributes and a null value is encountered, it *MUST* be treated as the equivalent of unset or omitted. *OPTIONAL* not omitted attributes *MAY* be represented as a null JSON value.
- The runtime data type of the `data` content inside the JSON object can be either:
 - a textual [JSON value](#) with member name `data`

- a binary JSON string expression containing the [Base64](#) encoded binary value with member name `data_base64`
- So if a `data_base64` member is present it indicates that its value is Base64 encoded binary data.
- JSON Batch Format can be used to batch several CloudEvents into a single JSON document.
 - The document contains a JSON array filled with CloudEvents in the JSON Event format.
 - Media type `application/cloudevents-batch+json` *MUST* be used.
 - The JSON Batch Format *MUST NOT* be used when only support for the JSON Format is indicated.

§2.2 Recommendations

- One *SHOULD* use the [JSON Event Format for CloudEvents](#).
- There are no agreements to deviate from the standard in any part.
- If applicable then one *SHOULD* use JSON as primary event format:
 - JSON is the only event format that [MUST be supported](#) when HTTP structured content mode is used.
 - JSON will be the primary format for APIs as formulated within the [API strategie voor de Nederlandse overheid - Extensies](#).

§2.3 Examples

Event with an attribute 'geheimnummer' having a null value and a 'data' attribute with a JSON value:

```
{
  "specversion": "1.0",
  "type": "nl.overheid.zaken.zaakstatus-gewijzigd",
  "source": "urn:nld:oin:00000001823288444000:systeem:BRP-component",
  "subject": "123456789",
  "id": "f3dce042-cd6e-4977-844d-05be8dce7cea",
  "time": "2021-12-10T17:31:00Z",
  "nlbrpnationaliteit": "0083",
  "geheimnummer": null,
  "dataref": "https://gemeenteX/api/persoon/123456789",
  "sequence": "1234",
```

```
"sequencetype": "integer",
"datacontenttype": "application/json",
"data": {
  "bsn": "1234567789",
  "naam": "Jan Jansen",
  "gecontroleerd": "ja"
}
}
```

Event with both the attribute 'datacontenttype' and 'data_base64' and a JSON string expression with Base64 encoded binary data as value of the 'data_base64' attribute:

```
{
  "specversion": "1.0",
  "type": "nl.overheid.zaken.zaakstatus-gewijzigd",
  "source": "urn:nld:oin:00000001823288444000:systeem:BRP-component",
  "id": "f3dce042-cd6e-4977-844d-05be8dce7cea",
  "datacontenttype": "application/vnd.apache.thrift.binary",
  "data_base64": "YWFwIG5vb3QgbWllcw=="
}
```

Event with only the attribute 'data_base64' and a JSON string expression with Base64 encoded binary data as value of the 'data_base64' attribute:

```
{
  "specversion": "1.0",
  "type": "nl.overheid.zaken.zaakstatus-gewijzigd",
  "source": "urn:nld:oin:00000001823288444000:systeem:BRP-component",
  "id": "f3dce042-cd6e-4977-844d-05be8dce7cea",
  "data_base64" : "YWFwIG5vb3QgbWllcw=="
}
```

§2.4 Normative References

- [JSON Event Format for CloudEvents - Version 1.0.1](#)

§3. Guideline for the use of the Webhook pattern for CloudEvents

The CloudEvents message format can be used when using different formats and protocols and patterns. In order to be able to use the NLgov profile for CloudEvents properly in practice, agreements must also be made when and in what way a certain format, protocol or pattern is used.

The Serverless Working Group has described how the Webhook pattern can be used in a standardized way in combination with the CloudEvents message format: [HTTP 1.1 Web Hooks for Event Delivery](#).

"Webhooks" are a popular pattern to deliver notifications between applications and via HTTP endpoints. Applications that make notifications available, allow for other applications to register an HTTP endpoint to which notifications are delivered. In spite of pattern usage being widespread, there is no formal definition for Web Hooks. The CloudEvents specification now provides such a definition for use with CNCF CloudEvents (but is considered generally usable beyond the scope of CloudEvents).

Similar to what happened in the NLgov profile for CloudEvents, this guideline makes recommendations about the use of the drafted CloudEvents specification within the context of the Dutch government. These are intended to make use of the specification more unambiguous and to work towards standardisation in the long term.

§3.1 Summary with points for attention

The 'HTTP 1.1 Web Hooks for Event Delivery' specification prescribes rules constraining the use and handling of specific HTTP methods and headers and defines:

1. a HTTP method by how notifications are delivered by the sender
2. an authorization model for event delivery to protect the delivery target
3. a registration handshake that protects the sender from being abused for flooding arbitrary HTTP sites with requests. For each of the mechanisms it is described which agreements apply to both sender and receiver. The specification

§ 3.1.1 Delivering notifications

- A delivery request *MUST* use a HTTP POST request via HTTPS.

- A delivery response *MUST* have the appropriate status code:
 - 200 OK or 200 Created if delivery had been accepted and processed and response carries a payload
 - 201 Created or 204 No Content when accepted and processed but carries no payload
 - 202 Accepted if accepted but not yet processed or processing status is unknown
 - 410 Gone if delivery target has been retired
 - 429 Too Many Requests when exceeding a request rate limit and *MUST* include the Retry-After header.
 - 415 Unsupported Media Type when notification format is not understood.
 - other error status codes apply as specified in [RFC7231](#).

§ 3.1.2 Authorization

The delivery request *MUST* use one of the following two methods (both of which lean on the OAuth 2.0 Bearer Token [RFC6750](#) model):

- The access token is sent in the Authorization request header field; for [OAuth 2.0 Bearer](#) tokens, the "Bearer" scheme *MUST* be used.
- The access token is added to the HTTP Request URI Query component as described in [URI Query Parameter](#).

§ 3.1.3 Abuse protection

It must be prevented that notifications are sent to recipients who have not requested this themselves. A legitimate delivery target needs to indicate that it agrees with notifications being delivered to it. Reaching the delivery agreement is realized using a validation handshake:

- A handshake can either be executed immediately at registration time or as a "pre-flight" request immediately preceding a delivery.
- Delivery targets *SHOULD* support the abuse protection feature. If a target does not support the feature, the sender *MAY* choose not to send to the target, at all, or send only at a very low request rate.
- The *validation request* uses the HTTP [OPTIONS](#) method with header fields:

- WebHook-Request-Origin (required): a DNS expression that identifies the sending system
- WebHook-Request-Callback (optional): a callback URL that allows the delivery target to grant send permission asynchronously, via a simple HTTPS callback.
- WebHook-Request-Rate (optional): a positive integer number that expresses the request rate in "requests per minute"
- The *validation response* *MUST* be sent if the delivery target does allow delivery of events with header fields:
 - WebHook-Allowed-Origin (required): *MUST* either be the origin name supplied in the WebHook-Request-Origin header, or a singular asterisk character (*), indicating that the delivery target supports notifications from all origins.
 - WebHook-Allowed-Rate (depends): *MUST* be returned if the request contained the WebHook-Request-Rate, otherwise it *SHOULD* be returned; an integer number expresses the permitted request rate in "requests per minute" or asterisk when there is no rate limitation.

§3.2 Recommendations

- One *SHOULD* use the [HTTP 1.1 Web Hooks for Event Delivery](#).
- There are no agreements to deviate from the standard in any part.
- As described in the specification usage of an access token added to the HTTP Request URI Query component has a number of security weaknesses and therefore *SHOULD NOT* be used unless it is impossible to send an access token in the Authorization request header field.
- The CloudEvents specification focuses on automated validation of intended notification applications. Within the context of the Dutch government, there can (also) be non-automated validation (e.g. by specifying endpoints in agreements between the organizations involved). In those cases it is not always necessary to perform an automated handshake before notifications may be sent.
- An automated handshake as described can take place at different moments. If automated subscription to event notification is used:
 - one *SHOULD* perform a handshake as described in the specification immediately at registration time
 - one *MAY* perform a handshake as a "pre-flight" request immediately preceding a delivery.

§3.3 Examples

Validation request:

```
OPTIONS /endpoint HTTP/1.1
Host: webhook.example.com
WebHook-Request-Origin: eventemitter.example.com
WebHook-Request-Callback: https://example.com/confirm?id=12345&key=...bas
WebHook-Request-Rate: 120
```

Validation response:

```
HTTP/1.1 200 OK
Allow: GET,POST,PUT,PATCH,DELETE,HEAD,OPTIONS
Access-Control-Allow-Origin: https://eventemitter.example.com
Access-Control-Allow-Methods: GET,POST,PUT,PATCH,DELETE,HEAD,OPTIONS
Access-Control-Allow-Headers: Content-Type
WebHook-Allowed-Origin: eventemitter.example.com
WebHook-Allowed-Rate: 120
```

Delivery request:

- [HTTP structured content mode](#) with a
- [JSON event format](#) encoded event with a
- [OAuth 2.0 Bearer](#) token

```
POST /myresource HTTP/1.1
Host: server.example.com
Authorization: Bearer mF_9.B5f-4.1JqM
WebHook-Request-Origin: eventemitter.example.com
Content-Type: application/cloudevents+json; charset=utf-8
Content-Length: nnnn

{
  "specversion": "1.0",
  "type": "nl.overheid.zaken.zaakstatus-gewijzigd",
  "source": "urn:nld:oin:00000001823288444000:systeem:BRP-component",
  "id": "f3dce042-cd6e-4977-844d-05be8dce7cea",
  ... further attributes omitted ...
}
```

Delivery response:

HTTP/1.1 204 No Content

§3.4 Normative References

- [HTTP 1.1 Web Hooks for Event Delivery - Version 1.0.1](#)

§A. Index

§A.1 Terms defined by this specification

§A.2 Terms defined by reference

§B. References

§B.1 Normative references

[RFC2119]

Key words for use in RFCs to Indicate Requirement Levels. S. Bradner. IETF. March 1997.
Best Current Practice. URL: <https://www.rfc-editor.org/rfc/rfc2119>

[RFC8174]

Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words. B. Leiba. IETF. May 2017.
Best Current Practice. URL: <https://www.rfc-editor.org/rfc/rfc8174>

§B.2 Informative references

[NLgov.CloudEvents]

NLgov profile for CloudEvents. Werkgroep Berichtenstandaard (Project Notificatieservices).

Logius. URL: <https://gitdocumentatie.logius.nl/publicatie/notificatieservices/cloudevents-nl/>