

Stelsel Toegang - SAML for DV/LC

Logius Guide

Draft August 03, 2026

**This version:**

<https://logius-standaarden.github.io/st-saml-spec/>

Latest published version:

<https://gitdocumentatie.logius.nl/publicatie/st/saml/dv.html>

Latest editor's draft:

<https://logius-standaarden.github.io/st-saml-spec/>

Editor:

Frans de Kok ([Logius](#))

Authors:

Frans de Kok ([Logius](#))

Jan Geert Koops ([DICTU](#))

Mark Nijmeijer ([DICTU](#))

Wiljan Pitlo ([ICTU](#))

Carlo Huiden ([ICTU](#))

Participate:

[GitHub Logius-standaarden/st-saml-spec](#)

[All issues](#)

[File an issue](#)

[Commit history](#)

[Pull requests](#)

This document is also available in these non-normative format: [PDF](#)



This document is licensed under

[Creative Commons Attribution 4.0 International Public License](#)

Status of This Document

This is a draft that could be altered, removed or replaced by other documents. It is not a recommendation approved by TO.

Table of Contents

Status of This Document

Conformance

Abstract

1. **Disclaimer**
2. **History**

3.	Glossary
3.1	Terms
3.2	Roles
4.	Introduction
5.	Frameworks
5.1	SAML generic
5.2	DV - SAML message flows & bindings
5.2.1	DV → RD authentication flow
5.2.1.1	Front-channel (re)authentication
5.2.1.2	Back-channel (Assertion)
5.2.2	DV → RD Federated Logout flow
6.	Supported Use Cases
6.1	Authentication
6.1.1	Actors
6.1.2	Functional description
6.2	Authentication with representation
6.2.1	standard representation
6.2.2	legal representation
6.2.3	Actors
6.2.4	Functional description
6.3	Cluster connection connectivity
6.3.1	Actors
6.3.2	Technical description
6.4	Authentication with AD/BVD preselection
6.4.1	Actors
6.4.2	Functional description
7.	Message Specification
7.1	DV - SAML Message specification
7.1.1	DV → RD - SAML authentication proces
7.1.1.1	DV → RD - authentication - diagram
7.1.1.2	DV → RD - authentication - steps
7.1.2	DV → RD - SAML messages
7.1.2.1	DV → RD AuthnRequest
7.1.2.1.1	DV → RD AuthnRequest Diagram
7.1.2.1.2	DV → RD AuthnRequest Message
7.1.2.1.3	DV → RD AuthnRequest Processing rules
7.1.2.2	DV ← RD Artifact Binding
7.1.2.2.1	DV ← RD - Artifact Binding - Diagram
7.1.2.2.2	DV ← RD - Artifact Binding - Message
7.1.2.3	DV → RD ArtifactResolve
7.1.2.3.1	DV → RD ArtifactResolve Diagram
7.1.2.3.2	DV → RD ArtifactResolve Message
7.1.2.4	DV ← RD ArtifactResponse
7.1.2.4.1	DV ← RD ArtifactResponse Diagram
7.1.2.4.2	DV ← RD ArtifactResponse Message
7.1.2.4.3	DV ← RD AuthN Response - Message
7.1.2.4.4	DV ← RD AuthN Response - Assertion

7.2 Federated Logout Message specification

7.2.1 DV → RD login & logout

7.2.1.1 DV Federated Login

7.2.1.2 DV → RD logout Request - Diagram

7.2.1.3 DV → RD logout Request - Message

7.2.1.4 DV ← RD logout Response - Diagram

7.2.1.5 DV ← RD logout Response - Message

7.2.2 RD → AD login & logout

7.2.2.1 RD → AD logout Request - Diagram

7.2.2.2 RD → AD logout Request - Message

7.2.2.3 RD ← AD logout Response - Diagram

7.2.2.4 RD → AD logout Response - Message

7.3 Error messages

7.3.1 Toplevel codes

7.3.2 Second-level status codes

7.3.3 Cancelling

7.3.4 Attributes not supported

7.3.5 Incorrect message (recoverable)

7.3.6 Incorrect message (non-recoverable)

8. SAML Metadata

8.1 Metadata

8.1.1 TLS certificates in metadata

8.1.2 General processing requirements

8.2 DV Metadata

8.2.1 DV → RD Metadata

8.2.2 LC → RD metadata

8.2.2.1 LC → RD EntityDescriptor

8.2.2.2 DV → RD EntityDescriptor

8.2.3 RD → DV/LC metadata

9. Technical requirements and recommendations

9.1 SAML Signing

9.1.1 SAML Signature

9.2 Encryption

9.2.1 SAML encryption

9.2.1.1 Encrypted elements

9.2.1.1.1 Multiple recipients

9.2.1.2 EncryptedID

9.2.1.2.1 Example EncryptedID

9.2.1.3 NameID - after decrypting EncryptedID

9.2.1.3.1 Example nameID (after decryption)

9.2.1.4 EncryptedAttribute

9.2.1.4.1 Example EncryptedAttribute

9.2.1.4.2 Example (Encrypted) Attribute after decryption

9.3 End-to-End encryption

9.3.1 Introduction

9.3.2 SAML E2E-protection measures

9.3.3 Additional protection measures for Identifiers

9.4	TLS transport
9.5	NotBefore and NotOnOrAfter
9.6	Levels of assurance
9.7	Local session
9.8	RelayState
9.9	EU interaction
10.	Type definitions
10.1	Attribute identifier types
10.2	Attribute representation types
10.3	EntityID Format
10.4	Level of Assurance
A.	Example SAML messages
A.1	Example - AuthnRequest
A.2	Example - AuthnRequest using Extensions
A.3	Example - AuthnRequest with Representation
A.4	Example - ArtifactResponse with Legal Representation
A.5	Example - ArtifactResolve
A.6	Example - ArtifactResponse
A.7	Example - ArtifactResponse with Representation
A.8	Example - LogoutRequest
A.9	Example - LogoutResponse
B.	Example SAML metadata
B.1	Example - Metadata DV for RD
B.2	Example - Metadata LC for RD
B.3	Example - Metadata RD for DV
C.	List of Figures
D.	Index
D.1	Terms defined by this specification
D.2	Terms defined by reference
E.	References
E.1	Normative references

Conformance

As well as sections marked as non-normative, all authoring guidelines, diagrams, examples, and notes in this specification are non-normative. Everything else in this specification is normative.

The key words *MAY*, *MUST*, *MUST NOT*, *SHOULD*, and *SHOULD NOT* in this document are to be interpreted as described in [BCP 14](#) [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

Abstract

This specification is intended for service providers ([DV](#)) who want to connect their webservices to [DigiD](#) and optionally [DigiD-Machtigen](#) and [BVD-OG](#) via a [RD](#) like [TVS](#).

§1. Disclaimer

This version of the document must not in any way be considered to be a normative source for the purpose of conducting audits on [participants](#). This topic will be addressed in future versions.

Errata, functional improvements and other developments will be added to this documentation in future versions. Version history for this document is included on the [History](#) page.

§2. History

Version	Changes	Distribution
	Release Candidate 1: derived from [<i>eID SAML4.4</i>] Final with the following additional changes	
	- Added support for BVD-OG in support of Stelsel Toegang release 1. - Added specifications for connection between RD and AD/BVD, based on [<i>eID SAML4.5</i>] specification	
[<i>ST-SAML1.0</i>] RC 1	- Change of structure to introduce two versions - Short version only covering DV and LC connecting to an RD (e.g. TVS) - Complete version also covering connections between RD and AD/BVD - All parts have been revised for improved clarity and consistency. - The specification now features extensive internal referencing, cross-linking and tooltips (aka 'Hover text') to improve navigation and context.	Internal

§3. Glossary

§3.1 Terms

Term/abbreviation	English	Nederlands	Explanation
<i>Artifact</i>		Artefact	(SAML) Pointer to SAML message that is send through the front-channel, to avoid exposing sensitive data to the Webbrowser (UA) of the EU .

Term/abbreviation	English	Nederlands	Explanation
Assertion		Verklaring	A signed statement about a user's identity and mandates made by an AD or BVD . See SAML Assertion message .
Back channel	Back channel		Receiver (DV , LC , RD) uses an Artifact to collect the actual SAML message from the Sender (RD , AD or BVD). All SAML Back channel messages are placed in a SOAP envelope, the Webbrowser (UA) of the EndUser (EU) is not involved.
Front channel	Front channel		Communication between DV , LC , RD , AD and BVD via (a browser redirect of) the Webbrowser (UA) of the EndUser (EU).
BSN		BSN	Dutch national citizen registration number.
BSNk		BSN-koppelregister	Register that activates the BSN of an EU and issues the corresponding Polymorphic Identity used to derive a Specific pseudonym or encrypted identifier for a Participant .
BVD-DDM		Bevoegdheidsverklaringsdienst DigiD-Machtigen	A public instance of BVD specifically for mandates registered in DigiD-Machtigen only for public DV
BVD-OG		BevoegdheidsVerklaringsDienst Ouderlijk Gezag	A public instance of BVD specifically for legal representation concerning parental authority, based on Dutch national database of personal information (maintained by municipalities)
DigiD		DigiD	public IdP (AD) only for public DV
DigiD-Machtigen	DDM	DigiD-Machtigen	- public Mandate Registry. See also BVD-DDM
DigiD-CC		DigiD CombiConnect	See also DigiD CC1.1 interface specification .
EntityConcernedTypes			The set of identifiers of the Service Consumer that a MR is allowed to provide to a DV , as configured per service in the Service Catalog (EntityConcernedTypesAllowed).
EntityID			All systems in the network are identified by a unique EntityId in SAML Metadata , which is specified in the SAML metadata
ETD	Trust Framework	Afsprakenstelsel Elektronische Toegangsdiensten	Dutch Trust Framework, also known as 'eHerkenning'. See

Term/abbreviation	English	Nederlands	Explanation
			https://afsprakenstelsel.etoegang.nl/ .
ETD Stelsel		Afsprakenstelsel Elektronische Toegangsdiensten	The set of agreements, standards and interface specifications that governs ETD , published at [ETD-Stelsel].
Intermediate Party		Intermediair	representing Service Consumer in a mandate chain
Legal Representation		Wettelijke Vertegenwoordiging	Legal Representation means that someone (EU) is allowed by law to act on behalf of another person (Represented Party).
LoA	Level of Assurance	Betrouwbaarheidsniveau	See supported Level of Assurance
Metadata	Metadata		Before a SAML connection can be established, all parties (DV , LC , RD , AD and BVD) must exchange connection properties. This is done through SAML Metadata.
Participant		Deelnemer	Any party that has a role in the authentication or representation processes that are within the scope of this specification. These include RD , AD and BVD .
Polymorphic Identity	PI / PP	Polymorfe Identiteit / Polymorf Pseudoniem	Identifier of the EU and/or Service Consumer derived from the BSN via polymorphic encryption at BSNk . Used as a Polymorphic Identity (PI) when the DV requires the BSN itself, or as a Polymorphic Pseudonym (PP) when a persistent recipient-specific specific pseudonym suffices. Managed by the AD (or in case of representation by MR of BVD), which transforms it into a recipient-specific encrypted identifier or a persistent recipient-specific pseudonym before sharing it.
Represented Party	Represented Party	Vertegenwoordigde	Service Consumer represented by EU
SAML	SAML		De SAML v 2.0 standard, also referred to as SAML 2.0. SAML is an acronym of Security Assertion Markup Language. See [SAML2.TO].
Service	Service	Dienst	Service offered by a DV
Service Catalog	Service Catalog	Dienstencatalogus of DC	Collection of Services offered by all Service Providers, kept by RD . The DV is responsible for keeping their Services in the Service Catalog up to date.

Term/abbreviation	English	Nederlands	Explanation
Service Consumer	Service Consumer	Belanghebbende	Service Consumer is the Entity Concerned (also see EntityConcernedTypes): either EU when acting on its own behalf, or the Represented Party when EU is representing someone else.
ServiceID			ETD ServiceID is an identifier of a service that is unique in the context of the DV . Both ServiceID and a ServiceUUID is registered in the ETD Service Catalog .
ServiceUUID		Service Universally Unique Identifier	ServiceUUID is an identifier of a service that is unique in the context of the network. Both ServiceID and a ServiceUUID is registered in the ETD Service Catalog .
Specific pseudonym	SP	Specifiek pseudoniem	Pseudonym of the EU when representing a ServiceConsumer in ETD Stelsel , generated by the MR . It is typically derived from the means of authentication rather than from the BSN. Used when a DV or MR requires a pseudonym but not the BSN itself; see also Polymorphic Identity .
SSO	Single Sign On	Eenmalig Inloggen	
SLO	Single Log Off	Federatief uitloggen	Single Log Off feature
ST-SAML		SAML specification for DV connecting via TVS (RD) to DigiD , DigiD-Machtigen and BVD-OG	SAML specification for a DV connecting via TVS (as RD) to DigiD , DigiD-Machtigen and BVD-OG
TVS	TVS	TVS	public RD only for public DV

§3.2 Roles

The following roles are used in this specification.

Abbreviation	Role/Actor	Description	Example
AD	Authenticatiedienst	Identity Provider (IdP)	DigiD , EB and AD in ETD
BVD	Bevoegdheidsverklaringsdienst	Service that provides assertions for representation relationships	The BVD-DDM (DigiD Machtigen), BVD-OG (parental authority)

Abbreviation	Role/Actor	Description	Example
DV	Dienstverlener	Service Provider	Website of municipality, hospital, government agency
EB	eIDAS Berichten Service	eIDAS Nederland knooppunt	
EU	EindGebruiker	End User	Natural Person acting on its own behalf to consume a Service OR acting on behalf of someone else (the Service Consumer).
LC	Leverancier Clusteraansluiting	Clusterconnection provider: This role assists the DV in connecting to RD . LC will handle all connectivity to RD for their registered DV	PaaS/SaaS providers within the health-care field
MR	MachtigingsRegister	eHerkenning Mandate Registry	Recony, DigiDentity, ZET-solutions, Signicat
RD	Routeringsdienst	Routing Service Provides access to ADs and BVDs	TVS
UA	User Agent	User Agent is application controlled by the EU	WebBrowser

§4. Introduction

This [ST-SAML](#) specification facilitates Stelsel Toegang release 1. [[ST-SAML1.0](#)] derived from [[eID SAML4.4](#)] and [[eID SAML4.5](#)]. It introduces the [BVD-OG](#) for an extra representation use case: legal representation of a minor by someone with parental authority (Ouderlijk Gezag). If a [DV](#) supports this use case, the [RD](#) (or [DV](#)) will offer the choice to do so to the [EU](#).

[ST-SAML](#) specifies the communication between [DV](#) and [RD](#) and also between [LC](#) and [RD](#). [ST-SAML](#) also specifies the communication between Routeringsdienst ([RD](#)) and [BVD](#) for parental authority ([BVD-OG](#)). [[eID SAML4.5](#)] specifies the communication between [RD](#) and DigiD (as [AD](#)) and between [RD](#) and [BVD](#) for registered mandates in DigiD-Machtigen: [BVD-DDM](#). These DigiD specific specifications are out of scope for this [ST-SAML](#) specification.




Figure 1 Stelsel Toegang SAML1.0

Routeringsdienst ([RD](#)) supports the use cases summarized below:

Use case	Description
Authentication	Authenticating an EU for a single Service , for a single purpose. This is the most basic use case scenario from a DV 's point of view. Authentication always implies consent of the EU for accessing the Service and may include authorization if the EU is using representation.
Cluster connection connectivity	In a Cluster connection setting, a LC is technically responsible for connecting a DV to RD .
Authentication with representation	an EU authenticates with the intent to consume the Service on behalf of another person Represented Party using a Representation Relationship that is registered within a BVD context.
Authentication and/or representation via a RD	At a RD , an EU interactively selects an AD for which they own an authentication means, and/or a BVD in which a representation relation that they intend to use is registered, from multiple options. The RD redirects the EU to the selected AD and/or BVD .
Authentication with AD/BVD preselection	Authenticating an EU where selection for the AD or BVD is done at the DV prior to the authentication request to the RD in order to optimize the EU experience.

§ SAML specification

The document is not a complete [SAML](#) reference. It is assumed that the reader is familiar with SAML and will use the referenced documentation as well when needed.

- SAML Message specification - Contains message definitions of all interactions between [DV/LC](#) – [RD](#) and between [RD](#) – [AD/BVD](#).
- SAML Metadata - Contains metadata definitions for [DV](#), [LC](#), [RD](#), [AD](#) and [BVD](#).

§5. Frameworks

§5.1 SAML generic

SAML Assertions and Protocols for the OASIS Security Assertion Markup Language (SAML) V2.0 [[SAML2](#)]

- saml-core-2.0-os [[SAML2.CORE](#)]
- saml-profiles-2.0-os [[SAML2.PROFILES](#)]
- saml-metadata-2.0-os [[SAML2.METADATA](#)]
- saml-bindings-2.0-os [[SAML2.BINDINGS](#)]
- saml errata [[SAML2.ERRATA.05](#)]

NORA, Nederlandse Overheid Referentie Architectuur [[NORA](#)].

NCSC ICT-beveiligingsrichtlijnen voor Transport Layer Security (TLS) [[NCSC.TLS](#)].

SAML profiles A SAML profile is a specific set of rules that are used for a specific use case. [ST-SAML](#) uses two profiles of the SAML standard, namely:

- Web Browser SSO Profile ([[SAML2.PROFILES](#)], par 4.1), with HTTP Post binding (see below).
- Single Logout Profile ([[SAML2.PROFILES](#)], par 4.4), with HTTP Post binding, issued by Session Participant to Identity Provider.

§5.2 DV - SAML message flows & bindings

Only the bindings that are listed in the tables are supported between [DV](#) and [LC](#)

§ 5.2.1 DV → RD authentication flow

The diagram below depicts the authentication flow between a [DV](#) and [LC](#) and the [RD](#).

See also [DV-RD - SAML authentication messages](#)




Figure 2 Authentication and representation flow - overview

§ 5.2.1.1 Front-channel (re)authentication

Step #	Route	Message	Endpoint	Binding	Metadata
2 + 3	<u>DV/LC</u> (→ <u>UA</u>) → <u>RD</u>	<u>AuthN Request</u> message	<u>SingleSignOnService</u>	HTTP-POST	<u>RD</u> → <u>DV</u>
8 + 9	<u>RD</u> (→ <u>UA</u>) → <u>DV/LC</u>	<u>Artifact binding</u> message	<u>AssertionConsumerService</u> (<u>DV</u>) <u>AssertionConsumerService</u> (<u>LC</u>)	HTTP- Artifact	<u>DV</u> → <u>RD</u> <u>LC</u> → <u>RD</u>

§ 5.2.1.2 Back-channel (Assertion)

Step #	Route	Message	Endpoint	Binding	Metadata
10	<u>DV/LC</u> → <u>RD</u>	<u>Artifact Resolve</u> message	<u>ArtifactResolutionService</u>	SOAP	<u>RD</u> → <u>DV</u>
11	<u>RD</u> → <u>DV/LC</u>	<u>AuthN Response</u> message	None, is a synchronous response	SOAP	

§ 5.2.2 DV → RD Federated Logout flow

Only a limited form of SP ([DV/LC](#)) initiated logout is supported within the context of a [SSO](#) federation. IdP ([AD](#)) initiated Logout is NOT supported! On receiving a logout request from the [EU](#) via the [UA](#) (step 1) a [DV/LC](#) which participates in a [SSO](#) federation *MUST* send a [LogoutRequest](#) to [RD](#) (step 2 and 3). [RD](#) propagates the Logout Request to appropriate [AD](#). If the AD replies success status, the [RD](#) will reply with a LogoutResponse with success status to the [DV/LC](#).

The diagram below depicts the single logout flow between a [DV](#) and [LC](#) and the [RD](#).

Also see [SAML Federated login and logout](#)




Figure 3 SAML Federated Logout overview

Step #	Route	Message	Endpoint	Binding	Meta-data
2 + 3	DV/LC (→ UA) → RD	LogoutRequest	SingleLogoutService	HTTP-POST	RD → DV
7 + 8	RD (→ UA) → DV/LC	LogoutResponse	SingleLogoutService (DV) SingleLogoutService (LC)	HTTP-POST	DV → RD LC → RD

§6. Supported Use Cases

§6.1 Authentication

An [EU](#) intends to consume a Service on his/her own behalf, from a DV for which authentication is required.

§ 6.1.1 Actors

Roles

- [EU](#)
- [DV](#)
- [RD](#)
- [AD](#)

For more information see also [Roles](#)

§ 6.1.2 Functional description

An [EU](#) intends to consume a [Service](#) on his/her own behalf. The Service is offered on the web by a [DV](#).

The [EU](#) visits the website of the Service, where the [EU](#) may have to interact to indicate the intent to consume the Service. As the Service requires authentication, this triggers the authentication process.

The DV will now redirect the [EU](#) to [RD](#), requesting authentication of the [EU](#) for the [Service](#). Note that in this use case the [EU](#) will not select to act on behalf of another. (See [Authentication with Representation](#))

Next, the [EU](#) is redirected to the [AD](#). After successful authentication the AD takes care the [EU](#) is redirected back to [RD](#), who includes the attestation of identity in the relevant interface response to the DV. This response includes at minimum an identifier of the [EU](#), the [LoA](#) attested to and the [Service](#) authenticated for. The [LoA](#) of the authentication is at minimum equal to or higher than the configured [LoA](#) for the [Service](#) within the [Service Catalog](#). The [RD](#) now includes the attestation of identity and the attestation of representation relationship in the relevant interface response to the [DV](#). This response includes at minimum an identifier of the [EU](#) and the [Represented Party](#), the [LoA](#) attested to and the [Service](#) authenticated for.

The [DV](#) can now take an access control decision to its [Service](#) for the [EU](#).

The technical steps in the authentication flow are described in [DV SAML Authentication](#).

NOTE

Communication between [RD](#) and [DigiD](#) is specified in DigiD Combiconnect specification ([DigiD-CC](#)) and is out of scope of this specification.

§6.2 Authentication with representation

An acting [EU](#) intends to consume a [Service](#) to represent another party, from a [DV](#), for which authentication is required. The [EU](#) acting on behalf of a [Represented Party](#), must be a Natural Person, using a representation relationship. The [Represented Party](#) must also be a Natural Person. The relationship must be formalized and a direct relationship.

The authentication of the acting [EU](#) takes place just like in the Authentication use case. Similarly, the representation information concerning both the acting [EU](#), the [Represented Party](#) and the [Service](#) for which they have a representation relation will be provided by a [BVD](#), either

1. Standard representation aka [DigiD-Machtigen](#) by [BVD-DDM](#)
2. Legal representation by other [BVDs](#) eg. [BVD-OG](#).

§ 6.2.1 standard representation

The acting [EU](#) acts on behalf of the [Represented Party](#) ([Service Consumer](#)). The representation relationship underpinning this must be registered by [Represented Party](#) as a formalized mandate in a mandate registry ([DigiD-Machtigen](#)), prior to application in this use case.

Rules governing representation and registration of a registration relationship are out of scope of this specification. Communication between [RD](#) and [BVD-DDM](#) is specified in [DigiD-CC](#) specification and is out of scope of this specification.

§ 6.2.2 legal representation

The information about the [type of legal representation](#) concerning the [EU](#) and the [Represented Party](#) will be provided by a [BVD](#), eg [BVD-OG](#) for parental authority. To make this use case succeed, the relationship between the [EU](#) and the [Represented Party](#) must be registered in the applicable registry in such a way that it meets the legal requirements.

Rules on governing legal representation are out of scope of this specification.

§ 6.2.3 Actors

Roles

- [EU](#)
- [DV](#)
- [RD](#)
- [AD](#)

- [BVD](#)

§ 6.2.4 Functional description

The [EU](#) visits the website of the [Service](#), where the [EU](#) may have to interact to indicate the intent to consume the [Service](#). As the [Service](#) requires authentication, this triggers the authentication process. The [EU](#) must be able to indicate the intent to consume the [Service](#) on behalf of a [Represented Party](#) (and not for his/herself) before the authentication process is triggered.

The [DV](#) (or [LC](#)) will now redirect the [EU](#) to [RD](#), requesting authentication of the [EU](#) for the [Service](#), including the request to authorize based on a representation relationship.

Next, the [EU](#) is redirected to the [AD](#). After successful authentication, the [AD](#) redirects the [EU](#) to [RD](#). [RD](#) will then redirect the [EU](#) to [BVD-DDM](#). Here the [EU](#) selects the representation relationship to use, if multiple options are available. Afterwards the [BVD](#) redirects the [EU](#) back to [RD](#).

[RD](#) now includes the attestation of identity and the attestation of the representation relationship in the relevant interface response to the [DV](#) (or [LC](#)). This response includes an identifier of the [EU](#) and the [Represented Party](#) and in case of legal representation also the specific [type of legal representation](#) between both. Also the requested [ServiceUUID](#) and the [LoA](#) of the authentication is included in the response. The [LoA](#) is at minimum equal to or higher than the configured [LoA](#) for the [Service](#) within the [Service Catalog](#).

The [DV](#) can now take an access control decision to its [Service](#) for the [EU](#) on behalf of the [Represented Party](#).

The technical steps in the authentication flow are described here: [DV SAML Authentication](#).

§ 6.3 Cluster connection connectivity

In Software-as-a-Service ([SaaS](#)) or multi-tenant solutions, multiple [DV](#)'s are hosted on a single environment operated by a software vendor. The software vendor can act as an [LC](#). Functionally the [LC](#) itself is not actively taking part in any of the primary use cases, thus is not an actor in those use cases.

NOTE

Although above the Cluster is linked to [SaaS](#) solutions, the cluster connection can be applicable in Platform-as-a-Service (PaaS) offerings as well. This is only the case if the platform natively offers connectivity to [RD](#); it is NOT applicable if the connectivity is built on top of the platform provided using PaaS.

For Infrastructure-as-a-Service solutions (IaaS), the Cluster Connection is NOT applicable.

§ 6.3.1 Actors

Roles	Description
DV	See also Roles
LC	

§ 6.3.2 Technical description

The Cluster Connection is acknowledged during requests for authentication, as made in the supported use cases. The [LC](#) is registered at [RD](#) and is also responsible for registering all [DV](#)'s he provides access for. Relationship between [DV](#) and [LC](#) must be established in the registration/on-boarding process with [RD](#) and in [LC](#)-metadata.

[DV](#) initiates authentication via the [LC](#). The [LC](#) will send an [AuthN Request Message](#) to [RD](#) on behalf of [DV](#).

Data in the response from [RD](#) will be encrypted only for the [DV](#) to decrypt, not the [LC](#).

In this way, the [LC](#) can facilitate the authentication processes, but cannot access the sensitive information contained in the response.

NOTE

The way a [DV](#) interacts with a [LC](#) is not part of this specification.

§ 6.4 Authentication with AD/BVD preselection

an [EU](#) intends to consume a [Service](#) on his/her own behalf, from a (semi-)governmental or public [DV](#)], for which authentication is required. The [EU](#) makes the selection for the [AD](#) at the [DV](#) , rather than at the [RD](#). In order to improve [=EU=|user] experience (UX), this enables presenting the choice of [AD](#) at the [DV](#) at the most appropriate time and in the best fitting manner.

Additionally in a representation scenario, the [EU](#) can (also) select the [BVD](#) at the [DV](#) .

NOTE

Passing the choice for [AD/BVD](#) is solely offered for improving [=EU=|user] experience. It is explicitly not the intention that [DV](#) introduce a bias in the choice for the [AD/BVD](#) to use. Valid use cases for bypassing [EU](#) preference, where a [DV](#) selects a specific [AD/BVD](#) for an [EU](#) , are very rare and specific. [DV](#) should offer the choice for each [AD/BVD](#) in a non-discriminatory way for all applicable [AD/BVD](#).

§ 6.4.1 Actors

Roles

- [EU](#)
- [DV](#)
- [RD](#)
- [AD](#)

- [BVD](#)

For more information see also [Roles](#)

§ 6.4.2 Functional description

This use case is a functional extension to Authentication. Instead of choosing the [AD](#) and/or [BVD](#) after being redirected to the [RD](#), the [EU](#) selects the [AD](#) and/or [BVD](#) for usage at an earlier stage at the [DV](#). The [RD](#) will apply the pre-selection as a filter on all available options. If, after filtering, alternative options are found, the [RD](#) will prompt the [EU](#) to further narrow down the selection.

The [DV](#) will offer the [EU](#) to make a choice from the list of applicable [ADs](#) before sending a request for authentication to the [RD](#). Simultaneously with the choice for an [AD](#), the choice to represent another will be offered the [EU](#) with (optionally) the [BVD](#) to be used. After making the choice for an [AD](#), acting-as-a-representative and the choice for a [BVD](#), these choices will be included in the request for authentication to the [RD](#). In case the [EU](#) acts on behalf of another without pre-selecting a [BVD](#), the choice for a [BVD](#) will be presented in a later stage at the [RD](#).

The technical steps in the authentication flow are described in the [SAML-Message-specification](#).

§7. Message Specification

§RD - Leeg

§7.1 DV - SAML Message specification

§ 7.1.1 DV → RD - SAML authentication proces

SAML authentication messages between [DV](#) (or [LC](#)) and [RD](#) are described in this chapter. First the authentication overview and the steps, then the specification of the individual SAML messages between [DV](#) and [RD](#).

§ 7.1.1.1 DV → RD - authentication - diagram

The diagram below contains the authentication steps that are made when an [EU](#) authenticates with a [DV](#) through the [RD](#). When an [LC](#) is present between [DV](#) and [RD](#) the [LC](#) will take the role of [DV](#) in relation to the [RD](#).




Figure 4 SAML authentication flow - DV/LC - RD

§ 7.1.1.2 DV → RD - authentication - steps

Before the above authentication steps are explained, it is important to make a distinction between the [Front channel](#) and the [Back channel](#). The [Front channel](#) is the communication between the [DV](#) or [LC](#) and [RD](#) via the [UA](#) of the [EU](#) (step 2 & 3 and step 8 & 9 in the figure above). The [Back channel](#) is the direct communication between the [DV](#) or [LC](#) and [RD](#) (step 10 and Step 11 in the figure above). This distinction is important because possibly sensitive data (such as a citizen service number) is never send via the [Front channel](#), so that they can never be intercepted or changed by the [UA](#).

Step 1

The [EU](#) with a [UA](#) wants to access a part on the web service of the [DV](#) that requires authentication of the [EU](#).

Step 2 and 3

The [DV](#) or [LC](#) will send the [EU](#) to [RD](#) for authentication and or proof of representation.

Step 4 up to and including 7 (out of scope for this flow)

In this step the [RD](#) will offer the [EU](#) a choice of [AD](#)'s and [BVD](#)'s that fulfil the authentication requirements (e.g. minimum level of assurance required, type of mandate). Optionally, the [DV](#) can pass pre-selection information concerning the [AD](#) to query, and if representation will be used, to the [RD](#).

If the [EU](#) hasn't already chosen in step 2, the [EU](#) chooses an authentication method that meets the minimum required [LoA](#), and also chooses whether to use representation. The [EU](#) is presented with the corresponding [AD](#) login screen. The [EU](#) authenticates with the chosen means.

Optionally, the [EU](#) also chooses a representation method. The [EU](#) is presented with the corresponding screen with choice of who to represent. The [EU](#) chooses the correct [Represented Party](#) to represent.

Step 8 and 9

[RD](#) sends the [EU](#) back to the [DV](#) or [LC](#) via a redirect. An opaque [Artifact](#) generated by [RD](#) is send here. This [Artifact](#) refers to the actual [Artifact Response message](#) that is waiting at [RD](#).

Even if the authentication starting in step 4 was unsuccessful or interrupted, an artifact is send to the [DV](#) or [LC](#). This [Artifact](#) provides an error message with the [Artifact Resolve request](#) and cannot be exchanged for a valid [Assertion](#).

Step 10

With the [Artifact](#) the [DV/LC](#) sends an [Artifact Resolve request](#) to the [RD](#) for the result of the (successful or unsuccessful) authentication and (optionally) representation via a [Back channel](#).

Artifacts are stored by [RD](#) for a maximum of 15 minutes and can only be retrieved once by the [DV/LC](#). Situations are possible (process breakdown, early logout) where [RD](#) saves an [Artifact](#) for less than 15 minutes.

Step 11

[RD](#) replies with an [Artifact Response message](#) that belongs to the [Artifact](#). In this message, [RD](#) provides an [Assertion](#) that includes the authentication result and optionally the representation selection. And, if the authentication / representation selection was successful, the requested (encrypted) identifier(s) and attribute(s) of the [EU](#) and optionally the [Represented Party](#). The identities and attributes are encrypted so that only the intended [DV](#)(s) can obtain the plain text value.

If the authentication or attempt to select representation was unsuccessful, it is indicated in the Status Code of the Response message and if possible, a reason is given so that the web service can inform the [EU](#).

Step 12 & 13

Successful authentication / selection of representation gives the [DV](#) information needed for access control decision typically resulting in [EU](#) access to service in step 13.

§ 7.1.2 DV → RD - SAML messages

The SAML messages are specified in detail in the following sections. The following rules apply

1. The messages contain at least the elements that are specified as mandatory by the standard.
2. In addition, the messages also contain optional elements. It is indicated whether these elements are mandatory, conditional or optional. With optional elements, it is up to the participants to determine whether they are used.
3. Optional SAML elements that are not in this specification *SHOULD NOT* be included. When present they will be ignored when possible.

§ 7.1.2.1 DV → RD AuthnRequest

When a principal (or an agent acting on the principal's behalf) wishes to obtain assertions containing authentication statements to establish a security context at one or more relying parties, it can use the authentication request protocol to send an [AuthN Request message](#) message element to a SAML authority and request that it returns a [AuthN-Response message](#) containing one or more such assertions.

§ 7.1.2.1.1 DV → RD AUTHNREQUEST DIAGRAM

The possible sender and recipient of the AuthnRequest message are the following:

Sender	Recipient
DV	RD
LC	RD




Figure 5 SAML authentication flow - DV/LC - RD - AuthN-Request

§ 7.1.2.1.2 DV → RD AUTHNREQUEST MESSAGE

See also [Example AuthnRequest DV for RD](#)

Element/@Attribute	0..n	Description
		Issuer = DV or LC Recipient = RD
@ID	1	Unique message identifier. <i>MUST</i> identify the message uniquely within the scope of the sender and receiver for a period of at least 12 months.
@Version	1	Version of the SAML protocol. The value <i>MUST</i> be 2.0.
@IssueInstant	1	Time of issuing of the request.
@Destination	1	URL of the recipient on which the message is offered. <i>MUST</i> match SingleSignOnService in the metadata .

Element/@Attribute	0..n	Description Issuer = DV or LC Recipient = RD
@ForceAuthn	0..1	The value <code>true</code> indicates that an existing SSO session <i>MUST NOT</i> be used for the request. If the value is <code>false</code> or empty or the attribute is missing, an existing SSO session <i>MAY</i> be used for the request.
@AssertionConsumerServiceIndex	1	This index <i>MUST</i> refer to an endpoint of an AssertionConsumerService in the issuer's metadata for the recipient. <i>NOTE: as a consequence, the AssertionConsumerServiceURL MUST NOT be included.</i>
@AttributeConsumingServiceIndex	0..1	Conditional. Only one of Extensions or @AttributeConsumingServiceIndex <i>MUST</i> be present. <i>NOTE: Also see the use of @AttributeConsumingServiceIndex and Extensions</i>
@ProviderName	0..1	Conditional. Reserved for use with eIDAS UIT to show information about the foreign DV and country in order to obtain EU consent. <i>SHOULD NOT</i> be used in other use cases and will be ignored if used.
Issuer	1	<i>MUST</i> contain the EntityID of the issuer as registered in the Metadata .
Signature	1	<i>MUST</i> contain the XML signature of the sender for the enveloped message. <i>MUST</i> contain a KeyInfo element with a KeyName or X509Certificate elements. See Signature
Extensions	0..1	Conditional. Only one of Extensions or AttributeConsumingServiceIndex <i>MUST</i> be present. And when Extensions is present, it <i>MUST</i> contain the attributes described below. <i>NOTE: Also see the use of @AttributeConsumingServiceIndex and Extensions</i>
-Attribute	1	An Attribute with the <code>@Name="urn:n1-eid-gdi:1.0:IntendedAudience"</code> <i>MUST</i> be present and contain an AttributeValue with the EntityID of the DV for which authentication is requested. <i>NOTE: (future) support for more than one audience where each audience receives the audience specific EncryptedID is provided by the Service Definition registered with the Service Catalog.</i>
-Attribute	1	An Attribute with the <code>@Name="urn:n1-eid-gdi:1.0:ServiceUUID"</code> <i>MUST</i> be present and contain an AttributeValue containing a ServiceUUID that is known at the Service Catalog of the receiving RD , AD and BVD .
Scoping	0..1	Conditional. Element <i>MAY</i> be used to limit the selection of AD 's or BVD 's at the RD .
-IDPList	0..1	Conditional. List of IDP's - Element <i>MUST</i> be present in DV Authn-request message when Scoping element is present.

Element/@Attribute	0..n	Description Issuer = DV or LC Recipient = RD
		At least one IDPEntry (of an AD) <i>MUST</i> be present if the IDPList element is present. If no valid IDPEntry is present, the AuthnRequest will fail with a top level status code urn:oasis:names:tc:saml:2.0:status:Requester and second-level code depending on the condition according to [SAML2.CORE] section 3.2.2.2:
--IDPEntry	1..n	urn:oasis:names:tc:SAML:2.0:status:NoSupportedIDP. If the list also contains the EntityID of a BVD . This indicates that representation using the BVD is optional in combination with the AD '(s) in the IDPList. The RD will let the EU choose whether to use representation with a BVD . The RD <i>MUST</i> limit the AD and BVD selection list presented to EU 's for AD 's or combination of AD 's and BVD 's that are supported.
---@ProviderID	1	<i>MUST</i> contain the EntityID of a pre-selected AD or BVD
-RequesterID	0..n	Conditional. Element <i>MAY</i> be present if using authentication with representation. If used it <i>MUST</i> contain the EntityID of a BVD . If more than one RequesterID is included with different BVD 's the RD <i>MUST</i> let the EU choose a BVD . If both RequesterID and IDPList are used, any BVD that is in a RequesterID <i>MUST</i> also be included in the IDPList.

§ 7.1.2.1.2.1 THE USE OF [ATTRIBUTECONSUMINGSERVICEINDEX](#) OR [EXTENSIONS](#) FOR REFERRING TO SERVICE DEFINITIONS

This specification uses the concept of a [Service Catalog](#) kept by [RD](#), which contains amongst others Service Definitions. In the [Service Catalog](#) each 'Service Definition' has a unique [ServiceUUID](#). Each [AuthN Request message](#) must refer to a [Service Definition](#) using its [ServiceUUID](#).

An [AuthN Request message](#) has two options for this [ServiceUUID](#) reference:

1. Only the [DV](#) *MAY* provide a [@AttributeConsumingServiceIndex](#) that *MUST* correspond to an [Index](#) attribute of an [AttributeConsumingService](#) entry in the [DV Metadata](#). And this [AttributeConsumingService](#) entry *MUST* contain a [ServiceUUID](#). When using the [AttributeConsumingServiceIndex](#) the [RD](#) will obtain the [DV](#)'s [EntityID](#) from the [Issuer](#) element in the [AuthN Request message](#).
2. Alternatively a [DV](#) *MAY* use the [Extensions](#) element in the [AuthN Request message](#). All other [Participants](#) *MUST* use the [Extensions](#) element in the [AuthN Request message](#). The [Extensions](#) element contains both the [EntityID](#) of the [DV](#) and the explicit [ServiceUUID](#).

§ 7.1.2.1.3 DV → RD AUTHNREQUEST PROCESSING RULES

In addition to the processing rules required by the SAML specification the following rule applies. If any of these validations fails, the authentication *MUST* fail:

1. [RD](#) *MUST* validate that the [DV](#) is registered for the requested [ServiceUUID](#) referenced by the index in the [DV metadata](#) or in the [Extensions element of the DV AuthN-request](#) and validate that the registration is valid;
2. IF an [LC](#) is involved THEN [RD](#) *MUST* validate that the [DV](#) is registered to use the requested [ServiceUUID](#) with the [LC](#) that sends the [DV AuthN-Request message](#) on behalf of the [DV](#) and that the registration is valid;

§ 7.1.2.2 DV ← RD Artifact Binding

The SAML response of a [RD](#) to a [SAML request](#) of a [DV](#) (or [LC](#)) uses an [Artifact](#)-Binding for extra security see [[SAML2.BINDINGS](#)] section 3.6.6. Therefor SAML Response does not return the actual SAML message with an Authentication Assertion but an [Artifact](#) as a reference to actual the SAML [AuthN Response - Assertion](#) message. The Artifact is used by the [DV](#) (or [LC](#)) to retrieve the SAML [AuthN Response - Assertion](#) at the [RD](#).

§ 7.1.2.2.1 DV ← RD - ARTIFACT BINDING - DIAGRAM

The sender and recipient of this message are the following:

Sender	Recipient
RD	DV
RD	LC




Figure 6 SAML authentication flow - DV/LC - RD - Artifact Response

§ 7.1.2.2.2 DV ← RD - ARTIFACT BINDING - MESSAGE

The [RD](#) sends an [Artifact](#) via the [Front channel](#) to the [DV/LC](#), using a HTTP-redirect of the [webbrowser](#) to the [AssertionConsumerService](#) referenced in the [AuthN Request message](#).

e.g. `https://dv.nl/SAML/ACS?`

`SAMLart=AAQAAMh0dHA6Ly9pZHAuZXhhbXBsZS5jb20vU0FNTC9N&RelayState=xyz123`

The [Artifact](#) is only a reference to the SAML [AuthN Response - Assertion](#). And even if no authentication has taken place, an [Artifact](#) will be send.

§ 7.1.2.3 DV → RD ArtifactResolve

The DV/LC uses the Artifact to send an ArtifactResolve request to the RD via a SOAP binding over the Back channel. The Back channel is protected with two-sided TLS authentication.

§ 7.1.2.3.1 DV → RD ARTIFACTRESOLVE DIAGRAM

The sender and recipient of the Artifact Resolve are the following:

Sender Recipient	
DV	RD
LC	RD




Figure 7 SAML authentication flow - DV/LC - RD - Artifact Resolve

§ 7.1.2.3.2 DV → RD ARTIFACTRESOLVE MESSAGE

Element/@Attribute	0..n	Description
@ID	1	Unique message identifier. <i>MUST</i> identify the message uniquely within the scope of the sender and receiver for a period of at least 12 months.
@Version	1	Version of the SAML protocol. The value <i>MUST</i> be 2.0.
@IssueInstant	1	Time at which the message was created.
@Destination	0..1	<i>MAY</i> be included. If included <i>MUST</i> contain the URL of the receiver on which the message is offered. <i>MUST</i> match one of the ArtifactResolutionService elements in the receiver's metadata.
Issuer	1	<i>MUST</i> contain the EntityID of the sender.
Signature	1	<i>MUST</i> contain the Digital signature of the sender for the enveloped message. <i>MUST</i> contain a KeyInfo element with either a KeyName or X509Certificate elements. See Signature .
Artifact	1	Contains the Artifact that was received as query parameter.

§ 7.1.2.4 DV ← RD ArtifactResponse

In response to the [Artifact Resolve message](#), the [RD](#) will send an [Artifact Response message](#) back to the [DV/LC](#) via the SOAP binding over the [Back channel](#). If successful this [Artifact Response message](#) contains the [AuthN-Response Assertion](#) for the original [AuthN Request message](#).

§ 7.1.2.4.1 DV ← RD ARTIFACTRESPONSE DIAGRAM

The sender and recipient of the [Artifact Response message](#) message are the following:

Sender	Recipient
RD	DV
RD	LC




Figure 8 SAML authentication flow - DV/LC - RD - Artifact Response

§ 7.1.2.4.2 DV ← RD ARTIFACTRESPONSE MESSAGE

Element/@Attribute	0..n	Description
@ID	1	Unique message identifier. <i>MUST</i> identify the message uniquely within the scope of the sender and receiver for a period of at least 12 months.
@InResponseTo	1	Unique ID attribute of the Artifact Resolve message request for which this ArtifactResponse message is the response.
@Version	1	Version of the SAML protocol. The value <i>MUST</i> be 2.0.
@IssueInstant	1	Time of issuing of the AuthN Response message .
Issuer	1	<i>MUST</i> contain the EntityID of the sender.

Element/@Attribute	0..n	Description
Signature	1	<i>MUST</i> contain the Digital signature of the sender for the enveloping message. <i>MUST</i> contain a KeyInfo element with a KeyName element. See Signature .
Status	1	<i>MUST</i> contain a StatusCode element with the status of the artifact resolve.
-StatusCode	1	<i>MUST</i> be present in a Status element.
-@Value	1	The Value of this StatusCode element <i>MUST</i> be from the top-level list provided in [SAML2.CORE] section 3.2.2.2 and follow the rules described in [SAML2.BINDINGS] section 3.6.6.
--StatusCode	0..1	Conditional. Should only be present if top-level StatusCode is not urn:oasis:names:tc:SAML:2.0:status:Success.
--@Value	1	If present <i>MUST</i> contain an URI reference indication details about the error.
-StatusMessage	0..1	Only present if top-level StatusCode is not urn:oasis:names:tc:SAML:2.0:status:Success. <i>MAY</i> contain a message detailing the error that occurred.
Response	0..1	Conditional. If the artifact resolves to a response this <i>MUST</i> contain the AuthN Response - Assertion to the AuthN Request message . The AuthN Response - Assertion is described below.

§ 7.1.2.4.2.1 PROCESSING RULES FOR STATUS

Special processing rules for [Status](#) are described in [SAML2.BINDINGS] §3.6.6.

Even if the ArtifactResponse's [Status](#) indicates success it may still not contain a [AuthN Response - Assertion](#) conform [SAML2.BINDINGS] §3.6.6:

If the [RD](#) receives an [Artifact Resolve message](#) message that it can understand, it *MUST* return a [AuthN Response message](#) with a [StatusCode](#) value of urn:oasis:names:tc:SAML:2.0:status:Success, even if it does not return the corresponding message (for example because the artifact requester is not authorized to receive the message or the artifact is no longer valid).

§ 7.1.2.4.3 DV ← RD AUTHN RESPONSE - MESSAGE

Via the [Artifact Response Message](#) the [RD](#) sends the [SAML AuthN-Response Message](#) which is the response the original [AuthN Request message](#) of the [DV/LC](#). The [SAML AuthN-Response Message](#) contains the [AuthN Response - Assertion](#) if authentication of the [EU](#) at the [AD](#) was successful, and (when relevant) the [BVD](#) could establish a valid representation relationship.

Element/@Attribute	0..n	Description
@ID	1	Unique message characteristic. <i>MUST</i> identify the message uniquely within the scope of the sender and receiver for a period of at least 12 months.
@InResponseTo	1	Unique ID attribute of the AuthN Request message request for which this AuthN Response - Message is the response.
@Version	1	Version of the SAML protocol. The value <i>MUST</i> be 2.0.

Element/@Attribute	0..n	Description
@IssueInstant	1	Time of issuing of the AuthN Response - Assertion .
@Destination		URL of the endpoint on which the message is offered. <i>MUST</i> match a recipient's metadata AssertionConsumerService .
Issuer	1	<i>MUST</i> contain the EntityID of the sender.
Signature	0..1	<i>SHOULD NOT</i> be used as the AuthN Response - Assertion is part of the AuthN Response message messages which is already signed by RD. If included <i>MUST</i> contain the Digital signature of RD for the enveloping message. <i>MUST</i> contain a KeyInfo element with a KeyName or X509Certificate element.
Status	1	<i>MUST</i> contain a StatusCode element with the status of the authentication.
-StatusCode	1	<i>MUST</i> be present in a Status element.
-@Value	1	If not urn:oasis:names:tc:SAML:2.0:status:Success additional information <i>SHOULD</i> be provided in the embedded StatusCode element. The Value of this StatusCode element <i>MUST</i> be from the top-level list provided in SAML core section 3.2.2.2. See the codes listed in Error codes.
--StatusCode	0..1	Conditional. <i>SHOULD</i> only be present if top-level StatusCode is not urn:oasis:names:tc:SAML:2.0:status:Success.
--@Value	1	In the event of a cancellation or error, the element <i>MUST</i> be populated with the value urn:oasis:names:tc:SAML:2.0:status:AuthnFailed .
-StatusMessage	0..1	Only present if top-level StatusCode is not urn:oasis:names:tc:SAML:2.0:status:Success. <i>MAY</i> contain a message detailing the error that occurred, <i>MUST</i> contain exact phrase Authentication cancelled when authentication is cancelled (see also SAML Error codes)
Assertion	0..1	Conditional. <i>MUST</i> contain the AuthN Response - Assertion if the request was processed successfully (Status was urn:oasis:names:tc:SAML:2.0:status:Success). See AuthN Response - Assertion . Otherwise, <i>MUST</i> not be included.
EncryptedAssertion	0	<i>MUST NOT</i> be included.

§ 7.1.2.4.4 DV ← RD AUTHN RESPONSE - ASSERTION

Element/@Attribute	0..n	Description
		Issuer = RD Recipient = DV or LC
@ID	1	Unique message identifier. <i>MUST</i> identify the message uniquely within the scope of the sender and receiver for a period of at least 12 months.
@Version	1	Version of the SAML protocol. The value <i>MUST</i> be 2.0.
@IssueInstant	1	Time of issuance of the AuthN Response - Assertion .
Issuer	1	<i>MUST</i> contain the EntityID of RD .
Signature	1	<i>MUST</i> contain the Digital signature of the sender for the enveloped message. <i>MUST</i> contain a KeyInfo element with a KeyName element. See Signature .
Subject	1	<i>MUST</i> be included.

Element/@Attribute	0..n	Description
-NameID	1	NameID <i>MUST</i> contain a TransientID.
-SubjectConfirmation	1	Contains the SubjectConfirmation conform the WebSSO profile. See also: SubjectConfirmation .
Conditions	1	NotBefore and NotOnOrAfter limit the window during which the assertion can be delivered. See also: Conditions .
-@NotBefore	1	<i>MUST</i> be included.
-@NotOnOrAfter	1	<i>MUST</i> be included.
-AudienceRestriction	1	<i>MUST</i> be included.
--Audience	1..n	<i>MUST</i> contain an EntityID for all relevant parties that are intended to receive and process this assertion, as per SAML WebSSO profile. See below under Audience restriction
AuthnStatement	1	<i>MUST</i> be included.
-@AuthnInstant	1	<i>MUST</i> contain the time of creation of the enclosing AuthN Response - Assertion .
-SessionIndex	0..1	Conditional, <i>MUST</i> contain the same TransientID as NameID . Is used to uniquely identify a session in case of a federated logout-request see Federated Logout-request message . <i>NOTE: For future proof better add SessionIndex element which will probably replace @NameID for LogOut request.</i>
-AuthnContext	1	<i>MUST</i> be included.
--AuthnContextClassRef	1	<i>MUST</i> contain the LoA at which authentication took place. Contains the obtained effective Level of assurance, see below under LoA .
--AuthenticatingAuthority	0..n	<i>MUST</i> contain the EntityID (s) of all authorities that were involved in the authentication and representation except for the assertion issuer.
AttributeStatement	0..1	Conditional. <i>MUST</i> be included if StatusCode is urn:oasis:names:tc:SAML:2.0:status:Success. <i>MUST NOT</i> be included otherwise. <i>MUST</i> contain a single attributestatement in accordance with the section Attributestatement below and the rules for processing an AuthN Response .
Advice	1	<i>MUST</i> contain the original assertions received from the AD and BVD (if applicable) that were involved in processing the AuthN Request message .
-Assertion	1..n	Contains the original Assertion elements this assertion is composed of: <i>MUST</i> contain the original AD Assertion. <i>MAY</i> contain the original Assertion of the BVD in case of representation.

§ 7.1.2.4.4.1 AUDIENCE RESTRICTION - DV

The [AudienceRestriction](#) element in the [AuthN Response - Assertion](#) must be checked in terms of content. An [AuthN Response - Assertion](#) may only be processed if the [AudienceRestriction](#) contains the [EntityID](#) of the recipient.

The values for DVs included in [Audience](#) are reflected in the [Recipient](#) attribute of the [EncryptedID](#) element in the [AttributeStatement](#). This does not apply to the [LC](#) or [RD](#) that is only included in the [AudienceRestriction](#). The [LC](#) or [RD](#) is not, after all, an entity which may receive identities.

§ 7.1.2.4.4.2 LEVEL OF ASSURANCE VALIDATION

The [AuthnContextClassRef](#) in the [AuthN Response - Assertion](#) always states the authentication level at which the citizen has authenticated himself. [DV](#)'s *MUST* be prepared for the [AuthnContextClassRef](#) to contain a higher [LoA](#) than the requested [LoA](#). [DV](#)'s *MUST* accept authentications with a level equal to or higher than the minimum level registered for the [Service](#) in the [Service Catalog](#). [DV](#) must configure minimum [LoA](#) for the [Service](#) when providing information in the onboarding process. The [AD](#) is responsible for providing the correct [LoA](#) for a given authentication request (equal to or higher than the [LoA](#) registered for the [Service](#) in the [Service Catalog](#))

§ 7.1.2.4.4.3 SUBJECTCONFIRMATION - DV

The [SubjectConfirmation](#) exists in a [Subject](#) and is used to hold a bearer confirmation in a [AuthN Response - Assertion](#) to an [AuthN Request message](#), to conform to the WebSSO profile. In case a relying party is requesting authentication of an [EU](#) according to the SAML Web SSO profile, a bearer [SubjectConfirmation](#) (see [SAML2.PROFILES], §3.3 and §4.1.4) must be provided. The [NotOnOrAfter](#) in the [SubjectConfirmationData](#) element limits the time during which the [AuthN Response - Assertion](#) result *MAY* be used to establish an authenticated session for the [EU](#) using the [AuthN Response - Assertion](#). The [NotOnOrAfter](#) is initially set to +2 minutes relative to the time of issuance of the enclosing [AuthN Response - Assertion](#). These values can be changed however in time. The `dv-authn-response-assertion/NotBefore` attribute *MUST NOT* be used.

Element/@Attribute	0..n	Description
<i>SubjectConfirmation</i>	1	Allows for association of client with assertion to conform to the SAML Web SSO profile.
<i>-@Method</i>	1	<i>MUST</i> contain the value <code>urn:oasis:names:tc:SAML:2.0:cm:bearer</code> .
<i>-SubjectConfirmationData</i>	1	<i>MUST</i> be included.
<i>--@NotOnOrAfter</i>	1	A time instance at which the subject can no longer be confirmed.
<i>--@Recipient</i>	1	The assertion consumer Service URL of the immediate requester to which an attesting entity can present the assertion.
<i>--@InResponseTo</i>	1	The ID of the AuthN Request message this AuthN Response - Assertion is in response to.

§ 7.1.2.4.4.4 CONDITIONS

The [NotBefore](#) and [NotOnOrAfter](#) in the [Conditions](#) element limit the time during which the [AuthN Response - Assertion](#) is considered valid within a prior established authenticated [EU](#) session based on this [AuthN Response - Assertion](#). The

value of these attributes should be aligned with the maximum session duration (which may be dependent on the [LoA](#)) and typically is much longer than the validity of the [SubjectConfirmation](#) .

§ 7.1.2.4.4.5 ATTRIBUTE STATEMENT - DV

The [AuthN Response - Assertion](#) when present *MUST* contain an [attributestatement](#). An [attributestatement](#) contains one or more [Attribute](#) elements and *MUST* contain exactly one [Attribute](#) with @Name="urn:n1-eid-gdi:1.0:ActingSubjectID". It *MAY* contain exactly one [Attribute](#) element with @Name="urn:n1-eid-gdi:1.0:LegalSubjectID" indicating representation. Both ActingSubjectID and LegalSubjectID [Attributes](#) *MUST* contain one or more [AttributeValues](#) for one or more Recipients (e.g. [DV](#)). And these Recipients must be included in the [AudienceRestriction](#) element.

Element/@Attribute	0..n	Description
AttributeStatement	1	<i>MUST</i> be included.
-Attribute	1..n	See the tables below for details.
--@Name	1	<i>MUST</i> contain the type of the attribute.
--AttributeValue	1..n	The Attribute <i>MUST</i> contain one or more AttributeValues.

§ 7.1.2.4.4.6 GENERIC ATTRIBUTES

In all cases the [LoA](#), [ServiceUUID](#) and [ServiceID](#) will be provided as an unencrypted [Attribute](#).

Attribute	1..n	Attribute Name	Description
ServiceUUID	1	Name ="urn:n1-eid-gdi:1.0:ServiceUUID"	
-AttributeValue	1..n		The ServiceUUID of the Service for which this SAML Response is intended as indicated in the AuthN Request message .
ServiceID	1	Name ="urn:etoegang:core:ServiceID"	
-AttributeValue	1..n	urn:etoegang:DV:< QIN >:services:<index>	The ServiceID of the Service for which this SAML Response is intended as indicated in the original AuthN Request message .

In case of representation in combination with (<https://afsprakenstelsel.etoegang.nl/Startpagina/as/guc4-3-portaalfunctie>) [\[ETD PortalService\]](#) a [ServiceUUID](#) and [\[ServiceID\]](#) can be multivalued, expressing the relevant services within the webportal (as registered in the ETD [Service Catalog](#)) for which the [EU](#) has a mandate.

In case of legal representation the [ServiceUUID](#) and [ServiceID](#) have only 1 value, a copy of [Attribute](#) in [AuthN Request message](#) and the associated [ServiceID](#).

§ 7.1.2.4.4.7 ATTRIBUTE CONTAINING IDENTIFIERS

In any response the following attributes containing the Identifier(s) will be provided as an [EncryptedID](#).

Attribute	1..n	Attribute Name	Description
ActingSubjectID	1	Name ="urn:n1-eid-gdi:1.0:ActingSubjectID"	Identity of the EndUser (EU)
-AttributeValue	1..n		The (encrypted) ActingSubjectID as received from the AD at which the EU was authenticated. All contain identities of the same EU .
LegalSubjectID	1	Name ="urn:n1-eid-gdi:1.0:LegalSubjectID"	Identity of the Service Consumer
-AttributeValue	1..n		The LegalSubjectID contains at least one (#dv-encryptedid)[Encrypted Identity] of the same Service Consumer .

If there is no representation the AttributeValues of ActingSubjectID and LegalSubjectID *MUST* be exactly the same, indentifying both the [EU](#) and [Service Consumer](#) as the same natural person. In case of Representation the AttributeValues of ActingSubjectID and LegalSubjectID *MUST* be different.

§ 7.1.2.4.4.8 EXAMPLE ATTRIBUTE STATEMENT

```
<saml2:AttributeStatement>
  ...
  <saml2:Attribute Name="urn:n1-eid-gdi:1.0:ActingSubjectID">
    <saml2:AttributeValue>
      // EncryptedID with BSN of ActingSubject
    </saml2:AttributeValue>
  </saml2:Attribute>
  <saml2:Attribute Name="urn:n1-eid-gdi:1.0:LegalSubjectID">
    <saml2:AttributeValue>
      // EncryptedID with BSN LegalSubject
    </saml2:AttributeValue>
  </saml2:Attribute>
  <saml:Attribute Name="urn:etoegang:core:ServiceID"> // multivalue example
    <saml:AttributeValue xsi:type="xs:string">
      urn:etoegang:DV:00000002003214394002:services:1
    </saml:AttributeValue>
    <saml:AttributeValue xsi:type="xs:string">
      urn:etoegang:DV:00000002003214394002:services:2
    </saml:AttributeValue>
  </saml:Attribute>
  <saml:Attribute Name="urn:etoegang:core:ServiceUUID"> // multivalue example
    <saml:AttributeValue xsi:type="xs:string">
      dd4dae83-0f35-4695-b24a-29d470a63ea7
    </saml:AttributeValue>
```

```

    <saml:AttributeValue xsi:type="xs:string">
      df4a5b79-2e56-3876-446b-56fe537f78b2
    </saml:AttributeValue>
  </saml:Attribute>
  ...
</saml2:AttributeStatement>

```

§ 7.1.2.4.4.9 ATTRIBUTE TYPES IN CASE OF LEGAL REPRESENTATION

In case of legal representation, via [BVD](#), the following attribute will be provided as an unencrypted [Attribute](#), next to the (#attribute-containing-identifiers)[Attribute containing Identifiers].

Type	1..n	Attribute Name	Description
RepresentationType	0-1	Name ="urn:nl-eid-gdi:1.1:RepresentationType"	Required for any type of legal representation by the BVD
-AttributeValue	1..n		The type of representation , to be used by Service Provider DV for access decision multiple values of Legal Representation allowed.

§ 7.1.2.4.4.10 EXAMPLE ATTRIBUTE STATEMENT FOR LEGAL REPRESENTATION

```

<saml2:AttributeStatement>
  ...
  <saml2:Attribute Name="urn:nl-eid-gdi:1.0:ActingSubjectID">
    <saml2:AttributeValue>
      // EncryptedID with BSN of ActingSubject (ouder/voogd)
    </saml2:AttributeValue>
  </saml2:Attribute>
  <saml2:Attribute Name="urn:nl-eid-gdi:1.0:LegalSubjectID">
    <saml2:AttributeValue>
      // EncryptedID with BSN LegalSubject (kind)
    </saml2:AttributeValue>
  </saml2:Attribute>
  <saml:Attribute Name="urn:etoegang:core:ServiceID" // must have 1 value
    <saml:AttributeValue xsi:type="xs:string">
      urn:etoegang:DV:000000002003214394002:services:1
    </saml:AttributeValue>
  </saml:Attribute>
  <saml:Attribute Name="urn:etoegang:core:ServiceUUID" // must have 1 value
    <saml:AttributeValue xsi:type="xs:string">
      dd4dae83-0f35-4695-b24a-29d470a63ea7
    </saml:AttributeValue>
  </saml:Attribute>
  </saml2:Attribute>
  <saml2:Attribute Name="urn:nl-eid-gdi:1.1:RepresentationType">

```

```

    <saml2:AttributeValue>urn:nl-eid-gdi:1.1:RT:Zorg_Volledig_Gezag_Kind</saml2:Attri
  </saml2:Attribute>
  ...
</saml2:AttributeStatement>

```

§ 7.1.2.4.4.11 ATTRIBUTE TYPES ISSUER IN CASE OF CHAIN REPRESENTATION

In case of a 'chain' representation the above described (#attribute-containing-identifiers)[Attribute containing Identifiers]. and in case of legal representation the (#attribute-for-legal-representation)[Attribute types in case of legal representation] will be provided.

the following attributes will be provided as Attribute or EncryptedAttribute

Type	1..n	Attribute Name	Description
IntermediateEntityID	1	Name ="urn:etoegang:1.9:IntermediateEntityID:KvKnr" OR "urn:etoegang:1.13:IntermediateEntityID:TRR-BD"	Identity of the Intermediate Party
-AttributeValue	1		The IntermediateEntityID as received from MR

Type	1..n	Encrypted Attribute Name	Description
Intermediate.CompanyName	1	Name ="urn:etoegang:1.13:attribute-intermediate:CompanyName"	CompanyName of the Intermediate Party
-AttributeValue	1		The Intermediate CompanyName as received from MR

§ 7.1.2.4.4.12 EXAMPLE ATTRIBUTE STATEMENT FOR CHAIN REPRESENTATION

```

<saml2:AttributeStatement>
  ...
  <saml2:Attribute Name="urn:nl-eid-gdi:1.0:ActingSubjectID">
    <saml2:AttributeValue>
      // EncryptedID with BSN of ActingSubject
    </saml2:AttributeValue>
  </saml2:Attribute>
  <saml2:Attribute Name="urn:nl-eid-gdi:1.0:LegalSubjectID">
    <saml2:AttributeValue>
      // EncryptedID with BSN LegalSubject
    </saml2:AttributeValue>
  </saml2:Attribute>
  <saml:Attribute Name="urn:etoegang:core:ServiceID"> // multivalue example
    <saml:AttributeValue xsi:type="xs:string">
      urn:etoegang:DV:00000002003214394002:services:1
    </saml:AttributeValue>
    <saml:AttributeValue xsi:type="xs:string">

```

```

urn:etoegang:DV:00000002003214394002:services:2
  </saml:AttributeValue>
</saml:Attribute>
<saml:Attribute Name="urn:etoegang:core:ServiceUUID"> // multivalue example
  <saml:AttributeValue xsi:type="xs:string">
    dd4dae83-0f35-4695-b24a-29d470a63ea7
  </saml:AttributeValue>
  <saml:AttributeValue xsi:type="xs:string">
    df4a5b79-2e56-3876-446b-56fe537f78b2
  </saml:AttributeValue>
</saml:Attribute>
<saml:Attribute Name="urn:etoegang:1.9:IntermediateEntityID:KvKnr">
  <saml:AttributeValue xsi:type="xs:string">
    987654321 // KvK of Intermediary
  </saml:AttributeValue>
</saml:Attribute>
...
<saml:EncryptedAttribute> // urn:etoegang:1.13:attribute-intermediate:CompanyName
  <xenc:EncryptedData Id="_cd52e15a16e2a0aa751725ce76a6b866">
    <xenc:EncryptionMethod Algorithm="http://www.w3.org/2001/04/xmlenc#aes256-cbc">
      <ds:KeyInfo>
        <ds:Keyname>
          _c009e2a74d6b655f2d5830537b49e81cad63a728
        </ds:Keyname>
      </ds:KeyInfo>
      <xenc:CipherData>
        <xenc:CipherValue>...</xenc:CipherValue>
      </xenc:CipherData>
    </xenc:EncryptedData>
    <xenc:EncryptedKey Id="_fd73ad54daf1ca14a4aac30ea850340a" Recipient="urn:etoegang:1.9:IntermediateEntityID:KvKnr">
      <xenc:EncryptionMethod Algorithm="http://www.w3.org/2001/04/xmlenc#rsa-oaep-mgf1p">
        <ds:DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1">
          <ds:DigestValue>...</ds:DigestValue>
        </ds:DigestMethod>
      </xenc:EncryptionMethod>
      <ds:KeyInfo>
        <ds:KeyName>...</ds:KeyName>
      </ds:KeyInfo>
      <xenc:CipherData>
        <xenc:CipherValue>H5nzimm7fAZuzdnZ...</xenc:CipherValue>
      </xenc:CipherData>
      <xenc:ReferenceList>
        <xenc:DataReference URI="#_cd52e15a16e2a0aa751725ce76a6b866">
          <xenc:CarriedKeyName>
            _c009e2a74d6b655f2d5830537b49e81cad63a728
          </xenc:CarriedKeyName>
        </xenc:DataReference>
      </xenc:ReferenceList>
    </xenc:EncryptedKey>
  </saml:EncryptedAttribute>
</saml2:AttributeStatement>

```

§ 7.1.2.4.4.13 OTHER ETD ATTRIBUTES

[RD](#) will copy any other EncryptedAttribute provided by [ETD Stelsel](#) if Recipient <xenc:EncryptedKey Id="_fd73ad54daf1ca14a4aac30ea850340a" Recipient="urn:etoegang:DV:00000002003214394002:entities:0">contains an (#entityid-format)[EntityID] with QID of [DV](#). See <https://afsprakenstelsel.etoegang.nl/Startpagina/as/attribuutcatalogus>

§ 7.1.2.4.5 DV ← RD AUTHN RESPONSE - MESSAGE PROCESSING RULES FOR DV

Regardless of the SAML binding used, the service provider *MUST* do the following:

1. Verify any signatures present on the [AuthN Response - Assertion](#) or the [AuthN Response - Assertion](#).
2. Verify that the **dv-subjectconfirmation/@Recipient** attribute in any bearer [Subject Confirmationdata](#) matches the assertion consumer service URL to which the [AuthN Response - Assertion](#) or [Artifact](#) was delivered.
3. Verify that the [@NotOnOrAfter](#) attribute in any bearer [Subject Confirmationdata](#) has not passed, subject to allowable clock skew between the providers.
4. Verify that the [@InResponseTo](#) attribute in the bearer [Subject Confirmationdata](#) equals the [@ID](#) of its original [AuthN Request message](#) message.
5. Verify that its [EntityID](#) is included as [Audience](#) in the [AuthN Response - Assertion](#).
6. Verify that any assertions relied upon are valid in other respects.
7. Any assertion which is not valid, or whose subject confirmation requirements cannot be met *SHOULD* be discarded and *SHOULD NOT* be used to establish a security context for the principal.

§7.2 Federated Logout Message specification

§ 7.2.1 DV → RD login & logout

NOTE

Support for federated login and logout may be subject to change in future versions of this specification. [DV/LCs](#) which decide to make use of federated login and logout, as supported by this version of the specification, must be prepared to make all the necessary changes to their use of federated login and logout as soon as a later version of the specification mandates such changes.

Support for federated login and logout in future versions of this specification will adhere to policies that are expected to emerge from the broader discussion about federated login and logout in the context of the eIDAS regulation.

Most notably, support for IdP [AD](#) initiated logout may become mandatory in a future version of this specification.

§ 7.2.1.1 DV Federated Login

Federated Login via a [SSO](#) federation is only supported for multiple connections (websites) of a single [DV](#). Furthermore, [DigiD](#) does not support SSO federation between [*DigiD SAML3.x*] and [*eID SAML4.4*] (or later) connections.

A [DV](#) who wants to grant access to his services through [SSO](#) can do so via the [SSO](#) service from [RD](#). The [DV](#) then participates in an [SSO](#) federation which may include several websites of the [DV](#) who all want to use the [SSO](#) functionality that is offered within the [SSO](#) federation. Details on the [SSO](#) service are provided by [RD](#). In a number of cases, the [EU](#) is still asked to provide his credentials:

1. The Level of Assurance [LoA](#) that the [DV](#) website requests may be higher than the level of reliability that is stored in the existing [SSO](#) session.
2. The existing [SSO](#) session can apply to a different [SSO](#) federation than the [DV](#) website is a member of.
3. The [DV](#) website can include the ForceAuthn element in the [authentication request](#), with the value True. If a value is not provided or the element is omitted, the default is "False"
4. The existing [SSO](#) session has expired.

§ 7.2.1.2 DV → RD logout Request - Diagram

A [DV](#) or [LC](#) can send this message to [RD](#) when an [EU](#) logs out at an [DV](#). A [RD](#) can send this message to an [AD](#).

Sender Recipient	
DV	RD
LC	RD




Figure 9 LogoutRequest DV/LC - RD

Only SP (DV) initiated logout is supported by RD. On receiving a logout request (1) a DV which participates in a SSO federation *MUST* send a [Logout request](#) to RD (2b).

This will result in RD to terminate the SSO session if it still was active. As a result, the EU will have to re-authenticate when accessing a DV even if that DV is part of the same SSO federation that was just terminated.

SP initiated logout is limited in the sense that any other active SSO originated sessions with DV's is not actively terminated upon receipt of a SP (DV) initiated logout message. Sessions with other active DV's within the same federation will continue to be active until the local DV session times out or the EU logs out of the DV.

§ 7.2.1.3 DV → RD logout Request - Message

Element/@Attribute	0..n	Description
@ID	1	Unique message attribute
@Version	1	Version of the SAML protocol. The value <i>MUST</i> be '2.0'.
@IssueInstant	1	Time at which the message was created.
@Destination	1	URL of the recipient on which the message is offered.
Signature	1	<i>MUST</i> contain the Digital signature of the sender for the enveloped message (@Algorithm="http://www.w3.org/2000/09/xmldsig#enveloped-signature"). <i>MUST</i> contain a KeyInfo element with either a KeyName or X509Certificate elements. See Signature .
NameID	1	<i>MUST</i> contain the @NameID NameID element of the original Assertion.

Element/@Attribute	0..n	Description
SessionIndex	0..1	Conditional, <i>MUST</i> contain the TransientID SessionIndex element of the original Assertion.
Issuer	1	<i>MUST</i> contain the of the sender.

§ 7.2.1.4 DV ← RD logout Response - Diagram

In response to a [Logout Request message](#) the [RD](#) will send this message to the [DV](#) or [LC](#), or a [AD](#) will send this message to the requesting [RD](#).

Sender	Recipient
RD	DV
RD	LC




Figure 10 LogoutResponse DV/LC - RD

§ 7.2.1.5 DV ← RD logout Response - Message

Element/@Attribute	0..n	Description
@ID	1	Unique message attribute

Element/@Attribute	0..n	Description
@Version	1	Version of the SAML protocol. The value <i>MUST</i> be 2.0.
@IssueInstant	1	Time at which the message was created.
@Destination	1	URL of the recipient on which the message is offered.
@InResponseTo	1	ID of the Logout Request message for which this Logout Response message is the answer.
Signature	1	<i>MUST</i> contain the Digital signature of the sender for the enveloped message (@Algorithm="http://www.w3.org/2000/09/xmldsig#enveloped-signature"). <i>MUST</i> contain a KeyInfo element with a KeyName element. See Signature .
Issuer	1	<i>MUST</i> contain the EntityID of the sender.
Status	1	<i>MUST</i> contain a StatusCode element with the status of the logout.
-StatusCode	1	<i>MUST</i> be present in a Status element.

§ 7.2.2 RD → AD login & logout

This section is extending the [DV/LC → RD SAML Federated login and logout](#) between [RD](#) and [AD](#).

A [RD](#) that supports [SSO](#) to [DV](#) s or [LC](#) s must propagate logout requests to the correct [AD](#) or [ADs](#). The diagram below depicts the flow between a [RD](#) and an [AD](#). The encompassing flow, between [DV/LC](#) and [RD](#), is out of scope (see [[eID SAML4.4](#)] for details).

§ 7.2.2.1 RD → AD logout Request - Diagram

A [DV](#) or [LC](#) can send this message to [RD](#) when a user logs out at an [DV](#). A [RD](#) can send this message to an [AD](#).

Sender	Recipient
RD	AD




Figure 11 Logout Response RD -AD

§ 7.2.2.2 RD → AD logout Request - Message

A [DV](#) or [LC](#) can send this message to [RD](#) when a user logs out at an [DV](#). A [RD](#) can send this message to an [AD](#). he message is identical to [DV/LC → RD SAML Federated logout Request - Message](#)

§ 7.2.2.3 RD ← AD logout Response - Diagram

In response to a [Logout Request message](#) from [RD](#), an [AD](#) will send this message to the requesting [RD](#).




Figure 12 Logout Response RD -AD

§ 7.2.2.4 RD → AD logout Response - Message

An AD can send this Federated logout response message to the requesting RD. The message is identical to DV/LC → RD SAML Federated logout Response - Message

§7.3 Error messages

§ 7.3.1 Toplevel codes

The standard SAML 2.0 error codes are used. For error handling, conformity regarding the interpretation of the status codes as used in the [AuthN Response - Assertion](#) element is critical. The following top-level status codes *MAY* be used:

Status code	Description
<i>urn:oasis:names:tc:SAML:2.0:status:Requester</i>	This status code is used for errors caused by the initiator of the SAML request. For example, because an assurance level is requested which is not supported by the recipient, or because the request message has expired.
<i>urn:oasis:names:tc:SAML:2.0:status:Responder</i>	This status code is used for errors caused by the recipient of the SAML request. For example, because of technical failure or because the recipient does not support requested (optional) functionality.

§ 7.3.2 Second-level status codes

The following second-level status codes *MAY* be used:

Status code	Description
<i>urn:oasis:names:tc:SAML:2.0:status:AuthnFailed</i>	This status code is used when a user cannot be authenticated for example because invalid credentials have been provided or the cancel button has been used.
<i>urn:oasis:names:tc:SAML:2.0:status:NoAuthnContext</i>	This status code is used when a user cannot be authenticated at the minimum level as specified in the Service Catalog .
<i>urn:oasis:names:tc:SAML:2.0:status:RequestUnsupported</i>	This status code is used when a message is correctly formatted by the requester, and understood by the recipient, but that functionality is requested which is not supported by the recipient.
<i>urn:oasis:names:tc:SAML:2.0:status:RequestDenied</i>	This status code is used when a SAML responder that refuses to perform a message exchange with the SAML requester, for example because a mandatory signature could not be verified.
<i>urn:oasis:names:tc:SAML:2.0:status:NoSupportedIDP</i>	Used to indicate that a RequesterID is not supported by the intermediary.

§ 7.3.3 Cancelling

During the process of authenticating and authorizing, an [EU](#) may cancel the process by clicking on the cancel button.

If an [EU](#) cancels, the [Participant](#) *MUST* direct the [EU](#) automatically to the latest sender of a SAML request, accompanying a valid SAML [AuthN Response - StatusMessage](#) including valid SAML status codes ([urn:oasis:names:tc:SAML:2.0:status:Responder](#) with [urn:oasis:names:tc:SAML:2.0:status:AuthnFailed](#)). A [AuthN Response - StatusMessage](#) element *MUST* be included, containing the exact phrase Authentication cancelled.

If [RD](#) receives a cancellation message (from an [AD](#) or [BVD](#)), it *MUST* be forwarded to the [DV](#) or [LC](#).

If a [DV](#) or [LC](#) receives a cancellation message (from [RD](#)), it *MUST* indicate to the [EU](#) that he is not logged in, and *MAY* offer the [EU](#) the option to re-authenticate.

§ 7.3.4 Attributes not supported

A [Participant](#) can receive a message that matches the Interface specifications but cannot be processed by the recipient.

A [Participant](#) receiving such a message:

- *MUST* show the [EU](#) a message indicating that something went wrong (without revealing security sensitive details).
- *MAY* offer the [EU](#) the option to cancel, in that case the flow continues as stated in Cancelling.

§ 7.3.5 Incorrect message (recoverable)

A [Participant](#) can receive a message that matches the interface specifications but cannot be processed by the recipient. The recipient *MUST* direct the [EU](#) to initiator of the SAML request, accompanying a valid SAML [AuthN-response message](#) including valid SAML status codes ([urn:oasis:names:tc:SAML:2.0:status:Responder](#) with [urn:oasis:names:tc:SAML:2.0:status:RequestUnsupported](#)). A [AuthN Response - StatusMessage](#) element *MUST* be included, containing a description of the problem (for example "Level of assurance not supported").

A [Participant](#) receiving such a response:

1. *MUST* show the [EU](#) a [AuthN-response message](#) indicating authentication has failed, including the contents of [AuthN Response - StatusMessage](#).
2. If the [Participant](#) is a [RD](#) then the [RD](#) *MUST* ask the [EU](#) to re-select an [AD](#) or [BVD](#) or cancel. Except in case of [Use Case AD-preselection](#), then the [RD](#) *MUST* forward the [AuthN-response message](#) to the [DV](#) or [LC](#).

§ 7.3.6 Incorrect message (non-recoverable)

A [Participant](#) can receive an invalid formatted message. Examples:

- Not a valid SAML message
- XML does not match XSD

Alternatively, the message can be valid according to SAML specifications, but it does not match the Interface specifications. Examples:

- Unknown issuer
- Invalid NotOnOrAfter in [Authn Response Assertion](#) or [Authn Response Subject Confirmation](#)
- Invalid signature
- The [AuthN-request message](#) contains invalid attributes
- The [AuthN-response message](#) contains attributes or a [LoA](#) that does not match the [AuthN-request](#)

Such messages are the result of either an incorrect implementation by a [Participant](#), or an attempt to hack the system. The [EU](#) cannot always be send back to the requester, because the source of the message is unknown and/or cannot be trusted. If the message is an [AuthN-response message](#), it would not make sense to send the [EU](#) back to the responder.

A [Participant](#) that receives a [AuthN-response message](#) in this category

- *MUST* investigate the nature of the error.
- *MUST* show the [EU](#) a message indicating a non-recoverable error has occurred, advising the [EU](#) how to resolve the problem if possible, in case a binding is used where the [EU](#) is involved;
- *MUST* return a [AuthN-response message](#) with status codes ([urn:oasis:names:tc:SAML:2.0:status:Requester](#) and [urn:oasis:names:tc:SAML:2.0:status:RequestUnsupported](#)) or an HTTP error in case a binding is used where a synchronous response is expected and can be returned, like SOAP.

§8. SAML Metadata

§8.1 Metadata

Before a SAML connection can be established, the participants must provide each other with configuration data about the connection. This indicates which services, locations of services and certificates are used for the connection.

§ 8.1.1 TLS certificates in metadata

For TLS certificates see technical requirements on [Signature](#) and on [Signing, encryption algorithms and hash functions](#)

§ 8.1.2 General processing requirements

Processing requirements for the consuming parties:

- The metadata *MUST* be validated by the consuming parties

- The consuming parties *MUST NOT* use the metadata if the validation is not successful

§8.2 DV Metadata

§ 8.2.1 DV → RD Metadata

Published by	Consumed by
DV that connects to RD directly	RD

This section describes the metadata that a [DV](#) with a direct connection to [RD](#) (not using a [LC](#)) must provide. This metadata *MAY* be published on a location known to [RD](#) or *MAY* be provided to [RD](#) by any other means supported.

See also [Example SAML-metadata DV for RD](#)

Element/@Attribute	0..n	Description
EntityDescriptor	1	The metadata <i>MUST</i> contain one EntityDescriptor with one SPSSODescriptor element.
-@ID	1	A document-unique identifier for the element, typically used as a reference point when signing.
-@entityID	1	Specifies the unique identifier of the SAML entity whose metadata is described by the element's contents. Contains the entityid of the DV.
-@validUntil	0..1	<i>MAY</i> contain a datetime at which the metadata expires. If validUntil is expired, the metadata is considered invalid. Either validUntil or cacheDuration <i>MUST</i> be present. (following OASIS specification [SAML2.METADATA])
-@cacheDuration	0..1	<i>MAY</i> contain cacheduration. Every Participant is advised to check for new Metadata after the given period. Either validUntil or cacheDuration <i>MUST</i> be present. (following OASIS specification [SAML2.METADATA])
-Signature	1	<i>MUST</i> contain the Digital signature of the DV to verify the integrity of this Metadata and <i>MUST</i> be generated with a (private signing key associated with a) PKIOverheid public-key certificate which contains the same QIN as used in the entityID . Also see technical requirements on Signature and on Signing, encryption algorithms and hash functions
-SPSSODescriptor	1	
--@AuthnRequestsSigned	1	<i>MUST</i> be set to true.
--@protocolSupportEnumeration	1	<i>MUST</i> be set to urn:oasis:names:tc:SAML:2.0:protocol
--@WantAssertionsSigned	1	<i>MUST</i> be set to true.
--KeyDescriptor	2..n	<i>MUST</i> contain KeyDescriptor element(s) that allow for signing of SAML messages and authenticating a TLS connection. This can be achieved by inclusion of 2 KeyDescriptor element with @use="signing" or a single certificate with @use="signing" that supports both functions. A second KeyDescriptor <i>MAY</i> be present for both of these keys to support certificate rollover. SAML message signing and TLS functions <i>MAY</i> be combined in

Element/@Attribute	0..n	Description
		a single certificate or in separate certificates. <i>MUST</i> contain at least 1 KeyDescriptor element that supports encryption (@use="encryption"). A second KeyDescriptor with @use="encryption" <i>MAY</i> be present to support certificate rollover. Also see technical requirements on Signing, encryption algorithms and hash functions
---KeyInfo	1	
----KeyName	1	Contains the name which identifies the key.
----X509Data	1	Contains the encoded PKIOverheid X509 certificate with the public key.
--SingleLogoutService	0..n	Conditional: <i>MUST</i> be present if the DV supports SSO . Describes the endpoint used to log the EU out of its current session if participating in a SSO session.
---@Binding	1	<i>MUST</i> contain the appropriate binding for the endpoint. The binding parameter denotes the type of binding used. This is an urn relating to [SAML2.BINDINGS]. At least one SingleLogoutService <i>MUST</i> contain the HTTP-POST binding.
---@Location	1	<i>MUST</i> contain the URL of the SingleLogoutService endpoint for the Binding .
--AssertionConsumerService	1..n	Must contain at least one URL to which the EU will be redirected after authentication. If more than one is included one <i>MUST</i> contain the attribute @isDefault with value true.
--AttributeConsumingService	0..n	Conditional: <i>MUST</i> be present when DV uses a corresponding AttributeConsumingServiceIndex in the DV AuthnRequest Message . <i>MUST NOT</i> be present in any other case or by any other Participant role. When used, AttributeConsumingService <i>MUST</i> contain 1 or more elements that describe the Service requested using an @Index to a Service Definition registered with Service Catalog kept by RD .
---@Index	1	<i>MUST</i> be present.
---@isDefault	0..1	<i>MUST</i> be present if more than one Index is specified in the metadata. <i>MAY</i> only be present once. If present indicates the default AttributeConsumingService which is used when no AttributeConsumingServiceIndex was referenced in the AuthN Request Message . It is advised to always include an AttributeConsumingServiceIndex in the AuthN Request Message .
---ServiceName	1..n	One or more language-qualified names for the service. Only one descriptor per language <i>MUST</i> be present.
---RequestedAttribute	1..n	At least one RequestedAttribute element <i>MUST</i> be present with @name="urn:n1-eid-gdi:1.0:ServiceUUID".
----AttributeValue	1	<i>MUST</i> contain the ServiceUUID to be used for this authentication. The ServiceUUID must be pre-registered with Service Catalog kept by RD .

§ 8.2.2 LC → RD metadata

Published by Consumed by

LC

RD

This section describes the metadata the LC publishes for the RD. The LC *MUST* provide the metadata for each DV it supports. The metadata *MUST* be signed by the LC. The metadata of all DVs using an LC *MUST* be supplied as a single file and *MAY* additionally be supplied as individual files.

This section describes the layout of the metadata. The XML schema for the Metadata is that of [[SAML2.METADATA](#)].

See also [Example SAML-metadata LC for RD](#)

Element/@Attribute	0..n	Description
EntitiesDescriptor	1	Required element to start metadata containing multiple EntityDescriptors .
-@ID	1	A document-unique identifier for the element, typically used as a reference point when signing.
-@validUntil	0..1	<i>MAY</i> contain a datetime at which the metadata expires. If validUntil is expired, the metadata is considered invalid. Either validUntil or cacheDuration <i>MUST</i> be present. (following OASIS specification [SAML2.METADATA]).
-@cacheDuration	0..1	<i>MAY</i> contain cache duration. Consumers are advised to check for new metadata after the given period. Either validUntil or cacheDuration <i>MUST</i> be present. (following OASIS specification [SAML2.METADATA]).
-Signature	1	<i>MUST</i> contain the Digital signature of the <u>LC</u> to verify the integrity of this Metadata and <i>MUST</i> be generated with a (private signing key associated with a) PKIoverheid public-key certificate which contains the same QIN as used in the entityID . Also see technical requirements on Signature and on Signing, encryption algorithms and hash functions
-EntityDescriptor	1..n	<i>MUST</i> contain the EntityDescriptor of the <u>LC</u> , see LC EntityDescriptor . <i>MUST</i> contain the EntityDescriptors of all <u>DV</u> 's the <u>LC</u> supports, see DV EntityDescriptor .

§ 8.2.2.1 LC → RD EntityDescriptor

Element/@Attribute	0..n	Description
@ID	1	A document-unique identifier for the element, typically used as a reference point when signing.
@entityID	1	<i>MUST</i> contain the entityid of the <u>LC</u> .
@validUntil	0..1	<i>SHOULD NOT</i> be used as either validUntil or cacheDuration is already present at EntitiesDescriptor level. <i>MAY</i> contain a datetime at which the metadata expires. If validUntil is expired, the metadata is considered invalid.
@cacheDuration	0..1	<i>SHOULD NOT</i> be used as either validUntil or cacheDuration is already present at EntitiesDescriptor level.

Element/@Attribute	0..n	Description
		<i>MAY</i> contain cacheduration. RD is advised to check for new metadata after the given period.
@Signature	0..1	<i>SHOULD NOT</i> be used as the metadata is already signed at the EntitiesDescriptor level. If used it <i>MUST</i> be generated with the private signing key with an associated PKIOverheid public-key certificate which contains the same QIN as the entityid in the EntityDescriptor .
@SPSSODescriptor	1	The SPSSODescriptor implements profiles specific to service providers.
-@AuthnRequestsSigned	1	Must be set to true.
-@WantAssertionsSigned	1	Must be set to true.
-@protocolSupportEnumeration	1	<i>MUST</i> be set to: urn:oasis:names:tc:SAML:2.0:protocol.
-KeyDescriptor	1..4	<i>MUST</i> contain KeyDescriptor element(s) that allow for signing of SAML messages and authenticating a TLS connection. This can be achieved by inclusion of 2 KeyDescriptor element with @use="signing" or a single certificate with @use="signing" that supports both functions. A second KeyDescriptor <i>MAY</i> be present for both of these keys to support certificate rollover. SAML message signing and TLS functions <i>MAY</i> be combined in a single certificate or in separate certificates. <i>NOTE:</i> Also see technical requirements on Signing, encryption algorithms and hash functions
--KeyInfo	1	
---KeyName	1	Contains the name which identifies the key. <i>MAY</i> be any string. Common practice is using the SHA1 fingerprint stripped of colons.
---X509Data	1	Contains the encoded X509 certificate with the public key.
-SingleLogoutService	0..n	Conditional: <i>MUST</i> be present if the LC supports SSO . Describes the endpoint used to log the EU out of its current session if participating in a SSO session.
--@Binding	1	<i>MUST</i> contain the appropriate binding for the endpoint. The binding parameter denotes the type of binding used. This is a urn relating to [SAML2.BINDINGS]. At least one SingleLogoutService <i>MUST</i> contain the HTTP-POST binding.
--@Location	1	<i>MUST</i> contain the URL of the SingleLogoutService endpoint for the @Binding .
-AssertionConsumerService	1..n	Must contain at least one URL to which the EU will be redirected after authentication.
--@Binding	1	The binding parameter denotes the type of binding used. This is a urn relating to [SAML2.BINDINGS] At least one AssertionConsumerService binding <i>MUST</i> be set to urn:oasis:names:tc:SAML:2.0:bindings:HTTP-Artifact. Other bindings are NOT supported.
--@Location	1	The URL of the SAML endpoint
--@Index	1	The index of the binding, <i>MUST</i> be unique for all AssertionConsumerService elements.

Element/@Attribute	0..n	Description
--@isDefault	0..1	If more than one AssertionConsumerService elements are included, one of these elements <i>MUST</i> be flagged as default by setting the isDefault XML attribute with value true.

§ 8.2.2.2 DV → RD EntityDescriptor

For each [DV](#) supported by an [LC](#) the following metadata must be included in the [LC](#) metadata.

Element/@Attribute	0..n	Description
@ID	1	A document-unique identifier for the element, typically used as a reference point when signing.
@entityID	1	Specifies the unique identifier of the SAML entity whose metadata is described by the element's contents. <i>MUST</i> contain the entityid of the DV .
@validUntil	0..1	<i>SHOULD NOT</i> be used as either validUntil or cacheDuration is already present at EntitiesDescriptor level. <i>MAY</i> contain a datetime at which the metadata expires. If validUntil is expired, the metadata is considered invalid.
@cacheDuration	0..1	<i>SHOULD NOT</i> be used as either validUntil or cacheDuration is already present at EntitiesDescriptor level. <i>MAY</i> contain cacheduration. RD is advised to check for new metadata after the given period.
Signature	0..1	<i>SHOULD NOT</i> be used as the metadata is already signed at the EntitiesDescriptor level. If used it <i>MUST</i> be generated with the private signing key with an associates PKIoverheid public-key certificate which contains the same QIN as the entityid in the DV EntityDescriptor . The public key certificate <i>MUST</i> be present in the KeyDescriptor metadata. <i>MUST</i> contain a KeyInfo element with a KeyName or X509Certificate elements.
SPSSODescriptor	1	
@-@protocolSupportEnumeration	1	Set to: urn:oasis:names:tc:SAML:2.0:protocol.
-KeyDescriptor	1..2	<i>MUST</i> contain at least 1 KeyDescriptor element that supports encryption (@use="encryption"). A second KeyDescriptor with @use="encryption" <i>MAY</i> be present to support certificate rollover. Also see technical requirements on Signing, encryption algorithms and hash functions
--KeyInfo	1	
---KeyName	1	Contains the name which identifies the key. <i>MAY</i> be any string. Common practice is using the SHA1 fingerprint stripped of colons.
---X509Data	1	Contains the encoded X509 certificate with the public key.
-AssertionConsumerService	1..n	According to saml-metadata-2.0 <i>MUST</i> contain at least one URL to which the EU will be redirected after authentication. <i>MUST</i> contain only one entry. <i>MUST</i> contain a copy of the AssertionConsumerService

Element/@Attribute	0..n	Description
		element in the LC's EntityDescriptor . This entry will be ignored as the AssertionConsumerService definitions in the LC EntityDescriptor <i>MUST</i> be used.

§ 8.2.3 RD → DV/LC metadata

Published by	Consumed by
RD	DV that connect directly with RD , LC

[RD](#) publishes metadata in accordance with [[SAML2.METADATA](#)] with one [EntityDescriptor](#) element. The metadata is signed in accordance with the SAML signature.

See also [Example SAML-metadata a RD for DV](#)

Element/@Attribute	0..n	Description
EntityDescriptor	1	
-@ID	1	A document-unique identifier for the element, typically used as a reference point when signing.
-@entityID	1	Specifies the unique identifier of the SAML entity whose metadata is described by the element's contents. Contains the entityid of RD.
-@validUntil	0..1	<i>MAY</i> contain a datetime at which the metadata expires. If validUntil is expired, the metadata is considered invalid. Either validUntil or cacheDuration <i>MUST</i> be present. (following OASIS specification [SAML2.METADATA])
-@cacheDuration	0..1	<i>MAY</i> contain cache duration. DV or LC is advised to check for new metadata after the given period. Either validUntil or cacheDuration <i>MUST</i> be present. (following OASIS specification [SAML2.METADATA])
-Signature	1	<i>MUST</i> contain the Digital signature of the RD to verify the integrity of this Metadata and <i>MUST</i> be generated with a (private signing key associated with a) PKIoverheid public-key certificate which contains the same QIN as used in the entityID . Also see technical requirements on Signature and on Signing, encryption algorithms and hash functions
-IDPSSODescriptor	1	
--@protocolSupportEnumeration	1	Set to: urn:oasis:names:tc:SAML:2.0:protocol
--@WantAuthnRequestsSigned	1	Set to true indication that AuthnRequest messages <i>MUST</i> be signed by the DV or LC .
--KeyDescriptor	1..n	Contains at least 1 KeyDescriptor element with @use="signing"
---KeyInfo	1	
----KeyName	1	Contains the name which identifies the key.
----X509Data	1	Contains the encoded X509 certificate with the public key.
--ArtifactResolutionService	1..n	The ArtifactResolutionService <i>MUST</i> be implemented at least once per service.

Element/@Attribute	0..n	Description
---@ <i>Binding</i>	1	The binding parameter denotes the type of binding used. In the ArtifactResolutionService this is the SAML-SOAP binding only. The value of this attribute is a urn relating to [SAML2.BINDINGS].
---@ <i>Location</i>	1	The URL of the SAML artifact resolution endpoint
---@ <i>Index</i>	1	The index of the binding, <i>MUST</i> be unique for all ArtifactResolutionService elements
-- <i>SingleSignOnService</i>	1..n	One or more elements of type EndpointType that describe endpoints that support the profiles of the Authentication Request protocol defined in [SAML2.PROFILES].
---@ <i>Binding</i>	1	The binding parameter denotes the type of binding used. In the SingleSignOnService this is the HTTP-POST binding only. The value of this attribute is an urn relating to [SAML2.BINDINGS].
---@ <i>Location</i>	1	The URL of the SAML SingleSignOnService endpoint
-- <i>SingleLogoutService</i>	1..n	Describes the endpoint used to log the EU out of its current session if participating in a SSO session.
---@ <i>Binding</i>	1	<i>MUST</i> be set to urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST. Other bindings are NOT supported.
---@ <i>Location</i>	1	The URL of the SAML endpoint

§9. Technical requirements and recommendations

§9.1 SAML Signing

[ST-SAML](#) does not support SHA1 except for the padding function (xmldsig # rsa-sha1). Only RSA is supported for signing as PKIOverhead certificates do not support other methods. For signing, the following list of signing algorithms is supported:

Signing algorithm	urn
RSAwithSHA256	http://www.w3.org/2001/04/xmldsig-more#rsa-sha256
RSAwithSHA384	http://www.w3.org/2001/04/xmldsig-more#rsa-sha384
RSAwithSHA512	http://www.w3.org/2001/04/xmldsig-more#rsa-sha512

(source: [[XML.SIG](#)] § 6.1)

At minimum, SHA256 must be used to calculate the message digest (<ds:DigestMethod Algorithm = "http://www.w3.org/2001/04/xmenc#sha256" />).

Digest algorithm	urn
SHA256	http://www.w3.org/2001/04/xmenc#sha256
SHA384	http://www.w3.org/2001/04/xmldsig-more#sha384
SHA512	http://www.w3.org/2001/04/xmenc#sha512

(source: [\[XML.SIG\]](#) § 6.1)

All SAML messages that must be signed, must be signed with an Enveloped Signature Transform
<http://www.w3.org/TR/2013/REC-xmlsig-core1-20130411/#enveloped-signature>

[Participants](#) are required to fully check signatures and associated messages according to standards including checking the correctness of the sender. This also applies to [Metadata](#).

To guarantee authenticity, integrity and non-repudiation, each message described *MUST* be provided with a digital signature from the message sender. The message recipient *MUST* validate all of the digital signatures - except signatures in an Assertion/Advice as they are intended for evidence - in the message before processing it according to the processing rules required by PKIoverheid per Certificate Practice Statements (CPS) including checking the validity of the certificate.

- The recipient *MUST* check that the message is signed with a valid digital signature that envelopes the whole message with Enveloped Signature Transform.
- The recipient *MUST NOT* process the message if signature validation fails.

The following requirements apply to generating digital signatures:

- The digital signature is embedded in the message content with Enveloped Signature Transform
<http://www.w3.org/2000/09/xmlsig#enveloped-signature>.
- Canonicalization *MUST* be carried out according to the exclusive c14n method without comments, as identified by <http://www.w3.org/2001/10/xml-exc-c14n#> (see [\[XML.C14N.EXCL\]](#))
- Digests *MUST* be calculated with at minimum the SHA256 algorithm except for the fore mentioned exception (padding with SHA1).
- The SignatureValue *MUST* be calculated with at minimum the RSAwithSHA256 algorithm.
- a [Participant](#) *MUST* sign messages and metadata with a PKIoverheid certificate with a key length of at least 2048 bits, and which contains the QJN of the [Participant](#). PKIoverheid TLS certificates can be included as a signing certificate (in saml [Metadata](#)). Difference with normal signing certificate can be made via extended key usage. See [\[SAML2.ERRATA.05\]](#), E62. So the (extended) key usage of the certificate *MUST* allow use for signing.
- The Reference *MUST* refer to the signed element via an ID attribute in the local document, as per the signature profile of [\[SAML2.CORE\]](#) (§ 5.4) and [\[SAML2.METADATA\]](#) (§ 3.1).

§ 9.1.1 SAML Signature

Each Signature element in SAML messages generated by a [DV](#) or [LC](#) (see [Signature](#) in [DV AuthN-request message](#)) and in the [DV](#) or [LC](#) entries in the [Service Catalog](#) (see [Signature](#) in [DV metadata](#)) *MUST* contain either a KeyInfo element with a X509Certificate element OR a KeyName element containing a key name. The use of KeyName is preferred as this limits the amount of data exchanged. The X509Certificate or KeyName *MUST* match a [X509Data](#) or [KeyName](#) in the [DV metadata KeyDescriptor](#) element with @use="signing".

Each Signature element in SAML messages generated by a [RD](#) (or any other [Participant](#)) and in the [Metadata](#) *MUST* contain a KeyInfo element with a KeyName element containing a key name that corresponds to a [KeyName](#) in a [KeyDescriptor](#) element in the [Metadata](#) for that [Participant](#) .

Certificates used to verify a Signature *MUST* be retrieved from the [Participant](#)'s verified [Metadata](#). The X509Certificate or KeyName in the KeyInfo of the Signature *MUST* only be used to retrieve the corresponding certificate from the [Participant](#)'s verified [Metadata](#).

§9.2 Encryption

Encryption is used to guarantee confidentiality. Encryption in combination with SAML is achieved via XML-encryption (see [EncryptedID](#)). In case encryption *MAY* or *MUST* be used, one *MUST* use the block encryption algorithms identified by the following URI in conjunction with the use of XML Encryption

algorithm	urn
AES-256	http://www.w3.org/2001/04/xmlenc#aes256-cbc

For asymmetric encryption, used to encrypt keys, the RSA algorithm in combination with OAEP padding and a SHA digest *MUST* be used, as described at <http://www.w3.org/TR/xmlenc-core1/#sec-RSA-OAEP>. The SHA1 version *MUST* be used (<http://www.w3.org/2009/xmlenc11#mgf1sha1>).

§ 9.2.1 SAML encryption

Encryption in combination with SAML is achieved via XML-encryption. This paragraph provides an explanation of encrypted elements as well as elements encrypted to multiple recipients.

§ 9.2.1.1 Encrypted elements

Any element that will be encrypted has to conform to the following:

- The element *MUST* be encrypted using applicable encryption algorithms, as defined in Encryption.
- A new, cryptographically sound randomly generated symmetric key *MUST* be used per encrypted element.
- The @Recipient of the resulting *MUST* be set to the EntityID of the recipient.
- XML contents in the encrypted element *MUST* have all namespace definitions.

§ 9.2.1.1.1 MULTIPLE RECIPIENTS

SAML and XML-encryption allow for multiple recipients of the same encrypted element. The construct for this is specified in more detail in errata E43 of [[SAML2.ERRATA.05](#)]. In case of multiple recipients:

- each [EncryptedKey](#) *MUST* have a CarriedKeyName equal to the KeyName used in the KeyInfo of the [EncryptedData](#).
- each [EncryptedKey](#) *SHOULD* have a ReferenceList referring back to the data encrypted with the symmetric key contained.

Upon decryption, elements without an [EncryptedKey](#) intended for the decrypting recipient *MAY* be ignored and [EncryptedKey](#) for other recipients of encrypted elements *SHOULD* be ignored.

§ 9.2.1.2 EncryptedID

Both ActingSubjectID as LegalSubjectID ([Attribute](#) with @Name="urn:n1-eid-gdi:1.0:ActingSubjectID" respectively @Name="urn:n1-eid-gdi:1.0:LegalSubjectID") are unencrypted [Attributes](#) and *MUST* contain one or more [AttributeValues](#). Each of these [AttributeValues](#) *MUST* contain exactly one [EncryptedID](#) element.

Element/@Attribute	0..n	Description
EncryptedID	1	<i>MUST</i> contain one encrypted NameID element. See below for details.
-EncryptedData	1..n	<i>MUST</i> contain the encrypted data containing the XML encrypted NameID which contains the identity.
-EncryptedKey	1..n	<i>MUST</i> contain the wrapped decryption keys, as defined by [XML.ENC]. This element <i>MUST</i> include the intended Recipient
--@Recipient	1	The recipient for which this EncryptedID is intended. This attribute <i>MUST</i> contain an EntityID .

§ 9.2.1.2.1 EXAMPLE ENCRYPTEDID

```
<saml2:EncryptedID xmlns:saml2="urn:oasis:names:tc:SAML:2.0:assertion"
  xmlns:xenc="http://www.w3.org/2001/04/xmenc#"
  xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
  <xenc:EncryptedData
    xmlns:xenc="http://www.w3.org/2001/04/xmenc#"
    Id="_cd52e15a16e2a0aa751725ce76a6b866"
    Type="http://www.w3.org/2001/04/xmenc#Element">
    <xenc:EncryptionMethod
      Algorithm="http://www.w3.org/2001/04/xmenc#aes256-cbc"
      xmlns:xenc="http://www.w3.org/2001/04/xmenc#" />
    <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
      <ds:RetrievalMethod
        Type="http://www.w3.org/2001/04/xmenc#EncryptedKey"
        URI="#_15531f77a9f1e0b5e0cce442aa31bbd4" />
      </ds:KeyInfo>
    <xenc:CipherData xmlns:xenc="http://www.w3.org/2001/04/xmenc#">
      <xenc:CipherValue>AZkW3hbBaQkxs...</xenc:CipherValue>
    </xenc:CipherData>
    </xenc:EncryptedData>
  <xenc:EncryptedKey xmlns:xenc="http://www.w3.org/2001/04/xmenc#"
    Id="_449673558dd0810e91009297f56fd051"
    Recipient="urn:n1-eid-gdi:1.0:DV:0000000999999999004:entities:0000">
    <xenc:EncryptionMethod
      Algorithm="http://www.w3.org/2001/04/xmenc#rsa-oaep-mgf1p"
      xmlns:xenc="http://www.w3.org/2001/04/xmenc#">
    <ds:DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
    </xenc:EncryptionMethod>
    <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
      <ds:KeyName>...</ds:KeyName>
    </ds:KeyInfo>
    <xenc:CipherData xmlns:xenc="http://www.w3.org/2001/04/xmenc#">
      <xenc:CipherValue>yRy923JJlgAi2MTgx1qohLiDBgi...</xenc:CipherValue>
```

```

        </xenc:CipherData>
        <xenc:ReferenceList>
            <xenc:DataReference URI="#_cd52e15a16e2a0aa751725ce76a6b866" />
        </xenc:ReferenceList>
    </xenc:EncryptedKey>
</saml2:EncryptedID>

```

§ 9.2.1.3 NameID - after decrypting EncryptedID

An [EncryptedID](#) *MUST* contain a SAML NameID after decryption, with the following properties:

- The @Format attribute *MUST* be set to urn:oasis:names:tc:SAML:2.0:nameid-format:persistent.
- The @NameQualifier attribute *MUST* be populated with the full name of the type of identifying attribute (see [Attribute Identifier Types](#) for the @NameQualifier types).
- The attributes @SPNameQualifier and @SPProvidedID *MUST NOT* be used.
- In case more than one certificate is listed for encryption for the recipient in the metadata, the content-encryption-key *MUST* be encrypted for each certificate. This will result in multiple [EncryptedKey](#) each with the same [Recipient](#).

§ 9.2.1.3.1 EXAMPLE NAMEID (AFTER DECRYPTION)

```

<saml2:NameID
  xmlns:saml2="urn:oasis:names:tc:SAML:2.0:assertion"
  Format="urn:oasis:names:tc:SAML:2.0:nameid-format:persistent"
  NameQualifier="urn:nl-eid-gdi:1.0:id:legacy-BSN">9999999047</saml2:NameID>

```

§ 9.2.1.4 EncryptedAttribute

An *MUST* contain a SAML after decryption, with the following properties:

Element/@Attribute	0..n	Description
-@Name	1	<i>MUST</i> contain the type of the attribute.
-@AttributeValue	1..n	The Attribute <i>MUST</i> contain one or more AttributeValues.

See also: [Example Encrypted Attribute](#) and [Example Encrypted Attribute after decryption](#)

NOTE

§ 9.2.1.4.1 EXAMPLE ENCRYPTEDATTRIBUTE

```
<saml2:EncryptedAttribute xmlns:saml2="urn:oasis:names:tc:SAML:2.0:assertion"
  xmlns:xenc="http://www.w3.org/2001/04/xmenc#"
  xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
  <xenc:EncryptedData Id="_3c63798db8a16b54ade207ea0df28ad4" Type="http://www.w3.org/2001/04/xmenc:EncryptedData"
    <xenc:EncryptionMethod xmlns:xenc="http://www.w3.org/2001/04/xmenc#"
      Algorithm="http://www.w3.org/2001/04/xmenc#aes256-cbc" />
    <ds:KeyInfo>
      <ds:KeyName>_dd0d7a0215f94ea81b170a2e65834ce8</ds:KeyName>
    </ds:KeyInfo>
    <xenc:CipherData>
      <xenc:CipherValue>5ef0YLEoY1PD2145...</xenc:CipherValue>
    </xenc:CipherData>
  </xenc:EncryptedData>
  <xenc:EncryptedKey Id="_fd73ad54daf1ca14a4aac30ea850340a" Recipient="urn:etoegang:1.13:attribute-intermediate:CompanyName"
    <xenc:EncryptionMethod Algorithm="http://www.w3.org/2001/04/xmenc#rsa-oaep-mgf1p"
      <ds:DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
    </xenc:EncryptionMethod>
    <ds:KeyInfo>
      <ds:KeyName>...</ds:KeyName>
    </ds:KeyInfo>
    <xenc:CipherData>
      <xenc:CipherValue>H5nzimm7fAZuzdnZ...</xenc:CipherValue>
    </xenc:CipherData>
    <xenc:ReferenceList>
      <xenc:DataReference URI="#_3c63798db8a16b54ade207ea0df28ad4" />
    </xenc:ReferenceList>
    <xenc:CarriedKeyName>_dd0d7a0215f94ea81b170a2e65834ce8</xenc:CarriedKeyName>
  </xenc:EncryptedKey>
</saml2:EncryptedAttribute>
```

§ 9.2.1.4.2 EXAMPLE (ENCRYPTED) ATTRIBUTE AFTER DECRYPTION

```
<saml2:Attribute xmlns:saml2="urn:oasis:names:tc:SAML:2.0:assertion"
  xmlns:attrest="urn:oasis:names:tc:SAML:attributes:ext" Name="urn:etoegang:1.13:attribute-
  intermediate:CompanyName" attrest:OriginalIssuer="urn:etoegang:1.11:attribute-sourceid:NLKvK"
  attrest:LastModified="2026-03-31T12:00:00Z"> saml2:AttributeValueBedrijfsnaam BV
```

§9.3 End-to-End encryption

End-to-end encryption is applied in Stelsel Toegang to protect privacy of any involved person as enduser ([EU](#)) or [Service Consumer](#)) or organisations (especially "single person businesses" or "eenmanszaak"). The BSN is one of the main privacy concerns, following from Dutch law, but other personally identifiable information must also be protected. Using

end-to-end encryption as described in this paragraph avoids [RD](#) becoming an unintended hotspot for information on service usage.

§ 9.3.1 Introduction

Personally Identifiable Information (PII) forms the basis of authentication and authorisation (mandates). PII can lead to identification of the particular person, either through the data itself (identifiers), or by combining data, leading to recognising the person through patterns in that data. Within Stelsel Toegang, PII is dispersed over various registers, operated by various [Participants](#). During the authentication and authorisation processes this data must be combined using assertions that are strongly linked together, in order to firmly establish involved identities and appropriate mandates that can be trusted by [DVs](#) in order to securely provide requested services.

Usage of this sensitive data implies that both "security" and "privacy" are important. Security refers to confidentiality, integrity (among which authenticity) and availability of the information. Privacy aims that the [EU](#) is always in control of his/her data, and can trust that only parties for which (s)he gave consent for, have access to that data.

In order to protect PII during this process, several measures are taken, jointly called "end-to-end encryption", that are intended to:

- allow only the intended recipients to see data as needed to perform the required service (principle of "least privilege"); this applies to [Participants](#) as well as [DVs](#).
- prevent "hotspots" to attack; within Stelsel Toegang this applies especially to [RD](#), since all information is routed through [RD](#).

§ 9.3.2 SAML E2E-protection measures

The data that must be protected, is categorised as:

- identifiers: eg. BSN, pseudonyms, KvK-nrs
- content/attributes: eg. name, address, date of birth

Both categories contain data that is considered business and/or privacy sensitive, but the measures to protect them, while partly overlapping, are also partly different.

All sensitive data is End-to-End encrypted, which means encrypted by the [Participant](#) for the intended recipient using XML-based encryption to provide confidentiality. For Identifiers [EncryptedID](#) is used, for all other attributes and content [SAML encryption](#) is used.

For "content" these basic measures are deemed sufficient.

§ 9.3.3 Additional protection measures for Identifiers

For an "identifier" of a natural person (in role of [EU](#) or [Service Consumer](#)) some additional measures were taken on top these basic SAML measures. Because:

- identifiers are more easily recognised by hackers, and allow for easy correlation of related data.

- BSN is determined as extra sensitive in Dutch law.
- RvIG authorises which [DV](#) MAY receive a BSN and [BSNk](#) enforces this authorisation.
- Citizens need to be in control on which [AD](#) (even EU-countries!) have registered a authentication means on their name/BSN.
- Identifiers are sometimes relevant to multiple relying parties (aka 'recipients' e.g. [DV](#), [MR](#)) and must therefore be encrypted separately for each recipient.

The additional measures for personal identifiers are:

- ETD Pseudonymisation - when [DV](#) is not authorised to receive a [BSN](#) or a [BSN](#) is not strickly required for [EU](#) or [Service Consumer](#) the [ETD Stelsel](#) will provide a identifier_types_specific_pseudonym">[ETD Specific Pseudonym](#):
 - These pseudonyms are persistent per relying party, employer and authentication-means. A [DV](#) can recognise returning [EU](#) or [Service Consumer](#)".
 - Because these pseudonyms [DV](#) and employer specific, they cannot be traced across [DV](#)'s, employees or authentication-means. -
- [BSNk](#) Polymorphic Encryption of identifiers and Pseudonyms based on [BSNk polymorphic encryption](#):
 - [Polymorph encrypted pseudonym](#) is cryptographically derived from a [BSN](#) and therefor can be recipient persistent independent of [AD](#), [BVD](#) and [MR](#). [Polymorph encrypted pseudonym](#) is not traceable back to the original BSN.
 - [Polymorph encrypted BSN](#) is cryptographically derived from a [BSN](#) and using the appropriate [BSNk](#) keys can be decrypted to a [BSN](#).
 - Both [Polymorph encrypted pseudonym](#) and [Polymorph encrypted BSN](#) are verifiable attributes: succesfull decryption ensures the identity and qualification of the originating [AD](#), [MR](#) or [BVD](#) and the registration (by this party) of the BSN at the [BSNk](#) under control of the appropriate natural person or a authorised representative.

NOTE

The use of [BSNk](#) Polymofic Encryption is mandatory for all private [Participants](#). The DigiD, DigiD-Machtigen and BVD can use 'legacy' [BSN](#) during a migration period.

§9.4 TLS transport

[RD](#) requires that a [DV](#) always protects http traffic with TLS v1.2 or higher in accordance with the NCSC directive with 'good' assessment (ICT security guidelines for Transport Layer Security (TLS)). The certificate used for this must be issued under PKIoverheid, and the certificate must have a key length or at least 2048 bits.

For the [Back Channel](#) between [RD](#) and the [DV](#) or [LC](#), both parties must use a PKIoverheid certificate and mutual authentication is mandatory. This is also called two-sided or mutual TLS.

§9.5 NotBefore and NotOnOrAfter

[DVs](#) and [LCs](#) must respect the NotBefore and NotOnOrAfter parameters in the message elements and reject messages that do not comply and cancel the authentication. With a re-authentication, the entire protocol handling must take place.

For this it is advisable to use NTP servers (for example from the nl.pool.ntp.org collection of NTP servers). This measure is taken because lag can make the web service vulnerable to certain attacks on the authentication protocol.

§9.6 Levels of assurance

The Levels of Assurance ([LoA](#)) that are supported in the interface are listed in [Level of Assurance](#).

§9.7 Local session

The [DV](#) is responsible for keeping track of the local [EU](#) session. This session *MUST* be terminated after at most 15 minutes inactivity.

The [DV](#) must recognize replay attacks and ward off these attacks.

If the [DV](#) uses cookies to manage sessions, the "Secure" and "HttpOnly" parameters must be used.

NOTE

The setting of the SameSite policy still has to be determined as browsers show inconsistent behavior.

§9.8 RelayState

DVs may provide a RelayState for their own session monitoring. [RD](#) returns the RelayState value provided without any verification. The monitoring of the content and integrity of the RelayState must be done by the service provider ([DV](#)).

The SAML standard uses a maximum of 80 bytes for the RelayState (see the SAML standard).

§9.9 EU interaction

When a [DV](#) forwards an [EU](#) to [RD](#) this must be done in such a way that it is clear to the [EU](#) on which website they are and that they can actually check this. That is why the following requirements apply:

1. The [EU](#) must be redirected to [RD](#) in the same screen that the [EU](#) clicked on "Log in to DigiD".
2. The [EU](#) must see a browser window with the full address bar. This allows an [EU](#) to see on which website he is entering his data. The [EU](#) can check this by inspecting the certificate (green lock).
3. It is not allowed to invoke [RD](#) in a frame or iframe, or to embed these websites in another way in a webpage of the [DV](#).

The [DV](#) must decide on the basis of the [Assertion in the AuthN-response](#) whether an [EU](#) can gain access to the [Service](#) or, in the case of re-authentication (applicable to SAML [SSO](#)), may continue his session.

If the status in the Assertion is not successful or the [EU](#) does not have the required [LoA](#) in the [AuthnContext](#) of the [Assertion in the AuthN-response](#) then:

1. The [DV](#) or [LC](#) *MUST* immediately end the current session of the [EU](#).
2. *SHOULD* show an appropriate message (see [SAML Error codes](#)).

§10. Type definitions

This page and underlying pages describe identifier types which are used by [ST-SAML](#)

- [Type definitions](#)
 - [Attribute identifier types](#)
 - [Attribute representation types {#representation-types}](#)
 - [EntityID Format {#entityid format}](#)
 - [Level of Assurance {#level-of-assurance}](#)

§10.1 Attribute identifier types

[Stelsel Toegang SAML v1.0 specification](#) describes the following attribute identifier types

Attribute	urn	Remarks
Legacy-BSN	urn:nl-eid-gdi:1.0:id:legacy-BSN	BSN encoded in 9-digits, padded with leading 0 if needed. Example: 123456789 or 012345678.
BSN	urn:nl-eid-gdi:1.0:id:BSN urn:etoegang:1.12:EntityConcernedID:BSN	BSNk Encrypted Identity (EI) - BSN encrypted using BSNk polymorphic encryption. For notation see [BSNk.DEC], Encrypted structures
Pseudonym	urn:nl-eid-gdi:1.0:id:Pseudonym urn:etoegang:1.12:EntityConcernedID:PseudoID	BSNk Encrypted Pseudonym (EP) - Pseudonym is cryptografically derived from BSN or eIDAS UniquenessID using BSNk polymorphic encryption. This pseudonym is both persistent and recipient specific (pseudonym@DV). For notation see [BSNk.DEC], Encrypted structures
ETD Specific Pseudonym	urn:etoegang:1.13:EntityConcernedID:Pseudo	An ETD Specific Pseudonym is used to identify an EU that represents a Service Consumer . The pseudonym is specific for the DV , the represented (employer) and the authentication means used by the EU .

The following attributes may be supplied additionally, only through [ETD](#) (see <https://afsprakenstelsel.etoegang.nl/Startpagina/as/identificerende-kenmerken>)

§10.2 Attribute representation types

The table shows the allowed representationTypes in URN format that are supported by the [BVD \(BVD-OG\)](#) and can be found in the [Attribute Statement](#) of the [AuthN Response - Assertion](#) as a unencrypted with @name [Name](#)="urn:nl-eid-gdi:1.1:RepresentationType". See [attribute for legal representation](#)

representation-types	urn	Sector	description
Zorg_Volledig_Gezag_Kind	urn:nl-eid-gdi:1.1:RT:Zorg_Volledig_Gezag_Kind	health care	Specific Parental authority for children under 12 years old in healthcare
Curatele	urn:nl-eid-gdi:1.1:RT:WV_Curator	All	"Curatele" as registered at the "centraal curatele- en bewindregister (CCBR)"
Bewindvoering	urn:nl-eid-gdi:1.1:RT:WV_Bewindvoerder	All	"Bewindvoering" as registered at the "centraal curatele- en bewindregister (CCBR)"
Mentorschap	urn:nl-eid-gdi:1.1:RT:WV_Mentor	All	"Mentoring" as registered at the "centraal curatele- en bewindregister (CCBR)"

§10.3 EntityID Format

The format of value of the @entityID attribute is: urn:nl-eid-gdi:1.0:<ROLE>:<OIN>:entities:<index>

<OIN>

The OIN of the organization.

<ROLE>

Indication of the role of the entity:

- AD
- DV
- BVD
- LC
- RD

<index>

The <index> is a number with 4 positions between 0000 and 8999 that can be selected by the [Participant](#) to define different endpoints (in the [Metadata](#)). Numbers between 9000 and 9999 are reserved for test systems.

§10.4 Level of Assurance

The table shows the four Levels of Assurance supported by [ST-SAML](#) and the corresponding urn's which are used in the SAML messages.

LoA	urn
Basis	<code>http://eID.logius.nl/LoA/basic</code>
Midden	<code>http://eid.europa.eu/LoA/low</code>
Substantieel	<code>http://eid.europa.eu/LoA/substantial</code>
Hoog	<code>http://eid.europa.eu/LoA/high</code>

§A. Example SAML messages

This section is non-normative.

§A.1 Example - AuthnRequest

EXAMPLE 1: AuthnRequest

```
<?xml version="1.0" encoding="UTF-8"?>
<samlp:AuthnRequest AssertionConsumerServiceIndex="0" AttributeConsumingServiceIndex="1
  Destination="http://idp.example.com/request_authentication"
  ID="_56ae2ef7ff51845153d8960e5b73d45128ad6d62" IssueInstant="2021-0
  xmlns:ds="http://www.w3.org/2000/09/xmldsig#" xmlns:ec="http://www.
  xmlns:saml="urn:oasis:names:tc:SAML:2.0:assertion"
  xmlns:samlp="urn:oasis:names:tc:SAML:2.0:protocol">
  <saml:Issuer>urn:nl-eid-gdi:1.0:DV:000000099999999999001:entities:0000</saml:Issuer>
  <ds:Signature>
    <ds:SignedInfo>
      <ds:CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml-exc-c14
      <ds:SignatureMethod Algorithm="http://www.w3.org/2001/04/xmldsig-more#rsa-s
      <ds:Reference URI="#_56ae2ef7ff51845153d8960e5b73d45128ad6d62">
        <ds:Transforms>
          <ds:Transform Algorithm="http://www.w3.org/2000/09/xmldsig#envelope
          <ds:Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#">
            <ec:InclusiveNamespaces PrefixList="ds saml samlp xs"/>
          </ds:Transform>
        </ds:Transforms>
        <ds:DigestMethod Algorithm="http://www.w3.org/2001/04/xmldsig#sha256"/>
        <ds:DigestValue>...</ds:DigestValue>
      </ds:Reference>
    </ds:SignedInfo>
    <ds:SignatureValue>...</ds:SignatureValue>
  </ds:Signature>
  <ds:KeyInfo>
    <ds:KeyName>4492219ba557ce9e547a933d15ab87b14a69788d</ds:KeyName>
  </ds:KeyInfo>
</samlp:AuthnRequest>
```

§A.2 Example - AuthnRequest using Extensions

EXAMPLE 2: AuthnRequest using Extensions

```
<?xml version="1.0" encoding="UTF-8"?>
<samlp:AuthnRequest xmlns:ds="http://www.w3.org/2000/09/xmldsig#"
  xmlns:saml="urn:oasis:names:tc:SAML:2.0:assertion"
  xmlns:samlp="urn:oasis:names:tc:SAML:2.0:protocol"
  Destination="http://idp.example.com/request_authentication"
  ForceAuthn="false" ID="_d68fdd07cb64ca845317aa145969187c1514129b"
  IsPassive="false" IssueInstant="2021-04-15T14:20:38Z" Version="2.0"
  <saml:Issuer Format="urn:oasis:names:tc:SAML:2.0:nameid-format:entity">
    urn:n1-eid-gdi:1.0:DV:000000009999999999001:entities:0000
  </saml:Issuer>
  <ds:Signature Id="uuid5e7c2bf-0178-146b-8597-ef90aa0f4487">
    <ds:SignedInfo>
      <ds:CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml-exc-c14
      <ds:SignatureMethod Algorithm="http://www.w3.org/2001/04/xmldsig-more#rsa-s
      <ds:Reference URI="#_d68fdd07cb64ca845317aa145969187c1514129b">
        <ds:Transforms>
          <ds:Transform Algorithm="http://www.w3.org/2000/09/xmldsig#envelope
          <ds:Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#">
            <xc14n:InclusiveNamespaces xmlns:xc14n="http://www.w3.org/2001/
              PrefixList="samlp saml ds"></xc14n:I
          </ds:Transform>
        </ds:Transforms>
        <ds:DigestMethod Algorithm="http://www.w3.org/2001/04/xmldsig-more#sha256"></
        <ds:DigestValue>...</ds:DigestValue>
      </ds:Reference>
    </ds:SignedInfo>
    <ds:SignatureValue>...</ds:SignatureValue>
  </ds:Signature>
  <samlp:Extensions>
    <saml:Attribute Name="urn:n1-eid-gdi:1.0:ServiceUUID">
      <saml:AttributeValue>336fa5edb569-13fb-b3e4-8968-86c62aea</saml:AttributeVa
    </saml:Attribute>
    <saml:Attribute Name="urn:n1-eid-gdi:1.0:IntendedAudience">
      <saml:AttributeValue>urn:n1-eid-gdi:1.0:DV:000000009999999999001:entities:00
    </saml:Attribute>
  </samlp:Extensions>
</samlp:AuthnRequest>
```

§A.3 Example - AuthnRequest with Representation

EXAMPLE 3: AuthnRequest with Representation

```
<?xml version="1.0" encoding="UTF-8"?>
<samlp:AuthnRequest AssertionConsumerServiceIndex="0" AttributeConsumingServiceIndex="1
  Destination="http://idp.example.com/request_authentication"
  ID="_56ae2ef7ff51845153d8960e5b73d45128ad6d62" IssueInstant="2021-0
  xmlns:ds="http://www.w3.org/2000/09/xmldsig#" xmlns:ec="http://www.
  xmlns:saml="urn:oasis:names:tc:SAML:2.0:assertion"
  xmlns:samlp="urn:oasis:names:tc:SAML:2.0:protocol">
  <saml:Issuer>urn:nl-eid-gdi:1.0:DV:000000099999999999001:entities:0000</saml:Issuer>
  <ds:Signature>
    <ds:SignedInfo>
      <ds:CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml-exc-c14
      <ds:SignatureMethod Algorithm="http://www.w3.org/2001/04/xmldsig-more#rsa-s
      <ds:Reference URI="#_56ae2ef7ff51845153d8960e5b73d45128ad6d62">
        <ds:Transforms>
          <ds:Transform Algorithm="http://www.w3.org/2000/09/xmldsig#envelope
          <ds:Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#">
            <ec:InclusiveNamespaces PrefixList="ds saml samlp xs"/>
          </ds:Transform>
        </ds:Transforms>
        <ds:DigestMethod Algorithm="http://www.w3.org/2001/04/xmldsig-more#sha256"/>
        <ds:DigestValue>...</ds:DigestValue>
      </ds:Reference>
    </ds:SignedInfo>
    <ds:SignatureValue>...</ds:SignatureValue>
  </ds:Signature>
  <samlp:Scoping>
    <samlp:RequesterID>urn:nl-eid-gdi:1.0:BVD:00000004003214345001:entities:9000</s
  </samlp:Scoping>
</samlp:AuthnRequest>
```

§A.4 Example - ArtifactResponse with Legal Representation

EXAMPLE 4: ArtifactResponse with Legal Representation

```
<?xml version="1.0" encoding="UTF-8"?>
<soap11:Envelope xmlns:soap11="http://schemas.xmlsoap.org/soap/envelope/">
  <soap11:Body>
    <saml2p:ArtifactResponse xmlns:saml2p="urn:oasis:names:tc:SAML:2.0:protocol"
      ID="_0fb52522f6e41b750df938ef5ea50154"
      InResponseTo="_1ea090efda5655760b6a0c9dfa8884b66d47522"
      IssueInstant="2025-05-05T08:10:51.018Z" Version="2.0">
      <saml2:Issuer xmlns:saml2="urn:oasis:names:tc:SAML:2.0:assertion">
        urn:n1-eid-gdi:1.0:TD:00000004183317817000:entities:9000
      </saml2:Issuer>
      <ds:Signature xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
        <ds:SignedInfo>
          <ds:CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml
          <ds:SignatureMethod Algorithm="http://www.w3.org/2001/04/xmldsig-mo
          <ds:Reference URI="#_0fb52522f6e41b750df938ef5ea50154">
            <ds:Transforms>
              <ds:Transform Algorithm="http://www.w3.org/2000/09/xmldsig#
              <ds:Transform Algorithm="http://www.w3.org/2001/10/xml-exc-
            </ds:Transforms>
            <ds:DigestMethod Algorithm="http://www.w3.org/2001/04/xm1enc#sh
            <ds:DigestValue>...</ds:DigestValue>
          </ds:Reference>
        </ds:SignedInfo>
        <ds:SignatureValue>...</ds:SignatureValue>
        <ds:KeyInfo>
          <ds:KeyName>356b4241808341cc9ff6295a43b01d00daab27406ddcd3f708a0a37
        </ds:KeyInfo>
      </ds:Signature>
    <saml2p:Status>
      <saml2p:StatusCode Value="urn:oasis:names:tc:SAML:2.0:status:Success"/>
    </saml2p:Status>
    <saml2p:Response>
      Destination="sp.example.com"
      ID="_31fa010c6af1bc61583f22c84b3a2b0d" InResponseTo="_a658d2c5c7426"
      IssueInstant="2021-10-06T08:10:51.018Z" Version="2.0">
      <saml2:Issuer xmlns:saml2="urn:oasis:names:tc:SAML:2.0:assertion">
        urn:n1-eid-gdi:1.0:TD:00000004183317817000:entities:9000
      </saml2:Issuer>
      <saml2p:Status>
        <saml2p:StatusCode Value="urn:oasis:names:tc:SAML:2.0:status:Succes
      </saml2p:Status>
      <saml2:Assertion xmlns:saml2="urn:oasis:names:tc:SAML:2.0:assertion"
        ID="_2a9deaff3a95b2193e74dbad4a69dfbf" IssueInstant="2
        Version="2.0">
      <saml2:Issuer>urn:n1-eid-gdi:1.0:TD:00000004183317817000:entities:9
      <ds:Signature xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
        <ds:SignedInfo>
          <ds:CanonicalizationMethod Algorithm="http://www.w3.org/200
```

```

<ds:SignatureMethod Algorithm="http://www.w3.org/2001/04/xm
<ds:Reference URI="#_2a9deaff3a95b2193e74dbad4a69dfbf">
  <ds:Transforms>
    <ds:Transform Algorithm="http://www.w3.org/2000/09/
    <ds:Transform Algorithm="http://www.w3.org/2001/10/
  </ds:Transforms>
  <ds:DigestMethod Algorithm="http://www.w3.org/2001/04/x
  <ds:DigestValue>...</ds:DigestValue>
</ds:Reference>
</ds:SignedInfo>
<ds:SignatureValue>...</ds:SignatureValue>
<ds:KeyInfo>
  <ds:KeyName>356b4241808341cc9ff6295a43b01d00daab27406ddcd3f
</ds:KeyInfo>
</ds:Signature>
<saml2:Subject>
  <saml2:NameID Format="urn:oasis:names:tc:SAML:2.0:nameid-format
    45e376c5-78a7-4cdc-a27d-a7dd5056e786
  </saml2:NameID>
  <saml2:SubjectConfirmation Method="urn:oasis:names:tc:SAML:2.0:
    <saml2:SubjectConfirmationData InResponseTo="_a658d2c5c7426
      NotOnOrAfter="2021-10-06T08:
      Recipient="http://sp.example
    </saml2:SubjectConfirmation>
</saml2:Subject>
<saml2:Conditions NotBefore="2021-10-06T08:08:50.916Z" NotOnOrAfter
  <saml2:AudienceRestriction>
    <saml2:Audience>urn:n1-eid-gdi:1.0:DV:000000009999999999004:
  </saml2:AudienceRestriction>
</saml2:Conditions>
<saml2:Advice>
  <saml2:Assertion ID="_797775d153ac85fe682d1c89f668adc1" IssueIn
    Version="2.0" xmlns:saml2="urn:oasis:names:tc:
  <saml2:Issuer>urn:n1-eid-gdi:1.0:AD:00000000273813120000:ent
  <ds:Signature xmlns:ds="http://www.w3.org/2000/09/xmlsig#"
    <ds:SignedInfo>
      <ds:CanonicalizationMethod Algorithm="http://www.w3
      <ds:SignatureMethod Algorithm="http://www.w3.org/20
      <ds:Reference URI="#_797775d153ac85fe682d1c89f668ad
        <ds:Transforms>
          <ds:Transform
            Algorithm="http://www.w3.org/2000/0
          <ds:Transform Algorithm="http://www.w3.org/
        </ds:Transforms>
        <ds:DigestMethod Algorithm="http://www.w3.org/2
        <ds:DigestValue>...</ds:DigestValue>
      </ds:Reference>
    </ds:SignedInfo>
    <ds:SignatureValue>...</ds:SignatureValue>
    <ds:KeyInfo>
      <ds:KeyName>24b1a2189f8af57114df0b93120f88b1d9cd38a
    </ds:KeyName>
    </ds:KeyInfo>
  </ds:Signature>
<saml2:Subject>
  <saml2:NameID Format="urn:oasis:names:tc:SAML:2.0:namei

```

```

45e376c5-78a7-4cdc-a27d-a7dd5056e786
</saml2:NameID>
<saml2:SubjectConfirmation Method="urn:oasis:names:tc:S
  <saml2:SubjectConfirmationData
    InResponseTo="_a658d2c5c7426b11dfbdb1e30d4b
    NotOnOrAfter="2021-10-06T08:12:50.916Z"
    Recipient="http://sp.example.com"/>
  </saml2:SubjectConfirmation>
</saml2:Subject>
<saml2:Conditions NotBefore="2021-10-06T08:08:50.916Z"
  NotOnOrAfter="2021-10-06T08:12:50.916Z">
  <saml2:AudienceRestriction>
    <saml2:Audience>urn:n1-eid-gdi:1.0:DV:0000000999999
    </saml2:Audience>
  </saml2:AudienceRestriction>
</saml2:Conditions>
<saml2:AuthnStatement AuthnInstant="2021-10-06T08:10:51.029
  <saml2:AuthnContext>
    <saml2:AuthnContextClassRef>http://eid.logius.nl/Lo
    </saml2:AuthnContextClassRef>
  </saml2:AuthnContext>
</saml2:AuthnStatement>
<saml2:AttributeStatement>
  <saml2:Attribute Name="urn:n1-eid-gdi:1.0:ServiceUUID">
    <saml2:AttributeValue>375b1cb114b7-12e9-3534-16cc-4
  </saml2:Attribute>
  <saml2:Attribute Name="urn:n1-eid-gdi:1.0:ActingSubject
    <saml2:AttributeValue>
      <saml2:EncryptedID>
        <xenc:EncryptedData xmlns:xenc="http://www.
          Id="_e4ed5fc71f364184a4
          Type="http://www.w3.org
        <xenc:EncryptionMethod
          Algorithm="http://www.w3.org/20
          xmlns:xenc="http://www.w3.org/2
        <ds:KeyInfo xmlns:ds="http://www.w3.org
          <ds:RetrievalMethod
            Type="http://www.w3.org/200
            URI="#_0ceelf147ad7e995e77e
          </ds:KeyInfo>
        <xenc:CipherData xmlns:xenc="http://www
          <xenc:CipherValue>...</xenc:CipherV
        </xenc:CipherData>
      </xenc:EncryptedData>
    <xenc:EncryptedKey xmlns:xenc="http://www.w
      Id="_0ceelf147ad7e995e77
      Recipient="urn:n1-eid-gd
    <xenc:EncryptionMethod
      Algorithm="http://www.w3.org/20
      xmlns:xenc="http://www.w3.org/2
    <ds:DigestMethod xmlns:ds="http://w
      Algorithm="http://
    </xenc:EncryptionMethod>
    <ds:KeyInfo xmlns:ds="http://www.w3.org
      <ds:KeyName>1d0bc832d839df789eca8ba
    </ds:KeyInfo>

```



```

        <xenc:CipherData xmlns:xenc="http://www
            <xenc:CipherValue>...</xenc:CipherV
        </xenc:CipherData>
        <xenc:ReferenceList>
            <xenc:DataReference URI="#_e4ed5fc7
        </xenc:ReferenceList>
    </xenc:EncryptedKey>
        <xenc:EncryptedKey xmlns:xenc="http
            Id="_0cee1f147ad7e995e77
            Recipient="urn:n1-eid-gd
        <xenc:EncryptionMethod
            Algorithm="http://www.w3.org/20
            xmlns:xenc="http://www.w3.org/2
        <ds:DigestMethod xmlns:ds="http://w
            Algorithm="http://
        </xenc:EncryptionMethod>
        <ds:KeyInfo xmlns:ds="http://www.w3.org
            <ds:KeyName>2c0bc832d839df789eca8ba
        </ds:KeyInfo>
        <xenc:CipherData xmlns:xenc="http://www
            <xenc:CipherValue>...</xenc:CipherV
        </xenc:CipherData>
        <xenc:ReferenceList>
            <xenc:DataReference URI="#_e4ed5fc7
        </xenc:ReferenceList>
    </xenc:EncryptedKey>
</saml2:EncryptedID>
</saml2:AttributeValue>
</saml2:Attribute>
</saml2:AttributeStatement>
</saml2:Assertion>
<saml2:Assertion ID="_c7a79a0e92311f0d3d2dadc247a855f6" IssueIn
    Version="2.0" xmlns:saml2="urn:oasis:names:tc:
    <saml2:Issuer>urn:n1-eid-gdi:1.0:BVD:00000004003214345001:e
    <ds:Signature xmlns:ds="http://www.w3.org/2000/09/xmlsig#"
        <ds:SignedInfo>
            <ds:CanonicalizationMethod Algorithm="http://www.w3
            <ds:SignatureMethod Algorithm="http://www.w3.org/20
            <ds:Reference URI="#_c7a79a0e92311f0d3d2dadc247a855
                <ds:Transforms>
                    <ds:Transform
                        Algorithm="http://www.w3.org/2000/0
                    <ds:Transform Algorithm="http://www.w3.org/
                </ds:Transforms>
            <ds:DigestMethod Algorithm="http://www.w3.org/2
            <ds:DigestValue>...</ds:DigestValue>
        </ds:Reference>
    </ds:SignedInfo>
    <ds:SignatureValue>...</ds:SignatureValue>
    <ds:KeyInfo>
        <ds:KeyName>4202df88ba9faae2d2860a0d821d2bde10babcb0
    </ds:KeyName>
    </ds:KeyInfo>
</ds:Signature>
<saml2:Subject>
    <saml2:NameID Format="urn:oasis:names:tc:SAML:2.0:namei

```

```

45e376c5-78a7-4cdc-a27d-a7dd5056e786
</saml2:NameID>
<saml2:SubjectConfirmation Method="urn:oasis:names:tc:S
  <saml2:SubjectConfirmationData
    InResponseTo="_a658d2c5c7426b11dfbdb1e30d4b
    NotOnOrAfter="2021-10-06T08:12:50.916Z"
    Recipient="http://sp.example.com"/>
  </saml2:SubjectConfirmation>
</saml2:Subject>
<saml2:Conditions NotBefore="2021-10-06T08:08:50.916Z"
  NotOnOrAfter="2021-10-06T08:12:50.916Z">
  <saml2:AudienceRestriction>
    <saml2:Audience>urn:n1-eid-gdi:1.0:DV:0000000999999
    </saml2:Audience>
  </saml2:AudienceRestriction>
</saml2:Conditions>
<saml2:AuthnStatement AuthnInstant="2021-10-06T08:10:51.090
  <saml2:AuthnContext>
    <saml2:AuthnContextClassRef>http://eid.logius.nl/Lo
    </saml2:AuthnContextClassRef>
  </saml2:AuthnContext>
</saml2:AuthnStatement>
<saml2:AttributeStatement>
  <saml2:Attribute Name="urn:n1-eid-gdi:1.0:ServiceUUID">
    <saml2:AttributeValue>375b1cb114b7-12e9-3534-16cc-4
  </saml2:Attribute>
  <saml2:Attribute Name="urn:n1-eid-gdi:1.1:Represent
    <saml2:AttributeValue>urn:n1-eid-gdi:1.1:RT:Zorg_
  </saml2:Attribute>
  <saml2:Attribute Name="urn:n1-eid-gdi:1.0:ActingSubject
    <saml2:AttributeValue>
      <saml2:EncryptedID>
        <xenc:EncryptedData xmlns:xenc="http://www.
          Id="_d4eb5b0632d3883739
          Type="http://www.w3.org
        <xenc:EncryptionMethod
          Algorithm="http://www.w3.org/20
          xmlns:xenc="http://www.w3.org/2
        <ds:KeyInfo xmlns:ds="http://www.w3.org
          <ds:RetrievalMethod
            Type="http://www.w3.org/200
            URI="#_720276d2e729cdec688
          </ds:KeyInfo>
        <xenc:CipherData xmlns:xenc="http://www
          <xenc:CipherValue>...</xenc:CipherV
        </xenc:CipherData>
      </xenc:EncryptedData>
    <xenc:EncryptedKey xmlns:xenc="http://www.w
      Id="_720276d2e729cdec68
      Recipient="urn:n1-eid-gd
    <xenc:EncryptionMethod
      Algorithm="http://www.w3.org/20
      xmlns:xenc="http://www.w3.org/2
    <ds:DigestMethod xmlns:ds="http://w
      Algorithm="http://
    </xenc:EncryptionMethod>

```

```

        <ds:KeyInfo xmlns:ds="http://www.w3.org
            <ds:KeyName>1d0bc832d839df789eca8ba
        </ds:KeyInfo>
        <xenc:CipherData xmlns:xenc="http://www
            <xenc:CipherValue>...</xenc:CipherV
        </xenc:CipherData>
        <xenc:ReferenceList>
            <xenc:DataReference URI="#_d4eb5b06
        </xenc:ReferenceList>
        </xenc:EncryptedKey>
    </saml2:EncryptedID>
</saml2:AttributeValue>
</saml2:Attribute>
<saml2:Attribute Name="urn:n1-eid-gdi:1.0:LegalSubjectI
    <saml2:AttributeValue>
        <saml2:EncryptedID>
            <xenc:EncryptedData xmlns:xenc="http://www.
                Id="_0fbab7451567b50413
                Type="http://www.w3.org
            <xenc:EncryptionMethod
                Algorithm="http://www.w3.org/20
                xmlns:xenc="http://www.w3.org/2
            <ds:KeyInfo xmlns:ds="http://www.w3.org
                <ds:RetrievalMethod
                    Type="http://www.w3.org/200
                    URI="#_2cab7ef2667689c6064d
            </ds:KeyInfo>
            <xenc:CipherData xmlns:xenc="http://www
                <xenc:CipherValue>...</xenc:CipherV
            </xenc:CipherData>
        </xenc:EncryptedData>
        <xenc:EncryptedKey xmlns:xenc="http://www.w
            Id="_2cab7ef2667689c6064
            Recipient="urn:n1-eid-gd
        <xenc:EncryptionMethod
            Algorithm="http://www.w3.org/20
            xmlns:xenc="http://www.w3.org/2
            <ds:DigestMethod xmlns:ds="http://w
                Algorithm="http://
        </xenc:EncryptionMethod>
        <ds:KeyInfo xmlns:ds="http://www.w3.org
            <ds:KeyName>1d0bc832d839df789eca8ba
        </ds:KeyInfo>
        <xenc:CipherData xmlns:xenc="http://www
            <xenc:CipherValue>...</xenc:CipherV
        </xenc:CipherData>
        <xenc:ReferenceList>
            <xenc:DataReference URI="#_0fbab745
        </xenc:ReferenceList>
        </xenc:EncryptedKey>
    </saml2:EncryptedID>
</saml2:AttributeValue>
</saml2:Attribute>
</saml2:AttributeStatement>
</saml2:Assertion>
</saml2:Advice>

```

```

<saml2:AuthnStatement AuthnInstant="2021-10-06T08:10:51.018Z" Sessi
  <saml2:AuthnContext>
    <saml2:AuthnContextClassRef>http://eid.logius.nl/LoA/basic<
    <saml2:AuthenticatingAuthority>urn:nl-eid-gdi:1.0:AD:000000
    </saml2:AuthenticatingAuthority>
    <saml2:AuthenticatingAuthority>urn:nl-eid-gdi:1.0:BVD:000000
    </saml2:AuthenticatingAuthority>
  </saml2:AuthnContext>
</saml2:AuthnStatement>
<saml2:AttributeStatement>
  <saml2:Attribute Name="urn:nl-eid-gdi:1.0:ServiceUUID">
    <saml2:AttributeValue>375b1cb114b7-12e9-3534-16cc-4d8997b0<
  </saml2:Attribute>
<saml2:Attribute Name="urn:nl-eid-gdi:1.1:RepresentationType">
<saml2:AttributeValue>urn:nl-eid-gdi:1.1:RT:Zorg_Volledig_Gezag_Kind</s
</saml2:Attribute>
  <saml2:Attribute Name="urn:nl-eid-gdi:1.0:ActingSubjectID">
    <saml2:AttributeValue>
      <saml2:EncryptedID>
        <xenc:EncryptedData xmlns:xenc="http://www.w3.org/2
          Id="_c108a849ffb239e73ac6083348
          Type="http://www.w3.org/2001/04
        <xenc:EncryptionMethod Algorithm="http://www.w3
          xmlns:xenc="http://www.w
        <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09
          <ds:RetrievalMethod Type="http://www.w3.org
            URI="#_df56cc944ecbb3a0
          </ds:KeyInfo>
        <xenc:CipherData xmlns:xenc="http://www.w3.org/
          <xenc:CipherValue>...</xenc:CipherValue>
        </xenc:CipherData>
      </xenc:EncryptedData>
      <xenc:EncryptedKey xmlns:xenc="http://www.w3.org/20
        Id="_df56cc944ecbb3a06fe5d0a0d45
        Recipient="urn:nl-eid-gdi:1.0:DV
      <xenc:EncryptionMethod
        Algorithm="http://www.w3.org/2001/04/xm
        xmlns:xenc="http://www.w3.org/2001/04/x
      <ds:DigestMethod xmlns:ds="http://www.w3.or
        Algorithm="http://www.w3.o
      </xenc:EncryptionMethod>
      <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09
        <ds:KeyName>1d0bc832d839df789eca8bae611c3ad
      </ds:KeyInfo>
      <xenc:CipherData xmlns:xenc="http://www.w3.org/
        <xenc:CipherValue>...</xenc:CipherValue>
      </xenc:CipherData>
      <xenc:ReferenceList>
        <xenc:DataReference URI="#_c108a849ffb239e7
      </xenc:ReferenceList>
    </xenc:EncryptedKey>
  </saml2:EncryptedID>
</saml2:AttributeValue>
</saml2:Attribute>
<saml2:Attribute Name="urn:nl-eid-gdi:1.0:LegalSubjectID">
  <saml2:AttributeValue>

```

```

<saml2:EncryptedID>
  <xenc:EncryptedData xmlns:xenc="http://www.w3.org/2001/04/xmldsig-core-schema#"
    Id="_5d50f7898d8afda532502d7f82"
    Type="http://www.w3.org/2001/04/xmldsig-core-schema#EncryptedData"
    <xenc:EncryptionMethod Algorithm="http://www.w3.org/2001/04/xmldsig-core-schema#rsaOAEP"
      xmlns:xenc="http://www.w3.org/2001/04/xmldsig-core-schema#" />
    <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09/xmldsig-core-schema#"
      <ds:RetrievalMethod Type="http://www.w3.org/2000/09/xmldsig-core-schema#uri"
        URI="#_ea31225223bb330e" />
      />
    <xenc:CipherData xmlns:xenc="http://www.w3.org/2001/04/xmldsig-core-schema#"
      <xenc:CipherValue>...</xenc:CipherValue>
    </xenc:CipherData>
  </xenc:EncryptedData>
  <xenc:EncryptedKey xmlns:xenc="http://www.w3.org/2001/04/xmldsig-core-schema#"
    Id="_ea31225223bb330ed5fe42bb55f"
    Recipient="urn:n1-eid-gdi:1.0:DV"
    <xenc:EncryptionMethod Algorithm="http://www.w3.org/2001/04/xmldsig-core-schema#rsaOAEP"
      xmlns:xenc="http://www.w3.org/2001/04/xmldsig-core-schema#" />
    <ds:DigestMethod xmlns:ds="http://www.w3.org/2000/09/xmldsig-core-schema#"
      Algorithm="http://www.w3.org/2000/09/xmldsig-core-schema#sha1" />
    </xenc:EncryptionMethod>
    <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09/xmldsig-core-schema#"
      <ds:KeyName>1d0bc832d839df789eca8bae611c3ad</ds:KeyName>
    </ds:KeyInfo>
    <xenc:CipherData xmlns:xenc="http://www.w3.org/2001/04/xmldsig-core-schema#"
      <xenc:CipherValue>...</xenc:CipherValue>
    </xenc:CipherData>
    <xenc:ReferenceList xmlns:xenc="http://www.w3.org/2001/04/xmldsig-core-schema#"
      <xenc:DataReference URI="#_5d50f7898d8afda532502d7f82" />
    </xenc:ReferenceList>
  </xenc:EncryptedKey>
</saml2:EncryptedID>
</saml2:AttributeValue>
</saml2:Attribute>
</saml2:AttributeStatement>
</saml2:Assertion>
</saml2p:Response>
</saml2p:ArtifactResponse>
</soap11:Body>
</soap11:Envelope>

```

§A.5 Example - ArtifactResolve

EXAMPLE 5: ArtifactResolve

```
<?xml version="1.0" encoding="UTF-8"?>
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
  <soapenv:Body>
    <samlp:ArtifactResolve xmlns:samlp="urn:oasis:names:tc:SAML:2.0:protocol"
      xmlns:saml="urn:oasis:names:tc:SAML:2.0:assertion"
      xmlns:ds="http://www.w3.org/2000/09/xmldsig#"
      xmlns:ec="http://www.w3.org/2001/10/xml-exc-c14n#"
      ID="_f0c06d3728f5da98c417b5add105d3c07cc3c868" Version="
      IssueInstant="2021-06-03T10:38:38Z"
      Destination="http://idp.example.com/resolve_artifact">
      <saml:Issuer>urn:nl-eid-gdi:1.0:DV:00000009999999999001:entities:0000</saml
    <ds:Signature>
      <ds:SignedInfo>
        <ds:CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml
        <ds:SignatureMethod Algorithm="http://www.w3.org/2001/04/xmldsig-mo
        <ds:Reference URI="#_f0c06d3728f5da98c417b5add105d3c07cc3c868">
          <ds:Transforms>
            <ds:Transform Algorithm="http://www.w3.org/2000/09/xmldsig#
            <ds:Transform Algorithm="http://www.w3.org/2001/10/xml-exc-
              <ec:InclusiveNamespaces PrefixList="ds saml samlp xs"/>
            </ds:Transform>
          </ds:Transforms>
          <ds:DigestMethod Algorithm="http://www.w3.org/2001/04/xmlenc#sh
          <ds:DigestValue>...</ds:DigestValue>
        </ds:Reference>
      </ds:SignedInfo>
      <ds:SignatureValue>...</ds:SignatureValue>
      <ds:KeyInfo>
        <ds:KeyName>4492219ba557ce9e547a933d15ab87b14a69788d</ds:KeyName>
      </ds:KeyInfo>
    </ds:Signature>
    <samlp:Artifact>AAQAAHZHHN7zNfV4yhPfX5thN0sFe10xr4B3crRVEmPn4m3DE2V GisdFYs
  </samlp:ArtifactResolve>
</soapenv:Body>
</soapenv:Envelope>
```

§A.6 Example - ArtifactResponse

EXAMPLE 6: ArtifactResponse

```
<?xml version="1.0" encoding="UTF-8"?>
<soap11:Envelope xmlns:soap11="http://schemas.xmlsoap.org/soap/envelope/">
  <soap11:Body>
    <saml2p:ArtifactResponse xmlns:saml2p="urn:oasis:names:tc:SAML:2.0:protocol"
      ID="_4d4d3e6984b2b2c036d7ee55d424ac78"
      InResponseTo="_8ecc43a04fc541f850fb66eb7259232b2d55627"
      IssueInstant="2021-10-06T08:09:50.226Z" Version="2.0">
      <saml2:Issuer xmlns:saml2="urn:oasis:names:tc:SAML:2.0:assertion">
        urn:n1-eid-gdi:1.0:TD:00000004183317817000:entities:9000
      </saml2:Issuer>
      <ds:Signature xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
        <ds:SignedInfo>
          <ds:CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml
          <ds:SignatureMethod Algorithm="http://www.w3.org/2001/04/xmldsig-mo
          <ds:Reference URI="#_4d4d3e6984b2b2c036d7ee55d424ac78">
            <ds:Transforms>
              <ds:Transform Algorithm="http://www.w3.org/2000/09/xmldsig#
              <ds:Transform Algorithm="http://www.w3.org/2001/10/xml-exc-
            </ds:Transforms>
            <ds:DigestMethod Algorithm="http://www.w3.org/2001/04/xm1enc#sh
            <ds:DigestValue>...</ds:DigestValue>
          </ds:Reference>
        </ds:SignedInfo>
        <ds:SignatureValue>...</ds:SignatureValue>
        <ds:KeyInfo>
          <ds:KeyName>356b4241808341cc9ff6295a43b01d00daab27406ddcd3f708a0a37
        </ds:KeyInfo>
      </ds:Signature>
    <saml2p:Status>
      <saml2p:StatusCode Value="urn:oasis:names:tc:SAML:2.0:status:Success"/>
    </saml2p:Status>
    <saml2p:Response>
      Destination="http://sp.example.com"
      ID="_99e95c51026d2af9914a2269a39519c5" InResponseTo="_e1234e91b1475"
      IssueInstant="2021-10-06T08:09:50.229Z" Version="2.0">
      <saml2:Issuer xmlns:saml2="urn:oasis:names:tc:SAML:2.0:assertion">
        urn:n1-eid-gdi:1.0:TD:00000004183317817000:entities:9000
      </saml2:Issuer>
      <saml2p:Status>
        <saml2p:StatusCode Value="urn:oasis:names:tc:SAML:2.0:status:Succes
      </saml2p:Status>
      <saml2:Assertion xmlns:saml2="urn:oasis:names:tc:SAML:2.0:assertion"
        ID="_12bb5ba7a77b6e09983fa26af000cfac" IssueInstant="2
        Version="2.0">
        <saml2:Issuer>urn:n1-eid-gdi:1.0:TD:00000004183317817000:entities:9
        <ds:Signature xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
          <ds:SignedInfo>
            <ds:CanonicalizationMethod Algorithm="http://www.w3.org/200
```

```

<ds:SignatureMethod Algorithm="http://www.w3.org/2001/04/xm
<ds:Reference URI="#_12bb5ba7a77b6e09983fa26af000cfac">
  <ds:Transforms>
    <ds:Transform Algorithm="http://www.w3.org/2000/09/
    <ds:Transform Algorithm="http://www.w3.org/2001/10/
  </ds:Transforms>
  <ds:DigestMethod Algorithm="http://www.w3.org/2001/04/x
  <ds:DigestValue>...</ds:DigestValue>
</ds:Reference>
</ds:SignedInfo>
<ds:SignatureValue>...</ds:SignatureValue>
<ds:KeyInfo>
  <ds:KeyName>356b4241808341cc9ff6295a43b01d00daab27406ddcd3f
</ds:KeyInfo>
</ds:Signature>
<saml2:Subject>
  <saml2:NameID Format="urn:oasis:names:tc:SAML:2.0:nameid-format
    6cdd6d85-a822-45cf-98f2-87792ab4c930
  </saml2:NameID>
  <saml2:SubjectConfirmation Method="urn:oasis:names:tc:SAML:2.0:
    <saml2:SubjectConfirmationData InResponseTo="_e1234e91b1475
      NotOnOrAfter="2021-10-06T08:
      Recipient="http://sp.example
    </saml2:SubjectConfirmation>
</saml2:Subject>
<saml2:Conditions NotBefore="2021-10-06T08:07:48.953Z" NotOnOrAfter
  <saml2:AudienceRestriction>
    <saml2:Audience>urn:nl-eid-gdi:1.0:DV:000000009999999999004:
  </saml2:AudienceRestriction>
</saml2:Conditions>
<saml2:Advice>
  <saml2:Assertion ID="_8de0f8271f4938285bfb6f66541a3b33" IssueIn
    Version="2.0" xmlns:saml2="urn:oasis:names:tc:
  <saml2:Issuer>urn:nl-eid-gdi:1.0:AD:00000000273813120000:ent
  <ds:Signature xmlns:ds="http://www.w3.org/2000/09/xmlsig#"
    <ds:SignedInfo>
      <ds:CanonicalizationMethod Algorithm="http://www.w3
      <ds:SignatureMethod Algorithm="http://www.w3.org/20
      <ds:Reference URI="#_8de0f8271f4938285bfb6f66541a3b
        <ds:Transforms>
          <ds:Transform
            Algorithm="http://www.w3.org/2000/0
          <ds:Transform Algorithm="http://www.w3.org/
        </ds:Transforms>
        <ds:DigestMethod Algorithm="http://www.w3.org/2
        <ds:DigestValue>...</ds:DigestValue>
      </ds:Reference>
    </ds:SignedInfo>
    <ds:SignatureValue>...</ds:SignatureValue>
    <ds:KeyInfo>
      <ds:KeyName>24b1a2189f8af57114df0b93120f88b1d9cd38a
    </ds:KeyName>
    </ds:KeyInfo>
  </ds:Signature>
<saml2:Subject>
  <saml2:NameID Format="urn:oasis:names:tc:SAML:2.0:namei

```



```
6cdd6d85-a822-45cf-98f2-87792ab4c930
</saml2:NameID>
<saml2:SubjectConfirmation Method="urn:oasis:names:tc:S
  <saml2:SubjectConfirmationData
    InResponseTo="_e1234e91b14755343ff8c69c046c
    NotOnOrAfter="2021-10-06T08:11:48.953Z"
    Recipient="http://sp.example.com"/>
  </saml2:SubjectConfirmation>
</saml2:Subject>
<saml2:Conditions NotBefore="2021-10-06T08:07:48.953Z"
  NotOnOrAfter="2021-10-06T08:11:48.953Z">
  <saml2:AudienceRestriction>
    <saml2:Audience>urn:nl-eid-gdi:1.0:DV:0000000999999
    </saml2:Audience>
  </saml2:AudienceRestriction>
</saml2:Conditions>
<saml2:AuthnStatement AuthnInstant="2021-10-06T08:09:50.300
  <saml2:AuthnContext>
    <saml2:AuthnContextClassRef>http://eid.logius.nl/Lo
    </saml2:AuthnContextClassRef>
  </saml2:AuthnContext>
</saml2:AuthnStatement>
<saml2:AttributeStatement>
  <saml2:Attribute Name="urn:nl-eid-gdi:1.0:ServiceUUID">
    <saml2:AttributeValue>375b1cb114b7-12e9-3534-16cc-4
  </saml2:Attribute>
  <saml2:Attribute Name="urn:nl-eid-gdi:1.0:ActingSubject
    <saml2:AttributeValue>
      <saml2:EncryptedID>
        <xenc:EncryptedData xmlns:xenc="http://www.
          Id="_d0d48b29e94d76c6a0
          Type="http://www.w3.org
        <xenc:EncryptionMethod
          Algorithm="http://www.w3.org/20
          xmlns:xenc="http://www.w3.org/2
        <ds:KeyInfo xmlns:ds="http://www.w3.org
          <ds:RetrievalMethod
            Type="http://www.w3.org/200
            URI="#_ab71ea3bafb606b8a89c
          </ds:KeyInfo>
        <xenc:CipherData xmlns:xenc="http://www
          <xenc:CipherValue>
            5q5RNYI9w79gCyq78PC8Pd3IY7GPaW3
          </xenc:CipherValue>
        </xenc:CipherData>
      </xenc:EncryptedData>
    <xenc:EncryptedKey xmlns:xenc="http://www.w
      Id="_ab71ea3bafb606b8a89
      Recipient="urn:nl-eid-gd
    <xenc:EncryptionMethod
      Algorithm="http://www.w3.org/20
      xmlns:xenc="http://www.w3.org/2
    <ds:DigestMethod xmlns:ds="http://w
      Algorithm="http://
    </xenc:EncryptionMethod>
    <ds:KeyInfo xmlns:ds="http://www.w3.org
```

```

        <ds:KeyName>1d0bc832d839df789eca8ba
    </ds:KeyInfo>
    <xenc:CipherData xmlns:xenc="http://www
        <xenc:CipherValue>
            YoXfK3S0PgipqMg8bvkQ2hD0Wwp6sbw
        </xenc:CipherValue>
    </xenc:CipherData>
    <xenc:ReferenceList>
        <xenc:DataReference URI="#_d0d48b29
    </xenc:ReferenceList>
    </xenc:EncryptedKey>
</saml2:EncryptedID>
</saml2:AttributeValue>
</saml2:Attribute>
</saml2:AttributeStatement>
</saml2:Assertion>
</saml2:Advice>
<saml2:AuthnStatement AuthnInstant="2021-10-06T08:09:50.236Z" Sessi
    <saml2:AuthnContext>
        <saml2:AuthnContextClassRef>http://eid.logius.nl/LoA/basic<
        <saml2:AuthenticatingAuthority>urn:nl-eid-gdi:1.0:AD:000000
        </saml2:AuthenticatingAuthority>
    </saml2:AuthnContext>
</saml2:AuthnStatement>
<saml2:AttributeStatement>
    <saml2:Attribute Name="urn:nl-eid-gdi:1.0:ServiceUUID">
        <saml2:AttributeValue>375b1cb114b7-12e9-3534-16cc-4d8997b0<
    </saml2:Attribute>
    <saml2:Attribute Name="urn:nl-eid-gdi:1.0:ActingSubjectID">
        <saml2:AttributeValue>
            <saml2:EncryptedID>
                <xenc:EncryptedData xmlns:xenc="http://www.w3.org/2
                    Id="_91c893ebalc1f87099c1d5a10b
                    Type="http://www.w3.org/2001/04
                <xenc:EncryptionMethod Algorithm="http://www.w3
                    xmlns:xenc="http://www.w
                <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09
                    <ds:RetrievalMethod Type="http://www.w3.org
                        URI="#_449673558dd0810e
                    </ds:KeyInfo>
                <xenc:CipherData xmlns:xenc="http://www.w3.org/
                    <xenc:CipherValue>...</xenc:CipherValue>
                </xenc:CipherData>
            </xenc:EncryptedData>
            <xenc:EncryptedKey xmlns:xenc="http://www.w3.org/20
                Id="_449673558dd0810e91009297f56
                Recipient="urn:nl-eid-gdi:1.0:DV
            <xenc:EncryptionMethod
                Algorithm="http://www.w3.org/2001/04/xm
                xmlns:xenc="http://www.w3.org/2001/04/x
            <ds:DigestMethod xmlns:ds="http://www.w3.or
                Algorithm="http://www.w3.o
            </xenc:EncryptionMethod>
            <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09
                <ds:KeyName>1d0bc832d839df789eca8bae611c3ad
            </ds:KeyInfo>

```

```
<xenc:CipherData xmlns:xenc="http://www.w3.org/
  <xenc:CipherValue>...</xenc:CipherValue>
</xenc:CipherData>
<xenc:ReferenceList>
  <xenc:DataReference URI="#_91c893eba1c1f870
</xenc:ReferenceList>
</xenc:EncryptedKey>
</saml2:EncryptedID>
</saml2:AttributeValue>
</saml2:Attribute>
</saml2:AttributeStatement>
</saml2:Assertion>
</saml2p:Response>
</saml2p:ArtifactResponse>
</soap11:Body>
</soap11:Envelope>
```

§A.7 Example - ArtifactResponse with Representation

EXAMPLE 7: ArtifactResponse with Representation

```
<?xml version="1.0" encoding="UTF-8"?>
<soap11:Envelope xmlns:soap11="http://schemas.xmlsoap.org/soap/envelope/">
  <soap11:Body>
    <saml2p:ArtifactResponse xmlns:saml2p="urn:oasis:names:tc:SAML:2.0:protocol"
      ID="_0fb52522f6e41b750df938ef5ea50154"
      InResponseTo="_1ea090efda5655760b6a0c9dfa8884b66d47522"
      IssueInstant="2021-10-06T08:10:51.018Z" Version="2.0">
      <saml2:Issuer xmlns:saml2="urn:oasis:names:tc:SAML:2.0:assertion">
        urn:nl-eid-gdi:1.0:TD:00000004183317817000:entities:9000
      </saml2:Issuer>
      <ds:Signature xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
        <ds:SignedInfo>
          <ds:CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml
          <ds:SignatureMethod Algorithm="http://www.w3.org/2001/04/xmldsig-mo
          <ds:Reference URI="#_0fb52522f6e41b750df938ef5ea50154">
            <ds:Transforms>
              <ds:Transform Algorithm="http://www.w3.org/2000/09/xmldsig#
              <ds:Transform Algorithm="http://www.w3.org/2001/10/xml-exc-
            </ds:Transforms>
            <ds:DigestMethod Algorithm="http://www.w3.org/2001/04/xmlesc#sh
            <ds:DigestValue>...</ds:DigestValue>
          </ds:Reference>
        </ds:SignedInfo>
        <ds:SignatureValue>...</ds:SignatureValue>
        <ds:KeyInfo>
          <ds:KeyName>356b4241808341cc9ff6295a43b01d00daab27406ddcd3f708a0a37
        </ds:KeyInfo>
      </ds:Signature>
    <saml2p:Status>
      <saml2p:StatusCode Value="urn:oasis:names:tc:SAML:2.0:status:Success"/>
    </saml2p:Status>
    <saml2p:Response>
      Destination="sp.example.com"
      ID="_31fa010c6af1bc61583f22c84b3a2b0d" InResponseTo="_a658d2c5c7426"
      IssueInstant="2021-10-06T08:10:51.018Z" Version="2.0">
      <saml2:Issuer xmlns:saml2="urn:oasis:names:tc:SAML:2.0:assertion">
        urn:nl-eid-gdi:1.0:TD:00000004183317817000:entities:9000
      </saml2:Issuer>
      <saml2p:Status>
        <saml2p:StatusCode Value="urn:oasis:names:tc:SAML:2.0:status:Succes
      </saml2p:Status>
      <saml2:Assertion xmlns:saml2="urn:oasis:names:tc:SAML:2.0:assertion"
        ID="_2a9deaff3a95b2193e74dbad4a69dfbf" IssueInstant="2
        Version="2.0">
        <saml2:Issuer>urn:nl-eid-gdi:1.0:TD:00000004183317817000:entities:9
        <ds:Signature xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
          <ds:SignedInfo>
            <ds:CanonicalizationMethod Algorithm="http://www.w3.org/200
```

```

<ds:SignatureMethod Algorithm="http://www.w3.org/2001/04/xm
<ds:Reference URI="#_2a9deaff3a95b2193e74dbad4a69dfbf">
  <ds:Transforms>
    <ds:Transform Algorithm="http://www.w3.org/2000/09/
    <ds:Transform Algorithm="http://www.w3.org/2001/10/
  </ds:Transforms>
  <ds:DigestMethod Algorithm="http://www.w3.org/2001/04/x
  <ds:DigestValue>...</ds:DigestValue>
</ds:Reference>
</ds:SignedInfo>
<ds:SignatureValue>...</ds:SignatureValue>
<ds:KeyInfo>
  <ds:KeyName>356b4241808341cc9ff6295a43b01d00daab27406ddcd3f
</ds:KeyInfo>
</ds:Signature>
<saml2:Subject>
  <saml2:NameID Format="urn:oasis:names:tc:SAML:2.0:nameid-format
    45e376c5-78a7-4cdc-a27d-a7dd5056e786
  </saml2:NameID>
  <saml2:SubjectConfirmation Method="urn:oasis:names:tc:SAML:2.0:
    <saml2:SubjectConfirmationData InResponseTo="_a658d2c5c7426
      NotOnOrAfter="2021-10-06T08:
      Recipient="http://sp.example
    </saml2:SubjectConfirmation>
</saml2:Subject>
<saml2:Conditions NotBefore="2021-10-06T08:08:50.916Z" NotOnOrAfter
  <saml2:AudienceRestriction>
    <saml2:Audience>urn:nl-eid-gdi:1.0:DV:000000009999999999004:
  </saml2:AudienceRestriction>
</saml2:Conditions>
<saml2:Advice>
  <saml2:Assertion ID="_797775d153ac85fe682d1c89f668adc1" IssueIn
    Version="2.0" xmlns:saml2="urn:oasis:names:tc:
  <saml2:Issuer>urn:nl-eid-gdi:1.0:AD:00000000273813120000:ent
  <ds:Signature xmlns:ds="http://www.w3.org/2000/09/xmlsig#"
    <ds:SignedInfo>
      <ds:CanonicalizationMethod Algorithm="http://www.w3
      <ds:SignatureMethod Algorithm="http://www.w3.org/20
      <ds:Reference URI="#_797775d153ac85fe682d1c89f668ad
        <ds:Transforms>
          <ds:Transform
            Algorithm="http://www.w3.org/2000/0
          <ds:Transform Algorithm="http://www.w3.org/
        </ds:Transforms>
        <ds:DigestMethod Algorithm="http://www.w3.org/2
        <ds:DigestValue>...</ds:DigestValue>
      </ds:Reference>
    </ds:SignedInfo>
    <ds:SignatureValue>...</ds:SignatureValue>
    <ds:KeyInfo>
      <ds:KeyName>24b1a2189f8af57114df0b93120f88b1d9cd38a
    </ds:KeyName>
    </ds:KeyInfo>
  </ds:Signature>
<saml2:Subject>
  <saml2:NameID Format="urn:oasis:names:tc:SAML:2.0:namei

```

```

45e376c5-78a7-4cdc-a27d-a7dd5056e786
</saml2:NameID>
<saml2:SubjectConfirmation Method="urn:oasis:names:tc:S
  <saml2:SubjectConfirmationData
    InResponseTo="_a658d2c5c7426b11dfbdb1e30d4b
    NotOnOrAfter="2021-10-06T08:12:50.916Z"
    Recipient="http://sp.example.com"/>
  </saml2:SubjectConfirmation>
</saml2:Subject>
<saml2:Conditions NotBefore="2021-10-06T08:08:50.916Z"
  NotOnOrAfter="2021-10-06T08:12:50.916Z">
  <saml2:AudienceRestriction>
    <saml2:Audience>urn:n1-eid-gdi:1.0:DV:0000000999999
    </saml2:Audience>
  </saml2:AudienceRestriction>
</saml2:Conditions>
<saml2:AuthnStatement AuthnInstant="2021-10-06T08:10:51.029
  <saml2:AuthnContext>
    <saml2:AuthnContextClassRef>http://eid.logius.nl/Lo
    </saml2:AuthnContextClassRef>
  </saml2:AuthnContext>
</saml2:AuthnStatement>
<saml2:AttributeStatement>
  <saml2:Attribute Name="urn:n1-eid-gdi:1.0:ServiceUUID">
    <saml2:AttributeValue>375b1cb114b7-12e9-3534-16cc-4
  </saml2:Attribute>
  <saml2:Attribute Name="urn:n1-eid-gdi:1.1:Representatio
    <saml2:AttributeValue>0G0-11</saml2:AttributeValue>
  </saml2:Attribute>
  <saml2:Attribute Name="urn:n1-eid-gdi:1.0:ActingSubject
    <saml2:AttributeValue>
      <saml2:EncryptedID>
        <xenc:EncryptedData xmlns:xenc="http://www.
          Id="_e4ed5fc71f364184a4
          Type="http://www.w3.org
        <xenc:EncryptionMethod
          Algorithm="http://www.w3.org/20
          xmlns:xenc="http://www.w3.org/2
        <ds:KeyInfo xmlns:ds="http://www.w3.org
          <ds:RetrievalMethod
            Type="http://www.w3.org/200
            URI="#_0cee1f147ad7e995e77e
          </ds:KeyInfo>
        <xenc:CipherData xmlns:xenc="http://www
          <xenc:CipherValue>...</xenc:CipherV
        </xenc:CipherData>
      </xenc:EncryptedData>
    <xenc:EncryptedKey xmlns:xenc="http://www.w
      Id="_0cee1f147ad7e995e77
      Recipient="urn:n1-eid-gd
    <xenc:EncryptionMethod
      Algorithm="http://www.w3.org/20
      xmlns:xenc="http://www.w3.org/2
    <ds:DigestMethod xmlns:ds="http://w
      Algorithm="http://
    </xenc:EncryptionMethod>

```

```

        <ds:KeyInfo xmlns:ds="http://www.w3.org
            <ds:KeyName>1d0bc832d839df789eca8ba
        </ds:KeyInfo>
        <xenc:CipherData xmlns:xenc="http://www
            <xenc:CipherValue>...</xenc:CipherV
        </xenc:CipherData>
        <xenc:ReferenceList>
            <xenc:DataReference URI="#_e4ed5fc7
        </xenc:ReferenceList>
        </xenc:EncryptedKey>
    </saml2:EncryptedID>
</saml2:AttributeValue>
</saml2:Attribute>
<saml2:Attribute Name="urn:n1-eid-gdi:1.0:LegalSubjectI
    <saml2:AttributeValue>
        <saml2:EncryptedID>
            <xenc:EncryptedData xmlns:xenc="http://www.
                Id="_46e926d560129ac377
                Type="http://www.w3.org
            <xenc:EncryptionMethod
                Algorithm="http://www.w3.org/20
                xmlns:xenc="http://www.w3.org/2
            <ds:KeyInfo xmlns:ds="http://www.w3.org
                <ds:RetrievalMethod
                    Type="http://www.w3.org/200
                    URI="#_0d819bc6f2168e97c83c
            </ds:KeyInfo>
            <xenc:CipherData xmlns:xenc="http://www
                <xenc:CipherValue>...</xenc:CipherV
            </xenc:CipherData>
        </xenc:EncryptedData>
        <xenc:EncryptedKey xmlns:xenc="http://www.w
            Id="_0d819bc6f2168e97c83
            Recipient="urn:n1-eid-gd
        <xenc:EncryptionMethod
            Algorithm="http://www.w3.org/20
            xmlns:xenc="http://www.w3.org/2
            <ds:DigestMethod xmlns:ds="http://w
                Algorithm="http://
        </xenc:EncryptionMethod>
        <ds:KeyInfo xmlns:ds="http://www.w3.org
            <ds:KeyName>1d0bc832d839df789eca8ba
        </ds:KeyInfo>
        <xenc:CipherData xmlns:xenc="http://www
            <xenc:CipherValue>...</xenc:CipherV
        </xenc:CipherData>
        <xenc:ReferenceList>
            <xenc:DataReference URI="#_46e926d5
        </xenc:ReferenceList>
        </xenc:EncryptedKey>
    </saml2:EncryptedID>
</saml2:AttributeValue>
</saml2:Attribute>
</saml2:AttributeStatement>
</saml2:Assertion>
<saml2:Assertion ID="_c7a79a0e92311f0d3d2dadcd247a855f6" IssueIn

```

```
Version="2.0" xmlns:saml2="urn:oasis:names:tc:
<saml2:Issuer>urn:nl-eid-gdi:1.0:BVD:00000004003214345001:e
<ds:Signature xmlns:ds="http://www.w3.org/2000/09/xmldsig#"
  <ds:SignedInfo>
    <ds:CanonicalizationMethod Algorithm="http://www.w3
    <ds:SignatureMethod Algorithm="http://www.w3.org/20
    <ds:Reference URI="#_c7a79a0e92311f0d3d2dad247a855
      <ds:Transforms>
        <ds:Transform
          Algorithm="http://www.w3.org/2000/0
        <ds:Transform Algorithm="http://www.w3.org/
      </ds:Transforms>
    <ds:DigestMethod Algorithm="http://www.w3.org/2
    <ds:DigestValue>...</ds:DigestValue>
  </ds:Reference>
</ds:SignedInfo>
<ds:SignatureValue>...</ds:SignatureValue>
<ds:KeyInfo>
  <ds:KeyName>4202df88ba9faae2d2860a0d821d2bde10babcb0
</ds:KeyName>
</ds:KeyInfo>
</ds:Signature>
<saml2:Subject>
  <saml2:NameID Format="urn:oasis:names:tc:SAML:2.0:namei
    45e376c5-78a7-4cdc-a27d-a7dd5056e786
  </saml2:NameID>
  <saml2:SubjectConfirmation Method="urn:oasis:names:tc:S
    <saml2:SubjectConfirmationData
      InResponseTo="_a658d2c5c7426b11dfbdb1e30d4b
      NotOnOrAfter="2021-10-06T08:12:50.916Z"
      Recipient="http://sp.example.com"/>
    </saml2:SubjectConfirmation>
  </saml2:Subject>
  <saml2:Conditions NotBefore="2021-10-06T08:08:50.916Z"
    NotOnOrAfter="2021-10-06T08:12:50.916Z">
    <saml2:AudienceRestriction>
      <saml2:Audience>urn:nl-eid-gdi:1.0:DV:0000000999999
    </saml2:Audience>
    </saml2:AudienceRestriction>
  </saml2:Conditions>
  <saml2:AuthnStatement AuthnInstant="2021-10-06T08:10:51.090
    <saml2:AuthnContext>
      <saml2:AuthnContextClassRef>http://eid.logius.nl/Lo
    </saml2:AuthnContextClassRef>
    </saml2:AuthnContext>
  </saml2:AuthnStatement>
  <saml2:AttributeStatement>
    <saml2:Attribute Name="urn:nl-eid-gdi:1.0:ServiceUUID">
      <saml2:AttributeValue>375b1cb114b7-12e9-3534-16cc-4
    </saml2:Attribute>
    <saml2:Attribute Name="urn:nl-eid-gdi:1.0:ActingSubject
      <saml2:AttributeValue>
        <saml2:EncryptedID>
          <xenc:EncryptedData xmlns:xenc="http://www.
            Id="_d4eb5b0632d3883739
            Type="http://www.w3.org
```



```

        <xenc:EncryptionMethod
            Algorithm="http://www.w3.org/20
            xmlns:xenc="http://www.w3.org/2
        <ds:KeyInfo xmlns:ds="http://www.w3.org
            <ds:RetrievalMethod
                Type="http://www.w3.org/200
                URI="#_720276d2e729cdec688
            </ds:KeyInfo>
        <xenc:CipherData xmlns:xenc="http://www
            <xenc:CipherValue>...</xenc:CipherV
        </xenc:CipherData>
    </xenc:EncryptedData>
    <xenc:EncryptedKey xmlns:xenc="http://www.w
        Id="_720276d2e729cdec68
        Recipient="urn:n1-eid-gd
    <xenc:EncryptionMethod
        Algorithm="http://www.w3.org/20
        xmlns:xenc="http://www.w3.org/2
    <ds:DigestMethod xmlns:ds="http://w
        Algorithm="http://
    </xenc:EncryptionMethod>
    <ds:KeyInfo xmlns:ds="http://www.w3.org
        <ds:KeyName>1d0bc832d839df789eca8ba
    </ds:KeyInfo>
    <xenc:CipherData xmlns:xenc="http://www
        <xenc:CipherValue>...</xenc:CipherV
    </xenc:CipherData>
    <xenc:ReferenceList>
        <xenc:DataReference URI="#_d4eb5b06
    </xenc:ReferenceList>
    </xenc:EncryptedKey>
</saml2:EncryptedID>
</saml2:AttributeValue>
</saml2:Attribute>
<saml2:Attribute Name="urn:n1-eid-gdi:1.0:LegalSubjectI
    <saml2:AttributeValue>
        <saml2:EncryptedID>
            <xenc:EncryptedData xmlns:xenc="http://www.
                Id="_0fbab7451567b50413
                Type="http://www.w3.org
            <xenc:EncryptionMethod
                Algorithm="http://www.w3.org/20
                xmlns:xenc="http://www.w3.org/2
            <ds:KeyInfo xmlns:ds="http://www.w3.org
                <ds:RetrievalMethod
                    Type="http://www.w3.org/200
                    URI="#_2cab7ef2667689c6064d
                </ds:KeyInfo>
            <xenc:CipherData xmlns:xenc="http://www
                <xenc:CipherValue>...</xenc:CipherV
            </xenc:CipherData>
        </xenc:EncryptedData>
        <xenc:EncryptedKey xmlns:xenc="http://www.w
            Id="_2cab7ef2667689c6064
            Recipient="urn:n1-eid-gd
        <xenc:EncryptionMethod

```

```

        Algorithm="http://www.w3.org/20
        xmlns:xenc="http://www.w3.org/2
        <ds:DigestMethod xmlns:ds="http://w
            Algorithm="http://
        </xenc:EncryptionMethod>
        <ds:KeyInfo xmlns:ds="http://www.w3.org
            <ds:KeyName>1d0bc832d839df789eca8ba
        </ds:KeyInfo>
        <xenc:CipherData xmlns:xenc="http://www
            <xenc:CipherValue>...</xenc:CipherV
        </xenc:CipherData>
        <xenc:ReferenceList>
            <xenc:DataReference URI="#_0fbab745
        </xenc:ReferenceList>
        </xenc:EncryptedKey>
    </saml2:EncryptedID>
    </saml2:AttributeValue>
</saml2:Attribute>
</saml2:AttributeStatement>
</saml2:Assertion>
</saml2:Advice>
<saml2:AuthnStatement AuthnInstant="2021-10-06T08:10:51.018Z" Sessi
    <saml2:AuthnContext>
        <saml2:AuthnContextClassRef>http://eid.logius.nl/LoA/basic<
        <saml2:AuthenticatingAuthority>urn:nl-eid-gdi:1.0:AD:000000
        </saml2:AuthenticatingAuthority>
        <saml2:AuthenticatingAuthority>urn:nl-eid-gdi:1.0:BVD:00000
        </saml2:AuthenticatingAuthority>
    </saml2:AuthnContext>
</saml2:AuthnStatement>
<saml2:AttributeStatement>
    <saml2:Attribute Name="urn:nl-eid-gdi:1.0:ServiceUUID">
        <saml2:AttributeValue>375b1cb114b7-12e9-3534-16cc-4d8997b0<
    </saml2:Attribute>
    <saml2:Attribute Name="urn:nl-eid-gdi:1.0:ActingSubjectID">
        <saml2:AttributeValue>
            <saml2:EncryptedID>
                <xenc:EncryptedData xmlns:xenc="http://www.w3.org/2
                    Id="_c108a849ffb239e73ac6083348
                    Type="http://www.w3.org/2001/04
                <xenc:EncryptionMethod Algorithm="http://www.w3
                    xmlns:xenc="http://www.w
                <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09
                    <ds:RetrievalMethod Type="http://www.w3.org
                        URI="#_df56cc944ecbb3a0
                </ds:KeyInfo>
                <xenc:CipherData xmlns:xenc="http://www.w3.org/
                    <xenc:CipherValue>...</xenc:CipherValue>
                </xenc:CipherData>
            </xenc:EncryptedData>
            <xenc:EncryptedKey xmlns:xenc="http://www.w3.org/20
                Id="_df56cc944ecbb3a06fe5d0a0d45
                Recipient="urn:nl-eid-gdi:1.0:DV
            <xenc:EncryptionMethod
                Algorithm="http://www.w3.org/2001/04/xm
                xmlns:xenc="http://www.w3.org/2001/04/x

```

```

        <ds:DigestMethod xmlns:ds="http://www.w3.org/2000/09
            Algorithm="http://www.w3.org/2001/04/xmldsig-core#sha1"
        </ds:DigestMethod>
    </xenc:EncryptionMethod>
    <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09"
        <ds:KeyName>1d0bc832d839df789eca8bae611c3ad
        </ds:KeyName>
    </ds:KeyInfo>
    <xenc:CipherData xmlns:xenc="http://www.w3.org/2001/04/xmldsig-core#
        <xenc:CipherValue>...</xenc:CipherValue>
    </xenc:CipherData>
    <xenc:ReferenceList>
        <xenc:DataReference URI="#_c108a849ffb239e7
        </xenc:DataReference>
    </xenc:ReferenceList>
    </xenc:EncryptedKey>
</saml2:EncryptedID>
</saml2:AttributeValue>
</saml2:Attribute>
<saml2:Attribute Name="urn:n1-eid-gdi:1.0:LegalSubjectID">
    <saml2:AttributeValue>
        <saml2:EncryptedID>
            <xenc:EncryptedData xmlns:xenc="http://www.w3.org/2001/04/xmldsig-core#
                Id="_5d50f7898d8afda532502d7f82
                Type="http://www.w3.org/2001/04/xmldsig-core#
            <xenc:EncryptionMethod Algorithm="http://www.w3.org/2001/04/xmldsig-core#
                xmlns:xenc="http://www.w3.org/2001/04/xmldsig-core#
            <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09"
                <ds:RetrievalMethod Type="http://www.w3.org/2001/04/xmldsig-core#
                URI="#_ea31225223bb330e
            </ds:RetrievalMethod>
            </ds:KeyInfo>
            <xenc:CipherData xmlns:xenc="http://www.w3.org/2001/04/xmldsig-core#
                <xenc:CipherValue>...</xenc:CipherValue>
            </xenc:CipherData>
        </xenc:EncryptedData>
        <xenc:EncryptedKey xmlns:xenc="http://www.w3.org/2001/04/xmldsig-core#
            Id="_ea31225223bb330ed5fe42bb55f
            Recipient="urn:n1-eid-gdi:1.0:DV
        <xenc:EncryptionMethod
            Algorithm="http://www.w3.org/2001/04/xmldsig-core#
            xmlns:xenc="http://www.w3.org/2001/04/xmldsig-core#
        <ds:DigestMethod xmlns:ds="http://www.w3.org/2000/09
            Algorithm="http://www.w3.org/2001/04/xmldsig-core#sha1"
        </ds:DigestMethod>
    </xenc:EncryptionMethod>
    <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09"
        <ds:KeyName>1d0bc832d839df789eca8bae611c3ad
        </ds:KeyName>
    </ds:KeyInfo>
    <xenc:CipherData xmlns:xenc="http://www.w3.org/2001/04/xmldsig-core#
        <xenc:CipherValue>...</xenc:CipherValue>
    </xenc:CipherData>
    <xenc:ReferenceList>
        <xenc:DataReference URI="#_5d50f7898d8afda5
        </xenc:DataReference>
    </xenc:ReferenceList>
    </xenc:EncryptedKey>
</saml2:EncryptedID>
</saml2:AttributeValue>
</saml2:Attribute>
</saml2:AttributeStatement>
</saml2:Assertion>

```

```

        </saml2p:Response>
      </saml2p:ArtifactResponse>
    </soap11:Body>
  </soap11:Envelope>

```

§A.8 Example - LogoutRequest

EXAMPLE 8: LogoutRequest

```

<?xml version="1.0" encoding="UTF-8"?>
<samlp:LogoutRequest Destination="http://idp.example.com/request_logout"
  ID="_2c952f14396dbab5f8c214d074e8e51272de9faa" IssueInstant="2021-
  xmlns:ds="http://www.w3.org/2000/09/xmldsig#" xmlns:ec="http://www
  xmlns:saml="urn:oasis:names:tc:SAML:2.0:assertion"
  xmlns:samlp="urn:oasis:names:tc:SAML:2.0:protocol">
  <saml:Issuer>urn:nl-eid-gdi:1.0:DV:000000099999999999004:entities:0000</saml:Issuer>
  <ds:Signature>
    <ds:SignedInfo>
      <ds:CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml-exc-c14
      <ds:SignatureMethod Algorithm="http://www.w3.org/2001/04/xmldsig-more#rsa-s
      <ds:Reference URI="#_2c952f14396dbab5f8c214d074e8e51272de9faa">
        <ds:Transforms>
          <ds:Transform Algorithm="http://www.w3.org/2000/09/xmldsig#envelope
          <ds:Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#">
            <ec:InclusiveNamespaces PrefixList="ds saml samlp xs"/>
          </ds:Transform>
        </ds:Transforms>
        <ds:DigestMethod Algorithm="http://www.w3.org/2001/04/xmlenc#sha256"/>
        <ds:DigestValue>...</ds:DigestValue>
      </ds:Reference>
    </ds:SignedInfo>
    <ds:SignatureValue>...</ds:SignatureValue>
    <ds:KeyInfo>
      <ds:KeyName>1d0bc832d839df789eca8bae611c3ad7ec5c5074</ds:KeyName>
    </ds:KeyInfo>
  </ds:Signature>
  <saml:SessionIndex>45e376c5-78a7-4cdc-a27d-a7dd5056e786</saml:SessionIndex>
  <saml:NameID>45e376c5-78a7-4cdc-a27d-a7dd5056e786</saml:NameID>
</samlp:LogoutRequest>

```

§A.9 Example - LogoutResponse

EXAMPLE 9: LogoutResponse

```
<?xml version="1.0" encoding="UTF-8"?>
<samlp:LogoutResponse xmlns:samlp="urn:oasis:names:tc:SAML:2.0:protocol"
    xmlns:saml="urn:oasis:names:tc:SAML:2.0:assertion" xmlns:ds="http
    ID="_1d0f30ecbc082449c36286d14063dcb4" Version="2.0" IssueInstant
    Destination="http://idp.example.com/single_logout_service"
    InResponseTo="_4565109c3326bc3ab8c680d8efeaba7e22b7e304">
  <saml:Issuer>urn:nl-eid-gdi:1.0:TD:00000004183317817000:entities:9000</saml:Issuer>
  <ds:Signature>
    <ds:SignedInfo>
      <ds:CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml-exc-c14
      <ds:SignatureMethod Algorithm="http://www.w3.org/2001/04/xmldsig-more#rsa-s
      <ds:Reference URI="#_1d0f30ecbc082449c36286d14063dcb4">
        <ds:Transforms>
          <ds:Transform Algorithm="http://www.w3.org/2000/09/xmldsig#envelope
          <ds:Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#"/>
        </ds:Transforms>
        <ds:DigestMethod Algorithm="http://www.w3.org/2001/04/xmllenc#sha256"/>
        <ds:DigestValue>...</ds:DigestValue>
      </ds:Reference>
    </ds:SignedInfo>
    <ds:SignatureValue>...</ds:SignatureValue>
    <ds:KeyInfo>
      <ds:KeyName>24b1a2189f8af57114df0b93120f88b1d9cd38a0f06780377f6f8ace82fb0b1
    </ds:KeyInfo>
  </ds:Signature>
  <samlp:Status>
    <samlp:StatusCode Value="urn:oasis:names:tc:SAML:2.0:status:Success"/>
  </samlp:Status>
</samlp:LogoutResponse>
```

§B. Example SAML metadata

This section is non-normative.

§B.1 Example - Metadata DV for RD

EXAMPLE 10: SAML metadata DV for RD

```
<md:EntityDescriptor xmlns:md="urn:oasis:names:tc:SAML:2.0:metadata"
  xmlns:saml="urn:oasis:names:tc:SAML:2.0:assertion"
  xmlns:dsig="http://www.w3.org/2000/09/xmldsig#"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  ID="_d611bce3fb2b4ee587bd508acfb89f2f1154815b"
  entityID="urn:nl-eid-gdi:1.0:DV:00000004000000010000:entities:9002"
  validUntil="2021-03-03T10:00:00Z"
>
  <dsig:Signature xmlns:dsig="http://www.w3.org/2000/09/xmldsig#">
    <dsig:SignedInfo>
      <dsig:CanonicalizationMethod
        Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
      <dsig:SignatureMethod
        Algorithm="http://www.w3.org/2001/04/xmldsig-more#rsa-sha256" />
      <dsig:Reference
        URI="#_d611bce3fb2b4ee587bd508acfb89f2f1154815b">
        <dsig:Transforms>
          <dsig:Transform
            Algorithm="http://www.w3.org/2000/09/xmldsig#enveloped-sign" />
          <dsig:Transform
            Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
        </dsig:Transforms>
        <dsig:DigestMethod
          Algorithm="http://www.w3.org/2001/04/xmldsig-more#sha256" />
        <dsig:DigestValue>...</dsig:DigestValue>
      </dsig:Reference>
    </dsig:SignedInfo>
    <dsig:SignatureValue>...</dsig:SignatureValue>
    <dsig:KeyInfo>
      <dsig:X509Data>
        <dsig:X509Certificate>...</dsig:X509Certificate>
      </dsig:X509Data>
    </dsig:KeyInfo>
  </dsig:Signature>
  <md:SPSSODescriptor AuthnRequestsSigned="true" WantAssertionsSigned="true"
    protocolSupportEnumeration="urn:oasis:names:tc:SAML:2.0:protoco" />
  <md:KeyDescriptor use="signing">
    <dsig:KeyInfo>
      <dsig:KeyName>dec5ed105fc56a8a6b85f83d1a4e7b64af0eb378</dsig:KeyName>
      <dsig:X509Data>
        <dsig:X509Certificate>...</dsig:X509Certificate>
      </dsig:X509Data>
    </dsig:KeyInfo>
  </md:KeyDescriptor>
  <md:KeyDescriptor use="encryption">
    <dsig:KeyInfo>
      <dsig:KeyName>cdb948c5dfde5c9a53bf4916763dc973d55e8dd0</dsig:KeyName>
```

```
        <dsig:X509Data>
            <dsig:X509Certificate>...</dsig:X509Certificate>
        </dsig:X509Data>
    </dsig:KeyInfo>
</md:KeyDescriptor>
<md:SingleLogoutService
    Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST"
    Location="https://login.dv.test/saml/sp/logout"/>
<md:AssertionConsumerService
    Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-Artifact"
    Location="https://login.dv.test/saml/sp/acs" index="0" isDefault="true"
<md:AttributeConsumingService index="0" isDefault="true">
    <md:ServiceName xml:lang="nl-NL">Dienstnaam 1</md:ServiceName>
    <md:RequestedAttribute Name="urn:nl-eid-gdi:1.0:ServiceUUID">
        <saml:AttributeValue xsi:type="xs:string">f847dc11-ac24-47b2-
            84a8-a057440ce56d
        </saml:AttributeValue>
    </md:RequestedAttribute>
</md:AttributeConsumingService>
</md:SPSSODescriptor>
</md:EntityDescriptor>
```

§B.2 Example - Metadata LC for RD

EXAMPLE 11: SAML metadata LC for RD

```
<md:EntitiesDescriptor xmlns:md="urn:oasis:names:tc:SAML:2.0:metadata"
    xmlns:dsig="http://www.w3.org/2000/09/xmldsig#"
    ID="_e611bce3fb2b4ee587bd508acfb89f2f1154815c"
    validUntil="2021-03-03T10:00:00Z"
>
  <dsig:Signature xmlns:dsig="http://www.w3.org/2000/09/xmldsig#">
    <dsig:SignedInfo>
      <dsig:CanonicalizationMethod>
        Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
      <dsig:SignatureMethod>
        Algorithm="http://www.w3.org/2001/04/xmldsig-more#rsa-sha256" />
      <dsig:Reference>
        URI="#_e611bce3fb2b4ee587bd508acfb89f2f1154815c">
          <dsig:Transforms>
            <dsig:Transform>
              Algorithm="http://www.w3.org/2000/09/xmldsig#enveloped-sign"
            <dsig:Transform>
              Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
          </dsig:Transforms>
          <dsig:DigestMethod>
            Algorithm="http://www.w3.org/2001/04/xmldsig-more#sha256" />
          <dsig:DigestValue>...</dsig:DigestValue>
        </dsig:Reference>
      </dsig:SignedInfo>
      <dsig:SignatureValue>...</dsig:SignatureValue>
      <dsig:KeyInfo>
        <dsig:X509Data>
          <dsig:X509Certificate>...</dsig:X509Certificate>
        </dsig:X509Data>
      </dsig:KeyInfo>
    </dsig:Signature>
    <md:EntityDescriptor xmlns:md="urn:oasis:names:tc:SAML:2.0:metadata"
        xmlns:dsig="http://www.w3.org/2000/09/xmldsig#"
        ID="_5d9c0e0ccb144714937dabffbf36e90ee57ee8ea"
        entityID="urn:nl-eid-gdi:1.0:LC:000000080000000020000:entities:
        validUntil="2021-03-03T10:00:00Z"
    >
      <md:SPSSODescriptor AuthnRequestsSigned="true" WantAssertionsSigned="true"
        protocolSupportEnumeration="urn:oasis:names:tc:SAML:2.0:pro
      <md:KeyDescriptor use="signing">
        <dsig:KeyInfo>
          <dsig:KeyName>5138f7018e8a9f81dade8cf0e554134c4cefaf06</dsig:KeyNam
          <dsig:X509Data>
            <dsig:X509Certificate>...</dsig:X509Certificate>
          </dsig:X509Data>
        </dsig:KeyInfo>
      </md:KeyDescriptor>
    </md:KeyDescriptor use="signing">
```



```

        <dsig:KeyInfo>
          <dsig:KeyName>6cfed4024668054e3cbf327c060aed4b050e0e7e</dsig:KeyNam
          <dsig:X509Data>
            <dsig:X509Certificate>...</dsig:X509Certificate>
          </dsig:X509Data>
        </dsig:KeyInfo>
      </md:KeyDescriptor>
    <md:SingleLogoutService
      Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST"
      Location="https://login.lc.test/saml/sp/logout"/>
    <md:AssertionConsumerService
      Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-Artifact"
      Location="https://login.lc.test/saml/sp/acs" index="0" isDefault="t
  </md:SPSSODescriptor>
</md:EntityDescriptor>
<md:EntityDescriptor xmlns:md="urn:oasis:names:tc:SAML:2.0:metadata"
  xmlns:dsig="http://www.w3.org/2000/09/xmldsig#"
  ID="_d611bce3fb2b4ee587bd508acfb89f2f1154815b"
  entityID="urn:nl-eid-gdi:1.0:DV:00000004000000010000:entities:
  validUntil="2021-03-03T10:00:00Z"
>
  <md:SPSSODescriptor AuthnRequestsSigned="true" WantAssertionsSigned="true"
    protocolSupportEnumeration="urn:oasis:names:tc:SAML:2.0:pro
  <md:KeyDescriptor use="encryption">
    <dsig:KeyInfo>
      <dsig:KeyName>cdb948c5dfde5c9a53bf4916763dc973d55e8dd0</dsig:KeyNam
      <dsig:X509Data>
        <dsig:X509Certificate>...</dsig:X509Certificate>
      </dsig:X509Data>
    </dsig:KeyInfo>
  </md:KeyDescriptor>
  <md:AssertionConsumerService
    Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-Artifact"
    Location="https://login.lc.test/saml/sp/acs" index="0" isDefault="t
  </md:SPSSODescriptor>
</md:EntityDescriptor>
<md:EntityDescriptor xmlns:md="urn:oasis:names:tc:SAML:2.0:metadata"
  xmlns:dsig="http://www.w3.org/2000/09/xmldsig#"
  ID="_c611bce3fb2b4ee587bd508acfb89f2f1154815a"
  entityID="urn:nl-eid-gdi:1.0:DV:00000004000000020000:entities:
  validUntil="2021-03-03T10:00:00Z"
>
  <md:SPSSODescriptor AuthnRequestsSigned="true" WantAssertionsSigned="true"
    protocolSupportEnumeration="urn:oasis:names:tc:SAML:2.0:pro
  <md:KeyDescriptor use="encryption">
    <dsig:KeyInfo>
      <dsig:KeyName>b459c1ecee731f2be4f50f68abe9bb070b5e2509</dsig:KeyNam
      <dsig:X509Data>
        <dsig:X509Certificate>...</dsig:X509Certificate>
      </dsig:X509Data>
    </dsig:KeyInfo>
  </md:KeyDescriptor>
  <md:KeyDescriptor use="encryption">
    <dsig:KeyInfo>
      <dsig:KeyName>45214df11fbed62751adf608d768f65d7fcd1e25</dsig:KeyNam
      <dsig:X509Data>

```

```
        <dsig:X509Certificate>...</dsig:X509Certificate>
      </dsig:X509Data>
    </dsig:KeyInfo>
  </md:KeyDescriptor>
  <md:AssertionConsumerService
    Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-Artifact"
    Location="https://login.lc.test/saml/sp/acs" index="0" isDefault="t
  </md:SPSSODescriptor>
</md:EntityDescriptor>
</md:EntitiesDescriptor>
```

§B.3 Example - Metadata RD for DV

EXAMPLE 12: SAML metadata RD for DV

```
<md:EntityDescriptor xmlns:md="urn:oasis:names:tc:SAML:2.0:metadata"
    xmlns:dsig="http://www.w3.org/2000/09/xmldsig#"
    ID="_c92a6365a0d0ff7e3187ef1ca6cc14918f390db3"
    entityID="urn:nl-eid-gdi:1.0:RD:00000004000000149000:entities:9002"
    validUntil="2021-05-01T12:00:00Z">
  <dsig:Signature xmlns:dsig="http://www.w3.org/2000/09/xmldsig#" Id="Id0001597663996">
    <dsig:SignedInfo>
      <dsig:CanonicalizationMethod>
        Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#"/>
      <dsig:SignatureMethod>
        Algorithm="http://www.w3.org/2001/04/xmldsig-more#rsa-sha256"/>
      <dsig:Reference>
        URI="#_c92a6365a0d0ff7e3187ef1ca6cc14918f390db3">
          <dsig:Transforms>
            <dsig:Transform>
              Algorithm="http://www.w3.org/2000/09/xmldsig#enveloped-sign"
            </dsig:Transform>
            <dsig:Transform>
              Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#"/>
            </dsig:Transforms>
          <dsig:DigestMethod>
            Algorithm="http://www.w3.org/2001/04/xmenc#sha256"/>
          <dsig:DigestValue>...</dsig:DigestValue>
        </dsig:Reference>
      </dsig:SignedInfo>
      <dsig:SignatureValue>...</dsig:SignatureValue>
      <dsig:KeyInfo xmlns:dsig="http://www.w3.org/2000/09/xmldsig#" Id="Id00015976639">
        <dsig:KeyName>07c3d08bc6c3303a85c5e0c9547dfd91047f7c58</dsig:KeyName>
      </dsig:KeyInfo>
    </dsig:Signature>
    <md:IDPSSODescriptor WantAuthnRequestsSigned="true"
        protocolSupportEnumeration="urn:oasis:names:tc:SAML:2.0:protoc
    <md:KeyDescriptor use="signing">
      <dsig:KeyInfo>
        <dsig:KeyName>07c3d08bc6c3303a85c5e0c9547dfd91047f7c58</dsig:KeyName>
        <dsig:X509Data>
          <dsig:X509Certificate>...</dsig:X509Certificate>
        </dsig:X509Data>
      </dsig:KeyInfo>
    </md:KeyDescriptor>
    <md:ArtifactResolutionService>
      Binding="urn:oasis:names:tc:SAML:2.0:bindings:SOAP"
      Location="https://artifact-pp2.toegang.overheid.nl/kvs/rd/resolve_artif
      index="0"/>
    <md:SingleLogoutService>
      Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST"
      Location="https://pp2.toegang.overheid.nl/kvs/rd/request_logout"/>
    <md:SingleSignOnService>
      Binding="urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST"
```

```
Location="https://pp2.toegang.overheid.nl/kvs/rd/request_authentication
</md:IDPSSODescriptor>
</md:EntityDescriptor>
```

§C. List of Figures

[Figure 1 Stelsel Toegang SAML1.0](#)

[Figure 2 Authentication and representation flow - overview](#)

[Figure 3 SAML Federated Logout overview](#)

[Figure 4 SAML authentication flow - DV/LC - RD](#)

[Figure 5 SAML authentication flow - DV/LC - RD - AuthN-Request](#)

[Figure 6 SAML authentication flow - DV/LC - RD - Artifact Response](#)

[Figure 7 SAML authentication flow - DV/LC - RD - Artifact Resolve](#)

[Figure 8 SAML authentication flow - DV/LC - RD - Artifact Response](#)

[Figure 9 LogoutRequest DV/LC - RD](#)

[Figure 10 LogoutResponse DV/LC - RD](#)

[Figure 11 Logout Response RD -AD](#)

[Figure 12 Logout Response RD -AD](#)

§D. Index

§D.1 Terms defined by this specification

[ActingSubjectID](#) §7.1.2.4.4.7

[AD](#) §3.2

[Advice](#) §7.1.2.4.4

[Artifact](#) §3.1

[ArtifactResolutionService](#) §8.2.3

Assertion

[definition of](#) §3.1

[definition of](#) §7.1.2.4.3

[definition of](#) §7.1.2.4.4

AssertionConsumerService

[definition of](#) §8.2.1

[definition of](#) §8.2.2.1

[definition of](#) §8.2.2.2

[AssertionConsumerServiceIndex](#) §7.1.2.1.2

Attribute

[definition of](#) §7.1.2.1.2

[definition of](#) §7.1.2.1.2

[definition of](#) §7.1.2.1.2

[definition of](#) §7.1.2.4.4.5

[AttributeConsumingService](#) §8.2.1

[AttributeConsumingServiceIndex](#) §7.1.2.1.2

AttributeStatement

[definition of](#) §7.1.2.4.4

[definition of](#) §7.1.2.4.4.5

AttributeValue

[definition of](#) §7.1.2.4.4.5

[definition of](#) §8.2.1

[Audience](#) §7.1.2.4.4

[AudienceRestriction](#) §7.1.2.4.4
[AuthenticatingAuthority](#) §7.1.2.4.4
[AuthnContext](#) §7.1.2.4.4
[AuthnContextClassRef](#) §7.1.2.4.4
[AuthnInstant](#) §7.1.2.4.4
AuthnRequestsSigned
 [definition of](#) §8.2.1
 [definition of](#) §8.2.2.1
[AuthnStatement](#) §7.1.2.4.4
[Back channel](#) §3.1
Binding
 [definition of](#) §8.2.1
 [definition of](#) §8.2.2.1
 [definition of](#) §8.2.2.1
 [definition of](#) §8.2.3
 [definition of](#) §8.2.3
 [definition of](#) §8.2.3
BSN
 [definition of](#) §3.1
 [definition of](#) §10.1
[BSNk](#) §3.1
[BVD](#) §3.2
[BVD-DDM](#) §3.1
[BVD-OG](#) §3.1
cacheDuration
 [definition of](#) §8.2.1
 [definition of](#) §8.2.2
 [definition of](#) §8.2.2.1
 [definition of](#) §8.2.2.2
 [definition of](#) §8.2.3
[Conditions](#) §7.1.2.4.4
Destination
 [definition of](#) §7.1.2.1.2
 [definition of](#) §7.1.2.3.2
 [definition of](#) §7.1.2.4.3
 [definition of](#) §7.2.1.3
 [definition of](#) §7.2.1.5
[DigiD](#) §3.1
[DigiD-CC](#) §3.1
[DigiD-Machtigen](#) §3.1
[DV](#) §3.2
[EB](#) §3.2
[EncryptedAssertion](#) §7.1.2.4.3

[EncryptedData](#) §9.2.1.2
[EncryptedID](#) §9.2.1.2
[EncryptedKey](#) §9.2.1.2
[EntitiesDescriptor](#) §8.2.2
[EntityConcernedTypes](#) §3.1
EntityDescriptor
 [definition of](#) §8.2.1
 [definition of](#) §8.2.2
 [definition of](#) §8.2.2.1
 [definition of](#) §8.2.2.2
 [definition of](#) §8.2.3
entityID
 [definition of](#) §8.2.1
 [definition of](#) §8.2.2.1
 [definition of](#) §8.2.2.2
 [definition of](#) §8.2.3
[EntityID](#) §3.1
[ETD](#) §3.1
[ETD Specific Pseudonym](#) §10.1
[ETD Stelsel](#) §3.1
[EU](#) §3.2
[Extensions](#) §7.1.2.1.2
[ForceAuthn](#) §7.1.2.1.2
[Front channel](#) §3.1
[Glossary](#) §3.
ID
 [definition of](#) §7.1.2.1.2
 [definition of](#) §7.1.2.3.2
 [definition of](#) §7.1.2.4.2
 [definition of](#) §7.1.2.4.3
 [definition of](#) §7.1.2.4.4
 [definition of](#) §7.2.1.3
 [definition of](#) §7.2.1.5
 [definition of](#) §8.2.1
 [definition of](#) §8.2.2
 [definition of](#) §8.2.2.1
 [definition of](#) §8.2.2.2
 [definition of](#) §8.2.3
[IDPEntry](#) §7.1.2.1.2
[IDPList](#) §7.1.2.1.2
[IDPSSODescriptor](#) §8.2.3

Index

[definition of §8.2.1](#)
[definition of §8.2.2.1](#)
[definition of §8.2.3](#)

InResponseTo

[definition of §7.1.2.4.2](#)
[definition of §7.1.2.4.3](#)
[definition of §7.1.2.4.4.3](#)
[definition of §7.2.1.5](#)

Intermediate Party §3.1

Intermediate.CompanyName §7.1.2.4.4.11

IntermediateEntityID §7.1.2.4.4.11

isDefault

[definition of §8.2.1](#)
[definition of §8.2.2.1](#)

IssueInstant

[definition of §7.1.2.1.2](#)
[definition of §7.1.2.3.2](#)
[definition of §7.1.2.4.2](#)
[definition of §7.1.2.4.3](#)
[definition of §7.1.2.4.4](#)
[definition of §7.2.1.3](#)
[definition of §7.2.1.5](#)

Issuer

[definition of §7.1.2.1.2](#)
[definition of §7.1.2.3.2](#)
[definition of §7.1.2.4.2](#)
[definition of §7.1.2.4.3](#)
[definition of §7.1.2.4.4](#)
[definition of §7.2.1.3](#)
[definition of §7.2.1.5](#)

KeyDescriptor

[definition of §8.2.1](#)
[definition of §8.2.2.1](#)
[definition of §8.2.2.2](#)
[definition of §8.2.3](#)

KeyInfo

[definition of §8.2.1](#)
[definition of §8.2.2.1](#)
[definition of §8.2.2.2](#)
[definition of §8.2.3](#)

KeyName

[definition of §8.2.1](#)
[definition of §8.2.2.1](#)
[definition of §8.2.2.2](#)
[definition of §8.2.3](#)

LC §3.2

Legacy-BSN §10.1

Legal Representation §3.1

LegalSubjectID §7.1.2.4.4.7

LoA §3.1

Location

[definition of §8.2.1](#)
[definition of §8.2.2.1](#)
[definition of §8.2.2.1](#)
[definition of §8.2.3](#)
[definition of §8.2.3](#)
[definition of §8.2.3](#)

Metadata §3.1

Method §7.1.2.4.4.3

MR §3.2

Name §7.1.2.4.4.5

NameID

[definition of §7.1.2.4.4](#)
[definition of §7.2.1.3](#)

NotBefore §7.1.2.4.4

NotOnOrAfter

[definition of §7.1.2.4.4](#)
[definition of §7.1.2.4.4.3](#)

Participant §3.1

Polymorphic Identity §3.1

protocolSupportEnumeration

[definition of §8.2.1](#)
[definition of §8.2.2.1](#)
[definition of §8.2.2.2](#)
[definition of §8.2.3](#)

ProviderID §7.1.2.1.2

ProviderName §7.1.2.1.2

Pseudonym §10.1

RD §3.2

Recipient

[definition of §7.1.2.4.4.3](#)
[definition of §9.2.1.2](#)

RepresentationType §7.1.2.4.4.9

[Represented Party](#) §3.1

[RequestedAttribute](#) §8.2.1

[RequesterID](#) §7.1.2.1.2

[Response](#) §7.1.2.4.2

[Roles](#) §3.2

[SAML](#) §3.1

[Scoping](#) §7.1.2.1.2

[Service](#) §3.1

[Service Catalog](#) §3.1

[Service Consumer](#) §3.1

[Service Definition](#) §7.1.2.1.2.1

[ServiceID](#) §3.1

[ServiceName](#) §8.2.1

[ServiceUUID](#) §3.1

SessionIndex

[definition of](#) §7.1.2.4.4

[definition of](#) §7.2.1.3

Signature

[definition of](#) §7.1.2.1.2

[definition of](#) §7.1.2.3.2

[definition of](#) §7.1.2.4.2

[definition of](#) §7.1.2.4.3

[definition of](#) §7.1.2.4.4

[definition of](#) §7.2.1.3

[definition of](#) §7.2.1.5

[definition of](#) §8.2.1

[definition of](#) §8.2.2

[definition of](#) §8.2.2.1

[definition of](#) §8.2.2.2

[definition of](#) §8.2.3

SingleLogoutService

[definition of](#) §8.2.1

[definition of](#) §8.2.2.1

[definition of](#) §8.2.3

[SingleSignOnService](#) §8.2.3

[SLO](#) §3.1

[Specific pseudonym](#) §3.1

SPSSODescriptor

[definition of](#) §8.2.1

[definition of](#) §8.2.2.1

[definition of](#) §8.2.2.2

[SSO](#) §3.1

[ST-SAML](#) §3.1

Status

[definition of](#) §7.1.2.4.2

[definition of](#) §7.1.2.4.3

[definition of](#) §7.2.1.5

StatusCode

[definition of](#) §7.1.2.4.2

[definition of](#) §7.1.2.4.2

[definition of](#) §7.1.2.4.3

[definition of](#) §7.1.2.4.3

[definition of](#) §7.2.1.5

StatusMessage

[definition of](#) §7.1.2.4.2

[definition of](#) §7.1.2.4.3

[Subject](#) §7.1.2.4.4

SubjectConfirmation

[definition of](#) §7.1.2.4.4

[definition of](#) §7.1.2.4.4.3

[SubjectConfirmationData](#) §7.1.2.4.4.3

[Terms](#) §3.1

[TVS](#) §3.1

[UA](#) §3.2

[urn:oasis:names:tc:SAML:2.0:status:AuthnFailed](#) §7.3.2

[urn:oasis:names:tc:SAML:2.0:status:NoAuthnContext](#) §7.3.2

[urn:oasis:names:tc:SAML:2.0:status:NoSupportedIDP](#) §7.3.2

[urn:oasis:names:tc:SAML:2.0:status:RequestDenied](#) §7.3.2

[urn:oasis:names:tc:SAML:2.0:status:Requester](#) §7.3.1

[urn:oasis:names:tc:SAML:2.0:status:RequestUnsupported](#)
§7.3.2

[urn:oasis:names:tc:SAML:2.0:status:Responder](#) §7.3.1

validUntil

[definition of](#) §8.2.1

[definition of](#) §8.2.2

[definition of](#) §8.2.2.1

[definition of](#) §8.2.2.2

[definition of](#) §8.2.3

Value

[definition of](#) §7.1.2.4.2

[definition of](#) §7.1.2.4.2

[definition of](#) §7.1.2.4.3

[definition of](#) §7.1.2.4.3

Version

[definition of §7.1.2.1.2](#)

[definition of §7.1.2.3.2](#)

[definition of §7.1.2.4.2](#)

[definition of §7.1.2.4.3](#)

[definition of §7.1.2.4.4](#)

[definition of §7.2.1.3](#)

[definition of §7.2.1.5](#)

WantAssertionsSigned

[definition of §8.2.1](#)

[definition of §8.2.2.1](#)

[WantAuthnRequestsSigned §8.2.3](#)

X509Data

[definition of §8.2.1](#)

[definition of §8.2.2.1](#)

[definition of §8.2.2.2](#)

[definition of §8.2.3](#)

§D.2 Terms defined by reference

§E. References

§E.1 Normative references

[BSNk.DEC]

BSNk PP technische specificaties. Logius. URL: <https://gitlab.com/logius/bsnk/bsnk-techspecs/bsnk/-/raw/main/BPTSlive.pdf>

[DigiD SAML3.x]

DigiD SAML3.x - legacy SAML specification for DigiD. LOGIUS. URL: <https://www.logius.nl/domeinen/toegang/digid/documentatie/koppelvlakspecificatie-digid-saml-authenticatie>

[eID SAML4.4]

eID SAML4.4 specification for DigiD. LOGIUS. URL: <https://logius.gitlab.io/eid-saml/4.4/index.html>

[eID SAML4.5]

eID SAML4.5 specification for DigiD. LOGIUS.

[ETD-Stelsel]

Afsprakenstelsel Elektronische Toegangsdiensten. URL: <https://afsprakenstelsel.etoegang.nl/Startpagina/as/>

[NCSC.TLS]

ICT-beveiligingsrichtlijnen voor Transport Layer Security (TLS). NCSC. URL: <https://www.ncsc.nl/transport-layer-security/ICT-beveiligingsrichtlijnen-voor-TLS>

[NORA]

Nederlandse Overheid Referentie Architectuur. URL: https://www.noraonline.nl/wiki/NORA_online

[RFC2119]

Key words for use in RFCs to Indicate Requirement Levels. S. Bradner. IETF. March 1997. Best Current Practice. URL: <https://www.rfc-editor.org/info/rfc2119/>

[RFC8174]

Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words. B. Leiba. IETF. May 2017. Best Current Practice. URL: <https://www.rfc-editor.org/info/rfc8174/>

[SAML2]

Security Assertion Markup Language (SAML) V2.0. OASIS. URL: <https://www.oasis-open.org/standard/saml/>

[SAML2.BINDINGS]

Bindings for the OASIS Security Assertion Markup Language (SAML) V2.0 – Errata Composite. OASIS. URL: <https://groups.oasis-open.org/higherlogic/ws/public/download/56779/sstc-saml-bindings-errata-2.0-wd-06.pdf>

[SAML2.CORE]

Assertions and Protocols for the OASIS Security Assertion Markup Language (SAML) V2.0 – Errata Composite. OASIS. URL: <https://groups.oasis-open.org/higherlogic/ws/public/download/56776/sstc-saml-core-errata-2.0-wd-07.pdf>

[SAML2.ERRATA.05]

SAML Version 2.0 Errata 05. OASIS. URL: <https://docs.oasis-open.org/security/saml/v2.0/sstc-saml-approved-errata-2.0.html>

[SAML2.METADATA]

Metadata for the OASIS Security Assertion Markup Language (SAML) V2.0 – Errata Composite. OASIS. URL: <https://groups.oasis-open.org/higherlogic/ws/public/download/56785/sstc-saml-metadata-errata-2.0-wd-05.pdf>

[SAML2.PROFILES]

Profiles for the OASIS Security Assertion Markup Language (SAML) V2.0 – Errata Composite. OASIS. URL: <https://groups.oasis-open.org/higherlogic/ws/public/download/56782/sstc-saml-profiles-errata-2.0-wd-07.pdf>

[SAML2.TO]

Security Assertion Markup Language (SAML) V2.0 Technical Overview. OASIS. URL: <https://docs.oasis-open.org/security/saml/Post2.0/sstc-saml-tech-overview-2.0.html>

[ST-SAML1.0]

Stelsel Toegang SAML v1.0 specification. LOGIUS. URL: <https://logius.gitlab.io/digid-combiconnect>

[XML.C14N.EXCL]

Exclusive XML Canonicalization. W3C. URL: <https://www.w3.org/TR/xml-exc-c14n/>

[XML.ENC]

XML Encryption Syntax and Processing. W3C. URL: <https://www.w3.org/TR/2002/REC-xmlenc-core-20021210/>

[XML.SIG]

XML Signature Syntax and Processing. W3C. URL: <https://www.w3.org/TR/xmldsig-core/>