

process_state(A,B)

Represents the state of a process containing Process_ID, Process_History_List, Process_Status.

author:

Michael Igler (michael.igler@uni-bayreuth.de)

version:

0.8

date:

2010/4/19

compilation:

static, context_switching_calls

(no dependencies on other files)

Public interface

get_highest_instance_id/1

Retrieves the highest instance-ID of the process.

compilation:

static

mode - number of solutions:

get_highest_instance_id(-number) - one

update_process_state/2

Updates a process state.

compilation:

static

mode - number of solutions:

update_process_state(+compound_term(concept_identifiers),-process_state) - one

instance_successtype_agents_data_tools/5

Retrieves information about a certain execution.

compilation:

static

mode - number of solutions:

instance_successtype_agents_data_tools(+instance_identifier,+action,+agent,
+data,+tool) - zero_or_one

instance_successtype_agents_data_tools_counter/6

Counts the executions by a certain person with certain data and tools.

compilation:

static

mode - number of solutions:

instance_successtype_agents_data_tools_counter(+instance_identifier,+action,
+agent,+data,+tool,-number) - zero_or_one

print/0

Prints some informations about the state.

compilation:

`static`

mode - number of solutions:

`print - one`

print/1

Prints some informations about the process state to a stream alias.

compilation:

`static`

mode - number of solutions:

`print(+var) - one`

Protected interface

(none)

Private predicates

(none)