

varlistp

List of variables protocol.

author:

Paulo Moura

version:

1.0

date:

2009/4/29

compilation:

static, context_switching_calls

(no dependencies on other files)

Public interface

append/3

Appends two lists.

compilation:

static

template:

append(List1,List2,List)

mode - number of solutions:

append(?list,?list,?list) - zero_or_more

delete/3

Deletes from a list all occurrences of an element returning the list of remaining elements.

compilation:

static

template:

delete(List,Element,Remaining)

mode - number of solutions:

delete(@list,@term,?list) - one

empty/1

True if the argument is an empty list.

compilation:

static

template:

empty(List)

mode - number of solutions:

empty(@list) - zero_or_one

flatten/2

Flattens a list of lists into a list.

compilation:

static

template:

```
flatten(List, Flatted)
```

mode - number of solutions:

```
flatten(@list, -list) - one
```

last/2

List last element (if it exists).

compilation:

```
static
```

template:

```
last(List, Last)
```

mode - number of solutions:

```
last(@list, @var) - zero_or_one
```

length/2

List length.

compilation:

```
static
```

template:

```
length(List, Length)
```

mode - number of solutions:

```
length(@list, ?integer) - zero_or_one
```

memberchk/2

Checks if a variable is a member of a list.

compilation:

```
static
```

template:

```
memberchk(Element, List)
```

mode - number of solutions:

```
memberchk(@var, @list) - zero_or_one
```

nextto/3

X and Y are consecutive elements in List.

compilation:

```
static
```

template:

```
nextto(X, Y, List)
```

mode - number of solutions:

```
nextto(@var, @var, ?list) - zero_or_more
```

nth0/3

Nth element of a list (counting from zero).

compilation:

```
static
```

template:

```
nth0(Nth, List, Element)
```

mode - number of solutions:
nth0(?integer,+list,@var) - zero_or_more

nth0/4

Nth element of a list (counting from zero).

compilation:
static

template:
nth0(Nth,List,Element,Residue)

mode - number of solutions:
nth0(?integer,+list,@var,?list) - zero_or_more

nth1/3

Nth element of a list (counting from one).

compilation:
static

template:
nth1(Nth,List,Element)

mode - number of solutions:
nth1(?integer,+list,@var) - zero_or_more

nth1/4

Nth element of a list (counting from zero).

compilation:
static

template:
nth1(Nth,List,Element,Residue)

mode - number of solutions:
nth1(?integer,+list,@var,?list) - zero_or_more

permutation/2

The two lists are a permutation of the same list.

compilation:
static

template:
permutation(List,Permutation)

mode - number of solutions:
permutation(@list,@list) - zero_or_one

prefix/2

Prefix is a prefix of List.

compilation:
static

template:
prefix(Prefix,List)

mode - number of solutions:
prefix(?list,@list) - zero_or_more

reverse/2

Reverses a list.

compilation:

static

template:

reverse(List,Reversed)

mode - number of solutions:

reverse(@list,?list) - zero_or_one

reverse(?list,@list) - zero_or_one

reverse(-list,-list) - one_or_more

same_length/2

The two lists have the same length.

compilation:

static

template:

same_length(List1,List2)

mode - number of solutions:

same_length(@list,?list) - zero_or_one

same_length(?list,@list) - zero_or_one

same_length(-list,-list) - one_or_more

select/3

Selects an element from a list, returning the list of remaining elements.

compilation:

static

template:

select(Element,List,Remaining)

mode - number of solutions:

select(@var,?list,?list) - zero_or_more

sublist/2

The first list is a sublist of the second.

compilation:

static

template:

sublist(Sublist,List)

mode - number of solutions:

sublist(?list,@list) - zero_or_more

subtract/3

Removes all elements in the second list from the first list, returning the list of remaining elements.

compilation:

static

template:

subtract(List,Elements,Remaining)

mode - number of solutions:

subtract(@list,@list,-list) - one

suffix/2

Suffix is a suffix of List.

compilation:

`static`

template:

`suffix(Suffix,List)`

mode - number of solutions:

`suffix(?list,@list) - zero_or_more`

Protected interface

(none)

Private predicates

(none)