

initialization

Object initialization protocol.

author:
 Paulo Moura
version:
 1.11
date:
 2008/10/10

compilation:
 static, context_switching_calls

uses:
 list

Public interface

init/1

Initialize an object with the given list of options.

compilation:
 static

template:
 init(Options)

mode - number of solutions:
 init(+list) - zero_or_one

valid_init_option/1

True if the argument is a valid initialization option.

compilation:
 static

template:
 valid_init_option(Option)

mode - number of solutions:
 valid_init_option(+nonvar) - zero_or_one

valid_init_options/1

True if the argument is list of valid initialization options.

compilation:
 static

template:
 valid_init_options(Options)

mode - number of solutions:
 valid_init_options(+list) - zero_or_one

default_init_options/1

List of default initialization options.

compilation:
 static

template:

```
default_init_options(Options)
```

mode - number of solutions:

```
default_init_options(+list) - one
```

default_init_option/1

Default initialization option.

compilation:

```
static
```

template:

```
default_init_option(Option)
```

mode - number of solutions:

```
default_init_option(?nonvar) - zero_or_more
```

free/1

Release an object with the given list of options.

compilation:

```
static
```

template:

```
free(Options)
```

mode - number of solutions:

```
free(+list) - zero_or_one
```

valid_free_option/1

compilation:

```
static
```

mode - number of solutions:

```
valid_free_option(+nonvar) - zero_or_one
```

valid_free_options/1

True if the argument is list of valid delete options.

compilation:

```
static
```

template:

```
valid_free_options(Options)
```

mode - number of solutions:

```
valid_free_options(+list) - zero_or_one
```

default_free_options/1

List of default delete options.

compilation:

```
static
```

template:

```
default_free_options(Options)
```

mode - number of solutions:

```
default_free_options(+list) - one
```

default_free_option/1

Default delete option.

compilation:
static

template:
default_free_option(Option)

mode - number of solutions:
default_free_option(?nonvar) - zero_or_more

Protected interface

process_init_option/1

Process initialization option.

compilation:
static

template:
process_init_option(Option)

mode - number of solutions:
process_init_option(?nonvar) - zero_or_one

process_free_option/1

Process delete option.

compilation:
static

template:
process_free_option(Option)

mode - number of solutions:
process_free_option(?nonvar) - zero_or_one

Private predicates

process_init_options/1

Process a list of initialization options.

compilation:
static

template:
process_init_options(Options)

mode - number of solutions:
process_init_options(+list) - zero_or_one

process_free_options/1

Process a list of delete options.

compilation:
static

template:
process_free_options(Options)

mode - number of solutions:
process_free_options(+list) - zero_or_one

merge_options/3

Constructs a complete list of options complementing the explicit options with the default ones.

compilation:

`static`

template:

`merge_options(Options,Defaults,Result)`

mode - number of solutions:

`merge_options(+list,+list,-list) - one`