

An easy way to access files in Gamma Mesh Format

The libMeshb library



Loïc MARÉCHAL / INRIA, Gamma Project

January 2018

Document v1.82

Library v7.33

Contents

1	Introduction	2
1.1	What is the Gamma Mesh Format ?	2
1.2	An evolutive keyword based format	2
1.3	A comprehensive C library	2
1.4	ASCII vs. Binary	2
1.5	Mesh and Sol files	3
1.6	File versions	3
2	Quick-start	4
2.1	Reading a file	4
2.2	Writing a file	6
2.3	Doing it all together	7
3	Commands	9
3.1	GmfOpenMesh	9
3.2	GmfCloseMesh	10
3.3	GmfStatKwd	10
3.4	GmfGotoKwd	12
3.5	GmfSetKwd	13
3.6	GmfGetLin	14
3.7	GmfSetLin	14
3.8	GmfGetBlock	15
3.9	GmfSetBlock	16
3.10	GmfSetHONodesOrdering	17
4	Keywords	19
4.1	List of basic keywords	19
4.2	List of keywords describing geometric properties	21
4.3	List of High Order elements keywords	22
4.4	List of solution keywords	24
4.5	Miscellaneous keywords	26

Cover picture: A variety of magnetic tape drives from the 1970's including the famous DECtapes.

1 Introduction

1.1 What is the Gamma Mesh Format ?

The Gamma Mesh Format (GMF) and the associated library *libMeshb* provide programmers of simulation and meshing softwares with an easy way to store their meshes and physical solutions.

The GMF features more than 90 kinds of data types, ranging from vertex to polyhedron or normal vectors to matricial solution fields.

The *libMeshb* provides a convenient way to move data between those files, via keyword tags, and the user's own structures.

1.2 An evolutive keyword based format

The GMF is a keyword based file format, meaning that a mesh file consists of a list of keywords, each followed by its data. No keyword is mandatory and a file may contain any combination of them. Furthermore, new keywords may be added while keeping upward and backward compatibility.

It means that older files can be accessed by newer version of the library and vice versa.

1.3 A comprehensive C library

The *libMeshb* provides programmers with a comprehensive set of commands and keywords covering most common operations on many different kinds of mesh or physical solution related data.

Reading, writing and querying files is easily done by calling a couple of commands which are provided in an ANSI C file "libmeshb7.c" and a header file "libmeshb7.h". All is needed is compiling those files along with the calling software.

Fortran APIs are also available: "libmeshb7.ins" for F77 and F90.

1.4 ASCII vs. Binary

GMF files can be stored in ascii or binary format (differentiated with *.mesh* or *.meshb* extensions).

This choice is transparent from a user's point of view and a routine reading GMF files will work on both kinds of storage. The library determining the right access method depending on the file extension.

It is advised to use ascii for debugging purpose only, when a file needs to be hand-written or checked by a human eye. Otherwise, when performance, compactness and portability are of concerns, binary is the way to go.

1.4.1 Size does matter

Binary files have a slightly smaller footprint than their ascii counterparts (typically 30% less). Not only does it save space on hard drives, but it allows for faster transfer as well.

1.4.2 About performance

Great care has been taken on performance issues when creating the *libMeshb*. When dealing with binary files, reading and writing throughputs will only be limited by the speed of the physical media where those files are located. Speed ranging from 20 MB/s to 60 MB/s can be achieved with hard drives and 10 MB/s or 100 MB/s with fast ethernet and gigabit ethernet networks, respectively.

The *libMeshb* performs very poorly in ascii mode, which is more processor bound rather than hard-drive bound. Don't expect more than 5 or 10 MB/s throughputs.

1.4.3 Compatibility issue: little vs. big endian

When it comes to binary storage, the compatibility problem posed by endianness always comes to mind.

Some processors like PowerPc or SPARC are called big endian because of the way they store bytes within a word from most significant byte to the lowest.

The other ones, like i86 (Intel core2, AMD opteron) or itanium, store bytes in the reverse order and are called little endian.

Consequently, a binary word written by a big endian processor cannot be read by a little endian one, and vice versa. This problem can be easily overcome by reversing bytes order when reading misoriented data. The *libMeshb* handles this compatibility issue via a control word that indicates which endian a mesh file was written in.

You may then use binary files as safely as ascii ones.

1.5 Mesh and Sol files

For the sake of understanding, different extensions must be given to files containing mesh related keywords, *.mesh* or *.meshb*, and files containing physical solution keywords, *.sol* or *.solb*.

1.6 File versions

Over the years, the library had to adapt to ever increasing system capabilities, henceforth, modification to the binary file format had to be done. As of today, there are three revisions of the meshb format:

Version	Size of integers	Size of reals	Maximum size of file
1	32 bits	32 bits	2 Giga Bytes
2	32 bits	64 bits	2 Giga Bytes
3	32 bits	64 bits	8 Exa Bytes
4	64 bits	64 bits	8 Exa Bytes

Although the *libMeshb* still handles versions 1 and 2 for the sake of compatibility, it is strongly advised to create version 3 or 4 files since most computers are now 64-bit capable.

A word of caution: great care must be taken when setting the library's arguments type. Regardless of the file version, some arguments are mandatory 32 bits integers like the open mode tag, mesh dimension or the file version. Even in "full 64 bits" version 4 mesh file format, only the number of lines given or set by the `GmfSetKeyword()` of `GmfStatKeyword()` commands and vertex indices used by elements field are using 64 bits integers.

The 64 bits integer data type used by the library is the *int64_t*, which is defined in the standard include file *stdint.h*. In case your system is too old to support 64 bits pointers and integers, you may define *int64_t* as a regular 32 bits *int*. The library will be aware of it and will still be able to handle version 1 or 2 files.

2 Quick-start

This section will guide you through three simple examples from which you may easily cut and paste to build your own code.

2.1 Reading a file

Let's start with reading an existing mesh file.

Reading a mesh is a two-step scheme:

1. opening and checking the file and allocating data structures according to its content
2. reading fields of interest (vertices, elements, etc...) and storing them in the previously allocated structures

2.1.1 Open, check and allocate a mesh

Opening a mesh file is done via the `GmfOpenMesh()` command. It allows to check for file existence and whether it is of the required version and dimension.

```
int64_t MeshIndex;
int Version, Dimension;
MeshIndex = GmfOpenMesh("testcase.meshb", GmfRead, &Version, &Dimension );
```

Then, the presence and quantity of each item can be checked and memory allocated accordingly via the `GmfStatKwd()` command.

```

int NumberOfTriangles, (*TableOfTriangles)[4];

NumberOfTriangles = GmfStatKwd( MeshIndex, GmfTriangles );

if(NumberOfTriangles > 0)
    TableOfTriangles = malloc(NumberOfTriangles * 4 * sizeof(int));

```

2.1.2 Example: reading vertices and triangles

Reading each keyword data is done via two commands:

- GmfGotoKwd() to set the file index to the beginning of keyword data
- GmfGetLin() to read one line of data

Let's say we would like to open a file, check if it contains vertices and quads, and read those fields into their respective tables:

```

int64_t idx;
int ver, dim, nbt, (*tt)[4], nbv, *rt;
float (*ct)[3];

/* Try to open the file and ensure its version is 1
   (single precision reals) and dimension is 3 */

idx = GmfOpenMesh("tri.meshb", GmfRead, &ver, &dim );

if( !idx || (ver != 1) || (dim != 3) )
    exit(1);

/* Read the number of vertices and triangles and allocate
   a triangle table (tt[nbt][4]) to store each triangle
   vertices and reference (hence the fourth integer).
   Two tables are allocated for the vertices:
   ct[nbv][3] to store the three coordinates
   rt[nbv] to store the references. */

nbv = GmfStatKwd( idx, GmfVertices );
nbt = GmfStatKwd( idx, GmfTriangles );

if( !nbv || !nbt )
    exit(1);

tt = malloc( nbt * 4 * sizeof(int) );

```

```

ct = malloc( nbv * 3 * sizeof(float) );
rt = malloc( nbv * sizeof(int) );

/* Move the file pointer to the begining of vertices data
   and start to loop over them. Then do likewise with triangles. */

GmfGotoKwd( idx, GmfVertices );

for(i=0;i<nbv;i++)
    GmfGetLin( idx, GmfVertices, &ct[i][0], &ct[i][1], &ct[i][2], &rt[i]);

GmfGotoKwd( idx, GmfTriangles );

for(i=0;i<nbt;i++)
    GmfGetLin( idx, GmfTriangles, &tt[i][0], &tt[i][1], &tt[i][2], &tt[i][3] );

GmfCloseMesh( idx );

```

2.2 Writing a file

Writing a mesh is also a two-step scheme:

1. creating a empty mesh file with the right version and dimension
2. writing every fields (vertices, elements, etc...)

2.2.1 Creating and defining a mesh

Mesh name, version and dimension must be provided at creation time. Creating a mesh following version 1 (single precision real numbers) in three dimensions named testcase.meshb runs this way:

```
Meshindex = GmfOpenMesh( "testcase.meshb", GmfWrite, 1, 3 );
```

2.2.2 Example: writing vertices and triangles

Following the reading example, we would like to write back the data to a new file:

```

int64_t idx;
int ver, dim, nbt, (*tt)[4], nbv, *rt;
float (*ct)[3];

/* Try to create a three-dimensional, version 1
   (single precision reals) file */

```

```

idx = GmfOpenMesh("tri.meshb", GmfWrite, 1, 3 );

if( !idx )
    exit(1);

/* Setup a vertex field with nbv lines
   and loop over vertices to write them down.
   Note that this time, direct values are passed on
   GmfSetLin() instead of pointers. */

GmfSetKwd( idx, GmfVertices, nbv );

for(i=0;i<nbv;i++)
    GmfSetLin( idx, GmfVertices, ct[i][0], ct[i][1], ct[i][2], rt[i]);

GmfSetKwd( idx, GmfTriangles, nbt );

for(i=0;i<nbt;i++)
    GmfSetLin( idx, GmfTriangles, tt[i][0], tt[i][1], tt[i][2], tt[i][3] );

GmfCloseMesh( idx );

```

2.3 Doing it all together

In this last example, the file "quad.mesh" a three-dimensional mesh made of quads will be read, transformed into a triangulated one, which will be written as "tri.mesh":

```

int64_t InpMsh, OutMsh;
int i, nbv, nbq, ver, dim, *rt, (*qt)[5];
float (*ct)[3];

// Open and check the input quadrilateral mesh
InpMsh = GmfOpenMesh("quad.mesh", GmfRead, &ver, &dim);

if( !InpMsh || (ver != 1) || (dim != 3) )
    exit(1);

// Allocate vertices and quads tables
nbv = GmfStatKwd(InpMsh, GmfVertices);
ct = malloc(nbv * 3 * sizeof(float));
rt = malloc(nbv * sizeof(int));

```



```

nbq = GmfStatKwd(InpMsh, GmfQuadrilaterals);
qt = malloc(nbq * 5 * sizeof(int));

// Read vertices and quads then close the input file
GmfGotoKwd(InpMsh, GmfVertices);

for(i=0;i<nbv;i++)
    GmfGetLin(InpMsh, GmfVertices, &ct[i][0], &ct[i][1], &ct[i][2], &rt[i]);

GmfGotoKwd(InpMsh, GmfQuadrilaterals);

for(i=0;i<nbq;i++)
    GmfGetLin(InpMsh, GmfQuadrilaterals, &qt[i][0],
              &qt[i][1], &qt[i][2], &qt[i][3], &qt[i][4]);

GmfCloseMesh(InpMsh);

// Now create the output file.
// Each quad being split into two triangles.

if(!(OutMsh = GmfOpenMesh("tri.mesh", GmfWrite, ver, dim)))
    exit(1);

GmfSetKwd(OutMsh, GmfVertices, nbv);

for(i=0;i<nbv;i++)
    GmfSetLin(OutMsh, GmfVertices, ct[i][0], ct[i][1], ct[i][2], rt[i]);

GmfSetKwd(OutMsh, GmfTriangles, 2*nbq);

for(i=1;i<=nbq;i++)
{
    GmfSetLin(OutMsh, GmfTriangles, qt[i][0], qt[i][1], qt[i][2], qt[i][4]);
    GmfSetLin(OutMsh, GmfTriangles, qt[i][0], qt[i][2], qt[i][3], qt[i][4]);
}

GmfCloseMesh(OutMsh);

```

3 Commands

3.1 GmfOpenMesh

Open a mesh file for reading or writing: in reading mode, it tries to open the file and returns some information about its content, in writing mode it creates an empty mesh file.

3.1.1 Reading mode

```
int64_t GmfOpenMesh( char *FileName,
                    int  OpenMode,
                    int  *Version,
                    int  *Dimension );
```

FileName: this string must contain the path and the mesh name with its extension (meshes/my_mesh.meshb).

OpenMode: must be set to GmfRead.

Version: will be set to the value read from file, which may range from 1 to 3.

1. real numbers in the whole file are written in single precision (32 bits)
2. real numbers in the whole file are written in double precision (64 bits)
3. same as 2 but file size may be greater than 2 GBytes.

Dimension: will be set to the value read from file, only dimensions 2 and 3 are supported.

Returns: Zero on failure or the opened mesh index otherwise. This index should be properly stored since it must be provided to any further *libMeshb* commands working on this file.

Example: open a mesh file and print its version and dimension.

```
int64_t MeshIndex;
int Version, Dimension;

Meshindex = GmfOpenMesh("testcase.meshb", GmfRead, &Version, &Dimension );

if(MeshIndex)
    printf("Version = %d, Dimension = %d\n.", Version, Dimension);
else
    puts("This file cannot be opened.");
```

3.1.2 Writing mode

```
int64_t GmfOpenMesh( char *FileName,  
                    int  OpenMode,  
                    int  Version,  
                    int  Dimension );
```

FileName: this string must contain the path and the mesh name with its extension (meshes/my_mesh.meshb).

OpenMode: must be set to GmfWrite.

Version: must be provided at file creation, see *Reading mode* for version values.

Dimension: must be provided at file creation, only dimensions 2 and 3 are supported.

Returns: zero on failure or the opened mesh index otherwise. This index should be properly stored since it must be provided to any further *libMeshb* commands working on this file.

Example: create a new three dimensional mesh file storing double precision numbers.

```
Meshindex = GmfOpenMesh("newfile.meshb", GmfWrite, 2, 3 );
```

3.2 GmfCloseMesh

A mesh file must be properly closed in order to release any allocated memory and to write tailing information.

```
GmfCloseMesh( int64_t MeshIndex );
```

MeshIdx: the index returned by GmfOpenMesh() must be provided for the file to be closed.

3.3 GmfStatKwd

This command queries the mesh file for the presence of a given keyword and the number of associated lines.

3.3.1 Getting information on a mesh keyword

```
int GmfStatKwd( int64_t MeshIndex,  
               int  Keyword );
```

MeshIndex: index of referenced mesh.

Keyword: the keyword tag you are requesting information on (see section 4 for a full list of available keywords).

Example: check out and print the number of triangles in a mesh file.

```
int NumberOfTriangles;

NumberOfTriangles = GmfStatKwd( MeshIndex, GmfTriangles );

if(NumberOfTriangles)
    printf("This file contains %d triangles\n.", NumberOfTriangles);
else
    puts("This file does not contain any triangle.");
```

3.3.2 Getting information on a solution keyword

In this case, additional information will be provided: the number of fields per solution, the number of real numbers a solution line occupies and a table of solutions types.

```
int64_t GmfStatKwd( int64_t MeshIndex,
                    int Keyword,
                    int *NumberOfTypes,
                    int *SizeOfSolution,
                    int *TableOfTypes );
```

MeshIndex: index of referenced mesh.

Keyword: the keyword tag you are requesting information on (see section 4 for a full list of available keywords).

NumberOfTypes: pointer to an integer, it will be set to the number of fields in the solution.

SizeOfSolution: pointer to an integer, it will be set to the number of real numbers (float or double depending on the file version) used by a solution line for memory allocation purpose.

TableOfTypes: pointer to a previously allocated table which will be filled with the type of each solution field.

Example: check out and print the number of solutions and their kinds associated to vertices.

```
int NmbSol, NmbTypes, NmbReals, TypesTab[ GmfMaxTyp ];

NmbSol = GmfStatKwd( MeshIndex, NmbSol, &NmbTypes, &NmbReals, TypesTab );

if(NmbSol)
{
    printf("This file contains %d solutions at each vertex\n.", NmbSol);
    printf("Each solution contains %d fields:\n", NmbTypes);

    for(i=0; i<NmbTypes; i++)
    {
        switch(TypesTab[i])
        {
            case GmfSca      : printf("scalar,\n"); break;
            case GmfVec      : printf("vector of %d scalars,\n", dim); break;
            case GmfSymMat   : printf("upper triangular part of a symetric \
                                   %d x %d matrix,\n", dim, dim); break;
            case GmfMat      : printf("full %d x %d matrix,\n", dim, dim); break;
        }
    }
}
else
    puts("This file does not contain triangles.");
```

3.4 GmfGotoKwd

Prior to reading each line of a keyword with the GmfGetLin() command, the file position must be set to the beginning of its data with GmfGotoKwd(). Note that positioning the file mark is only needed when reading, not writing.

```
int GmfGotoKwd( int64_t MeshIndex, int Keyword );
```

MeshIdx: the index returned by GmfOpenMesh() must be provided.

KeyWord: code of the keyword whose data are to be read.

Returns: zero if this keyword is not present in the pointed file, one otherwise.

3.5 GmfSetKwd

Prior to writing each line of a keyword with the `GmfSetLin()` command, the keyword header should be written along with the number of lines.

3.5.1 Writing a mesh keyword

```
int GmfSetKwd( int64_t MeshIndex,  
              int Keyword,  
              int NumberOfLines );
```

MeshIdx: the index returned by `GmfOpenMesh()` must be provided.

KeyWord: code of the keyword whose data are to be written.

NumberOfLines: number of data lines which are to be written.

Returns: zero if the data could not be written, and the number written lines otherwise.

3.5.2 Writing a solution keyword

When it comes to solution keywords, two extra arguments must be passed on: a table of solution types and its size.

```
int GmfSetKwd( int64_t MeshIndex,  
              int Keyword,  
              int NumberOfLines,  
              int NumberOfTypes,  
              int *TableOfTypes );
```

MeshIdx: the index returned by `GmfOpenMesh()` must be provided.

KeyWord: code of the keyword whose data are to be written.

NumberOfLines: number of data lines which are to be written.

NumberOfTypes: the number of fields stored for each line of this solution. It sets the size of the following `TableOfTypes` containing each field type.

TableOfTypes: pointer to a table of integers, each entry setting the type of each solution field: 1 for a scalar, 2 for a vector, 3 for symmetric matrix and 4 for a full matrix.

Returns: zero if the data could not be written, and the number written lines otherwise.

3.6 GmfGetLin

GmfGetLin() is a variable arguments command, it reads one line of data from the file and stores each items in the provided pointers to user's data structures.

```
int GmfGetLin( int64_t MeshIndex,  
              int Keyword,  
              arguments );
```

MeshIdx: the index returned by GmfOpenMesh() must be provided.

KeyWord: code of the keyword whose line data is to be read.

arguments: as many pointers to the required type of data as stated by the keyword definition (see section 4) should be provided.

Example: reading a vertex in three-dimensional case. Caution: the right size of real numbers, float or double, should be provided according to the mesh file version.

```
int ref;  
float xf, yf, zf;  
double xd, yd, zd;  
  
if(Version == 1)  
    GmfGetLine(MeshIndex, GmfVertices, &xf, &yf, &zf, &ref);  
else  
    GmfGetLine(MeshIndex, GmfVertices, &xd, &yf, &zf, &ref);
```

3.7 GmfSetLin

This commands works pretty much like GmfGetLin(), but arguments are given directly instead of pointers.

```
int GmfSetLin( int64_t MeshIndex,  
              int Keyword,  
              arguments );
```

MeshIdx: the index returned by GmfOpenMesh() must be provided.

KeyWord: code of the keyword whose line of data is to be written.

arguments: as many values of the required type of data as stated by the keyword definition (see section 4) should be provided.

3.8 GmfGetBlock

GmfGetBlock() is a variable arguments command, it reads all the lines of data from the file and stores each items in the provided pointers to user's data structures. The user's data structure has to be fully described in order for the library to fill all the lines automatically.

```
int GmfGetBlock(int64_t MeshIndex, int Keyword, int64_t BeginLine,
               int64_t EndLine, int MapType, void *RenumberingMap,
               void *Procedure, arguments...);
```

MeshIdx: the index returned by GmfOpenMesh() must be provided.

KeyWord: code of the keyword whose lines of data are to be read.

BeginLine: starting line in the mesh file, it enables partial reading for parallelism.

EndLine: ending line in the mesh file.

MapType: set the integer type (GmfInt or GmfLong) of the following renumbering table.

RenumberingMap: pointer to a renumbering table that gives the position to store each mesh entity in the user's table (for example: give the old to new renumbering through a Hilbert curve).

Procedure: pointer to an optional user's procedure that will be called in parallel after each block has been read. If a procedure is given, a second pointer on user's data must be provided right after.

arguments: for each type of data as stated by the keyword definition (see section 4), three arguments must be provided. First, the user's type of data in which the file's data will be stored (four kinds are available: GmfFloat, GmfDouble, GmfInt and GmfLong). Second, a pointer to the first line of this data type in the user's structure. Third, the same pointer but on the last line. The example below is more telling.

Example: reading all vertices in three-dimensional case.

```
int ref[nv];
double x[nv], y[nv], z[nv];

GmfGetBlock(MeshIndex, GmfVertices, 1, nv, 0, NULL, NULL,
            GmfDouble, &x[1], &x[nv],
            GmfDouble, &y[1], &y[nv],
```



```
GmfDouble, &z[1],    &z[nv],
GmfInt,    &ref[1], &ref[nv]);
```

In order to reduce the number of parameters, when dealing with high order polyhedra for example, you may concatenate a set of pointers to each vertices into one base address. The vertices will be loaded at consecutive addresses.

To indicate that the following begin and end set of pointers should be considered as a table, you should replace the GmfInt parameter by GmfIntTab followed by the size of the table. Conversely, GmfLong may be replaced by GmfLongTab.

In this example, the first GmfGetBlock reading hexahedra may be replaced by the second one:

```
GmfGetBlock(MeshIndex, GmfVertices, 1, nh, 0, NULL, NULL,
    GmfInt, &HexIdx[1][0],    &HexIdx[nh][0],
    GmfInt, &HexIdx[1][1],    &HexIdx[nh][1],
    GmfInt, &HexIdx[1][2],    &HexIdx[nh][2],
    GmfInt, &HexIdx[1][3],    &HexIdx[nh][3],
    GmfInt, &HexIdx[1][4],    &HexIdx[nh][4],
    GmfInt, &HexIdx[1][5],    &HexIdx[nh][5],
    GmfInt, &HexIdx[1][6],    &HexIdx[nh][6],
    GmfInt, &HexIdx[1][7],    &HexIdx[nh][7],
    GmfInt, &HexRef[1],       &HexRef[nh]);

GmfGetBlock(MeshIndex, GmfVertices, 1, nh, 0, NULL, NULL,
    GmfIntTab, 8, &HexIdx[1],    &HexIdx[nh],
    GmfInt,    &HexRef[1],    &HexRef[nh]);
```

3.9 GmfSetBlock

Works exactly as GmfGetBlock except that all lines are written, you cannot specify starting and ending lines in the file since concurrent writing is not supported for now. Note that you still need to set the keyword first with the help of GmfSetKwd() prior to writing the whole data lines with GmfSetBlock().

Example: applying a preprocessing function on vertices before writing them on disk.

```
int ref[nv];
double x[nv], y[nv], z[nv];

GmfSetBlock(MeshIndex, GmfVertices, 1, nv, 0, NULL, FlipRefs, ref,
    GmfDouble, &x[1],    &x[nv],
    GmfDouble, &y[1],    &y[nv],
```

```

        GmfDouble, &z[1],    &z[nv],
        GmfInt,    &ref[1], &ref[nv]);

FlipRefs(int64_t begin, int64_t end, void *data)
{
    int *ref = (int *)data;
    int64_t i;

    for(i=begin;i<=end;i++)
        if(ref[i] == 1)
            ref[i] = 2;
        else
            ref[i] = 1;
}

```

3.10 GmfSetHONodesOrdering

This command sets a special high-order nodes ordering for the specified element. There is, unfortunately, as many HO node ordering in each kinds of elements as there are programmers ! It is then useless to try to find a common node ordering in any high-order element so it was decided to add a new set of keywords (like *GmfTrianglesP2Ordering*), that map the sequential finite element ordering with the Bezier indices. When reading a HO mesh, you may provide the libMeshb with your own ordering table, as defined bellow, along with the one that you may have found in the processed mesh file, so that the *GmfGetBlock()* function will transparently reorder the nodes with each elements in your own way.

```

int GmfSetHONodesOrdering( int64_t MeshIndex, int Keyword,
                           int *YourOrder, int *FileOrdering );

```

MeshIdx: the index returned by *GmfOpenMesh()* must be provided.

KeyWord: code of the keyword whose lines of data are to be read.

YourOrder: a pointer to your ordering table.

FileOrdering: a pointer to the ordering table found in the mesh file.

Example: reading and reordering Q2 quads.

This example reads the ordering information stored in the *GmfQuadrilateralsQ2Ordering* keyword, calls the *GmfSetHONodesOrdering()* procedure to link the required ordering with that from the file, and finally reads the Q2 quads.

```

int quad[nq];
int FileOrdering[9][2];
int MyOrdering[9][2] = {
    {0,0}, {1,0}, {2,0},
    {0,1}, {1,1}, {2,1},
    {0,2}, {1,2}, {2,2} };

GmfGetBlock(MeshIndex, GmfQuadrilateralsQ2Ordering, 1, 9, 0, NULL,
            NULL, GmfIntTab, 9, FileOrdering[0], FileOrdering[8]);
GmfSetHONodesOrdering( MeshIndex, GmfQuadrilateralsQ2,
                        MyOrdering, FileOrdering );
GmfGetBlock(MeshIndex, GmfQ2Quadrilaterals, 1, nq, 0, NULL,
            NULL, GmfIntTable, 9, &quad[1], &quad[nq]);

```

4 Keywords

4.1 List of basic keywords

Those are topologic and geometric data types, commonly used in meshes such as vertices, triangles or normal vectors. Consequently they can only be used in *.mesh* or *.meshb* files.

They are made of a header, indicating the keyword code and the number of data lines stored in the file, followed by as many lines as stated.

Each data line format is described in the following table:

keyword	
data	description
Comments	
1 string	each strings cannot exceed 256 characters including the trailing 0
Corners	
1 integer	vertex index: this vertex is a geometric corner
Edges	
3 integers	vertex indices and a reference
Hexahedra	
9 integers	vertex indices and a reference
Normals	
2 or 3 reals	normal vector: 2 or 3 components depending on the mesh dimension
NormalAtQuadrilateralVertices	
4 integers	there must be as many NormalAtQuadrilateralVertices as there are Quadrilaterals in a mesh, each NormalAtQuadrilateralVertices line pointing implicitly to the respective quad. The four integers are associated with the quad vertices, they are indices pointing to a normal in the Normals table.
NormalAtTriangleVertices	
3 integers	there must be as many NormalAtTriangleVertices as there are Triangles in a mesh, each NormalAtTriangleVertices line pointing implicitly to the respective triangle. The three integers are associated with the triangle vertices, they are indices pointing to a normal in the Normals table.
NormalAtVertices	
2 integers	first integer points to a vertex and the second one points to the associated normal vector index
Polygons	

9 integers	Arbitrary polygonal face: can store up to 8 vertex indices and a reference, Useless indices are set to 0
Polyhedra	
9 integers	Arbitrary polyhedron: can store up to 32 polygonal face indices and a reference. Useless indices are set to 0. Caution: indices point to faces, not to vertices as other volume elements do.
Prisms	
7 integers	vertex indices and a reference
Pyramids	
6 integers	vertex indices and a reference
Quadrilaterals	
5 integers	vertex indices and a reference
RequiredEdges	
1 integer	edge index: this edge is required can not be modified
RequiredQuadrilaterals	
1 integer	quad index: this quad is required can not be modified
RequiredTriangles	
1 integer	triangle index: this triangle is required can not be modified
RequiredVertices	
1 integer	vertex index: this vertex is required can not be modified
Ridges	
1 integer	edge index: this edge is a ridge (geometric sharp angle)
Tangents	
2 or 3 reals	tangent vector: 2 or 3 components depending on the mesh dimension
TangentAtEdgeVertices	
3 integers	first integer points to an edge and the last two one points to the associated tangent vector indices
TangentAtVertices	
2 integers	first integer points to a vertex and the second one points to the associated tangent vector index
Tetrahedra	
5 integers	vertex indices and a reference
Triangles	
4 integers	vertex indices and a reference
Vertices	
2 or 3 reals + 1 integer	vertex coordinates followed by a reference

4.2 List of keywords describing geometric properties

keyword	
data	description
EdgesOnGeometricEdges	
2 integers	edge index from the source mesh and the corresponding edge index it is projected on in the geometric support mesh
TrianglesOnGeometricQuadrilaterals	
2 integers	triangle index from the source mesh and the corresponding quad index it is projected on in the support mesh
TrianglesOnGeometricTriangles	
2 integers	triangle index from the source mesh and the corresponding triangle index it is projected on in the geometric support mesh
PeriodicEdges	
2 integers	indices of linked entities
PeriodicQuadrilaterals	
2 integers	indices of linked entities
PeriodicTriangles	
2 integers	indices of linked entities
PeriodicVertices	
2 integers	indices of linked entities
QuadrilateralsOnGeometricQuadrilaterals	
2 integers	quad index from the source mesh and the corresponding quad index it is projected on in the geometric support mesh
QuadrilateralsOnGeometricTriangles	
2 integers	quad index from the source mesh and the corresponding triangle index it is projected on in the geometric support mesh
VerticesOnGeometricEdges	
2 integers and 2 reals	index of a vertex and the edge index in the geometric support mesh it is projected on followed by the barycentric position on this edge and the distance from it
VerticesOnGeometricQuadrilaterals	
2 integers and 3 reals	index of a vertex and the quad index in the geometric support mesh it is projected on followed by the barycentric position on this quad and the distance from it
VerticesOnGeometricTriangles	
2 integers and 3 reals	index of a vertex and the triangle index in the geometric support mesh it is projected on followed by the barycentric position on this triangle and the distance from it

VerticesOnGeometricVertices	
2 integers	vertex index from the source mesh and the corresponding vertex index it is projected on in the geometric support mesh

4.3 List of High Order elements keywords

keyword	
data	description
EdgesP2	
4 integers	two vertex nodes first then the middle node index a finally the reference
EdgesP2Ordering	
1 integer	one single Bezier index for each of the three vertices
EdgesP3	
5 integers	two vertex nodes first then the two middle nodes index a finally the reference
EdgesP3Ordering	
1 integer	one single Bezier index for each of the four vertices
EdgesP4	
6 integers	two vertex nodes first then the three middle nodes index a finally the reference
ExtraVerticesAtEdges	
n integers	the first integer points to a P1 edge and the remaining $n - 1$ point to middle nodes
ExtraVerticesAtHexahedra	
n integers	the first integer points to a P1 hexahedra and the remaining $n - 1$ point to middle nodes
ExtraVerticesAtPrisms	
n integers	the first integer points to a P1 prism and the remaining $n - 1$ point to middle nodes
ExtraVerticesAtQuadrilaterals	
n integers	the first integer points to a P1 quad and the remaining $n - 1$ point to middle nodes
ExtraVerticesAtTetrahedra	
n integers	the first integer points to a P1 tetrahedra and the remaining $n - 1$ point to middle nodes
ExtraVerticesAtTriangles	
n integers	the first integer points to a P1 triangle and the remaining $n - 1$ point to middle nodes

HexahedraQ2	
28 integers	27 vertex indices and a reference
HexahedraQ2Ordering	
3 integers	a set of three Bezier indices for each of the 27 vertices
PrismsP2	
19 integers	18 vertex indices and a reference
PrismsP2Ordering	
4 integers	a set of four Bezier indices for each of the 18 vertices
PyramidsP2	
15 integers	14 vertex indices and a reference
PyramidsP2Ordering	
3 integers	a set of three Bezier indices for each of the 14 vertices
QuadrilateralsQ2	
10 integers	9 vertex indices and a reference
QuadrilateralsQ2Ordering	
2 integers	a set of two Bezier indices for each of the 9 vertices
QuadrilateralsQ3	
17 integers	16 vertex indices and a reference
QuadrilateralsQ3Ordering	
2 integers	a set of two Bezier indices for each of the 16 vertices
QuadrilateralsQ4	
26 integers	25 vertex indices and a reference
TetrahedraP2	
11 integers	10 vertex indices and a reference
TetrahedraP2Ordering	
4 integers	a set of four Bezier indices for each of the 10 vertices
TrianglesP2	
7 integers	6 vertex indices and a reference
TrianglesP2Ordering	
3 integers	a set of three Bezier indices for each of the 6 vertices
TrianglesP3	
11 integers	10 vertex indices and a reference
TrianglesP3Ordering	
3 integers	a set of three Bezier indices for each of the 10 vertices
TrianglesP4	
16 integers	15 vertex indices and a reference

4.4 List of solution keywords

Those keywords are computation related and are to be used in *.sol* or *.solb* files.

They are made of an extended solution header and multiple data lines.

The header is similar to its mesh counterpart, but adds a solution format table to describe the number of fields and their types (scalar, vector or matrix) associated with each mesh entity.

There are basically two ways to store solutions associated with a mesh:

- Direct way. SolAtElement like keywords store data fields directly associated with each element.
- Indirect way. At first, data are directly stored for each vertex via the DSolAtVertices keyword. Then, ISolAtElements like keywords will have each element vertices pointing indirectly to a DSolAtVertices solution.

keyword	
data	description
DSolAtVertices	
SolSize * reals	as many reals as stated in the DSolAtVertices keyword header
ISolAtEdges	
2 integers	there must be as many ISolAtEdges as there are Edges in a mesh, each ISolAtEdges line pointing implicitly to the respective edge. The two integers are associated with the edge vertices, they are indices pointing to solutions fields in the DSolAtVertices table.
ISolAtHexahedra	
8 integers	there must be as many ISolAtHexahedra as there are Hexahedra in a mesh, each ISolAtHexahedra line pointing implicitly to the respective hex. The eight integers are associated with the hex vertices, they are indices pointing to solutions fields in the DSolAtVertices table.
ISolAtPyramids	
5 integers	there must be as many ISolAtPyramids as there are Pentahe-dra in a mesh, each ISolAtPyramids line pointing implicitly to the respective pyramid. The five integers are associated with the pyramid's vertices, they are indices pointing to solutions fields in the DSolAtVertices table.
ISolAtPrisms	

6 integers	there must be as many ISolAtPrisms as there are Pentahedra in a mesh, each ISolAtPrisms line pointing implicitly to the respective prism. The six integers are associated with the prism's vertices, they are indices pointing to solutions fields in the DSolAtVertices table.
ISolAtQuadrilaterals	
4 integers	there must be as many ISolAtQuadrilaterals as there are Quadrilaterals in a mesh, each ISolAtQuadrilaterals line pointing implicitly to the respective quad. The four integers are associated with the quad vertices, they are indices pointing to solutions fields in the DSolAtVertices table.
ISolAtTetrahedra	
4 integers	there must be as many ISolAtTetrahedra as there are Tetrahedra in a mesh, each ISolAtTetrahedra line pointing implicitly to the respective tet. The four integers are associated with the tet vertices, they are indices pointing to solutions fields in the DSolAtVertices table.
ISolAtTriangles	
3 integers	there must be as many ISolAtTriangles as there are Triangles in a mesh, each ISolAtTriangles line pointing implicitly to the respective triangles. The three integers are associated with the triangle vertices, they are indices pointing to solutions fields in the DSolAtVertices table.
ISolAtVertices	
1 integer	there must be as many ISolAtVertices as there are Vertices in a mesh, each ISolAtVertices line pointing implicitly to the respective vertex. The integer is an index pointing to a solutions field in the DSolAtVertices table.
SolAtEdges	
SolSize * reals	as many reals as stated in the DSolAtEdges keyword header
SolAtHexahedra	
SolSize * reals	as many reals as stated in the SolAtHexahedra keyword header
SolAtPyramids	
SolSize * reals	as many reals as stated in the SolAtPyramidamids keyword header
SolAtPrisms	
SolSize * reals	as many reals as stated in the SolAtPrisms keyword header
SolAtQuadrilaterals	

SolSize * reals	as many reals as stated in the SolAtQuadrilaterals keyword header
SolAtTetrahedra	
SolSize * reals	as many reals as stated in the SolAtTetrahedra keyword header
SolAtTriangles	
SolSize * reals	as many reals as stated in the SolAtTriangles keyword header
SolAtVertices	
SolSize * reals	as many reals as stated in the SolAtVertices keyword header

4.5 Miscellaneous keywords

Finally, those basic keywords have no header and contain only one line of data, most often giving global information on the mesh or the solution file.

keyword	
data	description
AngleOfCornerBound	
1 real	threshold angle for automatic sharp features detection, in degrees
BoundingBox	
4 or 6 reals	the box coordinates bounding the whole mesh: x_{min} , x_{max} , y_{min} , y_{max} and z_{min} and z_{max} (in three dimensional case only)
CoarseHexahedra	
1 integer	hexahedra index that is too big to capture the surface geometry
DRefGroups	
1 string and 3 integers	name of the super group, group index, type of elements and number of references included
IRefGroups	
2 integers	element keyword and element index
Iterations	
1 integer	discretionary iteration counter
PrivateTable	
1 integer	free form table
SubDomainFromGeom	
3 integers	triangle index, orientation (+1 or -1) and subdomain reference
Time	
1 real	discretionary time counter