Table 3: Audio temporal grounding results. mIoU represents the mean IoU. R1@.3 and R1@.5 denote Recall@1 across IoU thresholds of 0.3 and 0.5, respectively. `SpotSound-Q` and `SpotSound-A` denotes the integration of the SpotSound method with Qwen2 Audio and Audio Flamingo 3, respectively. Best results are in bold, and second-best are underlined.

Models	Clotho-Moment			UnAV-100 subset			**SpotSound-Bench**			AudioGrounding		
	R1@.3	R1@.5	mIoU	R1@.3	R1@.5	mIoU	R1@.3	R1@.5	mIoU	R1@.3	R1@.5	mIoU
Non-LLM Models												
WTATG [48]	12.1	6.3	9.1	53.0	37.0	38.4	47.0	26.7	32.3	72.5	53.7	51.4
AM-DETR [34]	89.8	88.0	80.9	59.0	46.0	42.8	30.0	19.7	22.5	52.5	15.6	30.2
Proprietary Models												
Gemini-2.5-Flash [8]	45.7	33.7	36.9	48.0	37.0	35.6	32.7	28.0	23.2	51.8	36.2	37.1
Gemini-2.5-Pro [8]	40.4	32.5	32.5	39.0	35.0	34.6	19.7	17.0	18.9	45.3	31.7	33.5
Open-Source Models												
Kimi-Audio [9]	0.7	0.1	0.9	8.0	2.0	5.3	2.7	0.7	2.4	4.6	2.8	4.9
TimeAudio [45]	39.5	24.9	28.6	21.0	7.0	16.0	8.7	1.3	11.0	83.3	68.7	67.4
Qwen2-Audio [6]	6.1	1.3	5.7	14.0	4.0	9.7	7.3	3.3	6.2	50.3	29.3	37.0
`SpotSound-Q`	**93.6**	**91.2**	85.4	**88.0**	**74.0**	**72.4**	62.3	45.0	46.6	87.2	66.1	67.8
Audio Flamingo 3 [13]	32.9	21.8	22.6	35.0	24.0	25.0	10.7	3.7	9.1	66.9	42.0	47.5
`SpotSound-A`	93.4	91.0	**85.6**	86.0	**74.0**	69.8	**69.0**	**53.3**	**52.7**	**90.1**	**74.8**	**70.3**