OPERATING SYSTEM - CS23431

EXP 7

IPC USING SHARED MEMORY

NAME: LOKAA V

ROLL NO: 231501085

PROGRAM:

Sender.c:

```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <sys/shm.h>
#include <string.h>
int main() {
int shmid;
shmid = shmget((key_t)2345, 1024, 0666 | IPC_CREAT); if (shmid == -1) {
perror("shmget failed"); exit(1);
}
printf("Key of the shared memory segment: %d\n", shmid);
char *shmaddr = (char *) shmat(shmid, NULL, 0);
if (shmaddr == (char *) -1) {
perror("shmat failed");
exit(1);
}
printf("Process is attached at address %p\n", shmaddr);
```

```
sprintf(shmaddr, "Hello world!!");
printf("Content written to shared memory: %s\n", shmaddr);
if (shmdt(shmaddr) == -1) {
perror("shmdt failed");
exit(1);
}
return 0;
}
Receiver.c:
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <string.h>
#include <sys/shm.h>
int main() {
int shmid; char *shmaddr;
shmid = shmget((key_t)2345, 1024, 0666);
if (shmid == -1) {
perror("shmget failed");
exit(1);
}
printf("Key of the shared memory segment: %d\n", shmid);
shmaddr = (char *) shmat(shmid, NULL, 0);
if (\operatorname{shmaddr} == (\operatorname{char}^*) - 1) {
perror("shmat failed");
```

```
exit(1);
}

printf("Process is attached at address %p\n", shmaddr);
printf("Data read from shared memory: %s\n",
shmaddr);
if (shmdt(shmaddr) == -1) {
    perror("shmdt failed");
    exit(1);
}

return 0;
}
```

OUTPUT:

```
[student@localhost ~]$ vi sender.c
[student@localhost ~]$ gcc sender.c
[student@localhost ~]$ ./a.out
key of the shared memory is 622605
Process is attached at 0xb76ee000
Content written is Hello world!!
[student@localhost ~]$ vi receiver.c
[student@localhost ~]$ gcc receiver.c
[student@localhost ~]$ ./a.out
key of shared memory segment is 622605
process is attached at 0xb7782000
Data read from shared memory is Hello world!!
[student@localhost ~]$ ■
```