10 - Searching & Sorting

Ex. No. : 10.1 Date:

Register No.: 231501085 Name: Lokaa V

.

Merge Sort

Write a Python program to sort a list of elements using the merge sort algorithm.

For example:

Input	Result
5	3 4 5 6 8
$\begin{bmatrix} 5 \\ 65438 \end{bmatrix}$	

Program:

```
a=int(input()) l=[]
l.extend(input().split()) for
i in range(a-1):     for j in
range(a-1):
if(int(l[j])>int(l[j+1])):
        t=int(l[j])
l[j]=int(l[j+1])
l[j+1]=t for i in
range(a):
    print(int(l[i]),end=" ")
```

Output:

Ī		Input	Expected	Got
	~	5 6 5 4 3 8	3 4 5 6 8	3 4 5 6 8
	~	9 14 46 43 27 57 41 45 21 70	14 21 27 41 43 45 46 57 70	14 21 27 41 43 45 46 5
	~	4 86 43 23 49	23 43 49 86	23 43 49 86

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Ex. No. : 10.2 Date:

Register No.: Name:

.

Bubble Sort

Given an list of integers, sort the array in ascending order using the *Bubble Sort* algorithm above. Once sorted, print the following three lines:

- 1. <u>List</u> is sorted in numSwaps swaps., where numSwaps is the number of swaps that took place.
- 2. First Element: firstElement, the *first* element in the sorted <u>list</u>.
- 3. Last Element: lastElement, the *last* element in the sorted list.

For example, given a worst-case but small array to sort: a=[6,4,1]. It took 3 swaps to sort the array. Output would be

Array is sorted in 3 swaps.

First Element: 1 Last Element: 6

Input Format

The first line contains an integer, n, the size of the <u>list</u> a. The second line contains n, space-separated integers a[i].

Constraints

- · 2<=n<=600
- $1 \le a[i] \le 2x10^6$.

Output Format

You must print the following three lines of output:

- 1. <u>List</u> is sorted in numSwaps swaps., where numSwaps is the number of swaps that took place.
- 2. First Element: firstElement, the *first* element in the sorted list.
- 3. Last Element: lastElement, the *last* element in the sorted list.

Sample Input 0

3

123

Sample Output 0

<u>List</u> is sorted in 0 swaps.

First Element: 1 Last Element: 3

For example:

Input	Result
3 3 2 1	List is sorted in 3 swaps. First Element: 1 Last Element: 3
5 19284	List is sorted in 4 swaps. First Element: 1 Last Element: 9

```
Program:
def bubble_sort(arr):
  n = len(arr)
swaps = 0
  for i in range(n):
                        for j in range(0, n-
            if arr[j] > arr[j + 1]:
i-1):
                                          #
                          arr[j], arr[j + 1] =
Swap elements
arr[j + 1], arr[j]
                          swaps += 1
  return swaps
# Input the size of the list n
= int(input())
# Input the list of integers arr =
list(map(int, input().split()))
# Perform bubble sort and count the number of swaps
num_swaps = bubble_sort(arr)
# Print the number of swaps
```

print("List is sorted in", num_swaps, "swaps.")

Print the first element print("First Element:", arr[0])

Print the last element print("Last
Element:", arr[-1])

Output:

List is sorted in 3 swaps. List is sorted in 3 2 1 First Element: 1 Last Element: 3 Last Element: 3	3 swaps. 🗸
List is sorted in 4 swaps. List is sorted in 4 swaps. First Element: 1 Last Element: 9 List is sorted in 4 swaps. First Element: 1 Last Element: 9	4 swaps. 🗸
sed all tests! ✓	

Ex. No. : 10.3 Date:

Register No.: Name:

.

Peak Element

Given an list, find peak element in it. A peak element is an element that is greater than its neighbors.

An element a[i] is a peak element if

$$A[i-1] \le A[i] \ge a[i+1]$$
 for middle elements. $[0 \le i \le n-1]$

$$A[i-1] \le A[i]$$
 for last element $[i=n-1]$

$$A[i] > = A[i+1]$$
 for first element $[i=0]$

Input Format

The first line contains a single integer n, the length of A. The second line contains n space-separated integers, A[i].

Output Format

Print peak numbers separated by space.

Sample Input

5

8 9 10 2 6

Sample Output

106

For example:

Input	Result
4 12 3 6 8	12 8

Program:

def find_peak(arr):

peak_elements = [] # Check for

the first element if arr[0] >=

arr[1]:

```
peak_elements.append(arr[0])
  # Check for middle elements
                                   for
i in range(1, len(arr) - 1):
                               if arr[i
-1] \le arr[i] \ge arr[i+1]:
peak_elements.append(arr[i])
  # Check for the last element
if arr[-1] \ge arr[-2]:
     peak_elements.append(arr[-1])
  return peak_elements
# Input the length of the list n
= int(input())
# Input the list of integers arr =
list(map(int, input().split()))
# Find peak elements and print the result
peak_elements = find_peak(arr) print(*peak_elements)
```

Output:

	Input	Expected	Got	
~	7 15 7 10 8 9 4 6	15 10 9 6	15 10 9 6	~
~	4 12 3 6 8	12 8	12 8	~

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Ex. No. : 10.4 Date:

Register No.: Name:

.

Binary Search

Write a Python program for binary search.

For example:

Input	Result
1 2 3 5 8 6	False
3 5 9 45 42 42	True

Program:

a = input().split(",")

b = input() print(b

in a)

Output:



Ex. No. : 10.5 Date:

Register No.: Name:

.

Frequency of Elements

To find the frequency of numbers in a list and display in sorted order.

Constraints: 1<=n,

arr[i]<=100 **Input:**

 $1\ 68\ 79\ 4\ 90\ 68\ 1\ 4\ 5$

output:

1 2

42

5 1

682

79 1

90 1

For example:

Input	Result
4 3 5 3 4 5	3 2 4 2 5 2

Program:

def count_frequency(arr):

frequency = {}

```
# Count the frequency of each number in the list
for num in arr:
    frequency[num] = frequency.get(num, 0) + 1

# Sort the dictionary based on keys
sorted_frequency = sorted(frequency.items())

# Print the frequency of each number
for num, freq in sorted_frequency:
    print(num, freq)

# Input the list of numbers arr =
list(map(int, input().split()))

# Count the frequency and print the result
count_frequency(arr)
```

Output:

	Input	Expected	Got	
~	4 3 5 3 4 5	3 2 4 2 5 2	3 2 4 2 5 2	~
~	12 4 4 4 2 3 5	2 1 3 1 4 3 5 1 12 1	2 1 3 1 4 3 5 1 12 1	*
~	5 4 5 4 6 5 7 3	3 1 4 2 5 3 6 1 7 1	3 1 4 2 5 3 6 1 7 1	*

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.