IncidentLens AI test document

Page 1 - API request timeout

Fictional training material for PDF extraction and RAG practice.

Simulated incident

A test integration sent a request but did not receive a response within its configured waiting period. The incident records status_code as null because no HTTP response status was recorded. The timeout alone does not identify the underlying cause.

Possible causes

The server may be slow, a network connection may be delayed, or an upstream dependency may be unavailable. These are hypotheses to investigate, not confirmed findings.

Troubleshooting steps

Record the endpoint, request method and incident time. Check application logs around that time. Inspect dependency response times and network connectivity. Compare the failing request with a known successful request.

Missing evidence

Request ID, server logs, dependency timings and the actual timeout configuration would help explain this simulated failure.

IncidentLens AI test document

Page 2 - HTTP 500 server error

Fictional training material for PDF extraction and RAG practice.

Simulated incident

A test API returned HTTP 500. This indicates a server-side error, but the status code alone does not reveal its precise cause. Do not assume an unhandled exception without supporting logs.

Possible causes

An application defect, a database operation failure or a failing dependency could be involved. Confirm the relevant evidence before selecting a root cause.

Troubleshooting steps

Locate the request ID and timestamp. Review server logs for that request. Check database and dependency health. Inspect recent deployments and compare the request with a successful example.

Missing evidence

The response body, a matching server log entry, deployment history and dependency errors would support further investigation.

IncidentLens AI test document

Page 3 - AI provider unavailable

Fictional training material for PDF extraction and RAG practice.

Simulated incident

In IncidentLens, the analysis router maps Gemini provider errors 429 and 503 to an HTTP 503 response. This describes the behavior of the project code, not a real provider outage.

Expected application behavior

Return a helpful message that AI analysis is unavailable. Include the provider code as configured in the current router. Do not return an invented analysis when the provider call failed.

Troubleshooting steps

Inspect the recorded provider error code and message. Check the configured model and the account quota or limits. For a temporary availability error, retry later according to the provider guidance. Do not assume all errors have the same cause.

Unit test approach

Replace the analysis function with a mock that raises APIError. Run the test once for provider code 429 and once for 503. Verify that the endpoint function raises HTTPException with status_code 503 and the expected detail message.