

Week 3 – 1:

--Coding-C-Language Features-Optional.

ROLL NO.:240801182

Name: Lokesh M

Q1) Write a program to read two integer values and print true if both the numbers end with the same digit, otherwise print false.

Example: If 698 and 768 are given, program should print true as they both end with 8.

Sample Input 1

25 53

Sample Output 1

false

Sample Input 2

27 77

Sample Output 2

true

Code:

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Saturday, 26 October 2024, 2:51 PM
Duration	58 days 2 hours

Question 1

Correct

Marked out of 3.00

[Flag question](#)

Write a program to read two integer values and print true if both the numbers end with the same digit, otherwise print false. Example: If 698 and 768 are given, program should print true as they both end with 8. Sample Input 1 25 53 Sample Output 1 false Sample Input 2 27 77 Sample Output 2 true

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int num1,num2;
5     scanf("%d%d",&num1,&num2);
6     int lastDigit1 = num1%10;
7     int lastDigit2 = num2%10;
8     if(lastDigit1 == lastDigit2)
9     {
10         printf("true\n");
11     }else{
12         printf("false\n");
13     }
14     return 0;
15 }
```

OUTPUT:

	Input	Expected	Got	
✓	25 53	false	false	✓
✓	27 77	true	true	✓

Passed all tests! ✓

Q2) In this challenge, we're getting started with conditional statements.

Task

Given an integer, n , perform the following conditional actions:

- If n is odd, print Weird
- If n is even and in the inclusive range of 2 to 5, print Not Weird
- If n is even and in the inclusive range of 6 to 20, print Weird
- If n is even and greater than 20, print Not Weird

Complete the stub code provided in your editor to print whether or not n is weird.

Input Format

A single line containing a positive integer, n .

Constraints

- $1 < n < 100$

Output Format

Print Weird if the number is weird; otherwise, print Not Weird.

Sample Input 0

3

Sample Output 0

Weird

Code:

```

1  #include<stdio.h>
2  int main()
3  {
4      int n;
5      scanf("%d",&n);
6      if(n%2!=0){
7          printf("Weird\n");
8      }else if(n>=2 && n<=5)
9      {
10         printf("Not Weird");
11     }else if(n>=6 && n<=20)
12     {
13         printf("Weird");
14     }else
15     {
16         printf("Not Weird");
17     }
18     return 0;
19 }

```

OUTPUT:

	Input	Expected	Got	
✓	3	Weird	Weird	✓
✓	24	Not Weird	Not Weird	✓

Passed all tests! ✓

Q3) Three numbers form a Pythagorean triple if the sum of squares of two numbers is equal to the square of the third.

For example, 3, 5 and 4 form a Pythagorean triple, since $3^2 + 4^2 = 25 = 5^2$

You are given three integers, a, b, and c. They need not be given in increasing order. If they form a Pythagorean triple, then print "yes", otherwise, print "no". Please note that the output message is in small letters.

Sample Input 1

3

5

4

Sample Output 1

Yes

Code:

```

1 | #include<stdio.h>
2 | int main()
3 | {
4 |     int a,b,c;
5 |     scanf("%d%d%d",&a,&b,&c);
6 |     if((a*a+b*b==c*c)|| (a*a+c*c==b*b) || (b*b+c*c==a*a))
7 |     {
8 |         printf("yes\n");
9 |     }else{
10 |         printf("no\n");
11 |     }
12 |     return 0;
13 | }

```

OUTPUT:

	Input	Expected	Got	
✓	3 5 4	yes	yes	✓
✓	5 8 2	no	no	✓

Passed all tests! ✓