

Case:

```
mysql> DELIMITER //
```

```
mysql>
```

```
mysql> CREATE PROCEDURE grade_example(IN mark INT)
```

```
  -> BEGIN
```

```
  ->     CASE
```

```
  ->         WHEN mark >= 90 THEN
```

```
  ->             SELECT 'A+' AS grade;
```

```
  ->         WHEN mark >= 80 THEN
```

```
  ->             SELECT 'A' AS grade;
```

```
  ->         WHEN mark >= 70 THEN
```

```
  ->             SELECT 'B' AS grade;
```

```
  ->         WHEN mark >= 60 THEN
```

```
  ->             SELECT 'C' AS grade;
```

```
  ->         ELSE
```

```
  ->             SELECT 'D' AS grade;
```

```
  ->     END CASE;
```

```
  -> END //
```

```
Query OK, 0 rows affected (0.01 sec)
```

```
mysql>
```

```
mysql> DELIMITER ;
```

```
mysql> CALL grade_example(85);
```

grade
A

```
1 row in set (0.00 sec)
```

```
Query OK, 0 rows affected (0.01 sec)
```

```
mysql> CALL grade_example(92);
```

grade
A+

```
1 row in set (0.00 sec)
```

```
Query OK, 0 rows affected (0.01 sec)
```

Loop:

```

mysql> DELIMITER //
mysql>
mysql> CREATE PROCEDURE loop_example()
-> BEGIN
->     DECLARE i INT DEFAULT 1;
->
->     simple_loop: LOOP
->         SELECT i AS number;
->
->         SET i = i + 1;
->
->         IF i > 5 THEN
->             LEAVE simple_loop;
->         END IF;
->     END LOOP simple_loop;
-> END //
Query OK, 0 rows affected (0.02 sec)

mysql>
mysql> DELIMITER ;

```

```

mysql> CALL loop_example();
+-----+
| number |
+-----+
|      1 |
+-----+
1 row in set (0.00 sec)

+-----+
| number |
+-----+
|      2 |
+-----+
1 row in set (0.00 sec)

+-----+
| number |
+-----+
|      3 |
+-----+
1 row in set (0.01 sec)

+-----+
| number |
+-----+
|      4 |
+-----+
1 row in set (0.01 sec)

```

```
+-----+
| number |
+-----+
|      5 |
+-----+
1 row in set (0.01 sec)

Query OK, 0 rows affected (0.01 sec)
```