

```
mysql> DELIMITER //
mysql>
mysql> CREATE FUNCTION get_grade(mark INT)
    -> RETURNS VARCHAR(5)
    -> DETERMINISTIC
    -> BEGIN
    ->     DECLARE grade VARCHAR(5);
    ->
    ->     IF mark >= 90 THEN
    ->         SET grade = 'A+';
    ->     ELSEIF mark >= 80 THEN
    ->         SET grade = 'A';
    ->     ELSEIF mark >= 70 THEN
    ->         SET grade = 'B';
    ->     ELSEIF mark >= 60 THEN
    ->         SET grade = 'C';
    ->     ELSE
    ->         SET grade = 'D';
    ->     END IF;
    ->
    ->     RETURN grade;
    -> END //
Query OK, 0 rows affected (0.04 sec)
```

```
mysql> DELIMITER ;
mysql> SELECT get_grade(85) AS grade;
+-----+
| grade |
+-----+
| A     |
+-----+
1 row in set (0.01 sec)

mysql> ^C
mysql> SELECT student_id, name, marks, get_grade(marks) AS grade
    -> FROM student;
+-----+-----+-----+-----+
| student_id | name  | marks | grade |
+-----+-----+-----+-----+
|          101 | Arun  |    85 | A     |
|          102 | Bala  |    78 | B     |
|          103 | Kavir |    92 | A+    |
|          104 | Ravi  |    88 | A     |
+-----+-----+-----+-----+
4 rows in set (0.00 sec)

mysql> DROP FUNCTION get_grade;
Query OK, 0 rows affected (0.03 sec)
```