

```
mysql> CREATE TABLE student_log (
  ->     log_id INT AUTO_INCREMENT PRIMARY KEY,
  ->     student_id INT,
  ->     name VARCHAR(50),
  ->     action VARCHAR(30),
  ->     log_time TIMESTAMP DEFAULT CURRENT_TIMESTAMP
  -> );
Query OK, 0 rows affected (0.13 sec)

mysql> SELECT * FROM student_log;
Empty set (0.01 sec)
```

```
mysql> SELECT * FROM student_log;
Empty set (0.01 sec)

mysql> DELIMITER //
mysql>
mysql> CREATE TRIGGER after_student_insert
  -> AFTER INSERT ON student
  -> FOR EACH ROW
  -> BEGIN
  ->     INSERT INTO student_log(student_id, name, action)
  ->     VALUES (NEW.student_id, NEW.name, 'INSERTED');
  -> END //
Query OK, 0 rows affected (0.03 sec)

mysql>
mysql> DELIMITER ;
mysql> INSERT INTO student
  -> VALUES (105, 'Vijay', 'IT', 81);
Query OK, 1 row affected (0.02 sec)
```

```
mysql> DELIMITER ;
mysql> INSERT INTO student
  -> VALUES (105, 'Vijay', 'IT', 81);
Query OK, 1 row affected (0.02 sec)

mysql> SELECT * FROM student;
+-----+-----+-----+-----+
| student_id | name  | department | marks |
+-----+-----+-----+-----+
| 101        | Arun  | CSE        | 85    |
| 102        | Bala  | ECE        | 78    |
| 103        | Kavın | IT         | 92    |
| 104        | Ravi  | CSE        | 88    |
| 105        | Vijay | IT         | 81    |
+-----+-----+-----+-----+
5 rows in set (0.00 sec)
```

```
mysql> SELECT * FROM student_log;
+-----+-----+-----+-----+-----+
| log_id | student_id | name | action | log_time |
+-----+-----+-----+-----+-----+
| 1 | 105 | Vijay | INSERTED | 2026-08-12 11:53:47 |
+-----+-----+-----+-----+-----+
1 row in set (0.00 sec)
```

```
mysql> SHOW CREATE TRIGGER after_student_insert;
+-----+-----+-----+-----+-----+
| Trigger | sql_mode | SQL Original Statement |
+-----+-----+-----+-----+-----+
| character_set_client | collation_connection | Database Collation | Created |
+-----+-----+-----+-----+-----+
| after_student_insert | ONLY_FULL_GROUP_BY,STRICT_TRANS_TABLES,NO_ZERO_IN_DATE,NO_ZERO_DATE,ERROR_FOR_DIVISION_BY_ZERO,NO_ENGINE_SUBSTITUTION | CREATE DEFINER='root'@'localhost' TRIGGER 'after_student_insert' AFTER INSERT ON 'student' FOR EACH ROW BEGIN
INSERT INTO student_log(student_id, name, action)
VALUES (NEW.student_id, NEW.name, 'INSERTED');
END | cp850 | cp850_general_ci | utf8mb4_0900_ai_ci | 2026-08-12 11:53:35.70 |
+-----+-----+-----+-----+-----+
1 row in set (0.01 sec)

mysql> DROP TABLE student_log;
Query OK, 0 rows affected (0.04 sec)
```