

```

mysql> CREATE PROCEDURE cursor_example()
-> BEGIN
->     DECLARE done INT DEFAULT 0;
->     DECLARE sname VARCHAR(50);
->     DECLARE smarks INT;
->
->     DECLARE student_cursor CURSOR FOR
->         SELECT name, marks FROM student;
->
->     DECLARE CONTINUE HANDLER FOR NOT FOUND
->         SET done = 1;
->
->     OPEN student_cursor;
->
->     read_loop: LOOP
->
->         FETCH student_cursor INTO sname, smarks;
->
->         IF done = 1 THEN
->             LEAVE read_loop;
->         END IF;
->
->         SELECT sname AS student_name, smarks AS marks;
->
->     END LOOP;
->
->     CLOSE student_cursor;
-> END //
Query OK, 0 rows affected (0.02 sec)

```

```

mysql> CALL cursor_example();
+-----+-----+
| student_name | marks |
+-----+-----+
| Arun         | 85    |
+-----+-----+
1 row in set (0.01 sec)

+-----+-----+
| student_name | marks |
+-----+-----+
| Bala         | 78    |
+-----+-----+
1 row in set (0.02 sec)

+-----+-----+
| student_name | marks |
+-----+-----+
| Kevin        | 92    |
+-----+-----+
1 row in set (0.02 sec)

```

```
+-----+-----+
| student_name | marks |
+-----+-----+
| Ravi        | 88    |
+-----+-----+
1 row in set (0.03 sec)

Query OK, 0 rows affected (0.03 sec)
```