

Create:

```
mysql> CREATE Database collegeDB;
Query OK, 1 row affected (0.02 sec)

mysql> Use collegeDB;
Database changed
mysql> create table Student(StudentID int,Name varchar(50),Age int,Department varchar(50));
Query OK, 0 rows affected (0.06 sec)

mysql> desc Student;
+-----+-----+-----+-----+-----+-----+
| Field      | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| StudentID  | int           | YES  |     | NULL    |       |
| Name       | varchar(50)   | YES  |     | NULL    |       |
| Age        | int           | YES  |     | NULL    |       |
| Department | varchar(50)   | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.01 sec)
```

Alter:

```
mysql> alter table Student ADD Email varchar(50);
Query OK, 0 rows affected (0.09 sec)
Records: 0  Duplicates: 0  Warnings: 0

mysql> Alter table Student Modify Age tinyint;
Query OK, 0 rows affected (0.12 sec)
Records: 0  Duplicates: 0  Warnings: 0
```

```
mysql> Alter Table Student Rename column Department to Dept;
Query OK, 0 rows affected (0.04 sec)
Records: 0  Duplicates: 0  Warnings: 0

mysql> desc Student;
+-----+-----+-----+-----+-----+-----+
| Field      | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| StudentID  | int           | YES  |     | NULL    |       |
| Name       | varchar(50)   | YES  |     | NULL    |       |
| Age        | tinyint       | YES  |     | NULL    |       |
| Dept       | varchar(50)   | YES  |     | NULL    |       |
| Email      | varchar(50)   | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)

mysql> Alter Table Student Drop column Email;
Query OK, 0 rows affected (0.08 sec)
Records: 0  Duplicates: 0  Warnings: 0
```

```
mysql> desc Student;
+-----+-----+-----+-----+-----+-----+
| Field      | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| StudentID  | int           | YES  |     | NULL    |       |
| Name       | varchar(50)   | YES  |     | NULL    |       |
| Age        | tinyint       | YES  |     | NULL    |       |
| Dept       | varchar(50)   | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

Insert:

```
Insert into Student Values(101,"Kishore",19,"CSE"),(102,"Rahul" at line 1
mysql> Insert into Student Values(101,"Kishore",19,"CSE"),(102,"Rahul",19,"ECE");
Query OK, 2 rows affected (0.02 sec)
Records: 2  Duplicates: 0  Warnings: 0
```

```
mysql> select * from Student;
+-----+-----+-----+-----+
| StudentID | Name      | Age | Dept |
+-----+-----+-----+-----+
|          101 | Kishore  | 19  | CSE  |
|          102 | Rahul    | 19  | ECE  |
+-----+-----+-----+-----+
2 rows in set (0.00 sec)
```

Truncate and Drop:

```
mysql> truncate table Student;
Query OK, 0 rows affected (0.07 sec)

mysql> desc Student;
+-----+-----+-----+-----+-----+-----+
| Field      | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| StudentID  | int           | YES  |     | NULL    |       |
| Name       | varchar(50)   | YES  |     | NULL    |       |
| Age        | tinyint       | YES  |     | NULL    |       |
| Dept       | varchar(50)   | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)

mysql> select * from Student;
Empty set (0.00 sec)

mysql> Drop table Student;
Query OK, 0 rows affected (0.04 sec)

mysql> show tables;
Empty set (0.00 sec)
```