

DEVOPS - exercise1


Multi-Service System with Persistent Storage (Service1, Service2, Storage)

This repository contains a simple system with three services, implemented in **different technologies**:

Platform Information

- **Hardware:** Windows Laptop
- **OS:** Windows OS
- **Docker:** 27.2.0
- **Docker Compose:** v4.34.x - desktop
- Git
- .NET 9 SDK (for building Service2 before containerizing, if required)

System Architecture



- **Service1** – Python (FastAPI)
 - The **only service accessible from outside**.
 - Collects system uptime and free disk space.
 - Stores logs in:
 - Shared file volume **vstorage**

- Storage service
 - Forwards requests to **Service2**.
 - Combine status from Service1 and Service2 and returns
 - Endpoints:
 - **GET /status** → Analyze uptime , space and Append new log entry (**text/plain**)
 - **GET /log** → Retrieve all logs (**text/plain**)
- **Service2** – .NET 9 Web API
 - Collects system uptime and free disk space.
 - Stores logs in:
 - Shared file volume **vstorage**
 - Storage service
 - Returns status info back to Service1.
 - Endpoints:
 - **GET /status** → Analyze uptime , space and Append new log entry (**text/plain**)
- **Storage** – Node.js (Express)
 - Simple REST API for persistent logs.
 - **storage_data**: a named Docker volume mounted only into Storage at **/app/data** and used to persist its internal **log.txt**.
 - Persists logs between container restarts using Docker volumes.
 - Endpoints:
 - **POST /log** → Append new log entry (**text/plain**)
 - **GET /log** → Retrieve all logs (**text/plain**)
- **vstorage** – host file **./vstorage** mounted into Service1 and Service2 at **/app/vstorage** and appended per request. This is the simple shared file method.
- **Networking**
- A single user-defined **services_network** network connects all three services. Only Service1 publishes a host port.

Analysis of Status Records

- **Timestamp**: Using ISO 8601 UTC (**2025-09-28T13:05:35Z**) format as required.
- **Uptime**: Both services report container uptime i.e service starting time and convert to hours with two decimal places.
- **Disk space measurement**:
 - Service1: Reads free disk space on the root filesystem (**/**) in MB using **shutil** library.
 - Service2: Reads free disk space on the root filesystem (**/**) in MB using the **driveinfo** (**/** on **Linux**, **C:** on **Windows**).

Measurement relevance:

- Uptime shows how long the container has been running, not the host.
- Disk space reflects the container's root filesystem, which may differ from the host OS storage.
- Monitor total system resources, such as CPU, memory usage percentages, and container health metrics.

Storage Comparison

1. Host file binding (./vstorage)

- **Pros:**
 - Simple to implement
 - Easy to view and edit files directly on the host (./vstorage)
 - Code changes on host reflect instantly inside the container
 - Persists between container restarts
- **Cons:**
 - File must exist on the host, moving between environments (Linux/Windows/VM/CI) can break.
 - Less secure (host file exposed)
 - Slower than named volumes.
 - Could cause permission issues between containers and host
 - Less isolation and Considered bad practice in production

2. Docker named volume (storage_data)

- **Pros:**
 - Docker manages it fully
 - Portable between different environments (Linux/Windows/VM/CI)
 - Faster than host file
 - Better isolation and security
 - Data persists beyond container lifecycle
- **Cons:**
 - Requires explicit management commands to inspect or clean
 - More complex to access from outside Docker
 - Depends on docker life cycle

How to Run

- Clone the repository using command: `git clone -b exercise1 https://github.com/LokeswariMelapattu/devops-course.git`
- `cd devops-course`
- Build and start: `docker-compose up --build -d`
- Test status flow: `curl localhost:8199/status`
- Fetch first storage log : `curl localhost:8199/log`
- Fetch second storage log : `cat ./vstorage`
- Stop: `docker-compose down`

Cleanup instructions

- Clean the logs from host-file storage: `> ./vstorage`
- Remove the named volume for Storage: `docker volume rm devops-course_storage_data`

Challenges and Problems

- Understanding the difference between container vs host measurements.

- Configuring networking between containers in VirtualBox and Docker
- Managing persistent storage across bind mounts and Docker volumes
- Permission issues for creating hostfile
- A key challenge was maintaining service isolation while enabling necessary inter-service communication. To achieve this, I created a custom `services_network` and exposed only the `Service1` port externally.