

Fast and Fourier ICPC Team Notebook

Contents

1 C++	1
1.1 C++ template	1
1.2 Opcion	2
1.3 Comand to compare output	2
1.3.1 Linux	2
1.3.2 windows	2
1.4 Bits Manipulation	2
1.5 Custom Hash	2
1.6 Trie	2
1.7 Suffix Tree	3
2 Graph algorithms	4
2.1 DFS cpbook	4
2.2 DFS iterativo - Lucas	4
2.3 BFS cpbook	4
2.4 BFS para camino mas corto de UN nodo a todos los DEMAS	5
2.5 BFS bipartito	5
2.6 DFS detect cycle	6
2.7 Dijkstra camino mas corto grafo dirigido CON PESOS($O((V+E)\log V)$)	7
3 Data Structures	7
3.1 unordered_map<clave,valor>(hacer siempre RESERVE)	7
3.1.1 Ejemplo basico Contar frecuencias	7
3.1.2 Buscar existencia de una llave	8
3.1.3 Transformar indices dispersos a continuos	8
3.1.4 Hashing pair	8
3.2 unordered_set<clave>(hacer siempre RESERVE)	8
3.3 unordered_multimap<clave,valorES>(hacer siempre RESERVE)	8
3.3.1 Ejemplo basico	8
3.3.2 Buscar por clave	9
3.3.3 Delete	9
3.4 Disjoint Set Union	9
3.5 Fenwick Tree	10
3.6 Segment Tree	12
3.7 Order Statistics Tree	13
3.7.1 Quick Selet	13
3.8 Ordered Statistics Tree	14

4 Math	14
4.1 Prime Numbers 1-2000	14
4.2 Serie de Fibonacci (hasta $n=20$)	15
4.3 Factorial (hasta $n=20$)	15
4.4 Numeros Triangulares (hasta $n=20$)	15
4.5 Numeros Cuadrados (hasta $n=20$)	16
4.6 Simple Sieve of Eratosthenes $O(n \cdot \log(\log(n)))$ - con $n=1e7$ 1.25 MB	16
4.7 Smallest Prime Factor AND Sieve of Eratosthenes $O(n)$ - con $n=1e7$ 45 MB	16
4.8 Smallest Prime Factor Piton++	16
4.9 Combinatorics	16
4.9.1 Next permutation	16
5 Dynamic Programming	17
6 Miscellaneous	17
6.1 Ternary Search	17

1 C++

1.1 C++ template

```
#include <bits/stdc++.h>
using namespace std;

//IMPRESINDIBLES PARA ICPC
#define form(i, s, e) for(int i = s; i < e; i++)
#define icin(x) \
    int x; \
    cin >> x;
#define llcin(x) \
    long long x; \
    cin >> x;
#define scin(x) \
    string x; \
    cin >> x;
#define endl '\n'
#define S second
#define F first
#define pb push_back
#define sz(x) x.size()
#define all(x) x.begin(), x.end()

typedef long long ll;
typedef vector<int> vi;
typedef vector<vi> vvi;
typedef pair<int, int> pii;

const ll INF = 1e9+7; //tambien es primo
```

```

const double PI = acos(-1);
//UTILS
#define DBG(x) cerr << #x << '=' << (x) << endl
#define coutDouble cout << fixed << setprecision(17)
#define numtobin(n) bitset<32>(n).to_string()
#define bintoint(bin_str) stoi(bin_str, nullptr, 2) //
    bin_str should be a STRING
#define LSONE(S) ((S) & ~(S))

typedef double db;
typedef vector<string> vs;
typedef vector<ll> vll;
typedef vector<vll> vvll;
typedef pair<int, bool> pib;
typedef pair<ll, ll> pll;
typedef vector<pii> vpii;
typedef vector<pib> vpib;
typedef vector<pll> vpll;

int main() {
    ios::sync_with_stdio(0);
    cin.tie(0);
    cout.tie(0);

    icin(nn0)
    while (nn0--) {
    }

    return 0;
}

```

1.2 Opcion

```

// En caso de que no sirva #include <bits/stdc++.h>
#include <algorithm>
#include <iostream>
#include <iterator>
#include <sstream>
#include <fstream>
#include <cassert>
#include <climits>
#include <cstdlib>
#include <cstring>
#include <string>
#include <cstdio>
#include <vector>
#include <cmath>
#include <queue>
#include <deque>
#include <stack>
#include <list>
#include <map>

```

```

#include <set>
#include <bitset>
#include <iomanip>
#include <unordered_map>

////
#include <tuple>
#include <random>
#include <chrono>

```

1.3 Comand to compare output

1.3.1 Linux

```

./programa < in.txt > myout.txt
diff -u out.txt myout.txt

```

1.3.2 windows

```

algo2.exe < in.txt > myout.txt
fc myout.txt out.txt

```

1.4 Bits Manipulation

1.5 Custom Hash

```

struct custom_hash {
    static ll splitmix64(ll x) {
        // http://xorshift.di.unimi.it/splitmix64.c
        x += 0x9e3779b97f4a7c15;
        x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
        x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
        return x ^ (x >> 31);
    }

    size_t operator()(ll x) const {
        static const ll FIXED_RANDOM = chrono::
            steady_clock::now().time_since_epoch().count();
        return splitmix64(x + FIXED_RANDOM);
    }
};

unordered_map<ll, int, custom_hash> mapa;

```

1.6 Trie

```

const static int N = 2e6, alpha = 26, B = 30; // MAX:
    abecedario, bits
int to[N][alpha], cnt[N], sz;
inline int conv(char ch){ return ch - 'a'; } // CAMBIAR
string to_bin(int num, int bits){ // B: Max(bits), bits
    : size
    return bitset<B>(num).to_string().substr(B - bits);}
// AGREGAR LO QUE HAYA QUE RESETEAR !!!!
void init(){
    forn(i, sz+1) cnt[i] = 0, memset(to[i], 0, sizeof to[i]
    );
    sz = 0;
}
void add(const string &s){
    int u = 0;
    for(char ch: s){
        int c = conv(ch);
        if(!to[u][c]) to[u][c] = ++sz;
        u = to[u][c];
    }
    cnt[u]++;
}

```

1.7 Suffix Tree

```

const int N=1000000, // maximum possible number of
    nodes in suffix tree
    INF=1000000000; // infinity constant
string a; // input string for which the suffix tree
    is being built
int t[N][26], // array of transitions (state, letter)
    l[N], // left...
    r[N], // ...and right boundaries of the substring
    of a which correspond to incoming edge
    p[N], // parent of the node
    s[N], // suffix link
    tv, // the node of the current suffix (if we're
    mid-edge, the lower node of the edge)
    tp, // position in the string which corresponds
    to the position on the edge (between l[tp] and r[
    tp], inclusive)
    ts, // the number of nodes
    la; // the current character in the string
void ukkadd(int c) { // add character s to the tree
    suff:; // we'll return here after each
    transition to the suffix (and will add character
    again)
    if (r[tp]<tp) { // check whether we're still within
    the boundaries of the current edge
        // if we're not, find the next edge. If it doesn't
        exist, create a leaf and add it to the tree
        if (t[tp][c]==-1) {t[tp][c]=ts;l[ts]=la;p[ts++]=
        tv;tv=s[tp];tp=r[tp]+1;goto suff;}
    }
}

```

```

    tv=t[tp][c];tp=l[tp];
} // otherwise just proceed to the next edge
if (tp==-1 || c==a[tp]-'a')
    tp++; // if the letter on the edge equal c, go
    down that edge
else {
    // otherwise split the edge in two with middle in
    node ts
    l[ts]=l[tp];r[ts]=tp-1;p[ts]=p[tp];t[ts][a[tp]-'a'
    ]=tv;
    // add leaf ts+1. It corresponds to transition
    through c.
    t[ts][c]=ts+1;l[ts+1]=la;p[ts+1]=ts;
    // update info for the current node - remember to
    mark ts as parent of tp
    l[tp]=tp;p[tp]=ts;t[p[ts]][a[l[ts]]-'a']=ts;ts
    +=2;
    // prepare for descent
    // tp will mark where are we in the current
    suffix
    tv=s[p[ts-2]];tp=l[ts-2];
    // while the current suffix is not over, descend
    while (tp<=r[ts-2]) {tv=t[tp][a[tp]-'a'];tp+=r[tp
    ]-l[tp]+1;}
    // if we're in a node, add a suffix link to it,
    otherwise add the link to ts
    // (we'll create ts on next iteration).
    if (tp==r[ts-2]+1) s[ts-2]=tv; else s[ts-2]=ts;
    // add tp to the new edge and return to add
    letter to suffix
    tp=r[tp]-(tp-r[ts-2])+2;goto suff;
}
}

void build() {
    ts=2;
    tv=0;
    tp=0;
    fill(r,r+N,(int)a.size()-1);
    // initialize data for the root of the tree
    s[0]=1;
    l[0]=-1;
    r[0]=-1;
    l[1]=-1;
    r[1]=-1;
    memset(t, -1, sizeof t);
    fill(t[1],t[1]+26,0);
    // add the text to the tree, letter by letter
    for (la=0; la<(int)a.size(); ++la)
        ukkadd (a[la]-'a');
}

```

2 Graph algorithms

2.1 DFS cpbook

```
enum { UNVISITED = -1, VISITED = -2 };
        // basic flags

// these variables have to be global to be easily
// accessible by our recursion (other ways exist)
vector<vii> AL;
vi dfs_num;

void dfs(int u) {
    normal usage
    printf("%d", u);
    vertex is visited
    dfs_num[u] = VISITED;
    u as visited
    for (auto &[v, w] : AL[u])
        style, w ignored
        if (dfs_num[v] == UNVISITED)
            avoid cycle
            dfs(v);
    recursively visits v
}

int main() {
    /*
    // Undirected Graph in Figure 4.1
    9
    1 1 0
    3 0 0 2 0 3 0
    2 1 0 3 0
    3 1 0 2 0 4 0
    1 3 0
    0
    2 7 0 8 0
    1 6 0
    1 6 0
    */

    freopen("dfs_cc_in.txt", "r", stdin);

    int V; scanf("%d", &V);
    AL.assign(V, vii());
    for (int u = 0; u < V; ++u) {
        int k; scanf("%d", &k);
        while (k--) {
            int v, w; scanf("%d %d", &v, &w);
            AL[u].emplace_back(v, w);
        }
    }

    printf("Standard DFS Demo (the input graph must be
    UNDIRECTED)\n");
    dfs_num.assign(V, UNVISITED);
}
```

```
int numCC = 0;
for (int u = 0; u < V; ++u)
    each u in [0..V-1]
    if (dfs_num[u] == UNVISITED)
        that u is unvisited
        printf("CC %d:", ++numCC), dfs(u), printf("\n"); //
        3 lines here!
printf("There are %d connected components\n", numCC);
return 0;
}
```

2.2 DFS iterativo - Lucas

```
vector<bool> vis;
void dfs(int start, vector<vector<int>> & adj, int v){
    // v = Vertices
    stack<int> s;
    s.push(start);
    vis[start] = true;
    int cont = 1;
    while (!s.empty()){
        int prox = s.top();
        if (!adj[prox].empty()){
            if (vis[adj[prox].back()] == false){
                vis[adj[prox].back()] = true;
                s.push(adj[prox].back());
            }
            else{
                adj[prox].pop_back();
            }
        }
        else{
            s.pop();
        }
    }
}
```

2.3 BFS cpbook

```
const int INF = 1e9; // INF = 1B, not 2^31-1 to avoid
// overflow
vi p;
// addition:parent vector

void printPath(int u) {
    extract info from vi p
    if (p[u] == -1) { printf("%d", u); return; }
    printPath(p[u]);
    output format: s -> ... -> t
    printf(" %d", u);
}
```

```

int main() {
    /*
     // Graph in Figure 4.3, format: list of unweighted
     edges
     // This example shows another form of reading graph
     input
     13 16
     0 1      1 2      2 3      0 4      1 5      2 6      3 7      5 6
     4 8      8 9      5 10     6 11     7 12     9 10     10 11    11 12
     */

    freopen("bfs_in.txt", "r", stdin);

    int V, E; scanf("%d %d", &V, &E);
    vector<vii> AL(V, vii());
    for (int i = 0; i < E; ++i) {
        int a, b; scanf("%d %d", &a, &b);
        AL[a].emplace_back(b, 0);
        AL[b].emplace_back(a, 0);
    }

    // as an example, we start from this source, see Figure
    4.3
    int s = 5;

    // BFS routine inside int main() -- we do not use
    recursion
    vi dist(V, INF); dist[s] = 0;           // INF =
    le9 here
    queue<int> q; q.push(s);
    p.assign(V, -1);                        // p is
    global

    int layer = -1;                         // for
    output printing
    bool isBipartite = true;                //
    additional feature

    while (!q.empty()) {
        int u = q.front(); q.pop();
        if (dist[u] != layer) printf("\nLayer %d: ", dist[u])
        ;
        layer = dist[u];
        printf("visit %d, ", u);
        for (auto &[v, w] : AL[u]) {         // C++17
            style, w ignored
            if (dist[v] == INF) {
                dist[v] = dist[u]+1;        // dist[
                v] != INF now
                p[v] = u;                    //
                parent of v is u
                q.push(v);                  // for
                next iteration
            }
            else if ((dist[v]%2) == (dist[u]%2)) // same
            parity
                isBipartite = false;
    }

```

```

    }
    printf("\nShortest path: ");
    printPath(7), printf("\n");
    printf("isBipartite? %d\n", isBipartite);
    return 0;
}

```

2.4 BFS para camino mas corto de UN nodo a todos los DEMAS

```

// inside int main()---no recursion
vi dist(V, INF); dist[s] = 0; // initial distances
queue<int> q; q.push(s); // start from source
while (!q.empty()) { // queue: layer by layer!
    int u = q.front(); q.pop(); // C++17 style, w ignored
    for (auto &[v, w] : AL[u]) {
        if (dist[v] != INF) continue; // already visited, skip
        dist[v] = dist[u]+1; // now set dist[v] != INF
        q.push(v); // for the next iteratio
    }
}

```

2.5 BFS bipartito

```

// Realiza una BFS desde el nodo 'src' en un grafo
// dirigido o no dirigido
// representado como lista de adyacencia.
// Parametros:
//   n : numero de nodos (0 .. n-1)
//   adj : vector de vectores, donde adj[u] contiene
//         todos los v tales que u -> v
//   src : nodo de partida
// Devuelve:
//   true si es bipartito y false si no lo es
bool bfs(int n, vector<pair<vector<int>, char>> &adj, int
src)
{
    queue<int> q;
    q.push(src);
    char decision = 'a';
    bool bipartito = true;

    while (!q.empty())
    {
        int u = q.front();
        q.pop();
        if (adj[u].second == 'c')
        {
            adj[u].second = decision;

```

```

    }
    if (adj[u].second == 'a')
        decision = 'b';
    else
        decision = 'a';
    for (int v : adj[u].first)
    {
        if (adj[v].second == 'c')
        {
            q.push(v);
            adj[v].second = decision;
        }
        if (adj[u].second == adj[v].second)
        {
            bipartito = false;
            break;
        }
    }
}
return bipartito;
}

int main()
{
    ios::sync_with_stdio(false);
    cin.tie(nullptr);
    int n, m;
    // Leer numero de nodos y aristas
    cin >> n >> m;
    // Construir lista de adyacencia
    vector<pair<vector<int>, char>> adj(n);
    // a = 1er conjunto
    // b = 2do
    // c = sin conjunto
    for (int i = 0; i < m; ++i)
    {
        int u, v;
        cin >> u >> v;
        adj[u].first.push_back(v);
        adj[v].first.push_back(u);
    }
    // inicializacion en c para saber si no esta
    // explorado
    for (int i = 0; i < n; i++)
        adj[i].second = 'c';
    bool es_bipartito = true;
    // Iterar por todos los nodos para manejar grafos no
    // conexos
    for (int i = 0; i < n; ++i)
    {
        // Si el nodo 'i' no ha sido coloreado, iniciar
        // un BFS desde el
        if (adj[i].second == 'c')

```

```

    {
        // Si cualquier componente no es bipartita,
        // el grafo entero no lo es
        if (!bfs(n, adj, i))
        {
            es_bipartito = false;
            break; // Podemos detenernos en cuanto
            // encontramos un fallo
        }
    }
    cout << "res: " << es_bipartito << endl;
    return 0;
}

```

2.6 DFS detect cycle

```

vector<vector<int>> adj(5);
int n;
vector<char> state(5);
/*
a = no visitado
b = visitando
c = visitado
*/
bool dfs_detect_cycle(int node)
{
    if (state[node] == 'b')
        return true;
    state[node] = 'b';
    for (auto i : adj[node])
    {
        if (dfs_detect_cycle(i))
        {
            return true;
        }
    }
    state[node] = 'c';
    return false;
}

int main()
{
    ios::sync_with_stdio(0); cin.tie(0); cout.tie(0);
    n = 5;
    adj[1].push_back(2);
    // Componente 2 (con ciclo)
    adj[3].push_back(4);
    adj[4].push_back(0);
    // adj[0].push_back(3); // CON ESTO SI HAY CICLO

    form(i, 0, 5) state[i] = 'a';
    int i;
    for (i = 0; i < 5; i++)

```

```

{
    if(state[i] == 'a')
        if(dfs_detect_cycle(i))
        {
            cout << "Hay ciclo" << endl;
            return 0;
        }
    }
    if(i == 5)
        cout << "NO hay ciclo" << endl;
    return 0;
}

```

2.7 Dijkstra camino mas corto grafo dirigido CON PESOS($O((V+E)\log V)$)

```

vector<long long> dist;
struct cmp {
    bool operator()(const pair<int, long long>& a, const
        pair<int, long long>& b) const {
        return a.second > b.second;
    }
};
priority_queue<pair<int, long long>, vector<pair<int,
    long long>>, cmp> q;
void dijkstra(int n, vector<vector<pair<int, long long>>>
    &adj, int src)
{
    dist.resize(n+1, -1);
    dist[src] = 0;
    q.push({src, 0});
    while (!q.empty())
    {
        auto u = q.top();
        q.pop();
        if (u.second > dist[u.first])
        {
            continue; // Ya encontramos un camino mas
                corto a 'u', ignoramos este.
        }
        for (auto v : adj[u.first])
        {
            if (dist[v.first] > dist[u.first] + v.second
                or dist[v.first] == -1)
            {
                dist[v.first] = dist[u.first] + v.second;
                q.push({v.first, dist[v.first]});
            }
        }
    }
}
true;

```

```

}
int main()
{
    ios::sync_with_stdio(false);
    cin.tie(nullptr);
    int n, m;
    cin >> n >> m;
    int u, v;
    long long p;
    vector<vector<pair<int, long long>>> adj(n+1); //nodo
        destino, peso
    for (int i = 0; i < m; ++i)
    {
        cin >> u >> v >> p;
        adj[u].push_back({v, p});
    }
    dijkstra(n, adj, 1); // desde nodo origen a todos los
        demas
    for (int i = 1; i <= n; ++i)
    {
        cout << dist[i] << " ";
    }
    return 0;
}

```

3 Data Structures

3.1 unordered_map<clave,valor>(hacer siempre RE-SERVE)

Almacena pares clave valor.

```

unordered_map<int, int> a;
a.reserve(n*1.33); // IMPORTANTEEEEEEE
n = 1e6 aprox 42.6 MB

```

n = 3e6 aprox 128 MB

n = 5e6 aprox 213 MB (aún puede entrar, pero ojo con pila, I/O buffers, otros contenedores).

3.1.1 Ejemplo basico Contar frecuencias

```

int main()
{
    int n;
    cin >> n;
    vector<int> arr(n);
    for (int &x : arr)

```

```

    cin >> x;
    unordered_map<int,int> freq; //<clave, valor>
    freq.reserve(n*1.33); // evita rehash
    for (int x : arr)
        freq[x]++;
    for (auto &p : freq)
        cout << p.first << " aparece " << p.second << "
            veces\n";
}

```

3.1.2 Buscar existencia de una llave

```

unordered_map<string,int> id;
id.reserve(1e5);
id["uva"] = 10;
id["manzana"] = 20;
// Con count
if (id.count("uva")) cout << "uva existe\n";

```

3.1.3 Transformar indices dispersos a continuos

```

vector<int> vals = {1000, 5000, 1000, 42};
unordered_map<int,int> comp;
comp.reserve(vals.size()*1.33);

int id = 0;
for (int v : vals)
    if (!comp.count(v))
        comp[v] = id++;
/*
This will compress the indices of the values
in 'vals' into a contiguous range starting from 0.
Ahora 1000 = 1
      5000 = 2
      42 = 3
*/
for (int v : vals)
    cout << v << " -> " << comp[v] << "\n";

```

3.1.4 Hashing pair

```

struct pair_hash {
    size_t operator()(const pair<int,int>& p) const {
        return ((long long)p.first << 32) ^ p.second;
    }
};

```

```

int main()
{
    unordered_map<pair<int,int>, int, pair_hash> edge_cost;
    edge_cost.reserve(1e6);
    //Muy usado para representar grafos dispersos.
    edge_cost[{1,2}] = 5;
    edge_cost[{2,3}] = 10;

    cout << edge_cost[{1,2}] << "\n"; // 5
}

```

3.2 unordered_set<clave> (hacer siempre RESERVE)

No existe acceso aleatorio con h[] ,
pero se puede iterar con for auto.

```

int main() {
    int n = 3e5;
    vi a = {1,2,3,42,42,42};
    unordered_set<int> s; //<T>
    s.reserve(n * 1.3); // evita rehash

    //insert(T)
    for (int x : a)
        s.insert(x);

    //VERIFICAR EXISTENCIA
    if (s.find(42) != s.end())
        cout << "42 existe" << endl;

    //Iterar para ver claves existentes
    for (auto x : s)
        cout << x << " ";

    return 0;
}

```

3.3 unordered_multimap<clave,valorES> (hacer siempre RESERVE)

Una misma clave puede tener varios valores asociados

3.3.1 Ejemplo basico

```

int main() {
    multimap<int,string> mm;

    // insertar pares (clave, valor)
    mm.insert({1, "uva"});
    mm.insert({2, "manzana"});
    mm.insert({2, "pera"});
}

```



```

mm.insert({3, "melon"});
// Iterar (se imprime ordenado por clave)
for (auto &p : mm)
    cout << p.first << " -> " << p.second << "\n";
/*
1 -> uva
2 -> manzana
2 -> pera
3 -> melon
*/
}

```

3.3.2 Buscar por clave

```

multimap<int, string> mm;
// insertar pares (clave, valor)
mm.insert({1, "uva"});
mm.insert({2, "manzana"});
mm.insert({2, "pera"});
mm.insert({3, "melon"});

// Buscar la primera aparicion de clave 2
auto it = mm.find(2);
if (it != mm.end())
    cout << "Encontrado: " << it->second << "\n";

// Contar cuantos con clave=2
cout << "Claves con 2: " << mm.count(2) << "\n";

// Obtener todos los con clave=2
auto [ini, fin] = mm.equal_range(2);
for (auto it = ini; it != fin; ++it)
    cout << it->second << " ";
/*
SALIDA
Encontrado: manzana
Claves con 2: 2
manzana pera
*/

```

3.3.3 Delete

```

mm.erase(2); // borra *todas* las entradas con clave=2
// Si quieres borrar solo uno:
auto it = mm.find(2);
if (it != mm.end())
    mm.erase(it);

```

3.4 Disjoint Set Union

Cada que unimos dos Sets del mismo RANK(altura subgrafo, rank=4, size=16) nuestro rank aumenta en +1. Entonces para formar un RANK r se necesitan por lo menos 2^r vertices.




Figure 1: Inicializacion de Union-Find. Cada nodo es su propio padre.




Figure 2: Union-Find despues de unir 3 y 5

```

// Union-Find Disjoint Sets Library written in OOP manner
// , using both path compression and union by rank
// heuristics

#include <bits/stdc++.h>
using namespace std;

typedef vector<int> vi;

class UnionFind { // OOP
    style
private: // vi p
    vi p, rank, setSize; // is the key part
    int numSets;
public:
    UnionFind(int N) {
        p.assign(N, 0); for (int i = 0; i < N; ++i) p[i] = i;
    }

```

```

rank.assign(N, 0); //
optional speedup
setSize.assign(N, 1); //
optional feature
numSets = N; //
optional feature
}

int findSet(int i) { return (p[i] == i) ? i : (p[i] =
    findSet(p[i])); }
bool isSameSet(int i, int j) { return findSet(i) ==
    findSet(j); }

int numDisjointSets() { return numSets; } //
optional
int sizeOfSet(int i) { return setSize[findSet(i)]; } //
optional

void unionSet(int i, int j) {
    if (isSameSet(i, j)) return; // i and
    j are in same set
    int x = findSet(i), y = findSet(j); // find
    both rep items
    if (rank[x] > rank[y]) swap(x, y); // keep
    x 'shorter' than y
    p[x] = y; // set x
    under y
    if (rank[x] == rank[y]) ++rank[y]; //
    optional speedup
    setSize[y] += setSize[x]; //
    combine set sizes at y
    --numSets; // a
    union reduces numSets
}
};

int main() {
    printf("Assume that there are 5 disjoint sets initially
        \n");
    UnionFind UF(17); // create 5 disjoint sets
    UF.unionSet(1,2);
    UF.unionSet(3,4);
    UF.unionSet(1,3);
    UF.unionSet(5,6);
    UF.unionSet(7,8);
    UF.unionSet(5,7);
    UF.unionSet(1,5);

    UF.unionSet(9,10);
    UF.unionSet(11,12);
    UF.unionSet(9,11);
    UF.unionSet(13,14);
    UF.unionSet(15,16);
    UF.unionSet(13,16);
    UF.unionSet(9,13);

```

```

UF.unionSet(9,1);
UF.findSet(10);
UF.findSet(11);

int a = 1 + 2;
printf("isSameSet(0, 3) = %d\n", UF.isSameSet(0, 3));
// will return 0 (false)
printf("isSameSet(4, 3) = %d\n", UF.isSameSet(4, 3));
// will return 1 (true)
for (int i = 0; i < 5; i++) // findSet will return 1
    for {0, 1} and 3 for {2, 3, 4}
        printf("findSet(%d) = %d, sizeOfSet(%d) = %d\n", i,
            UF.findSet(i), i, UF.sizeOfSet(i));
UF.unionSet(0, 3);
printf("%d\n", UF.numDisjointSets()); // 1
for (int i = 0; i < 5; i++) // findSet will return 3
    for {0, 1, 2, 3, 4}
        printf("findSet(%d) = %d, sizeOfSet(%d) = %d\n", i,
            UF.findSet(i), i, UF.sizeOfSet(i));
return 0;
}

```

3.5 Fenwick Tree

```

#include <bits/stdc++.h>
using namespace std;

#define LSONE(S) ((S) & -(S)) // the
key operation

typedef long long ll; // for
extra flexibility
typedef vector<ll> vll;
typedef vector<int> vi;

class FenwickTree { // index
    0 is not used
private:
    vll ft; //
    internal FT is an array
public:
    FenwickTree(int m) { ft.assign(m+1, 0); } //
    create an empty FT

    void build(const vll &f) {
        int m = (int)f.size()-1; // note
        f[0] is always 0
        ft.assign(m+1, 0);
        for (int i = 1; i <= m; ++i) { // O(m)
            ft[i] += f[i]; // add
            this value
            if (i+LSONE(i) <= m) // i has
                parent

```

```

        ft[i+LSOne(i)] += ft[i];           // add
        to that parent
    }
}
FenwickTree(const vll &f) { build(f); }    //
    create FT based on f
FenwickTree(int m, const vi &s) {          //
    create FT based on s
    vll f(m+1, 0);
    for (int i = 0; i < (int)s.size(); ++i) // do
        the conversion first
        ++f[s[i]];                         // in O(
            n)
    build(f);                             // in O(
        m)
}
ll rsq(int j) {                           //
    returns RSQ(1, j)
    ll sum = 0;
    for (; j; j -= LSOne(j))
        sum += ft[j];
    return sum;
}
ll rsq(int i, int j) { return rsq(j) - rsq(i-1); } //
    inc/exclusion
// updates value of the i-th element by v (v can be +ve
// inc or -ve/dec)
void update(int i, ll v) {
    for (; i < (int)ft.size(); i += LSOne(i))
        ft[i] += v;
}
int select(ll k) {                        // O(log
    m)
    int p = 1;
    while (p*2 < (int)ft.size()) p *= 2;
    int i = 0;
    while (p) {
        if (k > ft[i+p]) {
            k -= ft[i+p];
            i += p;
        }
        p /= 2;
    }
    return i+1;
}
};
class RUPQ {                             // RUPQ
    variant
private:
    FenwickTree ft;                       //

```

```

        internally use PURQ FT
public:
    RUPQ(int m) : ft(FenwickTree(m)) {}
    void range_update(int ui, int uj, ll v) {
        ft.update(ui, v);                 // [ui,
            ui+1, ..., m] +v
        ft.update(uj+1, -v);              // [uj
            +1, uj+2, ..., m] -v
    }                                     // [ui,
            ui+1, ..., uj] +v
    ll point_query(int i) { return ft.rsq(i); } // rsq(i
        ) is sufficient
};
class RUPQ {                             // RUPQ
    variant
private:                                 // needs
    two helper FTs
    RUPQ rupq;                          // one
    RUPQ and
    FenwickTree purq;                   // one
    PURQ
public:
    RUPQ(int m) : rupq(RUPQ(m)), purq(FenwickTree(m)) {} //
        initialization
    void range_update(int ui, int uj, ll v) {
        rupq.range_update(ui, uj, v);    // [ui,
            ui+1, ..., uj] +v
        purq.update(ui, v*(ui-1));        // -(ui
            -1)*v before ui
        purq.update(uj+1, -v*uj);         // +(uj-
            ui+1)*v after uj
    }
    ll rsq(int j) {
        return rupq.point_query(j)*j -    //
            optimistic calculation
            purq.rsq(j);                  //
            cancelation factor
    }
    ll rsq(int i, int j) { return rsq(j) - rsq(i-1); } //
        standard
};
int main() {
    vll f = {0,0,1,0,1,2,3,2,1,1,0};    // index
        0 is always 0
    FenwickTree ft(f);
    cout << "select:" << ft.select(5);
    printf("%lld\n", ft.rsq(1, 6)); // 7 => ft[6]+ft[4] =
        5+2 = 7
    printf("%d\n", ft.select(7)); // index 6, rsq(1, 6) ==
        7, which is >= 7
    ft.update(5, 1); // update demo
    printf("%lld\n", ft.rsq(1, 10)); // now 12
    printf("=====\n");
}

```

```

RUPQ rupq(10);
RURQ rurq(10);
rupq.range_update(2, 9, 7); // indices in [2, 3, ..., 9]
    updated by +7
rupq.range_update(6, 7, 3); // indices 6&7 are further
    updated by +3 (10)
rupq.point_query(6);

rurq.range_update(2, 9, 7); // same as rupq above
rurq.range_update(6, 7, 3); // same as rupq above
// idx = 0 (unused) | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9
// val = -          | 0 | 7 | 7 | 7 | 7 |10 |10 | 7 | 7
//         | 0
for (int i = 1; i <= 10; i++)
    printf("%d -> %lld\n", i, rupq.point_query(i));
printf("RSQ(1, 10) = %lld\n", rurq.rsq(1, 10)); // 62
printf("RSQ(6, 7) = %lld\n", rurq.rsq(6, 7)); // 20
return 0;
}

```

3.6 Segment Tree

```

#include <bits/stdc++.h>
using namespace std;
typedef vector<int> vi;
class SegmentTree { // OOP
    style
private:
    int n; // n = (
    vi A, st, lazy; // the
    arrays

    int l(int p) { return p<<1; } // go to
        left child
    int r(int p) { return (p<<1)+1; } // go to
        right child

    int conquer(int a, int b) {
        if (a == -1) return b; //
        corner case
        if (b == -1) return a;
        return min(a, b); // RMQ
    }

    void build(int p, int L, int R) { // O(n)
        if (L == R)
            st[p] = A[L]; // base
        else {
            int m = (L+R)/2;

```

```

        build(l(p), L, m);
        build(r(p), m+1, R);
        st[p] = conquer(st[l(p)], st[r(p)]);
    }

    void propagate(int p, int L, int R) {
        if (lazy[p] != -1) { // has a
            lazy flag
            st[p] = lazy[p]; // [L..R
            ] has same value
            if (L != R) // not a
                leaf
                lazy[l(p)] = lazy[r(p)] = lazy[p]; //
                propagate downwards
            else // L ==
                R, a single index
                A[L] = lazy[p]; // time
                to update this
            lazy[p] = -1; // erase
            lazy flag
        }
    }

    int RMQ(int p, int L, int R, int i, int j) { // O(log
        n)
        propagate(p, L, R); // lazy
        propagation
        if (i > j)
            return -1; // infeasible
        if ((L >= i) && (R <= j))
            return st[p]; // found the segment
        int m = (L+R)/2;
        int left = RMQ(l(p), L, m, i, min(m, j));
        int right = RMQ(r(p), m+1, R, max(i, m+1), j);
        return conquer(left, right);
    }

    void update(int p, int L, int R, int i, int j, int val)
        { // O(log n)
        propagate(p, L, R); // lazy
        propagation
        if (i > j) return;
        if ((L >= i) && (R <= j)) { // found
            the segment
            lazy[p] = val; //
            update this
            propagate(p, L, R); // lazy
            propagation
        }
        else {
            int m = (L+R)/2;
            update(l(p), L, m, i, min(m, j), val);
            update(r(p), m+1, R, max(i, m+1), j, val);
            int lsubtree = (lazy[l(p)] != -1) ? lazy[l(p)] : st
                [l(p)];

```

```

    int rsubtree = (lazy[r(p)] != -1) ? lazy[r(p)] : st
      [r(p)];
    st[p] = conquer(lsubtree, rsubtree);
  }
}

public:
  SegmentTree(int sz) : n(sz), A(n), st(4*n), lazy(4*n,
    -1) {}

  SegmentTree(const vi &initialA) : SegmentTree((int)
    initialA.size()) {
    A = initialA;
    build(1, 0, n-1);
    true;
  }

  void update(int i, int j, int val) { update(1, 0, n-1,
    i, j, val); }

  int RMQ(int i, int j) { return RMQ(1, 0, n-1, i, j); }
};

int main() {
  vi A = {18, 17, 13, 19, 15, 11, 20, 99}; // make
    n a power of 2
  SegmentTree st(A);
  st.update(4, 7, 2);

  st.RMQ(1, 2);
  printf("          idx    0, 1, 2, 3, 4, 5, 6, 7\n");
  printf("          A is {18,17,13,19,15,11,20,oo}\n");
  printf("RMQ(1, 3) = %d\n", st.RMQ(1, 3)); // 13
  printf("RMQ(4, 7) = %d\n", st.RMQ(4, 7)); // 11
  printf("RMQ(3, 4) = %d\n", st.RMQ(3, 4)); // 15
  st.update(5, 5, 77); //
    update A[5] to 77
  printf("          idx    0, 1, 2, 3, 4, 5, 6, 7\n");
  printf("Now, modify A into {18,17,13,19,15,77,20,oo}\n");
  printf("RMQ(1, 3) = %d\n", st.RMQ(1, 3)); //
    remains 13
  printf("RMQ(4, 7) = %d\n", st.RMQ(4, 7)); // now
    15
  printf("RMQ(3, 4) = %d\n", st.RMQ(3, 4)); //
    remains 15
  st.update(0, 3, 30); //
    update A[0..3] to 30
  printf("          idx    0, 1, 2, 3, 4, 5, 6, 7\n");
  printf("Now, modify A into {30,30,30,30,15,77,20,oo}\n");
  printf("RMQ(1, 3) = %d\n", st.RMQ(1, 3)); // now

```

```

    30
  printf("RMQ(4, 7) = %d\n", st.RMQ(4, 7)); //
    remains 15
  printf("RMQ(3, 4) = %d\n", st.RMQ(3, 4)); //
    remains 15
  st.update(3, 3, 7); //
    update A[3] to 7
  printf("          idx    0, 1, 2, 3, 4, 5, 6, 7\n");
  printf("Now, modify A into {30,30,30, 7,15,77,20,oo}\n");
  printf("RMQ(1, 3) = %d\n", st.RMQ(1, 3)); // now 7
  printf("RMQ(4, 7) = %d\n", st.RMQ(4, 7)); //
    remains 15
  printf("RMQ(3, 4) = %d\n", st.RMQ(3, 4)); // now 7
  return 0;
}

```

3.7 Order Statistics Tree

3.7.1 Quick Select

Ranking(v) = posicion del elemento v si el arreglo estuviese ordenado.

```

int Partition(int A[], int l, int r) {
  int p = A[l]; // p is
    the pivot
  int m = l; // S1
  and S2 are empty
  for (int k = l+1; k <= r; ++k) { //
    explore unknown region
    if (A[k] < p) { // case
      2
      ++m;
      swap(A[k], A[m]);
    } // notice that we do nothing in case 1: a[k] >= p
  }
  swap(A[l], A[m]); // swap
  pivot with a[m]
  return m; //
    return pivot index
}

int RandPartition(int A[], int l, int r) {
  int p = l + rand() % (r-l+1); //
    select a random pivot
  swap(A[l], A[p]); // swap
  A[p] with A[l]
  return Partition(A, l, r);
}

```

```

int QuickSelect(int A[], int l, int r, int k) { //
    expected O(n)
    if (l == r) return A[l];
    int q = RandPartition(A, l, r); // O(n)
    if (q+1 == k)
        return A[q];
    else if (q+1 > k)
        return QuickSelect(A, l, q-1, k);
    else
        return QuickSelect(A, q+1, r, k);
}

int main() {
    int A[] = { 2, 8, 7, 1, 5, 4, 6, 3 };
    nth_element(A, A+4, A+8);
    printf("%d\n", A[4]);
    //output: 5
    for(auto i:A)
        cout << i << ", ";
    //output: [3,2,1,4,5,7,6,8]
    return 0;
}

```

3.8 Ordered Statistics Tree

```

#include <bits/stdc++.h>
using namespace std;

#include <bits/extc++.h> // pbds
using namespace __gnu_pbds;
typedef tree<int, null_type, less<int>, rb_tree_tag,
            tree_order_statistics_node_update> ost;

int main() {
    int n = 9;
    int A[] = { 2, 4, 7, 10, 15, 23, 50, 65, 71 }; // as in
                                                    Chapter 2
    ost tree;
    for (int i = 0; i < n; ++i) // O(n)
        tree.insert(A[i]);
    // O(log n) select
    cout << *tree.find_by_order(0) << "\n"; // 1-
        smallest = 2
    cout << *tree.find_by_order(n-1) << "\n"; // 9-
        smallest/largest = 71
    cout << *tree.find_by_order(4) << "\n"; // 5-
        smallest = 15
    // O(log n) rank
    cout << tree.order_of_key(2) << "\n"; // index
        0 (rank 1)

```

```

cout << tree.order_of_key(71) << "\n"; // index
        8 (rank 9)
cout << tree.order_of_key(15) << "\n"; // index
        4 (rank 5)
return 0;
}

```

4 Math

4.1 Prime Numbers 1-2000

```

2 3 5 7 11 13 17 19 23 29
31 37 41 43 47 53 59 61 67 71
73 79 83 89 97 101 103 107 109 113
127 131 137 139 149 151 157 163 167 173
179 181 191 193 197 199 211 223 227 229
233 239 241 251 257 263 269 271 277 281
283 293 307 311 313 317 331 337 347 349
353 359 367 373 379 383 389 397 401 409
419 421 431 433 439 443 449 457 461 463
467 479 487 491 499 503 509 521 523 541
547 557 563 569 571 577 587 593 599 601
607 613 617 619 631 641 643 647 653 659
661 673 677 683 691 701 709 719 727 733
739 743 751 757 761 769 773 787 797 809
811 821 823 827 829 839 853 857 859 863
877 881 883 887 907 911 919 929 937 941
947 953 967 971 977 983 991 997 1009 1013
1019 1021 1031 1033 1039 1049 1051 1061 1063 1069
1087 1091 1093 1097 1103 1109 1117 1123 1129 1151
1153 1163 1167 1181 1187 1193 1201 1213 1217 1223
1229 1231 1237 1249 1259 1277 1279 1283 1289 1291
1297 1301 1303 1307 1319 1321 1327 1361 1367 1373
1381 1399 1409 1423 1427 1429 1433 1439 1447 1451
1453 1459 1471 1481 1483 1487 1489 1493 1499 1511
1523 1531 1543 1549 1553 1559 1567 1571 1579 1583
1597 1601 1607 1609 1613 1619 1621 1627 1637 1657
1663 1667 1669 1693 1699 1709 1721 1723 1733
1741 1747 1753 1759 1777 1783 1787 1789 1801 1811
1823 1831 1847 1861 1867 1871 1873 1877 1879 1889
1901 1907 1913 1931 1933 1949 1951 1973 1979 1987

970'997 971'483 921'281'269 999'279'733

```

1'000'000'009 1'000'000'021 1'000'000'409
1'005'012'527

4.2 Serie de Fibonacci (hasta n=20)

Def: $F(0)=0$, $F(1)=1$, $F(n)=F(n-1)+F(n-2)$
 $F(0) = 0$
 $F(1) = 1$
 $F(2) = 1$
 $F(3) = 2$
 $F(4) = 3$
 $F(5) = 5$
 $F(6) = 8$
 $F(7) = 13$
 $F(8) = 21$
 $F(9) = 34$
 $F(10) = 55$
 $F(11) = 89$
 $F(12) = 144$
 $F(13) = 233$
 $F(14) = 377$
 $F(15) = 610$
 $F(16) = 987$
 $F(17) = 1597$
 $F(18) = 2584$
 $F(19) = 4181$
 $F(20) = 6765$

4.3 Factorial (hasta n=20)

Def: $n!=n(n-1)!$
 $0! = 1$
 $1! = 1$
 $2! = 2$
 $3! = 6$
 $4! = 24$
 $5! = 120$
 $6! = 720$
 $7! = 5040$

$8! = 40320$
 $9! = 362880$
 $10! = 3628800$
 $11! = 39916800$
 $12! = 479001600$
 $13! = 6227020800$
 $14! = 87178291200$
 $15! = 1307674368000$
 $16! = 20922789888000$
 $17! = 355687428096000$
 $18! = 6402373705728000$
 $19! = 121645100408832000$
 $20! = 2432902008176640000$

4.4 Numeros Triangulares (hasta n=20)

Def: $T(n)=n(n+1)/2$
 $T(1) = 1$
 $T(2) = 3$
 $T(3) = 6$
 $T(4) = 10$
 $T(5) = 15$
 $T(6) = 21$
 $T(7) = 28$
 $T(8) = 36$
 $T(9) = 45$
 $T(10) = 55$
 $T(11) = 66$
 $T(12) = 78$
 $T(13) = 91$
 $T(14) = 105$
 $T(15) = 120$
 $T(16) = 136$
 $T(17) = 153$
 $T(18) = 171$
 $T(19) = 190$
 $T(20) = 210$

4.5 Numeros Cuadrados (hasta n=20)

Def: $Q(n) = n^2$

```
Q(1) = 1
Q(2) = 4
Q(3) = 9
Q(4) = 16
Q(5) = 25
Q(6) = 36
Q(7) = 49
Q(8) = 64
Q(9) = 81
Q(10) = 100
Q(11) = 121
Q(12) = 144
Q(13) = 169
Q(14) = 196
Q(15) = 225
Q(16) = 256
Q(17) = 289
Q(18) = 324
Q(19) = 361
Q(20) = 400
```

4.6 Simple Sieve of Eratosthenes $O(n \cdot \log(\log(n)))$ - con $n=1e7$ 1.25 MB

```
#define tam 1e7
vector< bool > criba(tam , true);
void criba_function()
{
    criba[0]=false;
    criba[1]=false;
    //( i*i < tam) equivalente a (i <= sqrt(tam))
    for(int i = 2; i*i <= tam ; i++)
    {
        if(!criba[i]) continue;
        for(int j = 2; i*j <= tam ; j++)
            criba[i * j] = false;
    }
}
```

4.7 Smallest Prime Factor AND Sieve of Eratosthenes $O(n)$ - con $n=1e7$ 45 MB

```
// O(n)
// pr contains prime numbers
// lp[i] == i if i is prime
// else lp[i] is minimum prime factor of i
const int nax = 1e7;
int lp[nax+1]; //because lp is an array nax have to be
               //less than 1e7 or change to a vector(nax+1,0)
vector<int> pr; // It can be sped up if change for an
               //array

void sieve(){
    form(i,2,nax){
        if (lp[i] == 0) {
            lp[i] = i; pr.pb(i);
        }
        for (int j=0, mult= i*pr[j]; j<sz(pr) && pr[j]<=lp[i]
            && mult<nax; ++j, mult= i*pr[j])
            lp[mult] = pr[j];
    }
}
```

4.8 Smallest Prime Factor Piton++

```
// O(n)
// pr contains prime numbers
// lp[i] == i if i is prime
// else lp[i] is minimum prime factor of i
const int nax = 1e7;
int lp[nax+1]; //because lp is an array nax have to be
               //less than 1e7 or change to a vector(nax+1,0)
vector<int> pr; // It can be sped up if change for an
               //array

void sieve(){
    form(i,2,nax){
        if (lp[i] == 0) {
            lp[i] = i; pr.pb(i);
        }
        for (int j=0, mult= i*pr[j]; j<sz(pr) && pr[j]<=lp[i]
            && mult<nax; ++j, mult= i*pr[j])
            lp[mult] = pr[j];
    }
}
```

4.9 Combinatorics

4.9.1 Next permutation


```
// O(n)
// pr contains prime numbers
// lp[i] == i if i is prime
// else lp[i] is minimum prime factor of i
const int nax = 1e7;
int lp[nax+1]; //because lp is an array nax have to be
               //less than 1e7 or change to a vector(nax+1,0)
vector<int> pr; // It can be sped up if change for an
               //array

void sieve() {
    form(i,2,nax){
        if (lp[i] == 0) {
            lp[i] = i; pr.pb(i);
        }
        for (int j=0, mult= i*pr[j]; j<sz(pr) && pr[j]<=lp[i]
            && mult<nax; ++j, mult= i*pr[j])
            lp[mult] = pr[j];
    }
}
```

Decimal - Binary - Octal - Hex – ASCII
Conversion Chart

Decimal	Binary	Octal	Hex	ASCII	Decimal	Binary	Octal	Hex	ASCII	Decimal	Binary	Octal	Hex	ASCII	Decimal	Binary	Octal	Hex	ASCII
0	00000000	000	00	NUL	32	00100000	040	20	SP	64	01000000	100	40	@	96	01100000	140	60	`
1	00000001	001	01	SOH	33	00100001	041	21	!	65	01000001	101	41	A	97	01100001	141	61	a
2	00000010	002	02	STX	34	00100010	042	22	"	66	01000010	102	42	B	98	01100010	142	62	b
3	00000011	003	03	ETX	35	00100011	043	23	#	67	01000011	103	43	C	99	01100011	143	63	c
4	00000100	004	04	EOT	36	00100100	044	24	\$	68	01000100	104	44	D	100	01100100	144	64	d
5	00000101	005	05	ENQ	37	00100101	045	25	%	69	01000101	105	45	E	101	01100101	145	65	e
6	00000110	006	06	ACK	38	00100110	046	26	&	70	01000110	106	46	F	102	01100110	146	66	f
7	00000111	007	07	BEL	39	00100111	047	27	'	71	01000111	107	47	G	103	01100111	147	67	g
8	00001000	010	08	BS	40	00101000	050	28	(72	01001000	110	48	H	104	01101000	150	68	h
9	00001001	011	09	HT	41	00101001	051	29)	73	01001001	111	49	I	105	01101001	151	69	i
10	00001010	012	0A	LF	42	00101010	052	2A	*	74	01001010	112	4A	J	106	01101010	152	6A	j
11	00001011	013	0B	VT	43	00101011	053	2B	+	75	01001011	113	4B	K	107	01101011	153	6B	k
12	00001100	014	0C	FF	44	00101100	054	2C	,	76	01001100	114	4C	L	108	01101100	154	6C	l
13	00001101	015	0D	CR	45	00101101	055	2D	-	77	01001101	115	4D	M	109	01101101	155	6D	m
14	00001110	016	0E	SO	46	00101110	056	2E	.	78	01001110	116	4E	N	110	01101110	156	6E	n
15	00001111	017	0F	SI	47	00101111	057	2F	/	79	01001111	117	4F	O	111	01101111	157	6F	o
16	00010000	020	10	DLE	48	00110000	060	30	0	80	01010000	120	50	P	112	01110000	160	70	p
17	00010001	021	11	DC1	49	00110001	061	31	1	81	01010001	121	51	Q	113	01110001	161	71	q
18	00010010	022	12	DC2	50	00110010	062	32	2	82	01010010	122	52	R	114	01110010	162	72	r
19	00010011	023	13	DC3	51	00110011	063	33	3	83	01010011	123	53	S	115	01110011	163	73	s
20	00010100	024	14	DC4	52	00110100	064	34	4	84	01010100	124	54	T	116	01110100	164	74	t
21	00010101	025	15	NAK	53	00110101	065	35	5	85	01010101	125	55	U	117	01110101	165	75	u
22	00010110	026	16	SYN	54	00110110	066	36	6	86	01010110	126	56	V	118	01110110	166	76	v
23	00010111	027	17	ETB	55	00110111	067	37	7	87	01010111	127	57	W	119	01110111	167	77	w
24	00011000	030	18	CAN	56	00111000	070	38	8	88	01011000	130	58	X	120	01111000	170	78	x
25	00011001	031	19	EM	57	00111001	071	39	9	89	01011001	131	59	Y	121	01111001	171	79	y
26	00011010	032	1A	SUB	58	00111010	072	3A	:	90	01011010	132	5A	Z	122	01111010	172	7A	z
27	00011011	033	1B	ESC	59	00111011	073	3B	;	91	01011011	133	5B	[123	01111011	173	7B	{
28	00011100	034	1C	FS	60	00111100	074	3C	<	92	01011100	134	5C	\	124	01111100	174	7C	
29	00011101	035	1D	GS	61	00111101	075	3D	=	93	01011101	135	5D]	125	01111101	175	7D	}
30	00011110	036	1E	RS	62	00111110	076	3E	>	94	01011110	136	5E	^	126	01111110	176	7E	~
31	00011111	037	1F	US	63	00111111	077	3F	?	95	01011111	137	5F	_	127	01111111	177	7F	DEL

This work is licensed under the Creative Commons Attribution-ShareAlike License. To view a copy of this license, visit <http://creativecommons.org/licenses/by-sa/3.0/> ASCII Conversion Chart.doc Copyright © 2008, 2012 Donald Weisman 22 March 2012

5 Dynamic Programming

6 Miscellaneous

6.1 Ternary Search

Figure 3: Ascii code

Tipo	Tam. Bits	Dígitos de precisión	Rango	
			Min	Max
Bool	8	0	0	1
Char	8	2	-128	127
Signed char	8	2	-128	127
unsigned char	8	2	0	255
short int	16	4	-32,768	32,767
unsigned short int	16	4	0	65,535
Int	32	9	-2,147,483,648	2,147,483,647
unsigned int	32	9	0	4,294,967,295
long int	32	9	-2,147,483,648	2,147,483,647
unsigned long int	32	9	0	4,294,967,295
long long int	64	18	-9,223,372,036,854,775,808	9,223,372,036,854,775,807
unsigned long long int	64	18	0	18,446,744,073,709,551,615
Float	32	6	1.17549e-38	3.40282e+38
Double	64	15	2.22507e-308	1.79769e+308

Figure 4: Data types limits




Figure 6: Combinatorics




Figure 5: DFS y BFS

The following are true involving modular arithmetic:

- $(a + b) \% m = ((a \% m) + (b \% m)) \% m$
 Example: $(15 + 29) \% 8$
 $= ((15 \% 8) + (29 \% 8)) \% 8 = (7 + 5) \% 8 = 4$
- $(a - b) \% m = ((a \% m) - (b \% m)) \% m$
 Example: $(37 - 15) \% 6$
 $= ((37 \% 6) - (15 \% 6)) \% 6 = (1 - 3) \% 6 = -2 \text{ or } 4$
- $(a \times b) \% m = ((a \% m) \times (b \% m)) \% m$
 Example: $(23 \times 12) \% 5$
 $= ((23 \% 5) \times (12 \% 5)) \% 5 = (3 \times 2) \% 5 = 1$

Figure 7: Modulo properties




Figure 8: Pascal's triangle