

# cs-logistic-regression

May 20, 2023

## 1 Linear Regression

```
[7]: import pandas as pd
import numpy as np
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LogisticRegression
from sklearn.metrics import accuracy_score, precision_score, recall_score, f1_score, confusion_matrix, classification_report
import matplotlib.pyplot as plt

# Load the dataset
df = pd.read_csv('preprocessed_dataset.csv')

# Map label values to corresponding attack names
label_mapping = {
    0: 'BENIGN',
    1: 'Brute Force',
    2: 'SQL Injection',
    3: 'XSS'
}
df['Label'] = df['Label'].map(label_mapping)

# Split the dataset into features (X) and labels (y)
X = df.iloc[:, :-1] # All columns except the last one
y = df.iloc[:, -1]  # Last column (labels)

# Split the dataset into training and testing sets
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)

# Create and train the Logistic Regression model
model = LogisticRegression()
model.fit(X_train, y_train)

# Predict the test set
y_pred = model.predict(X_test)
```

```

# Evaluate the model
accuracy = accuracy_score(y_test, y_pred)
precision = precision_score(y_test, y_pred, average='weighted')
recall = recall_score(y_test, y_pred, average='weighted')
f1 = f1_score(y_test, y_pred, average='weighted')
confusion_matrix_4x4 = confusion_matrix(y_test, y_pred)
confusion_matrix_2x2 = np.zeros((2, 2))

# Calculate values for the 2x2 confusion matrix
confusion_matrix_2x2[0, 0] = confusion_matrix_4x4[0, 0] # True Negatives (0, 0)
confusion_matrix_2x2[1, 0] = np.sum(confusion_matrix_4x4[1:, 0]) # False
    ↳Negatives (1, 0)
confusion_matrix_2x2[0, 1] = np.sum(confusion_matrix_4x4[0, 1:]) # False
    ↳Positives (0, 1)
confusion_matrix_2x2[1, 1] = np.sum(confusion_matrix_4x4[1:, 1:]) # True
    ↳Positives (1, 1)

classification = classification_report(y_test, y_pred)

# Plot the confusion matrix 4x4
plt.figure(figsize=(6, 4))
plt.imshow(confusion_matrix_4x4, cmap='Blues', interpolation='nearest')
plt.title('Confusion Matrix (4x4)')
plt.colorbar()
tick_marks = np.arange(len(np.unique(y)))
plt.xticks(tick_marks, np.unique(y), rotation=45)
plt.yticks(tick_marks, np.unique(y))
plt.xlabel('Predicted')
plt.ylabel('True')
for i in range(len(np.unique(y))):
    for j in range(len(np.unique(y))):
        plt.text(j, i, str(confusion_matrix_4x4[i, j]),
    ↳horizontalalignment='center', verticalalignment='center')
plt.show()

# Plot the confusion matrix 2x2
plt.figure(figsize=(6, 4))
plt.imshow(confusion_matrix_2x2, cmap='Blues', interpolation='nearest')
plt.title('Confusion Matrix (2x2)')
plt.colorbar()
tick_marks = np.arange(2)
plt.xticks(tick_marks, ['0', '1'], rotation=45)
plt.yticks(tick_marks, ['0', '1'])
plt.xlabel('Predicted')
plt.ylabel('True')
for i in range(2):
    for j in range(2):

```

```

        plt.text(j, i, str(confusion_matrix_2x2[i, j]),
        ↪horizontalalignment='center', verticalalignment='center')
plt.show()

# Print the model's evaluation results
print('==== Logistic Regression Model =====')
print()
print("Model Accuracy:\n", accuracy)
print("Model Precision:\n", precision)
print("Model Recall:\n", recall)
print("Model F1-score:\n", f1)
print()
print("Confusion matrix 4*4:\n", confusion_matrix_4x4)
print()
print("Confusion matrix 2*2:\n", confusion_matrix_2x2)
print()
print("Classification report:\n", classification)
print()
print("Distribution of Attacks:")
df['Label'].value_counts().plot(kind='bar')
plt.xticks(np.arange(4), ['BENIGN', 'Brute Force', 'SQL Injection', 'XSS'],
↪rotation=0)
plt.show()

```

C:\Users\pappu\anaconda3\lib\site-packages\sklearn\linear\_model\\_logistic.py:814: ConvergenceWarning: lbfgs failed to converge (status=1):  
STOP: TOTAL NO. of ITERATIONS REACHED LIMIT.

Increase the number of iterations (max\_iter) or scale the data as shown in:

<https://scikit-learn.org/stable/modules/preprocessing.html>

Please also refer to the documentation for alternative solver options:

[https://scikit-learn.org/stable/modules/linear\\_model.html#logistic-regression](https://scikit-learn.org/stable/modules/linear_model.html#logistic-regression)

```

n_iter_i = _check_optimize_result(
C:\Users\pappu\anaconda3\lib\site-packages\sklearn\metrics\_classification.py:1318: UndefinedMetricWarning:
Precision is ill-defined and being set to 0.0 in labels with no predicted
samples. Use `zero_division` parameter to control this behavior.
    _warn_prf(average, modifier, msg_start, len(result))
C:\Users\pappu\anaconda3\lib\site-packages\sklearn\metrics\_classification.py:1318: UndefinedMetricWarning:
Precision and F-score are ill-defined and being set to 0.0 in labels with no
predicted samples. Use `zero_division` parameter to control this behavior.
    _warn_prf(average, modifier, msg_start, len(result))
C:\Users\pappu\anaconda3\lib\site-packages\sklearn\metrics\_classification.py:1318: UndefinedMetricWarning:

```

Precision and F-score are ill-defined and being set to 0.0 in labels with no predicted samples. Use `zero\_division` parameter to control this behavior.


```
_warn_prf(average, modifier, msg_start, len(result))
```


C:\Users\pappu\anaconda3\lib\site-

packages\sklearn\metrics\\_classification.py:1318: UndefinedMetricWarning:

Precision and F-score are ill-defined and being set to 0.0 in labels with no predicted samples. Use `zero\_division` parameter to control this behavior.

```
_warn_prf(average, modifier, msg_start, len(result))
```





===== Logistic Regression Model =====

Model Accuracy:  
 0.9908291339322044  
 Model Precision:  
 0.9896449158200842  
 Model Recall:  
 0.9908291339322044  
 Model F1-score:  
 0.9899058612405326

Confusion matrix 4\*4:  
 [[31396 75 0 31]  
 [ 39 260 0 1]  
 [ 2 0 0 0]  
 [ 8 137 0 0]]

Confusion matrix 2\*2:  
 [[31396. 106.]  
 [ 49. 398.]]

Classification report:  


```

precision    recall  f1-score   support


```

|               |      |      |      |       |
|---------------|------|------|------|-------|
| BENIGN        | 1.00 | 1.00 | 1.00 | 31502 |
| Brute Force   | 0.55 | 0.87 | 0.67 | 300   |
| SQL Injection | 0.00 | 0.00 | 0.00 | 2     |
| XSS           | 0.00 | 0.00 | 0.00 | 145   |
| accuracy      |      |      | 0.99 | 31949 |
| macro avg     | 0.39 | 0.47 | 0.42 | 31949 |
| weighted avg  | 0.99 | 0.99 | 0.99 | 31949 |

Distribution of Attacks:



```
[10]: # Create a DataFrame to store the evaluation metrics
evaluation_data = pd.DataFrame({
    'Model': ['Logistic Regression'],
    'Accuracy': [accuracy],
    'Precision': [precision],
    'Recall': [recall],
    'F1-score': [f1]
})
```

```
# Save the evaluation metrics to a CSV file  
evaluation_data.to_csv('evaluation_results_LR.csv', index=False)
```

```
[11]: print(evaluation_data)
```

|   | Model               | Accuracy | Precision | Recall   | F1-score |
|---|---------------------|----------|-----------|----------|----------|
| 0 | Logistic Regression | 0.990829 | 0.989645  | 0.990829 | 0.989906 |

```
[ ]:
```