

Настроил айпи на пк

И на свиче

```
Switch(config) #int vlan 1
Switch(config-if) #ip address 192.168.0.2 255.255.255.0
Switch(config-if) #no sh

Switch(config-if) #
%LINK-5-CHANGED: Interface Vlan1, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan1, changed stat

Switch(config-if) #line vty 0 5
Switch(config-line) #pass 111
Switch(config-line) #login
Switch(config-line) #enable pass 111
Switch(config-line) #enable pass 111
Switch(config-line) #enable pass 111
```

```
Cisco Packet Tracer PC Command Line 1.0
C:\>telnet 192.168.0.2
Trying 192.168.0.2 ...Open

User Access Verification

Password:
Switch>en
Password:
Switch#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#
```

Подключаю ssh

```
Switch(config) #hostname swl
swl(config) #ip domain name test
swl(config) #crypto key generate rsa
The name for the keys will be: swl.test
Choose the size of the key modulus in the range of 360 to 4096 for your
    General Purpose Keys. Choosing a key modulus greater than 512 may take
    a few minutes.

How many bits in the modulus [512]: 768
% Generating 768 bit RSA keys, keys will be non-exportable...[OK]

swl(config) #ip ssh version 2
*Mar 1 0:4:15.317: %SSH-5-ENABLED: SSH 1.99 has been enabled
swl(config-line) #transport input ssh
swl(config-line) #transport input ssh
swl(config-line) #
```

проверяю

```
C:\>telnet 192.168.0.2
Trying 192.168.0.2 ...Open

[Connection to 192.168.0.2 closed by foreign host]
C:\>telnet 192.168.0.2
Trying 192.168.0.2
Trying 192.168.0.2 ...Open
```

