

Создал сеть



Хоум волп



Настройка роутера

```
Router>en
Router#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Router(config) #interface fa0/0
Router(config-if) #ip address 10.3.0.1 255.255.255.0
Router(config-if) #no sh
Router(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up
Router(config-if) #exit
Router(config) #ip dhcp exc
Router(config) #ip dhcp excluded-address 10.3.0.1
Router(config) #net 10.3.0.0 255.255.255.0
% Invalid input detected at '^' marker.
Router(config) #net 10.3.0.0 255.255.255.0
% Invalid input detected at '^' marker.
Router(config) #ip dhcp pool Telephony
Router(dhcp-config) #net 10.3.0.0 255.255.255.0
Router(dhcp-config) #default-router 10.3.0.1
Router(dhcp-config) #option 150 ip 10.3.0.1
Router (dhcp-config) #exit
Router (config) #telephony-service
Router (config-telephony) #max-ep
Router (config-telephony) #max-ephones 10
Router(config-telephony) #max-dn 10
Router(config-telephony) #ip source-address 10.3.0.1 port 2000
Router(config-telephony) #auto assign 1 to 10
Router (config-telephony) #ephone-dn 1
Router(config-ephone-dn) #%LINK-3-UPDOWN: Interface ephone dsp DN 1.1, changed state to up
Router(config-ephone-dn) #number 101
Router (config-ephone-dn) #eph
%IPPHONE-6-REGISTER: ephone-1 IP:10.3.0.3 Socket:2 DeviceType:Phone has registered.
% Ambiguous command: "eph"
Router (config) #ephone-dn 2
Router(config-ephone-dn) #%LINK-3-UPDOWN: Interface ephone dsp DN 2.1, changed state to up
Router(config-ephone-dn) #number 102
Router (config-ephone-dn) #exit
Router (config) #ephone 1
Router(config-ephone) #mac-address 0009.7C34.3C01
ephone slot is already registered with 0007.ECBC.3101
Cannot change MAC address.
Router(config-ephone) #type ata
Router (config-ephone) #button 1:1
Dn already assigned.
Router(config-ephone) #ephone 2
Router(config-ephone) #mac-address 000C.CF09.D862
Router(config-ephone) #type 7960
Router(config-ephone) #button 1:2
Router (config-ephone) #exit
Router(config) #ephone 3
Router(config-ephone) #mac-address 006.2A28.7710
Router(config-ephone) #type CIPC
Router(config-ephone) #button 1:3
```

