

Router 0

Router>en
Router#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Router(config) #int fa0/0
Router(config-if) #ip ad 192.168.10.1 255.255.255.0
Router(config-if) #no sh

BINDINGIO O GIDOMA. BINC PIGGGGGI ON INCCITAGE LABORDHEINEGG/G/ GHANGEA BOAGE

```
louter(config-if) #exit
louter(config) #ip dhcp pool VOICE
louter(dhcp-config) #network 192.168.10.0 255.255.255.0
touter(dhcp-config) #default-router 192.168.10.1
touter(dhcp-config) #opinion 150 ip 192.168.10.1
: Invalid input detected at '^' marker.
louter(dhcp-config) #opition 150 ip 192.168.10.1
: Invalid input detected at '^' marker.
louter(dhcp-config) #option 150 ip 192.168.10.1
louter (dhcp-config) #exit
louter (config) #telep
louter(config) #telephony-service
louter(config-telephony) #max-dn 5
louter (config-telephony) #max-ep
touter(config-telephony) #max-ephones 5
louter(config-telephony) #ip source-address 192.168.10.1 port 2000
louter(config-telephony) #auto assign 1 to 5
louter(config-telephony)#exit
louter(config)#
```

Вкл телефоны



Switch 0

```
Switch>en
Switch#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#int range fa0/1-6
Switch(config-if-range)#switchport mode access
Switch(config-if-range)#switchport voice vlan l
Switch(config-if-range)#
```

Зарегал телефоны

```
Router(config) #ephone-dn 1
Router(config-ephone-dn) #%LINK-3-UPDOWN: Interface ephone_dsp DN 1.1, change
Router(config-ephone-dn) #number 1000
```

```
Router(config-ephone-dn) #ephone-dn 2
Router(config-ephone-dn) #%LINK-3-UPDOWN: Interface ephone_dsp D
Router(config-ephone-dn) #number 1001
Router(config-ephone-dn) #
```

БЛИН ДЕДУ ЗВОНИТ. АЛО АЛО ДЕДУ

ПРИВЕТ ВНУЧОК ТЫ КОГДА МНЕ ЧЕРВЕЙ НАКОПАЕШ???

КАКИХ НАФИК ЧЕРВЕЙ Я В МАЙНКРАФТ ИГРАЮ

