AI Usage & Decision Note

Process. Update this note as work progresses. Important decisions require student acceptance before implementation or documentation. Keep English code/comments/documentation and Spanish collaboration.

Tools used. OpenAI Codex read the exam photographs, reviewed prior deliverables, proposed the design, implemented the backend and tests, and drafted documentation. Official Google documentation and installed ADK source informed framework integration. The earlier submission reports Claude Code use; that historical account was not independently verified. Runtime integration uses Google ADK and the Gemini API; provider failures currently prevent a successful real-model run.

Student decisions. The student rejected the initial LangGraph proposal and chose Google ADK. After reviewing the numbered proposals, the student approved a single-agent controlled workflow, deterministic policy/connection logic, privacy boundaries, human escalation, confirmation controls, SQLite, FastAPI, pytest and JSON traces. The student requested a local `.env` for the Gemini key and authorized implementation. These approvals do not imply the student personally ran tests or reviewed every generated line.

Accepted and revised outputs. Reused prior contracts, mocks, rule parsing and reconciliation, adapting them to the approved design. Replaced optional AI phrasing with mandatory model-selected function calls. Retained connection-risk wording rather than treating propagated departure delay as verified connection loss. The final passenger response is rendered from validated facts; unchecked LLM prose is not delivered. The adults-only control fixture uses a 200-minute delay to exercise eligible rebooking, distinct from the target's 160 minutes.

Rejected outputs. Rejected automatic compensation, booking remarks as instructions, zero fare difference as proof of a free change, and request acceptance as proof of a completed reservation. Gemini 2.5 Flash returned 404 indicating unavailability for new users; the configurable default was updated to the provider-recommended Gemini 3.8 Flash, whose published pricing includes a free tier.

Validation and limits. Codex ran 17 pytest tests and four scripted evaluations through ADK's real runner/function dispatcher; all passed. These verify controlled trajectories, responses, policy references and write safeguards, not Gemini's intent recognition. A scripted evaluation exposed unclosed SQLite connections preventing temporary-file cleanup on Windows; explicit closing fixed it. Actual Gemini requests and the four-case live evaluation returned HTTP 503 high-demand errors; saved evidence reports 0/4 live cases passing, not successful model behavior. No earlier test count is presented as evidence for this implementation.

Excluded information. The model-facing booking DTO excludes names, contact details, document numbers, raw booking/passenger IDs, loyalty data, exact age and remarks. The API key remains in ignored `.env`, never committed or placed in application traces. Known identities and common identifier patterns are redacted from input; arbitrary free-text PII detection is not guaranteed. Production identity, retention and human approval integration remain outside the implemented demo.