Introduction to Python

Operations and Variables

Topics

1) Arithmetic Operations
2) Floor Division vs True Division
3) Modulo Operator
4) Operator Precedence
5) String Concatenation
6) Augmented Assignment

Arithmetic Operations

Operator	Name	Description
`a + b`	Addition	Sum of a and b
`a - b`	Subtraction	Difference of a and b
`a * b`	Multiplication	Product of a and b
`a / b`	True division	Quotient of a and b
`a // b`	Floor division	Quotient of a and b, removing fractional parts
`a % b`	Modulus	Remainder after division of a by b
`a ** b`	Exponentiation	a raised to the power of b
`-a`	Negation	The negative of a
`+a`	Unary plus	a unchanged (rarely used)

Mixing Types

Any expression that two floats produce a float.

```
x = 17.0 - 10.0
print(x)        # 7.0
```

When an expression's operands are an int and a float, Python automatically converts the int to a float.

```
x = 17.0 - 10
print(x)        # 7.0
y = 17 - 10.0
print(y)        # 7.0
```

True Division vs Floor Division

The operator / is true division and the operator // returns floor division(round down after true divide). True divide / always gives the answer as a float.

```
print(23 // 7)      # 3
print(3 // 9)       # 0
print(-4 // 3)      # -2
print(6 / 5)        # 1.2
print(6 / 3)        # 2.0 NOT 2!
```

Remainder with %

The % operator computes the remainder after floor division.

- `14 % 4` is `2`
- `218 % 5` is `3`

```
    3
4 ) 14
   12
    2
```

```
   43
5 ) 218
   20
    18
    15
     3
```

Applications of % operator:

- Obtain last digit of a number: `230857 % 10` is `7`
- Obtain last 4 digits: `658236489 % 10000` is `6489`
- See whether a number is odd: `7 % 2` is `1`, `42 % 2` is `0`

Modulo Operator

The operator % returns the modulus which is the remainder after floor division.

```
print(18 % 5)         # 3
print(2 % 9)          # 2, if first number is smaller, it's the answer
print(125 % 10)       # 5
print(-17 % 10)       # 3
print(17 % -10)       # -3
```

Why floor/modulo division is useful

Floor division allows us to extract the integer part of the division while the modulo operator extracts the remainder part of the division. Consider the question:

How many weeks and days are there in 25 days?

Answer: 3 weeks plus 4 days.

```
num_weeks = 25 // 7  # extracting number of weeks
print(num_weeks)     # 3

num_days = 25 % 7    # extracting number of days
print(num_days)      # 4
```

Why the modulo operator is useful

If today is a Tuesday, which day is 43 days from today?

Answer: 43 divided by 7 is 6 with a remainder of 1. Thus, it will be Wednesday.

```
print(43 % 7)   # 1
```

Even/odd: A number x is even if x % 2 is 0 and odd if x % 2 is 1.

```
num = int(input('Please enter an integer value: '))
print(num, 'is even:', num%2==0)
```

Output 1:
Please enter an integer value: 4
4 is even: True

Output 2:
Please enter an integer value: 13
13 is even: False

Expressions

Find the exact change for 137 cents using quarters, dimes, nickels and cents. Use the least number of coins.

How many quarters? 137 // 25 = 5 quarters (Floor Division!)

What's leftover? 137 % 25 = 12 cents

How many dimes? 12 // 10 = 1 dime

What's leftover? 12 % 10 = 2 cents

How many nickels? 2 // 5 = 0 nickels.

What's leftover? 2 % 5 = 2 cents.

How many pennies? 2 // 1 = 2 pennies

What's leftover? 2 % 1= 0 cents. Done!

Extracting Digits

Given a three-digit integer. Extract its the ones, tens and hundreds digits.

For example, if the integer is 352. Its ones digit is the 2, its tens digit is the 5 and its hundreds digit is the 3.

```
number = 352
print("ones:", number % 10)          # ones: 2
number = number // 10                # number = 35 (discards last digit)
print(number)                        # 35
print("tens:", number % 10)          # tens: 5
number = number // 10                # number = 3 (discards last digit)
print(number)                        # 3
```

Note: Modulo 10 (% 10) extracts the last digit. Floor division (// 10) discards the last digit. Later in another lecture, we will see how to generalize this to any number of digits.

Extracting Digits

Alternatively:

```
number = 352
ones = number % 10
tens = (number // 10) % 10
hundreds = number // 100
print("ones:", ones, "tens", tens, "hundreds:", hundreds)
```

Output:

ones: 2 tens: 5 hundreds: 3

Exponentiation and Negation

```
x = 2 ** 3
print(x)        # 8
```

Negation is a **unary operator**. It applies to only one operand. Other operations such as +, -, *, /, //, % are **binary operators**, they apply to two operands.

```
x = -5
y = --5
print(x)    # -5
print(y)    # 5
```

Operator Precedence

Precedence	Operator	Operation
highest	**	exponentiation
	-	negation
	*, /, //, %	multiplication, division, floor division, modulus
lowest	+, -	adding, subtraction

Operators on the same row are applied left to right. Exponentiation, however, is applied right to left. Expressions in parenthesis are evaluated first(PEMDAS).

Operator Precedence

```
x = -2 ** 4
print(x)   # -16

y = 7 - 4 * 5 % (1 + 2)
print(y)   # 5
```

```
7 - 4 * 5 % (1 + 2)
  7 - 4 * 5 % 3
    7 - 20 % 3
      7 - 2
        5
```

Augmented Assignment

An **augmented assignment** combines an assignment statement with an operator to make the statement more concise.

Shorthand	Equivalent version
`variable += value;`	`variable = variable + value;`
`variable -= value;`	`variable = variable - value;`
`variable *= value;`	`variable = variable * value;`
`variable /= value;`	`variable = variable / value;`
`variable %= value;`	`variable = variable % value;`

```
x = 4
x += 1      # equivalent to x = x + 1
print(x)    # 5
```

Augmented Assignment

```
x = 3
x *= 2 + 5
print(x)              # 21

number = 5
number *= number
print(number)         # 25
```

String Concatenation

Two strings can be combined, or **concatenated**, using the + operator:

```
string1 = "abra"
string2 = "cadabra"
magic_string = string1 + string2
```

```
first = "Michael"
last = "Smith"
full_name = first + " " + last
```

Concatenating a string and a number raises a TypeError. Must first cast the number into a string using str().

```
apples = "I have " + 3 + "apples"    # error!
apples = "I have " + str(3) + "apples"    # correct!
```

Lab 1

Create a new repl on repl.it. Write code to match the following console output:

Enter a three-digit number: 245

The sum of the digits of 245 is 11.

Enter amount in cents: 137

Number of quarters: 5

Number of dimes: 1

Number of nickels: 0

Number of pennies: 2

References

1) Vanderplas, Jake, A Whirlwind Tour of Python, O'Reilly Media.
This book is completely free and can be downloaded online at O'reilly's site.