Introduction to Python

Basic Syntax

Datatypes II: Strings, NoneType

Topics

- I) Strings (indexing, slicing)
- 2) NoneType

String

Strings in Python are created with single or double quotes.

String Concatenation

String Indexing

```
In [23]: message = "what do you like?"
In [24]: message[0]
Out [24]: 'w'
In [24]: # negative indices wraps around the end
         message[-1] # last character
Out [24]: '?'
```

String Indexing and Slicing

```
In [23]: message = "what do you like?"
In [24]: # Access individual characters (zero-based indexing)
         message[0]
Out [24]: 'w'
In [25]: message[0:4] # up to but not including index 4
Out [25]: 'what'
In [25]: message [0:7:2] # step size of 2
Out [25]: 'wa o'
```

String Indexing and Slicing

```
In [26]: message = "python"
In [26]: # default start index is 0
         message[:4]
Out [26]: 'pyth'
In [27]: # default end index is length of string
         message[4:]
Out [27]: 'on'
In [28]: message[:] # default 0 to end of string
Out [28]: 'python'
```

String Indexing and Slicing

```
In [26]: message = "python"
In [24]: # negative indices wraps around the end
         message[-1] # last character
Out [24]: 'n'
In [25]: # all except the last character
         message[:-1]
Out [25]: 'pytho'
In [25]: # negative step size traverses backwards
         message[::-1]
Out [25]: 'nohtyp'
```

f-Strings

f-Strings is the new way to format strings in Python. (v 3.6)

f-Strings Precision

```
In [26]: import math
         x = math.pi
         print(f"{x}")
         print(f"{x:.2f}")
         print(f"{x:.3f}")
3.141592653589793
3.14
3.142
```

NoneType

Python includes a special type, the NoneType, which has only a single possible value: None.

```
In [24]: type(None)
```

Out [24]: NoneType

You'll see None used in many places, but perhaps most commonly it is used as the default return value of a function.

```
In [25]: return_value = print('abc')
abc
```

```
In [26]: print(return_value)
None
```

NoneType

You'll see None used in many places, but perhaps most commonly it is used as the default return value of a function.

```
In [25]: return_value = print('abc')
abc

In [26]: print(return_value)
None
```

References

1) Vanderplas, Jake, A Whirlwind Tour of Python, O'reilly Media.

This book is completely free and can be downloaded online at O'reilly's site.