

Introduction to Python

Tuples and Dictionaries

Topics

- 1) Tuples
- 2) Tuple unpacking
- 3) List of tuples, List of lists(2D lists)
- 4) enumerate()
- 5) Dictionaries
- 6) Iterating over a dictionary

Tuples

Tuples are in many ways similar to lists, but they are defined with parentheses rather than square brackets:

```
t = (1, 2, 3)
```

They can also be defined without any brackets at all:

```
t = 1, 2, 3  
print(t, type(t))  # (1, 2, 3) tuple
```

Tuples

Like the lists, tuples have a length and individual elements can be extracted using square-bracket indexing. Slicing is also supported.

```
t = (1, 2, 3)
print(len(t))      # 3
print(t[0])        # 1
print(t[0:2])      # [1, 2]
```

Tuples

Unlike lists, tuples are *immutable*: this means that once they are created, their size and contents cannot be changed:

```
lst = [1, 2, 3]
lst[1] = 5          # ok! a list is mutable
t = (1, 2, 3)
t[0] = 1            # error! a tuple is immutable
t.append(10)        # error! a tuple is immutable
```

Note: a tuple takes less memory than a list and can be generally manipulated faster.

Tuple Unpacking

Tuple unpacking is an assignment feature that assigns right hand side of values into left hand side. In packing, we put values into a new tuple while in unpacking we extract those values into a single variable.

This is packing values into a variable.

```
student = ("Mike Smith", 3.2)
```

This is unpacking values from a variable.

```
name, gpa = student  
print(name, gpa)      # Mike Smith 3.2
```

Tuple Unpacking

Tuple unpacking can be used to do parallel assignment.

```
a = 1
b = 2
a, b = b, a    # parallel assignment
print(a, b)    # 2 1
```

Note: In Java, you would need a temporary variable for this.

list(), tuple()

Converting between sequences can be done using the appropriate constructors: list(), tuple().

```
lst = [1, 2, 3]
```

```
t = tuple(lst)      # (1, 2, 3)
```

```
s = (1, 2, 3)
```

```
lst2 = list(s)      # [1, 2, 3]
```


Iterating over tuples

Like lists, we can iterate over a tuple.

```
lst = [1, 2, 3]
```

```
for x in lst:
```

```
    print(x, end=" ")
```

```
1 2 3
```

```
t = (1, 2, 3)
```

```
for y in t:
```

```
    print(y, end=" ")
```

```
1 2 3
```

List of Tuples

We can form a list of tuples(or of lists) and iterate over them.

There are three ways to iterate over a list of tuples.We will show code for all three methods in the next few slides.

Method 1) Using nested loop:

```
lst = [("Mike", 3.2), ("Sarah", 3.6), ("Jack", 2.8)]
```

```
for student in lst:  
    for data in student:  
        print(data)
```

Mike

3.2

Sarah

3.6

Jack

2.8

Note:We can use a list of lists in this example.

But this is a case where a list of tuples is a bit easier to use.

List of Tuples

We can form a list of tuples(or of lists) and iterate over them.

Method 2) Using []:

```
lst = [("Mike", 3.2), ("Sarah", 3.6), ("Jack", 2.8)]  
for student in lst:  
    print(student[0], student[1])
```

Mike 3.2

Sarah 3.6

Jack 2.8

List of Tuples

We can form a list of tuples(or of lists) and iterate over them.

Method 3) Using tuple unpacking. This is most pythonic method.

```
lst = [("Mike", 3.2), ("Sarah", 3.6), ("Jack", 2.8)]  
for name, gpa in lst: # tuple unpacking  
    print(name, gpa)
```

Mike 3.2

Sarah 3.6

Jack 2.8

Average GPA

Using tuple unpacking to compute the average.


```
lst = [("Mike", 3.2), ("Sarah", 3.6), ("Jack", 2.8)]  
s = 0  
for name, gpa in lst: # tuple unpacking  
    s += gpa  
ave = s / len(lst)
```

enumerate()

It is useful to have access to the index of elements when iterating over a list or 2D list. For example, if we need to modify elements of a list, having access to the indices is useful.

The `enumerate()` function adds an index to elements of the list and returns it.

```
lst = ['bread', 'milk', 'ham']  
for item in enumerate(lst):  
    print(item)
```



(0, 'bread') **This is a tuple!**

(1, 'milk')

(2, 'ham')

enumerate()

Unpacking from enumerate().

```
lst = ['bread', 'milk', 'ham']  
for t in enumerate(lst):  
    index, value = t          # unpacking  
    print(index, value)
```

Output:

```
0 bread  
1 milk  
2 ham
```

Or more simply(more pythonic):

```
lst = ['bread', 'milk', 'ham']  
for index, value in enumerate(lst):  
    print(index, value)
```

enumerate()

enumerate() is helpful when we want to modify our list.

```
lst = ['bread', 'milk', 'ham']  
for index, value in enumerate(lst):  
    if value == 'bread':  
        lst[index] = 'butter'  
print(lst)
```

Output:

```
['butter', 'milk', 'ham']
```


Dictionaries

Python lists are useful but in some applications, it is nice to have a different indexing scheme than the integers. For example, consider a database of students' names and their grades:

Mike Smith: [70, 81, 84]

Sarah Johnson: [88, 71, 85]

...

Suppose that this database has hundreds of records. It is hard to access these students' grades using 0-based integer indexing.

Python dictionaries allow "values" to be accessed by meaningful "keys". In the example above, we can access the database of grades by name(keys) instead of integer index.

Dictionaries

Dictionaries are extremely flexible mappings of keys to values, and form the basis of much of Python's internal implementation.

They can be created via a comma-separated list of key:value pairs within curly braces. The "keys" must be distinct.

```
data = {"Mike":3.1, "Sarah":3.6, "John":3.4}
print(data["Mike"])           # 3.1
gpa = data["John"]
print(gpa)                    # 3.4
print(len(data))              # 3
```

Dictionaries

New items can be added to the dictionary using indexing as well.

```
data = {"Mike":3.1, "Sarah":3.6, "John":3.4}  
data['Andy'] = 2.9  
print(data)
```

Output:

```
{'Mike': 3.1, 'Sarah': 3.6, 'John': 3.4, 'Andy': 2.9}
```

```
print(data['Courtney']) # KeyError  
                        # 'Courtney' not in set of keys
```

Dictionaries

Modifying dictionary.

```
data = {"Mike":3.1, "Sarah":3.6, "John":3.4}
data['Mike'] = 3.2
print(data)      # {'Mike': 3.2, 'Sarah': 3.6, 'John': 3.4}
data['Sarah'] += 0.2
print(data)      # {'Mike': 3.2, 'Sarah': 3.8, 'John': 3.4}
```

Membership Operations

By default, membership operations **checks keys** of a dictionary.

```
scores = {'Mike':5, 'John':2, 'Sarah':4}
```

```
print('Mike' in scores)           # True
```

```
print(5 in scores)                # False
```

```
print('Michele' not in scores)    # True
```

This will allow use to loop through a dictionary.

Iterating over keys a dictionary

It is easy to iterate over keys of the dictionary. The default loop iterates over the keys.

```
grades = {"Mike":3.1, "Sarah":3.6, "John":3.4}
for x in grades:
    print(x, end=" ")
```

Output:

Mike Sarah John

Iterating over keys a dictionary

The following compute the average GPA.

```
grades = {"Mike":3.1, "Sarah":3.6, "John":3.4}
sum = 0
for student in grades:
    sum += grades[student]
average = sum/len(grades)
```

Note: This `[]` syntax is the same as the syntax for lists and strings!

Other languages, like Java, has different syntax for accessing different data structures.

Example of a Use for Dictionaries

One use of a dictionary is keep track of frequency count.

```
words = ['baby', 'shark', 'do', 'do', 'do', 'do', 'do', 'do']
```

```
frequency = {}
```

```
for word in words:
```

```
    if word not in frequency:
```

```
        frequency[word] = 1
```

```
    else:
```

```
        frequency[word] += 1
```

```
print(frequency)
```

Output:

```
{'baby': 1, 'shark': 1, 'do': 6}
```

We will use this code to do word frequency analysis of the works of Shakespeare!

References

- I) Vanderplas, Jake, A Whirlwind Tour of Python, O'reilly Media.