

R version 3.5.0 (2018-04-23) -- "Joy in Playing"
 Copyright (C) 2018 The R Foundation for Statistical Computing
 Platform: x86_64-w64-mingw32/x64 (64-bit)

R is free software and comes with ABSOLUTELY NO WARRANTY.
 You are welcome to redistribute it under certain conditions.
 Type 'license()' or 'licence()' for distribution details.

Natural language support but running in an English locale

R is a collaborative project with many contributors.
 Type 'contributors()' for more information and
 'citation()' on how to cite R or R packages in publications.

Type 'demo()' for some demos, 'help()' for on-line help, or
 'help.start()' for an HTML browser interface to help.
 Type 'q()' to quit R.

[Previously saved workspace restored]

```
> #####portfolio b5
> #####Consider portfolios on derivatives based on 10 underlying uncorrelated assets
> #####investigate the loss probability, which is critical to estimating VAR
> install.packages("rootSolve")
Installing package into 'C:/Users/s1155058334/Documents/R/win-library/3.5'
(as 'lib' is unspecified)
--- Please select a CRAN mirror for use in this session ---
trying URL 'https://mirror-hk.koddos.net/CRAN/bin/windows/contrib/3.5/rootSolve_1.7.zip'
Content type 'application/zip' length 787735 bytes (769 KB)
downloaded 769 KB
```

package 'rootSolve' successfully unpacked and MD5 sums checked

```
The downloaded binary packages are in
  C:\Users\s1155058334\AppData\Local\Temp\RtmpuyyVaY\downloaded_packages
> library(rootSolve)
Warning message:
package 'rootSolve' was built under R version 3.5.2
> install.packages("gtools")
Installing package into 'C:/Users/s1155058334/Documents/R/win-library/3.5'
(as 'lib' is unspecified)
trying URL 'https://mirror-hk.koddos.net/CRAN/bin/windows/contrib/3.5/gtools_3.8.1.zip'
Content type 'application/zip' length 325812 bytes (318 KB)
downloaded 318 KB
```

package 'gtools' successfully unpacked and MD5 sums checked

```
The downloaded binary packages are in
  C:\Users\s1155058334\AppData\Local\Temp\RtmpuyyVaY\downloaded_packages
> library(gtools)
Warning message:
package 'gtools' was built under R version 3.5.2
> rm(list=ls())
>
> set.seed(3000)
> S0<-rep(100,10)
> T<-rep(0.1,10)
> sigma<-rep(0.3,10)
> r<-rep(0.05,10)
> K<-rep(100,10)
> H<-rep(95,10)
> dt<-0.04
> #####for the cash or nothing put options
> cash<-K
>
>
> #####define a function for calculating the value of a unit of down-and-out call option (long
  position), under risk neutral framework
> #####notice that H<K, refers to P.579 of Options, Futures, and Other Derivatives(8 ed.) for
  the pricing formula of down-and-out call option.
> #####MUST take into account the situation that the call options are knocked out at time t+de
  ltat
> Cdo<-function(S,T,t,sigma,r,K,H) {
```

```

+ lam<-(r+0.5*sigma^2)/(sigma^2)
+ y<-log((H^2)/S/K)/sigma/sqrt(T-t)+lam*sigma*sqrt(T-t)
+ cdi<-S*(H/S)^(2*lam)*pnorm(y)-K*exp(-r*(T-t))*(H/S)^(2*lam-2)*pnorm(y-sigma*sqrt(T-t))
+
+ d1<-(log(S/K)+(r+0.5*sigma^2)*(T-t))/(sigma*sqrt(T-t))
+ d2<-d1-sigma*sqrt(T-t)
+ c<-S*pnorm(d1)-K*exp(-r*(T-t))*pnorm(d2)
+
+ value<-(c-cdi)*(S>H)
+ return(value)
+ }
> #####All the partial derivatives, thus the greeks, are evaluated at t=0
> #####Calculating the greeks of down-and-out call options on each assets
> #####Since the theoretical greeks is complicated to derive, we approximate them with the Finite Difference Method at the moment
> dS<-0.01
> #####approximating delta of the Cdo's on each asset using FDM
> deltacdo<-(Cdo(S0+dS,T,0,sigma,r,K,H)-Cdo(S0,T,0,sigma,r,K,H))/dS
> #####approximating gamma of the cdo's on each asset using FDM
> gammacdo<-(Cdo(S0+dS,T,0,sigma,r,K,H)-2*Cdo(S0,T,0,sigma,r,K,H)+Cdo(S0-dS,T,0,sigma,r,K,H))/dS/dS
> #####approximating theta of the cdo's on each asset by the relation among theta, delta and gamma of an derivative at time 0 (OFAOD ed.10 P.393)
> thetacdo<-r*Cdo(S0,T,0,sigma,r,K,H)-r*S0*deltacdo-0.5*sigma^2*S0^2*gammacdo
>
>
> #####define a function for caluculating the value of a cash-or-nothing put option(long position), under risk neutral framework
> Pcon<-function(S,T,t,sigma,r,K,cash){
+ d1<-(log(S/K)+(r+0.5*sigma^2)*(T-t))/sigma/sqrt(T-t)
+ d2<-d1-sigma*sqrt(T-t)
+ pcon<-cash*exp(-r*(T-t))*pnorm(-d2)
+ return(pcon)
+ }
> #####All the partial derivatives, thus the greeks, are evaluated at t=0
> #####Calculating the greeks of cash-or-nothing put options on each assets
> d1<-(log(S0/K)+(r+0.5*sigma^2)*T)/sigma/sqrt(T)
> d2<-d1-sigma*sqrt(T)
> #####caluculating theta of the cash or nothing put options on each asset
> thetapcon<-r*cash*exp(-r*T)*pnorm(-d2)-cash*exp(-r*T)*dnorm(-d2)*(log(S0/K)/2/sigma*T^(-3/2)-(r-0.5*sigma^2)/2/sigma*T^(-1/2))
> #####caluculating delta of the cash or nothing put option on each asset
> deltapcon<-(-cash)*exp(-r*T)/S0/sigma/sqrt(T)*dnorm(-d2)
> #####caluculating gamma of the cash or nothing put option on each asset
> gammapcon<-(r*Pcon(S0,T,0,sigma,r,K,cash)-thetapcon-r*S0*deltapcon)*2/(sigma^2)/(S0^2)
> #####Cross validate against approximated greeks using FDM
> ##dS<-0.01
> ##deltapconpi<-(Pcon(S0+dS,T,0,sigma,r,K,cash)-Pcon(S0,T,0,sigma,r,K,cash))/dS
> ##gammapconpi<-(Pcon(S0+dS,T,0,sigma,r,K,cash)-2*Pcon(S0,T,0,sigma,r,K,cash)+Pcon(S0-dS,T,0,sigma,r,K,cash))/dS/dS
> ##thetapconpi<-r*Pcon(S0,T,0,sigma,r,K,cash)-r*S0*deltapconpi-0.5*sigma^2*S0^2*gammapconpi
> #####Checked
>
>
> #####characterize b5(short 10 down-and-out calls and short 5 cash-or-nothing put options on each assets)
> weightcdo<-rep(-10,10)
> weightpcon<-rep(-5,10)
> #####calculate the initial value of the portfolio (value at time 0)
> V0<-sum(weightcdo*Cdo(S0,T,0,sigma,r,K,H)+weightpcon*Pcon(S0,T,0,sigma,r,K,cash))
> V0
[1] -2809.468
> #####In order to simulate the loss, we have to be able to sample the change in asset price s(assumed to follow multivariate normal),
> #####Hence we need to approximate the SIGMA, given the asset price are uncorrelated, SIGMA is diagonal
> sigmadum<-S0^2*exp(2*r*dt)*(exp(sigma^2*dt)-1)
> SIGMA<-diag(sigmadum,10)
>
>
> #####consider Delta-GAMMA approximation of the portfolio loss, calculating the greeks of the portfolio
> #####caluculating theta of the portfolio consisting of mix of the options on the 10 assets
> THETA<-sum(weightcdo*thetacdo+weightpcon*thetapcon)

```

```

> #####caluculating delta of the portfolio(by assets) consisting of mix of the options on the
10 assets
> delta<-matrix(weightcdo*deltacdo+weightpcon*deltapcon,10,1)
> #####caluculating gamma of the portfolio(by pairs of assets) consisting of mix of the option
s on the 10 assets.
> GAMMA<-diag(weightcdo*gammaacdo+weightpcon*gammaapcon,10)
> #####Caluculating parameters for the Delta-Gamma approximatino on the portfolio loss
> a0=-THETA*dt
> a=-delta
> A=-1/2*GAMMA
>
>
> #-----#
>
>
> #####
> #####step1: Express Q in diagonal form
> Ct<-t(chol(SIGMA))
> ED<-eigen(t(Ct)%*%A%*%Ct)
> U<-ED$vectors
> LAMBDA<-diag(ED$values,10)
> C<-Ct%*%U
> b<-t(C)%*%a
> #define a function to calculate Q
> Q<-function(Z){t(b)%*%Z+t(Z)%*%LAMBDA%*%Z}
>
>
> #####
> #####step2: Identify the IS distribution  $Z \sim N(\text{thetax} * B(\text{thetax}) \% \% b, B(\text{thetax}))$ ,  $B(\text{thetax}) = \text{solve}(I - 2\text{thetax} * LAMBDA)$ 
> ###Given x, find thetax that makes  $E[Q] = (x - a_0)$  under the IS chagne of measure (assume D-G ap
proximation is exact)
> ###The x is adjusted so that the loss probability is close to 1.1%, xstd=2.75 under the orig
inal distribution of Z
> vecb<-as.vector(b)
> veclambda<-diag(LAMBDA)
> xstd<-2.75
> x<-(a0+sum(veclambda))+xstd*sqrt(sum(vecb^2)+2*sum(veclambda^2))
> ###To identify thetax, we numerically solve psipithetax=(x-a0), notice that  $E[Q] = \text{psipithetax}$ 
for general theta
> psipithetax<-function(thetax){
+ (thetax*vecb[1]^2*(1-thetax*veclambda[1])/(1-2*thetax*veclambda[1])^2 + veclambda[1]/(1-2*th
etax*veclambda[1])
+ +thetax*vecb[2]^2*(1-thetax*veclambda[2])/(1-2*thetax*veclambda[2])^2 + veclambda[2]/(1-2*th
etax*veclambda[2])
+ +thetax*vecb[3]^2*(1-thetax*veclambda[3])/(1-2*thetax*veclambda[3])^2 + veclambda[3]/(1-2*th
etax*veclambda[3])
+ +thetax*vecb[4]^2*(1-thetax*veclambda[4])/(1-2*thetax*veclambda[4])^2 + veclambda[4]/(1-2*th
etax*veclambda[4])
+ +thetax*vecb[5]^2*(1-thetax*veclambda[5])/(1-2*thetax*veclambda[5])^2 + veclambda[5]/(1-2*th
etax*veclambda[5])
+ +thetax*vecb[6]^2*(1-thetax*veclambda[6])/(1-2*thetax*veclambda[6])^2 + veclambda[6]/(1-2*th
etax*veclambda[6])
+ +thetax*vecb[7]^2*(1-thetax*veclambda[7])/(1-2*thetax*veclambda[7])^2 + veclambda[7]/(1-2*th
etax*veclambda[7])
+ +thetax*vecb[8]^2*(1-thetax*veclambda[8])/(1-2*thetax*veclambda[8])^2 + veclambda[8]/(1-2*th
etax*veclambda[8])
+ +thetax*vecb[9]^2*(1-thetax*veclambda[9])/(1-2*thetax*veclambda[9])^2 + veclambda[9]/(1-2*th
etax*veclambda[9])
+ +thetax*vecb[10]^2*(1-thetax*veclambda[10])/(1-2*thetax*veclambda[10])^2 + veclambda[10]/(1-
2*thetax*veclambda[10]))-(x-a0)
+ }
> curve(psipithetax)
> abline(h=0,v=0)
> uni<-uniroot.all(psipithetax,c(0,0.5))
> uni
[1] 0.008497496 0.137959273
>
> ###choose the thetax that makes a valid change of measure
> k<-0
> for(i in 1:length(uni)){
+ if(sum(sign(1-2*uni[i]*veclambda))==length(veclambda)){
+ k<-i

```

```

+ break}
+ }
> (thetax<-uni[k])
[1] 0.008497496
> psipithetax(thetax)
[1] -0.4276395
> ax<-thetax-0.0001
> bx<-thetax+0.0001
> while(abs(psipithetax(thetax))>0.0000001){
+ thetax<-(ax+bx)/2
+ ifelse(sign(psipithetax(thetax))==sign(bx),bx<-(ax+bx)/2,ax<-(ax+bx)/2)
+ }
> thetax
[1] 0.008501598
> psipithetax(thetax)
[1] -2.281865e-08
>
> ###identify the IS distribution
> Bthetax<-solve(diag(10)-2*thetax*LAMBDA)
> muthetax<-thetax*Bthetax*%*%b
>
> ###generate 5000000 samples of Q under IS change of measure, check whether E[Q] approximatel
y equals (x-a0)
> Qsamples<-rep(0,5000000)
> for(j in 1:5000000){
+ Z<-muthetax+chol(Bthetax)*%*%matrix(rnorm(10),10,1)
+ Qsamples[j]<-Q(Z)
+ }
> ###check whether E[Q] approximately equals (x-a0) under the importance sampling change of me
asure
> mean(Qsamples)
[1] 807.5491
> x-a0
[1] 807.4484
> a0
[1] -33.50115
> x
[1] 773.9472
> thetax
[1] 0.008501598
> #####By trial and error, a more accurate thetax would be 0.008501598
>
> ###display the parameters
> SIGMA
      [,1]      [,2]      [,3]      [,4]      [,5]      [,6]      [,7]      [,8]      [,9]     [,10]
[1,] 36.20943  0.00000  0.00000  0.00000  0.00000  0.00000  0.00000  0.00000  0.00000  0.0000
0
[2,]  0.00000 36.20943  0.00000  0.00000  0.00000  0.00000  0.00000  0.00000  0.00000  0.0000
0
[3,]  0.00000  0.00000 36.20943  0.00000  0.00000  0.00000  0.00000  0.00000  0.00000  0.0000
0
[4,]  0.00000  0.00000  0.00000 36.20943  0.00000  0.00000  0.00000  0.00000  0.00000  0.0000
0
[5,]  0.00000  0.00000  0.00000  0.00000 36.20943  0.00000  0.00000  0.00000  0.00000  0.0000
0
[6,]  0.00000  0.00000  0.00000  0.00000  0.00000 36.20943  0.00000  0.00000  0.00000  0.0000
0
[7,]  0.00000  0.00000  0.00000  0.00000  0.00000  0.00000 36.20943  0.00000  0.00000  0.0000
0
[8,]  0.00000  0.00000  0.00000  0.00000  0.00000  0.00000  0.00000 36.20943  0.00000  0.0000
0
[9,]  0.00000  0.00000  0.00000  0.00000  0.00000  0.00000  0.00000  0.00000 36.20943  0.0000
0
[10,] 0.00000  0.00000  0.00000  0.00000  0.00000  0.00000  0.00000  0.00000  0.00000 36.2094
3
> THETA
[1] 837.5286
> a0
[1] -33.50115
> delta
      [,1]
[1,] 14.04863
[2,] 14.04863

```

```

[3,] 14.04863
[4,] 14.04863
[5,] 14.04863
[6,] 14.04863
[7,] 14.04863
[8,] 14.04863
[9,] 14.04863
[10,] 14.04863
> a
      [,1]
[1,] -14.04863
[2,] -14.04863
[3,] -14.04863
[4,] -14.04863
[5,] -14.04863
[6,] -14.04863
[7,] -14.04863
[8,] -14.04863
[9,] -14.04863
[10,] -14.04863
> GAMMA
      [,1]      [,2]      [,3]      [,4]      [,5]      [,6]      [,7]      [,8]
      [,9]      [,10]
[1,] -0.3734297  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000
0.0000000  0.0000000
[2,]  0.0000000 -0.3734297  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000
0.0000000  0.0000000
[3,]  0.0000000  0.0000000 -0.3734297  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000
0.0000000  0.0000000
[4,]  0.0000000  0.0000000  0.0000000 -0.3734297  0.0000000  0.0000000  0.0000000  0.0000000
0.0000000  0.0000000
[5,]  0.0000000  0.0000000  0.0000000  0.0000000 -0.3734297  0.0000000  0.0000000  0.0000000
0.0000000  0.0000000
[6,]  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000 -0.3734297  0.0000000  0.0000000
0.0000000  0.0000000
[7,]  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000 -0.3734297  0.0000000
0.0000000  0.0000000
[8,]  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000 -0.3734297
0.0000000  0.0000000
[9,]  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000
-0.3734297  0.0000000
[10,] 0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000
0.0000000 -0.3734297
> A
      [,1]      [,2]      [,3]      [,4]      [,5]      [,6]      [,7]      [,8]      [,9]
      [,10]
[1,] 0.1867149  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000
0 0.0000000
[2,] 0.0000000  0.1867149  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000
0 0.0000000
[3,] 0.0000000  0.0000000  0.1867149  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000
0 0.0000000
[4,] 0.0000000  0.0000000  0.0000000  0.1867149  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000
0 0.0000000
[5,] 0.0000000  0.0000000  0.0000000  0.0000000  0.1867149  0.0000000  0.0000000  0.0000000  0.0000000
0 0.0000000
[6,] 0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.1867149  0.0000000  0.0000000  0.0000000
0 0.0000000
[7,] 0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.1867149  0.0000000  0.0000000
0 0.0000000
[8,] 0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.1867149  0.0000000
0 0.0000000
[9,] 0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.1867149
9 0.0000000
[10,] 0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000  0.0000000
0 0.1867149
>
> b
      [,1]
[1,] -84.53663
[2,] -84.53663
[3,] -84.53663
[4,] -84.53663
[5,] -84.53663

```

```

[6,] -84.53663
[7,] -84.53663
[8,] -84.53663
[9,] -84.53663
[10,] -84.53663
> LAMBDA
      [,1]      [,2]      [,3]      [,4]      [,5]      [,6]      [,7]      [,8]      [,9]     [,10]
]
[1,] 6.760838 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000
0
[2,] 0.000000 6.760838 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000
0
[3,] 0.000000 0.000000 6.760838 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000
0
[4,] 0.000000 0.000000 0.000000 6.760838 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000
0
[5,] 0.000000 0.000000 0.000000 0.000000 6.760838 0.000000 0.000000 0.000000 0.000000 0.000000
0
[6,] 0.000000 0.000000 0.000000 0.000000 0.000000 6.760838 0.000000 0.000000 0.000000 0.000000
0
[7,] 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 6.760838 0.000000 0.000000 0.000000
0
[8,] 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 6.760838 0.000000 0.000000
0
[9,] 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 6.760838 0.000000
0
[10,] 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 6.76083
8
> muthetax
      [,1]
[1,] -0.8120459
[2,] -0.8120459
[3,] -0.8120459
[4,] -0.8120459
[5,] -0.8120459
[6,] -0.8120459
[7,] -0.8120459
[8,] -0.8120459
[9,] -0.8120459
[10,] -0.8120459
> Bthetax
      [,1]      [,2]      [,3]      [,4]      [,5]      [,6]      [,7]      [,8]      [,9]     [,10]
]
[1,] 1.129887 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000
0
[2,] 0.000000 1.129887 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000
0
[3,] 0.000000 0.000000 1.129887 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000
0
[4,] 0.000000 0.000000 0.000000 1.129887 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000
0
[5,] 0.000000 0.000000 0.000000 0.000000 1.129887 0.000000 0.000000 0.000000 0.000000 0.000000
0
[6,] 0.000000 0.000000 0.000000 0.000000 0.000000 1.129887 0.000000 0.000000 0.000000 0.000000
0
[7,] 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 1.129887 0.000000 0.000000 0.000000
0
[8,] 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 1.129887 0.000000 0.000000
0
[9,] 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 1.129887 0.000000
0
[10,] 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 1.12988
7
>
>
> #-----#
>
> ###define a function that calculate the Loss for a generated ds (ds=C%*%Z)
> L<-function(dS){
+   Sdt<-S0+as.vector(dS)
+   Vdt<-sum(weightcdo*Cdo(Sdt,T,dt,sigma,r,K,H)+weightpcon*Pcon(Sdt,T,dt,sigma,r,K,cash
+ ))
+   return(V0-Vdt)

```

```

+ }
> ###define a function that calculate the likelihood ratio for a generated Z
> likelihood<-function(Z){
+ p1<-sum((1/2)*((thetax*vecb)^2/(1-2*thetax*veclambda)-log(1-2*thetax*veclambda)))
+ p2<-thetax*Q(Z)
+ return(exp(p1-p2))
+ }
>
> #-----#
>
>
> #####
> #####step3: Define k strata
> ###plot the empirical CDF
> Qsamples<-sort(Qsamples,decreasing=FALSE)
> ECDFb5<-ecdf(Qsamples)
> #plot.ecdf(Qsamples)
> ###mimics the quantiles of Q using the 5000000 samples of Q generated in the previous step
> stratabyQ<-rep(0,40-1)
> for(i in 1:39){stratabyQ[i]<-quantile(Qsamples,0.025*i)}
> stratabyQ
[1] 196.8038 290.0317 351.3856 399.0340 438.9165 473.7160 505.0928 533.6544 560.4106
585.7383 609.7575 632.8191
[13] 655.0433 676.7334 697.8152 718.5402 739.0852 759.4083 779.6488 799.8870 820.1476
840.5805 861.2837 882.2493
[25] 903.5576 925.4474 948.0464 971.3481 995.5572 1021.0183 1048.0145 1076.8296 1107.9985
1142.3368 1181.0642 1225.8950
[37] 1280.2102 1351.3315 1461.9436
> ECDFb5(stratabyQ)
[1] 0.025 0.050 0.075 0.100 0.125 0.150 0.175 0.200 0.225 0.250 0.275 0.300 0.325 0.350 0.375
0.400 0.425 0.450 0.475 0.500
[21] 0.525 0.550 0.575 0.600 0.625 0.650 0.675 0.700 0.725 0.750 0.775 0.800 0.825 0.850 0.875
0.900 0.925 0.950 0.975
>
> ###calculate the optimal allocation of samples size for each strata
> options(warn=-1)
> bins<-c(stratabyQ,.Machine$double.xmax)
> vars<-matrix(0,40,10000)
> counts<-rep(0,40)
> while(sum(counts)!=400000){
+ Z<-muthetax+chol(Bthetax)%*%matrix(rnorm(10),10,1)
+ k<-tail(binsearch(function(y) bins[y]-(Q(Z)), range=c(1, length(bins))))$where,1)
+ if(counts[k]<10000){
+ counts[k]<-counts[k]+1
+ vars[k,counts[k]]<-ifelse(L(C%*%Z)>x,1,0)*likelihood(Z)
+ }
+ else{}
+ }
> (dumvar<-apply(vars,1,var))
[1] 0.000000e+00 0.000000e+00 0.000000e+00 0.000000e+00 0.000000e+00 0.000000e+00 0.000000e+00 0.000000e+00
0 9.840296e-05 1.022001e-04
[10] 2.165604e-04 3.699105e-04 1.079643e-03 2.055780e-03 2.261316e-03 2.140477e-03 1.681862e-03
3 1.204805e-03 8.161134e-04
[19] 5.284948e-04 3.334967e-04 2.118773e-04 1.242773e-04 7.435835e-05 4.115145e-05 2.422504e-05
5 1.251744e-05 7.459260e-06
[28] 3.739792e-06 1.990309e-06 1.023459e-06 5.759874e-07 2.432131e-07 1.230038e-07 7.039274e-08
8 3.634879e-08 1.993011e-08
[37] 1.248842e-08 7.131167e-09 3.830684e-09 1.549497e-09
> #Since we assume equiprobable strata, pj=1/k, where k is the number of strata, which is 40 i
n the case
> (qj<-sqrt(dumvar)/sum(sqrt(dumvar)))
[1] 0.000000e+00 0.000000e+00 0.000000e+00 0.000000e+00 0.000000e+00 0.000000e+00 0.000000e+00 0.000000e+00
0 2.305211e-02 2.349267e-02
[10] 3.419765e-02 4.469460e-02 7.635664e-02 1.053647e-01 1.105064e-01 1.075132e-01 9.530198e-02
2 8.066129e-02 6.638683e-02
[19] 5.342285e-02 4.243776e-02 3.382586e-02 2.590614e-02 2.003879e-02 1.490731e-02 1.143771e-02
2 8.221754e-03 6.346796e-03
[28] 4.493973e-03 3.278438e-03 2.350942e-03 1.763653e-03 1.146041e-03 8.150158e-04 6.165533e-04
4 4.430489e-04 3.280663e-04
[37] 2.596931e-04 1.962398e-04 1.438285e-04 9.147492e-05
>
>
> #####

```

```

> #####step4: Perform the simulation
> ###define a function to generate estimates of  $P\{L>x_p\}$  using three methods: SMC, IS, ISSQ, IS
SQO
> options(warn=-1)
> run<-function(n,strata){
+
+ results<-rep(0,4)
+ SMC<-0
+ IS<-0
+ ISSQ<-0
+ ISSQO<-0
+
+ bins<-c(stratabyQ,.Machine$double.xmax)
+ binscount<-rep(0,strata)
+ binscountpi<-rep(0,strata)
+
+ nj<-round(n*qj)
+ nj[match(max(nj),nj)]<-nj[match(max(nj),nj)]+(n-sum(nj))
+
+
+ for(i in 1:n){
+ Z1<-matrix(rnorm(10),10,1)
+ #Standard Monte Carlo
+ dS1<-C%%Z1
+ L1<-L(dS1)
+ SMC<-SMC+(ifelse(L1>x,1,0)*(1/n))
+
+ Z2<-muthetax+chol(Bthetax)%%Z1
+ #Monte Carlo (IS)
+ dS2<-C%%Z2
+ L2<-L(dS2)
+ IS<-IS+(ifelse(L2>x,1,0)*likelihood(Z2)*(1/n))
+ kthbins<-tail(binsearch(function(y) bins[y]-(Q(Z2)), range=c(1, length(bins)))$where,1)
+ #Monte Carlo (IS and Stratification)
+ if(binscount[kthbins]<(n/strata)){
+ binscount[kthbins]<-binscount[kthbins]+1
+ ISSQ<-ISSQ+(ifelse(L2>x,1,0)*likelihood(Z2)*(1/n))
+ }
+ else{
+ }
+ #Monte Carlo (IS and Stratification with optimized sample size for each strata)
+ if(binscountpi[kthbins]<nj[kthbins]){
+ binscountpi[kthbins]<-binscountpi[kthbins]+1
+ ISSQO<-ISSQO+(ifelse(L2>x,1,0)*likelihood(Z2)*(1/nj[kthbins]))*(1/strata))
+ }
+ else{
+ }
+ }
+ results[1]<-SMC
+ results[2]<-IS
+
+
+ while(sum(binscount)<n){
+ Z2<-muthetax+chol(Bthetax)%%matrix(rnorm(10),10,1)
+ kthbins<-tail(binsearch(function(y) bins[y]-(Q(Z2)), range=c(1, length(bins)))$where,1)
+ #Monte Carlo (IS and Stratification) continue...
+ if(binscount[kthbins]<(n/strata)){
+ binscount[kthbins]<-binscount[kthbins]+1
+ ISSQ<-ISSQ+(ifelse(L(C%%Z2)>x,1,0)*likelihood(Z2)*(1/n))
+ }
+ else{
+ }
+ }
+ #Monte Carlo (IS and Stratification with optimized sample size for each strata) continue...
+ if(binscountpi[kthbins]<nj[kthbins]){
+ binscountpi[kthbins]<-binscountpi[kthbins]+1
+ ISSQO<-ISSQO+(ifelse(L(C%%Z2)>x,1,0)*likelihood(Z2)*(1/nj[kthbins]))*(1/strata))
+ }
+ else{
+ }
+ }
+ results[3]<-ISSQ
+
+
+ while(sum(binscountpi)<n){
+ Z2<-muthetax+chol(Bthetax)%%matrix(rnorm(10),10,1)

```



```

+ kthbins<-tail(binsearch(function(y) bins[y]-(Q(Z2)), range=c(1, length(bins)))$where,1)
+ #Monte Carlo (IS and Stratification with optimized sample size for each strata) continue...
+ if(binscountpi[kthbins]<nj[kthbins]){
+ binscountpi[kthbins]<-binscountpi[kthbins]+1
+ ISSQO<-ISSQO+(ifelse(L(C%*%Z2)>x,1,0)*likelihood(Z2)*(1/nj[kthbins])*(1/strata))
+ }
+ else{
+ }
+ }
+ results[4]<-ISSQO
+
+ return(results)
+ }
> run(1000,40)
[1] 0.00800000 0.01137408 0.01144932 0.01080505
> run(10000,40)
[1] 0.00950000 0.01061067 0.01067615 0.01055742
>
> ###define a function to generate the replications
> replication<-function(N,n,strata){
+ dum<-c(0,0,0,0)
+ for(i in 1:N){
+ dum<-rbind(dum,run(n,strata))
+ }
+ return(tail(dum,-1))
+ }
>
>
> #####
> #####Step5:evaluate the performance of the algorithm
> SAMPLES<-replication(10000,10000,40)
> (ISratio<-var(SAMPLES[,1])/var(SAMPLES[,2]))
[1] 21.64032
> (ISSQratio<-var(SAMPLES[,1])/var(SAMPLES[,3]))
[1] 31.45442
> (ISSQOratio<-var(SAMPLES[,1])/var(SAMPLES[,4]))
[1] 94.41758
>
> n<-10000
> strata<-40
> var(SAMPLES[,1])
[1] 1.076677e-06
> (sum(sqrt(dumvar)*(1/strata)))^2/n
[1] 1.157355e-08
> (theoreticalISSQOratio<-var(SAMPLES[,1])/((sum(sqrt(dumvar)*(1/strata)))^2/n))
[1] 93.02914
>
> save.image("C:\\Users\\s1155058334\\Desktop\\portfolio b5 (5.3) os5 pending\\b5os5workspace
")
>

```