### **NAME**

xzcmp, xzdiff, lzcmp, lzdiff - compare compressed files

### **SYNOPSIS**

```
xzcmp [cmp_options] file1 [file2]
xzdiff [diff_options] file1 [file2]
lzcmp [cmp_options] file1 [file2]
lzdiff [diff_options] file1 [file2]
```

# **DESCRIPTION**

**xzcmp** and **xdiff** invoke **cmp**(1) or **diff**(1) on files compressed with **xz**(1), **lzma**(1), **gzip**(1), or **bzip2**(1). All options specified are passed directly to **cmp** or **diff**. If only one file is specified, then the files compared are *file1* (which must have a suffix of a supported compression format) and *file1* from which the compression format suffix has been stripped. If two files are specified, then they are uncompressed if necessary and fed to **cmp**(1) or **diff**(1). The exit status from **cmp** or **diff** is preserved.

The names  ${\bf lzcmp}$  and  ${\bf lzdiff}$  are provided for backward compatibility with LZMA Utils.

## **SEE ALSO**

```
\boldsymbol{cmp}(1),\,\boldsymbol{diff}(1),\,\boldsymbol{xz}(1),\,\boldsymbol{gzip}(1),\,\boldsymbol{bzip2}(1),\,\boldsymbol{zdiff}(1)
```

### **BUGS**

Messages from the  $\mbox{cmp}(1)$  or  $\mbox{diff}(1)$  programs refer to temporary filenames instead of those specified.