From the First Token

Building Language Models from Scratch

Wanglong Lu

2026-10-28 · Public Reading Edition

Contents

Rights and use 1

A note to the reader 2
- The route through the book . . . 2
- How to read the figures . . . 3
- How to use the companion code . . . 3
- How to follow the sources . . . 4

Technical Introduction 5
- Start with a model whose workings you can see . . . 5
- Your starting point . . . 6
- An implementation that grows in stages . . . 6
- Work through a section completely . . . 8
- From implementation to your own experiments . . . 8

Notation and conventions 10

01 Text becomes data 12
- 01.01 Text, Tokens, and Next-Token Targets . . . 12
- Looking back . . . 19

02 Learn a vocabulary 20
- 02.01 BPE and Adjacent Pair Counts . . . 20
- 02.02 Non-Overlapping BPE Merges . . . 24
- 02.03 The BPE Training Loop . . . 27
- 02.04 Select a Learned BPE Rule . . . 31
- 02.05 Encode New Text with Frozen BPE Rules . . . 35
- 02.06 Decode BPE Tokens Back to Text . . . 40
- 02.07 Save and Reload a Tokenizer . . . 44
- Looking back . . . 50

03 Make a model learn 51
- 03.01 Token IDs to Embedding Vectors . . . 51
- 03.02 Parameters, Loss, and Gradients . . . 57
- 03.03 A Scalar Training Loop . . . 63
- 03.04 Chain Rule and Automatic Differentiation . . . 68

03.05 Scalar Automatic Differentiation with PyTorch . . . 73
03.06 Updating a Tensor Parameter . . . 78
03.07 A Tensor Training Loop . . . 88
03.08 Trainable Embeddings . . . 94
03.09 Logits and Softmax . . . 107
03.10 Cross-Entropy for Next-Token Targets . . . 121
03.11 One Joint Next-Token Training Step . . . 132
03.12 Repeat the Next-Token Training Step . . . 142
03.13 Predict One Next Token . . . 149
03.14 Autoregressive Generation . . . 157
03.15 Temperature and Sampling . . . 163
03.16 Sampled Autoregressive Generation . . . 168
03.17 EOS and Generation Stopping . . . 174
03.18 Decode the Generated Continuation . . . 181
03.19 Batched Next-Token Training Windows . . . 187
03.20 Batched Logits and Mean Token Loss . . . 194
03.21 One Joint Update from a Next-Token Batch . . . 201
03.22 Persistent Training over Ordered Batches . . . 209
03.23 Fixed-Parameter Batch Loss Evaluation . . . 218
03.24 Connect the small baseline . . . 226
Looking back . . . 237

04 Build a causal Transformer **238**
04.01 Why context matters . . . 238
04.02 Registered parameters and modules . . . 248
04.03 Query, key and value projections . . . 252
04.04 Scaled dot-product attention . . . 258
04.05 Causal visibility and isolation . . . 271
04.06 Multiple attention heads . . . 287
04.07 Learned absolute position vectors . . . 298
04.08 Residuals, LayerNorm and a position-wise FFN . . . 316
04.09 Assemble a causal decoder . . . 326
04.10 Train and generate with the tiny Transformer . . . 337
Looking back . . . 352

05 Choose reliable model components **353**
05.01 RMS normalization . . . 353
05.02 RoPE, rotary query and key positions . . . 360
05.03 SwiGLU, gated feed-forward networks . . . 379
05.04 Compose the modern baseline . . . 387
05.05 AdamW, initialization and weight decay . . . 403
05.06 Learning-rate schedules and global gradient clipping . . . 418

05.07 Exact checkpoint and resume . . . 428
Looking back . . . 442

06 Turn documents into pretraining **443**
06.01 Data provenance and fingerprints . . . 443
06.02 Split by document before windows . . . 452
06.03 Cleaning and deduplication . . . 466
06.04 Frozen tokenizer and special IDs . . . 478
06.05 Packing and supervision masks . . . 489
06.06 A complete pretraining experiment . . . 504
Looking back . . . 519

07 Measure and use the model **520**
07.01 Token-aware language metrics . . . 520
07.02 Fixed evaluation protocols . . . 537
07.03 KV cache and position alignment . . . 556
07.04 Turn a KV cache into a generation loop . . . 568
Looking back . . . 578

08 Teach responses and preferences **579**
08.01 Give a conversation an exact token format . . . 579
08.02 Assistant-only supervised fine-tuning . . . 591
08.03 Direct preference optimization . . . 594
08.04 Rewards, advantages and clipped policy objectives . . . 597
Looking back . . . 601

09 Scale execution without losing meaning **602**
09.01 Memory, compute and profiling . . . 602
09.02 Position-weighted gradient accumulation . . . 605
09.03 Autocast and gradient scaling . . . 608
09.04 Efficient attention with equivalence checks . . . 611
09.05 Distributed gradients and recovery . . . 615
Looking back . . . 618

10 Make experiments explainable **619**
10.01 Reproducible experiment records . . . 619
10.02 Measured scaling and budget choices . . . 622
10.03 Original ideas, ablations and uncertainty . . . 625
Looking back . . . 629

Appendix A Glossary **630**
Text and tokenization . . . 630
Tensors and learning . . . 630

Attention and architecture 631
Optimization and execution 632
Data, evaluation and alignment 633

Appendix B Companion exercises **635**

References **636**

Edition and production **639**

Rights and use

From the First Token: Building Language Models from Scratch

Author: **Wanglong Lu (卢望龙)**. Copyright 2026.

The book is shared under **Creative Commons Attribution–NonCommercial–NoDerivatives 4.0 International (CC BY-NC-ND 4.0)**, except for separately identified software and third-party material. You may copy and share the unchanged book noncommercially while retaining the author, title, version and license notice. Sharing an altered or translated edition requires separate permission. Private annotations, permitted format changes and applicable statutory rights are not removed by this notice. Full license.

The separately supplied teaching exercises and author-owned executable code examples are available under **PolyForm Noncommercial 1.0.0**. That software license permits changes and sharing for its defined permitted purposes, with its required notices. Commercial uses outside those permissions require separate authorization. Software terms.

The author retains the ability to grant separate commercial permissions for material the author has the right to license. Third-party software, fonts and cited works retain their own rights and terms.

A note to the reader

In early 2023, I gave GPT a serious try for the first time. I had heard about it, but the descriptions had not made much of an impression on me. Then I asked it to write some PyTorch code. I remember being surprised by what appeared on the screen. I did not even run that first snippet. Seeing it write familiar code from a short conversation was enough to make me stop and pay attention.

By then, I had been researching deep learning algorithms for four or five years, often working with PyTorch and Transformer-based methods. I continued to follow new models and papers, and later built agent workflows in my day-to-day work. Those experiences kept bringing me back to one question: how did all the pieces inside a language model actually work together? Using a model, reading its architecture and tracing an implementation each reveal different parts of the answer. I wanted to connect them.

That led me back through the whole pipeline. I took each step apart, worked through a small example, wrote and ran the code, and checked the intermediate results. Then I put the pieces together and trained a small model from scratch. Each run gave me something concrete to examine: a shape I had misunderstood, a loss that needed explaining, or a result that did not support the conclusion I had expected. Writing those explanations down became this book.

For me, learning by doing means giving an idea a calculation and an implementation that I can inspect. The small examples matter because they make it possible to follow every value. Connecting those examples matters because a working system creates questions that isolated formulas leave open. I hope the route in these pages gives you room to try things, make mistakes, and work out why a correction helps.

You may be building your first language model, or revisiting methods you already use. Either way, take your time with the examples. Change a value, predict what should happen, and then run the code. I hope you enjoy the process, and that the next model or paper you encounter becomes a little easier to reason about.

The route through the book

A language model is easier to understand when one prediction can be followed all the way through. A piece of text becomes a sequence of IDs. Those IDs select vectors. The model transforms the vectors, assigns a score to each possible next token, and turns those scores into a distribution. A training example tells us which token actually followed. The difference between prediction and observation becomes a loss; differentiation tells us how to change the parameters.

This book builds that chain without asking you to accept its middle steps on trust. We begin with bytes and short lists, then use small tensors whose entries can be checked by hand. Attention appears

when a model needs context. Position information appears when order matters. Checkpoints appear when a training run must survive interruption. Evaluation appears when a plausible answer is no longer enough to establish an improvement. Each addition answers a problem created by the implementation that came before it.

The book grew alongside a learning project called OneLong. Its teaching examples preserve questions that often disappear from finished explanations: Is a token ID a count? Why does lookup add a dimension? Why does training predict at several known positions while generation chooses one new token? Which mask belongs to which axis? These questions are part of the technical argument. Understanding an implementation means being able to answer them precisely.

The chapters have a practical rhythm. Read the idea and its notation, trace a complete example, then write the core of a small function. The supplied check driver helps you locate mistakes. It cannot replace an explanation of why the calculation works. Return to the example whenever a line of code looks like an unexplained trick.

The later chapters extend the model to instruction tuning, efficient execution and reproducible experiments. Each exercise develops one part of the system; the chapter summaries show how those parts fit into a training or inference run. For an experiment, record the data, budget and evaluation method alongside its result so the calculation can be reconstructed.

The ten chapters follow this route from text representation to a complete model and its experiments. Read them in order when the material is new. When reviewing a familiar topic, begin with its worked example: explain the shapes, reproduce the values, then compare your reasoning with the implementation guidance.

How to read the figures

Square brackets describe a tensor's **shape**, such as `[B,T,D]`. A displayed matrix contains **values**. A shape labels an axis; a value occupies a position on that axis. When a figure shows both, read the shape first and then trace the selected values through the operation. A vocabulary index, a position index and a feature index are different quantities even when an example happens to give them the same number.

How to use the companion code

The chapter and section numbers match the shared assignment filenames. For example, Section 04.04 uses `exercises/04_04_scaled_attention.py`. Work from the companion package root and create the Python environment described in its README. Read the function contract before editing the region marked `START LEARNER CODE`. The surrounding setup and supplied driver make the exercise repeatable.

The book gives derivations, examples and implementation guidance. It leaves the central implementation to you. If a helper requires an unfinished earlier exercise, finish that prerequisite before interpreting a failure as an environment problem. Details of the repository layout, checks and release identity appear in the appendices.

How to follow the sources

Key methods have a Method sources paragraph near their introduction. A citation such as “Su et al., 2021; R07” identifies the authors and year and the matching full entry in References; its link opens the primary source. These notes distinguish the method from our small implementation and examples. Software behavior is tied to the cited documentation version. Appendix A gives English definitions of the book’s terms.

Technical Introduction

Enter some text, and new text follows it on the screen. This familiar process contains a sequence of computations we can take apart: text becomes integers, integers select vectors, a model transforms vectors into scores, scores form probabilities, and selected tokens become text again. Training adjusts the parameters within those computations using examples.

This book follows that path by building a language model. We begin with examples small enough to calculate by hand, make the movement of data and parameters visible, and gradually add context, attention, and a more complete training system. Each new component comes with an explanation of the problem it addresses and a way to check its behavior.

The aim is to let you follow a prediction, a backward pass, and a parameter update through your own code, understand where an experimental result comes from, and use that understanding to plan a change.

Start with a model whose workings you can see

The main subject is a causal language model that predicts the next token from an available prefix. A token is a unit defined by a tokenizer: it may represent a byte, a text fragment, or an agreed special marker. Its ID is an index in the vocabulary. Selecting a new token, appending it to the input, and predicting again produces incremental generation.

With our first byte tokenizer, `hello` becomes `[104, 101, 108, 108, 111]`. This known text provides the input `hell` and target `ello`: every target is one source position after its corresponding input. In a causally constrained model, a position can use only the input prefix through that position. Training has the targets supplied by the source text; generation selects new continuation IDs step by step.

We then connect integer IDs to learnable floating-point parameters, calculate scores for vocabulary candidates, and form a loss using the true targets' probabilities. Gradients describe how local parameter changes affect the loss, and an update rule adjusts the parameters accordingly. The earliest baseline scores each current ID independently. Its limitations give us a concrete reason to introduce context.

Small examples expose dependencies. We can inspect the number of rows in a tensor, see a row being reused, and identify the parameter state at which a loss was calculated. These habits carry into larger models: dimensions, data boundaries, gradient paths, and evaluation conditions continue to require explicit definitions.

Your starting point

You can begin Chapter 01 if you can read Python functions, lists, dictionaries, loops, indexing, and slicing. Tensors, matrix multiplication, derivatives, and the chain rule are developed through small examples when they become necessary. If a topic is familiar, skim its derivation and use the example to check the notation and conventions used here.

Building from scratch means implementing the essential data processing, model components, and training flow. The early tokenizer exercises use Python's standard library. Later sections use PyTorch for tensor operations and automatic differentiation. We explain which work the library performs and which computational relationships your implementation must preserve.

Learning starts with small arithmetic fixtures and tiny models. As data and models grow, measured speed, memory use, evaluation results, and a training budget guide the next scale. The companion instructions specify the runtime and software versions.

An implementation that grows in stages

The first two chapters establish text representation. We distinguish Unicode, UTF-8, bytes, and token IDs, then implement BPE counting, merging, training, encoding, decoding, and persistence. Since model parameters depend on stable ID meanings, tokenizer rules and vocabulary become artifacts to preserve and reuse.

Chapter 03 connects those IDs to training. Embeddings, loss, gradients, output projection, generation, and evaluation first appear as small components, then form a baseline pipeline. Chapters 04 and 05 build a causal Transformer that can use earlier context, followed by modern components and reliable optimization, saving, and recovery.

The route through this book

Each stage builds on the preceding implementation.

Chapters	What we build
01–02	**Represent text** Bytes, IDs, BPE
03	**Learn the training flow** Predict, update, generate
04–05	**Build contextual models** Attention and reliable training
06–08	**Connect data and use** Pretrain, evaluate, adapt
09–10	**Measure and investigate** Systems and experiments

Figure 1: The learning route moves from text representation to baseline training, contextual models, data workflows, systems, and experiments.

Read the rows from top to bottom. Each chapter range names a stage that adds a capability or a way to verify the preceding implementation. Follow the numbered sections in the contents to work through that route.

Chapters 06 through 08 place the model within a fuller data and usage workflow: preparing data, splitting documents, training and freezing a tokenizer, organizing pretraining, defining fixed evaluation, and studying inference and instruction tuning. Preference optimization and policy objectives provide foundations for further experiments; a concrete task determines which methods to use.

The final two chapters focus on measurement and research. You will inspect where time and memory go, understand the effects of precision, gradient accumulation, and distributed training, and turn your own ideas into testable hypotheses with controlled comparisons and ablations. OneLong serves as the implementation and experimental project that develops along this route.

Work through a section completely

Each section follows a consistent rhythm: establish the problem, define the quantities in a formula, trace a complete small example, and express the calculation through a function interface. Rows, columns, arrows, and highlights in the figures use the same symbols and values as the text. You should be able to point to the source of every displayed result.

When implementing a section, follow this sequence:

1. Read the inputs, outputs, and assumptions. Separate fixed data from parameters to be learned.
2. Predict the example's intermediate results, especially shapes, indices, summation ranges, and return timing.
3. Use the numbered hints to write the core implementation, preserving the supplied initialization and check driver.
4. Run the checks, then change an input or boundary condition and compare the result with your explanation.
5. Explain the key relationship in your own words, or set the hints aside and reconstruct a small step.

The supplied checks examine behavior; your explanations and reconstructions help examine understanding. When a check fails, follow the example to locate the cause: an incorrect position, a confused dimension, or a value recorded at a different parameter state after an update. An error you can explain often becomes a useful clue when diagnosing a more complicated computation later.

Syntax and library interfaces can be looked up, and tools can help compare explanations. While practicing core logic, leave room to reason through it and write an attempt yourself. Check suggested changes against the formulas, examples, and observed execution.

From implementation to your own experiments

Once a model generates text, we need a way to assess it. Training loss, performance on data held out from training, and a few generated samples provide different information. We make data splits,

tokenizer versions, valid-target counting, and evaluation protocols explicit so that comparisons between runs have a defined basis.

Before changing a model, state what you expect to improve and design a comparison that can test that expectation. Retain the training budget, seeds, code version, and results, including attempts that did not help. Experiments show the conditions under which an idea works and the evidence still needed.

The intended result is a language-model implementation whose essential mechanisms you can explain, whose training you can check, and whose results you can examine independently. It provides a starting point for larger training runs and original ideas. Actual data and evaluation establish its capabilities and limits.

Chapter 01 begins with a short piece of text. Turning it into bytes, and then into IDs usable for training, gives the model its first computable input.

Each section names its numbered companion assignment. Appendix B, Companion exercises, explains how to use the supplied checks; the companion package README gives the setup and code revision. Work through a complete example before moving from the mathematics to the implementation.

Begin with 01.01: text, tokens, and training windows

Notation and conventions

The same letter can have a local meaning in different derivations. Each section defines its symbols before using them. The following conventions cover the model's most common tensors; a worked example may deliberately choose unequal sizes to expose an incorrect transpose.

Symbol	Meaning	Typical example
B	Number of sequences in a batch	2 independent sequences
T	Number of token positions in one input window	8 positions per sequence
V	Number of vocabulary candidates	259 entries in one teaching vocabulary
D	Width of a model representation	An 8-component vector per position
H	Number of attention heads when used as a count	4 heads
d	Matching width of a query and key in one head	D/H in the standard equal-width layout
d_v	Width of a value vector in one head	May differ from d in an attention fixture
K	Number of selected targets when defined as a loss denominator	Count of True mask entries
P	Parameter count or cached-prefix length as locally defined	Never infer its meaning from the letter alone

`[B,T,D]` is a shape, not a vector's values. `[[1,2],[3,4]]` is an explicit matrix with shape `[2,2]`. An embedding table `[V,D]` maps an ID tensor `[B,T]` to selected vectors `[B,T,D]`; it does not change its number of stored rows when the batch changes.

Python positions and IDs are zero-based. A token ID is a vocabulary index, and repeated IDs can occupy different sequence positions. Special IDs must be reserved against the actual frozen tokenizer. ID0 is not automatically padding, and IDs greater than255 are not automatically special: ordinary BPE merges can also use them.

For a token sequence `s`, the ordinary next-token convention pairs `x=s[:-1]` with `y=s[1:]`: the model sees each input position and predicts the following token. Chapter 03 constructs these pairs before the model call. Sections 08.01–08.02 use another interface for complete conversations: the model receives all of `ids`, and the loss pairs each position's prediction with the following ID and its target flag. Both interfaces express the same next-token task. The slicing belongs at the boundary specified by the function contract; repeating it would skip a token and change the target.

Logarithms are natural unless explicitly marked base2. Cross-entropy is then measured in nats per

selected target. Bits per byte additionally needs the matching original UTF-8 byte count; neither a tensor's memory size nor its number of elements supplies that denominator. EOS and padding can have zero source bytes while having different target-mask roles.

Approximate equality in numerical tests uses a stated tolerance. Exact arithmetic examples explain a relationship; they are not measurements of trained-model quality. A formula estimating FLOPs or state bytes is not a measurement of elapsed time or peak allocation.

01 Text becomes data

Before a model can learn from a sentence, the sentence must have a computational representation. That requirement sounds simple until the same visible character occupies several bytes, an unfinished sequence cannot yet decode, or a number is mistaken for the meaning of a word. This chapter fixes the distinctions we will rely on throughout the book.

We begin with UTF-8 bytes because every step can be inspected without an external vocabulary. The point is not to claim that a useful language model should always predict one byte at a time. It is to establish exactly what an ID represents and how the same sequence yields an input and a next-token target. Once that contract is clear, a more economical tokenizer can change the units without changing the learning problem.

01.01 Text, Tokens, and Next-Token Targets

Method sources

Unicode code points and UTF-8 bytes follow Unicode Consortium, 2024; R01 and Yergeau, 2003; R02. The character-to-integer exercise is a teaching bridge, not a complete language-model tokenizer.

A language model cannot read a Python string directly. Before it can learn from a sentence, we need a reversible path from text to integers, and a way to say which integer should come next. We will start with one byte per token: a small tokenizer whose behavior we can trace all the way back to the original text.

Work through the example before editing 01_01_text_to_tokens.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

1. Encode text into token IDs




Figure 2: Use the brackets to group the byte cells under their code points. The four middle cells belong to one code point; six cells still mean six byte tokens, not six characters.

Use the brackets to group the byte cells under their code points. The four middle cells belong to one code point; six cells still mean six byte tokens, not six characters.

Implement `ByteTokenizer.encode`:

- Encode text using UTF-8.
- Return a list of byte values, each an integer from 0 through 255.
- Preserve whitespace and case. Empty text produces an empty list.

Examples:

```
"hello" -> [104, 101, 108, 108, 111]
"A 🌍 B"  -> [65, 240, 159, 140, 141, 66]
```

The second string contains three Unicode code points but six UTF-8 bytes. Token count depends on the tokenizer. Here, every byte is one token and the vocabulary contains exactly 256 IDs. This tokenizer has no learned vocabulary or special tokens yet.

Hint: inspect `str.encode` and how iterating over a `bytes` object behaves. Then run:

```
python3 exercises/01_01_text_to_tokens.py --check encode
```

2. Decode token IDs back into text

Implement `ByteTokenizer.decode` using the reverse path: integer IDs to bytes, then strict UTF-8 decoding.

For text that can be encoded as UTF-8, the round-trip requirement is:

```
decode(encode(text)) == text
```

Use strict decoding in this exercise. Out-of-range byte values should raise `ValueError`; invalid or incomplete UTF-8 should raise `UnicodeDecodeError`. Do not discard undecodable bytes with `errors="ignore"`.

A complete encoded string can round-trip while an arbitrary token slice cannot: a slice may stop halfway through a multi-byte character. Later, generation will need to handle this distinction when displaying output.

Hint: inspect the `bytes` constructor and `bytes.decode`. Then run:

```
python3 exercises/01_01_text_to_tokens.py --check decode
```

3. Construct next-token training examples




Figure 3: Compare the two rows by column: each target comes from exactly one source position after its input. T=3 therefore needs four source IDs from the starting point.

Compare the two rows by column: each target comes from exactly one source position after its input. T=3 therefore needs four source IDs from the starting point.

Implement `make_example(token_ids, start, context_length)`:

- Return two new lists, `x` and `y`, each containing `context_length` tokens.
- `x` starts at `start`; `y` starts at `start + 1`.
- Require `start >= 0`, `context_length > 0`, and enough tokens for the input plus one following token. Raise `ValueError` otherwise.
- Leave the original list unchanged.

For `[10, 20, 30, 40, 50, 60]`, `start=1`, and `context_length=3`:

```
x = [20, 30, 40]
y = [30, 40, 50]
```

Five tokens in `"hello"` provide four supervised positions:

Input prefix	Next-token target
`h`	`e`
`he`	`l`
`hel`	`l`
`hell`	`o`

These prefixes describe what the model will be allowed to see at each position. We will enforce that visibility with causal masking when implementing attention; constructing shifted labels alone does not prevent future-token leakage.

Hint: use list slicing, but validate the available length first. Python silently truncates an oversized slice. Then run:

```
python3 exercises/01_01_text_to_tokens.py --check example
```

Finish the lesson

Run all acceptance checks from the repository root:

```
python3 exercises/01_01_text_to_tokens.py
```

The final line should read `Lesson 01.01 checks passed.` Passing these checks verifies this small exercise; it does not yet verify a trainable language model.

In your own words, explain:

1. Why does `"A 🌍 B"` produce six tokens here?
2. Why must the target window be shifted by one token?
3. At the second position of the `"hello"` example, which input tokens may causal attention see?

Share the output and your explanation for review before starting the next exercise. Save teaching notes in the paired English and Chinese chapters. Training experiments will use the experiment tracking format once we have a model to train.

Variables and implementation review

Name	Type	Meaning
`text`	`str`	Input to `ByteTokenizer.encode`; Python text, before UTF-8 encoding.
`token_ids`	`list[int]`	Input to `ByteTokenizer.decode` and `make_example`; in this lesson each ID is a byte value.
`start`	`int`	Zero-based start of the input window.
`context_length`	`int`	Number of positions in each input/target window.
`x`, `y`	`list[int]`	Returned input window and one-position-shifted target window.

For encoding, first obtain bytes with `.encode("utf-8")`; then expose their integer values with `list(...)` and return that list. For decoding, first construct `bytes(token_ids)`; then decode the complete bytes with UTF-8 and strict error handling, returning a string.

For `make_example`, check the allowed start and length before slicing. An `if` runs its indented block only when its condition is true; `raise ValueError(...)` reports an invalid request. Ensure at least `context_length + 1` tokens remain from `start`. Then take an input slice beginning at `start` and a target slice beginning at `start + 1`, each of the requested length. Slice ends are excluded. Return `(x, y)` after constructing both lists.

Questions from practice

Why is the byte vocabulary size 256, and the largest value 255?

A byte in this representation has eight bits. Each bit has two possible states, so there are $2^8 = 256$ distinct bit patterns. Zero-based values run from 0 to 255; `11111111` is 255. Thus 256 counts possible values, not bits, stored bytes, or the sum of the values. The choice of an eight-bit byte determines this limit; it is not an arbitrary homework constant.




Figure 4: Eight binary choices give 256 patterns. The place values add to 255 for the all-ones pattern.

Read the eight columns as place values: a bit contributes its column's value when it is one, and zero otherwise. The all-zero pattern would represent zero; the displayed all-one row represents 128 + 64 + 32 + 16 + 8 + 4 + 2 + 1 = 255. There are 256 distinct patterns including zero.

This limit belongs to one raw byte. A token ID is an integer vocabulary index. Byte-pair encoding (BPE), introduced in Chapter 02, adds IDs such as 256 and 257 without changing the raw-byte range. With k learned merges and no special tokens, our contiguous vocabulary has $256 + k$ entries and largest ID $255 + k$. Any later special tokens must be counted separately.

How do Unicode and UTF-8 relate?

Unicode defines characters and their code points. UTF-8 is a way to represent Unicode scalar values as byte sequences. A valid scalar value uses one to four UTF-8 bytes; surrogate code points are excluded. For example, `" 你"` has code point `U+4F60` and UTF-8 byte values `[228, 189, 160]`: three bytes, or 24 bits, not three bits.

A newly encountered character does not need a new byte value. If it has a valid Unicode scalar value, UTF-8 represents it by combining existing byte values. An arbitrary byte sequence, however, is not necessarily valid UTF-8. A visible character can also involve several code points, so visible-character count and byte count need not agree.

What are `b"a"`, byte IDs, and embedding vectors?

`"a"` is a Python `str`; `b"a"` is a `bytes` object containing the single value 97. `list(b"a")` produces `[97]`, and `bytes([97])` reconstructs that byte object. The leading `b` is Python syntax and is not an extra byte

in the contents. Non-ASCII text is converted with `.encode("utf-8")`.

In this first tokenizer, the byte value itself is the token ID. Later BPE IDs label byte sequences through a vocabulary. Embedding vectors are a separate model representation: the ID selects a row of floating-point values. Joining bytes does not create an embedding vector, and an embedding dimension is a count of components, not a numeric range from 0 to 256.

If three code points produce six tokens, must every shorter output fail to decode?

No. For `"A 🌍 B"`, the six byte IDs are `[65, 240, 159, 140, 141, 66]`. The first five already contain the complete `A` and the complete globe, so they decode to `"A 🌍"`. The first three stop inside the globe's four-byte encoding and cannot yet be strictly decoded. Completion of byte sequences determines validity, rather than whether the expected token count was reached.

Generated IDs can also map to invalid byte patterns; merely generating more IDs does not guarantee a repair. Strict decoding reports incomplete or invalid UTF-8. Later streaming display can buffer an incomplete suffix. Decoding success and predicting the intended text are separate properties.

Does training predict five tokens at once, or one next token?

Each supervised position predicts one next-token target conditioned on the preceding tokens. A length-five input window supplies five such positions; a causal model can compute their distributions in one training pass using known input tokens. This is not the same as generating five unknown future tokens in parallel.

Generation normally selects one next token, adds it to the sequence, and predicts again. `make_example` prepares shifted labels; the causal model and loss will be implemented later. A `PASS encode` line confirms that the supplied cases behaved as expected; it does not show that a language model has been trained or that every concept has been independently mastered.

Learn byte-level BPE: count adjacent token pairs, merge the most frequent pair, and assign a new token ID. The byte tokenizer from this lesson provides the starting vocabulary. Compression and reversibility will be the first checks.

References

- Python string encoding and byte decoding: API behavior for this exercise.
- minbpe: a compact reference for the next lesson. Try implementing your own first, then compare the designs.
- Python Unicode HOWTO: code points, encodings, and byte representations.

Looking back

The first training pairs are now explicit, but bytes can make common fragments unnecessarily long. The next chapter learns larger units while preserving a reversible route back to the original bytes.

02 Learn a vocabulary

A tokenizer is a learned data-processing rule that becomes fixed before the language model uses its IDs. Byte-pair encoding gives us a compact example of this distinction. During tokenizer training, frequent adjacent pairs may create new vocabulary entries. During encoding, the learned rules are applied in their learned order; an unfamiliar input does not authorize a new ID.

The functions in this chapter are deliberately separate. Counting tells us which pairs exist. Selection chooses a rule. Merging changes one sequence. Training repeats those operations, whereas encoding consults a frozen rule set. Decoding reconstructs bytes before asking UTF-8 to interpret them. Keeping these responsibilities distinct prevents a tokenizer from changing the meaning of an embedding row halfway through training.

02.01 BPE and Adjacent Pair Counts

Method sources

For the use of byte-pair encoding in neural text models, see Sennrich et al., 2016; R03. The byte-level vocabulary design is related to Radford et al., 2019; R25; this worksheet does not reproduce the GPT-2 pretokenizer.

The byte tokenizer can represent new text without inventing new byte values, but it often repeats the same short sequences. Could a frequently repeated sequence have its own token? BPE begins by answering a smaller question: which adjacent pairs actually occur, and how often?

Work through the example before editing 02_01_bpe_pair_counts.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

Why extend the byte tokenizer?

Our first tokenizer represents every byte separately. A repeated byte sequence can instead have its own token ID. This reduces the number of tokens needed for some texts and lets a fixed token context hold more text. The vocabulary grows, so the embedding table and output vocabulary also grow; compression is one tradeoff, not proof of a better language model.

Tokenizer training here means learning merge rules from frequency counts. It does not use gradient descent. The language model will learn its own parameters separately.

A single BPE merge

Start with `"ababab"`:




Figure 5: Read the ID sequence from left to right and compare the table's two rows. Starts 0, 2 and 4 have the ordered pair (97,98); starts 1 and 3 have (98,97). Sharing an endpoint does not remove a count.

Read the ID sequence from left to right and compare the table's two rows. Starts 0, 2 and 4 have the ordered pair (97,98); starts 1 and 3 have (98,97). Sharing an endpoint does not remove a count.

```
UTF-8 byte IDs: [97, 98, 97, 98, 97, 98]
```

Scan each adjacent position:

Start position	Pair	Byte text
0	`(97, 98)`	`ab`
1	`(98, 97)`	`ba`
2	`(97, 98)`	`ab`
3	`(98, 97)`	`ba`
4	`(97, 98)`	`ab`

The counts are:

```
{(97, 98): 3, (98, 97): 2}
```

Choose the most frequent pair, `(97, 98)`, and introduce token ID `256` for its byte sequence `b"ab"`. A left-to-right merge produces:

```
[97, 98, 97, 98, 97, 98] -> [256, 256, 256]
```

There are now 257 vocabulary entries: the original 256 byte tokens plus one new token. Each new token still gets one embedding vector. Its ID is a lookup index, not the concatenation of embedding vectors.

The raw UTF-8 encoding has not changed. A BPE vocabulary records what bytes each token represents:

```
97  -> b"a"
98  -> b"b"
256 -> b"ab"
```

To decode merged IDs later, look up their byte sequences, join those bytes, and then decode UTF-8. `bytes([256])` cannot perform this lookup. BPE tokens can still contain partial UTF-8 characters, so arbitrary token slices or generated sequences need the decoding care discussed in Lesson 01.01.

Your function

Implement:

```
def count_pairs(token_ids: list[int]) -> dict[tuple[int, int], int]:
    ...
```

The keys are ordered two-token tuples; the values are occurrence counts. At each valid index `i`, inspect the tokens at `i` and `i + 1` and increment that pair's count.

- Visit every adjacent position. A sequence of length n has $n - 1$ adjacent positions when $n \geq 1$.
- Preserve order: `(97, 98)` and `(98, 97)` are different pairs.
- Include overlaps: `[42, 42, 42]` contains two occurrences of `(42, 42)`.
- Return `{}` for empty or one-token input.
- Accept already merged IDs such as `256`; keep the source list unchanged.

Counting visits overlapping pairs. Replacing pairs later will consume matched tokens without overlap. For example, the two counted pairs in `[42, 42, 42]` cannot both be replaced in a single left-to-right pass. We will implement that distinction next.

Hint: use a dictionary with tuple keys and a loop over adjacent positions. You may inspect pairs with indexing or with two offset views of the list.

Check your implementation

Variables and numbered review

`token_ids` is `list[int]`. The returned `pair_counts` is `dict[tuple[int, int], int]`. The imple-

mentation uses `i` as a source index and `pair` as the current two-ID tuple.

1. Start an empty dictionary named `pair_counts`. `{}` creates a dictionary.
2. Visit valid adjacent starts with `range(len(token_ids) - 1)`. `range` excludes its endpoint; for six tokens it yields indices 0 through 4. With zero or one token this range is empty.
3. Inside the loop, form `pair` from `token_ids[i]` and `token_ids[i + 1]`. Parentheses with a comma create a tuple. After the first position in `"ababab"`, the key is `(97, 98)`.
4. Increment that key's count. `.get(pair, 0)` reads the previous count or zero if the key is absent. The first two positions produce `{(97, 98): 1, (98, 97): 1}`.
5. Return `pair_counts` after the loop, including `{}` when no adjacent pair exists.

Classroom clarification

This function counts pair occurrences; it does not choose the winner, allocate a token ID, or merge anything. A pair occurring once is still a real pair and receives count 1. Only empty input or one token produces no adjacent pair. Counting all positions includes overlap, while the next lesson's replacement must avoid reusing the same source token.

```
python3 exercises/02_01_bpe_pair_counts.py
```

The final line should be `Lesson 02.01 checks passed.`

Explain why `[97, 98, 97, 98]` contains both `(97, 98)` and `(98, 97)`. Share your implementation and check output for review.

Later BPE steps

1. Implement non-overlapping pair replacement.
2. Repeat counts and merges with deterministic tie-breaking; store the ordered merge rules and token-to-byte vocabulary.
3. Encode new text using the fixed learned merge ranking, rather than relearning merges for each input.
4. Decode via byte lookup and verify round trips, vocabulary serialization, special tokens, and boundary cases.
5. Define text segmentation and document boundaries, fit on training data, and compare compression and throughput before choosing a working vocabulary size.

Next exercise

Continue with Lesson 02.02: non-overlapping BPE merges after the pair-count checks and review.

Reference

minbpe's pair-counting and merge helpers are a reference for later review. The exercise checks specify the behavior; write your version before comparing implementations.

02.02 Non-Overlapping BPE Merges

Counting a pair does not yet tell us how to replace it. Two counted occurrences may share a token, and using that token twice would change the underlying text. We will walk from left to right, consuming each source token once and preserving its bytes.

Work through the example before editing 02_02_bpe_merge.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

Byte values and token IDs

One byte contains eight bits, so it has $2^8 = 256$ possible values, numbered `0` through `255`. This is a count of possible values, not a quantity of stored bytes.

Our initial tokenizer uses those byte values as its token IDs. BPE adds vocabulary entries: token ID `256` can represent the two bytes `b"ab"`. A token ID is an integer lookup index and is not restricted to a single byte. In binary, integer `256` is `100000000`, which requires nine bits in an unsigned representation; that does not change what its vocabulary entry represents. Actual token-array storage uses a chosen integer dtype, which we will consider when preparing data.

One merge pass

For pair `(97, 98)` and new ID `256`:

```
Source: [97, 98, 97, 98, 97, 98]
Result: [256, 256, 256]
```

The caller chooses the pair and its new ID. This helper performs the replacement; vocabulary construction is a separate step.

Why counting and merging handle overlap differently




Figure 6: Track which source positions have been consumed. The valid result keeps three original bytes; the rejected overlapping replacement would produce four.

Track which source positions have been consumed. The valid result keeps three original bytes; the rejected overlapping replacement would produce four.

For `"aaa"`, the source is `[97, 97, 97]`. Pair counting sees `(97, 97)` twice: at positions 0–1 and 1–2. Both occurrences share the middle token.

If new ID `256` represents `b"aa"`, left-to-right replacement consumes the first two tokens and leaves the third:

```
[97, 97, 97] -> [256, 97]
bytes: aaa  ->       aa + a
```

Replacing both overlapping occurrences would produce `[256, 256]`, representing `"aaaa"`, which changes the source text. For four `a` tokens, two non-overlapping replacements are possible and `[256, 256]` is correct.

Algorithm to implement

Build a new output list and track the current source position `i`:

1. If two source tokens remain and they match `pair`, append `new_id` and advance `i` by two.
2. Otherwise, append the current source token and advance `i` by one.
3. Continue until all source tokens are consumed, then return the new list.

Check that a next token exists before inspecting `i + 1`. Process the original sequence in this pass; unmatched tokens retain their order. Empty and one-token inputs also return new lists.

The result has one fewer token for each replacement. Its reconstructed bytes must remain the same once the vocabulary maps `new_id` to the concatenated byte contents of the matched tokens.

Check your implementation

Variables and control flow

`token_ids` is `list[int]`, `pair` is `tuple[int, int]`, and `new_id` is `int`. Return a new `list[int]`. The output list is named `new_res`, and `i` tracks the current source position.

Start `new_res` empty and `i` at zero. A `while` loop repeats its indented body while its condition is true; here, continue while `i < len(token_ids)`. An `if` chooses the matching branch; `else` handles everything else. Test `i + 1 < len(token_ids)` before reading the second ID. Python's `and` evaluates its right side only if the left side is true, so the boundary test protects the lookup.

For `"aaa"`, start with `new_res=[]` and `i=0`. A match appends 256 and advances `i` to 2. Only one source token remains, so the unmatched branch appends 97 and advances `i` to 3. The loop stops and returns `[256, 97]`. `i += 2` adds two to the index; it does not modify the source list. Keep the final return outside the loop and never reuse tokens consumed by a match.

```
python3 exercises/02_02_bpe_merge.py
```

The final line should read `Lesson 02.02 checks passed.` The checks include repeated and overlapping pairs, a match at the end, already merged IDs, and preservation of the source sequence.

Explain why counting two `(97, 97)` pairs in `[97, 97, 97]` leads to only one replacement. Share your implementation and output for review.

Next step

Continue with Lesson 02.03: the BPE training loop. Select a most frequent pair, assign the next vocabulary ID, store its bytes and merge rank, apply the merge, and recompute counts on the changed sequence. Tie-breaking and stopping behavior are explicit parts of that lesson; encoding unseen text with fixed rules follows afterward.

Reference

minbpe's helper functions provide a reference for review after implementing your version.

02.03 The BPE Training Loop

Method sources

The iterative subword-merge procedure follows the BPE approach of Sennrich et al., 2016; R03. Our byte starting symbols, tie-breaking rules and tiny corpus are explicit teaching choices; compare the byte-level variant in Radford et al., 2019; R25.

We now have both ingredients for learning BPE rules: count adjacent pairs and replace a chosen pair. A training loop connects them. Each round gives one repeated byte sequence a new ID, records what that ID means, and then examines the shorter sequence again.

Work through the example before editing 02_03_bpe_train.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

Inputs, state, and returned values

Name	Type	Meaning
`text`	`str`	Text supplied for learning merge rules.
`vocab_size`	`int`	Requested upper bound on vocabulary entries, at least 256.
`ids`	`list[int]`	Current token sequence for the training text.
`vocab`	`dict[int, bytes]`	Each token ID and its byte contents.
`merges`	`dict[tuple[int, int], int]`	Each learned pair and its new token ID.
`next_id`	`int`	Next ID to allocate, starting at 256.
`pair_counts`	Pair-to-count dictionary	Adjacent-pair counts for the current `ids`.
`max_account`	`int`	Local variable for the maximum current pair count.
`candidates`	List of two-ID tuples	Highest-count pairs before numeric tie-breaking.
`best_pair`	Two-ID tuple	Pair selected by the exercise's tie rule.
Returned value	Three-object tuple	`(ids, merges, vocab)` in that order.

Start with all 256 byte entries, including byte values absent from this particular text. Their IDs are `0` through `255`. The initializer is provided:

```
vocab = {idx: bytes([idx]) for idx in range(256)}
```

For example, `vocab[97]` is `b"a"` and `vocab[98]` is `b"b"`. A vocabulary entry stores bytes, not an embedding vector.

Trace two rounds

Use `text="ababab"` and `vocab_size=258`:




Figure 7: Read downward through the three sequence states. A new vocabulary entry appears each round, while joining its byte contents always recovers the same six bytes.

Read downward through the three sequence states. A new vocabulary entry appears each round, while joining its byte contents always recovers the same six bytes.

Stage	Current IDs	Vocabulary entries
Initial	`[97, 98, 97, 98, 97, 98]`	256
After round 1	`[256, 256, 256]`	257
After round 2	`[257, 256]`	258

In round 1, `(97, 98)` occurs three times and `(98, 97)` twice. Select `(97, 98)`, assign the next ID `256`, and record:

```
merges[(97, 98)] = 256
vocab[256] = b"ab"
```

After replacement, count again on `[256, 256, 256]`. Now `(256, 256)` occurs twice. The two occurrences overlap, so the replacement pass makes one replacement. Introduce ID `257` for `b"abab"` and obtain `[257, 256]`.

The reconstructed bytes are `b"abab" + b"ab"`, which preserves `"ababab"`. The vocabulary now has 258 entries, so stop. The maximum allocated ID is 257; the text uses two token positions at this stage. Vocabulary size, maximum ID, and sequence length are three different quantities.

Record the new token's meaning

Let the selected pair be `(a, b)`. Because each child ID already has a vocabulary entry, its new byte contents are:

```
vocab[a] + vocab[b]
```

For bytes, `+` concatenates byte sequences. Store that result under the new ID. Child tokens may already represent several bytes, so this works in later rounds too.

The next ID can be `len(vocab)` because the IDs start at zero and grow contiguously. Record the pair-to-ID rule in `merges`; the increasing allocated IDs also capture the learned merge ranking needed to encode new text later.

Loop behavior

Repeat while the actual vocabulary contains fewer than `vocab_size` entries:

1. Call `count_pairs` on the current `ids`.
2. Stop early if the count dictionary is empty.
3. Select a pair with the largest occurrence count, using the tie rule below.
4. Allocate a fresh ID and record both its byte contents and merge rule.
5. Call `merge_pair` and replace `ids` with its returned sequence.

Return `(ids, merges, vocab)` after the loop. A limit of 256 allows no new entries. An empty or one-token sequence has no adjacent pair, so it may stop below the requested limit. This exercise allows frequency-one pairs to be merged.

The implementation rejects limits below 256 and imports your previous helpers. Its `max_account` variable stores the maximum current pair count. This frequency-based choice is specific to training; the encoding selector in Lesson 02.04 compares learned rule IDs instead.

Deterministic tie rule

Equal-frequency choices need a specified policy for reproducibility. In this exercise choose the numerically smallest pair tuple among the highest-count pairs. Compare the first ID, then the second if necessary.

For `"bac"`, the pairs `(98, 97)` and `(97, 99)` each occur once. Choose `(97, 99)` because 97 is smaller than 98. Different tie policies can produce different vocabularies; this policy fixes the expected results for our exercise.

Check the implementation

```
python3 exercises/02_03_bpe_train.py
```

The final line should read `Lesson 02.03 checks passed.` The first demonstrated result is:

```
ababab -> [257, 256]; vocabulary entries: 258
```

The checks verify new counts after each merge, byte preservation, retained base entries, the vocabulary budget, tie-breaking, and early stopping.

Individual vocabulary entries may contain incomplete UTF-8 characters. Reconstruct a complete training string by joining all token byte contents before UTF-8 decoding. This preserves the decoding distinction from Lesson 01.01.

Share your implementation and output. Explain why the second round counts `(256, 256)` instead of continuing to count `(97, 98)`.

Classroom questions and Python details

What does `{idx: bytes([idx]) for idx in range(256)}` do?

This is a dictionary comprehension. `range(256)` supplies integers 0 through 255; `idx` is the current integer. The expression before the colon supplies the key, and `bytes([idx])` supplies a one-byte value. For `idx=97`, the entry is `97: b"a"`. For `idx=0`, it is `0: b"\x00"`. All 256 entries are created, including bytes absent from the training text. Values are bytes, not vectors.

`b"a" + b"b"` gives `b"ab"`. The displayed `b` prefixes mark Python bytes literals; they are not inserted into the contents. Concatenation also works with chunks that are not independently decodable as UTF-8; decode only the joined complete byte stream.

What does `if not pair_counts: break` test? Does a count of one stop training?

`pair_counts` is a dictionary. An empty dictionary is false in a condition, so `not pair_counts` is true only when this dictionary is empty. A dictionary such as `{(97, 99): 1}` is nonempty even though the count is one. `break` exits the nearest loop; it does not return the function's final values by itself. After leaving the loop, execution reaches the return.

Our trainer permits frequency-one merges. It stops when the vocabulary budget is reached or the current sequence has no adjacent pair. A requested size is an upper bound; small inputs can stop before reaching it.

How do frequency ties work, and what do I need to remember?

First retain the pairs with the largest count. Then choose the numerically smallest tuple among those candidates. Tuple comparison examines the first ID, then the second if the first IDs match. This is different from choosing whichever dictionary entry appears first.

For counts `{(98, 99): 4, (97, 99): 4}`, both pairs have the maximum count, but `(97, 99)` wins. `pair_counts.items()` supplies `(pair, count)` entries; a loop can collect only the maximum-count pairs before selection. The variable `max_account` stores that maximum despite its spelling. Preserve it when tracing the actual code.

Remember the state transitions rather than memorizing a whole program: count the current sequence, choose a pair, record a new ID and its bytes, replace, then count the changed sequence again. Practice a small trace and reconstruct one step without AI completion. The AI-assisted acceptance result does not close the independent reconstruction checkpoint.

Continue with Lesson 02.04: selecting a learned rule, then Lesson 02.05: encoding new text. Decoding and save/load follow encoding. Corpus preparation, segmentation boundaries, special tokens, and efficiency follow the verified basic implementation.

Reference

minbpe's basic tokenizer illustrates the count/merge/vocabulary loop. Our exercise specifies its own numeric tie rule and early-stopping behavior.

02.04 Select a Learned BPE Rule

A trained tokenizer must give the same rules to every new input. Encoding therefore asks a different question from training: among the learned rules that apply right now, which was learned first? This small selector makes that distinction explicit before we build the full encoder.

Work through the example before editing 02_04_bpe_select_rule.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

Match the explanation to the actual exercise

This lesson is in `exercises/02_04_bpe_select_rule.py`. Its exercise function is exactly:

```
select_merge_pair(pair_counts, merges)
```

`pair_counts` and `merges` are passed into this function by `check_selection()`. Each check uses its own example dictionaries. The examples represent separate rule sets; they do not all share the vocabulary learned from `"ababab"`.

Part of the file	Purpose
`select_merge_pair`	Assigned function: return an applicable pair, or `None`.
`check_selection`	Supplied checks: pass dictionaries to the exercise function and check its result.
The main guard	Run the supplied checks when the file is executed.

There is no `max_count` argument in this exercise. `train_bpe` in the previous exercise uses its `max_account` variable for frequency-based selection. Here the choice depends on `merges[pair]`. This helper returns a pair; the next lesson's `encode_bpe(text, merges)` returns the complete encoded sequence.

Inputs and returned value

Name	Type	Meaning
`pair_counts`	`dict[tuple[int, int], int]`	Current adjacent pairs and their occurrence counts; its keys determine which pairs are present.
`merges`	`dict[tuple[int, int], int]`	Fixed learned pairs and their replacement IDs; smaller learned IDs have earlier priority in our format.
`candidates`	List of two-integer tuples	Current pairs that also have a learned rule.
`best_pair`	Two-integer tuple	Candidate with the smallest learned replacement ID.
Returned value	`Optional[tuple[int, int]]`	One selected pair, or `None` when no learned rule applies.

Keep both dictionaries unchanged. Current counts determine presence, while learned IDs determine priority. `None` is a stopping signal for the caller, not a token ID.

Training and encoding have different jobs

Training discovers a vocabulary: count the current adjacent pairs, choose the highest-frequency pair using the specified tie policy, allocate an ID, and record a new rule.

Encoding applies the existing vocabulary to a new input. Its vocabulary and rules remain fixed. Start from the new text's UTF-8 byte IDs, apply eligible learned rules, and stop when no learned rule applies. New text does not create new vocabulary entries.

Operation	How the next pair is selected	Creates new entries?
Training	Highest frequency; numeric pair order breaks ties in our exercise.	Yes, within the requested budget.
Encoding	Earliest learned rule among pairs currently present.	No.

This remains tokenizer processing. Predicting the next token with a neural language model comes later.

Select by learned order

Our trainer allocates IDs 256, 257, and so on in learning order. For this implementation, the smallest new ID identifies the earliest learned rule. This is a property of our allocation scheme; other tokenizer formats can store rule ranks separately.

Encoding selects the earliest learned rule

A pair must be present and already learned.

Pair	Count	Rule ID	Action
(97,98)	1	256	select
(98,99)	10	257	wait
(97,99)	2	—	no rule

Rule order, rather than current frequency, decides the next merge.

Figure 8: In the first two rows, the less frequent pair wins because ID 256 records an earlier learned rule. The last row is the separate no-rule example: presence alone does not make a pair eligible.

In the first two rows, the less frequent pair wins because ID 256 records an earlier learned rule. The last row is the separate no-rule example: presence alone does not make a pair eligible.

Suppose the current input has these pair counts:

```
pair_counts = {(97, 98): 1, (98, 99): 10}
merges = {(97, 98): 256, (98, 99): 257}
```

Both pairs have learned rules. Select `(97, 98)` because its rule was learned earlier: 256 is smaller than 257. Current frequency does not set rule priority during encoding.

One actual acceptance case reverses the rule order:

```
pair_counts = {(97, 98): 3, (98, 99): 1}
merges = {(97, 98): 257, (98, 99): 256}
```

The expected result is `(98, 99)` because its learned ID is 256. Taking `min(candidates)` would choose the numerically smaller pair `(97, 98)` and fail this case. Compare the candidates' `merges[pair]` values instead. This case is named `"rule order overrides numeric child-pair order"` in `check_selection()`.

Consider only pairs that occur in the current sequence and have a learned rule. A rule absent from the current sequence cannot apply; a present pair absent from `merges` cannot apply either.

Complete small trace

Use the second rule-order example above. Both current pairs have a rule, so collecting eligible pairs gives `[(97, 98), (98, 99)]`. The list is nonempty. Compare their learned IDs: 257 for `(97, 98)` and 256 for `(98, 99)`. The selected pair is `(98, 99)`, and that tuple is the returned value. The caller will look up ID 256 and perform replacement.

If `pair_counts` is `{(97, 99): 2}` with the same `merges`, the candidate list is empty and the returned value is `None`. Encoding cannot invent a rule for that pair.

Numbered implementation review

Review the completed `select_merge_pair(pair_counts, merges)`:

1. Start `candidates` as an empty list. Visit each current pair using a `for` loop. Keep only pairs for which `pair in merges` is true, and append each eligible pair. In the worked example, the result is `[(97, 98), (98, 99)]`. An `if` runs its indented block only when its condition is true; dictionary membership checks keys.
2. Test `not candidates`. An empty list makes this condition true. Return `None` in that case, leaving the function before selection. A nonempty list proceeds to the next step.
3. Select `best_pair` by comparing `merges[pair]`, rather than pair counts or the numeric order of child pairs. `min(..., key=...)` compares the values supplied by its key function while returning the original pair. The `lambda x: merges[x]` is a small function mapping a candidate `x` to its learned ID. The example selects `(98, 99)`.
4. Return `best_pair` after selection. The selector returns one pair; the caller performs the merge.

Keep input dictionaries unchanged. Prefer explicit loops while learning. Syntax references are allowed; practice without AI completion. The file separates exercise code from the supplied `check_selection()` driver.

Run the checks

```
python3 exercises/02_04_bpe_select_rule.py
```

The expected final line is:

```
Lesson 02.04 checks passed.
```

Checks cover learned order, currently applicable rules, empty inputs, unknown pairs, and unchanged input dictionaries.

Classroom questions: candidates and selection

Why is the frequency-based candidate loop no longer the right one?

This function applies rules learned earlier. `pair_counts` tells us which pairs are present; `merges` tells us which of those pairs are legal and which rule came first. The selected output is a pair tuple, not a count or a replacement ID.

If a loop uses `if pair in merges: continue`, it skips exactly the learned pairs we need to consider. `continue` abandons the rest of that iteration and proceeds to the next loop item. Eligible candidates must belong to both dictionaries. In contrast, the trainer keeps highest-frequency candidates and may create a new rule; these are different decisions in different functions.

How do `.items()`, `item[0]`, and `item[1]` relate?

For an item `((97, 98), 3)` from `pair_counts.items()`, `item[0]` is `(97, 98)` and `item[1]` is 3. Unpacking it as `pair, count` gives the same two objects with clearer names. Comparing `item[1]` with a maximum count belongs to training, not learned-rule selection. Here a candidate's comparison value is `merges[pair]`.

Our IDs encode learning order only because the trainer assigns them consecutively. A `lambda` used as the `key` for `min` tells Python what value to compare for each candidate. The returned result is still the candidate pair itself.

Continue with Lesson 02.05: encode new text, connecting this selector with `count_pairs` and `merge_pair`.

02.05 Encode New Text with Frozen BPE Rules

Method sources

The learned-merge view of subword encoding is grounded in Sennrich et al., 2016; R03; the byte-level language-model context is Radford et al., 2019; R25. The exact merge ordering and interface here belong to this tokenizer exercise.

The tokenizer has learned its vocabulary; now we can give it text it has never seen. Encoding repeatedly applies eligible frozen rules and leaves other byte tokens intact. An unfamiliar pair is not a failure: the base byte vocabulary already gives us a way to keep it.

Work through the example before editing 02_05_bpe_encode.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

Training and encoding have different jobs

Training discovers a vocabulary: count the current adjacent pairs, choose the highest-frequency pair using the specified tie policy, allocate an ID, and record a new rule.

Encoding applies the existing vocabulary to a new input. Its vocabulary and rules remain fixed. Start from the new text's UTF-8 byte IDs, apply eligible learned rules, and stop when no learned rule applies. New text does not create new vocabulary entries.

Operation	How the next pair is selected	Creates new entries?
Training	Highest frequency; numeric pair order breaks ties in our exercise.	Yes, within the requested budget.
Encoding	Earliest learned rule among pairs currently present.	No.

This remains tokenizer processing. Predicting the next token with a neural language model comes later.

Trace one new input

Training on `"ababab"` with a vocabulary budget of 258 learned:




Figure 9: After each merge, read the newly formed sequence before choosing again. The final three IDs still contain pairs, but none has an applicable learned rule.

After each merge, read the newly formed sequence before choosing again. The final three IDs still contain pairs, but none has an applicable learned rule.

```
(97, 98)   -> 256   contents: b"ab"     first learned rule
(256, 256) -> 257   contents: b"abab"   second learned rule
```

Now encode `"ababac"` with those same rules:

```
Initial bytes: [97, 98, 97, 98, 97, 99]
After rule 1:  [256, 256, 97, 99]
After rule 2:  [257, 97, 99]
```

The final sequence has adjacent pairs, but neither has a learned rule. Stop. In particular, `(97, 99)` cannot receive a fresh ID during encoding. The base vocabulary already contains ID 99 for the byte in `"c"`.

The reconstructed bytes are `b"abab" + b"a" + b"c"`, preserving the complete input.

Connect the helpers

Implement the `encode_bpe` region in `exercises/02_05_bpe_encode.py`. The file supplies helper imports, byte conversion, checks, and a complete example. Numbered comments now sit beside the corresponding implementation steps. No package installation is needed.

Variables used in this exercise

Name	Type	Meaning
`text`	`str`	New text supplied by the caller.
`merges`	Pair-to-ID dictionary	Fixed learned rules supplied by the caller.
`ids`	List of integers	Current encoding state; replaced after each merge pass.
`pairs`	Pair-to-count dictionary	Adjacent pairs in the current `ids`, recomputed each round. The encoder passes this object to the selector's `pair_counts` parameter.
`pair`	Two-integer tuple or `None`	Result of the rule selector.
`merges[pair]`	Integer expression	Existing replacement ID passed directly to `merge_pair`.

The grading code also uses a byte vocabulary to check reconstruction. That vocabulary is not an argument needed by your encoder.

Numbered implementation steps

1. Start a repeating loop. `while True` runs until `break` leaves the loop.

2. Call `count_pairs` on the current `ids` and store its dictionary in `pairs`.
3. Call `select_merge_pair` with `pairs` and `merges`, storing its result in `pair`.
4. If `pair is None`, use `break`. This test belongs before dictionary lookup.
5. Look up `merges[pair]`, call `merge_pair` with the current sequence and chosen rule, and store the returned sequence back in `ids`.
6. After the loop, return the final `ids`.

For the worked input `"ababac"`, the state checkpoints are:

Checkpoint	`ids`
Provided starting state	`[97, 98, 97, 98, 97, 99]`
After the first replacement	`[256, 256, 97, 99]`
After the second replacement	`[257, 97, 99]`
No applicable rule; returned result	`[257, 97, 99]`

There are still three tokens at the end. Stopping depends on whether a learned rule applies, not on reaching a one-token sequence or an empty count dictionary. Assigning the returned merge result back to `ids` ensures the next round sees the updated sequence. Keeping the final return outside the loop allows multiple rounds.

Run and interpret the checks

```
python3 exercises/02_05_bpe_encode.py
```

Each named `PASS` line identifies a tested behavior. The final line is `Lesson 02.05 checks passed.` Checks cover empty inputs, multiple rounds, unlearned pairs, non-overlapping replacement, fixed rule priority, Unicode bytes, and unchanged rules.

The Lesson 02.04 selector remains available as a review reference. Both exercises use independent rule sets in some acceptance cases, so always inspect the `merges` dictionary supplied to that case.

Classroom question: can `"abac"` create an `ac` token?

Suppose the frozen rules contain only $(97, 98) \to 256$. New text `"abac"` starts as `[97, 98, 97, 99]`; applying the learned `ab` rule produces `[256, 97, 99]`. The current pairs are `(256, 97)` and `(97, 99)`, neither of which has a rule. Return those three IDs. The final `ac` stays as two byte tokens.

During BPE training, a present `ac` pair could be selected and assigned a new ID within the vocabulary budget. During encoding, the vocabulary is frozen, so no such allocation is allowed. Byte coverage lets the new text remain representable without a rule for every possible pair. Adjacent pairs can still exist at stopping time; absence of an applicable learned rule is the stopping condition.

The encoder also differs from neural generation: it receives the complete known text and determines its IDs. It is not predicting unknown next tokens.

Next lessons

Continue with Lesson 02.06: BPE decoding and its decoding exercise: look up each token's bytes, join them in sequence order, and decode the complete byte stream as UTF-8.

After decoding, Lesson 02.07 preserves the tokenizer through save/load. Lesson 03.01: embedding lookup then begins the model side of the pipeline. Segmentation, special-token handling, and tokenizer versioning remain separate topics before corpus preparation.

02.06 Decode BPE Tokens Back to Text

An ID is a label, so recovering text requires the vocabulary that gives the label meaning. We will look up each byte fragment, join the fragments in order, and decode the complete stream. That order matters whenever a token ends in the middle of a UTF-8 character.

Work through the example before editing 02_06_bpe_decode.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

Function and variables

```
decode_bpe(token_ids: list[int], vocab: dict[int, bytes]) -> str
```

Name	Type	Meaning
`token_ids`	`list[int]`	IDs supplied by the caller, in sequence order. These are vocabulary keys and may exceed 255.
`vocab`	`dict[int, bytes]`	The caller's learned mapping from each ID to its byte contents.
`token_id`	`int`	One ID visited inside your loop.
`chunks`	`list[bytes]`	Byte contents collected by your implementation, one item per input ID.
`raw_bytes`	`bytes`	All chunks joined without adding a separator.
Returned value	`str`	Text obtained by decoding the complete byte stream as UTF-8.

The trainer returns `(ids, merges, vocab)`. In the supplied checks, `_, merges, vocab = train_bpe("ababab", 258)` stores the third returned object in `vocab`. Here `_` is an ordinary variable name indicating that the first result is unused in this context. The decoder receives the vocabulary as its second argument. The checks already do this; you do not call the trainer inside your decoder.

Trace the whole example first

Training on `"ababab"` with budget 258 learned these relevant entries:

ID	Byte contents	How the entry was created
97	`b"a"`	Base byte vocabulary.
99	`b"c"`	Base byte vocabulary; it exists even though the training text has no `c`.
256	`b"ab"`	First merge, `(97, 98)`.
257	`b"abab"`	Second merge, `(256, 256)`.

Your encoder maps new text `"ababac"` to `[257, 97, 99]`. Decode it in this order:

1. Look up ID 257: `vocab[257]` is `b"abab"`. Now `chunks` is `[b"abab"]`.
2. Look up ID 97: append `b"a"`. Now `chunks` is `[b"abab", b"a"]`.
3. Look up ID 99: append `b"c"`. Now `chunks` is `[b"abab", b"a", b"c"]`.
4. Join the chunks with an empty byte separator: `raw_bytes` is `b"ababac"`.
5. Decode the complete bytes as UTF-8: the returned text is `"ababac"`.

ID 257 is a label for four bytes. It is not a raw byte whose numeric value is 257. The old byte-only operation `bytes(token_ids)` cannot handle this sequence, because raw byte values must be between 0 and 255. Vocabulary lookup recovers the bytes associated with each BPE ID.

Why decoding belongs after the loop

Join the bytes before UTF-8 decoding

Two vocabulary examples are kept separate.

IDs	Vocabulary lookup	Joined text
[257,97,99]	b"abab" + b"a" + b"c"	"ababac"
[228,256]	[228] + [189,160]	"你"

Second example: 228 | 189 160

Neither fragment is a complete UTF-8 character on its own.

ID 256 names different bytes in different vocabularies.

Figure 10: The first table row recovers an ASCII example. The second row uses a different vocabulary trained on “你”: neither byte fragment is text by itself, but their ordered concatenation is valid UTF-8.

The first table row recovers an ASCII example. The second row uses a different vocabulary trained on "你": neither byte fragment is text by itself, but their ordered concatenation is valid UTF-8.

UTF-8 represents `" 你"` with the three bytes `[228, 189, 160]`. With budget 257, our trainer first merges `(189, 160)`, so encoding returns `[228, 256]`:

```
vocab[228] = bytes([228])       first byte of the character
vocab[256] = bytes([189, 160])  the remaining two bytes
```

Neither chunk is valid UTF-8 text on its own. Joined in order, they form the complete three-byte character. This is why the loop collects bytes and a single decoding operation follows the loop. Decoding each token separately would reject a valid complete input.

An arbitrary generated sequence can end with an incomplete character or contain invalid bytes. Strict decoding then raises `UnicodeDecodeError`. Collecting all bytes does not make an invalid sequence valid. In a later generation lesson, we will distinguish incomplete display buffers from invalid output and deliberate stopping.

Review the implementation steps

Implement the region in `decode_bpe` inside `exercises/02_06_bpe_decode.py`:

1. Create an empty `chunks` list. Visit `token_ids` in order with `for token_id in token_ids`. Inside the loop, look up `vocab[token_id]` and append that entire bytes object to `chunks`.
2. After the loop, join `chunks` into `raw_bytes`. The bytes method `separator.join(parts)` combines byte chunks. Use an empty byte separator so the original text receives no extra spaces or punctuation.
3. Decode the complete `raw_bytes` with UTF-8 and `errors="strict"`, and return the resulting string. Keep this operation and the return outside the loop.

The numbered comments explain list creation, loop indentation, dictionary lookup, `append`, byte joining, and `.decode`, including expected intermediate values. The implementation follows these steps; the placeholder has been removed.

For empty input, the loop performs no iterations, the empty list joins to `b""`, and decoding returns `""`. No separate empty-input branch is required.

An ID absent from `vocab` naturally raises `KeyError` at lookup. Invalid or incomplete UTF-8 naturally raises `UnicodeDecodeError` during strict decoding. Leave these errors visible; the supplied checks require them. Keep both input objects unchanged.

Run the checks

From the repository root:

```
python3 exercises/02_06_bpe_decode.py
```

Named `PASS` lines cover empty inputs, base and merged IDs, ordering and repetition, Unicode across

token boundaries, encoder/decoder round trips, input preservation, and the required errors. The final line is:

```
Lesson 02.06 checks passed.
```

If the Unicode boundary case fails, inspect whether you decode inside the loop. If an ID above 255 fails, inspect whether you tried to convert IDs directly to raw bytes. If output contains extra characters, inspect the join separator.

Classroom questions: byte joining and failures

Why can bytes be joined even when their display looks strange?

The `bytes` representation is a Python display of integer byte values. `b"\xe4"` and `b"\xbd\xa0"` can be concatenated even though neither can be independently decoded as UTF-8. In the decoder, `b"".join(chunks)` uses an empty bytes separator to assemble their values in order, and the joined bytes decode to `" 你"`.

`append` stores a complete bytes object as one item in `chunks`. It does not decode it or turn it into a vector. `.join` combines the collected objects after the loop; an empty collection produces `b""`, which decodes to the empty string.

Does a failed prediction always mean decoding fails?

An incorrect next-token prediction may still form valid UTF-8 text, so prediction correctness and decoding validity are different. A sequence that stops inside a multi-byte character is incomplete; a sequence with an illegal byte pattern is invalid. Our strict decoder raises `UnicodeDecodeError` for either case, regardless of how many token positions were generated. An unknown vocabulary ID instead raises `KeyError` before byte decoding.

The decoder must use the vocabulary belonging to the encoder or model. The same integer in another learned vocabulary may represent different bytes. Token IDs alone do not carry a universal text meaning.

What follows

Continue with Lesson 02.07 and exercises/02_07_bpe_save_load.py. Stage A prepares JSON-compatible records; stage B restores the exact vocabulary and rules. Then continue to the prepared embedding lookup lesson, which maps IDs to learned numeric vectors rather than byte contents.

02.07 Save and Reload a Tokenizer

A tokenizer should survive the end of a Python process. Saving it means preserving more than a vocabulary size: every ID must retain its byte contents and every merge must retain its priority. We will translate those Python objects into JSON records and restore them without relearning anything.

Work through the example before editing 02_07_bpe_save_load.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

JSON and the representation problem

Preserve IDs, byte contents and rule order

One record from a complete tokenizer file

Object	Python	JSON record
merges	(97,98) → 256	[97,98,256]
vocab	256 → b"ab"	[256,[97,98]]

Reload: tuple key + bytes value

Same vocabulary and rules reproduce the same encoding.

Figure 11: Compare the Python and JSON columns, then the reload statement below. Serialization changes the representation; reloading must restore the child IDs, replacement ID and byte values unchanged.

Compare the Python and JSON columns, then the reload statement below. Serialization changes the representation; reloading must restore the child IDs, replacement ID and byte values unchanged.

JSON is a text format for structured data. It can store objects, arrays, strings, numbers, booleans, and null. Python dictionaries and lists map to JSON objects and arrays. A rule dictionary keyed by tuples cannot be dumped directly; bytes values also need another representation.

Our portable format stores record lists:

In-memory data	Saved record	Meaning
`merges[(97, 98)] = 256`	`[97, 98, 256]`	Left ID, right ID, original learned replacement ID.
`vocab[256] = b"ab"`	`[256, [97, 98]]`	Original token ID and the exact integer byte values.

The complete payload also includes `"format": "onelong-byte-bpe"` and `"version": 1`. These identify this file schema, not a particular learned vocabulary. Versioning the learned tokenizer itself requires retaining the exact saved artifact and its checksum when experiments begin.

Keep all base vocabulary entries, including bytes absent from the training text. Preserve every merged entry and the original IDs. Store byte values without decoding individual tokens as UTF-8: a token can contain only part of a character, as the previous lesson demonstrated.

Stage A inputs and output

```
pack_tokenizer(merges: dict[tuple[int, int], int], vocab: dict[int, bytes]) -> dict
```

Name	Type	Meaning
`merges`	`dict[tuple[int, int], int]`	Learned rules supplied by the caller, from `train_bpe`.
`vocab`	`dict[int, bytes]`	Matching vocabulary supplied by the caller.
`payload`	`dict`	Provided outer structure; fill its `"merges"` and `"vocab"` lists.
`item`	`tuple[tuple[int, int], int]`	One key/value pair from `merges.items()`, such as `((97, 98), 256)`.
`out_merges`	`list[list[int]]`	Collected three-integer rule records.
`out_vocab`	`list`	Collected records containing each ID and its byte-value list.
`token_id`	`int`	One vocabulary key, visited inside your second loop.
`token_bytes`	`bytes`	That token's original contents.
`list(token_bytes)`	`list[int]` expression	Integer values obtained from those bytes, used directly in the record.
Returned value	`dict`	Complete JSON-compatible `payload`; the file helper writes it.

Assume valid matching dictionaries from our trainer. Leave both input dictionaries unchanged. There is no file path argument in this exercise function; file writing is supplied separately.

Trace the completed stage A

Train on `"ababab"` with budget 258. Start with the provided payload containing metadata and two empty lists.

1. The first rule $(97, 98) \rightarrow 256$ becomes `[97, 98, 256]`. After appending it, `out_merges` is `[[97, 98, 256]]`.

2. The second rule $(256, 256) \rightarrow 257$ becomes `[256, 256, 257]`. The list is now `[[97, 98, 256], [256, 256, 257]]`.
3. Each base vocabulary entry becomes a record: ID 0 becomes `[0, [0]]`, ID 1 becomes `[1, [1]]`, and so on through ID 255.
4. ID 256 contains `b"ab"`. `list(token_bytes)` produces `[97, 98]`; its complete record is `[256, [97, 98]]`.
5. ID 257 contains `b"abab"`; its complete record is `[257, [97, 98, 97, 98]]`.
6. Assign `out_merges` and `out_vocab` to the corresponding payload fields, then return `payload`. It has two merge records and 258 vocabulary records.

`list(b"ab")` exposes the byte values. It does not decode text and does not modify the original bytes. This is reversible: `bytes([97, 98])` restores `b"ab"`.

Review stage A's implementation

Collect the record lists before assigning them to the provided payload:

1. Visit `merges.items()` with the name `item`. `item[0]` is the child pair and `item[1]` is its learned replacement ID. `item[0][0]` and `item[0][1]` supply the two child IDs. Append the three-integer record to `out_merges`.
2. Visit `vocab.items()` with names `token_id` and `token_bytes`. Convert the contents to integer byte values, build a two-item record containing the ID and that nested list, and append it to `out_vocab`.
3. After both loops, assign the collected lists to `payload["merges"]` and `payload["vocab"]`, then return `payload`.

The file's comments give the relevant loop, indexing, `append`, conversion, and indentation hints. With zero merges, the first list stays empty; the vocabulary loop still saves the 256 base entries.

Run:

```
python3 exercises/02_07_bpe_save_load.py --check pack
```

Stage A checks cover: exact IDs and bytes, all entries, partial UTF-8 contents, unchanged inputs, JSON compatibility, and file writing. The final line is `Lesson 02.07 stage A checks passed.` These checks exercise packing independently of restoration.

Stage B: inputs and returned value

`unpack_tokenizer(payload)` creates new `merges` and `vocab` dictionaries from the parsed JSON data. A merge record supplies the original tuple key and replacement ID. A vocabulary record supplies its original ID and byte values, which `bytes(...)` restores. Return `(merges, vocab)` in that order.

Name	Type	Meaning
`payload`	`dict`	Saved-format data passed by the caller; leave it unchanged.
`payload["merges"]`	`list[list[int]]`	Rule records, each containing three integers.
`item`	`list`	One saved record from the list currently being visited.
`a`, `b`, `c`	`int`	Local variable names for the left ID, right ID, and original replacement ID.
`payload["vocab"]`	`list`	Vocabulary records, each containing an ID and byte-value list.
`token_id`	`int`	Saved vocabulary ID.
`byte_list`	`list[int]`	Local variable name for the saved integer byte values.
`merges`	`dict[tuple[int, int], int]`	Newly reconstructed rules.
`vocab`	`dict[int, bytes]`	Newly reconstructed byte vocabulary.
Returned value	`tuple`	`(merges, vocab)` for the caller to unpack.

The provided file reader handles JSON parsing and format/version checks. Your exercise function receives the resulting dictionary, not a path or JSON text string. Assume a valid matching payload.

Trace the completed stage B

Start with empty `merges` and `vocab` dictionaries. Use the payload from the stage A worked example:

1. Read rule record `[97, 98, 256]`. Its left, right, and replacement IDs are 97, 98, and 256. The restored rule is `merges[(97, 98)] = 256`.
2. Read `[256, 256, 257]`. The rules now contain both `{(97, 98): 256, (256, 256): 257}`.
3. Restore each base entry: `[0, [0]]` supplies ID 0 and its original byte, continuing through ID 255.
4. Read vocabulary record `[256, [97, 98]]`. `bytes([97, 98])` restores `b"ab"`; store it under key 256.
5. Read `[257, [97, 98, 97, 98]]`. The bytes restore to `b"abab"`; store them under key 257.
6. Return the two dictionaries. There are two rules and 258 vocabulary entries. Encoding `"ababac"` returns `[257, 97, 99]`, and decoding returns the original text.

Review stage B's implementation

Review the stage B learner region in `unpack_tokenizer`:

1. Create empty dictionaries named `merges` and `vocab`. `{}` creates a dictionary.

2. Loop over `payload["merges"]` directly; it is a list, so no `.items()` is needed. The implementation names each record `item` and unpacks it into `a`, `b`, and `c`. These represent the left ID, right ID, and saved replacement ID. Use the tuple `(a, b)` as the key and `c` as its value. Keep this assignment inside the first loop.
3. Loop over `payload["vocab"]`. Unpack each two-item `item` into `token_id` and `byte_list`. Convert the byte values with `bytes(byte_list)` and associate those bytes with the original `token_id`. Keep this assignment inside the second loop. Do not decode partial token contents into text.
4. After both loops, return the two dictionaries in the order `(merges, vocab)`. A comma-separated return produces a tuple. The stage B placeholder has been removed.

Keep all saved IDs unchanged. A list cannot serve as a dictionary key, so reconstruct each child pair as a tuple. Byte conversion changes the representation back to `bytes`; it does not reinterpret the ID or allocate a new one.

Run stage B checks first:

```
python3 exercises/02_07_bpe_save_load.py --check unpack
```

The final line is `Lesson 02.07 stage B checks passed.` Checks cover exact dictionary reconstruction, rule priority even when record order changes, zero merges, partial UTF-8 contents, unchanged payloads, and file reading.

Then run the complete save/load checks:

```
python3 exercises/02_07_bpe_save_load.py --check all
```

The supplied writer converts the packed data to JSON text; the supplied reader parses JSON text back into data, checks the format/version, and calls the unpacker. The complete flow is:

```
merges + vocab -> pack_tokenizer -> JSON file
JSON file -> unpack_tokenizer -> restored merges + restored vocab
```

Classroom questions: preserving meaning

Why save all 256 base entries, including unseen bytes?

Encoding new text may need bytes absent from the training example. The full base vocabulary preserves byte coverage. Saving only the entries used by the training string would lose that coverage. Merged entries and their original IDs must also survive reload.

Is saving the schema version enough to identify the tokenizer?

No. `version=1` describes how the file is structured. Many different learned vocabularies can use that schema. An experiment must retain the exact tokenizer artifact and its checksum, alongside its code and data versions. This exercise saves tokenizer rules and bytes; model parameters need a separate checkpoint later.

Why use lists of records and restore tuples and bytes?

JSON object keys cannot directly represent our tuple keys, and JSON has no bytes type. A merge record `[97, 98, 256]` preserves the two child IDs and learned ID. A vocabulary record `[256, [97, 98]]` preserves the ID and byte values. Restoration rebuilds `(97, 98)` as a tuple key and `[97, 98]` as bytes. It does not decode text, renumber IDs, or train again. List records can appear in a different order while the saved IDs still determine learned priority.

Looking back

We can now preserve text as stable IDs. The next question is how a model learns anything from those integers. Chapter03 gives them trainable vectors and follows the resulting gradients.

03 Make a model learn

The vocabulary defines the candidates, but it does not say which candidate should follow a prefix. We now introduce parameters: numerical values that can change in response to examples. An embedding lookup selects a row; an output projection scores candidates; a loss measures the probability assigned to the observed answer.

This is the longest chapter because it follows one training calculation through several changes of scale. We first differentiate a scalar, then a tensor, then a trainable lookup table. We connect logits, softmax and cross-entropy before adding prediction, sampling and batches. Each version retains the same questions: which value is fixed, which value is learned, where is the next-token target, and which parameter state produced the reported loss?

The resulting baseline is intentionally limited. Its modest architecture makes mistakes easier to diagnose and gives attention a specific problem to solve in the next chapter.

03.01 Token IDs to Embedding Vectors

Method sources

Learned word representations in a probabilistic language model are developed in Bengio et al., 2003; R24. This lookup exercise isolates row selection; it does not reproduce that paper's complete architecture or training experiment.

The tokenizer tells us which token an integer names, but a model needs numbers it can learn with. An embedding table supplies a floating-point vector for each ID. We will first make lookup concrete with ordinary Python lists, keeping the vocabulary table separate from the sequence of rows selected from it.

Work through the example before editing 03_01_embedding_lookup.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

Follow one complete input




Figure 12: The arrows select rows from the same table in input order. Positions zero and two both use ID 97, so their four-component output rows agree.

The arrows select rows from the same table in input order. Positions zero and two both use ID 97, so their four-component output rows agree.

The byte tokenizer encodes `"aba"` as:

```
text:       "aba"
token IDs:  [97, 98, 97]
```

An embedding table contains one floating-point row per vocabulary entry. Choose vocabulary size $V = 256$ and embedding dimension $D = 4$. The table E has shape `[256, 4]`.

For a lookup demonstration, give two of its rows these values:

Token ID	Embedding row
97	`[0.2, -0.1, 0.4, 0.3]`
98	`[-0.3, 0.5, 0.1, -0.2]`

These numbers are supplied demonstration values. In the eventual model, embedding parameters start from an initialization and are updated through the training loss.

Lookup follows the token sequence in order:

```
97 -> E[97] -> [ 0.2, -0.1, 0.4,  0.3]
98 -> E[98] -> [-0.3,  0.5, 0.1, -0.2]
97 -> E[97] -> [ 0.2, -0.1, 0.4,  0.3]
```

The resulting sequence has three rows and four columns:

```
[
    [ 0.2, -0.1, 0.4,  0.3],
    [-0.3,  0.5, 0.1, -0.2],
    [ 0.2, -0.1, 0.4,  0.3],
]
```

Repeated token IDs retrieve the same row from the same table at this stage. Later model layers use position and context to produce contextual representations.

Three quantities and two shapes

Symbol	Meaning	Value in this example
V	Number of vocabulary entries; number of table rows.	256
D	Number of floating-point components in each embedding.	4
T	Number of input token positions.	3

The embedding table has shape `[V, D]`. A sequence lookup has shape `[T, D]`. The table contains VD parameters in a trainable implementation; input length does not change the table size.

With $T = 6$ and $D = 8$, the lookup result has shape `[6, 8]` and contains 48 scalar values. With a batch of B equal-length sequences, the corresponding output shape is `[B, T, D]`; batching will be implemented later.




Figure 13: A separate D=8 example distinguishes shape labels from vector contents. Two input positions select two complete rows; the full table still has 256 rows.

This second example uses $D = 8$, rather than the exercise's $D = 4$, to make the distinction explicit. In a shape label, `[2, 8]` means two rows of eight components, or 16 scalar entries. Inside a value row, `[0, 0]` means two actual zero-valued components. Changing the input from three positions to two changes the output's first dimension; it does not resize the vocabulary table.

What each representation means

Token IDs select rows. Their numeric ordering does not impose a semantic ordering or distance on the vectors. Embedding components are floating-point parameters and are not restricted to byte values `0` through `255`.

The tokenizer's vocabulary maps an ID to byte contents. The model's embedding table maps that ID to a learnable vector. For a BPE token representing `b"ab"`, its embedding is its own table row; byte concatenation does not determine that vector.

Tokenizer vocabulary size and embedding-table row count must agree. A vocabulary of 258 entries permits IDs `0` through `257` and requires 258 embedding rows. The byte-tokenizer example above uses only the original 256 entries.

Exercise: retrieve rows in sequence order

Review the completed function:

```
lookup_embeddings(token_ids, embedding_table)
```

Return a list of rows, one for each input token position. Keep input order and repeated IDs. An empty input returns an empty list. Assume valid nonnegative IDs and a rectangular table; input validation and tensor operations are outside this small exercise. Keep the input sequence and table unchanged.

The relevant Python operation is `embedding_table[token_id]`, which retrieves the row at that index. A result list can be built using the loop and `append` operations already encountered.

The inputs are `token_ids: list[int]` and `embedding_table: list[list[float]]`. The output is `list[list[float]]`. The supplied checks construct the table; your function only retrieves rows. Use `vectors` for the output list and `token_id` for the current ID, matching the numbered hints in the actual file.

Name	Type	Meaning
`token_ids`	`list[int]`	Ordered input IDs supplied by the caller.
`embedding_table`	`list[list[float]]`	Supplied table with one row per vocabulary entry and D components per row.
`vectors`	`list[list[float]]`	Output rows collected by the learner.
`token_id`	`int`	Current ID visited in the input loop.
Returned value	`list[list[float]]`	One whole row per token position, including repeated IDs.

The numbered implementation review is:

1. Create an empty `vectors` list before the loop. `[]` creates a list; this is the starting result with zero rows.
2. Visit `token_ids` in its existing order, including repeated IDs. `for token_id in token_ids:` assigns each ID to `token_id` in turn. Keep its body indented; a set would remove repeats.
3. Inside the loop, retrieve `embedding_table[token_id]` and append that whole vector as one item in `vectors`. Bracket indexing selects a row; `.append(value)` adds one element. After IDs 97 and 98, the result has two rows of four values. Append the whole row, rather than extending the result with its individual components.
4. After the loop, return `vectors`. Align the return with the loop header, outside the body, so all positions are processed. Empty input naturally returns the empty list. Keep both input objects unchanged; this exercise permits reusing or copying row lists because it only reads their values.

Run the completed exercise for review:

```
python3 exercises/03_01_embedding_lookup.py
```

The expected final success line is `Lesson 03.01 checks passed.`

Classroom questions: IDs, dimensions, and repeated rows

Does a dimension of 8 mean values range from 0 to 256?

No. $D = 8$ means eight numeric components per vector. Their values can be negative or positive floating-point numbers and are not limited to the raw-byte range. For $T = 6$ token positions, the output shape is `[6, 8]` with 48 scalar values. Shape counts rows and columns; it does not specify their numeric limits.

Where do the numbers in `embedding_table[97]` come from?

The table supplied by our checks contains hand-chosen demonstration numbers. ID 97 simply selects row 97; it does not compute those values from the integer 97. In a trainable model, a parameter table is initialized and updated through the training loss. This exercise performs lookup only, without training or automatic differentiation.

Why do the first and third rows match, and is a BPE embedding a concatenation?

Both positions contain ID 97 and use the same table, so both retrieve the same row. Preserve both occurrences in the output. Later positional and attention operations can distinguish the positions using their contexts.

A merged BPE ID has its own embedding row with the same dimension D. Its tokenizer byte contents are a concatenation, but its model vector is not defined by concatenating the children's vectors. Growing the vocabulary grows the row count V; it does not automatically change D.

Explanation checkpoint and next lesson

Follow-up clarification: a shape, a table, and repeated IDs

`[3, 8]` describes the output shape: three token positions, each represented by eight numbers. A shape describes dimensions; it is not itself the tensor containing those numbers. The current exercise returns a nested Python list. A later tensor implementation can represent the same rectangular values as a rank-two tensor.

For $V = 258$, $D = 8$, and `token_ids=[256, 97, 256]`, distinguish the two objects:

Object	Rows	Components per row	Shape
Full `embedding_table`	258 vocabulary entries	8	`[258, 8]`
Returned `vectors`	3 input positions	8	`[3, 8]`

The first and third output rows match because the first and third IDs are both 256. Their lookups are:

```
position 0: ID 256 -> embedding_table[256]
position 1: ID  97 -> embedding_table[97]
position 2: ID 256 -> embedding_table[256]
```

Both repeated positions read the same row of the same fixed table. The complete text, surrounding IDs, and position do not change this lookup row. Later position and context processing can produce different representations. Different IDs select different rows, but those rows can happen to contain equal values; different IDs do not guarantee different numeric vectors.

For another short trace, change the input to `[256, 97]` while keeping the table fixed. What is the returned shape, and does the full table change size? This checks whether input length and vocabulary size are being distinguished.

In this example, the output has shape `[2, 8]`, while the lookup table stays the same size. This demonstrates the distinction between input length and vocabulary size in this example. Write a shape with a comma, `[2, 8]`; the product 2×8 counts 16 scalar values.

Explain what V, D, and T count. Trace the three output rows for `"aba"`, and explain why the first and third are equal at the lookup stage. Then reconstruct the lookup loop without AI completion.

For an explanation checkpoint, use $V = 258$, $D = 8$, and `token_ids=[256, 97, 256]`. State the shape of the full table and the returned sequence, then explain why the first and third lookup rows match.

The submitted loop starts an empty `vectors`, visits each `token_id`, and appends `embedding_table[token_id]` as a whole row. Its return is outside the loop, so every position is processed and an empty input returns the empty result. This is the correct lookup behavior. The table is still supplied data; this function does not update embedding parameters.

Next, read Lesson 03.02: parameters, loss, and gradients, which develops a scalar loss and assigns one gradient-descent step before moving to a training loop. Then represent these operations with trainable tensors, produce vocabulary logits in a minimal next-token model, and connect predictions to shifted targets and cross-entropy. Attention and the Transformer follow after the minimal training path is understood.

03.02 Parameters, Loss, and Gradients

An embedding table becomes useful when its numbers can change in response to mistakes. Before updating a whole table, let us train just one number. Squared error gives us a loss we can draw, and its slope explains both the direction and the limits of a gradient-descent step.

Work through the example before editing 03_02_scalar_gradient_step.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

What will change during training?

The numbers in the embedding table are model parameters: adjustable floating-point values. Its shape is fixed by vocabulary size and embedding dimension. An input selects rows; training can update their values through the model's prediction and loss. Changing input length changes the number of selected rows, not the table size.

In a language model, the broader path is:

```
token IDs -> embedding rows -> model computation -> next-token prediction
                                                 -> loss against known targets
loss -> gradients of parameters -> parameter update
```

The tokenizer supplies IDs. Training adjusts model parameters. Later lessons will implement the forward computation, the next-token objective, automatic differentiation, and parameter updates.

A small task with one adjustable number

For this example only, let the prediction be the parameter itself, prediction $= w$. Set the desired target to `1.0`. Use squared error to measure the discrepancy:

```
L(w) = (w - target)^2
```

This is a teaching example, not the language model's next-token objective. The scalar target here is deliberately chosen. Real language-model embedding values receive gradients through the model and a prediction loss, rather than being given desired coordinates manually.

Symbol	Type	Meaning	Example value
`w`	Floating-point scalar	Adjustable parameter and prediction in this toy task.	`0.2`
`target`	Floating-point scalar	Fixed desired prediction.	`1.0`
`error`	Floating-point scalar	Prediction minus the target: `w - target`.	`-0.8` initially
L	Nonnegative scalar	Squared-error loss; lower means closer to the target here.	`0.64` initially
g	Floating-point scalar	Gradient: derivative of the loss with respect to `w`.	`-1.6` initially
`learning_rate`	Positive scalar	Step size used for the update.	`0.1`
`w_new`	Floating-point scalar	Parameter after one update.	`0.36`

What does the gradient tell us?

The gradient describes how the loss changes locally when the parameter increases a little. With one scalar, it is a derivative. For this squared-error example:

```
g = dL/dw = 2 * (w - target)
```

If g is positive, a small increase in `w` increases the loss locally, so a descent update moves `w` downward. If g is negative, a small increase in `w` decreases the loss locally, so the update moves `w` upward. In this example, zero gradient occurs when the prediction equals the target.

The elementary gradient-descent update is:

```
w_new = w - learning_rate * g
```

The learning rate controls the step size. A step that is too large can increase the loss; decreasing loss after every update is not a universal guarantee.

Why is the gradient $2(w - \text{target})$?

A derivative measures the local rate of change. Increase `w` by a small amount h, keep `target` fixed, and compare the change in loss with the change in the parameter:

```
change in loss / change in w = (L(w + h) - L(w)) / h
```

Here, h is a nonzero scalar perturbation used to examine the loss function. It is not the learning rate or a training update. For example, with `w=0.2`, `target=1.0`, and `h=0.01`:

1. The original loss is $(0.2 - 1.0)^2 = 0.64$.
2. The perturbed parameter is `0.21`, with loss $(0.21 - 1.0)^2 = 0.6241$.
3. The loss change is $0.6241 - 0.64 = -0.0159$.
4. The ratio is $-0.0159/0.01 = -1.59$, close to the gradient `-1.6`.

The exact expression follows by expanding the square. Write $a = w -$ target temporarily:

```
L(w + h) - L(w) = (a + h)^2 - a^2
                = 2 * a * h + h^2
(L(w + h) - L(w)) / h = 2 * a + h
```

As h approaches zero, the ratio approaches $2a = 2(w - \text{target})$. That limit is the derivative $\frac{dL}{dw}$, which is the scalar gradient in this task. The factor `2` comes from expanding the squared error. A different loss or prediction formula generally has a different derivative.

For a sufficiently small parameter change, the gradient gives a local estimate:

```
change in loss approximately equals g * change in w
```

For this squared loss, the exact change also includes $(\Delta w)^2$. The approximation becomes more accurate as the change becomes smaller.

Complete worked update

Use `w=0.2`, `target=1.0`, and `learning_rate=0.1`.




Figure 14: The dashed tangent has negative slope at w=0.2. Subtracting that negative gradient moves right to w=0.36; the new point lies lower on the actual loss curve.

The dashed tangent has negative slope at $w = 0.2$. Subtracting that negative gradient moves right to $w = 0.36$; the new point lies lower on the actual loss curve.

1. **Predict:** the toy task returns `0.2` because its prediction is `w` itself.
2. **Compute the loss:** $(0.2 - 1.0)^2 = (-0.8)^2 = 0.64$.
3. **Compute the gradient:** $g = 2 \times (0.2 - 1.0) = -1.6$.
4. **Update the parameter:** $w_{\text{new}} = 0.2 - 0.1 \times (-1.6) = 0.36$. Subtracting a negative quantity increases `w`.
5. **Check the new prediction:** the next prediction is `0.36`, and its loss is $(0.36 - 1.0)^2 = 0.4096$, smaller than `0.64`.

This update moved the adjustable number toward the target. It changed a parameter value; it did not change any table dimensions or vocabulary IDs.

Classroom follow-up: arithmetic and update direction

Why does a negative gradient make `w` increase? Subtracting a negative number is equivalent to adding a positive number. Here, $0.1 \times (-1.6) = -0.16$, so the update adds `0.16` to `w`.

Connect that arithmetic to the purpose of learning: a negative gradient means that increasing `w` a little decreases the loss locally. The update therefore moves in a direction that can reduce the error, with the learning rate controlling how far it moves.

Does training always increase a parameter? Consider the same task with `w=1.2`, `target=1.0`, and `learning_rate=0.1`:

1. **Compute the loss:** $(1.2 - 1.0)^2 = 0.04$.
2. **Compute the gradient:** $g = 2 \times (1.2 - 1.0) = 0.4$, a positive value.
3. **Update the parameter:** $w_{\text{new}} = 1.2 - 0.1 \times 0.4 = 1.16$. This time, `w` decreases.
4. **Check the new loss:** $(1.16 - 1.0)^2 = 0.0256$, smaller than `0.04`.

In these two examples, the updates approach the target from opposite sides. Gradient descent adjusts the parameter according to the gradient; it does not always increase the parameter.

What happens when `w` already equals the target? For `w=1.0`, `target=1.0`, and `learning_rate=0.1`, the result is $g = 0$ and `w_new=1.0`. The full calculation is $g = 2 \times (1.0 - 1.0) = 0$, followed by $w_{\text{new}} = 1.0 - 0.1 \times 0 = 1.0$. The loss is zero, and this update leaves the parameter unchanged. This squared-error example has reached its minimum.

What does $g = -1.6$ predict for a parameter increase of `0.001`? The loss decreases by `0.0016`, using the supplied relation between gradient and local loss change:

```
estimated loss change = -1.6 * 0.001 = -0.0016
exact new loss = (0.201 - 1.0)^2 = 0.638401
exact loss change = 0.638401 - 0.64 = -0.001599
```

The gradient gives a local linear approximation. For this squared loss, the difference is the additional $h^2 = 0.000001$ term from the expansion. The exact calculation here is supplied explanation.

Returning to the embedding table

An embedding row has D adjustable values. A model can calculate a gradient for each participating parameter and use those gradients to update the numbers. The gradients come from how those values affect the prediction loss. The table remains shape `[V, D]` after an update.

Lesson 03.01's list lookup reads the existing values and does not calculate a loss, gradients, or updates. The coming tensor implementation will connect those operations. With many parameters, the same basic idea applies to arrays of values and gradients.

From the update rule to a function

The interface in 03_02_scalar_gradient_step.py is `gradient_step(w, target, learning_rate)`. Retain the numbered implementation plan below for review and independent reconstruction. The inputs

are three finite floats: the current parameter `w`, the fixed desired prediction `target`, and a positive `learning_rate`. The caller supplies these inputs; do not replace them with the example numbers.

Return a three-float tuple `(loss, gradient, w_new)` in that exact order. Both `loss` and `gradient` must describe the original `w`; `w_new` is the result of one update. The worked call `gradient_step(0.2, 1.0, 0.1)` should return approximately `(0.64, -1.6, 0.36)`. The new loss, `0.4096`, is checked separately by the supplied driver and is not the returned `loss`.

Follow these numbered steps, using four spaces of indentation inside the function:

1. **Calculate `error`.** Subtract `target` from `w`. The worked example gives `-0.8`.
2. **Calculate `loss`.** Square `error`. Python's power syntax is `value ** 2`; `^` is a different operator. The example gives `0.64`.
3. **Calculate `gradient`.** Multiply `error` by `2`, using `*`, and retain the sign. The example gives `-1.6`.
4. **Calculate `w_new`.** Multiply `gradient` by `learning_rate`, then subtract that quantity from the original `w`. The example gives `0.36`. Keep the original `w` available for the other calculations.
5. **Return the three values.** The pattern `return first, second, third` returns a tuple. Use the required order, and keep the return at the same indentation as the calculations. One update needs no loop.

The original scaffold used `raise NotImplementedError(...)` to stop the unfinished assignment. Replace that placeholder with your implementation. The supplied check driver remains unchanged. The bottom `if __name__ == "__main__":` calls that driver when the file is run directly; this control flow is supplied.

Run from the repository root to review the completed exercise:

```
python3 exercises/03_02_scalar_gradient_step.py
```

Expected success output:

```
PASS: negative gradient increases w and reduces loss
PASS: positive gradient decreases w and reduces loss
PASS: zero gradient leaves the parameter unchanged
PASS: supplied target and learning rate control the update
PASS: a large learning rate can increase loss
Lesson 03.02 checks passed.
```

The driver compares floats with a tolerance because decimal values can have small rounding differences. It also checks a larger step: `learning_rate=1.2` moves `w=0.2` to `2.12`, giving a new loss of `1.2544`, larger than `0.64`. Calculate the requested update faithfully; a positive learning rate does not guarantee a decrease for every step.

This function performs one training step in the toy task. Repeated training would feed `w_new` into the next call, then calculate the loss and gradient again at that new value. A training loop and automatic differentiation are later steps.

Next concept: repeated updates use the latest parameter

Keep `target=1.0` and `learning_rate=0.1`. One call returns an updated parameter; the next call must use that value as its input `w` and recalculate the loss and gradient.

Update	Input `w`	Loss before update	Gradient at input `w`	Returned `w_new`
1	`0.2`	`0.64`	`-1.6`	`0.36`
2	`0.36`	`0.4096`	`-1.28`	`0.488`
3	`0.488`	`0.262144`	`-1.024`	`0.5904`

For update 2, gradient $= 2 \times (0.36 - 1.0) = -1.28$, then $w_{\text{new}} = 0.36 - 0.1 \times (-1.28) = 0.488$. After update 3, the loss is $(0.5904 - 1.0)^2 = 0.16777216$.

The gradient depends on the current parameter. Reusing `-1.6` at input `w=0.36` would produce `0.52`; that uses a derivative measured at a different point rather than the gradient at the current value. Recalculate both loss and gradient on each iteration.

Returning `w_new` does not automatically replace the caller's `w`. This function uses ordinary floats and returns a new value; the caller must keep that value for the next step. Calling the function repeatedly with `w=0.2` would keep returning the same first update. Repeated training connects each update's output to the next update's input.

At the second update, `w` became `0.36`, its error is `-0.64`, and multiplying by `2` gives `-1.28`. This demonstrates recalculation at the latest parameter. Keeping returned values in caller state and implementing the loop are separate tasks.

Continue with Lesson 03.03: a scalar training loop. Its guided exercise is now prepared; trainable tensors follow later.

Explanation checkpoint

Continue with the loop assignment in Lesson 03.03. Independently explain why the function returns the original loss, why a larger learning rate can overshoot, and which quantity changes when training updates an embedding table: its number of rows, or its floating-point values?

03.03 A Scalar Training Loop

One update changes the parameter, so the next update must ask a fresh question at the new value. A training loop carries that value forward and keeps a record of the losses that produced each step. The arithmetic stays small enough to check by hand while we learn the loop structure used later.

Work through the example before editing 03_03_scalar_training_loop.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

What a training loop connects

For each requested update, the loop:

1. Calls `gradient_step` with the current parameter.
2. Records the returned loss, measured before that update.
3. Keeps the returned `w_new` as the parameter for the next call.

The target and learning rate remain fixed in this exercise. The parameter changes between calls, so the helper recalculates both loss and gradient. The number of steps is a fixed budget: perform exactly that many updates, even if a gradient is zero or a large step increases loss.

An ordinary float is a value. The helper returns a new value; the caller must assign it to the working parameter. Repeated calls with the same original input would repeat the same first update.

Exact inputs, state, and returned values

Implement `train_scalar(initial_w, target, learning_rate, num_steps)`.

Name	Type	Meaning	Example
`initial_w`	`float`	Parameter before any updates.	`0.2`
`target`	`float`	Fixed desired prediction.	`1.0`
`learning_rate`	`float`	Positive update multiplier.	`0.1`
`num_steps`	`int`	Nonnegative number of updates.	`3`
`w`	`float`	Working parameter, initialized once and carried forward.	`0.2`, then `0.36`
`losses`	`list[float]`	One loss before each update, in order.	`[0.64, 0.4096, 0.262144]`
`step`	`int`	Loop repetition counter; not a parameter or learning rate.	`0`, `1`, `2`

Assume finite float inputs, a positive learning rate, and `num_steps >= 0`; input validation is outside this learner task. Return a tuple `(w, losses)` of type `tuple[float, list[float]]`, containing the final parameter and the history. Its list has exactly `num_steps` items. For zero updates, return the original parameter and an empty list.

Each helper call returns three local values: `loss`, `gradient`, and `w_new`. The loop needs the loss for its history and the new parameter for the next call. The helper has already used the gradient to calculate `w_new`.

Complete worked example

Use `initial_w=0.2`, `target=1.0`, `learning_rate=0.1`, and `num_steps=3`.

Log the loss before each update

x = 1, target = 1, learning_rate = 0.1

step	w_{before}	loss	gradient	w_{after}
0	0.2	0.64	-1.6	0.36
1	0.36	0.4096	-1.28	0.488
2	0.488	0.262144	-1.024	0.5904

losses = [0.64, 0.4096, 0.262144]

Evaluate the final state separately: $L(w_3) = 0.16777216$.

Figure 15: Read each table row from the pre-update parameter through its loss and gradient to the updated parameter. The three loss entries form the returned history. The last row ends at the final parameter; its separately evaluated loss appears in the footer.

Read each table row from the pre-update parameter through its loss and gradient to the updated parameter. The three loss entries form the returned history. The last row ends at the final parameter; its separately evaluated loss appears in the footer.

Before the loop, the working parameter is `w=0.2` and `losses=[]`.

1. **First iteration, `step=0`:** call the helper with `w=0.2`. It returns approximately `(0.64, -1.6, 0.36)`. Append `0.64` and keep `w=0.36`. State: `losses=[0.64]`.
2. **Second iteration, `step=1`:** use `w=0.36`, not the initial value. The helper returns approximately `(0.4096, -1.28, 0.488)`. Append `0.4096` and keep `w=0.488`. State: `losses=[0.64, 0.4096]`.
3. **Third iteration, `step=2`:** use `w=0.488`. The helper returns approximately `(0.262144, -1.024, 0.5904)`. Append `0.262144` and keep `w=0.5904`.

After all three iterations, return approximately:

```
(0.5904, [0.64, 0.4096, 0.262144])
```

The final parameter's loss is `0.16777216`. This list records the loss used before each update, so it does not add that final loss as a fourth item. Logging time matters: a record should say which parameter

state its loss describes.

For `num_steps=0`, no helper call occurs. The initialized `w` and empty history are returned directly. For example, `train_scalar(0.2, 1.0, 0.1, 0)` returns `(0.2, [])`.

Syntax and indentation before implementation

`range(3)` produces counters `0`, `1`, and `2`: exactly three repetitions. Its last counter is `2`, because the stopping value is excluded. `range(0)` is empty.

The header `for step in range(num_steps):` repeats its indented body once per counter. It belongs at four-space indentation inside the function. The loop body uses eight spaces. `step` controls repetition; pass the current `w` to the helper, not this counter.

Tuple unpacking assigns by position. For example, `a, b, c = (10, 20, 30)` assigns `10` to `a`, `20` to `b`, and `30` to `c`. Use the helper's order when assigning `loss`, `gradient`, and `w_new`.

`collection.append(item)` adds one item to a list. Here the item is a single loss float. Initialize the history before the loop so each iteration adds to the same list.

`return` leaves the whole function. Place it after the loop at four-space indentation, so all requested updates finish and the zero-update case also returns.

Guided implementation

Use this plan to implement the function and review the reasoning.

1. **Initialize `w` from `initial_w`.** Use ordinary assignment at four-space indentation. Do this once before looping.
2. **Initialize `losses`.** Create a fresh empty list with `[]`, also before the loop.
3. **Create the fixed-length loop.** Use `for step in range(num_steps):` at four-space indentation. Steps 4–6 go inside its body at eight spaces.
4. **Call the completed helper.** Pass the current `w`, `target`, and `learning_rate` to `gradient_step`. Unpack the return into `loss`, `gradient`, and `w_new`. The second call should receive `w=0.36` in the example.
5. **Record `loss`.** Append that one float to `losses`. After two iterations, the list should be approximately `[0.64, 0.4096]`.
6. **Keep the updated parameter.** Assign `w_new` to the working `w`. This is the value the next call will read. After two iterations, it should be `0.488`.
7. **Return after the loop.** Return `w` and `losses`, in that order, at four-space indentation. The pattern `return first, second` returns a two-item tuple.

The supplied setup loads `gradient_step` from `03_02_scalar_gradient_step.py` without running that exercise's driver. The setup and supplied check driver remain unchanged. The bottom `if __name__ == "__main__":` calls the checks when this file is run directly.

Run and expected success output

From the repository root, to review the completed exercise:

```
python3 exercises/03_03_scalar_training_loop.py
```

Expected output:

```
PASS: current parameter, recalculated gradients, and loss history
PASS: zero and one update
PASS: requested step count and separate calls
PASS: different starting values, targets, and learning rates
PASS: zero gradient still records every requested step
PASS: large steps remain visible in loss history
Lesson 03.03 checks passed.
```

The checks allow small floating-point rounding differences. They verify more than the three-step example: zero and one step, another step count, independent histories across calls, changed inputs, zero gradients, and a large learning rate. With `learning_rate=1.2`, two updates return approximately `(-0.568, [0.64, 1.2544])`; faithfully retain the requested history even when a loss increases.

Reading a tuple assignment

Consider this implementation:

```
loss, gradient, w = gradient_step(w, target, learning_rate)
```

This correctly combines unpacking the helper's results and carrying the new parameter forward. Python first evaluates the right-hand-side call with the old `w`, then assigns its three returned values to the left-hand-side variables. For the first update:

1. The helper receives the old `w=0.2`.
2. It returns approximately `(0.64, -1.6, 0.36)`.
3. Assignment gives `loss=0.64`, `gradient=-1.6`, and the new `w=0.36`.
4. `losses.append(loss)` records the pre-update loss `0.64`, even though `w` now holds the updated parameter.
5. The next iteration calls the helper with `w=0.36`.

The helper's third return value is called `w_new` inside that helper; the caller may bind it directly to `w`. The tuple's positions determine which value is assigned. The loop counter name `step` is also valid and is now used consistently in these notes. The unused returned `gradient` does not require an additional update: the helper already used it to compute the third result.

Classroom follow-up: zero updates

For `train_scalar(0.2, 1.0, 0.1, 0)`, the result is `(0.2, [])`: `range(0)` skips the loop body, and the return after the loop still executes.

The complete trace is:

1. `w = initial_w` gives `w=0.2`.
2. `losses = []` creates the empty history.
3. `range(0)` provides no counters, so neither the helper call nor the append runs.
4. The final `return w, losses`, at the loop header's indentation, executes and returns `(0.2, [])`.

An empty loop skips its body; execution then continues with the following statement.

Questions to work through

Why must the parameter and loss history be initialized before the loop? In the tuple assignment, which value of `w` reaches `gradient_step`, and when is the returned value bound to `w`? Why does the history record the loss before each update rather than an extra loss at the final parameter? Use the three-step trace and the zero-step example to explain your answers.

Continue with Lesson 03.04: chain rule and automatic differentiation. The remaining loop checkpoints stay available for review. Trainable tensors follow the chain-rule introduction.

03.04 Chain Rule and Automatic Differentiation

Method sources

For neural-network backpropagation, see Rumelhart et al., 1986; R39; for the graph and gradient behavior used by our exercises, see PyTorch, v2.0 autograd; R16. Backpropagation computes derivatives; the optimizer performs a separate parameter update.

A parameter usually affects a loss through several operations. To understand automatic differentiation, we will follow one such path: multiply an input, subtract a target, and square the error. The chain rule connects the local response of each operation into the derivative of the whole computation.

This section develops the chain rule without a separate code assignment. The next section turns the same calculation into PyTorch operations.

Define the functions and gradient before calculating numbers

Hold x and `target` fixed. The model and objective are functions of the adjustable parameter w:

```
prediction(w) = w * x
L(w) = loss = (prediction(w) - target) ** 2
     = (w * x - target) ** 2
```

The gradient sought here is $\frac{dL}{dw}$: the derivative of the loss with respect to the parameter. For a differentiable scalar function, its definition is:

```
dL/dw = limit as h approaches 0 of (L(w + h) - L(w)) / h
```

Here h is a nonzero change in w before taking the limit. The derivative measures the loss's local rate of change as w changes, with the fixed quantities held constant. It does not mean dividing the current loss value by the current parameter value.

The **chain rule**, for this composition through `prediction`, is:

```
dL/dw = dL/d(prediction) * d(prediction)/dw

dL/d(prediction) = 2 * (prediction - target)
d(prediction)/dw = x

gradient = dL/dw = 2 * (prediction - target) * x
                 = 2 * (w * x - target) * x
```

The first derivative describes the loss's response to the prediction; the second describes the prediction's response to the parameter. Their product connects the loss to the parameter. This is the scalar chain rule for the dependency path in this example. The derivation below obtains the result from the derivative definition, before substituting numerical values.

Parameter, input, prediction, and loss

For this example, every quantity is a scalar number. Python examples use `float` values.

Name	Role	Initial value
w	Adjustable model parameter.	`0.2`
x	Fixed input for this example.	`2.0`
`target`	Fixed desired prediction.	`1.0`
`prediction`	Model output, calculated as wx.	`0.4`
`error`	Prediction minus target.	`-0.6`
`loss`	Squared error, a scalar objective to reduce.	`0.36`
`gradient`	Derivative of loss with respect to w at its current value.	Calculated below.
`learning_rate`	Positive multiplier used in the parameter update.	`0.1`

The parameter and the prediction now have different values. With `x=1.0`, this model reduces to the earlier prediction $= w$ example. For this calculation, hold x and `target` fixed while considering a change in w.

Derivation: why the two rates multiply

At the original w, write error $= wx -$ target. Changing w to $w + h$ changes the prediction and error by exactly xh:

```
prediction(w + h) = prediction(w) + x * h
error_new = error + x * h
```

Expand the square to obtain the exact finite loss change:

```
L(w + h) - L(w)
    = (error + x * h) ** 2 - error ** 2
    = 2 * error * x * h + x ** 2 * h ** 2
```

Divide by the parameter change, then take the limit:

```
(L(w + h) - L(w)) / h = 2 * error * x + x ** 2 * h

as h approaches 0:
    dL/dw = 2 * error * x
          = 2 * (w * x - target) * x
```

The term x^2h tends to zero. The factor $2\,\texttt{error}$ comes from the loss's response to its prediction, and the factor x comes from the prediction's response to w. Multiplying the rates accounts for both dependencies. This derivation establishes the formula for this example; the general chain rule extends the same local-rate reasoning to differentiable compositions.

Using the intermediate `error` explicitly gives the three-factor form:

```
dL/dw = dL/d(error) * d(error)/d(prediction) * d(prediction)/dw
      = (2 * error) * 1 * x
```

Subtracting a fixed target has derivative `1`, so the two-factor and three-factor forms give the same result. The value $2\,\texttt{error}$ gives the loss derivative with respect to `error`, and also with respect to `prediction` here. To obtain the derivative with respect to w, include the prediction's derivative x. When `x=1`, this reduces to the earlier formula in Lesson 03.02.

Worked forward pass: substitute the values

Follow the operations in order:

```
prediction = w * x
error = prediction - target
loss = error ** 2
```

With `w=0.2`, `x=2.0`, and `target=1.0`:

1. prediction $= 0.2 \times 2.0 = 0.4$.
2. error $= 0.4 - 1.0 = -0.6$.
3. $L = (-0.6)^2 = 0.36$.

This calculation from the inputs and parameter to the loss is the **forward pass**. Its dependency path is `w → prediction → error → loss`. A computation graph records such dependencies and operations;

the fixed input and target also feed their respective operations.

Local derivatives: how each operation responds

The notation $\frac{dA}{dB}$ means the derivative of A with respect to B: the local rate at which A changes as B changes. It is not ordinary division of the values A and B. A rate can be negative or greater than one.

Read the operations backward, starting at the loss:

1. **Square:** $L = \text{error}^2$. Its derivative with respect to `error` is $2\,\text{error}$. At `error=-0.6`, this is `-1.2`.
2. **Subtract a fixed target:** $\text{error} = \text{prediction} - \text{target}$. Increasing `prediction` by a small amount increases `error` by the same amount. Its derivative with respect to `prediction` is `1`.
3. **Multiply by a fixed input:** $\text{prediction} = wx$. Increasing w by a small amount changes `prediction` by x times that amount. Its derivative with respect to w is `x=2.0`.

The square derivative uses the rule introduced in Lesson 03.02. Here it is first applied to the intermediate variable `error`; the chain rule connects it to the parameter.

Worked chain rule: evaluate the derived formula

The loss depends on the error, the error on the prediction, and the prediction on w. The derivative along this single path is the product of its local derivatives:

```
d(loss)/d(w)
    = d(loss)/d(error) * d(error)/d(prediction) * d(prediction)/d(w)
    = (2 * error) * 1 * x
    = (-1.2) * 1 * 2.0
    = -2.4
```

Therefore, for this model and loss:

```
gradient = 2 * (w * x - target) * x
```

The final factor x accounts for how strongly the parameter affects the prediction. For example, increasing w by `0.001` increases `prediction` and `error` by `0.002`. At the current values, the first-order estimate of the loss change is $-1.2 \times 0.002 = -0.0024$, which also equals gradient $\times\, 0.001$. This estimate describes a small local change, not an exact finite difference.

Multiply the derivative factors associated with the operations. The prediction value `0.4` and loss value `0.36` are forward results, not extra derivative factors.

Backward pass and automatic differentiation




Figure 16: Teal arrows follow the forward calculation; the reverse orange arrows carry local derivatives. Multiply the three displayed factors to obtain dL/dw=-2.4.

Teal arrows follow the forward calculation; the reverse orange arrows carry local derivatives. Multiply the three displayed factors to obtain dL/dw=-2.4.

Computing the loss gradient through the operations in reverse order is the **backward pass**, also called **backpropagation** in model training. In this example:

Gradient being computed	Rule	Result
Loss with respect to `error`	2 error	`-1.2`
Loss with respect to `prediction`	Previous gradient times `1`	`-1.2`
Loss with respect to w	Previous gradient times x	`-2.4`

Automatic differentiation records the relevant operations and intermediate values, then applies their derivative rules and the chain rule to compute gradients. A framework can perform this bookkeeping for many parameters. In a scalar-loss model, each parameter's gradient expresses the loss's local response to that parameter while the other parameters are held fixed.

This lesson follows one dependency path. When a parameter contributes through multiple paths, their gradient contributions are added; a later lesson will work through that case.

The training responsibilities remain distinct:

1. Define the model's forward computation and the loss.
2. Calculate gradients with a backward pass.

3. Apply an update rule, using the selected learning rate.
4. Recompute the forward values and gradients at the updated parameters for the next iteration.

Automatic differentiation supplies gradients. The parameter update is a separate operation.

One complete update

With `gradient=-2.4` and `learning_rate=0.1`, gradient descent gives:

```
w_new = w - learning_rate * gradient
      = 0.2 - 0.1 * (-2.4)
      = 0.44
```

Recompute the forward pass with this new parameter:

```
prediction_new = 0.44 * 2.0 = 0.88
error_new = 0.88 - 1.0 = -0.12
loss_new = (-0.12) ** 2 = 0.0144
```

This example's loss decreased from `0.36` to `0.0144`. These values establish the result for this update; a large learning rate can still increase loss, as Lesson 03.02 demonstrated. The forward pass, backward pass, and update together make one training iteration.

A hand-calculation exercise

The numerical checkpoint used `w=0.6`, `x=2.0`, and `target=1.0`. Retain its calculation plan for optional review:

1. Calculate prediction $= wx$.
2. Calculate error $=$ prediction $-$ target.
3. Calculate the square operation's local derivative, 2 error.
4. Multiply it by the subtraction derivative `1` and multiplication derivative x to obtain `d(loss)/d(w)`.

With `w=0.6`, `x=2`, and `target=1`, prediction is `1.2`, error is `0.2`, loss is `0.04`, and the parameter gradient is $2 \times 0.2 \times 2 = 0.8$. The factor x comes from differentiating the prediction with respect to w.

03.05 Scalar Automatic Differentiation with PyTorch

Method sources

The differentiation context is Rumelhart et al., 1986; R39; the specific PyTorch graph, leaf-tensor and gradient-accumulation rules are documented in PyTorch, v2.0 autograd; R16. Our scalar arithmetic is an independently constructed example.

The chain rule does not change when PyTorch computes it for us. What changes is how we describe the computation: a trainable tensor records dependencies, a scalar loss is sent backward, and the parame-

ter receives its gradient. We will match every API operation to the hand calculation from the previous section.

Work through the example before editing 03_05_scalar_autograd.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

The model, loss, and gradient

Keep `x` and `target` fixed, and differentiate with respect to `w`:

```
prediction = w * x
error = prediction - target
L = loss = error ** 2

dL/dw = dL/d(error) * d(error)/d(prediction) * d(prediction)/dw
      = (2 * error) * 1 * x
      = 2 * (w * x - target) * x
```

The derivative formula is our reference for understanding and verification. In the exercise, write the forward computation and let automatic differentiation calculate the gradient from that computation.

Principle: reverse differentiation through recorded operations

For an intermediate quantity u, define $g_u = \frac{dL}{du}$: the loss's derivative with respect to that quantity. For an operation $v = f(u)$, its reverse contribution is:

```
g_u += g_v * d(v)/d(u)
```

Initialize gradient accumulators to zero and start at the scalar loss with $g_L = \frac{dL}{dL} = 1$. The `+=` notation means adding the contribution to the current accumulator; several paths can contribute to the same quantity. On the single path in this exercise, each quantity receives one contribution.

In the forward pass, PyTorch computes tensor values and records relevant operations and the information needed by their derivative rules. In the backward pass, it processes those dependencies in reverse, combining each incoming gradient with the operation's local derivative. This is reverse-mode automatic differentiation. The official autograd tutorial explains this recording and propagation.

The chain-rule result is evaluated at the current forward values. Floating-point arithmetic can round the result. A finite-difference calculation perturbs the input and estimates a derivative; this lesson's driver uses one as an independent check. A symbolic derivation manipulates a formula, as in Lesson 03.04. Autograd here evaluates operation derivative rules along the recorded computation.

Complete forward and backward example




Figure 17: The forward values match the hand calculation. Backward uses those dependencies to populate the leaf parameter's .grad; extracting a reporting number with .item() is a different operation.

The forward values match the hand calculation. Backward uses those dependencies to populate the leaf parameter's .grad; extracting a reporting number with .item() is a different operation.

The mathematical names `w` and `prediction` are `w_tensor` and `prediction_tensor` in the exercise code; the extracted gradient number is `grad_value`. These local names are valid. The API explanation and implementation plan below use them consistently.

Use `w_value=0.2`, `x=2.0`, and `target=1.0`.

Forward quantity	Formula	Value
Parameter `w_tensor`	Tensor created from `w_value`	`0.2`
`prediction_tensor`	`w_tensor * x`	`0.4`
`error`	`prediction_tensor - target`	`-0.6`
`loss`	`error ** 2`	`0.36`

Before backward, the fresh parameter's `w_tensor.grad` is `None`: no gradient has been stored yet. The conceptual reverse trace is:

```
g_L = 1
g_error = g_L * (2 * error) = 1 * (-1.2) = -1.2
g_prediction = g_error * 1 = -1.2
g_w = g_prediction * x = (-1.2) * 2.0 = -2.4
```

`None` differs from a zero gradient: it represents the absence of a stored gradient. A computed zero derivative is stored as a zero-valued gradient tensor after backward.

After backward, `w_tensor.grad` contains approximately `-2.4`. The parameter still holds `0.2`; backward calculated its loss derivative. A separate update would use `w_new = w - learning_rate * gradient`. This function returns only loss and gradient, so it has no learning-rate argument or update step. The expected return is approximately `(0.36, -2.4)`.

For the positive-error example, `w_value=0.6`, `x=2.0`, and `target=1.0` give prediction `1.2`, error `0.2`, loss `0.04`, and parameter gradient `0.8`.

A useful boundary case is `x=0` and `target=1`: the prediction is zero for every `w_tensor`, so the loss is `1` and the parameter gradient is `0`. Changing this parameter cannot change the prediction for that input. A zero gradient alone does not imply a zero loss.

The PyTorch objects and syntax

`import torch` loads the library. A tensor stores numerical data and supports operations that can participate in automatic differentiation. A scalar tensor contains one number and has zero dimensions; it is distinct from an empty tensor. Later lessons extend tensors to vectors and tables.

An isolated constructor example is:

```
parameter = torch.tensor(0.6, dtype=torch.float64, requires_grad=True)
```

The first argument supplies the number. `dtype=torch.float64` chooses 64-bit floating-point precision; this is a numeric representation, not a tensor shape or embedding dimension. `requires_grad=True` requests gradient tracking for operations involving this tensor in normal gradient mode. `True` is a Boolean value with a capital T. This directly created parameter is a **leaf tensor**, the starting parameter node. See the tensor constructor.

Arithmetic with this tensor produces connected tensor results. Keep `prediction_tensor`, `error`, and `loss` as tensors through the forward computation. This example can multiply by a Python float `x` and subtract a Python float `target` while preserving the dependency on `w_tensor`.

`loss.backward()` calls the loss tensor's method. The dot selects a method; parentheses execute it. For this scalar loss, the starting gradient is implicitly `1`. The method returns `None` and stores gradients on the participating leaf tensors, including `w_tensor.grad`. Read `.grad` after the call. By default, intermediate tensors do not retain a `.grad` value, even though their derivatives are used internally. Each call in this exercise creates a fresh `w_tensor`; accumulation and clearing when reusing a parameter are later topics. See Tensor.backward.

`w_tensor.grad` is an attribute containing a gradient tensor. `w_tensor.grad.item()` then calls that tensor's method to extract its Python number. Similarly, `loss.item()` extracts the loss number. `.item()` operates on a one-element tensor and is not differentiable; extract numbers for the return after backward. Replacing the connected `loss` with a Python float before calling backward loses the needed tensor object. See Tensor.item.

Exact inputs, local variables, and return

Name	Type	Meaning
`w_value`	`float`	Parameter number at the start of this call.
`x`	`float`	Fixed input multiplier.
`target`	`float`	Fixed desired prediction.
`w_tensor`	Scalar `torch.Tensor`	Fresh parameter with gradient tracking enabled.
`prediction_tensor`, `error`, `loss`	Scalar `torch.Tensor`	Connected forward results.
`w_tensor.grad`	`None`, then scalar `torch.Tensor`	Uncomputed gradient, then stored loss derivative with respect to `w_tensor`.
`grad_value`	`float`	Number extracted from the computed parameter gradient.

Assume finite input floats. Return a tuple `(loss_value, grad_value)` of two Python floats, both describing the original parameter. The implementation stores the extracted loss in local variable `loss_value` and the extracted gradient in `grad_value`. The function does not need loops, conditions, or input validation.

Guided implementation

Retain this plan for reviewing or reconstructing the implementation, using its actual local names. Keep the supplied imports and driver. Each implementation statement uses four spaces of indentation inside the function.

1. **Create `w_tensor` from `w_value`.** Use `torch.tensor(value, dtype=..., requires_grad=...)` with the function argument, `torch.float64`, and `True`. Its value is `0.2` in the example, with `w_tensor.grad` initially `None`. Create it inside the function for an independent calculation on every call.
2. **Calculate `prediction_tensor`.** Multiply tensor `w_tensor` by argument `x` using `*` and ordinary assignment. The example result is a scalar tensor holding `0.4`.
3. **Calculate `error`.** Subtract argument `target` from `prediction_tensor`. The example result holds `-0.6`.
4. **Calculate `loss`.** Square `error` with `** 2`. The example result holds `0.36`. Keep the tensor connected to `w_tensor`.
5. **Run backward once.** Call `loss.backward()` on its own line. `w_tensor.grad` then holds `-2.4`, while `w_tensor` still holds `0.2`.
6. **Read `grad_value`.** Extract the number from `w_tensor.grad` with `.item()`. The example Python float is approximately `-2.4`; obtain it from autograd rather than the manual derivative formula.

7. **Return two numbers.** Extract the number from `loss`, then return it followed by `grad_value`. The syntax `return first, second` produces a two-item tuple. The example result is approximately `(0.36, -2.4)`.

Run, expected output, and troubleshooting

Activate the existing PyTorch environment in your terminal. Run from the project root with that environment's `python`:

```
python exercises/03_05_scalar_autograd.py
```

The example produces:

```
PASS: negative and positive parameter gradients
PASS: unit input matches the earlier scalar loss
PASS: changed inputs and targets
PASS: zero gradients with zero and nonzero losses
PASS: separate calls produce independent results
PASS: finite-difference gradient agreement
Lesson 03.05 checks passed.
```

If `torch` cannot be imported, check the selected interpreter and activate the existing environment. If the loss has no gradient history, check `requires_grad=True` and that tensor results were preserved. If `w_tensor.grad` is `None`, check that backward ran on the connected loss before reading it. `loss.backward()` returning `None` is normal; retrieve the gradient from the parameter's attribute. The checks allow floating-point rounding differences.

Questions to work through

Optional review: explain what `requires_grad` enables, why reverse differentiation starts with `1`, where the computed gradient is stored, why backward leaves `w_tensor` unchanged, and when `.item()` is appropriate. Continue with Lesson 03.06 to clear old gradients and apply a tensor parameter update. Later lessons connect these steps to training loops and embeddings.

03.06 Updating a Tensor Parameter

Method sources

The tensor backward operation relies on the autograd rules in PyTorch, v2.0 autograd; R16. For the neural-network chain-rule context, see Rumelhart et al., 1986; R39; this worksheet uses a small squared-error example.

A gradient is information about a parameter, not a changed parameter. Completing a training step requires us to clear old derivative buffers, compute the new gradient, and then update the same tensor. We will keep the differentiable calculation and the parameter update in their proper scopes.

Work through the example before editing 03_06_tensor_gradient_step.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

Derivative and update

Hold the input `x` and desired prediction `target` fixed. For the scalar parameter `w`:

```
prediction = w * x
error = prediction - target
L(w) = loss = error ** 2
g = dL/dw = 2 * (w * x - target) * x
w_new = w - learning_rate * g
```

The derivative comes from Lesson 03.04's chain rule. For a small parameter change Δw, the local estimate is $\Delta L \approx g\,\Delta w$. Substituting gradient descent's change $\Delta w = -\texttt{learning_rate}\,g$ gives $\Delta L \approx -\texttt{learning_rate}\,g^2$. With a positive learning rate and nonzero gradient, that estimate is negative. This explains the chosen direction; the approximation does not guarantee a decrease for a large finite step.

For this particular squared loss, the exact finite change is:

```
L(w + delta_w) - L(w) = g * delta_w + x ** 2 * delta_w ** 2
```

The extra square term can outweigh the negative first-order term. The supplied checks retain the earlier large-learning-rate example as a boundary case.

Classroom Q&A: prediction minus target, or target minus prediction?

Consider whether `error = predicted_tensor - target` could instead subtract in the opposite order, and what difference `target - predicted_tensor` would make. Let a = prediction $= wx$ and b = target, with `x` and `target` fixed. Both signed-error conventions are valid for this squared-error objective:

```
error = a - b
error_reversed = b - a = -error

loss = error ** 2 = error_reversed ** 2
```

`error_reversed` is a name for this explanatory alternative, not a new variable added to the completed exercise. The current exercise code keeps `error = predicted_tensor - target`.

The sign describes opposite meanings:

Signed-error definition	Positive value means	Negative value means
`a - b`	Prediction is above the target	Prediction is below the target
`b - a`	Prediction is below the target	Prediction is above the target

For prediction `0.4` and target `1.0`, the two errors are `-0.6` and `+0.6`; their squares both equal `0.36`. For prediction `1.2` and target `1.0`, they are `+0.2` and `-0.2`; their squares both equal `0.04`. The opposite sign changes the description of the deviation, not the value of this squared loss.

Reversing the error also reverses its derivative with respect to the prediction. Apply the chain rule consistently:

```
prediction = w * x

Original definition:
    error = prediction - target
    d(error)/d(prediction) = +1
    dL/dw = (2 * error) * (+1) * x

Reversed definition:
    error_reversed = target - prediction
    d(error_reversed)/d(prediction) = -1
    dL/dw = (2 * error_reversed) * (-1) * x
```

Why is the reversed subtraction's derivative `-1`? When prediction increases by a small amount, `target - prediction` decreases by that same amount. Meanwhile $\text{error}_{\text{reversed}} = -\text{error}$, so the two sign changes cancel and the final parameter gradients agree.

With `w=0.2`, `x=2.0`, and `target=1.0`, the complete comparison is:

Quantity	Prediction minus target	Target minus prediction
Prediction	`0.4`	`0.4`
Signed error	`-0.6`	`+0.6`
Squared loss	`0.36`	`0.36`
Error derivative with respect to prediction	`+1`	`-1`
Loss derivative with respect to `w`	$2 \times (-0.6) \times (+1) \times 2 = -2.4$	$2 \times (+0.6) \times (-1) \times 2 = -2.4$

Both parameter updates at learning rate `0.1` give $w_{\text{new}} = 0.2 - 0.1 \times (-2.4) = 0.44$. The intermediate errors and local derivatives have opposite signs; the squared objective, final parameter gradient, and update are the same. Do not change the subtraction in gradient descent merely because the error definition was reversed.

When manually deriving a gradient for `error_reversed`, use the factor `-1`: its formula is `-2 * error_reversed * x`, not `2 * error_reversed * x`. In this exercise, `loss.backward()` differentiates the written forward expression, so it accounts for that factor automatically. This equivalence follows from the symmetric square; it is not a rule that subtraction order is irrelevant to every possible objective.

Classroom Q&A: why subtract `learning_rate * gradient`?

A common question is why the update subtracts the scaled gradient rather than adding it. Start with what the gradient means: $g = \frac{dL}{dw}$ describes the local change in loss when the parameter increases. It is

a derivative, not the prediction error or a direct instruction to increase the parameter.

For a small parameter change, write:

```
delta_L ≈ g * delta_w
```

We want a negative loss change. With a positive learning rate, choose a parameter change with the opposite sign to the gradient:

```
delta_w = -learning_rate * g
delta_L ≈ g * (-learning_rate * g)
        = -learning_rate * g ** 2
```

For nonzero g, this local estimate is negative. Adding the scaled gradient instead gives $\Delta L \approx +\texttt{learning_rate}\, g^2$, a positive local estimate. The negative sign chooses the descent direction; the positive learning rate sets the step size.

Gradient at the current parameter	Effect of a small increase in `w`	Descent choice
$g > 0$	Loss increases locally	Decrease `w`
$g < 0$	Loss decreases locally	Increase `w`
$g = 0$	First-order change is zero	This update leaves `w` unchanged

Using the existing example, `w=0.2`, `x=2.0`, and `target=1.0` give `prediction=0.4`, `error=-0.6`, `loss=0.36`, and $g = -2.4$. Compare the two signs at `learning_rate=0.1`:

Update	New `w`	New prediction	New error	Recomputed loss
Subtract: $0.2 - 0.1 \times (-2.4)$	`0.44`	`0.88`	`-0.12`	`0.0144`
Add: $0.2 + 0.1 \times (-2.4)$	`-0.04`	`-0.08`	`-1.08`	`1.1664`

Subtracting this negative gradient increases the parameter and lowers the loss for this step. Adding it decreases the parameter and raises the loss. In both cases, recalculate the loss from the new parameter to assess the finite step. The local descent argument still needs a sufficiently small step; a large learning rate can overshoot. A zero gradient alone does not prove a minimum.

The useful interpretation is: read the gradient as a local slope, choose the opposite direction to reduce the loss, and use the learning rate to scale that change.

Classroom Q&A: numerical examples of positive and negative slopes

```
L(w) = (w - 1) ** 2
g(w) = dL/dw = 2 * (w - 1)
```

The squared distance to `1` is smallest at `w=1`. The derivative is evaluated at the current parameter, so the same function can have different gradient signs at different points. Compare two starting points without using an optimizer; simply recalculate the loss after increasing or decreasing `w` by `0.1`.

Start at `w=2`: a positive gradient. The derivative is $g(2) = 2(2-1) = +2$.

Action from the starting point	Parameter	Exact loss
Original	`2.0`	$(2.0-1)^2 = 1.0$
Increase by `0.1`	`2.1`	$(2.1-1)^2 = 1.21$
Decrease by `0.1`	`1.9`	$(1.9-1)^2 = 0.81$

Increasing the parameter moves farther from the target and raises the loss. Decreasing it moves toward the target and lowers the loss. Thus a positive gradient calls for a negative parameter change in gradient descent.

Start at `w=0`: a negative gradient. The derivative is $g(0) = 2(0-1) = -2$.

Action from the starting point	Parameter	Exact loss
Original	`0.0`	$(0.0-1)^2 = 1.0$
Increase by `0.1`	`0.1`	$(0.1-1)^2 = 0.81$
Decrease by `0.1`	`-0.1`	$(-0.1-1)^2 = 1.21$

Increasing the parameter now moves toward the target and lowers the loss. Decreasing it moves farther away and raises the loss. Thus a negative gradient calls for a positive parameter change in gradient descent.

The two original losses both equal `1`, while their gradients are `+2` and `−2`. A gradient's sign describes the local slope, not whether the loss itself is positive or negative. For this example, being on different sides of the minimum explains the opposite slopes; general models require examining their own loss derivatives.

Connect both cases to the update with `learning_rate=0.05`:

```
At w=2, g=+2:
    w_new = 2 - 0.05 * 2 = 1.9
    loss: 1.0 -> 0.81

At w=0, g=-2:
    w_new = 0 - 0.05 * (-2) = 0.1
    loss: 1.0 -> 0.81
```

One subtraction rule selects the appropriate direction at both starting points. The table values are exact finite-step calculations up to floating-point rounding, whereas $\Delta L \approx g\,\Delta w$ is a first-order estimate. At a change of `0.1`, the square term accounts for the difference between an estimated change of `0.2` and the exact increase `0.21`, or between an estimated decrease of `0.2` and the exact decrease `0.19`. These examples illustrate the sign locally; very large changes may cross the minimum.

A complete first update

Use `w=0.2`, `x=2.0`, `target=1.0`, and `learning_rate=0.1`. In code, the parameter is named `w_tensor` and the prediction is `predicted_tensor`.

Stage	Calculation	Result
Clear prior gradient	Discard the stored `.grad` value	Parameter still `0.2`
Forward prediction	0.2×2.0	`0.4`
Forward error	`0.4 - 1.0`	`-0.6`
Forward loss	$(-0.6)^2$	`0.36`
Backward gradient	$2 \times (-0.6) \times 2.0$	`-2.4`
Parameter update	$0.2 - 0.1 \times (-2.4)$	`0.44`

Backward stores the gradient and leaves the parameter at `0.2`. The update changes it to `0.44`. Recomputing afterward gives prediction `0.88`, error `-0.12`, and loss `0.0144`.

Return the original `(loss_value, grad_value)`, approximately `(0.36, -2.4)`. Separately, the caller's tensor now holds `0.44`. The returned loss describes the forward pass used to obtain that gradient; it is not the newly recomputed loss `0.0144`. This matches the pre-update logging convention in Lesson 03.03.

Why old gradients must be cleared

Backward adds contributions to a leaf tensor's existing `.grad`. Reusing a parameter across new forward calculations does not automatically clear this stored value. The official autograd tutorial demonstrates this accumulation.

Our function clears the gradient at the start of each step, because each update should use the derivative from its current forward computation. Assigning `None` to `w_tensor.grad` discards the old stored gradient; it does not zero or replace the parameter. Backward then stores the fresh result. This works even when `.grad` was already `None` on the first call.

Two calls on the same parameter illustrate the distinction:

```
First call:
    w_before = 0.2
    loss = 0.36
    gradient = -2.4
    w_after = 0.44

Second call, after clearing the old gradient:
    w_before = 0.44
    prediction = 0.88
    error = -0.12
    loss = 0.0144
    gradient = 2 * (-0.12) * 2.0 = -0.48
    w_after = 0.44 - 0.1 * (-0.48) = 0.488
```

If the second call omitted the reset, `.grad` would contain $-2.4 + (-0.48) = -2.88$. Updating with that accumulated value would give `0.728`, not `0.488`. Accumulation can be intentional when combining multiple batches, but that later technique needs its own scaling and update schedule. Here each call is one complete update, so clear old gradients first. Clearing at the start also lets the caller inspect the current gradient after the step.

Why the update uses `torch.no_grad()`

Change the parameter after backward

w = 0.2, x = 2, target = 1, learning_rate = 0.1

Step	Operation	State
1	w_tensor.grad = None	old gradient cleared
2	forward + backward	loss=.36; grad=−2.4
3	Read loss / .grad with .item()	save reporting values
4	`no_grad: update w_tensor`	w_{new}=.44

Only the parameter update is inside no_grad.

Figure 18: Read the numbered rows from top to bottom, keeping the old-state loss and gradient separate from the new parameter. Only the final in-place update belongs inside torch.no_grad().

Read the numbered rows from top to bottom, keeping the old-state loss and gradient separate from the new parameter. Only the final in-place update belongs inside torch.no_grad().

We need a differentiable forward computation to obtain $\frac{dL}{dw}$ at the current parameter. Once backward finishes, changing the parameter for the next step should not extend that computation's backward graph. Use `torch.no_grad()` only around the update. The autograd mechanics documentation explains this use for optimizer updates.

The new Python keyword `with` enters a temporary context for its indented block. For `torch.no_grad()`, operations inside that block are excluded from reverse-mode graph recording; leaving the block restores the prior gradient mode. The syntax in a function is:

```
with torch.no_grad():
    # Write the parameter update here, with eight spaces of indentation.
```

```
    ...
# Outside the block: return with four spaces of indentation.
```

The colon starts the block. `...` is an illustration placeholder, not the finished update. Existing `w_tensor.requires_grad` remains `True`; the temporary context does not permanently freeze the parameter. A later forward calculation outside the block can still record operations on it. Keep the forward pass and backward outside this context. See the no_grad API.

Trying the leaf parameter's in-place update in normal gradient mode raises a runtime error. The appropriate sequence here is forward, backward, then the parameter update inside the context. Advanced differentiation through an optimizer is a separate topic.

Update the parameter the caller holds

Unlike Lesson 03.05's function, this function receives an already-created tensor. The local name `w_tensor` refers to the same tensor object that the caller supplied. Its values must change in place so the caller and the next call see the updated parameter.

The operator `-=` means subtract and assign; for this tensor it performs an in-place subtraction. An isolated numeric syntax example is `counter -= 2`. In the exercise, subtract the learning-rate-scaled gradient from `w_tensor` inside the no-grad block. Ordinary `w_tensor = ...` assignment to a newly calculated tensor would rebind the local name rather than change the tensor the caller holds. Do not create a replacement parameter or use `.data` as a shortcut. Keep the original trainable leaf and its storage.

Classroom continuation: replace the `.data` update

The `.data` access shares the parameter's storage while bypassing normal autograd tracking; modifying it can evade modification checks and give incorrect gradients if another backward calculation needs the overwritten value. The official migration guide illustrates this issue. That earlier version's single-step numerical results passed because the update occurred after that step's backward calculation. Do not infer that every `.data` update necessarily produces a wrong number. Here, learn the explicit context already introduced for parameter updates.

`with torch.no_grad():` enters a temporary mode for its indented block; it is not a loop or a condition. The parameter's existing `requires_grad=True` remains unchanged, and its computed `.grad` stays stored. In-place updates retain normal modification bookkeeping while adding no update operations to the reverse graph. Leaving the block restores the prior mode, so the next forward pass can record operations again.

Use the same complete example before editing:

Moment	`w_tensor` value	Stored gradient	Return values being saved
After clearing old gradients	`0.2`	`None`	Not yet computed

Moment	`w_tensor` value	Stored gradient	Return values being saved
After forward and backward	`0.2`	`-2.4`	`(0.36, -2.4)`
After the no-grad update	`0.44`	`-2.4`	Still the original `(0.36, -2.4)`

The update formula stays `w_new = w - learning_rate * gradient`: $0.2 - 0.1 \times (-2.4) = 0.44$. The context changes how that update participates in autograd bookkeeping; it does not change the arithmetic.

1. Immediately above the existing update, enter `with torch.no_grad():` at four-space indentation. The parentheses call the context manager; the colon begins its block.
2. Indent the update to eight spaces. Update `w_tensor` directly with `-=`, removing `.data`; subtract the product of `learning_rate` and `w_tensor.grad`. Keep the original parameter object.
3. Keep the return at four spaces, outside the context. Return the already-saved `loss_value` and `grad_value`, then run the same exercise command. No new loop or replacement parameter is needed.

Classroom follow-up: only the update belongs in the context

A common mistake is to put `predicted_tensor`, `error`, `loss`, and `loss.backward()` inside `with torch.no_grad()`. Backward then stops with:

```
element 0 of tensors does not require grad and does not have a grad_fn
```

The context disables recording for the forward operations too, so this new `loss` has no recorded dependence on the parameter. Calling backward inside the same block cannot recover the missing forward graph. Merely moving backward out is insufficient if the forward calculation still takes place inside no-grad mode. The existing parameter's `requires_grad=True` does not force operations in this context to be recorded.

The intended order is: record the forward computation, differentiate that recorded computation, save the results, and then temporarily stop recording while updating the parameter. With `w_tensor=0.2`, `x=2.0`, and `target=1.0`, forward gives loss `0.36`; backward stores gradient `-2.4` while the parameter stays `0.2`. Only the update changes the parameter to `0.44` at learning rate `0.1`.

Correct the calculation as follows:

1. Keep gradient clearing, the forward calculations, `loss.backward()`, and extraction of `loss_value`/`grad_value` at four-space function indentation, outside the context.
2. Place `with torch.no_grad():` after those operations at four spaces; keep only the parameter update inside it at eight spaces. Its subtraction still uses `learning_rate` and `w_tensor.grad`.
3. Keep the return at four spaces outside the context, then run the same exercise command again.

Exact inputs, variables, return, and side effect

Follow this sequence: reset the stored gradient, calculate `predicted_tensor`, `error`, and `loss`, run backward, extract `loss_value` and `grad_value`, update `w_tensor` inside the no-grad block, then return the saved numbers. For the first example, the return is approximately `(0.36, -2.4)` while the caller's parameter becomes `0.44`. The next call starts at `0.44`, returns approximately `(0.0144, -0.48)`, and updates the same parameter to `0.488`. The supplied checks verified this sequence, persistent storage, fresh gradients, and a trainable leaf.

Name	Type	Meaning
`w_tensor`	Scalar floating-point `torch.Tensor`	Supplied trainable leaf with `requires_grad=True`; its stored gradient may be `None` or old data.
`x`	`float`	Fixed input multiplier.
`target`	`float`	Fixed desired prediction.
`learning_rate`	Nonnegative `float`	Multiplier determining the update size.
`predicted_tensor`, `error`, `loss`	Scalar `torch.Tensor`	Current forward computation, kept connected to the parameter.
`loss_value`, `grad_value`	`float`	Values extracted after backward, describing the parameter before the update.

Assume finite inputs and the stated tensor prerequisites; input validation is not part of this exercise. The supplied driver creates CPU `float64` parameters. Return exactly two Python floats `(loss_value, grad_value)`. The supplied parameter is updated in place, remains a trainable leaf, and retains this step's `.grad` until the next call clears it. A zero learning rate changes no parameter value even though backward still computes the gradient.

Guided implementation

Retain this full plan for reviewing or reconstructing the implementation. The imports, parameter setup, and checks are supplied. Use four spaces for statements in the function; only the update inside `with` uses eight.

1. **Reset the previous gradient.** Use attribute assignment, `object.attribute = value`, to put `None` in `w_tensor.grad`. The parameter stays `0.2` in the example.
2. **Calculate `predicted_tensor`.** Multiply `w_tensor` by `x` using `*` and save the tensor result. It holds `0.4`.
3. **Calculate `error` and `loss`.** Subtract `target` from the prediction, then square the error using `**2`. They hold `-0.6` and `0.36`. Preserve the tensor dependency.
4. **Run backward.** Call the `backward()` method on `loss`, once, outside the no-grad context. `w_tensor.grad` now holds `-2.4`; the parameter still holds `0.2`.

5. **Save the return values.** Use `.item()` on `loss` for `loss_value` and on `w_tensor.grad` for `grad_value`. These are Python floats from the original forward/backward calculation.
6. **Apply the update.** At four spaces, enter `with torch.no_grad():`. At eight spaces inside it, use `-=` on `w_tensor`, subtracting `learning_rate` multiplied by `w_tensor.grad`. The same tensor now holds `0.44`.
7. **Return outside the context.** At four spaces, return `loss_value`, then `grad_value`, using `return first, second`. The example returns approximately `(0.36, -2.4)`. Leave the current gradient stored.

No loop is needed in the exercise function: one call performs one step. The supplied driver calls it again on the same tensor to verify the next step.

Run and expected output

Activate the existing PyTorch environment, then run from the project root:

```
python exercises/03_06_tensor_gradient_step.py
```

The corrected implementation produced:

```
PASS: both gradient directions and in-place trainable parameters
PASS: repeated steps use current parameters and fresh gradients
PASS: previously stored gradients are cleared
PASS: zero gradients and zero learning rate
PASS: changed inputs, targets, and learning rates
PASS: a large learning rate can increase loss
Lesson 03.06 checks passed.
```

Keep forward/backward outside the no-grad update block. The examples below help diagnose mistakes. A leaf in-place error suggests the update lies outside the no-grad block. An incorrect second gradient suggests old gradients were retained. An unchanged caller parameter suggests local rebinding or an omitted update. A return of `0.0144` in the first example suggests returning a post-update loss instead of the required original loss. These checks also allow floating-point rounding.

Questions to work through

Optional review: why does clearing `.grad` leave the parameter unchanged? Why is the second step's fresh gradient `-0.48`? Why is only the update inside `no_grad`, and how does the caller observe the changed parameter? Continue with Lesson 03.07 to connect the verified update to a tensor training loop. Trainable embeddings follow.

03.07 A Tensor Training Loop

The scalar loop returned a new Python number after every step. The tensor step instead changes a persistent parameter in place. Our new loop must respect that interface: create the parameter once, let

the helper update it repeatedly, and record each returned loss without performing a second update.

Work through the example before editing 03_07_tensor_training_loop.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

The recurrence we will implement

Keep `x`, `target`, and `learning_rate` fixed. Let w_t be the parameter before update number t, with $w_0 =$ `initial_w`. For $t = 0, 1, \ldots,$ `num_steps` $- 1$:

```
w_0 = initial_w
prediction_t = w_t * x
error_t = prediction_t - target
loss_t = error_t ** 2
gradient_t = 2 * error_t * x
w_(t+1) = w_t - learning_rate * gradient_t
```

Each gradient is evaluated at the current parameter w_t, not at `initial_w` again. The parameter after one update is the starting parameter for the next. These equations describe repeated gradient descent; the helper obtains each gradient through autograd rather than a handwritten derivative in the loop.

The history and return are:

```
losses = [loss_0, loss_1, ..., loss_(num_steps-1)]
final_w = w_(num_steps)
return (final_w, losses)
```

For `num_steps=0`, the history is empty and the final parameter is the initial value. There are exactly `num_steps` recorded pre-update losses, with no extra post-training entry.

Principle: one persistent parameter, one step per iteration

Create `w_tensor` once before the loop. Its numerical value changes, while the same tensor object stays available to the following iteration. The completed helper is:

```
tensor_gradient_step(w_tensor, x, target, learning_rate)
    returns (loss_value, grad_value)
    updates the supplied w_tensor in place
```

The helper already clears old gradients, builds the current forward computation, runs backward, extracts the pre-update loss/gradient, and applies the update in its own no-grad block. The outer loop calls it once and appends its returned loss. Do not add a second backward call or update. Keep the outer loop in normal gradient mode so the helper's forward pass can record dependencies.

Each helper call performs new forward operations, creating the graph for that iteration. We retain the parameter tensor, not a previous `loss` tensor or backward graph. No `retain_graph=True` is needed in this task: do not repeatedly call backward on the same old loss. Gradient clearing happens inside the helper before each new backward pass.

Compare the helper interfaces:

Earlier scalar loop	This tensor loop
`gradient_step` returns `(loss, gradient, w_new)`	`tensor_gradient_step` returns `(loss_value, grad_value)`
The caller must keep the returned `w_new`	The passed `w_tensor` is already updated in place
The working parameter is a Python number	The working parameter is one trainable tensor

The two returned numbers do not include a new parameter. In this loop, `grad_value` is unpacked for clarity but does not need to be stored in the loss history. Do not replace `w_tensor` with the helper's return tuple.

Complete three-update example

Log the loss before each update

x = 2, target = 1, learning_rate = 0.1

step	w_{before}	**loss**	**gradient**	w_{after}
0	0.2	0.36	-2.4	0.44
1	0.44	0.0144	-0.48	0.488
2	0.488	0.000576	-0.096	0.4976

losses = [0.36, 0.0144, 0.000576]

Evaluate the final state separately: L(w_3) = 2.304e-05.

Figure 19: Each table row records one helper call on the same tensor, with its before/after values. The three loss entries are the returned old-state history; L_3 is evaluated separately in the footer.

Each table row records one helper call on the same tensor, with its before/after values. The three loss entries are the returned old-state history; L_3 is evaluated separately in the footer.

Use `initial_w=0.2`, `x=2.0`, `target=1.0`, `learning_rate=0.1`, and `num_steps=3`.

Before the loop, create one trainable `w_tensor` holding `0.2` and a fresh `losses=[]`.

Loop counter	Parameter before update	Prediction	Error	Pre-update loss	Gradient	Parameter after update
`0`	`0.2`	`0.4`	`-0.6`	`0.36`	`-2.4`	`0.44`
`1`	`0.44`	`0.88`	`-0.12`	`0.0144`	`-0.48`	`0.488`
`2`	`0.488`	`0.976`	`-0.024`	`0.000576`	`-0.096`	`0.4976`

For the first update, gradient $= 2 \times (-0.6) \times 2 = -2.4$ and $w_{\text{new}} = 0.2 - 0.1 \times (-2.4) = 0.44$. Save the returned loss `0.36`. The same parameter now holds `0.44`.

For the second, the helper uses `0.44`: `prediction=0.88`, `error=-0.12`, `loss=0.0144`, and gradient $= 2 \times (-0.12) \times 2 = -0.48$. It updates the parameter to $0.44 - 0.1 \times (-0.48) = 0.488$; append `0.0144`.

For the third, it uses `0.488`: `prediction=0.976`, `error=-0.024`, `loss=0.000576`, and `gradient=-0.096`. The parameter becomes `0.4976`; append `0.000576`.

The changing state is:

```
Before looping: w_tensor=0.2, losses=[]
After counter 0: w_tensor=0.44, losses=[0.36]
After counter 1: w_tensor=0.488, losses=[0.36, 0.0144]
After counter 2: w_tensor=0.4976, losses=[0.36, 0.0144, 0.000576]

Return approximately:
(0.4976, [0.36, 0.0144, 0.000576])
```

All values are subject to floating-point rounding. The comparison driver allows a small tolerance.

Why appending after the helper still records the old loss

The helper returns a Python float captured from the forward pass before its parameter update. By the time the call returns, `w_tensor` has changed, but `loss_value` still describes the parameter that produced that forward computation. Appending it after the call records the pre-update loss.

The loss at the final parameter is $(0.4976 \times 2 - 1)^2 = 0.00002304$. That is a separate evaluation at w_3; the requested three updates used and recorded L_0, L_1, and L_2. Do not append the final evaluation as a fourth entry. Later training systems can report final evaluations separately from update history.

Inputs, local variables, and returned values

Check that `w_tensor` and `losses` are initialized before `for i in range(num_steps)`. The loop body calls `tensor_gradient_step` once and appends `loss_value`; the final return extracts `w_tensor.item()` after the loop. Naming the counter `i` is valid: it receives `0, 1, 2` in the three-step example, just as the original hint's `step` did. The helper updates the tensor directly, so no returned `w_new` assignment is needed. `grad_value` is unpacked but unused because this task records only losses.

The checks observe the same tensor reaching the helper at `0.2`, `0.44`, and `0.488`; the result is approximately `(0.4976, [0.36, 0.0144, 0.000576])`. They also verify that zero steps return the initial

value and an empty list.

Name	Type	Meaning
`initial_w`	`float`	Parameter value before this training call.
`x`	`float`	Fixed input multiplier.
`target`	`float`	Fixed desired prediction.
`learning_rate`	Nonnegative `float`	Multiplier used in each parameter update.
`num_steps`	Nonnegative `int`	Number of requested updates.
`w_tensor`	Scalar `torch.Tensor`	One trainable parameter created with `float64` and `requires_grad=True` before the loop.
`losses`	`list[float]`	Fresh history with one pre-update loss per step.
`i`	`int`	Loop counter; it counts repetitions, not the parameter or learning rate.
`loss_value`, `grad_value`	`float`	Two numbers returned by the completed step helper.
`final_w`	`float`	Final parameter number extracted with `.item()`; a separate local variable with this name is optional.

Assume finite floating-point inputs and the stated nonnegative learning rate/step count; no input validation is required. Return a tuple `(final_w, losses)`, consisting of a Python float and a list of Python floats. Separate calls create separate parameter tensors and history lists. For zero updates, return `(initial_w, [])`.

The supplied `runpy.run_path` setup finds `03_06_tensor_gradient_step.py` beside the current exercise and loads the helper without running its check driver. Numbered filenames and the loading pattern match the existing exercises; the learner does not need to implement this setup.

Syntax and indentation before implementation

`torch.tensor(value, dtype=torch.float64, requires_grad=True)` creates the trainable scalar. Use `initial_w` as its value, and create it outside the loop. `[]` creates the fresh history list, also outside the loop.

The `for` keyword repeats a block. `range(num_steps)` supplies the counters: `range(3)` gives `0, 1, 2`, exactly three iterations, while `range(0)` supplies no counters and skips the body. The loop header's colon starts its indented body. Inside the function, setup and the loop header use four spaces; the helper call and append use eight.

Tuple unpacking binds two returned values in order, as in the unrelated syntax example `first, second = (10, 20)`. Here the first result is `loss_value` and the second is `grad_value`. `losses.`

`append(loss_value)` adds one loss float to the end of the list.

`return` exits the function. Place it after the loop at four spaces so all updates finish, and so the zero-step case still returns. Extract the final parameter with `w_tensor.item()`. If the return were inside the loop, it would exit after the first iteration and never execute when `num_steps=0`.

Guided implementation

Keep the supplied setup and checks; retain these six steps for reviewing or reconstructing the implementation:

1. **Create `w_tensor` once.** At four-space indentation, use the tensor constructor with `initial_w`, `torch.float64`, and `requires_grad=True`. The example starts at `0.2`. This stays before the loop.
2. **Create `losses`.** At four spaces, create a fresh empty list with `[]`. Its initial value is `[]` even when zero updates are requested.
3. **Start the loop.** At four spaces, use `for i in range(num_steps):`. With `num_steps=3`, the body runs for counters `0`, `1`, and `2`.
4. **Call the completed helper.** At eight spaces, call `tensor_gradient_step(w_tensor, x, target, learning_rate)` and unpack the two results into `loss_value` and `grad_value`. The first call returns approximately `(0.36, -2.4)` and already changes `w_tensor` to `0.44`. Do not assign a new parameter from those results.
5. **Record the loss.** At eight spaces, append only `loss_value` to `losses`. After two iterations, it is approximately `[0.36, 0.0144]`. No extra backward or update is needed in the loop.
6. **Return after the loop.** Back at four spaces, extract the final parameter with `.item()` and return that float followed by `losses`, using `return first, second`. The three-step result is approximately `(0.4976, [0.36, 0.0144, 0.000576])`; the zero-step result is `(initial_w, [])`.

Optional mathematical review: why this example's loss falls quickly

For this fixed scalar example, substitute the update into the next error:

```
error_(t+1)
    = x * (w_t - learning_rate * 2 * error_t * x) - target
    = (1 - 2 * learning_rate * x ** 2) * error_t

loss_(t+1) = (1 - 2 * learning_rate * x ** 2) ** 2 * loss_t
```

With `x=2` and `learning_rate=0.1`, the error multiplier is `0.2`, and the loss multiplier is `0.04`: $0.36 \to 0.0144 \to 0.000576$. For nonzero `x`, the error magnitude shrinks when $0 <$ `learning_rate` $< \frac{1}{x^2}$. This exact relationship is specific to the fixed scalar squared loss. With `x=0`, the parameter cannot affect the prediction; with learning rate zero, it does not move. Larger steps can increase the loss, so history must report the actual values rather than assuming improvement or stopping early.

Run and expected output

Activate the existing PyTorch environment and run from the repository root:

```
python exercises/03_07_tensor_training_loop.py
```

The example produces:

```
PASS: repeated tensor updates and pre-update loss history
PASS: zero and one update
PASS: requested step count and separate calls
PASS: supplied helper reuse and one persistent parameter tensor
PASS: changed inputs, targets, and learning rates
PASS: zero gradients and zero learning rate still record every step
PASS: large-step loss increases remain visible
Lesson 03.07 checks passed.
```

An incorrect history length can come from returning inside the loop or appending a final extra loss. Repeated first-step values can come from recreating the initial parameter in the loop. A loss without gradient history can come from wrapping the outer loop in no-grad mode. A tuple or tensor where a float is expected suggests appending the whole helper return or failing to extract the final parameter number.

Questions to work through

Optional review: why create the parameter and history before the loop? Why does the second helper call see `0.44` without assigning `w_new`? Why is the last history value `0.000576` instead of the final loss `0.00002304`? Why can zero steps still return?

Continue with Lesson 03.08: trainable embeddings. A minimal next-token objective follows that assignment.

03.08 Trainable Embeddings

Method sources

Embedding learning in neural language models is motivated by Bengio et al., 2003; R24, while the gradient mechanics here follow PyTorch, v2.0 autograd; R16. Repeated lookup indices sum their gradient contributions; this toy loss is not a reproduction of the cited model.

We are ready to move from one trainable number to an entire embedding table. Lookup chooses which rows affect the loss, and backward routes derivatives to those rows. A deliberately supplied target vector makes this mechanism visible; later, next-token prediction will provide the learning signal instead.

Work through the example before editing 03_08_embedding_gradient_step.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver

remain separate.

From one scalar parameter to a table of parameters

In Lesson 03.06, one floating-point number `w_tensor` was the parameter. Here every floating-point entry of `embedding_table` is a parameter. A table with V rows and D columns therefore contains VD trainable numbers. Lookup selects some of them for the current loss; it does not reduce the table to the selected rows.

The mechanism remains the same: calculate the loss from the current parameters, differentiate that loss with respect to the parameters, then update those parameters. Integer token IDs choose rows. The floating-point values in the rows are what learning changes.

Symbols, shapes, and how to read the indices

We use the following symbols throughout the formulas and code:

Symbol	Exact code name	Meaning	Shape or range
E	`embedding_table`	Trainable floating-point lookup table	`[V, D]`
V	Table row count	Vocabulary size	Positive integer
D	Table column count	Number of components in each embedding vector	Positive integer
T	Input length	Number of token positions in this call	Positive integer
i_t	`token_ids[t]`	ID at input position t	Integer from `0` to $V - 1$
Z	`selected_vectors`	Vectors selected in input order	`[T, D]`
Y	`target_vectors`	Fixed target vectors for this teaching objective	`[T, D]`
e	`errors`	Componentwise prediction minus target	`[T, D]`
L	`loss_value` before `.item()`	One scalar measuring the current error	Scalar tensor
G	`embedding_table.grad` after backward	Loss derivative for every table entry	`[V, D]`
η	`learning_rate`	Update multiplier	Nonnegative float

The table is a real-valued matrix, written $E \in \mathbb{R}^{V \times D}$ in mathematics and stored as a floating-point tensor in the exercise. V comes from the tokenizer vocabulary and can exceed 256. D counts components; it does not bound their values. A vector can contain negative numbers or values larger than one.

All indices start at zero, matching Python. t runs from `0` to $T - 1$ over input positions; r runs from `0` to $V - 1$ over table rows; d runs from `0` to $D - 1$ over vector components. A subscript $E_{r,d}$ means the same entry as `embedding_table[r, d]`.

Distinguish an input position from a table row. For `token_ids=[0,2]`, input position `t=1` contains ID `2`, so it reads table row `r=2`. Repeated IDs can make several input positions read the same row.

During differentiation, the IDs, targets, and dimensions are fixed. We ask how the loss changes when a floating-point table entry changes. We do not differentiate the integer row addresses.

Lookup, loss, gradient, and update

1. Lookup chooses a source row

$$Z_{t,d} = E_{i_t,d}$$

Read this as: component d at input position t equals component d in the row named by that position's token ID. The code operation is `embedding_table[token_ids]`. It produces `[T,D]` while the parameter table remains `[V,D]`.

2. Error and mean squared loss

$$e_{t,d} = Z_{t,d} - Y_{t,d}$$

$$L = \frac{1}{TD} \sum_{t=0}^{T-1} \sum_{d=0}^{D-1} \left(Z_{t,d} - Y_{t,d}\right)^2$$

The two sums visit every input position and every vector component. Compute each component's deviation, square it, add the squares, then divide by the number of selected components, TD. For two positions and two components, the divisor is four. The vocabulary size V is not the divisor because the loss is formed from the selected output, not all vocabulary rows.

The matching tensor operations are elementwise subtraction, `** 2`, and `.mean()` without a dimension argument. That mean turns all `[T,D]` squared errors into one scalar. This is the all-element mean described by the MSELoss documentation.

3. Derive the gradient of one selected component

First treat the entries of the selected output Z as separate variables. For one chosen entry $Z_{t,d}$, all the other squared-error terms are constant with respect to that entry. Its target $Y_{t,d}$ and divisor TD are also fixed. Applying the square derivative and chain rule gives:

$$\frac{\partial L}{\partial Z_{t,d}} = \frac{1}{TD} \cdot 2\left(Z_{t,d} - Y_{t,d}\right) \cdot 1 = \frac{2e_{t,d}}{TD}$$

The final factor `1` comes from the derivative of $Z_{t,d} - Y_{t,d}$ with respect to $Z_{t,d}$. The symbol ∂ means a partial derivative: change this one component while keeping the other selected components fixed. The result describes the local loss change per small increase in that component.

For error `1` with four total components, the derivative is $2 \times 1/4 = 0.5$. For error `2`, it is $2 \times 2/4 = 1.0$. This is the gradient of the selected output; we still need to send it to the table parameters that produced that output.

4. Use the chain rule to route gradients back to the table

For a fixed component d, lookup has the local derivative:

$$\frac{\partial Z_{t,d}}{\partial E_{r,d}} = \begin{cases} 1, & i_t = r, \\ 0, & i_t \neq r. \end{cases}$$

If position t reads row r, increasing that table entry by a small amount increases the selected component by the same amount: derivative `1`. If it reads another row, that selected component does not change: derivative `0`. Different vector components also have no cross-dependence in lookup.

The parameter gradient adds contributions from every position that depends on it:

$$\begin{aligned} G_{r,d} &= \frac{\partial L}{\partial E_{r,d}} \\ &= \sum_{t=0}^{T-1} \frac{\partial L}{\partial Z_{t,d}} \frac{\partial Z_{t,d}}{\partial E_{r,d}} \\ &= \frac{2}{TD} \sum_{\substack{0 \le t < T \\ i_t = r}} (E_{r,d} - Y_{t,d}) \end{aligned}$$

The last sum includes only positions whose ID equals row r. If no position reads that row, there are no contributions and its gradient is zero. If several positions read it, their contributions add to the same parameter. A selected row can also have zero gradient when errors vanish or opposing contributions cancel.

G has shape `[V,D]` because there is one derivative per table parameter. The selected-output gradient has shape `[T,D]`. Keeping these two shapes distinct explains why backward returns a full table gradient even when the input reads only two rows.

5. Update every table component

$$E_{\text{new}} = E - \eta G$$

Equivalently, for each table entry:

$$(E_{\text{new}})_{r,d} = E_{r,d} - \eta G_{r,d}$$

A positive gradient makes the update decrease that entry; a negative gradient makes it increase. A zero gradient leaves it unchanged. This is the same gradient-descent rule as in Lesson 03.06, applied to all entries. A sufficiently large step can still increase loss; the rule does not guarantee improvement for every learning rate.

These zero-gradient statements concern this lookup-only objective with plain gradient descent. Later objectives can introduce other paths to table parameters. In the exercise function, `loss_value.backward()` performs the derivatives and routing; the formulas explain the mechanism, rather than requiring a manual gradient implementation.

Complete small example: every forward and backward step




Figure 20: The three matrices compare the full table, its gradient and its update. The footer gives a separate repeated-ID example with zero targets.

The three matrices compare the full table, its gradient and its update. The footer gives a separate `[0, 0]` example with zero targets: two normalized contributions accumulate into row 0.

Start with:

$$E = \begin{bmatrix} 1 & 2 \\ 3 & 4 \\ 5 & 6 \end{bmatrix}$$

$$\text{token_ids} = [0, 2]$$

$$Y = \begin{bmatrix} 0 & 0 \\ 4 & 4 \end{bmatrix}$$

$$\eta = 0.1$$

For comparison with the exercise, the same inputs in plain text are:

```
embedding_table E =
    row 0: [1.0, 2.0]
    row 1: [3.0, 4.0]
    row 2: [5.0, 6.0]

token_ids = [0, 2]
target_vectors Y = [[0.0, 0.0], [4.0, 4.0]]
learning_rate = 0.1
```

Here $V = 3$, $D = 2$, $T = 2$, and $TD = 4$. The three hypothetical token IDs are `0`, `1`, and `2`; this tiny vocabulary is only for hand calculation.

Step 1: Select the rows in input order

Position `t=0` has ID `0`, so it reads `[1,2]`. Position `t=1` has ID `2`, so it reads `[5,6]`:

$$Z = \begin{bmatrix} 1 & 2 \\ 5 & 6 \end{bmatrix}$$

The table shape is `[3,2]`, and the selected-output shape is `[2,2]`. Table row `1` still exists even though this call does not read it.

Step 2: Subtract targets and square each error

$$e = Z - Y = \begin{bmatrix} 1-0 & 2-0 \\ 5-4 & 6-4 \end{bmatrix} = \begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix}$$

The operation `errors ** 2` squares each entry separately. It is not matrix multiplication:

$$\text{squared errors} = \begin{bmatrix} 1^2 & 2^2 \\ 1^2 & 2^2 \end{bmatrix} = \begin{bmatrix} 1 & 4 \\ 1 & 4 \end{bmatrix}$$

Step 3: Average all four squared errors

$$L = \frac{1 + 4 + 1 + 4}{2 \times 2} = \frac{10}{4} = 2.5$$

The scalar `loss_value` is `2.5`. Using a sum would give `10`; dividing only by the two token positions would give `5`. Both would describe a different objective from this assignment's mean over all components.

Step 4: Differentiate the selected output

Apply $2e_{t,d}/4$ to every component:

$$\frac{\partial L}{\partial Z} = \begin{bmatrix} 2 \times 1/4 & 2 \times 2/4 \\ 2 \times 1/4 & 2 \times 2/4 \end{bmatrix} = \begin{bmatrix} 0.5 & 1 \\ 0.5 & 1 \end{bmatrix}$$

The following trace keeps the position, source row, error, and contribution separate:

Position t	Component d	Source row `token_ids[t]`	Selected value	Target	Error	Contribution `2*error/4`
`0`	`0`	`0`	`1`	`0`	`1`	`0.5`
`0`	`1`	`0`	`2`	`0`	`2`	`1.0`
`1`	`0`	`2`	`5`	`4`	`1`	`0.5`
`1`	`1`	`2`	`6`	`4`	`2`	`1.0`

Step 5: Send those contributions to the original table

Position `0` sends `[0.5,1.0]` to table row `0`; position `1` sends `[0.5,1.0]` to table row `2`. Table row `1` receives no contribution:

$$G = \frac{\partial L}{\partial E} = \begin{bmatrix} 0.5 & 1 \\ 0 & 0 \\ 0.5 & 1 \end{bmatrix}$$

You can also write the loss directly in terms of table entries to see why:

$$L(E) = \frac{1}{4}\left[(E_{0,0} - 0)^2 + (E_{0,1} - 0)^2 + (E_{2,0} - 4)^2 + (E_{2,1} - 4)^2\right]$$

Neither $E_{1,0}$ nor $E_{1,1}$ appears. Changing either of them leaves this loss unchanged, so both derivatives are zero. `loss_value.backward()` stores this full `[3,2]` tensor in `embedding_table.grad`.

Step 6: Subtract the scaled gradient from the table

$$E_{\text{new}} = \begin{bmatrix} 1 & 2 \\ 3 & 4 \\ 5 & 6 \end{bmatrix} - 0.1 \begin{bmatrix} 0.5 & 1 \\ 0 & 0 \\ 0.5 & 1 \end{bmatrix} = \begin{bmatrix} 0.95 & 1.9 \\ 3 & 4 \\ 4.95 & 5.9 \end{bmatrix}$$

Table row	Original values	Gradient	Updated values
`0`	`[1.0, 2.0]`	`[0.5, 1.0]`	`[0.95, 1.9]`
`1`	`[3.0, 4.0]`	`[0.0, 0.0]`	`[3.0, 4.0]`
`2`	`[5.0, 6.0]`	`[0.5, 1.0]`	`[4.95, 5.9]`

For the first entry, $1.0 - 0.1 \times 0.5 = 0.95$. For its second component, $2.0 - 0.1 \times 1.0 = 1.9$. Row `1` subtracts zero, and row `2` uses the same component gradients as row `0`. The table keeps shape `[3,2]`, and the IDs remain `[0,2]`.

Step 7: Distinguish returned values from updated parameters

The function returns the pre-update loss `2.5` and the full gradient snapshot shown above. Its side effect is to update the supplied table in place. Those returned values describe the calculation that produced the update.

If you subsequently run a new lookup and evaluate the updated table, the errors are `[0.95,1.9]` at both positions, giving:

$$L(E_{\text{new}}) = \frac{0.95^2 + 1.9^2 + 0.95^2 + 1.9^2}{4} = 2.25625$$

This re-evaluation is a new calculation. It does not change the returned Python loss value `2.5` or its copied gradient snapshot.

Repeated IDs: two positions, one shared row

Start again from the original table. Change the input and targets to:

$$\text{token_ids} = [0, 0], \qquad Y = \begin{bmatrix} 0 & 0 \\ 0 & 0 \end{bmatrix}$$

Both positions read the same parameter row `[1,2]`. Therefore:

$$Z = \begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix}$$
$$e = \begin{bmatrix} 1 & 2 \\ 1 & 2 \end{bmatrix}$$
$$L = \frac{1+4+1+4}{4} = 2.5$$

With four selected components, each position contributes `[0.5,1.0]`. The lookup chain rule sends both contributions to row `0`:

$$G_{0,:} = [0.5, 1.0] + [0.5, 1.0] = [1.0, 2.0]$$

Here the colon in `G[0, :]` means all components of row `0`. The full gradient and update are:

$$G = \begin{bmatrix} 1 & 2 \\ 0 & 0 \\ 0 & 0 \end{bmatrix}, \qquad E_{\text{new}} = \begin{bmatrix} 0.9 & 1.8 \\ 3 & 4 \\ 5 & 6 \end{bmatrix}$$

The row is shared. Backward adds both contributions; it does not create a separate parameter row for each occurrence. Only row `0` changes in this example.

Why repeating inputs does not always multiply the final gradient

Keep the mean denominator in the calculation. Compare these two calls, each starting from row `[1,2]` with zero targets:

Input	Number of selected components	Contribution from each position	Total row-0 gradient
`[0]`	$1 \times 2 = 2$	$[2 \times 1/2, 2 \times 2/2] = [1, 2]$	`[1,2]`
`[0,0]`	$2 \times 2 = 4$	$[2{\times}1/4, 2{\times}2/4] = [0.5, 1]$	$[0.5, 1] + [0.5, 1] = [1, 2]$

The two half-sized contributions give the same final gradient. The earlier comparison between `[0, 2]` and `[0,0]` held $T = 2$ fixed and changed which rows received the contributions. Always account for both the number of paths and the loss normalization.

Contributions can also cancel. With IDs `[0,0]`, row `[1,2]`, and targets `[0,0]` at the first position and `[2,4]` at the second, the errors are `[1,2]` and `[-1,-2]`. Their row contributions `[0.5,1]` and `[-0.5,-1]` sum to zero. A selected row is therefore not guaranteed a nonzero gradient.

Tensor operations and new syntax

`embedding_table[token_ids]` selects rows in order, preserving repetitions, and keeps a differentiable connection to the floating-point table. This replaces the Python-list representation of the earlier lookup

exercise. Keep `selected_vectors` as a tensor; converting it to ordinary numbers and reconstructing a new tensor would lose the original dependency.

Subtracting matching-shape tensors and applying `** 2` act element by element. `.mean()` without a dimension argument averages every element into a scalar. It is not just the sum, and its denominator is neither V nor T alone. The table's gradient after backward has shape `[V,D]`, not the selected output's `[T,D]`.

`.item()` extracts the scalar loss as a Python float. A multi-element gradient matrix cannot be extracted with one `.item()`. Keep the returned `gradient_table` as a tensor.

`.clone()` makes a tensor copy with independent storage. Copy `embedding_table.grad` after ordinary backward so later changes to the stored gradient do not change the returned snapshot. The gradient buffer here already has `requires_grad=False`; cloning itself is not a general way to turn off differentiation. See the clone documentation.

The update uses `with torch.no_grad():` exactly as in Lesson 03.06. Forward and backward stay outside it. Inside, subtract the scaled full table gradient from `embedding_table` itself, not from the selected output. Keep the original trainable leaf and leave the current gradient stored for inspection; the next call resets it.

Connect the mathematics to the tensor operations

The supplied table is a trainable leaf: it is the original parameter tensor, rather than the result of a calculation from other tracked tensors. Lookup produces a new result connected to that parameter. In normal gradient mode, PyTorch records the dependence through lookup, subtraction, squaring, and averaging:

$$E \longrightarrow Z \longrightarrow e \longrightarrow L$$

Backward follows those dependencies in reverse, computes the derivatives, and stores the parameter gradient in `embedding_table.grad`. Calling backward does not update the parameter values. The explicit update is a separate step.

Mathematics or purpose	Tensor operation	Expected result in the example
$Z_{t,d} = E_{i_t,d}$	`embedding_table[token_ids]`	Selected values `[[1,2],[5,6]]`, `[T, D]`
$e = Z - Y$	Subtract `target_vectors` from `selected_vectors`	Errors `[[1,2],[1,2]]`
Square each error	`errors ** 2`	`[[1,4],[1,4]]`
Mean over TD components	`.mean()` on the squared errors	Scalar tensor `2.5`
$G = \partial L / \partial E$	`loss_value.backward()`	Full gradient stored in the table's `.grad`
Save scalar loss for return	`loss_value.item()`	Python float `2.5`

Mathematics or purpose	Tensor operation	Expected result in the example
Save an independent gradient snapshot	`.clone()` on the table's `.grad`	A separate `[V,D]` gradient tensor
$E_{\text{new}} = E - \eta G$	In-place subtraction on the table inside `torch.no_grad()`	Updated parameter table

Keep the tensor `loss_value` available for backward. A Python float obtained by `.item()` has no recorded tensor dependency through which backward can reach the table. Extracting the final return value after backward leaves the earlier computation intact.

Directly assigning the stored gradient to another name gives both names the same tensor. If that tensor is later modified in place, both names see the change. `.clone()` gives the returned snapshot separate storage. Resetting `.grad` to `None` is a different operation: it removes the table's reference to its old gradient buffer; it does not change the table's parameter values. Ordinary backward adds into any existing gradient buffer, which is why each independent step starts with the reset.

The selected output is a calculation result. Updating that result does not perform this exercise's parameter-table update. Apply the full `[V,D]` gradient to `embedding_table` itself.

Forward and backward need the recorded dependency; parameter updating is performed inside a temporary `with torch.no_grad():` context. `with` enters that context for its indented block and restores the previous gradient mode afterward. The indentation pattern is:

```
with torch.no_grad():
    ...  # Update the original table here: eight spaces.
...  # Return outside the context: four spaces.
```

This fragment shows the block structure, not the assignment solution. The seven implementation steps below explain where each operation belongs.

Exact inputs, variables, and return

Name	Type and shape	Meaning
`embedding_table`	Floating-point `torch.Tensor`, `[V,D]`	Supplied trainable leaf with `requires_grad=True`; update it in place.
`token_ids`	Integer `torch.Tensor`, `[T]`, `torch.long`	Valid indices selecting table rows; not trainable.
`target_vectors`	Fixed floating-point `torch.Tensor`, `[T,D]`	Supplied desired output vectors for this teaching loss, same dtype/device as the table.
`learning_rate`	Nonnegative `float`	Update multiplier.
`selected_vectors`, `errors`	Floating-point `torch.Tensor`, `[T,D]`	Connected lookup result and componentwise deviations.

Name	Type and shape	Meaning
`loss_value` before `.item()`	Scalar `torch.Tensor`	Mean of all selected squared deviations.
`loss_value` after `.item()`	`float`	Extracted pre-update loss.
`gradient_table`	Floating-point `torch.Tensor`, `[V,D]`	Independent copy of the current loss derivative with respect to the table.

Assume finite values, valid IDs, $V > 0$, $D > 0$, $T > 0$, fixed targets with `requires_grad=False`, and normal gradient mode. No validation or constructor work is required in the exercise function. An empty lookup can exist, but this mean-loss assignment requires at least one selected component; there is no empty-training case. Supplied checks use CPU `float64` table/target tensors and `torch.long` IDs.

Return `(loss_value, gradient_table)`. Both describe the table before updating; the passed table now holds updated values and remains a trainable leaf. The IDs and target vectors keep their values. The gradient return is a snapshot, not a replacement parameter table.

Guided implementation

Use these seven steps to implement `embedding_gradient_step` in `03_08_embedding_gradient_step.py`. The input tensors and check driver are supplied. Ordinary function statements use four spaces; only the update inside the context uses eight. The example names the deviations `errors` and uses `loss_value` first for the loss tensor, then for the extracted float.

1. **Clear the old gradient.** At four spaces, assign `None` to `embedding_table.grad`, using attribute assignment `object.attribute = value`. The original table values stay unchanged. This makes the next backward calculate the current step gradient without adding the previous step's gradient.
2. **Look up `selected_vectors`.** At four spaces, use `embedding_table[token_ids]` and save the result as `selected_vectors`. Bracket indexing selects whole rows in order; a tensor of integer indices can select several rows at once and retain repeats. The example result is `[[1,2],[5,6]]`, shape `[2,2]`. Keep this connected tensor for the loss calculation.
3. **Calculate `errors` and `loss_value`.** Keep both statements at four spaces. Subtract `target_vectors` from `selected_vectors` to form `errors`, square each element with `** 2`, and use `.mean()` without a dimension argument to form `loss_value`. Parentheses group the squared-error expression before its mean. The error is `[[1,2],[1,2]]`, the squares are `[[1,4],[1,4]]`, and the scalar loss is `2.5`.
4. **Run backward once.** At four spaces, call `loss_value.backward()`, using method-call syntax `object.method()`. Keep this outside no-grad mode. The stored `embedding_table.grad` is `[[0.5,1],[0,0],[0.5,1]]`, shape `[3,2]`. This operation calculates and stores gradients; the table has not yet been updated.
5. **Save the return values.** At four spaces, copy `embedding_table.grad` with `.clone()` into `gradient_table`, then extract the scalar loss with `.item()` and reassign `loss_value` to that float. Expect a `[3,2]` gradient tensor and Python float `2.5`. A multi-element matrix cannot use one `.item()`. The clone gives the saved gradient independent storage.

6. **Update the table in place.** At four spaces, enter `with torch.no_grad():`. At eight spaces, use `-=` on `embedding_table`, subtracting `learning_rate` times `embedding_table.grad`. In the example, row `0` becomes `[0.95,1.9]` and row `1` stays `[3,4]`.
7. **Return outside the context.** Return to four spaces and use `return first, second`. Return `loss_value` first and `gradient_table.detach()` second; `.detach()` returns a tensor without an autograd connection. It is valid but unnecessary here because ordinary backward already produced an untracked gradient, and `.clone()` already gave the snapshot independent storage. Commas form the two-item return that the caller can unpack. The loss is `2.5`, and the gradient snapshot still describes the original table. The passed table has already changed in place, so it does not need to be a third return value.

No learner loop is needed: indexing and arithmetic act on tensors together. You write the core; hints are not a completed function.

Run and expected output

Activate the existing PyTorch environment, then run from the repository root:

```
python exercises/03_08_embedding_gradient_step.py
```

After completing the implementation, expect:

```
PASS: indexed lookup, mean loss, table gradients, and untouched rows
PASS: repeated token positions add gradient contributions to one row
PASS: different vector dimensions and vocabulary IDs above 255
PASS: zero loss and zero learning rate
PASS: old gradients are cleared and repeated steps use the updated table
PASS: returned gradient snapshots have independent storage
PASS: full table gradients agree with finite differences
Lesson 03.08 checks passed.
```

A loss of `10` in the first example indicates summing rather than averaging the four squared errors. A missing repeated-row contribution suggests overwriting contributions or breaking the lookup dependency. An unchanged table can come from updating only the selected output. A changed old gradient snapshot suggests returning an alias instead of a copy. Keep the supplied inputs and driver unchanged.

Questions to work through

Optional review: distinguish table, selected-output, and gradient shapes; explain the TD denominator; explain why an unselected row has zero gradient in this objective; trace repeated-ID contributions including normalization; distinguish token IDs from trainable values; explain why the gradient snapshot is cloned. This teaching loss verifies lookup gradients. Continue with Lesson 03.09: logits and softmax, then the planned next-token loss.

03.09 Logits and Softmax

An embedding vector is not yet a prediction over tokens. We need an output projection that scores every vocabulary candidate, followed by a rule for turning those scores into probabilities. This gives each input position its own distribution while keeping vector width, sequence length, and vocabulary size distinct.

Work through the example before editing 03_09_logits_and_softmax.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

Where logits fit in a language model

A tokenizer supplies token IDs. Embedding lookup supplies floating-point vectors. A language model processes the input to produce a vector at each position, then an output projection scores every candidate vocabulary token. Softmax converts one position's scores into probabilities.

```
input token IDs -> embedding vectors -> position vectors [T,D]
               -> vocabulary logits [T,V] -> probabilities [T,V]
```

Here `hidden_vectors` contains supplied position vectors. In a minimal model these can come straight from lookup. A Transformer later uses contextual processing before the output projection. This exercise implements the projection and probability conversion; it does not yet implement attention or a full language model.

In next-token prediction, probability column v corresponds to vocabulary ID v. A row represents the candidate distribution for the next token at that position. The toy vocabulary below has three hypothetical IDs, `0`, `1`, and `2`; they are not a complete byte tokenizer.

A logit is a real-valued score before softmax. It can be negative, zero, or positive. It need not lie between zero and one, and a row of logits need not sum to one. A higher score gives a higher softmax probability within that same row. The input vector has D components; the output has V candidate scores. D and V count different things and need not match.

The example weights are chosen for arithmetic, not learned from data. A probability from this untrained toy head is an output of that calculation; it does not establish useful language-model capability.

What does the input-position count T mean?

What does an input position mean, and why can there be several? For the single sequence discussed here, a position is one slot in the tokenized input. T counts how many token occurrences the input contains. A text prompt usually contains several tokens, so it has several positions.

Conceptually:

$$T = \text{len}(\text{token_ids})$$

The current `compute_logits` function receives vectors rather than IDs. Each row of `hidden_`

`vectors` represents one of those positions, so its T is `hidden_vectors.shape[0]`. No extra `token_ids` parameter is being added to the exercise. This lesson uses one sequence; a separate batch dimension for multiple sequences comes later.

A concrete token sequence

For illustration, assume a tokenizer splits the text 我爱猫 into the three tokens 我, 爱, and 猫:

Zero-based position	Token occupying that position
`0`	我
`1`	爱
`2`	猫

There are three occupied positions, so $T = 3$. This one-character-per-token split is an explicit teaching assumption, not a claim about the existing byte/BPE tokenizer. Actual token boundaries depend on the tokenizer. Count the resulting tokens, not the original characters. For example, the earlier sequence `[256,97,256]` also has $T = 3$, even though there are only two distinct IDs; the repeated ID occupies another position.

Each position gets one vector. If the vector dimension is $D = 8$, the shapes are:

```
position 0 -> one 8-component vector
position 1 -> one 8-component vector
position 2 -> one 8-component vector

hidden_vectors: [3,8]
logits:         [3,V]
probabilities:  [3,V]
```

T counts the input occurrences, D counts components of each vector, and V counts all vocabulary candidates. The vocabulary size need not equal three. If a separate toy vocabulary contained exactly 我, 爱, 猫, and 。, it would have $V = 4$, giving probabilities `[3,4]`: three input positions, four candidates per position.

The existing numeric example in this lesson has `hidden_vectors=[[1,2],[2,1]]`. That is two vectors, one per position, so $T = 2$ and $D = 2$. The first vector is `[1,2]`; the second is `[2,1]`. Its logits have shape `[2,3]` because that example's vocabulary has three candidates. The text illustration above is a different example and does not replace those exercise inputs.

Why training can return a prediction row at every position

Assume the full training sequence is 我, 爱, 猫, 。. The earlier shifted-window idea uses:

```
input tokens:  [我, 爱, 猫]
target tokens: [爱, 猫, 。]
```

In a causal next-token model, the intended alignment is:

Position	Context permitted at that position	Next-token target during training
`0`	我	爱
`1`	我爱	猫
`2`	我爱猫	。

The three output rows predict the next token after three different available prefixes. Their targets are already known in the training data, so training can calculate several next-token predictions and losses in one forward pass. A causal model must prevent an earlier position from seeing later tokens in the input; otherwise it could read its answer. Causal masking and attention are later topics.

In a contextual model, a hidden vector can represent the permitted prefix up to its position. In this exercise, `hidden_vectors` is supplied and the projection processes each row independently; it does not itself combine earlier tokens or enforce a causal mask. The exercise learns the final vector-to-scores-to-probabilities mechanism. Context processing is not yet implemented.

How this relates to generating one next token

When the current prompt tokenizes to 我, 爱, 猫, it already has three input positions. For next-token generation, use the distribution at the final input position to select the next token. If the selected token is 。, appending it gives four positions; a later generation step predicts what follows that longer prefix.

Several input positions therefore describe the context already supplied. They do not make the next-token generation step produce several unknown future tokens at once. If probabilities are calculated for all positions, the earlier rows concern shorter prefixes; the final row concerns the full current prefix. T is an input-length count, not the number of future tokens selected in one generation step.

Symbols, exact code names, and shapes

Symbol	Code name	Meaning	Shape or range
H	`hidden_vectors`	Supplied floating-point vector at each position	`[T,D]`
W	`output_weights`	Weights connecting vector components to candidate scores	`[D,V]`
b	`output_bias`	One added score offset per vocabulary token	`[V]`
Z	`logits`	Scores for all candidate tokens at all positions	`[T,V]`
P	`probabilities`	Softmax probability distribution at each position	`[T,V]`
T	Position count	Number of input vectors in this call	Positive integer

Symbol	Code name	Meaning	Shape or range
D	Vector dimension	Number of components per input vector	Positive integer
V	Vocabulary size	Number of candidate token IDs	Positive integer
t, d, v	Formula indices	Position, vector component, vocabulary candidate	Zero-based
m_t	`row_max[t,0]`	Maximum score at position t	`row_max` is `[T,1]`

Indices start at zero: $0 \leq t < T$, $0 \leq d < D$, and $0 \leq v < V$. The subscript $Z_{t,v}$ means `logits[t, v]`. In this lesson Z denotes logits; Lesson 03.08's selected embedding vectors can supply this lesson's H.

Assume finite floating-point inputs, $T > 0$, $D > 0$, $V > 0$, matching shapes, matching dtype/device, and normal gradient mode. The supplied driver uses CPU `float64`. Inputs may require gradients. No tensor construction or input-validation logic is assigned to the learner. Empty rows and nonfinite inputs are outside this exercise's contract.

From a vector to vocabulary scores




Figure 21: Read one row of H against one column of W. Their two products sum to one candidate score; changing D into V changes columns, while the two input positions remain two rows.

Read one row of H against one column of W. Their two products sum to one candidate score; changing D into V changes columns, while the two input positions remain two rows.

For each position and candidate token:

$$Z_{t,v} = \sum_{d=0}^{D-1} H_{t,d} W_{d,v} + b_v$$

Read one candidate score as follows: multiply each input component by the corresponding weight for that candidate, add those products, then add the candidate's bias. W has one column per candidate. Column v contains the D weights used to score candidate v.

The matrix form is:

$$Z = HW + b$$

The shape calculation is:

$$[T, D] \mathbin{@} [D, V] \longrightarrow [T, V]$$

The inner sizes D must match. The outer sizes give T rows and V columns. Python's `@` performs this matrix product for two-dimensional tensors; the matrix-product documentation explains its shape behavior. $*$ is elementwise multiplication and does not calculate these row-column weighted sums.

Adding bias `[V]` to scores `[T,V]` applies the same bias vector to every row. Conceptually `[V]` aligns as `[1,V]` and broadcasts across T. This follows the broadcasting rules; it does not require a learner loop or manually copied bias matrix.

W and `b` can be trained along with the embedding table in a later loss-based training loop. Softmax itself has no learned parameters. This exercise returns logits while keeping their dependence on the supplied vectors, weights, and bias.

From scores to probabilities

At position t, softmax is:

$$P_{t,v} = \frac{e^{Z_{t,v}}}{\sum_{j=0}^{V-1} e^{Z_{t,j}}}$$

Here $e \approx 2.71828$ is Euler's number, the base of natural logarithms, and $e^x = \exp(x)$ is the exponential function. This `e` is not Lesson 03.08's error variable. j visits all vocabulary candidates in the same row, and v denotes the particular candidate whose probability we want.

The exponential turns any finite real score into a positive weight and preserves score ordering. Dividing by the sum of those weights normalizes the row:

$$\sum_{v=0}^{V-1} P_{t,v} = \frac{\sum_{v=0}^{V-1} e^{Z_{t,v}}}{\sum_{j=0}^{V-1} e^{Z_{t,j}}} = 1$$

For a finite real row with $V > 1$, mathematical probabilities are strictly between zero and one. With $V = 1$, the only probability is one. Floating-point calculations can underflow tiny probabilities to zero, so numerical checks allow the closed interval `[0,1]` and a tolerance when checking the row sum. The official softmax documentation defines the normalization along a chosen dimension.

The denominator belongs to one position's V candidates. It does not combine probabilities across the T positions. Every output row sums to one independently; the sum of the entire `[T,V]` output is consequently T.

Softmax preserves score ordering. For two candidates in one row:

$$\frac{P_{t,a}}{P_{t,b}} = e^{Z_{t,a} - Z_{t,b}}$$

A score gap of one gives a probability ratio of approximately `2.71828`. The relative differences matter. Equal logits give equal probabilities, including when the common score is negative.

Softmax calculates the distribution. Selecting a token is a subsequent operation: a greedy rule chooses a largest-probability candidate, while sampling can choose according to the distribution. Neither is performed inside these two exercise functions.

Stable softmax: subtract the row maximum




Figure 22: Follow a row through maximum subtraction and normalization. Candidate order stays fixed, and each output row sums to one independently of every other row.

Follow a row through maximum subtraction and normalization. Candidate order stays fixed, and each output row sums to one independently of every other row.

Directly evaluating `exp(1000)` exceeds the range of ordinary floating-point formats. Very negative scores can make every unshifted exponential underflow to zero. The quotient can then become undefined numerically even though the mathematical softmax is well-defined.

First prove that shifting all scores in a row by the same finite constant `c` preserves the distribution:

$$\begin{aligned}\frac{e^{Z_{t,v}-c}}{\sum_j e^{Z_{t,j}-c}} &= \frac{e^{-c}e^{Z_{t,v}}}{e^{-c}\sum_j e^{Z_{t,j}}} \\ &= \frac{e^{Z_{t,v}}}{\sum_j e^{Z_{t,j}}}\end{aligned}$$

The common factor cancels in exact arithmetic. We choose each row's largest score:

$$m_t = \max_{0\le j<V} Z_{t,j}, \qquad P_{t,v} = \frac{e^{Z_{t,v}-m_t}}{\sum_{j=0}^{V-1} e^{Z_{t,j}-m_t}}$$

Now every shifted score is at most zero, so its exponential is at most one. At least one shifted score is zero, giving $\exp(0) = 1$. This avoids large positive exponentials and prevents a row of all-zero exponentials in the finite `float64` examples used here. Small tails can still underflow to zero.

Each position uses its own maximum and denominator. One global maximum for the whole tensor can leave a distant row with all exponentials numerically zero; the supplied driver includes rows with widely separated offsets to detect that mistake.

For example, `[1001,1002,1003]` becomes `[-2,-1,0]` after subtracting `1003`. It gives the same mathematical probabilities as `[1,2,3]`, while avoiding the large exponentials.

Complete worked example: projection and softmax

Use:

$$H = \begin{bmatrix} 1 & 2 \\ 2 & 1 \end{bmatrix}$$

$$W = \begin{bmatrix} 1 & 0 & 1 \\ 0 & 1 & 1 \end{bmatrix}$$

$$b = [0, 0, 0]$$

Here $T = 2$, $D = 2$, and $V = 3$. There are two input positions, two components per vector, and three candidate tokens.

Step 1: Calculate each row-column score

For position `0`, the vector is `[1,2]`. The three weight columns are `[1,0]`, `[0,1]`, and `[1,1]`:

$$Z_{0,0} = 1 \times 1 + 2 \times 0 + 0 = 1$$
$$Z_{0,1} = 1 \times 0 + 2 \times 1 + 0 = 2$$
$$Z_{0,2} = 1 \times 1 + 2 \times 1 + 0 = 3$$

For position `1`, the vector is `[2,1]`:

$$Z_{1,0} = 2 \times 1 + 1 \times 0 + 0 = 2$$
$$Z_{1,1} = 2 \times 0 + 1 \times 1 + 0 = 1$$
$$Z_{1,2} = 2 \times 1 + 1 \times 1 + 0 = 3$$

Thus:

$$Z = \begin{bmatrix} 1 & 2 & 3 \\ 2 & 1 & 3 \end{bmatrix}$$

The input vectors are `[2,2]`, while logits are `[2,3]`. The projection changes the component count into the candidate count.

To see nonzero bias, keep H and W, but change `b` to `[0.5,-1,2]`:

$$Z = \begin{bmatrix} 1+0.5 & 2-1 & 3+2 \\ 2+0.5 & 1-1 & 3+2 \end{bmatrix} = \begin{bmatrix} 1.5 & 1 & 5 \\ 2.5 & 0 & 5 \end{bmatrix}$$

The following softmax trace uses the original zero-bias logits `[1,2,3]` and `[2,1,3]`.

Step 2: Find a maximum for each row and keep a column shape

$$\text{row_max} = \begin{bmatrix} 3 \\ 3 \end{bmatrix}$$

Its shape is `[2,1]`. Subtract row `0`'s maximum from row `0`, and row `1`'s maximum from row `1`:

$$\text{shifted_logits} = \begin{bmatrix} 1-3 & 2-3 & 3-3 \\ 2-3 & 1-3 & 3-3 \end{bmatrix} = \begin{bmatrix} -2 & -1 & 0 \\ -1 & -2 & 0 \end{bmatrix}$$

The logits input itself remains unchanged.

Step 3: Exponentiate each shifted score

$$\text{exp_scores} = \begin{bmatrix} e^{-2} & e^{-1} & e^{0} \\ e^{-1} & e^{-2} & e^{0} \end{bmatrix} \approx \begin{bmatrix} 0.1353352832 & 0.3678794412 & 1 \\ 0.3678794412 & 0.1353352832 & 1 \end{bmatrix}$$

These are positive weights, not yet normalized probabilities.

Step 4: Sum each row's candidate weights

For either row:

$$0.1353352832 + 0.3678794412 + 1 \approx 1.5032147244$$

Therefore `row_sums` is approximately `[[1.5032147244],[1.5032147244]]`, shape `[2,1]`. The shape keeps a separate denominator for each position.

Step 5: Divide every weight by its row denominator

Position	Candidate ID	Logit	Shifted logit	Exponential weight	Probability, approximately
`0`	`0`	`1`	`-2`	`0.1353352832`	`0.0900305732`
`0`	`1`	`2`	`-1`	`0.3678794412`	`0.2447284711`
`0`	`2`	`3`	`0`	`1.0`	`0.6652409558`
`1`	`0`	`2`	`-1`	`0.3678794412`	`0.2447284711`
`1`	`1`	`1`	`-2`	`0.1353352832`	`0.0900305732`
`1`	`2`	`3`	`0`	`1.0`	`0.6652409558`

For the first row's candidate `0`, calculate $0.1353352832/1.5032147244$, approximately `0.0900305732`. Apply the same division to each component:

$$P \approx \begin{bmatrix} 0.0900305732 & 0.2447284711 & 0.6652409558 \\ 0.2447284711 & 0.0900305732 & 0.6652409558 \end{bmatrix}$$

Each row sums to one, and the output shape remains `[2,3]`. Candidate `2` has the largest probability in both rows. Returning the probability tensor does not yet choose or generate that token.

Displayed decimals are rounded. The actual calculation keeps full tensor precision, and checks use a tolerance.

New syntax: dimensions, keepdim, and broadcasting

Stage A introduces `@`; Stage B introduces exponential and reductions along a chosen axis. No new loop or context keyword is needed. All learner statements are indented four spaces inside their function.

For `[T,V]`, `dim=0` is the position axis and `dim=1` is the vocabulary axis. `dim=-1` names the last axis, which is also the vocabulary axis here. Maxima and sums must reduce that last axis.

`logits.max(dim=-1, keepdim=True)` returns two pieces: maximum values and their index locations. Select the numerical maxima with `.values`, giving the `row_max` tensor. The max documentation specifies both results. Indices are not the score values we need to subtract.

`keepdim=True` retains the reduced dimension with size one. Without it, a reduction of `[2,3]` produces `[2]`; with it, the result is `[2,1]`. Broadcasting aligns dimensions from the right:

```
logits:    [T,V]
row_max:   [T,1]
subtraction result: [T,V]

exp_scores: [T,V]
row_sums:   [T,1]
division result: [T,V]
```

The single value in each row is applied to that row's V entries. A plain `[T]` result does not describe a per-row column: for `[2,3]`, the trailing `2` conflicts with `3`; when $T = V$, it can broadcast in a misleading way without an error. Keeping `[T,1]` makes the intended relationship explicit.

`torch.exp(shifted_logits)` applies e^x elementwise and returns a tensor with the same shape. `exp_scores.sum(dim=-1, keepdim=True)` gives one denominator per row. A `.sum()` without the dimension would add every row together; the sum documentation explains dimension reduction and retained shape.

Keep forward results connected to their inputs. Unlike the previous lesson's recorded gradient snapshot, this returned probability tensor is a forward result through which a future loss must differentiate. Avoid `.item()`, `.detach()`, rebuilding tensors from lists, or no-grad mode in these exercise functions. No backward or parameter update belongs inside them.

Exact inputs, intermediate values, and returns

Name	Type and shape	Meaning
`hidden_vectors`	Floating `torch.Tensor`, `[T,D]`	Position vectors supplied to Stage A.
`output_weights`	Floating `torch.Tensor`, `[D,V]`	One weight column per candidate, in this exercise's explicit layout.
`output_bias`	Floating `torch.Tensor`, `[V]`	Shared candidate offsets added to each row.
`weighted_scores`	Floating `torch.Tensor`, `[T,V]`	Matrix product before bias.
`logits`	Floating `torch.Tensor`, `[T,V]`	Stage A return and Stage B input.
`row_max`	Floating `torch.Tensor`, `[T,1]`	Stage B row maxima, selected from the reduction's `.values`.
`shifted_logits`, `exp_scores`	Floating `torch.Tensor`, `[T,V]`	Shifted scores and their exponential weights.
`row_sums`	Floating `torch.Tensor`, `[T,1]`	Sum of weights per position.
`probabilities`	Floating `torch.Tensor`, `[T,V]`	Stage B return, normalized over candidates in each row.

Both functions return one tensor, with matching dtype/device and the appropriate autograd connection when inputs require gradients. Neither changes any input. Input creation and checks are supplied; the learner implements only the two forward calculations.

Stage A: numbered implementation plan for compute_logits

Open `03_09_logits_and_softmax.py` and find the Stage A learner region in `compute_logits`. Ordinary statements use four spaces.

1. **Form `weighted_scores`.** Use the `@` operator with `hidden_vectors` on the left and `output_weights` on the right. The inner D sizes match; the result is `[T,V]`. The worked example gives `[[1,2,3],[2,1,3]]` before bias.
2. **Add `output_bias` to produce `logits`.** Use tensor addition `left + right`. `[V]` broadcasts across the rows; zero bias leaves the example unchanged, while `[0.5,-1,2]` produces `[[1.5,1,5],[2.5,0,5]]`. Preserve the input tensors.
3. **Return `logits`.** Use `return value` at four spaces. Keep the tensor and its dependence on the input vectors, weights, and bias.

After implementing Stage A, run its checks:

```
python exercises/03_09_logits_and_softmax.py --check logits
```

Expected final line for this stage:

```
PASS logits: all three check categories
```

This command checks only Stage A. Both stages are now implemented and can also be checked separately.

Stage B: numbered implementation plan for softmax_probabilities

After Stage A, find the learner region in `softmax_probabilities(logits)`. All six steps remain at four spaces; tensor operations handle the whole input, so there is no learner loop.

1. **Find `row_max`.** Use `logits.max(dim=-1, keepdim=True).values`. The keyword arguments choose the vocabulary axis and retain a one-column shape; `.values` selects maxima instead of indices. The example gives `[[3],[3]]`, `[2,1]`.
2. **Compute `shifted_logits`.** Subtract `row_max` from `logits`, using a new subtraction result. The example is `[[-2,-1,0],[-1,-2,0]]`. Do not subtract in place from the supplied logits.
3. **Compute `exp_scores`.** Call `torch.exp` on `shifted_logits`. The first row is approximately `[0.1353352832,0.3678794412,1.0]`, with shape `[2,3]` unchanged.
4. **Compute `row_sums`.** Call `.sum(dim=-1, keepdim=True)` on `exp_scores`. Add the weights, not the original logits. The example produces `[[1.5032147244],[1.5032147244]]`, `[2,1]`.
5. **Compute `probabilities`.** Use elementwise `/` to divide `exp_scores` by `row_sums`. Broadcasting applies each denominator to its row. The first row is approximately `[0.0900305732,0.2447284711,0.6652409558]`.
6. **Return `probabilities`.** Keep the `[T,V]` tensor connected for later differentiation. This function does not select a token or update parameters.

Implement the primitive operations yourself for this assignment; the driver's built-in `torch.softmax`

is a supplied reference. The learner core stays yours to write. Run:

```
python exercises/03_09_logits_and_softmax.py --check softmax
```

Expected final line for this stage:

```
PASS softmax: all five check categories
```

This command checks Stage B independently. Once both stages are complete, run:

```
python exercises/03_09_logits_and_softmax.py --check all
```

Expected complete output:

```
PASS: row-column score projection and shared vocabulary bias
PASS: different vector/vocabulary dimensions and preserved inputs
PASS: projection gradients reach vectors, weights, and bias
PASS logits: all three check categories
PASS: worked-example probabilities and vocabulary-axis normalization
PASS: equal logits, negative logits, and a one-token vocabulary
PASS: row-wise shift invariance and large-score numerical stability
PASS: varied shapes and unchanged input scores
PASS: softmax gradients agree with the PyTorch reference
PASS softmax: all five check categories
PASS: connected vectors-to-probabilities forward and backward pipeline
Lesson 03.09 checks passed.
```

Keep the supplied setup and driver unchanged. A `.values` omission can leave a reduction result object instead of a tensor; missing `keepdim` can cause shape errors; normalizing every element together gives incorrect row sums; unshifted exponentials can overflow; disconnected returns stop later training gradients.

Reading questions and clarified distinctions

Why are logits allowed to be negative? They are scores. For `[-2,-1,0]`, exponentials are positive and softmax still defines a normalized distribution. A negative logit is not a negative probability.

Does subtracting the maximum destroy information? The same constant is subtracted from every score in one row, so all score differences remain unchanged. The common exponential factor cancels. Subtracting different arbitrary offsets per candidate would generally change the distribution.

Are the input token IDs and output candidate IDs the same axis? Input positions choose which vectors enter the calculation. Output columns enumerate all V vocabulary candidates. An input of length $T = 2$ still gives three candidate probabilities per row when $V = 3$; it does not shrink the vocabulary.

Do two output rows mean generating two future tokens simultaneously? The example computes the distributions for two supplied positions. In a causal model, each training position predicts its own next-token target using permitted context. Autoregressive generation selects the next token from the current position, appends it, and recomputes the next distribution. Context processing and generation

loops follow later.

Is softmax itself the training loss? It returns probabilities. A later objective uses the probability assigned to the observed next-token target to measure prediction quality. Cross-entropy and a minimal next-token training loop are planned continuations.

Optional reference: how softmax can pass gradients

This derivation is saved for completeness and is not a manual-derivative coding task. Consider one position, with $s = \sum_k e^{z_k}$ and $p_i = e^{z_i}/s$. Differentiating the numerator and shared denominator gives:

$$\frac{\partial p_i}{\partial z_j} = \frac{\mathbf{1}_{i=j} e^{z_i} s - e^{z_i} e^{z_j}}{s^2} = p_i \left(\mathbf{1}_{i=j} - p_j\right)$$

The indicator $\mathbf{1}_{i=j}$ is one for the same candidate and zero otherwise. Thus the derivative is $p_i(1-p_i)$ for $i = j$ and $-p_i p_j$ for different candidates. Increasing one score can raise its own probability and lower the others through the shared denominator. The stable form defines the same mathematical function. Autograd handles the connected tensor operations; the supplied driver checks gradients without requiring you to write this derivative.

Questions to work through

Optional checkpoints: distinguish D from V; trace a row-column logit calculation and bias broadcasting; calculate one probability row; prove shift invariance; explain the vocabulary axis and `[T,1]` reductions; explain why returned probabilities stay connected. Continue with Lesson 03.10: next-token cross-entropy.

03.10 Cross-Entropy for Next-Token Targets

Method sources

The probabilistic next-word objective in Bengio et al., 2003; R24 provides context for this negative-log-probability loss. This exercise isolates the loss calculation from supplied logits; it does not introduce a context model.

A probability distribution tells us what the model predicts. Training also needs to say how well that prediction matches the observed next token. Cross-entropy selects the probability of the true target, turns it into a penalty, and combines the penalties across positions without breaking the gradient path.

Work through the example before editing 03_10_cross_entropy_loss.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

What the true target means

Each input position has one observed next-token ID from the training data. If a teaching tokenizer splits 我爱猫。 as 我, 爱, 猫, 。, shifted windows give:

```
input tokens:  [我, 爱, 猫]
target tokens: [爱, 猫, 。]
```

This token split is an explicit example assumption, not a claim about the existing byte/BPE tokenizer. A full causal model lets a position use only its permitted prefix. Context processing and causal masking are still later topics; the current exercise receives scores directly.

`target_ids[t]` identifies the correct candidate column for position t. It is not a probability, a desired embedding vector, or a prediction chosen by argmax. For targets `[2,0]`, position `0` has true next-token ID `2`, and position `1` has true next-token ID `0`. ID zero does not mean probability zero.

Symbols and shapes before the formulas

Symbol	Exact code name	Meaning	Shape
Z	`logits`	Supplied raw vocabulary scores	`[T,V]`
P	Mathematical softmax probabilities	Distribution implied by each score row	`[T,V]`
y_t	`target_ids[t]`	Observed next-token candidate at position t	`target_ids` is `[T]`
ℓ_t	Per-position loss	Negative log-probability of the observed candidate	One value per position
L	`loss`	Mean of those position losses	Scalar tensor
m_t	`row_max[t,0]`	Largest score in one row	`row_max` is `[T,1]`
S	`shifted_logits`	Scores after subtracting each row's maximum	`[T,V]`

T counts input positions, as clarified in Lesson 03.09. Each of those positions contributes one target loss. V counts the candidates in each distribution. Indices are zero-based. Supplied logits are floating-point tensors; target IDs are fixed integer tensors with dtype `torch.long`, one valid ID in `[0,V)` per row.

Assume $T > 0$, $V > 0$, finite scores, valid target IDs, matching devices, and normal gradient mode. Checks use CPU `float64` scores. Input construction and validation are supplied; the only new tensor created by the learner is a row-index sequence. Both inputs must keep their values.

Negative log-likelihood and mean loss

The probability implied by the scores is:

$$P_{t,v} = \frac{e^{Z_{t,v}}}{\sum_{j=0}^{V-1} e^{Z_{t,j}}}$$

For the observed next token y_t:

$$\ell_t = -\ln P_{t,y_t}$$

The function returns the mean over positions:

$$L = -\frac{1}{T}\sum_{t=0}^{T-1} \ln P_{t,y_t}$$

Read this as: select the probability of the true candidate in each row, take its natural logarithm, negate it, then average the T resulting losses. The divisor is T, not V or TV. The candidates collectively determine the probability, but each position contributes one supervised outcome. This class-index formulation is described by CrossEntropyLoss.

Natural logarithm is the inverse of the exponential: $\ln(e^x) = x$. `torch.log` applies it elementwise, as specified in the log documentation. For probabilities between zero and one, the log is nonpositive; negation makes the loss nonnegative. Higher true-token probability gives smaller loss:

True-token probability	Loss $-\ln p$, approximately
`0.9`	`0.105361`
`0.5`	`0.693147`
`0.1`	`2.302585`
`0.01`	`4.605170`




Figure 23: Loss curve: increasing the true next-token probability reduces its negative log-likelihood.

Figure 03.10-1 — Read the formula as a curve. The horizontal axis is the probability assigned to the observed token, and the vertical axis is its loss. Moving right along the curve increases that probability and lowers the loss; the orange points match the table above. The domain is $0 < p \leq 1$. The visible vertical range ends near five, while loss continues growing without bound as `p` approaches zero. Labels are rounded.

At probability one, the loss is zero; as the probability approaches zero, the loss grows without bound. Locally:

$$\frac{d(-\ln p)}{dp} = -\frac{1}{p} < 0$$

Thus increasing the observed token's probability decreases the objective. A correct argmax prediction can still have positive loss: assigning probability `0.665241` to the correct candidate is different from assigning probability one.

Why the name cross-entropy fits

For a hard class target, define a target distribution $Q_{t,v}$ that is one at the observed ID and zero elsewhere:

$$Q_{t,v} = \mathbf{1}_{v=y_t}, \qquad \ell_t = -\sum_{v=0}^{V-1} Q_{t,v} \ln P_{t,v} = -\ln P_{t,y_t}$$

This is cross-entropy between that target distribution and the model distribution. The index representation supplies the same target without constructing a whole `[T,V]` one-hot matrix.

For a sequence model, the likelihood of observed next tokens is a product of conditional probabilities. Taking its negative logarithm turns multiplication into addition:

$$-\ln\left(\prod_{t=0}^{T-1} P_{t,y_t}\right) = -\sum_{t=0}^{T-1} \ln P_{t,y_t}$$

Dividing by T gives the per-position mean used here. It helps compare average loss across examples of different lengths under the same tokenizer and evaluation setup.

Derive the stable computation directly from logits

Substitute the softmax expression into the logarithm:

$$\begin{aligned}\ln P_{t,v} &= \ln\left(\frac{e^{Z_{t,v}}}{\sum_j e^{Z_{t,j}}}\right) \\ &= Z_{t,v} - \ln\left(\sum_j e^{Z_{t,j}}\right)\end{aligned}$$

Therefore $\ell_t = \ln(\sum_j e^{Z_{t,j}}) - Z_{t,y_t}$. Instead of first computing tiny probabilities and then taking their log, use the equivalent score expression.

Reuse the previous lesson's stable shift:

$$\begin{aligned}m_t &= \max_j Z_{t,j} \\ S_{t,v} &= Z_{t,v} - m_t \\ \ln P_{t,v} &= S_{t,v} - \ln\left(\sum_j e^{S_{t,j}}\right)\end{aligned}$$

The shift leaves softmax unchanged. Every shifted score is at most zero, and at least one exponential is one. In the finite examples here, the row sum stays positive even when a tiny candidate's own exponential underflows. Subtracting the log of that row sum from the shifted score gives the candidate's log-probability directly.

For scores `[1000,0,-1000]` and true ID `2`:

```
shifted logits: [0,-1000,-2000]
exponentials in float64: [1,0,0]
log of their sum: 0
true-target log-probability: -2000 - 0 = -2000
loss: 2000
```

Computing softmax first gives a numerical target probability of zero, and `log(0)` is not finite. The direct log-score expression still produces the appropriate finite loss `2000`. Clipping the probability with an added floor would alter that loss rather than reproduce this objective.




Figure 24: Two computation paths: logging an underflowed probability produces infinity, while computing log-probabilities directly preserves a finite loss of 2000.

Figure 03.10-2 — Follow the arrows from the same logits. The left branch first stores probabilities in floating-point arithmetic; the true candidate's tiny probability underflows to zero before the log. The right branch computes the shifted log-probability directly, selects `-2000`, and negates it to obtain `2000`. The displayed values are computed floating-point results. The mathematical softmax probability of this candidate is still positive; the two branches define the same objective, but their numerical paths differ.

In practice, cross_entropy receives raw logits, and stabilized logsumexp is a standard building block. Here you write the primitive operations to understand the calculation. The completed softmax remains useful for displaying distributions and selecting tokens; this loss uses its logarithm through an equivalent stable expression.

Complete worked example

Reuse the score rows from Lesson 03.09, with supplied true targets:

$$Z = \begin{bmatrix} 1 & 2 & 3 \\ 2 & 1 & 3 \end{bmatrix}, \qquad \text{target_ids} = [2, 0]$$

Here $T = 2$, $V = 3$. From the previous softmax calculation:

$$P \approx \begin{bmatrix} 0.0900305732 & 0.2447284711 & 0.6652409558 \\ 0.2447284711 & 0.0900305732 & 0.6652409558 \end{bmatrix}$$

Step 1: Identify the probability to evaluate in each row

Position	True target ID	Selected probability	Position loss, approximately
`0`	`2`	`0.6652409558`	`0.4076059644`
`1`	`0`	`0.2447284711`	`1.4076059644`

The first row assigns more probability to its true token, so it has the smaller loss. Although candidate `2` is the argmax in both rows, the second row's actual target is candidate `0`. Choosing the argmax as the target would reward the model's own prediction instead of assessing the observed outcome.




Figure 25: A two-by-three probability matrix with coordinates (0,2) and (1,0) highlighted, leading to two position losses and their mean.

Figure 03.10-3 — Read rows as positions and columns as candidate IDs. Targets `[2,0]` select the teal cells at `(0,2)` and `(1,0)`. In the second row, the selected probability is approximately `0.2447`, even though candidate `2` has the largest probability. Each selected value yields one position loss through negative natural log. The final box averages those two losses, dividing by $T = 2$; $V = 3$ counts columns. Displayed probabilities and losses are rounded from full-precision calculations.

Step 2: Shift scores and calculate the row normalizers

```
row_max = [[3],[3]]
shifted_logits = [[-2,-1,0],[-1,-2,0]]
exp_scores = [[0.1353352832,0.3678794412,1],
              [0.3678794412,0.1353352832,1]]
row_sums = [[1.5032147244],[1.5032147244]]
log_row_sums = [[0.4076059644],[0.4076059644]]
```

The maximum and row-sum tensors are `[2,1]`. The shifted scores and exponentials are `[2,3]`.

Step 3: Calculate all log-probabilities without logging tiny probabilities

$$\ln P \approx \begin{bmatrix} -2 - 0.4076059644 & -1 - 0.4076059644 & 0 - 0.4076059644 \\ -1 - 0.4076059644 & -2 - 0.4076059644 & 0 - 0.4076059644 \end{bmatrix}$$

Thus:

```
log_probabilities =
    [[-2.4076059644,-1.4076059644,-0.4076059644],
     [-1.4076059644,-2.4076059644,-0.4076059644]]
```

Log-probabilities are not themselves probabilities. They can be negative and do not sum to one.

Step 4: Select one true-target coordinate per position

Construct `row_indices=[0,1]`. Pair these with `target_ids=[2,0]`:

```
row_indices[0]=0, target_ids[0]=2 -> coordinate (0,2)
row_indices[1]=1, target_ids[1]=0 -> coordinate (1,0)

target_log_probabilities = [-0.4076059644,-1.4076059644]
```

The paired expression `log_probabilities[row_indices, target_ids]` produces `[T]`, not a cross-product matrix of every row and every listed target.

Step 5: Negate and average over the two positions

$$L = \frac{0.4076059644 + 1.4076059644}{2} \approx 0.9076059644$$

Return this as a scalar tensor so it remains connected to the logits. Displayed decimals are rounded; checks use full precision and tolerances.

For comparison, equal scores over three candidates assign probability $\frac{1}{3}$ to any target and give loss $\ln 3 \approx 1.098612$. A vocabulary with only one candidate assigns probability one and gives loss zero. Both are covered by the driver.

New syntax: log, row indices, and paired indexing

`torch.log(row_sums)` applies the natural log to each row normalizer and keeps shape `[T,1]`. It is the log of a sum of exponentials, not a sum of logs and not the log of the original logits, which can be negative.

`logits.shape[0]` supplies T. `torch.arange(logits.shape[0], device=logits.device)` builds `[0,1,...,T-1]` on the score tensor's device. Integral bounds produce integer indices; see arange. For two positions it produces `[0,1]`.

With two same-length index tensors, `matrix[rows, columns]` picks the coordinate pair at each index. In this example it picks `(0,2)` and `(1,0)`. One-index lookup in the embedding lesson selected entire rows; here we select one number from each row. This selection remains differentiable with respect to the floating-point log-probabilities. The integer labels and row indices are fixed selectors.

Negation uses unary `-`. Parentheses group the negative selected vector before `.mean()`. At this point the vector has T values, so the mean divides by T. The loss must remain a tensor; `.item()` belongs only in logging after the tensor has been retained for differentiation.

Exact inputs, intermediate values, and return

Name	Type and shape	Meaning
`logits`	Floating `torch.Tensor`, `[T,V]`	Raw scores; preserve values and graph.
`target_ids`	Integer `torch.Tensor`, `[T]`, `torch.long`	Observed next-token column in each row.
`row_max`	Floating tensor `[T,1]`	Maximum score per position.
`shifted_logits`, `exp_scores`	Floating tensor `[T,V]`	Shifted scores and exponential weights.
`row_sums`, `log_row_sums`	Floating tensor `[T,1]`	Normalizers and their natural logs.
`log_probabilities`	Floating tensor `[T,V]`	Logarithm of each candidate's implied probability.
`row_indices`	Integer tensor `[T]`	Position indices aligned with `target_ids`.
`target_log_probabilities`	Floating tensor `[T]`	One selected value per observed outcome.
`loss`	Scalar floating tensor	Mean negative target log-probability.

The returned dtype/device matches logits. The scalar stays connected when logits require gradients. Both inputs remain unchanged. No reset, backward, or parameter update belongs in this function.

Guided implementation

Open `03_10_cross_entropy_loss.py` and find the completed `cross_entropy_loss(logits, target_ids)`. The following plan supports review or independent reconstruction while preserving the implementation. All statements use four spaces; no loop or context block is needed.

1. **Find `row_max`.** Reuse `logits.max(dim=-1, keepdim=True).values`. Example `[[3],[3]]`, shape `[T,1]`.
2. **Calculate `shifted_logits`.** Subtract `row_max` from `logits` into a new result. Example `[[-2,-1,0],[-1,-2,0]]`, shape `[T,V]`.
3. **Calculate `exp_scores` and `row_sums`.** Use `torch.exp`, then `.sum(dim=-1, keepdim=True)`. The example denominators are both approximately `1.5032147244`.
4. **Calculate `log_row_sums`.** Apply `torch.log` to `row_sums`. Example `[[0.4076059644],[0.4076059644]]`, shape `[T,1]`.
5. **Calculate `log_probabilities`.** Subtract `log_row_sums` from `shifted_logits`. Broadcasting applies one log normalizer to each row; the first row is approximately `[-2.407606,-1.407606,-0.407606]`.
6. **Construct `row_indices`.** Use `torch.arange(logits.shape[0], device=logits.device)`. Example `[0,1]`, an integer tensor `[T]`.
7. **Select `target_log_probabilities`.** Use paired indexing `log_probabilities[row_indices, target_ids]`. Example `[-0.407606,-1.407606]`, shape `[T]`.
8. **Form and return `loss`.** Negate the selected vector, average with `.mean()`, and return the scalar tensor. Example approximately `0.907606`. Keep it connected for later backward.

The core is yours to write. Reference helpers in the supplied driver do not replace the assigned primitive calculation. Setup loads the completed `compute_logits` from the sibling `03_09_logits_and_softmax.py`; it also checks gradients reaching the embedding table through indexed lookup. Do not edit the setup or driver.

Run in the existing PyTorch environment from the project root:

```
python exercises/03_10_cross_entropy_loss.py
```

Expected output after implementation:

```
PASS: true-target selection and mean loss in the worked example
PASS: varied targets, vocabulary sizes, single-candidate case, and preserved inputs
PASS: row-shift invariance and finite loss for very unlikely targets
PASS: logit gradients equal mean-normalized probability minus target indicator
PASS: PyTorch loss agreement and finite-difference gradient agreement
PASS: loss gradients reach the embedding table and completed output projection
Lesson 03.10 checks passed.
```

Formula reference: how this loss guides training

The following derivation is preserved for understanding, not assigned as manual derivative code. For one row:

$$\ell_t = \ln\left(\sum_j e^{Z_{t,j}}\right) - Z_{t,y_t}$$

Differentiate the log normalizer and selected score, then include the mean factor:

$$\frac{\partial L}{\partial Z_{t,v}} = \frac{1}{T}\left(\frac{e^{Z_{t,v}}}{\sum_j e^{Z_{t,j}}} - \mathbf{1}_{v=y_t}\right) = \frac{P_{t,v} - \mathbf{1}_{v=y_t}}{T}$$

The indicator is one for the true candidate and zero for other candidates. For a true candidate with probability below one, the gradient is negative; gradient descent applied directly to scores would raise that score. Other candidate scores receive positive gradients. Actual model training updates the parameters that produced scores through the chain rule, so their effects can be shared across positions.

In row `0` of the worked example, the true candidate is `2`, giving gradient $(0.6652409558 - 1)/2 \approx -0.1673795221$ for that logit. Candidate `0` receives $0.0900305732/2 \approx 0.0450152866$. Even though the scalar loss selects the true log-probability, every candidate contributes through its shared normalizer.

Reading questions and status

Why average only true-target losses? Each position supplies one observed next token. All vocabulary candidates affect its probability through normalization, but they are not V separate observed outcomes.

Why not use argmax as the target? The target comes from data. Replacing it with the model's current favorite fails to measure the actual next-token prediction.

Why does the helper not call backward? It supplies the differentiable objective. A training step later clears parameter gradients, calculates scores and loss, calls backward, and updates parameters. Reusing this loss for evaluation should not force an update.

The continuation is the current guided Lesson 03.11: a minimal next-token training step using embeddings, the completed output projection, this loss, and parameter updates. Contextual attention remains a later chapter.

Two spellings of a reduction. `torch.sum(exp_scores, dim=-1, keepdim=True)` and `exp_scores.sum(dim=-1, keepdim=True)` perform the same reduction. Both retain one column per row so broadcasting remains explicit.

03.11 One Joint Next-Token Training Step

Lookup, vocabulary scores, and loss now form one connected computation. One backward pass can therefore tell all three parameter tensors how to change. We will calculate every gradient at the old state before updating the table, projection, and bias together.

Work through the example before editing 03_11_next_token_train_step.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

Symbols, inputs, and the differentiation object

Symbol	Exact parameter name	Type and shape	Role
E	`embedding_table`	Floating trainable leaf tensor `[V,D]`	Input token vectors
x	`token_ids`	Fixed `torch.long` tensor `[T]`	Input table row selectors
W	`output_weights`	Floating trainable leaf tensor `[D,V]`	Vector-to-candidate weights
b	`output_bias`	Floating trainable leaf tensor `[V]`	Shared candidate biases
y	`target_ids`	Fixed `torch.long` tensor `[T]`	Observed next-token candidate IDs
η	`learning_rate`	Nonnegative Python float	Step multiplier
H	`selected_vectors`	Connected floating tensor `[T,D]`	Selected input vectors
Z	`logits`	Connected floating tensor `[T,V]`	Raw output scores
L	`loss`	Connected scalar tensor	Mean true-target cross-entropy

V is vocabulary size, D vector dimension, and T input-position count. Inputs and observed targets are fixed during the update. The loss is a function of all three trainable tensors, $L(E, W, b)$; a partial derivative with respect to one parameter component holds the other components fixed. Integer IDs select locations and are not differentiation variables.

Assume positive dimensions, finite values, valid IDs, matching dtype/device, and normal gradient mode. The three parameter tensors have separate storage, are leaves with `requires_grad=True`, and are not tied to one another. The supplied driver constructs them as CPU `float64`; the learner does not need new parameter construction or validation.

Lookup, prediction, and one scalar objective

Lookup selects a table row for each input position:

$$H_{t,d} = E_{x_t,d}$$

The completed output projection computes:

$$Z_{t,v} = \sum_{d=0}^{D-1} H_{t,d} W_{d,v} + b_v, \qquad Z = HW + b$$

The completed loss evaluates the observed next-token IDs:

$$P_{t,v} = \frac{e^{Z_{t,v}}}{\sum_j e^{Z_{t,j}}}, \qquad L(E, W, b) = -\frac{1}{T} \sum_{t=0}^{T-1} \ln P_{t,y_t}$$

`compute_logits(selected_vectors, output_weights, output_bias)` supplies Z. `cross_entropy_loss(logits, target_ids)` supplies L using the stable expression from 03.10. Calling the completed softmax separately is useful for displaying a distribution, but is unnecessary when passing raw logits to this loss helper.

The loss reaches three sets of parameters through the same connected computation:

$$G_E = \frac{\partial L}{\partial E}, \qquad G_W = \frac{\partial L}{\partial W}, \qquad G_b = \frac{\partial L}{\partial b}$$

Each gradient has the shape of its own parameter. One scalar objective can therefore produce many derivatives; it does not supply one common scalar gradient for every parameter. Calling `loss.backward()` once traverses the graph and fills the participating leaf tensors' `.grad` attributes through the chain rule. PyTorch backward documentation.

After all three gradients describe the same pre-update state, apply plain gradient descent:

$$\begin{aligned} E_{\text{new}} &= E - \eta G_E \\ W_{\text{new}} &= W - \eta G_W \\ b_{\text{new}} &= b - \eta G_b \end{aligned}$$

The formulas act component by component. A positive component gradient decreases that parameter component; a negative one increases it. The objective guides the embedding values through prediction quality rather than a hand-chosen target vector.




Figure 26: One scalar loss sends gradients through the output head and lookup to the embedding table, weights, and bias.

Figure 03.11-1 — Read blue arrows forward, orange arrows backward. Input IDs select H from E; W and b turn it into Z; true target IDs determine the scalar loss. Reverse arrows show the derivative paths to all three parameters. There is no gradient/update arrow to the integer IDs. The boxed update follows the completed backward pass. Shapes and values match the small example below.

Complete small example: two candidates and one input position

Use a teaching vocabulary of two IDs. A token sequence `[0,1]` supplies input `[0]` and target `[1]`. Choose $T = 1$, $D = 1$, $V = 2$ to make every component visible; these small dimensions serve the example.

$$E = \begin{bmatrix} 1 \\ 2 \end{bmatrix}, \quad W = \begin{bmatrix} 1 & 0 \end{bmatrix}, \quad b = \begin{bmatrix} 0 & 0 \end{bmatrix}, \quad x = [0], \quad y = [1], \quad \eta = 0.1$$

Bias is stored as a one-dimensional `[2]` tensor even though mathematical row notation shows its two entries side by side.

1. Forward: calculate scores, true probability, and loss

Select input row zero: $H = [[1]]$, shape `[1,1]`. Matrix multiplication and the bias give:

$$Z = \begin{bmatrix} 1 \times 1 + 0 & 1 \times 0 + 0 \end{bmatrix} = \begin{bmatrix} 1 & 0 \end{bmatrix}$$

The two probabilities and the true-target loss are:

$$P = \begin{bmatrix} \frac{e^1}{e^1+e^0} & \frac{e^0}{e^1+e^0} \end{bmatrix} \approx \begin{bmatrix} 0.7310585786 & 0.2689414214 \end{bmatrix}, \qquad L = -\ln P_{0,1} \approx 1.3132616875$$

The true ID is `1`, whose probability is the second entry. $T = 1$ means one position loss; dividing by $V = 2$ would be incorrect. This forward calculation has not changed any parameter.

2. Backward: derive every gradient in this example

The formula from 03.10 is:

$$(G_Z)_{t,v} = \frac{P_{t,v} - \mathbf{1}_{v=y_t}}{T}$$

Here the target indicator is `[0,1]`, so:

$$G_Z = \begin{bmatrix} 0.7310585786 & -0.7310585786 \end{bmatrix}$$

For the weight $W_{0,0}$, the local derivative of score $Z_{0,0} = H_{0,0}W_{0,0} + b_0$ with respect to that weight is $H_{0,0} = 1$. Multiplying by the loss derivative gives 1×0.7310585786. For $W_{0,1}$ it gives $1 \times (-0.7310585786)$. Each bias has local score derivative one. Thus:

$$G_W = \begin{bmatrix} 0.7310585786 & -0.7310585786 \end{bmatrix}, \qquad G_b = \begin{bmatrix} 0.7310585786 & -0.7310585786 \end{bmatrix}$$

To reach the selected embedding, add the paths through both candidates:

$$\frac{\partial L}{\partial H_{0,0}} = \sum_v \frac{\partial L}{\partial Z_{0,v}} W_{0,v} = 0.7310585786 \times 1 + (-0.7310585786) \times 0 = 0.7310585786$$

Only $H_{0,0} = E_{0,0}$ was selected, so:

$$G_E = \begin{bmatrix} 0.7310585786 \\ 0 \end{bmatrix}$$

Row one of the input table was not used. The true target being ID `1` selects an output candidate for the loss; it does not select input row one for lookup. With this untied lookup/head objective and plain descent, that input row's gradient is zero. The output weight and bias for candidate one still receive nonzero gradients.

3. Update all three parameters from those old gradients

For the selected embedding component, $1 - 0.1 \times 0.7310585786 \approx 0.9268941421$. For the second candidate weight, $0 - 0.1 \times (-0.7310585786) \approx 0.0731058579$. Applying the same rule to every component gives:

$$\begin{aligned} E_{\text{new}} &\approx \begin{bmatrix} 0.9268941421 \\ 2 \end{bmatrix}, \\ W_{\text{new}} &\approx \begin{bmatrix} 0.9268941421 & 0.0731058579 \end{bmatrix}, \\ b_{\text{new}} &\approx \begin{bmatrix} -0.0731058579 & 0.0731058579 \end{bmatrix}. \end{aligned}$$

The table's unused row remains exactly `2`. The gradients are copied and the original loss is extracted before the update. The function returns, in order:

```
loss_value = 1.3132616875
gradient_table = [[0.7310585786],[0]]
gradient_weights = [[0.7310585786,-0.7310585786]]
gradient_bias = [0.7310585786,-0.7310585786]
```

The floating tensors keep the full gradient values; displayed decimals are rounded. All four returned observations describe the pre-update state. The passed parameter objects now hold updated values.

4. A separate forward check shows what the update changed

Recompute using all three updated parameters:

$$Z'_{0,0} \approx 0.9268941421 \times 0.9268941421 - 0.0731058579 \approx 0.7860268929$$
$$Z'_{0,1} \approx 0.9268941421 \times 0.0731058579 + 0.0731058579 \approx 0.1408672493$$

The new true-target probability is approximately `0.3440811280`, and the new loss is approximately `1.0668778121`. The model still assigns higher probability to candidate zero; one useful update need not immediately fix the argmax. It increases probability on the actual target and lowers the loss in this example. This second forward belongs to the check driver, not the learner step's returned observations.




Figure 27: Before and after the same joint update: true-target probability rises and cross-entropy loss falls in the worked example.

Figure 03.11-2 — Compare one parameter state with the next. Blue bars use the original E, W, b; teal bars use the three updated tensors with `learning_rate=0.1`. Read the left axis as a probability and the right axis as loss. The helper returns the original loss `1.3133`. A separate forward obtains the new loss `1.0669`. Bar labels are rounded. This measured improvement applies to the given example; a sufficiently large step can increase loss.

Derivative reference for multiple positions

Autograd computes these derivatives. The formulas explain the shared-parameter paths and their shapes:

$$G_W = H^\mathsf{T} G_Z, \qquad (G_b)_v = \sum_t (G_Z)_{t,v}, \qquad G_H = G_Z W^\mathsf{T}$$

The matrix product for G_W adds contributions from all input positions to each shared weight. The sum for G_b reverses bias broadcasting. The product for G_H adds candidate paths back to each vector component. For lookup:

$$(G_E)_{r,d} = \sum_{t:x_t=r} (G_H)_{t,d}$$

Repeated input IDs add contributions to the same table row. Unused rows have zero gradient in this objective. The division by T already occurs in G_Z; do not divide again by T, D, or V when applying these chains. In the small example $H = 1$, so weight and bias gradients happen to have equal values; they need not agree in general.

For sufficiently small steps, a first-order loss estimate is:

$$\Delta L \approx -\eta \left(\|G_E\|_F^2 + \|G_W\|_F^2 + \|G_b\|_2^2 \right)$$

The norms sum squared gradient components. This local approximation explains the descent direction; it does not guarantee lower loss at an arbitrary finite learning rate. The driver includes a larger step that increases loss.

Exact return and gradient/reset semantics

Return `(loss_value, gradient_table, gradient_weights, gradient_bias)`. The first entry is a Python float from the original scalar `loss.item()`. The other entries are independent `.clone()` snapshots of the three `.grad` tensors, with shapes `[V,D]`, `[D,V]`, and `[V]`. They preserve each parameter's floating dtype and device. Ordinary backward leaves those gradients untracked; cloning copies their storage without needing an extra detach.

`loss` remains a tensor until backward completes. Its numeric extraction is for reporting; item returns a Python number without an autograd connection. Keep a distinct `loss_value` name for that report.

Reset all three `.grad` attributes at the start because backward accumulates gradients into leaves. This lesson wants the current step's gradient, rather than accumulated previous steps. Setting `.grad=None` clears the stored derivative, leaving parameter values intact. The next forward uses the updated values from the preceding call.

Only the parameter mutation is inside `with torch.no_grad():`. This context suppresses tracking of the update operation, while the same supplied leaves remain trainable for the next call. Lookup, score computation, loss computation, and backward stay in normal gradient mode. No-grad documentation.

New loop syntax and indentation before implementation

`parameters = (embedding_table, output_weights, output_bias)` creates a tuple holding references to the three existing tensors. It does not copy values or combine them into a larger tensor. `for`

`parameter in parameters:` visits each object once; the trailing colon opens the indented loop body. Resetting the current object's `.grad` acts on that actual parameter.

Inside the update loop, `parameter -= learning_rate * parameter.grad` mutates the original tensor under no-grad. Assigning `parameter = parameter - ...` would only bind the local loop variable to a new tensor, leaving the caller's original parameter unchanged. The assignment requires persistent original tensors.

Region	Spaces from line start
Ordinary function statement and outer `for`/`with`	4
Body of the gradient-reset `for`	8
Parameter `for` inside no-grad	8
Update body inside both no-grad and parameter `for`	12
Final return, after leaving both blocks	4

The two loops visit three parameters, not input positions or training steps. Tensor operations already calculate all T positions together.

Guided implementation

Open `03_11_next_token_train_step.py` and find `next_token_train_step(embedding_table, token_ids, output_weights, output_bias, target_ids, learning_rate)`. The following plan guides your implementation.

1. **Group and clear parameters.** At four spaces, create `parameters` using the three trainable tensors in the order table, weights, bias. At four spaces, begin `for parameter in parameters:`; at eight spaces, assign `parameter.grad = None`. Values remain unchanged.
2. **Look up `selected_vectors`.** Return to four spaces and index `embedding_table[token_ids]`. Shape `[T,D]`; the example yields `[[1]]`. Keep the graph connected to the supplied table.
3. **Calculate `logits`.** At four spaces, call `compute_logits(selected_vectors, output_weights, output_bias)`. Shape `[T,V]`; the example yields `[[1,0]]`. This helper includes the bias.
4. **Calculate `loss`.** At four spaces, call `cross_entropy_loss(logits, target_ids)`. It returns a connected scalar, approximately `1.3132616875` here. Keep `loss` as the tensor.
5. **Run one backward.** At four spaces, call `loss.backward()`. Table, weight, and bias gradients are now available and all describe the old parameter state. The selected table gradient is positive; candidate-one weight and bias gradients are negative.
6. **Save observations.** At four spaces, obtain `loss_value` with `.item()`. Obtain `gradient_table`, `gradient_weights`, and `gradient_bias` with `.clone()` on each corresponding parameter's `.grad`. Save separate full tensor copies.
7. **Update all three original tensors.** At four spaces, enter `with torch.no_grad():`; at eight spaces, write `for parameter in parameters:`; at twelve spaces, subtract `learning_rate *`

`parameter.grad` with `-=`. The selected table value becomes approximately `0.9268941421`. Only this update loop belongs in no-grad.

8. **Return in the specified order.** At four spaces, outside both blocks, return `loss_value`, `gradient_table`, `gradient_weights`, and `gradient_bias`. These describe the pre-update state; no second forward or outer training loop is required.

The supplied loader exposes the completed helpers through portable sibling filenames. Preserve earlier implementations and the supplied setup/check driver. The learner core connects the pieces; it does not rewrite the loss or hand-derived gradients.

From the repository root in the existing PyTorch environment:

```
python exercises/03_11_next_token_train_step.py
```

Expected output after the learner implements the core:

```
PASS: worked example, three parameter gradients, and joint in-place update
PASS: multiple positions, varied dimensions, repeated IDs, and untouched input rows
PASS: zero learning rate and single-candidate zero gradients
PASS: all old gradients cleared and repeated calls use updated trainable parameters
PASS: independent table, weight, and bias gradient snapshots
PASS: all parameter gradients agree with trusted autograd and finite differences
PASS: pre-update reporting, small-step improvement, and possible large-step loss increase
Lesson 03.11 checks passed.
```

Reader questions

How does one loss train several tensors? Each parameter component has its own partial derivative. A connected backward pass follows every path contributing to the same scalar, including the head and lookup.

Why does the embedding shrink while the true probability rises? Embedding coordinates are features rather than probabilities. In this example, reducing the selected feature reduces the initially favored candidate's score contribution; changes to both head columns and biases also affect the prediction. Evaluate the complete updated model to see the effect.

Why is the true target's input table row unchanged? The input IDs select table rows. The target IDs select candidate columns in the loss. Those are different operations, with untied parameters in this exercise.

Does backward update parameters? It calculates and stores derivatives. The following no-grad mutation applies the learning-rate-scaled update.

What happens at learning rate zero? Loss and gradients are still calculated and reported. Parameter values remain unchanged. A zero gradient also leaves its corresponding parameter component unchanged.

Example variable names. The reset loop consistently uses `parememter`, a valid local identifier. `loss_values` holds the connected scalar tensor, while `loss_value` holds its extracted Python float.

Three explicit `-=` statements update the table, weights, and bias inside no-grad. With no inner parameter loop, those statements correctly use eight spaces. Twelve spaces apply only to the optional nested-loop form in the implementation plan. This form has the required behavior.

The continuation is the current guided Lesson 03.12: repeat this completed step while retaining parameters and recording pre-update loss history. Context processing remains a later chapter.

03.12 Repeat the Next-Token Training Step

The next-token model has taken its first step; now we will let the same parameters take several more. A useful loss history must preserve which state produced each number. This loop revisits the same training pairs so that parameter continuity and logging time are easy to inspect.

Work through the example before editing 03_12_next_token_training_loop.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

Exact inputs and returned value

Name	Type and shape	Meaning
`embedding_table`	Trainable floating leaf tensor `[V,D]`	Existing input table, updated in place
`token_ids`	Fixed `torch.long` tensor `[T]`	Input row selectors
`output_weights`	Trainable floating leaf tensor `[D,V]`	Existing projection weights, updated in place
`output_bias`	Trainable floating leaf tensor `[V]`	Existing shared bias, updated in place
`target_ids`	Fixed `torch.long` tensor `[T]`	Observed next-token candidate IDs
`learning_rate`	Nonnegative Python float	Passed unchanged to the step helper
`num_steps`	Nonnegative Python int	Exact number of update calls
`losses`	Fresh `list[float]`	One pre-update loss per call, in order

T counts supervised input positions per step, D vector components, and V vocabulary candidates. Assume the valid IDs, finite values, matching dtype/device, separate parameter storage, and normal gradient mode from 03.11. The driver supplies CPU `float64` trainable leaves. The learner does not construct parameters or validate inputs.

The function returns only `losses`. The caller already holds the original three parameter objects, and their values become the final trained values. Every stored entry is a Python float rather than a loss tensor or gradient tuple. For `num_steps=0`, return a fresh empty list and leave parameter values and stored gradients untouched.

Parameter states and loss history

Group the contents of the three parameter tensors after k updates as:

$$\theta_k = (E_k, W_k, b_k), \qquad \theta_0 = (E_0, W_0, b_0)$$

This notation describes changing values inside persistent tensors, not new tensor objects. The input IDs, target IDs, and learning rate are fixed during this exercise. Define the objective for a parameter state:

$$L(\theta) = -\frac{1}{T}\sum_{t=0}^{T-1} \ln \text{softmax}(E[x]W + b)_{t,y_t}, \qquad L_k = L(\theta_k)$$

Here x is `token_ids`, y is `target_ids`, and softmax normalizes each row over vocabulary candidates. The completed stable loss helper implements this objective.

One call obtains the current gradient and changes the parameters:

$$\theta_{k+1} = \theta_k - \eta \nabla_\theta L(\theta_k), \qquad k = 0, \ldots, N-1$$

$N =$ `num_steps`, and η is `learning_rate`. The gradient is the three parameter-shaped derivatives from 03.11. Each call uses the latest values, with a new forward calculation and fresh gradients supplied by the helper. The next call therefore starts at θ_{k+1}.

The returned numeric record is:

$$\text{losses}[k] = L(\theta_k), \qquad \text{losses} = [L_0, L_1, \ldots, L_{N-1}] \quad (N \geq 1)$$

After N calls, the original tensors contain θ_N. The last recorded value measures θ_{N-1}, before the last update. A separate forward can evaluate $L(\theta_N)$; it is not another history entry under this contract. Thus N updates visit $N + 1$ parameter states while producing exactly N recorded values.




Figure 28: Three persistent parameter updates produce three pre-update loss entries, with final evaluation shown separately.

Figure 03.12-1 — Follow the states, then the recorded values. Each top box represents the contents of the same E, W, b after k updates. Blue arrows are the three update calls. Teal arrows collect the loss at each call's starting state. The orange state is the final trained state, whose loss is separately evaluated. In the curve, solid teal markers are the returned history; the hollow orange marker is the separate final evaluation. Values are rounded and use the complete example below.

Complete three-update example

Reuse the exact 03.11 example:

```
embedding_table = [[1],[2]]
output_weights = [[1,0]]
output_bias = [0,0]
token_ids = [0]
target_ids = [1]
learning_rate = 0.1
num_steps = 3
```

The table has shape `[2,1]`, the weights `[1,2]`, the bias `[2]`, and both ID tensors `[1]`. The token sequence `[0,1]` supplies the observed input/target pair. The first forward selects `[[1]]`, gives logits `[[1,0]]`, and obtains true probability approximately `0.2689414214`. Its loss is:

$$L_0 = -\ln(0.2689414214) \approx 1.3132616875$$

The first call uses the gradients already derived in 03.11 and leaves the table's selected component at approximately `0.9268941421`. The second call starts from all three updated tensors. Every active parameter component and the evaluated loss at each state are shown below. The unused table row `E[1, 0]` stays exactly `2` throughout this fixed-window example.

Updates completed k	E[0,0]	W[0,0]	W[0,1]	b[0]	b[1]	Evaluated loss L_k
0	1.0000000000	1.0000000000	0.0000000000	0.0000000000	0.0000000000	1.3132616875
1	0.9268941421	0.9268941421	0.0731058579	−0.0731058579	0.0731058579	1.0668778121
2	0.8708925573	0.8660974061	0.1339025939	−0.1386977451	0.1386977451	0.8894180392
3	0.8277585808	0.8147926734	0.1852073266	−0.1976082643	0.1976082643	0.7580921817

For example, at state one, $H \approx 0.9268941421$ and the probability of candidate zero is approximately `0.6559188720`. For this one-position target `1`, the new score gradient is $[p_0, -p_0]$. The next selected-table gradient is:

$$\begin{aligned}\frac{\partial L_1}{\partial E_{0,0}} &= p_0(W_{0,0} - W_{0,1}) \\ &\approx 0.6559188720 \times (0.9268941421 - 0.0731058579) \\ &\approx 0.5600158483.\end{aligned}$$

Thus the second call changes that component to approximately $0.9268941421 - 0.1 \times 0.5600158483 = 0.8708925573$. This gradient differs from the first call's `0.7310585786` because the parameters have changed. The wrapper delegates those calculations to the completed helper.

Track the Python list and caller-owned tensors in execution order:

Call	Starting state	Helper's first returned item	State after the call	`losses` after append
`1`	θ_0	`1.3132616875`	θ_1	`[1.3132616875]`
`2`	θ_1	`1.0668778121`	θ_2	`[1.3132616875,1.0668778121]`
`3`	θ_2	`0.8894180392`	θ_3	`[1.3132616875,1.0668778121,0.8894180392]`

The list append executes after the helper has updated parameters and returned. Its saved number still describes the state before that update because the helper extracted that loss earlier. Execution time and the state measured by a report are different concepts.

The function returns approximately:

```
[1.3132616875, 1.0668778121, 0.8894180392]
```

The original parameter objects now contain:

```
embedding_table = [[0.8277585808],[2]]
output_weights = [[0.8147926734,0.1852073266]]
output_bias = [-0.1976082643,0.1976082643]
```

The separate final loss `0.7580921817` is available from evaluating those parameters. Adding it to the returned list would change this exercise's history convention. It is also unnecessary to call the update helper again merely to evaluate: that would perform a fourth update. Displayed values are rounded; the driver uses full precision.

Zero steps, repeated calls, and training budget

When `num_steps=0`, `range(0)` yields no iterations. No step helper runs, no gradient is reset, and no parameter is changed. The final return outside the loop still executes and returns `[]`. By contrast, zero learning rate with three steps still calls the helper three times and records three losses. Gradients are recalculated even though parameter values do not move.

Every function call creates its own fresh history list. If the caller passes the same trained parameters to another call, training continues from their current values. For the same fixed data and learning rate, three updates followed by two updates produce the same parameter trajectory as five uninterrupted updates. The two returned lists remain independent.

`num_steps` counts update calls rather than generated tokens or epochs. Each call scores all T supplied targets. This toy budget therefore performs NT supervised-position evaluations during training; those repeated evaluations are not NT distinct examples. An epoch needs a defined pass through a dataset, which this fixed-window wrapper does not implement.

The example's losses fall for `learning_rate=0.1`. Loss need not decrease at every arbitrary learning rate; the check driver preserves a large-step increase. Lower loss on repeatedly used training pairs alone also does not establish performance on unseen text. Dataset splits and independent evaluation remain later topics.

Reusing the helper and preserving its graph

`next_token_train_step(embedding_table, token_ids, output_weights, output_bias, target_ids, learning_rate)` returns a four-item tuple. Save it as `step_result`. Index zero, `step_result[0]`, is the pre-update Python loss. The remaining items are gradient snapshots, which this wrapper does not store in its history.

The helper already clears all parameter gradients, creates the forward computation, runs backward once, and updates each original tensor inside its own no-grad block. The wrapper stays in normal gradient mode and calls it exactly once per iteration. It does not repeat those internal actions. Keep all three original parameter objects so their updates carry into the next call.

Only floats accumulate in `losses`; it does not retain the differentiable loss graph or every step's full gradient tensors. The teaching helper still creates gradient snapshots for inspection, but they are not part of this returned history. More efficient training code follows after the learning version is understood.

Loop syntax and indentation before implementation

`losses = []` creates a new empty list. `for step in range(num_steps):` repeats the indented body. With three steps, the counter takes `0,1,2`; the first call corresponds to counter zero. The name `step` is a local repetition counter. The helper's arguments contain the actual parameters and learning rate.

`step_result[0]` selects the first tuple item using zero-based indexing. `losses.append(loss_value)` adds that float at the end of the same list. Appending the complete tuple would store loss plus gradient tensors rather than the requested scalar history.

Use four spaces for the fresh list, loop header, and final return. Use eight spaces for the helper call, first-item selection, and append inside the loop. Return outside the loop so it executes after all requested calls and also handles zero calls. No new nested update block is needed; that already exists in the completed helper.

Five numbered implementation steps

Open `03_12_next_token_training_loop.py` and find the completed `train_next_token(embedding_table, token_ids, output_weights, output_bias, target_ids, learning_rate, num_steps)`. The following plan supports review or independent reconstruction while preserving the exercise code.

1. **Create the history.** At four spaces, assign an empty list to `losses` using `[]`. Parameters are already supplied. Before the loop, the list is empty.
2. **Set the repetition budget.** At four spaces, write `for step in range(num_steps):`. Its colon begins the eight-space body. `range(3)` repeats three times; `range(0)` skips that body.
3. **Reuse one complete update.** At eight spaces, call `next_token_train_step` with `embedding_table`, `token_ids`, `output_weights`, `output_bias`, `target_ids`, `learning_rate` in that order. Save its returned tuple as `step_result`. The first call updates the original tensors from θ_0 to θ_1; the next call sees θ_1.
4. **Record the first tuple item.** Still at eight spaces, select `step_result[0]` as `loss_value`, then call `losses.append(loss_value)`. After two calls the example list contains approximately `[1.3132616875,1.0668778121]`. The helper's gradient snapshots are not history entries.
5. **Return after the loop.** At four spaces, return `losses`. Three calls produce three floats; zero calls produce `[]`. The original parameter tensors contain the final values. Do not append another evaluation or perform another update.

The core remains for you to write. The supplied loader imports the completed sibling step without running its check driver. Preserve that setup and all earlier implementations.

Run from the repository root in the existing PyTorch environment:

```
python exercises/03_12_next_token_training_loop.py
```

Expected output after the learner implements the loop:

```
PASS: three updates, ordered pre-update losses, and final parameter values
PASS: zero and one step preserve the specified budget and gradient state
PASS: supplied step reused exactly once per update with persistent parameters
PASS: fresh histories and continuation across separate calls
PASS: varied positions, vocabulary dimensions, repeated IDs, and learning rates
PASS: zero learning rate and single-candidate zero loss still record every step
PASS: large-step loss increases remain visible without extra updates
Lesson 03.12 checks passed.
```

Reader questions

Why is the last recorded loss not the final trained loss? Each helper returns the loss from the state before its update. After the last call, parameters have advanced one state beyond the last recorded number. A separate forward measures that new state.

Why return only a list rather than new parameters? The caller still holds the same tensor objects.

In-place updates have already changed their values; the list supplies observations about training.

Why reset gradients within each step? This loop requests the derivative of the current loss, rather than accumulation across earlier steps. The completed helper handles that reset before each new backward pass.

Does three steps mean generating three tokens? It means three parameter-update calls on the supplied input/target pairs. Generating a token is a later prediction operation using parameter values.

The continuation is the completed 03.13: fixed-parameter next-token prediction and the autoregressive idea. The generation loop is completed in 03.14. Contextual attention and practical data/optimization remain later topics.

A continued call is not another block. Arguments inside parentheses can occupy several lines. Their visual indentation groups the arguments; only a new control-flow header such as `for` or `with` opens a nested suite.

03.13 Predict One Next Token

Training changes the model; prediction uses the model as it stands. Given a prompt, we will inspect the distribution at its final position and choose one next ID. This is the smallest inference operation from which a generation loop can be built.

Work through the example before editing 03_13_predict_next_token.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

Inputs, symbols, and returned values

Symbol or value	Exact code name	Type/shape	Meaning
E	`embedding_table`	Floating tensor `[V,D]`	Fixed input vectors for this prediction
x	`context_ids`	`torch.long` tensor `[T]`	Nonempty prompt token IDs
W	`output_weights`	Floating tensor `[D,V]`	Fixed projection weights
b	`output_bias`	Floating tensor `[V]`	Fixed candidate biases
H	`selected_vectors`	Floating tensor `[T,D]`	Prompt lookup rows
Z	`logits`	Floating tensor `[T,V]`	Per-position candidate scores
P	`probabilities`	Floating tensor `[T,V]`	Row-normalized distributions
p	`next_probabilities`	Untracked floating tensor `[V]`	Distribution following the prompt
$\hat{v}$	`next_token_id`	Python `int`	Greedy candidate ID

T counts prompt token occurrences, D vector components, and V vocabulary candidates. Indices are zero-based. Assume positive dimensions, valid IDs, compatible shapes/devices/dtypes, and finite forward scores. The supplied floating parameters are leaves and may require gradients or be frozen; preserve their flags, values, storage, and any stored gradients. The checks construct CPU `float64` tensors.

Return `(next_token_id, next_probabilities)` in that order. The ID is in `[0,V)`, and the probability vector has the same floating dtype/device as the parameters. Preserve the supplied prompt and caller's gradient mode. There are no target labels, loss calculation, backward call, learning rate, or parameter update in this helper.

From the prompt to its next distribution

The completed operations still compute one row per input position:

$$H_{t,d} = E_{x_t,d}, \qquad Z = HW + b, \qquad P_{t,v} = \frac{e^{Z_{t,v}}}{\sum_j e^{Z_{t,j}}}$$

The next token follows the final input position, so select:

$$p_v = P_{T-1,v}, \qquad p = P[T-1,:]$$

In code, `probabilities[-1]` selects that final row and removes the position axis: `[T,V]` becomes `[V]`. The minus one is a row index meaning the last position; it is not a negative token ID.

An earlier row predicts at an earlier position. For a two-token prompt, row zero predicts after its first token, while row one predicts after the second token. The distribution needed to extend the prompt is therefore row one. Calculating several rows does not generate several new future tokens at once.

Greedy selection chooses the largest probability:

$$\hat{v} = \underset{0 \le v < V}{\operatorname{argmax}}\, p_v$$

`next_probabilities.argmax()` returns its index as a scalar integer tensor; `.item()` turns that into a Python integer. The index is the candidate ID, whereas `.max()` on the vector returns the probability value. If several entries tie for the largest value, the first index is selected, so this vector's lowest tied ID wins. Argmax documentation.

In exact arithmetic, softmax preserves the score ordering, so greedy selection can also compare logits. This exercise computes probabilities because the returned distribution is useful for inspection. Sampling from a distribution is a different selection rule and follows later.

Complete hand-calculation example

Use these hand-picked arithmetic parameters; they are not reported as a training outcome. The toy vocabulary has two IDs:

$$E = \begin{bmatrix} 1 & 2 \\ 3 & 1 \end{bmatrix}, \qquad W = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}, \qquad b = [0, 0], \qquad x = [0, 1]$$

Here $T = 2$, $D = 2$, $V = 2$; equal dimension sizes are incidental. Bias is stored as a one-dimensional `[2]` tensor. The prompt uses two positions. Lookup gives:

$$H = \begin{bmatrix} 1 & 2 \\ 3 & 1 \end{bmatrix}, \qquad Z = HW + b = \begin{bmatrix} 1 & 2 \\ 3 & 1 \end{bmatrix}$$

For instance, the final row's candidate-zero score is $3 \times 1 + 1 \times 0 + 0 = 3$, and candidate one's score is $3 \times 0 + 1 \times 1 + 0 = 1$.

The stable softmax intermediates are:

```
row_max = [[2],[3]]
shifted_logits = [[-1,0],[0,-2]]
exp_scores = [[0.3678794412,1],[1,0.1353352832]]
row_sums = [[1.3678794412],[1.1353352832]]
probabilities = [[0.2689414214,0.7310585786],
                 [0.8807970780,0.1192029220]]
```

The last row is:

$$p = \begin{bmatrix} \frac{1}{1+e^{-2}} & \frac{e^{-2}}{1+e^{-2}} \end{bmatrix} \approx \begin{bmatrix} 0.8807970780 & 0.1192029220 \end{bmatrix}, \qquad \hat{v} = 0$$

Return Python integer `0` and the `[2]` probability tensor. ID zero does not mean probability zero. The first row favors ID one, so choosing the first row would produce a different and inappropriate prediction for extending this prompt. Selecting argmax over the entire matrix would flatten both position and candidate axes rather than selecting one candidate from the final row.




Figure 29: The final input row supplies one vocabulary probability vector, and argmax selects its candidate ID.

Figure 03.13-1 — Read columns as candidate IDs and rows as input positions. The first row belongs to the first prompt token. Both teal cells form the final row's `[V]` distribution. The orange border marks its largest entry at candidate zero; the returned ID is `0`, and the whole last row is returned alongside it. Labels are rounded from the calculation above.

Training and inference use different scopes

Operation	Training step, 03.11	This inference helper
Input	Input IDs and observed target IDs	Prompt IDs
Forward tracking	Needed for backward	Entire forward under no-grad
Backward	Computes all parameter gradients	None
Parameter update	Applied after backward	Parameters stay fixed
Stored gradients	Cleared and replaced by the new step	Preserved
Result	Pre-update loss and gradient snapshots	Greedy ID and next distribution

`with torch.no_grad():` disables gradient tracking for the forward computations inside it. It does not permanently change the original parameters' `requires_grad` flags or clear their stored gradients. Keep lookup, projection, softmax, and selection inside this context; return after leaving it so the caller's previous gradient mode is restored. No-grad documentation.

The returned probability vector is untracked, so no extra detach is needed. Parameters can still be used for a later training call; that training helper controls its own gradient clearing. Inference uses model scores to make a choice. Observed target IDs remain the source of supervision during training, rather than replacing training targets with greedy predictions.

A verified bridge from training to byte prediction

The supplied driver also trains a small current-byte model after implementing the training loop, then calls this inference helper. This is a separate example from the two-ID hand calculation.

Item	Portable specification
Training helper code	Section 03.12 companion interface, after implementation
Synthetic data version	`synthetic-byte-aba-v1`: UTF-8 bytes of `aba`
Tokenizer version	`utf8-byte-256-v1`: token ID equals byte value
Training inputs / targets	`[97,98]` / `[98,97]`, giving `a` → `b` and `b` → `a`
Shapes	$V = 256$, $D = 2$, $T = 2$
Initialization	Table zeros except row 97 `[1,2]` and row 98 `[3,1]`; output weights and bias zero
Update budget	Plain gradient descent, `learning_rate=0.1`, `num_steps=100`; 200 supervised-position uses

Item	Portable specification
Evaluation	Fixed same two pairs; mean cross-entropy and greedy next-ID queries without updates

Zero initial output weights/bias imply probability $\frac{1}{256}$ for each candidate and initial mean loss $\ln 256 \approx 5.5451774445$. After the 100 updates, the separate final mean loss is approximately `0.0188148725`. The last pre-update history entry is approximately `0.0190794658`, preserving the distinction from 03.12.

Prompt/query	Greedy next ID after training	Probability assigned to that target
`a`, IDs `[97]`	`98`, byte `b`	`0.9789934959`
`ab`, IDs `[97,98]`	`97`, byte `a`	`0.9837342743`

The full distributions contain 256 candidates. The measured values show learning of these reused synthetic pairs, not held-out text performance. The lookup-plus-head architecture still uses only the current byte. The checks and figures preserve the data, initialization, budget, evaluation, and code provenance; no model-weight file or raw execution log is stored.




Figure 30: True-next-byte probabilities before and after the specified training budget.

Figure 03.13-2 — Inspect the trained prediction on each supplied pair. Each bar is one target's probability from a full 256-candidate distribution, not a two-candidate normalization. Before training it is $\frac{1}{256}$; after training the fixed-parameter query assigns approximately `0.9790` or `0.9837`. Both queries evaluate the training pairs. An independent NumPy calculation reproduced these values.

What autoregressive generation adds next

The current helper returns one ID and leaves the prompt unchanged. A generation caller can append that ID, ask again using the extended prompt, and repeat while keeping parameters fixed. In the hand-picked example:

Prediction call	Prompt before the call	Last-row distribution, approximately	Chosen ID	Extended prompt
1	`[0,1]`	`[0.8808,0.1192]`	0	`[0,1,0]`
2	`[0,1,0]`	`[0.2689,0.7311]`	1	`[0,1,0,1]`
3	`[0,1,0,1]`	`[0.8808,0.1192]`	0	`[0,1,0,1,0]`

This is the autoregressive idea: generated output becomes part of the next input. It changes the token sequence; training changes parameter values. The generation loop and stopping budget are the completed separate assignment in 03.14.

This model's rows are independent lookups, so prompts with the same final ID have the same next distribution even when earlier tokens differ. A contextual model needs to combine the allowed prefix into its final hidden vector; attention and Transformer components are later lessons.

Greedy selection maximizes each immediate choice. It does not necessarily maximize an entire sequence's joint probability: with first-choice probabilities $A = 0.6$, $B = 0.4$ and best continuations `0.51` after A or `0.99` after B, the greedy A path has probability `0.306`, while the B path has `0.396`. This optional probability example explains the local nature of greedy selection; broader decoding methods follow later.

Seven numbered implementation steps

Open `03_13_predict_next_token.py` and find `predict_next_token(embedding_table, context_ids, output_weights, output_bias)`. Replace only the learner placeholder after studying this trace.

1. **Enter inference scope.** At four spaces, write `with torch.no_grad():`. Its colon starts the eight-space body. Steps 2–6 go inside. Original parameter flags and gradients stay unchanged.
2. **Look up the prompt.** At eight spaces, index `embedding_table[context_ids]`, saving `selected_vectors`. Shape `[T,D]`; the example yields `[[1,2],[3,1]]`.
3. **Calculate scores.** At eight spaces, call `compute_logits(selected_vectors, output_weights, output_bias)`, saving `logits`. Shape `[T,V]`; the example yields `[[1,2],[3,1]]`.
4. **Calculate distributions.** At eight spaces, call `softmax_probabilities(logits)`, saving `probabilities`. Reuse the stable completed helper. Each row sums to one.

5. **Select the final row.** At eight spaces, save `probabilities[-1]` as `next_probabilities`. Shape becomes `[V]`; the example vector is approximately `[0.8807970780,0.1192029220]`.
6. **Choose the candidate ID.** At eight spaces, apply `.argmax()` to that vector and `.item()` to its scalar integer result, saving `next_token_id`. The example yields Python int `0`; ties choose the first candidate index.
7. **Return after the context.** At four spaces, return `next_token_id`, then `next_probabilities`. The prompt and parameters remain unchanged. A later generation caller will append chosen IDs.

All tensor construction and helper loading are supplied. Preserve the setup, driver, and earlier implementations. The new core performs inference rather than training or prompt growth.

Run from the repository root in the existing PyTorch environment:

```
python exercises/03_13_predict_next_token.py
```

Expected output after the learner implements the helper:

```
PASS: worked example, last-position distribution, and Python integer selection
PASS: single/multiple positions, repeated IDs, varied shapes, and merged vocabulary IDs
PASS: stable extreme logits and deterministic first-index tie handling
PASS: unchanged parameters, prompts, gradient buffers, trainability, and caller mode
PASS: completed helpers reused under no-grad without retaining a forward graph
PASS: repeatable predictions, independent outputs, and current-token model scope
PASS: completed training loop connects to byte-level next-token inference
Lesson 03.13 checks passed.
```

Reader questions

Why does inference have no target IDs? The next token is the requested prediction. A known target can be used separately to evaluate that prediction, but selecting an output does not require it.

Why preserve existing gradients? Prediction does not need a new gradient or parameter update. Keeping stored buffers lets the caller inspect the preceding training step; the next training call handles clearing them.

Does an ID always decode as one character? A vocabulary entry may contain a byte, a byte fragment, or several bytes. Accumulate entries and use the completed BPE decoder; one selected token need not be a complete UTF-8 character. The byte example's `a` and `b` are complete ASCII bytes. Merged-token IDs may exceed 255 and must not be clamped to the byte-value range.

Does greedy selection change the learned model? It reads the distribution and selects an ID. The supplied parameters stay fixed, and repeating the same prompt produces the same choice under this deterministic helper.

03.14 Autoregressive Generation

Method sources

Autoregressive language modeling and repeated next-token prediction are illustrated by Radford et al., 2019; R25. Our tiny generation loop is a teaching implementation, not a reproduction of GPT-2 or evidence of its language quality.

A single next-token prediction becomes generation when we feed its result back into the input. The sequence grows while the parameters stay fixed. We will trace that recurrence explicitly and postpone text decoding until the collected IDs can be interpreted together.

Work through the example before editing 03_14_autoregressive_generation.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

Inputs and return contract

Exact name	Type/shape	Meaning
`embedding_table`	Floating tensor `[V,D]`	Fixed token vectors, E
`context_ids`	`torch.long` tensor `[T]`	Original nonempty prompt
`output_weights`	Floating tensor `[D,V]`	Fixed vocabulary projection, W
`output_bias`	Floating tensor `[V]`	Fixed candidate biases, b
`num_new_tokens`	Python integer $N \geq 0$	Exact number of newly appended IDs
`generated_ids`	Returned `torch.long` tensor `[T+N]`	Original prompt plus continuation

T is the original prompt length, V the vocabulary size, and D the vector dimension. Assume valid IDs, positive dimensions, compatible shapes/dtypes/devices, and finite forward scores; learner input validation is not assigned. The output uses the prompt's dtype/device and independent storage. Preserve the original prompt, parameter values/storage/trainability/stored gradients, and caller gradient mode.

Return one full ID tensor, not a probability vector, Python list, or tuple. Even $N = 0$ returns an independent copy of the original prompt and makes zero model calls. This lesson stops after exactly N new tokens. End-of-sequence (EOS) stopping, context truncation, and sampling are later topics.

The sequence changes, parameters stay fixed

Let x denote the original `context_ids` prompt, $\theta = (E, W, b)$ the parameters, and $s^{(k)}$ the complete sequence after k new tokens:

$$s^{(0)} = x, \qquad |s^{(k)}| = T + k$$

The completed helper computes $H^{(k)} = E[s^{(k)}]$, $Z^{(k)} = H^{(k)}W + b$, and $P^{(k)} = \text{softmax}(Z^{(k)})$ row by row. Select its final row and greedily choose:

$$p^{(k)} = P^{(k)}[T + k - 1, :], \qquad v_k = \underset{0 \le v < V}{\text{argmax}}\ p_v^{(k)}$$

Append this single ID, for $k = 0, \ldots, N - 1$:

$$s^{(k+1)} = \text{concat}(s^{(k)}, [v_k]), \qquad |s^{(k+1)}| = T + k + 1, \qquad \theta \text{ stays fixed}$$

The final return is $s^{(N)}$, length $T + N$. The next distribution depends on the ID just selected, so the loop feeds its output back in. Asking repeatedly with the unchanged original prompt would repeat the original query instead of generating a continuation.

In this lookup-plus-head model, $p^{(k)} = \text{softmax}(E_{s^{(k)}[-1]}W + b)$: only the final ID affects it. Passing the full prefix establishes the generation interface; attention will later combine information from earlier positions. This tiny model can repeat token transitions but does not yet implement contextual language understanding.

Complete small worked trace

Use the same hand-picked arithmetic parameters as 03.13; these are not claimed to be a training result:

$$E = \begin{bmatrix} 1 & 2 \\ 3 & 1 \end{bmatrix}, \quad W = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}, \quad b = [0, 0], \quad x = [0, 1], \quad T = 2, \quad N = 3$$

The final row after ID `1` has scores `[3,1]`; stable softmax subtracts `3`, giving `[0,-2]`, then divides $[1, e^{-2}]$ by $1 + e^{-2}$. Its probabilities are approximately `[0.8807970780,0.1192029220]`, so select ID `0`.

After ID `0`, scores are `[1,2]`; subtract `2`, giving `[-1,0]`, then divide $[e^{-1}, 1]$ by $e^{-1} + 1$. Its probabilities are approximately `[0.2689414214,0.7310585786]`, so select ID `1`.

Iteration k / call	Current `generated_ids`	Last ID	Final-row probabilities, rounded	Selected ID	After concatenation
`0 / 1`	`[0,1]`	`1`	`[0.8808,0.1192]`	`0`	`[0,1,0]`
`1 / 2`	`[0,1,0]`	`0`	`[0.2689,0.7311]`	`1`	`[0,1,0,1]`
`2 / 3`	`[0,1,0,1]`	`1`	`[0.8808,0.1192]`	`0`	`[0,1,0,1,0]`

Return `tensor([0,1,0,1,0])`, shape `[5]`. The original `context_ids` stays `[0,1]`. Three predictions produced three new IDs `[0,1,0]`, while the complete returned sequence has five IDs. For $N = 1$, return `[0,1,0]`; for $N = 0$, return a fresh `[0,1]` without calling prediction.




Figure 31: Three selected IDs grow the prompt through four sequence states, while parameters stay fixed.

Figure 03.14-1 — Read the upper boxes from left to right. Each arrow appends one selected ID; `+0` means append ID zero, not add numeric zero to existing entries. The lower cards give the corresponding final-row distribution. Three calls increase the length from two to five, and all use the same parameter values.

New syntax: copying and concatenating ID tensors

`generated_ids = context_ids.clone()` makes an independent tensor copy. Ordinary assignment `generated_ids = context_ids` makes another name for the same tensor. Although concatenation later creates new storage, copying first also guarantees an independent zero-budget return. These integer IDs have no gradient graph; cloning here is not a gradient-detachment operation. Clone documentation.

The helper's first tuple entry is a Python integer. To join it to a one-dimensional ID sequence, make a one-dimensional tensor of length one:

```
torch.tensor([next_token_id], dtype=generated_ids.dtype,
             device=generated_ids.device)
```

`[next_token_id]` matters: it gives shape `[1]`. A bare integer would produce a scalar tensor with shape `[]`. `dtype` is the tensor's numeric type, here `torch.long`; `device` describes where the tensor is stored. Matching both keeps the new ID compatible with the current sequence.

`torch.cat((generated_ids, next_id_tensor), dim=0)` concatenates the two tensors along their

existing sequence axis. The inner tuple supplies two tensors; `dim=0` is the only axis of these one-dimensional sequences. In the first iteration it joins `[0,1]` and `[0]` to produce `[0,1,0]`. Save the returned tensor back to `generated_ids`: `cat` does not extend the original tensor in place. Addition would add numeric values; stacking would create a new axis. Concatenation documentation.

The completed `predict_next_token` already puts the full forward under no-grad. This wrapper only handles integer sequences and calls that helper. Do not clear stored gradients, call backward, or update parameters during generation. A later training call still controls its own gradient clearing.

Seven numbered implementation steps

After the formula and trace, open `03_14_autoregressive_generation.py`; replace only the placeholder in `generate_token_ids`.

1. **Copy the prompt.** At four spaces, use `context_ids.clone()` to initialize `generated_ids`. Expected `[0,1]`, shape `[2]`; this also defines the zero-budget result.
2. **Count new tokens.** At four spaces, write a `for` loop over `range(num_new_tokens)`. The colon starts an eight-space body for steps 3–6. `range(3)` supplies counters `0,1,2`; `range(0)` runs no iterations.
3. **Predict from the current sequence.** At eight spaces, call `predict_next_token` with `embedding_table`, `generated_ids`, `output_weights`, and `output_bias` in that order; save `prediction_result`. The second argument changes after each iteration.
4. **Take the selected ID.** At eight spaces, save `prediction_result[0]` as `next_token_id`. The helper returns `(ID, probabilities)`; index `0` selects its Python integer, first `0`, then `1`, then `0` in the example.
5. **Wrap one ID.** At eight spaces, create `next_id_tensor` using `torch.tensor` on `[next_token_id]`, with `dtype=generated_ids.dtype` and `device=generated_ids.device`. Expected shape `[1]`, first value `[0]`.
6. **Append and retain the result.** At eight spaces, concatenate `generated_ids` and `next_id_tensor` with `torch.cat((generated_ids, next_id_tensor), dim=0)`; assign its result back to `generated_ids`. The first new shape is `[3]`.
7. **Return after the loop.** Back at four spaces, return `generated_ids`. Three iterations give five total IDs; zero iterations return the copied prompt. A return inside the body would stop after the first generated token.

Keep the setup and driver unchanged. You write this loop; decoder loading and text checks are supplied. Run from the project root in the existing environment:

```
python exercises/03_14_autoregressive_generation.py
```

Expected output after implementation:

```
PASS: worked trace, full prompt-plus-continuation tensor, and original prompt preservation
PASS: zero/one/multiple-token budgets, varied shapes, repeated IDs, and noncontiguous prompts
PASS: exactly one completed-helper call per new token with the full growing prefix
PASS: fixed parameters, stored gradient objects/values, trainability, and caller mode
```

```
PASS: vocabulary IDs above 255 remain IDs and decode through the matching byte vocabulary
PASS: repeatable independent outputs, continued calls, and accumulated UTF-8 decoding
PASS: completed training -> fixed-parameter generation -> matching decoder: abababa
Lesson 03.14 checks passed.
```

Connecting accumulated IDs to the completed decoder

Generation returns IDs. The caller uses `generated_ids.tolist()` to supply the Python list expected by 02.06's decoder, together with the vocabulary matching the model's IDs. Look up each token's byte contents, join them in order, then decode the combined bytes. Do not assume every token is one byte or convert every ID directly with `bytes([ID])`.

The supplied merged-ID example uses an illustrative vocabulary with `vocab[256]=b"ab"`. IDs `[97, 256,256]` decode to `aabab`: three tokens, five ASCII characters. This separately tests ID preservation above 255; it is not the trained raw-byte example below.

For a raw-byte vocabulary, 中 is bytes `[228,184,173]`, hexadecimal `E4 B8 AD`. `[228,184]` is an incomplete prefix and strict decoding raises `UnicodeDecodeError`; after adding `173`, the full sequence decodes to one character. A budget counts tokens and can stop within a character. Keep the accumulated IDs; byte-safe streaming and policies for unfinished output follow later. Do not silently change the completed strict decoder or claim all generated byte sequences are valid UTF-8.




Figure 32: Two bytes remain an incomplete UTF-8 prefix; joining all three bytes decodes one character.

Figure 03.14-2 — Follow each row from IDs to joined bytes to text. This is a separate decoder

illustration, not generated Chinese capability. The upper row exposes the incomplete suffix; the lower row supplies the full encoding of 中. Decimal ID labels and hexadecimal byte labels describe the same values.

Verified training-to-generation bridge and its scope

Item	Portable specification
Completed training/inference helper code	03.12–03.14 companion interfaces
Data / tokenizer versions	`synthetic-byte-aba-v1` / `utf8-byte-256-v1`
Training pairs	Inputs `[97,98]`, targets `[98,97]`: `a` → `b`, `b` → `a`
Shapes / initialization	$V = 256, D = 2, T = 2$; table zeros except rows 97 `[1, 2]`, 98 `[3,1]`; weights and bias zero
Training budget	Plain gradient descent, learning rate `0.1`, 100 updates, 200 supervised-position uses
Evaluation protocol	Same-pair synthetic verification; prompt `[97]`, six greedy predictions, parameters fixed
Returned IDs / decoded text	`[97,98,97,98,97,98,97]` / `abababa`

The 03.13 record retains the mean-loss and target-probability measurements for this initialization/budget. This continuation verifies the training → prediction → generation → decoder connection. It demonstrates two learned byte transitions on reused synthetic data; it is not held-out language capability evidence. No weights or raw execution logs are stored.

Reader questions, evidence, and next topics

Does one call predict three tokens? Each helper call selects one. Three loop iterations make three calls, with prompt lengths two, three, and four before prediction in the worked example.

Does repeating generation teach the model? It grows the input sequence. The parameters, stored gradients, and trainability stay fixed; training changes parameters using observed targets and losses.

Why return the prompt too? The full sequence is convenient for continued calls and decoding. If only new IDs are needed, the caller can take `generated_ids[context_ids.numel():]`; the exercise still returns the full tensor.

Why is the sample repetitive? This toy learns current-token transitions and uses deterministic greedy choices. It lacks attention over earlier context; varying selection or improving the model/data changes different parts of this pipeline.

Why does a local tensor name match the function name without breaking calls? Assignment binds that name locally inside the function; the module-level name still refers to the function, so outside callers can invoke it normally. This loop does not need a recursive call. A distinct local name such as `generated_ids` makes the tensor's role clearer, but the valid implementation is preserved.

The completed 03.15 introduces temperature and sampling; the completed 03.16 connects sampled generation, followed by completed 03.17 stopping and 03.18 display. Completed 03.19 prepares batches; completed 03.20 connects scores and loss. Contextual attention, caches, and substantive corpus training remain later topics in the roadmap.

03.15 Temperature and Sampling

Always choosing the most likely token is only one way to use a distribution. Temperature changes how concentrated the distribution is, and sampling draws an ID according to its probabilities. We will separate these two operations so randomness has a clear source and a clear meaning.

Work through the example before editing 03_15_temperature_and_sampling.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

Stage A inputs, symbols, and output

Name/symbol	Type/shape	Meaning
`logits`, Z	Floating tensor `[T,V]`	Scores for each position and candidate
`temperature`, τ	Positive finite Python float	Scale applied before softmax
`scaled_logits`	Floating tensor `[T,V]`	Scores divided by temperature
`probabilities`, $P^{(\tau)}$	Returned floating tensor `[T,V]`	Normalized candidate distribution per row

T still counts positions and V counts vocabulary candidates. Use τ for temperature to avoid confusing it with T. Assume $T, V > 0$, finite logits, and finite scaled logits; learner input validation is not assigned. Preserve input values, dtype/device, stored gradients, and the autograd connection, as in the completed 03.09 mathematical helper. The later inference caller controls no-grad scope.

Temperature scales logits before normalization

$$P_{t,v}^{(\tau)} = \frac{\exp(Z_{t,v}/\tau)}{\sum_{j=0}^{V-1} \exp(Z_{t,j}/\tau)}, \qquad \tau > 0$$

Compute `scaled_logits = logits / temperature`, then reuse `softmax_probabilities`. The helper already subtracts each scaled row's maximum before exponentiating. Divide the **logits before softmax**, rather than dividing probabilities afterward: the denominator must normalize the adjusted exponential scores.

The relative probabilities of two candidates explain the effect:

$$\frac{P_{t,a}^{(\tau)}}{P_{t,b}^{(\tau)}} = \exp\left(\frac{Z_{t,a} - Z_{t,b}}{\tau}\right)$$

For a positive score gap, smaller τ magnifies the gap and concentrates probability on the higher score; larger τ reduces relative gaps and makes the distribution flatter. At $\tau = 1$, recover the original softmax. In exact arithmetic, positive division preserves score ordering, so greedy argmax keeps the same winner and ties. Temperature affects selection frequencies when a sampling policy uses the resulting distribution; it does not by itself turn argmax into sampling.

As τ approaches zero from above, probability concentrates on the largest scores; a unique maximum gets limiting probability one, while equal maxima share the limiting mass. As τ grows without bound, finite-score candidates approach equal probabilities $1/V$. These are mathematical limits, not a reason to divide by zero. This exercise accepts strictly positive temperature; a future caller can define temperature zero as a separate greedy branch. Floating-point rounding can create zero probabilities or ties at extreme scales.

Complete temperature calculation

Use the hand-picked two-position tensor `logits=[[3,1],[1,3]]`, with $T = 2, V = 2$. These are arithmetic inputs, not a training result. For `temperature=0.5`:

```
scaled_logits = [[6,2],[2,6]]
row_max = [[6],[6]]
shifted_logits = [[0,-4],[-4,0]]
exp_scores = [[1,0.0183156389],[0.0183156389,1]]
row_sums = [[1.0183156389],[1.0183156389]]
probabilities = [[0.9820137900,0.0179862100],
                 [0.0179862100,0.9820137900]]
```

The first row's candidate-zero probability is:

$$p_0^{(\tau)} = \frac{e^{3/\tau}}{e^{3/\tau} + e^{1/\tau}} = \frac{1}{1 + e^{-2/\tau}}$$

Temperature	First scaled row	ID 0 probability	ID 1 probability	Greedy ID
`0.5`	`[6,2]`	`0.9820137900`	`0.0179862100`	`0`
`1`	`[3,1]`	`0.8807970780`	`0.1192029220`	`0`
`2`	`[1.5,0.5]`	`0.7310585786`	`0.2689414214`	`0`

The second row reverses those probabilities and favors ID `1` at all three settings. Return all position rows, shape `[2,2]`; the later inference caller chooses the final row. Lower temperature does not train different parameter values, and higher temperature does not guarantee better text quality.




Figure 33: Temperature changes candidate probabilities while the greedy winner remains the same.

Figure 03.15-1 — Read the horizontal axis as temperature and the vertical axis as probability. Blue is candidate ID zero, orange ID one. Bars show the three table settings; curve points mark the same values. The scores `[3,1]` stay fixed. Blue stays higher, explaining why argmax alone selects ID zero throughout.

Optional autograd review: temperature is fixed during differentiation. The chain rule gives $\partial P_{t,a}/\partial Z_{t,b} = (1/\tau)P_{t,a}(\delta_{ab} - P_{t,b})$, where δ_{ab} is one for equal indices and zero otherwise. The supplied check uses this analytic derivative to verify that Stage A remains connected. A mathematical probability helper preserves the graph; an inference wrapper places the full forward under no-grad, as in 03.13.

Stage B: sample one ID from one probability row

`sample_token_id(probabilities, generator)` accepts a floating tensor `[V]`, a single normalized candidate distribution, and a caller-supplied `torch.Generator`. Assume finite nonnegative entries with positive sum, and a compatible generator device on a supported backend. Return one Python integer in `[0,V)`. Preserve probability values/storage/trainability/stored gradients and caller gradient mode. The supplied generator's state advances for this draw; the global random stream remains unchanged.

Let X denote the sampled token ID. The symbol $\sim$ means "is drawn from"; Categorical(p) is the discrete distribution over IDs with probabilities p_v:

$$X \sim \text{Categorical}(p), \qquad \Pr(X = v) = p_v$$

Compare greedy and sampling on the separate three-candidate example `probabilities=[0.6,0.3, 0.1]`. Greedy chooses ID `0` every time. Sampling chooses ID `0`, `1`, or `2` with probabilities `0.6`, `0.3`, and `0.1`. Larger probability means a higher chance, not certainty. Adjacent samples may repeat; a single sample does not estimate the frequency.

A complete probability illustration divides a unit interval:

Region for a hypothetical uniform draw u	Selected ID	Region length
$0 \le u < 0.6$	`0`	`0.6`
$0.6 \le u < 0.9$	`1`	`0.3`
$0.9 \le u < 1$	`2`	`0.1`

Thus $u = 0.2$ illustrates ID `0`, $u = 0.75$ ID `1`, and $u = 0.95$ ID `2`. The ID-one example shows a valid sample that is not argmax. These numbers explain the distribution; they do not claim that PyTorch implements this diagram literally or that a particular seed produces those draws.




Figure 34: Probability regions illustrate why sampling can select a candidate below the maximum.

Figure 03.15-2 — Region widths equal candidate probabilities. Arrows mark three hypothetical draws in the three regions. This is a separate `[3]` probability example, not the two-candidate temperature calculation.

Use `torch.multinomial(probabilities, num_samples=1, generator=generator)`. For a `[V]` input, it returns a `[1]` integer tensor containing a sampled **index**. `.item()` extracts that index as a Python integer. Its general API also accepts unnormalized nonnegative weights; this exercise supplies normalized probabilities. One sample per call does not prohibit repeated IDs across later calls, even with the default `replacement=False`: that option concerns multiple draws within one invocation. Multinomial documentation.

Seed once, then reuse the random stream

A generator stores pseudorandom state. The supplied setup creates it and calls `.manual_seed(seed)` once; each sampling call consumes the continuing stream. Passing `generator=generator` selects that stream. Do not reseed inside `sample_token_id`, create a replacement generator, or change global randomness. Generator documentation.

Two generators with the same initial state, inputs, call order, and compatible runtime reproduce a stream. Continuing one generator does not mean every draw differs; resetting its seed for every call would restart the stream. Exact sample sequences are not promised across library versions or backends. The checks compare to the reference operation within the current runtime and separately inspect many-draw frequencies, allowing finite-sample variation.

Implementation plan: two small stages

All core statements use four spaces. Neither helper needs a loop; repetition belongs to generation. Keep the supplied loader and driver intact.

1. **A1 — Scale the scores.** In `temperature_probabilities`, divide `logits` by `temperature`, saving `scaled_logits`. Shape remains `[T,V]`; at `0.5`, the example becomes `[[6,2],[2,6]]`. Use a new result and preserve the original input.
2. **A2 — Reuse normalization.** Call `softmax_probabilities(scaled_logits)` and save `probabilities`. The loaded completed function handles stable row-wise normalization; first row becomes approximately `[0.9820,0.0180]`.
3. **A3 — Return the tensor.** Return `probabilities`, keeping its graph, dtype/device, and `[T, V]` shape. Do not use `.item()` or no-grad in this mathematical helper. Check Stage A before continuing.
4. **B1 — Draw one candidate.** In `sample_token_id`, call `torch.multinomial` with `probabilities`, `num_samples=1`, and `generator=generator`; save `sampled_ids`. Its shape is `[1]`. Select by probability, not argmax.
5. **B2 — Extract the ID.** Use `sampled_ids.item()` to obtain `next_token_id`, a Python integer. It is an index, not the chosen probability value.
6. **B3 — Return the integer.** Return `next_token_id`. Probability inputs stay fixed and the supplied stream advances. Do not seed inside the function.

Run from the project root in the existing environment, in this order:

```
python exercises/03_15_temperature_and_sampling.py --check temperature
```

```
python exercises/03_15_temperature_and_sampling.py --check sample
python exercises/03_15_temperature_and_sampling.py --check all
```

The individual commands end with `Lesson 03.15 temperature checks passed.` and `Lesson 03.15 sample checks passed.`. With both stages implemented, the full output is:

```
PASS: temperature worked example, row-wise normalization, and unchanged greedy ordering
PASS: positive temperatures, extreme/tied scores, varied shapes/dtypes, and shift invariance
PASS: completed stable helper reused with connected analytic gradients and preserved
 ↪  inputs/buffers
PASS: Python ID return, zero-probability exclusion, merged IDs, and input/gradient/mode
 ↪  preservation
PASS: supplied random stream matches one categorical draw per call without global RNG changes
PASS: reproducible caller-seeded streams and many-draw frequencies consistent with probabilities
PASS: fixed-parameter logits -> temperature -> last row -> sampling -> growing-prefix pipeline
Lesson 03.15 checks passed.
```

Connection, reader questions, and evidence

The supplied final check uses hand-picked `E=[[1,2],[3,1]]`, identity W, zero `b`, prompt `[0,1]`, temperature `2`, six new IDs, and generator seed `137`. A caller places lookup/projection/temperature under no-grad, selects the final probability row, samples one ID, and appends it. It matches a reference stream, produces eight total IDs, and preserves parameters. The original greedy predictor and generation loop stay intact; the completed 03.16 connects sampled generation, followed by EOS stopping in 03.17 and continuation decoding in 03.18.

Why not divide probabilities by temperature? That does not implement the exponential score scaling or, by itself, preserve a sum of one. Temperature acts before softmax.

Can sampling choose a zero-probability token? No. A smaller positive probability can be selected; zero probability cannot. Merged token IDs above 255 remain vocabulary indices.

Is random selection uniform? Uniform sampling gives equal chances. Here chances follow the supplied distribution. Higher temperature makes the distribution flatter, but finite-temperature sampling is not generally uniform.

Does this improve what the model knows? Parameters stay fixed. Selection changes how a distribution is used; contextual architecture, data, and training determine different parts of model behavior.

03.16 Sampled Autoregressive Generation

We can now replace the greedy choice in the generation loop with a sampled choice. The recurrence stays familiar, but the random stream must continue across steps. We will also keep tensor type and device consistent as the prompt grows.

Work through the example before editing 03_16_sampled_generation.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

Exact inputs and returned values

Name	Type/shape	Meaning
`embedding_table`, E	Floating tensor `[V,D]`	Fixed token vectors
`context_ids`, x	`torch.long` tensor `[T]`	Original nonempty prompt
`output_weights`, W	Floating tensor `[D,V]`	Fixed vocabulary projection
`output_bias`, b	Floating tensor `[V]`	Fixed candidate biases
`num_new_tokens`, N	Python integer $N \geq 0$	Exact number of newly appended IDs
`temperature`, τ	Positive finite Python float	Logit scaling before softmax
`generator`	Caller-owned `torch.Generator`	Already seeded pseudorandom stream
`generated_ids`	Returned `torch.long` tensor `[T+N]`	Prompt plus sampled continuation

T is prompt length, V vocabulary size, and D vector dimension. Assume valid IDs, compatible shapes, dtypes and devices and supported generator, and finite logits/scaled logits; input validation is not assigned. Return a fresh full ID tensor on the prompt's device, including the original prompt. Preserve original prompt values and parameter values/storage/trainability/stored gradients, caller gradient mode, and global random stream. The supplied generator advances through one completed sampler call per new ID.

For $N = 0$, return an independent prompt copy without any projection, temperature, or sampling calls and without consuming the generator state. The positive-temperature formula applies here; no zero-temperature branch, EOS stop, or context truncation is added. The caller still decodes IDs through the matching tokenizer vocabulary.

Sampling inside the recurrence

Let $s^{(k)}$ be the full sequence after k generated IDs, with $s^{(0)} = x$ and $|s^{(k)}| = T + k$. For each $k = 0, \ldots, N-1$:

$$H^{(k)} = E[s^{(k)}], \qquad Z^{(k)} = H^{(k)}W + b$$

The temperature helper normalizes vocabulary columns independently per position:

$$P^{(k)}_{t,v} = \frac{\exp(Z^{(k)}_{t,v}/\tau)}{\sum_{j=0}^{V-1} \exp(Z^{(k)}_{t,j}/\tau)}, \qquad p^{(k)} = P^{(k)}[T + k - 1, :]$$

Sample one ID, then feed that output back into the next input:

$$v_k \sim \text{Categorical}(p^{(k)}), \qquad s^{(k+1)} = \text{concat}(s^{(k)}, [v_k])$$

Return $s^{(N)}$, length $T + N$. The ID sequence and random-stream state change; E, W, b and the temperature remain fixed. The same supplied generator is passed onward instead of being reset each iteration.

`compute_logits` returns `[T+k,V]`; `temperature_probabilities` preserves that shape; `probabilities[-1]` reduces it to `[V]`; `sample_token_id` returns a Python integer. A `[1]` integer tensor then extends the one-dimensional ID sequence. Each iteration selects one token, so three new tokens require three complete cycles.




Figure 35: Lookup, scores, temperature, final-row selection, sampling, and append form one repeating inference cycle.

Figure 03.16-1 — Follow the upper row rightward, then the lower row leftward. The left upward arrow enters the next iteration, whose index is now $k + 1$; its length is the previous $T + k + 1$. Only the final distribution is sampled. Orange marks the ID selection; parameter values stay fixed throughout.

The current lookup-plus-head model still uses only the last input ID for its next distribution. Passing the growing full prefix establishes the interface; contextual attention follows later. Stochastic output does not itself add contextual understanding or train new knowledge.

Complete worked example with hypothetical choices

Reuse the hand-picked arithmetic model from Lesson 03.13:

$$E = \begin{bmatrix} 1 & 2 \\ 3 & 1 \end{bmatrix}, \quad W = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}, \quad b = [0, 0], \quad x = [0, 1], \quad T = 2, \quad \tau = 2, \quad N = 3$$

The first forward has `selected_vectors=[[1,2],[3,1]]`; the logits have those same values because W is identity and `b` is zero. Temperature scaling gives `[[0.5,1],[1.5,0.5]]`. Its final row subtracts `1.5`, yielding `[0,-1]`; exponentials $[1, e^{-1}]$ normalize to:

$$p^{(0)} \approx [0.7310585786, 0.2689414214]$$

For an illustrative unit-interval draw $u = 0.2$, choose ID `0` and append it, producing `[0,1,0]`. The next final ID is zero, so its scores are `[1,2]`; after scaling and stable subtraction they become `[-0.5, 0]`, with exponentials $[e^{-0.5}, 1]$:

$$p^{(1)} \approx [0.3775406688, 0.6224593312]$$

An illustrative $u = 0.3$ lies below the first cumulative boundary `0.3775`, so choose ID `0` again, even though ID `1` has larger probability. This produces `[0,1,0,0]`. With the same final ID, the next distribution is unchanged; illustrative $u = 0.8$ selects ID `1`.

Call	Current sequence	Final-row probabilities, rounded	Illustrative u	Sampled ID	Extended sequence
`1`	`[0,1]`	`[0.7311,0.2689]`	`0.2`	`0`	`[0,1,0]`
`2`	`[0,1,0]`	`[0.3775,0.6225]`	`0.3`	`0`	`[0,1,0,0]`
`3`	`[0,1,0,0]`	`[0.3775,0.6225]`	`0.8`	`1`	`[0,1,0,0,1]`

Return `tensor([0,1,0,0,1])`, shape `[5]`, **for these hypothetical choices**. They explain recurrence and valid non-greedy selection, not a promised PyTorch seed trace or its internal algorithm. The real sampler consumes the caller's generator. The supplied checks separately compare actual draws and final generator state with a same-runtime reference.




Figure 36: Three hypothetical sampled choices extend the sequence, with the second selecting a smaller-probability ID.

Figure 03.16-2 — Each rightmost sequence becomes the next row's input. The orange second choice is valid because ID zero has positive probability. It changes the next input, and thus which scores the next call uses. A greedy trajectory for this model would instead return `[0,1,0,1,0]`; the third-call inputs of those two trajectories differ.

Full no-grad scope and nested indentation

The mathematical temperature helper from 03.15 preserves autograd when used normally. This generation caller puts the entire lookup/projection/temperature calculation under `torch.no_grad()`. It does not permanently alter parameter flags, clear gradients, or update weights. After the context ends, the previous caller mode is restored. No-grad documentation.

There are two nested blocks: the no-grad context contains the loop, and the loop contains its operations. Each block adds four spaces:

Indentation	Location	Statements
Four spaces	Function body	Copy prompt; enter no-grad; final return
Eight spaces	Inside no-grad	`for step in range(num_new_tokens):`

Indentation	Location	Statements
Twelve spaces	Inside context and loop	Lookup, scores, probabilities, final row, sample, tensor creation, append

The colon in `with` starts the temporary gradient context; the colon in `for` starts the repeated body. Return at four spaces, after both blocks. Returning inside the loop would stop after the first token; leaving forward tracking enabled and detaching only at the end would still construct unnecessary intermediate graphs.

Ten guided implementation steps for review

Do these after finishing 03.15 and reviewing the formula and complete trace. Replace only the core placeholder in `generate_sampled_ids`; preserve setup, driver, and earlier implementations.

1. **Copy the prompt.** Four spaces: initialize `generated_ids` using `context_ids.clone()`. First shape `[2]`, values `[0,1]`; it also handles the zero-budget result.
2. **Enter inference scope.** Four spaces: write `with torch.no_grad():`. All iterations go inside this context.
3. **Count newly generated IDs.** Eight spaces: loop over `range(num_new_tokens)`. Steps 4–9 are at twelve spaces, inside both blocks. For three new tokens, the counter visits `0,1,2`.
4. **Lookup the current sequence.** Twelve spaces: obtain `selected_vectors` from `embedding_table[generated_ids]`. First shape `[2,2]`, then `[3,2]`, then `[4,2]` in the example.
5. **Compute scores.** Twelve spaces: call `compute_logits(selected_vectors, output_weights, output_bias)`, saving `logits`. Shape `[T+k,V]`; first final row `[3,1]`.
6. **Apply the supplied temperature.** Twelve spaces: call `temperature_probabilities(logits, temperature)`, saving `probabilities`. Reuse the completed helper; first final row approximately `[0.7311,0.2689]`.
7. **Select the next distribution.** Twelve spaces: save `probabilities[-1]` as `next_probabilities`, shape `[V]`.
8. **Sample one ID.** Twelve spaces: call `sample_token_id(next_probabilities, generator)`, saving `next_token_id`. Pass the same generator each time, without reseeding or replacing it.
9. **Wrap and append the ID.** Twelve spaces: create `next_id_tensor` using `torch.tensor([next_token_id], dtype=generated_ids.dtype, device=generated_ids.device)`. Then concatenate with `torch.cat((generated_ids, next_id_tensor), dim=0)` and assign its new tensor back to `generated_ids`. First extended shape `[3]`.
10. **Return after both blocks.** Four spaces: return `generated_ids`, shape `[T+N]`. For the illustrative choices it is `[0,1,0,0,1]`; for zero budget it is a fresh `[0,1]` with no helper calls or random draws.

The generator is supplied and already seeded by the caller. Consecutive draws can repeat. Continuing generation with the same generator state and returned sequence should agree with one longer call using the same initial state, inputs, policy, and compatible runtime. Reseeding every iteration would restart the stream. Generator documentation.

After the current formula/example walkthrough and implementation, run from the project root:

```
python exercises/03_16_sampled_generation.py
```

Expected output after implementation:

```
PASS: worked recurrence with scripted valid choices, including a non-greedy selection
PASS: positive temperatures, exact budgets, varied shapes/prompts, and reference random streams
PASS: completed helpers reused once per token in order under full no-grad with growing prefixes
PASS: fixed parameters, stored gradients, original prompts, global RNG, and caller-mode
 ↪  preservation
PASS: zero budget returns an independent prompt without forward calls or random-state consumption
PASS: same-state replay and continued calls agree with one longer call while outputs stay
 ↪  independent
PASS: single-candidate generation and merged IDs decoded through the matching vocabulary
Lesson 03.16 checks passed.
```

Reader questions

Why not call the completed greedy predictor? Its selection rule is argmax. This wrapper needs the completed score and temperature helpers followed by the sampling helper; keep the earlier greedy path intact.

Does one sampler call return all future tokens? It selects one ID. The generation loop makes exactly N calls, growing the prefix once per call.

Does the caller's seed specify the hypothetical u values above? No. Those numbers explain valid choices. Real sample traces depend on the generator state, inputs, call order, and runtime; the tests use a matching reference rather than a cross-version promised list.

How is the result displayed as text? Use the matching byte vocabulary and 02.06 decoder on accumulated IDs. The supplied illustrative merged vocabulary maps ID `256` to `b"ab"`; IDs `[97,256,256]` decode to `aabab`. Tokens can span multiple bytes, and a token budget can stop inside a UTF-8 character; strict decoding behavior remains unchanged.

These are hand-picked arithmetic and scaffold-verification recipes, not training experiments. The continuation 03.17 covers EOS and a maximum new-token limit; contextual attention and substantive data/training remain later work.

03.17 EOS and Generation Stopping

A generation loop needs an answer to a practical question: when is it finished? A token budget limits the work, while a newly generated EOS can end it earlier. We will make both stopping conditions explicit without losing the marker that explains why generation stopped.

Work through the example before editing 03_17_generation_stopping.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

Inputs, outputs, and the chosen policy

Exact name	Type/shape	Meaning
`embedding_table`	Floating tensor `[V,D]`	Fixed token vectors
`context_ids`	`torch.long` tensor `[T]`	Original nonempty prompt
`output_weights`	Floating tensor `[D,V]`	Fixed vocabulary projection
`output_bias`	Floating tensor `[V]`	Fixed candidate biases
`max_new_tokens`	Python integer $M \geq 0$	Maximum number of newly appended IDs
`temperature`	Positive finite Python float	Sampling temperature passed to 03.16
`generator`	Caller-owned `torch.Generator`	Continuing random stream
`eos_token_id`	Python `int` in `[0,V)`, or `None`	Configured stop marker, or disabled stopping

Assume valid IDs, compatible shapes/dtypes/devices/generator, and finite scores/scaled scores. Input validation is not assigned. Return `(generated_ids, stop_reason)`:

- `generated_ids`: fresh `torch.long` tensor `[T+L]`, including the original prompt and any generated EOS, where $0 \leq L \leq M$.
- `stop_reason`: Python string `"eos"` when a newly generated EOS ends the loop; otherwise `"length"` when the maximum budget is exhausted.

Preserve original prompt values, parameter values/storage/trainability/stored gradients, caller gradient mode, and global randomness. Pass the same supplied generator through each one-token helper call. Stop without another draw once EOS has been appended. With zero budget, return an independent prompt copy and `"length"`, with zero helper calls and unchanged generator state.

Only **newly generated** IDs trigger this request's EOS stop. An EOS in the original prompt, including its final ID, does not itself end the new continuation. This explicit exercise policy keeps prompt interpretation separate from stopping the new output. EOS selected on the final permitted draw has reason `"eos"`, even though the length budget is also reached.

Actual length is bounded by two stopping events

Let $v_0, v_1, \ldots$ denote the new IDs that would be sampled using the same continuing policy. Let e be the configured EOS. Define the first new EOS position, counted from one:

$$K = \inf\{k + 1 \mid k \geq 0,\ v_k = e\}$$

The inf notation selects the smallest matching positive position here. Take $K = \infty$ if EOS is disabled (`None`) or there is no new EOS. With maximum budget M:

$$L = \min(M, K), \qquad |\text{generated_ids}| = T + L$$

The stopping reason is:

$$r = \begin{cases} \text{eos}, & K \le M \\ \text{length}, & K > M \end{cases}$$

Here T is original prompt length, M is the maximum number of new tokens, and L is the actual number generated, including EOS if it ends the output. The maximum does not count existing prompt tokens. For zero budget, no new ID is drawn, so $L = 0$ and reason is `"length"`.

The recurrence still appends before checking:

$$s^{(k+1)} = \text{concat}(s^{(k)}, [v_k])$$

This retains the selected EOS in the returned IDs and makes the stop event inspectable. Text-display policy can then handle the control marker separately.

What an EOS ID means

EOS is a special control token whose meaning is defined by the tokenizer/model protocol. It is not a universal numeric ID or a UTF-8 end byte. The small example below defines `0 -> a`, `1 -> b`, `2 -> EOS`; this differs from the raw-byte vocabulary where ID `2` represents byte value `2`.

For an existing contiguous vocabulary $0, \ldots, V_{\text{old}} - 1$, one possible extension reserves previously unused ID V_{old} and increases candidate count to $V_{\text{old}} + 1$. The embedding table gains a row, the output head a column and bias entry, and training examples must teach that EOS follows the intended sequence boundary. Do not overwrite an existing merged-token ID or assume adding a stopping condition teaches the model when to stop.

The existing educational BPE byte dictionaries do not yet implement a complete special-token serialization/segmentation policy. This assignment supplies an explicit illustrative EOS configuration; general tokenizer integration remains later work. The decoder stays strict and receives ordinary token byte mappings after the caller handles the special marker.

Complete small worked example

Use a hand-picked, three-candidate model with vocabulary `illustrative-ab-eos-v1`:

$$E = \begin{bmatrix} 1 & 0 \\ 0 & 1 \\ 0 & 0 \end{bmatrix}, \quad W = \begin{bmatrix} 0 & 1000 & 0 \\ 0 & 0 & 1000 \end{bmatrix}, \quad b = [0, 0, 0], \quad x = [0], \quad M = 5, \quad \tau = 1, \quad e = 2$$

Input ID zero selects vector `[1,0]`. Its scores are `[0,1000,0]`; stable subtraction gives `[-1000,0,-1000]`. In the supplied `float64` computation, the small exponentials underflow to zero, producing `[0,1,0]`, so the first draw selects ID `1`.

Input ID one selects vector `[0,1]`. Scores are `[0,0,1000]`, with shifted values `[-1000,-1000,0]`. Computed probabilities become `[0,0,1]`, selecting EOS ID `2`. These exact computed one-hot rows force a test path; mathematically the tiny exponentials are positive. The parameters are not reported as a training outcome.

Helper call	Prompt before call	Requested new IDs	Newly appended ID	Full sequence	Action
`1`	`[0]`	`1`	`1`	`[0,1]`	Continue: new ID is not EOS
`2`	`[0,1]`	`1`	`2`	`[0,1,2]`	Set reason to `"eos"`, then break
`3–5`	—	—	—	—	Never called

Return `(tensor([0,1,2]), "eos")`. Here $T = 1$, $K = 2$, $L = \min(5, 2) = 2$, and total length is `3`. The EOS ID is included. Ordinary display IDs `[0,1]` decode to `ab` through `{0:b"a",1:b"b"}` after the caller separates the final marker.




Figure 37: Only two new IDs are generated even though the budget permits five, and the EOS is retained.

Figure 03.17-1 — Count the generated boxes, not the maximum slots. Orange is the newly appended EOS. Gray slots are unused budget and do not consume helper calls or randomness. The original prompt contributes one more returned ID.

Setting on the same forced path	Actual result	Reason
`max_new_tokens=0`	`[0]`, no draw	`"length"`
`max_new_tokens=1`	`[0,1]`	`"length"`
`max_new_tokens=2`	`[0,1,2]`	`"eos"`, even on the last allowed draw
`max_new_tokens=5`	`[0,1,2]`	`"eos"`, before budget exhaustion

With `eos_token_id=None`, EOS stopping is disabled and the full budget is used. If the configured marker is never newly sampled, the length limit also ends generation. The sequence after a disabled EOS need not follow the forced two-step prefix indefinitely; further draws still use the model's distributions.

New control-flow syntax before implementation

`None` means EOS stopping is disabled by this function's contract. `eos_token_id is not None` tests whether an ID was configured. Do not substitute truthiness: integer EOS ID `0` is valid, but `bool(0)` is false.

`next_token_id == eos_token_id` compares values; `=` assigns a value. `and` requires both conditions to be true and short-circuits its right side when the left is false. `if condition:` executes its indented body only when the condition is true. The stop condition is configuration present **and** newly sampled ID equal to the configured EOS.

`break` exits the nearest loop immediately. Execution continues after that loop, where the final return belongs; `break` does not itself return from the function. Python break reference.




Figure 38: The budget controls loop entry, and a newly appended EOS determines the early exit.

Figure 03.17-2 — Budget and EOS control different points. The `for` loop already handles the maximum count; the diagram is conceptual and does not ask for an additional while loop. Generate and append one ID, then test the new EOS. A positive test sets `"eos"` and breaks; otherwise the next loop iteration proceeds if budget remains.

Eight implementation steps for generate_until_eos

Implement `generate_until_eos` in `03_17_generation_stopping.py` using the inputs listed above. All forward and sampling work remains in the completed `generate_sampled_ids`. This wrapper performs integer and control operations; no separate parameter update, backward, or gradient clearing is needed. It can reuse the helper's no-grad scope without adding a new outer context.

1. **Copy the prompt.** Four spaces: initialize `generated_ids` with `context_ids.clone()`. Example `[0]`, shape `[1]`; this also defines a fresh zero-budget return.
2. **Initialize the default reason.** Four spaces: set `stop_reason` to `"length"`. EOS detection will replace it only when that event occurs.
3. **Loop within the maximum.** Four spaces: use `for step in range(max_new_tokens):`. Its body uses eight spaces. `range(5)` permits five iterations, while `break` may end it after two.
4. **Generate one new ID.** Eight spaces: call `generate_sampled_ids` with `embedding_table`, `generated_ids`, `output_weights`, `output_bias`, literal `1`, `temperature`, `generator` in that order. Save the full returned tensor back into `generated_ids`; first result `[0,1]`. The literal `1` is the per-call new-token count.
5. **Extract the newly appended ID.** Eight spaces: save `generated_ids[-1].item()` as `next_token_id`. First `1`, then `2`; this is a Python integer.
6. **Test the stop condition.** Eight spaces: write an `if` combining `eos_token_id is not None` and `next_token_id == eos_token_id`, joined with `and`. The colon opens a twelve-space body.
7. **Record EOS and exit the loop.** Twelve spaces: set `stop_reason` to `"eos"`, then put `break` at the same indentation. EOS has already been appended; do not make another generation call.
8. **Return after the loop.** Back at four spaces: return `generated_ids, stop_reason`. Example `(tensor([0,1,2]), "eos")`; zero budget returns the copied prompt and `"length"`.

Complete and review 03.16 first. During the next walkthrough, use this exact file/function/parameter naming. Preserve the supplied setup and driver. From the project root:

```
python exercises/03_17_generation_stopping.py
```

Expected output after implementation:

```
PASS: worked EOS path, appended stop marker, two new IDs, and eos reason
PASS: zero/short/full budgets, disabled or absent EOS, and eos priority on the final allowed draw
PASS: completed generation helper reused for one new ID per growing-prefix call with no call
 ↪  after EOS
PASS: stochastic EOS-or-budget stopping matches a same-runtime reference and generator state
PASS: EOS ID zero is valid and only newly generated IDs trigger stopping
PASS: fresh returns, fixed parameters/gradients, caller/global RNG preservation, and zero-budget
 ↪  independence
```

```
PASS: caller separates the illustrative EOS control marker before matching-vocabulary byte
 ↪  decoding
Lesson 03.17 checks passed.
```

Reader questions

Why keep EOS in the returned IDs? It records which sampled event ended the request. The caller can remove the special marker for display while retaining the original IDs and reason for inspection.

Does a maximum guarantee a complete UTF-8 character? No. The maximum counts tokens. Ordinary token byte contents still need accumulated strict decoding; output handling and byte-safe streaming remain separate from these stop controls.

Why not generate all M IDs and cut at the first EOS afterward? That consumes extra inference and random draws after the stop event. This exercise stops immediately, preserving the stream position after the actual L draws.

Does adding the if teach EOS behavior? No. The stopping wrapper responds to a configured ID. The model needs appropriate training targets and a matching special-token protocol to learn when that ID should have high probability.

This is a hand-picked arithmetic/control example rather than a training experiment. Stopping, special-token integration, contextual attention, and substantive data/training remain distinct parts of the learning path.

03.18 Decode the Generated Continuation

The generated sequence contains both the prompt and its continuation, and it may end with a control token. Displaying only the new text requires selecting the right IDs before interpreting their bytes. Token counts, byte boundaries, and text boundaries each play a different role in this small adapter.

Work through the example before editing 03_18_decode_continuation.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

Exact inputs and returned value

Name	Type	Meaning
`generated_ids`, g	One-dimensional `torch.long` tensor `[T+L]`	Full IDs returned by generation, including the prompt
`prompt_length`, T	Python integer, $0 \leq T \leq \lvert g \rvert$	Number of prompt **tokens**, not bytes or characters
`vocab`	`dict[int, bytes]`	Matching ordinary token ID to original byte contents

Name	Type	Meaning
`eos_token_id`, e	Python integer or `None`	Separate EOS control ID; `None` disables marker removal
Returned `text`	Python `str`	New ordinary-token text, excluding the prompt and trailing EOS

Assume a valid tensor shape and prompt length. Configured EOS is separate from ordinary keys in `vocab`. Under the 03.17 output protocol, a newly generated EOS is only at the end. This exercise removes one trailing marker; it does not scan for arbitrary control IDs or silently discard unknown IDs. Marker IDs and the byte vocabulary must come from the same agreed tokenizer/model protocol.

Preserve `generated_ids`, `vocab`, caller gradient mode, and random streams. Empty ordinary output returns `""`. Unknown ordinary IDs raise `KeyError` through the decoder; invalid or incomplete UTF-8 raises `UnicodeDecodeError`. These errors remain visible and are part of the exercise contract.

Select IDs, then interpret their bytes

Let g contain T prompt tokens and L new IDs. Its new suffix is:

$$c = g[T:], \qquad |c| = L$$

Let $\delta = 1$ exactly when $L > 0$, EOS is configured, and $c_{L-1} = e$; otherwise $\delta = 0$. Remove only that final control marker:

$$q = \begin{cases} c[:-1] & \delta = 1 \\ c & \delta = 0 \end{cases}, \qquad m = |q| = L - \delta$$

For the remaining ordinary IDs, look up and concatenate their bytes in order:

$$B = \operatorname{concat}_{i=0}^{m-1} \operatorname{vocab}[q_i], \qquad \text{text} = \operatorname{UTF8Decode}_{\text{strict}}(B)$$

If $m = 0$, the empty concatenation is `b""`, which decodes to `""`. The existing `decode_bpe` already performs the last two operations. `decode_continuation` handles token selection and control-marker separation before calling it.

This path does not convert IDs directly with `bytes(ids)`. A merged ID such as 256 can represent several bytes and cannot itself be one raw byte. EOS is a control event, not ordinary byte content. Neither token count nor byte count determines the number of decoded characters.




Figure 39: Prompt selection, trailing EOS removal, vocabulary lookup, and joined UTF-8 decoding.

Figure 03.18-1 — Read downward from the full IDs. Gray excludes the prompt; orange identifies EOS; teal retains ordinary byte contents. The two partial Chinese byte chunks become valid only after joining. Three ordinary tokens produce five bytes and three Unicode code points in this example.

Complete worked example

Use the hand-built artifact `fixture-bpe-utf8-v1`, supplied for arithmetic and decoder practice, not produced by a claimed training run. All base IDs `0..255` map to `bytes([id])`. Its extra ordinary entries and separate control ID are:

```
vocab[256] = b"ab"
vocab[257] = bytes([228,189])
eos_token_id = 258
generated_ids = tensor([97,256,257,160,258])
prompt_length = 1
```

The prompt is one token, ID 97, whose ordinary content is `b"a"`. First, `.tolist()` gives `[97,256,257,160,258]`. The slice starting at index one gives `[256,257,160,258]`. The list is nonempty, EOS is configured, and its last ID is 258, so remove that one item to obtain `[256,257,160]`.

Ordinary ID	`vocab` byte content	Interpretation before joining
`256`	`b"ab"`, byte values `[97,98]`	Two ASCII letters
`257`	`bytes([228,189])`	First two bytes of 你; incomplete by itself
`160`	`bytes([160])`	Last byte of 你; invalid by itself

Join the chunks to get byte values `[97,98,228,189,160]`. Strict UTF-8 decoding yields **`"ab 你"`**. The return excludes the prompt's `"a"`; including it would instead display `"aab 你"`. The two Chinese chunks must not be decoded independently.

Three ordinary tokens, five bytes, and three Unicode code points are distinct counts here. More generally, a visually perceived character can contain multiple code points, so Python string length is not a universal count of visible symbols.

A concrete special-token protocol

This fixture has 258 ordinary IDs, `0..257`. Reserve the unused ID 258 for EOS; the model candidate count becomes $V = 259$. An integrated model needs embedding shape `[259,D]`, head shape `[D,259]`, and bias shape `[259]`, while the ordinary byte vocabulary excludes EOS. Adding the candidate does not train its meaning: appropriate sequence-boundary training targets are still needed.

Do not overwrite a learned merged ID or assume every model uses ID 258 for EOS. Ordinary merged IDs above 255 stay ordinary. This adapter consumes an explicit supplied mapping; it does not extend the existing BPE training rules or JSON format. Persistence of special-token metadata and production training integration remain later work.

The caller can retain `generated_ids` and `stop_reason` and separately request display text using `prompt.numel()` as `prompt_length`. The stop reason explains why generation ended; it does not say that the returned bytes are valid text.

Stopping and UTF-8 validity are separate

A maximum budget counts tokens. It can end after bytes `[228,189]`, before the final byte 160 of 你. Even a generated EOS after those two bytes cannot repair them. After removing EOS, strict decoding still raises `UnicodeDecodeError`. A complete but invalid byte sequence, such as `[255]`, also fails. The required strict policy is inherited from 02.06. Python `bytes.decode` documentation.

There is also a **prompt boundary** case. The full ordinary IDs `[228,189,160]` decode to 你. If `prompt_length=1`, the new suffix is only `[189,160]`, starting inside that character; it cannot be decoded independently. With `prompt_length=0`, the same full input decodes successfully.




Figure 40: The full byte sequence decodes successfully while its selected continuation starts inside a character.

Figure 03.18-2 — Compare the two byte streams. The left retains all three bytes. The right excludes prompt byte 228, so its suffix is not standalone UTF-8. This adapter deliberately reports that error. Rendering the combined full text, carrying an incremental decoder across the boundary, or using replacement characters are separate display policies; no such policy is implemented here.

Syntax before implementation

`.tolist()` converts the integer tensor to a Python list. `all_ids[prompt_length:]` selects from that

token index to the end; `continuation_ids[:-1]` excludes the final item. These list slices produce new lists. `len(continuation_ids)>0` checks for an item before accessing `[-1]`.

The `and` operator evaluates from left to right and stops when a condition is false. Put the nonempty check before the final-ID lookup. `eos_token_id is not None` checks whether an EOS is configured; testing the number's truthiness would incorrectly disable valid ID zero. `==` compares values; `=` assigns. An `if` ends with a colon and its body has one extra indentation level. Python sequence and Boolean operations.

Five guided implementation steps

After the 03.17 implementation and this formula/example walkthrough, write only the marked learner region in `decode_continuation`. The supplied decoder performs the byte operations; reuse it.

1. **Convert full IDs.** Four spaces: call `generated_ids.tolist()` and store `all_ids`. Example `[97,256,257,160,258]`. Keep the original tensor unchanged.
2. **Select new IDs.** Four spaces: store `all_ids[prompt_length:]` as `continuation_ids`. Example `[256,257,160,258]`. Slice by prompt tokens rather than text length.
3. **Check the trailing marker safely.** Four spaces: start one `if` with three checks joined by `and`: nonempty list, configured EOS, and equality of its final ID to `eos_token_id`. Check nonemptiness before `[-1]` and use explicit presence rather than EOS truthiness.
4. **Remove that one marker.** Eight spaces inside the `if`: replace `continuation_ids` with its `[:-1]` slice. Example `[256,257,160]`. Do not drop all unknown IDs or alter the full tensor.
5. **Reuse the decoder and return.** Four spaces after the `if`: call `decode_bpe(continuation_ids, vocab)` and return its `str`. The example yields `"ab 你"`; an empty list yields `""`. Do not catch required errors or add a second implementation of joining and decoding.

Boundary case	Required result
Only prompt, or immediate new EOS	`""`
Length stopping with complete ordinary bytes	Decode all new ordinary IDs
`eos_token_id=None`	Remove no ID; decode the suffix as ordinary data
Configured EOS ID `0`, absent from ordinary vocabulary	Remove it when it is the new final ID
Unknown ordinary ID, or unexpected interior control marker	`KeyError` through lookup
Invalid/incomplete new bytes, including a split prompt boundary	`UnicodeDecodeError`

From the project root, after implementing the learner core and the preceding prerequisite:

```
python exercises/03_18_decode_continuation.py
```

Expected supplied output:

```
PASS: prompt exclusion, trailing EOS removal, merged IDs, and cross-token UTF-8
```

```
PASS: empty output, immediate EOS, length stopping, zero prompt, and ordered repeats
PASS: explicit EOS ID zero, disabled removal, prompt control IDs, and unhidden interior markers
PASS: completed decoder reused with a Python list, preserved inputs/mode/RNG, and strided IDs
PASS: unknown IDs and incomplete/invalid UTF-8 propagate required decoder errors
PASS: valid full text can have an invalid independently decoded continuation at a byte boundary
PASS: EOS and length returns from generation both display only the matching-vocabulary
 ↪  continuation
Lesson 03.18 checks passed.
```

Reader questions

Why not decode everything and remove the prompt string afterward? Token count specifies the exact ID boundary. Removing a repeated text substring can erase the wrong occurrence, and independently decoding the prefix can fail if it ends inside a character. Select IDs first under this exercise's continuation-only policy.

Why not turn EOS into `b""` inside the ordinary vocabulary? That silently changes the ordinary-token mapping and loses an explicit control distinction. This protocol keeps the control ID separate; the display adapter removes only the permitted final marker.

Does successful EOS stopping guarantee a readable answer? It establishes a stop event. Byte validity, contextual modeling, and answer quality are separate properties.

The completed 03.19 returns to training data: construct batched input windows and shifted next-token targets. Its full chapter, figures, and guided exercise are ready.

03.19 Batched Next-Token Training Windows

We return to training with the same shifted-window idea from Chapter 01. This time, several source starts supply several rows at once. Stacking those rows introduces the batch dimension without changing what each position is asked to predict.

Work through the example before editing 03_19_next_token_batch.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

Exact inputs and returned values

Exact name	Type/shape	Meaning
`token_ids`, s	One-dimensional `torch.long` tensor `[N]`	An already encoded source token stream
`start_positions`, i	Nonempty `list[int]`, length B	One chosen source start per batch row, in supplied order
`context_length`, T	Positive Python integer	Input positions in each row, also target positions per row

Exact name	Type/shape	Meaning
`input_ids`, X	Returned `torch.long` tensor `[B,T]`	Input windows
`target_ids`, Y	Returned `torch.long` tensor `[B,T]`	Corresponding next-token answers

N counts source tokens; B counts samples; T counts positions per sample. V is vocabulary size and is separate from all three. Each output stays on the source tensor's device. Preserve the source, start list, caller gradient mode, and random stream. Return two fresh tensors independent of the source, each other, and later calls.

Assume valid inputs: $B \geq 1$, $T \geq 1$, and every start satisfies $0 \leq i_b$ and $i_b + T < N$. Validation is not assigned. Duplicate, overlapping, or out-of-order starts are allowed and must retain their supplied order. Token IDs can exceed 255. This exercise has no empty-batch branch, padding, shuffle, document-boundary policy, or new special-token mapping.

One next-token answer per input position

For batch row $b = 0, \ldots, B-1$ and position $t = 0, \ldots, T-1$:

$$X_{b,t} = s_{i_b+t}, \qquad Y_{b,t} = s_{i_b+t+1}$$

Both rows contain T IDs. Their combined source span needs $T + 1$ consecutive IDs, because the final input also needs a next-token answer:

$$X_b = s[i_b : i_b + T], \qquad Y_b = s[i_b + 1 : i_b + T + 1]$$

The latest required source index is $i_b + T$, so it must be smaller than N. The largest valid start is $N - T - 1$. A slice end is excluded: `s[0:3]` contains indices `0,1,2`, not index 3.

Stack the B rows along a new batch dimension:

$$X = \text{stack}(X_0, \ldots, X_{B-1}), \qquad Y = \text{stack}(Y_0, \ldots, Y_{B-1}), \qquad \text{shape}(X) = \text{shape}(Y) = [B, T]$$

There are BT supervised positions in this fixed-length, unmasked batch. This is a count of target comparisons, not a promise of improved model quality or a measured training throughput.




Figure 41: Two source spans become input/target rows with the target shifted one source position.

Figure 03.19-1 — Each downward arrow is one prediction/answer pair. The upper source labels show actual token indices. Each lower input row has three IDs, and its target row also has three. The final target comes from the extra fourth source token. The two samples form `[2,3]` tensors.

Complete worked example

Use the illustrative byte-token stream `toy-ascii-stream-v1`, the UTF-8 bytes of `"abcdefg"`:

```
token_ids = tensor([97,98,99,100,101,102,103])
start_positions = [0,3]
context_length = 3
N = 7, B = 2, T = 3
```

Before the loop, `input_rows=[]` and `target_rows=[]`. For the first supplied start, `start=0`, take input indices `0:3` and target indices `1:4`:

```
x_row = [97,98,99]   # abc
y_row = [98,99,100]  # bcd
```

Append these two tensors to their respective lists. Each list now contains one `[3]` tensor. For the next start, `start=3`, input indices are `3:6`, and target indices are `4:7`:

```
x_row = [100,101,102]  # def
y_row = [101,102,103]  # efg
```

The two source spans are `abcd` and `defg`. They share d: it is the first sample's final answer and the second sample's first input. Two four-token spans therefore need only seven distinct source positions here; valid windows may overlap.

After appending, each list holds two `[3]` tensors. Stack each list on dimension zero to obtain:

$$X = \begin{bmatrix} 97 & 98 & 99 \\ 100 & 101 & 102 \end{bmatrix}, \qquad Y = \begin{bmatrix} 98 & 99 & 100 \\ 101 & 102 & 103 \end{bmatrix}$$

Return `(input_ids, target_ids)`, each shape `[2,3]`. For example, `input_ids[0,1]` is 98 (`b`) and its answer `target_ids[0,1]` is 99 (`c`). The final input `c` in row zero predicts d, which is outside that row's input window.

Row	Inputs	Targets	Three aligned comparisons
`0`	`abc`	`bcd`	`a→b`, `b→c`, `c→d`
`1`	`def`	`efg`	`d→e`, `e→f`, `f→g`

The arrows label input/target alignment. A future contextual model can also use each position's preceding visible tokens; an arrow does not require it to use only one input ID. Our earlier lookup-plus-head baseline does use only the current ID and is still unchanged.

Why targets shift, and why training can use multiple positions

Copying the input as its own target would teach the model to predict the current ID. Next-token modeling instead assigns the observed next ID to every position. The last input position therefore still has a target. Repeating only the final target across the row would discard the other intended comparisons.

For a future causal contextual model, the intended distribution at position t is:

$$p_\theta(Y_{b,t} \mid X_{b,0}, \ldots, X_{b,t})$$

Training uses observed preceding tokens as input, often called teacher forcing. It can compute the position predictions together because the observed input row is available, while causal visibility blocks future positions from influencing earlier predictions. The target tensor is used to calculate loss and stays outside the model's forward input.

In row `abc`, the position predicting `b` may see `a`; the position predicting `c` may see `ab`; the position predicting d may see `abc`. Although `b` and `c` are stored in the input row, the first prediction must not see them. Merely constructing shifted targets does not implement that restriction; causal attention/masking follows later.




Figure 42: The visible input prefix grows by position while future input cells remain blocked.

Figure 03.19-2 — Teal marks a conceptual causal model's permitted input cells. Gray marks future cells that must be blocked. Orange identifies the true next ID. This window builder supplies data;

it does not implement the mask or make the earlier model contextual. During free generation, future IDs are unknown and still must be selected sequentially.

For later fixed-length batched training, the mean token loss would be:

$$\mathcal{L} = -\frac{1}{BT}\sum_{b=0}^{B-1}\sum_{t=0}^{T-1}\log p_\theta(Y_{b,t} \mid X_{b,0:t})$$

Here $X_{b,0:t}$ denotes the inclusive mathematical prefix through position t; its Python slice is `input_ids[b, :t+1]`. The batch builder calculates none of these probabilities or losses. Padding masks and weighted losses would require a different normalization protocol.

New syntax and storage

`[]` creates a Python list. `input_rows.append(x_row)` adds one tensor to it, preserving that row as an item. `for start in start_positions:` visits the caller's starts in order, including repeats. The loop body uses eight spaces; setup and the final return use four. No new conditional or error handling is required under the valid-input contract.

Tensor slices can share source storage, so do not modify the collected row views. `torch.stack(rows, dim=0)` adds a new dimension to same-shaped tensors and produces `[B,T]`; with two `[3]` rows, the result is `[2,3]`. The provided runtime also verifies this behavior. PyTorch stack documentation.

By comparison, `torch.cat(rows, dim=0)` joins those two one-dimensional rows into `[6]`. In generation, `cat` extends one ID sequence; here `stack` keeps separate samples as separate rows. `stack(.., dim=1)` would place the new batch dimension elsewhere, giving `[T,B]` for these one-dimensional rows.

Seven guided implementation steps

After the verified 03.18 completion and this chapter's walkthrough, replace only the placeholder in `make_next_token_batch`; preserve the supplied driver and previous implementations.

1. **Prepare row lists.** Four spaces: create separate fresh `input_rows` and `target_rows` lists. Each will hold B tensors of shape `[T]`.
2. **Visit chosen starts.** Four spaces: start `for start in start_positions:`. Its eight-space body handles one sample. In the example, `start` is first 0, then 3; use the values, not their list indices.
3. **Take shifted slices.** Eight spaces: obtain `x_row` with `token_ids[start:start+context_length]`; obtain `y_row` beginning at `start+1` and ending at `start+context_length+1`. Ends are excluded. First rows are `[97,98,99]` and `[98,99,100]`.
4. **Collect both rows.** Eight spaces: append `x_row` to `input_rows` and `y_row` to `target_rows`. After two iterations, each list contains two `[3]` tensors. Do not alter the slice views.
5. **Stack input rows.** Four spaces after the loop: call `torch.stack(input_rows, dim=0)`, saving `input_ids`. Example shape `[2,3]`.

6. **Stack target rows.** Four spaces: stack `target_rows` on dimension zero as `target_ids`. Example rows are `bcd` and `efg`, also `[2,3]`.
7. **Return both tensors.** Four spaces after both stack operations: return `input_ids, target_ids`, in that order. Returning inside the loop would omit later samples.

From the project root, after the walkthrough and implementation:

```
python exercises/03_19_next_token_batch.py
```

Expected supplied output:

```
PASS: complete worked batch, shifted final targets, and two [2,3] tensors
PASS: one sample, one position, maximal span, and the last valid start
PASS: supplied order, repeated/overlapping starts, and vocabulary IDs above 255
PASS: strided source, dtype/device propagation, caller mode, and unchanged random stream
PASS: fresh outputs independent of the source, each other, and later calls
PASS: varied batch/window sizes agree with completed single-window references
PASS: six aligned supervised positions feed completed projection/loss with connected gradients
Lesson 03.19 checks passed.
```

Bridge to model shapes and reader questions

Embedding lookup on IDs `[B,T]` produces vectors `[B,T,D]`. A contextual model should preserve the sample and position axes while computing context, then produce scores `[B,T,V]`. V is the number of candidate IDs for each position, not a third sample dimension.

The supplied last check is a smaller, independent fixture: IDs `[0,1,2,0,1,2,0]`, starts `[0,3]`, length 3, and fixed parameters with $V = 3, D = 2$. It flattens the **independent lookup baseline's** six vectors into `[6,2]`, calls completed projection and loss helpers, and checks gradients. This is a correctness bridge without parameter updates or a training-quality claim. It does not authorize flattening away sequence structure before future attention; batched contextual loss will be taught separately.

Must start positions be contiguous or random? No. This function accepts already chosen valid starts. `[2,0,2]` means three samples in that order, with the same source window repeated in rows zero and two. Choosing a sampling strategy is separate work.

Does T+1 mean the model receives an extra token? No. The data builder needs an extra source token to supply the last answer. Each returned model input row still has only T tokens.

Does batching train different models? The future batch shares one model's parameters across all rows. B organizes data; it does not allocate one separate model per row.

Does the second row see the first row? Each row is a separate sample. The second row's prefixes are d, `de`, and `def`; it does not attend to the first row's `abc`. Cropping a window also omits earlier source context before its chosen start. Sharing model parameters does not merge sample contexts.

Can windows cross documents? This exercise assumes one supplied stream with permitted spans. Real data preparation must specify document boundaries, EOS insertion, splits, and masking. No such policy is silently imposed here. Overlapping training windows are allowed; train/validation splitting

must be designed separately to prevent shared-data leakage.

The completed 03.20 connects these batch shapes to raw vocabulary scores and a connected mean token loss. Its expanded chapter, paired figures, and two-stage scaffold are ready.

03.20 Batched Logits and Mean Token Loss

A batch adds a dimension to the data, but every position still needs its own vocabulary scores and true target. We will carry the batch and position axes through lookup and projection, then flatten them together for the familiar two-dimensional loss interface. The target order must travel with the score order.

Work through the example before editing 03_20_batched_logits_and_loss.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

Exact inputs, outputs, and state

Exact name	Type/shape	Meaning
`embedding_table`, E	Floating tensor `[V,D]`	Shared token-vector table
`input_ids`, X	`torch.long` tensor `[B,T]`	Observed input ID at each sample/position
`output_weights`, W	Floating tensor `[D,V]`	Shared vocabulary projection
`output_bias`, β	Floating tensor `[V]`	Shared candidate biases
`logits`, Z	Floating tensor `[B,T,V]`	Stage A return; Stage B score input
`target_ids`, Y	`torch.long` tensor `[B,T]`	Already shifted observed next-token answers
Returned `loss`, $\mathcal{L}$	Scalar floating tensor, shape `[]`	Mean true-target negative log-probability

B counts samples, T positions per sample, D embedding features, and V candidate IDs per position. In formulas the bias is written β to distinguish it from row index b. For example, `logits[1,0]` is one `[V]` score vector; `logits[1,0,2]` is the score for candidate ID 2 at sample one, position zero.

Assume positive dimensions, valid IDs, compatible dtypes/devices, and finite scores in the numerical range used by the checks. Validation is not assigned. Preserve all input values, parameter storage/trainability/stored gradients, caller gradient mode, and global random state. Keep the graph when gradients are enabled. Do not detach, enter no-grad, call backward, clear gradients, extract a Python float, or update parameters inside either exercise function.

No positions are ignored, and there are no padding weights, class weights, or label smoothing. Every one of the BT targets contributes equally. Targets are already shifted by the data builder; this lesson does not shift them again.

One vocabulary score vector per position

For $b = 0, \ldots, B-1$, $t = 0, \ldots, T-1$, and $v = 0, \ldots, V-1$:

$$H_{b,t,:} = E[X_{b,t}], \qquad \text{shape}(H) = [B, T, D]$$

$$Z_{b,t,v} = \sum_{d=0}^{D-1} H_{b,t,d} W_{d,v} + \beta_v, \qquad \text{shape}(Z) = [B, T, V]$$

Every position uses the same table and head parameters. Scores are raw logits. For each position, the mathematical candidate distribution is:

$$P_{b,t,v} = \frac{\exp(Z_{b,t,v})}{\sum_{j=0}^{V-1} \exp(Z_{b,t,j})}$$

Normalize over the candidate axis V, separately for every `(b,t)`. One true target ID selects one probability per position. The desired mean loss is:

$$\mathcal{L} = -\frac{1}{BT} \sum_{b=0}^{B-1} \sum_{t=0}^{T-1} \log P_{b,t,Y_{b,t}}$$

The denominator counts supervised positions. Each position has V candidate scores, but only one supplied answer. The stable 03.10 helper computes target log-probabilities directly from raw scores, avoiding an intermediate tiny probability that may underflow before taking its log.

Flatten positions while preserving candidates and answer alignment

Map a batch position to flat row index:

$$q = bT + t, \qquad \widetilde{Z}_{q,v} = Z_{b,t,v}, \qquad \widetilde{Y}_q = Y_{b,t}$$

The shape conversion is `[B,T,V] → [B*T,V]`, accompanied by `[B,T] → [B*T]`. Candidate columns remain together. For $B = 2, T = 2$, the position order is `(0,0),(0,1),(1,0),(1,1)`.

Stage A also uses this order to adapt vectors `[B,T,D] → [B*T,D]` before calling the completed two-dimensional projection. Its scores `[B*T,V]` are restored to `[B,T,V]`. Stage B flattens those scores and their targets in the same order, then calls the completed two-dimensional loss.




Figure 43: The batch/position axes merge for completed helpers while feature and vocabulary axes stay explicit.

Figure 03.20-1 — Follow Stage A left to right, then follow the score route to Stage B. Stage A returns restored raw scores. Stage B receives targets separately and computes one scalar. D and V both equal three only in this example; their meanings and possible sizes differ.

Complete worked example

Use the hand-picked artifact `batch-three-id-v1`, not a trained capability result. Source IDs `[0,1,2,0,1]`, starts `[0,2]`, and row length two give:

$$X = \begin{bmatrix} 0 & 1 \\ 2 & 0 \end{bmatrix}, \qquad Y = \begin{bmatrix} 1 & 2 \\ 0 & 1 \end{bmatrix}, \qquad B = 2,\ T = 2$$

Choose shared parameters. Here I_3 is the three-by-three identity matrix: ones on its main diagonal and zeros elsewhere.

$$E = \begin{bmatrix} 1 & 2 & 3 \\ 2 & 1 & 3 \\ 3 & 2 & 1 \end{bmatrix}, \qquad W = I_3, \qquad \beta = [0,0,0], \qquad D = 3,\ V = 3$$

Lookup gives `hidden_vectors` shape `[2,2,3]`. Identity weights and zero bias make its values equal to the scores:

```
logits = [
    [[1,2,3], [2,1,3]],
    [[3,2,1], [1,2,3]],
]
flat_logits = [[1,2,3], [2,1,3], [3,2,1], [1,2,3]]
flat_targets = [1,2,0,1]
```

For the first position, scores `[1,2,3]` have maximum 3. Subtract it to get `[-2,-1,0]`; exponentials are approximately `[0.1353352832,0.3678794412,1]`. Their sum and its logarithm are:

$$S = 1 + e^{-1} + e^{-2} \approx 1.5032147244, \qquad \log S \approx 0.4076059644$$

The supplied target is ID 1, so its probability is $\frac{0.3678794412}{S} \approx 0.2447284711$. Its stable negative log-probability is $1 + \ln(S) \approx 1.4076059644$. The largest-score candidate is ID 2, but loss selects the observed answer ID 1.

All four rows are permutations of `[1,2,3]`, so they share S. Their complete true-target trace is:

Flat q	Position `(b,t)`	Raw scores	Target ID	Selected probability	Negative log-probability
`0`	`(0,0)`	`[1,2,3]`	`1`	`0.2447284711`	`1.4076059644`
`1`	`(0,1)`	`[2,1,3]`	`2`	`0.6652409558`	`0.4076059644`
`2`	`(1,0)`	`[3,2,1]`	`0`	`0.6652409558`	`0.4076059644`

Flat q	Position `(b,t)`	Raw scores	Target ID	Selected probability	Negative log-probability
`3`	`(1,1)`	`[1,2,3]`	`1`	`0.2447284711`	`1.4076059644`

Thus:

$$\mathcal{L} = \frac{1.4076059644 + 0.4076059644 + 0.4076059644 + 1.4076059644}{4} \approx 0.9076059644$$

Return a scalar tensor with that value, keeping its gradient path. The completed helper already takes this mean; the outer adapter performs no additional division.

Choose one true target from each position, then average

Z shape [2,2,3] -> [4,3] | target_ids [[1,2],[0,1]] -> [1,2,0,1]

q	Position (b,t)	Z[q,0]	Z[q,1]	Z[q,2]	Target y	True p	Loss $-\ln(p)$
0	(0,0)	1	**2**	3	1	0.244728	1.407606
1	(0,1)	2	1	**3**	2	0.665241	0.407606
2	(1,0)	**3**	2	1	0	0.665241	0.407606
3	(1,1)	1	**2**	3	1	0.244728	1.407606

Mean over B*T = 4 positions: (1.407606+0.407606+0.407606+1.407606)/4 = 0.907606

Orange selects the supplied answer, which can differ from the largest-score candidate.

Figure 44: Flattened positions select their supplied targets and contribute one loss each.

Figure 03.20-2 — Orange identifies the true-target score column in each row. The probability and loss columns refer to that selected candidate. Four losses are averaged, including both occurrences of input ID zero.

Gradients remain connected through reshape

Under normal gradient mode, the mean-loss score derivative is:

$$\frac{\partial \mathcal{L}}{\partial Z_{b,t,v}} = \frac{P_{b,t,v} - \mathbf{1}\{v = Y_{b,t}\}}{BT}$$

For the first worked position, this is approximately `[0.0225076433,-0.1888178822,0.1663102389]`. The target component is negative: increasing that score locally reduces loss. Non-target components are positive. The $\frac{1}{BT}$ factor comes from the mean across four positions.

The caller can later run `loss.backward()` and obtain gradients for the shared table, weights, and bias. Repeated ID zero sends contributions from both its positions to the same embedding row. Because W is identity, their combined table-row gradient is approximately `[0.0450152866,-0.3776357645,0.3326204779]`. Backward computes gradients; an optimizer/update is still a separate operation.

Reshape syntax before implementation

`batch_size, context_length = input_ids.shape` unpacks the two dimensions. `embedding_table[input_ids]` keeps `[B,T]` and appends the vector dimension D. `.reshape(-1, embedding_dim)` groups the first two axes and lets PyTorch infer the missing size from the element count. Here $2 \times 2 \times 3 = 12$ values become four rows of three.

Only one reshape dimension may be `-1`. A later `.reshape(batch_size, context_length, -1)` restores the sample/position axes and infers V. For loss, `.reshape(-1, vocab_size)` retains each position's candidate vector; `.reshape(-1)` on targets produces one ID per flat position.

Reshape preserves logical element order and may return a view or a copy depending on layout. Do not rely on storage ownership or modify its result in place. It keeps autograd connected; a copy needed for a strided layout does not mean detachment. PyTorch reshape documentation.

Stage A: six guided implementation steps

After verified 03.19 completion and this formula/example walkthrough, write only `compute_batch_logits`'s marked learner region. Every statement uses four spaces; no loop or context block is required.

1. **Read batch shape.** Unpack `input_ids.shape` into `batch_size` and `context_length`, both two in the worked example.
2. **Lookup vectors.** Save `embedding_table[input_ids]` as `hidden_vectors`, shape `[2,2,3]`.
3. **Prepare the helper's vector rows.** Read `embedding_dim` from `embedding_table.shape[1]`. Reshape `hidden_vectors` to `(-1, embedding_dim)` as `flat_hidden`, shape `[4,3]`, preserving the four-position order.
4. **Reuse projection once.** Call `compute_logits(flat_hidden, output_weights, output_bias)`, saving `flat_logits`, shape `[B*T,V]`. Keep its graph.
5. **Restore batch axes.** Reshape `flat_logits` to `(batch_size, context_length, -1)` as `logits`, shape `[2,2,3]`.
6. **Return raw scores.** Return `logits` as a tensor. Keep probability conversion and sampling outside this function.

Run Stage A alone after implementing it:

```
python exercises/03_20_batched_logits_and_loss.py --check logits
```

Its final line should be `Lesson 03.20 logits checks passed.`

Stage B: five guided implementation steps

Write only `batch_cross_entropy`'s marked learner region. Every statement again uses four spaces.

1. **Read the candidate count.** Save `logits.shape[-1]` as `vocab_size`, three in the example.
2. **Flatten score positions.** Save `logits.reshape(-1, vocab_size)` as `flat_logits`, shape `[4, 3]`. Preserve candidate columns.
3. **Flatten answers in the same order.** Save `target_ids.reshape(-1)` as `flat_targets`, `[1,2, 0,1]`. Keep the already shifted IDs in their original order.
4. **Reuse the stable loss once.** Call `cross_entropy_loss(flat_logits, flat_targets)` and save `loss`. It already averages the four true-target rows.
5. **Return the connected scalar.** Return `loss` as a tensor. Backward, clearing gradients, and updates belong to a later training caller.

Run Stage B alone using its supplied score fixtures:

```
python exercises/03_20_batched_logits_and_loss.py --check loss
```

Its final line should be `Lesson 03.20 loss checks passed.` Stage B's isolated checks do not require Stage A to be complete.

Once both cores are complete, run:

```
python exercises/03_20_batched_logits_and_loss.py --check all
```

Expected combined output:

```
PASS: worked [B,T] lookup and restored [2,2,3] raw scores
PASS: nonsquare batch shapes, D different from V, bias, singleton axes, and merged IDs
PASS: 2D helper reuse, logical position order, strided IDs, fixed state, and caller mode
PASS: four true targets selected in matching order and averaged to one scalar
PASS: varied shapes/dtypes, row shifts, single candidate, large IDs, and stable extreme loss
PASS: 2D stable helper reuse, aligned flattening of strided tensors, and preserved mode
PASS: connected analytic gradients scaled by B*T, finite differences, and existing buffers
PASS: full batch forward/loss reaches all parameters with repeated-ID accumulation and no update
Lesson 03.20 checks passed.
```

Reader questions

Does flattening turn several samples into one context? Here each lookup vector is scored independently, so merging position rows adapts the old helper without changing predictions. A future contextual model must keep sample and sequence structure while applying attention; its final logits can then be

flattened for token loss. Do not merge samples into one sequence before attention.

Why not shift targets again or choose argmax answers? Data construction already provides the observed next IDs. Shifting again misaligns labels; using argmax would score the model's own choice instead of the observed answer.

Why not feed probabilities into the old loss? That helper expects raw logits and computes stable log-probabilities internally. Applying softmax first changes its input interpretation. Cross-entropy documentation.

Can a library cross-entropy accept `[B,T,V]` directly? The usual class-index interface uses scores `[N,C,...]`, with candidate classes on the second axis. Our layout keeps V last. This adapter uses unambiguous `[B*T,V]` scores with `[B*T]` targets and the completed 2D helper; other layouts require a deliberate compatible conversion.

Why return a scalar tensor rather than `.item()`? The training caller needs the graph for backward. `.item()` is suitable for display/logging after retaining the connected loss, not as this function's return.

A closer look at example dimensions and flat indices

Does D=V=3 require D and V always to be equal? No. D counts embedding features, while V counts candidate IDs. For B=2, T=3, D=2, V=5, the table is [5,2], weights [2,5], lookup vectors [2,3,2], flat vectors [6,2], flat scores [6,5], and restored scores [2,3,5]. The matrix product [6,2] @ [2,5] changes feature width two to candidate count five. Loss retains [6,5] scores with six targets.

Does q=b*T+t use the batch size B? Lowercase b is a zero-based sample index, distinct from uppercase B, the sample count. For B=2, T=2, positions (0,0),(0,1),(1,0),(1,1) map to q=0,1,2,3. The second row's first position is 1*2+0=2. In general, 0<=b<B, 0<=t<T, and 0<=q<B*T. Scores and targets follow the same mapping, with all V candidate columns retained.

03.21 One Joint Update from a Next-Token Batch

Several samples can contribute to a single update. Their position losses are averaged into one scalar, and their gradients meet at shared parameters before those parameters change. We will extend the joint training step to a batch while retaining the timing and object identity learned earlier.

Work through the example before editing 03_21_batch_train_step.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

Exact inputs, returns, and effects

Exact name	Type and shape	Meaning
`embedding_table`, E	Trainable floating leaf tensor `[V,D]`	Shared token-vector table
`input_ids`, X	Fixed `torch.long` tensor `[B,T]`	Input IDs at each sample/position

Exact name	Type and shape	Meaning
`output_weights`, W	Trainable floating leaf tensor `[D,V]`	Shared vocabulary projection
`output_bias`, β	Trainable floating leaf tensor `[V]`	One bias per candidate
`target_ids`, Y	Fixed `torch.long` tensor `[B,T]`	Already shifted next-token answers
`learning_rate`, η	Nonnegative Python float	Common update multiplier

B counts sample rows, T positions per row, D vector features, and V candidate IDs. D and V can differ: this chapter deliberately uses $D = 1, V = 2$. Assume positive dimensions, valid IDs, compatible floating dtypes/devices, finite values, normal gradient mode, and separately stored untied parameters. Input validation is not assigned.

Return `(loss_value, gradient_table, gradient_weights, gradient_bias)`:

- `loss_value` is a Python float for the loss **before** updating.
- The three gradients are independent tensor snapshots with shapes `[V,D]`, `[D,V]`, and `[V]`, all from the same pre-update state.
- The original three parameter tensors contain their updated values. Preserve their storage, dtype/device, and trainable-leaf identity. Both ID tensors and random state stay unchanged.
- Leave the current gradients in `.grad`; clear all three at the start of the next call. Returned snapshots must survive subsequent calls or edits to these live buffers.

A leaf parameter is the original trainable tensor supplied by setup, rather than an intermediate tensor produced by forward computation. Its `.grad` stores derivatives after backward. IDs select table rows; they are fixed observations, not trainable floating parameters.

Forward, mean loss, gradient, update

Let $b = 0, \ldots, B-1$, $t = 0, \ldots, T-1$, $d = 0, \ldots, D-1$, and $v = 0, \ldots, V-1$. With the current parameters held at one state:

$$H_{b,t,:} = E[X_{b,t}], \qquad Z_{b,t,v} = \sum_d H_{b,t,d} W_{d,v} + \beta_v$$

$$P_{b,t,v} = \frac{e^{Z_{b,t,v}}}{\sum_j e^{Z_{b,t,j}}}, \qquad \mathcal{L}(E, W, \beta; X, Y) = -\frac{1}{BT} \sum_{b,t} \log P_{b,t,Y_{b,t}}$$

`X` and Y are fixed for differentiation. The loss depends on all three parameters through this connected computation. Call the completed `compute_batch_logits` and `batch_cross_entropy`; the stable loss helper computes log-probabilities directly. The mathematical probabilities below explain the derivatives, rather than requiring an extra softmax call in your core.

For one candidate score, the derivative is:

$$(G_Z)_{b,t,v} = \frac{\partial \mathcal{L}}{\partial Z_{b,t,v}} = \frac{P_{b,t,v} - \mathbf{1}\{v = Y_{b,t}\}}{BT}$$

The indicator is one for the supplied target and zero otherwise. The denominator comes from averaging supervised positions. The helper already applies it: do not divide loss or gradients by B, T, or V again.

Flatten positions in the same order $q = bT + t$: $\widetilde{H}$ has shape `[B*T,D]` and $\widetilde{G}_Z$ has shape `[B*T,V]`. Applying the chain rule to the linear head gives:

$$G_W = \widetilde{H}^\mathsf{T}\widetilde{G}_Z, \qquad (G_\beta)_v = \sum_{b,t}(G_Z)_{b,t,v}, \qquad (G_H)_{b,t,:} = (G_Z)_{b,t,:}W^\mathsf{T}$$

The embedding table is shared, so every occurrence of an input ID contributes to the same table row:

$$(G_E)_{i,:} = \sum_{(b,t):X_{b,t}=i} (G_H)_{b,t,:}$$

An unselected row has zero gradient for this lookup-only objective. These formulas explain what autograd computes. Your implementation calls **one** `loss.backward()` instead of manually coding these derivatives.

Once all three gradients have been computed at that same old state:

$$E_{\text{new}} = E - \eta G_E, \qquad W_{\text{new}} = W - \eta G_W, \qquad \beta_{\text{new}} = \beta - \eta G_\beta$$

Why subtraction? For a small displacement $\Delta\theta$, $\Delta\mathcal{L} \approx G_\theta^\mathsf{T}\Delta\theta$. Choosing $\Delta\theta = -\eta G_\theta$ makes the first-order term $-\eta\|G_\theta\|^2 \leq 0$. This is a local approximation; an overly large step can increase the actual loss.




Figure 45: One connected batch loss supplies all gradients before the parameter update.

Figure 03.21-1 — Follow the top row rightward, then the lower row leftward. Forward and backward use normal gradient mode. Only the final in-place update uses `torch.no_grad()`. Save pre-update observations before that update.

Complete worked example: four positions, D different from V

Use the hand-picked correctness fixture `batch-two-id-sgd-v1`. Source IDs `[0,1,0,1]`, starts `[0,1]`, and $T = 2$ yield:

$$X = \begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix}, \quad Y = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}, \quad E = \begin{bmatrix} 1 \\ 2 \end{bmatrix}, \quad W = \begin{bmatrix} 1 & 0 \end{bmatrix}, \quad \beta = [0, 0], \quad \eta = 0.1$$

Here $B = 2, T = 2, D = 1, V = 2$. The tensor shapes are `E: [2,1]`, `H: [2,2,1]`, `W: [1,2]`, and `Z: [2,2,2]`. The projection changes vector width one to candidate count two. In flat position order `(0,0),(0,1),(1,0),(1,1)`:

q	Input ID	Vector	Scores	Target ID	Target probability	Position loss
0	0	`[1]`	`[1,0]`	1	`0.2689414214`	`1.3132616875`

q	Input ID	Vector	Scores	Target ID	Target probability	Position loss
1	1	`[2]`	`[2,0]`	0	`0.8807970780`	`0.1269280110`
2	1	`[2]`	`[2,0]`	0	`0.8807970780`	`0.1269280110`
3	0	`[1]`	`[1,0]`	1	`0.2689414214`	`1.3132616875`

For `[1,0]`, subtract the maximum one: `[0,-1]`. The target is candidate one, so $p_1 = e^{-1}/(1 + e^{-1}) \approx 0.2689414214$ and $-\log p_1 = 1 + \log(1 + e^{-1}) \approx 1.3132616875$. For `[2,0]`, the target is candidate zero, so $p_0 = 1/(1 + e^{-2}) \approx 0.8807970780$ and loss $\log(1 + e^{-2}) \approx 0.1269280110$.

$$\mathcal{L} = \frac{1.3132616875 + 0.1269280110 + 0.1269280110 + 1.3132616875}{4} \approx 0.7200948493$$

Define $a = 0.7310585786/4 \approx 0.1827646447$ and $c = (0.8807970780 - 1)/4 \approx -0.0298007305$. The full score gradient is:

$$\widetilde{G}_Z = \begin{bmatrix} a & -a \\ c & -c \\ c & -c \\ a & -a \end{bmatrix}$$

Since $W^\mathsf{T} = [1, 0]^\mathsf{T}$, each position's vector gradient is its first score-gradient component. The two input-zero contributions add to $2a$; the two input-one contributions add to $2c$. For the weight gradient, each vector multiplies its score-gradient row; the vectors are `[1,2,2,1]`. Bias gradients simply sum the four rows. Therefore:

$$G_E = \begin{bmatrix} 2a \\ 2c \end{bmatrix} \approx \begin{bmatrix} 0.3655292893 \\ -0.0596014610 \end{bmatrix}$$

$$G_W = [2a + 4c,\ -(2a + 4c)] \approx [0.2463263673, -0.2463263673]$$

$$G_\beta = [2a + 2c,\ -(2a + 2c)] \approx [0.3059278283, -0.3059278283]$$

Subtract `0.1` times each matching gradient:

$$E_{\text{new}} \approx \begin{bmatrix} 0.9634470711 \\ 2.0059601461 \end{bmatrix},$$
$$W_{\text{new}} \approx [0.9753673633, 0.0246326367],$$
$$\beta_{\text{new}} \approx [-0.0305927828, 0.0305927828].$$

For example, $E_{0,0} = 1 - 0.1 \times 0.3655292893 = 0.9634470711$. The second row increases because its gradient is negative: $2 - 0.1 \times (-0.0596014610) = 2.0059601461$.

The function returns `0.7200948493` and the three **old-state** gradient snapshots. Recomputing forward separately at the new state gives input-zero scores `[0.9091220465,0.0543250245]`, input-one scores `[1.9259552757,0.0800048704]`, selected probabilities `[0.2984275419,0.8636509327, 0.8636509327,0.2984275419]`, and new mean loss `0.6779073607`. The supplied driver checks this separate observation; it is not the returned loss.




Figure 46: Repeated IDs accumulate into shared rows, followed by one SGD update.

Figure 03.21-2 — Four position contributions form three shared parameter gradients. Each contribution already contains the mean factor $\frac{1}{4}$. The lower table shows the original values, gradients, and updated values; every column uses the same fixture.

Syntax and state before coding

`parameters = (embedding_table, output_weights, output_bias)` creates a tuple of three references. It does not copy the tensors. `for parameter in parameters:` visits each original tensor. Inside that loop, `parameter.grad = None` clears the previous derivative buffer while leaving parameter

values unchanged.

Backward normally adds into existing gradients. Repeated-ID contributions **within this batch** should add together. Old gradients **from the previous update** should be cleared for this assignment. Gradient accumulation across batches is a later deliberate training method.

`loss` must remain a connected scalar tensor until `loss.backward()`. Saving `loss_value = loss.item()` separately creates a Python float for reporting. A float has no `.backward()` method. Ordinary backward produces untracked gradient buffers; `.clone()` on each `.grad` gives an independent snapshot without requiring another detach.

`with torch.no_grad():` scopes gradient tracking to an indented block. Use it only for the three updates. `embedding_table -= learning_rate * embedding_table.grad` modifies the original parameter in place. An assignment with = to a newly computed tensor instead rebinds a local name and does not update the caller's original parameter.

Eight guided implementation steps

Edit only the marked learner region of `batch_train_step`. The supplied loader already exposes both completed 03.20 helpers. Do not implement softmax or manual gradients here.

1. **Clear previous gradients.** At four spaces, group the three parameters into `parameters`, then start `for parameter in parameters:`. Its body uses eight spaces: set `.grad` to `None`. Exclude IDs; all numerical parameter values remain unchanged.
2. **Compute batch scores.** Return to four spaces. Call `compute_batch_logits(embedding_table, input_ids, output_weights, output_bias)` once and save `logits`, shape `[2,2,2]` in the example. Forward must be outside no-grad.
3. **Compute connected mean loss.** At four spaces, call `batch_cross_entropy(logits, target_ids)` once and save `loss`. It is a scalar tensor near `0.7200948493`. Keep targets unchanged and use the helper's existing mean.
4. **Differentiate once.** At four spaces, call `loss.backward()`. Now `embedding_table.grad`, `output_weights.grad`, and `output_bias.grad` describe the same old parameter state. Finish this before any update.
5. **Save the reporting value.** At four spaces, save `loss_value` with `loss.item()`. Keep the tensor variable distinct from the reporting float.
6. **Copy all gradients.** At four spaces, obtain `gradient_table`, `gradient_weights`, and `gradient_bias` by `.clone()` on each corresponding `.grad`. Their example values are the three matrices/vectors above.
7. **Update originals.** At four spaces, start `with torch.no_grad():`. Its body uses eight spaces: write three explicit `-=` updates using each parameter's own gradient. No nested loop is needed. The example first table entry becomes `0.9634470711`.
8. **Return old-state observations.** Return to four spaces outside the context. Return `loss_value, gradient_table, gradient_weights, gradient_bias` in that order. Do not perform a second forward in this function.

Supplied checks and expected output

Run from the repository root in the existing environment:

```
python exercises/03_21_batch_train_step.py
```

After you implement the core, expected output is:

```
PASS: four-position mean, all three gradients, in-place update, and pre-update return
PASS: varied B/T/D/V, distinct targets, singleton axes, and one-candidate zero gradients
PASS: completed batch helpers called once with unchanged old parameters before backward
PASS: stale gradients cleared, repeated calls use current parameters, and snapshots stay
 ↪  independent
PASS: zero learning rate still computes gradients; a large step can increase loss
PASS: strided ID tensors, IDs above 255, dtype preservation, and fixed input/random state
PASS: actual window builder and batch helpers connect across three toy updates
Lesson 03.21 checks passed.
```

Before implementation, the deliberate `NotImplementedError` means the learner region is still open. The checks independently compare loss and gradients with a library reference, verify updates and storage continuity, and connect actual completed prerequisites. They are setup supplied for this exercise, rather than code you must write.

Questions, limitations, and understanding checkpoints

Is this four separate updates? Four supervised positions contribute to one mean loss, one backward, and one joint parameter update. A parameter's gradient includes all applicable contributions before it changes.

Why can two identical positions add yet the average stay unchanged when duplicated? Each additional contribution increases the sum, while the mean denominator increases proportionally when the whole batch is duplicated. Here each contribution contains $\frac{1}{4}$; the shared-row gradient adds its two contributions. Arbitrary changed batches need not give the same mean or gradient.

Does clearing `.grad` erase learned values? No. It resets derivative buffers only. The next forward uses the already updated parameter values.

Does no-grad stop training? It prevents the update operation itself from becoming part of a new tracked graph. Forward and backward already computed this step's gradients outside that context.

Why return a float here when 03.20 returns a tensor? 03.20 is a differentiable loss component for its caller. This training step has already called backward and returns a reporting value plus copied derivatives.

Must loss decrease on every update? No. The worked small step decreases this batch loss. Large steps may increase it, and lower training loss on this tiny fixed fixture does not establish generalization or language-model capability.

Can I reconstruct the reasoning independently? Optional checkpoints: explain the four-position denominator; derive `2a` and `2c`; explain why all gradients must use the old state; distinguish previous-

step accumulation from repeated IDs; explain snapshots and return timing.

03.22 Persistent Training over Ordered Batches

Real training does not revisit just one fixed batch. An ordered schedule lets us follow different batches through the same persistent parameters. It also reveals why a rising loss history can reflect changing data rather than a broken update.

Work through the example before editing 03_22_batch_training_loop.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

Exact inputs, returns, and state

Exact name	Type and shape	Meaning
`embedding_table`, E	Trainable floating leaf tensor `[V,D]`	Existing token-vector table
`token_ids`	Fixed `torch.long` tensor `[N]`	Source sequence from which batches are built
`output_weights`, W	Trainable floating leaf tensor `[D,V]`	Existing vocabulary projection
`output_bias`, β	Trainable floating leaf tensor `[V]`	Existing candidate biases
`batch_starts`	`list[list[int]]`	Ordered schedule; one inner list supplies the starts for one batch/update
`context_length`, T	Positive Python integer	Positions in each input/target row
`learning_rate`, η	Nonnegative Python float	Multiplier passed unchanged to each step

N is the source length, D the vector width, and V the candidate count. Let $K =$ `len(batch_starts)`. For update index k, $B_k =$ `len(batch_starts[k])`. Batches may have different sample counts. For example, `[[0,1],[3,4]]` means two updates, each with two samples. `[[0],[3,4]]` means two updates with one and two samples respectively. K counts updates; each B_k counts samples within that update.

Assume $N \geq T + 1$, every inner list is nonempty, starts satisfy $0 \leq$ `start` $\leq N - T - 1$, IDs are valid, floating dtypes/devices match, parameters have separate storage, and gradient mode is normal. Repeated starts are permitted. The **outer** schedule may be empty. Input validation is not assigned.

Return a fresh `losses: list[float]`, length K, preserving update order. Original parameters retain their final values; do not return replacement tensors. Source IDs, the nested schedule, caller gradient mode, and random state stay unchanged. The last step's gradients remain stored. An empty schedule returns `[]`, calls neither helper, and preserves existing parameter values and gradient buffers.

Changing batches and persistent parameters

For update k, let its start list be S_k, sample count B_k, and sample index b. For $k = 0, \dots, K-1$, $b = 0, \dots, B_k - 1$, and $t = 0, \dots, T-1$:

$$(X_k)_{b,t} = \texttt{token_ids}[S_k[b] + t], \qquad (Y_k)_{b,t} = \texttt{token_ids}[S_k[b] + t + 1]$$

Both tensors have shape $[B_k, T]$. Targets are already shifted by one. Reuse `make_next_token_batch(token_ids, start_positions, context_length)` rather than writing the slicing logic again.

Let $\theta_k = (E_k, W_k, \beta_k)$ be the parameters after k updates, before the next update. For the mathematical candidate distribution from those parameters:

$$\mathcal{L}_k = \mathcal{L}(\theta_k; X_k, Y_k) = -\frac{1}{B_k T} \sum_{b,t} \log P_{\theta_k}(Y_{k,b,t} \mid X_{k,b,t})$$

This conditional notation refers to the current-ID lookup baseline. It does not yet claim an attention model conditions on the full prefix. For each step, IDs and targets are fixed during differentiation, and the derivative is with respect to the current parameters.

$$\theta_{k+1} = \theta_k - \eta \nabla_\theta \mathcal{L}(\theta_k; X_k, Y_k), \qquad \texttt{losses}[k] = \mathcal{L}_k$$

The recurrence means the second helper call starts from the first call's updated parameters. Creating new parameters or restoring their initial values inside the loop breaks it. `batch_train_step` already clears previous gradients, runs forward/backward, copies its observations, and updates all three parameters. This wrapper organizes data and records its returned loss; it performs no extra backward or update.

The number of updates and supervised-position budget are:

$$K = \text{len}(\texttt{batch_starts}), \qquad M = T \sum_{k=0}^{K-1} B_k$$

M counts processed supervision positions, including repeated windows and overlaps. It is not a count of unique source IDs, new generated tokens, or the number of vocabulary entries.




Figure 47: An explicit source-window schedule feeds successive updates on the same parameter objects.

Figure 03.22-1 — Read the two update rows from top to bottom. Each row lists its source starts, constructed inputs and targets, old/new parameter state, and one returned loss. The first row produces the state used by the second.

Complete worked example: two distinct batches

Use the hand-picked correctness fixture `ordered-two-batch-v1`:

```
token_ids = [0,1,0,1,1,0,1]
batch_starts = [[0,1],[3,4]]
context_length = 2
learning_rate = 0.1
```

Initial parameters are `E=[[1],[2]]`, `W=[[1,0]]`, and `beta=[0,0]`, so $D = 1, V = 2$. There are $K = 2$ updates, $B_0 = B_1 = 2$ samples per update, and $M = 2(2 + 2) = 8$ processed supervision positions. The source has seven IDs; overlapping windows legitimately give eight processed positions.

First batch: starts [0,1], state θ_0

Start zero gives input `[0,1]`, target `[1,0]`. Start one gives input `[1,0]`, target `[0,1]`:

$$X_0 = \begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix}, \qquad Y_0 = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}$$

This matches 03.21's full example. Flat score rows are `[1,0],[2,0],[2,0],[1,0]`. Targets `[1,0,0,1]` select probabilities `[0.2689414214,0.8807970780,0.8807970780,0.2689414214]`. Four position losses are:

```
[1.3132616875, 0.1269280110, 0.1269280110, 1.3132616875]
```

Their mean is $L_0 = 0.7200948493$. The old-state gradients are:

```
G_E    = [[ 0.3655292893],[-0.0596014610]]
G_W    = [[ 0.2463263673, -0.2463263673]]
G_beta = [ 0.3059278283, -0.3059278283]
```

The first step changes the original parameters to state θ_1:

```
E_1    = [[0.9634470711],[2.0059601461]]
W_1    = [[0.9753673633,0.0246326367]]
beta_1 = [-0.0305927828,0.0305927828]
losses = [0.7200948493]
```

The append happens after the helper returns, but the number describes the state **before** its update. Do not recompute it with the new parameters.

Second batch: starts [3,4], state θ_1

Start three gives input `[1,1]`, target `[1,0]`. Start four gives input `[1,0]`, target `[0,1]`:

$$X_1 = \begin{bmatrix} 1 & 1 \\ 1 & 0 \end{bmatrix}, \qquad Y_1 = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}$$

The source includes a $1 \rightarrow 1$ pair; these targets are correct. Use θ_1 from the preceding update. Input one now gives scores `[1.9259552757,0.0800048704]`; input zero gives `[0.9091220465,0.0543250245]`. For example, candidate zero for input one is $2.0059601461 \times 0.9753673633 - 0.0305927828 \approx 1.9259552757$.

q	Input ID	Target ID	Selected probability	Position loss
0	1	1	`0.1363490673`	`1.9925370102`
1	1	0	`0.8636509327`	`0.1465866049`
2	1	0	`0.8636509327`	`0.1465866049`
3	0	1	`0.2984275419`	`1.2092281165`

Thus:

$$\mathcal{L}_1 = \frac{1.9925370102 + 0.1465866049 + 0.1465866049 + 1.2092281165}{4} \approx 0.8737345841$$

The second old-state gradients are:

```
G_E    = [[0.1667523248],[0.1404598367]]
G_W    = [[0.4653389228,-0.4653389228]]
G_beta = [0.3231313141,-0.3231313141]
```

For instance, the last position's score gradient is approximately `[0.1753931145,-0.1753931145]`. Multiplying by W_1^T gives its input-zero table gradient $0.1753931145 \times (0.9753673633 - 0.0246326367) \approx 0.1667523248$. Three input-one positions contribute to their shared row. The complete chain-rule derivation is retained in 03.21; this wrapper delegates it to the step helper.

After the second update, the same original tensors hold θ_2:

```
E_2    = [[0.9467718386],[1.9919141624]]
W_2    = [[0.9288334710,0.0711665290]]
beta_2 = [-0.0629059142,0.0629059142]
losses = [0.7200948493,0.8737345841]
```

Return this two-item history. For example, $(E_2)_{0,0} = 0.9634470711 - 0.1 \times 0.1667523248 \approx 0.9467718386$. The caller already holds the final parameter tensors. A separate final evaluation is not a third update or an extra history item.

Why the returned loss history can rise

The two history entries measure different data at different parameter states:

$$\texttt{losses}[0] = \mathcal{L}(\theta_0; X_0, Y_0), \qquad \texttt{losses}[1] = \mathcal{L}(\theta_1; X_1, Y_1)$$

Batch B contains a harder $1 \to 1$ target for the current model. Comparing `0.720095` with `0.873735` alone cannot isolate the effect of the parameter update. For this illustration, recompute each fixed batch separately at the same successive states:

Parameter state	Fixed batch A	Fixed batch B
θ_0	`0.7200948493`	`0.9235114302`
θ_1	`0.6779073607`	`0.8737345841`
θ_2	`0.6404176541`	`0.8092791313`

Both fixed-batch columns decrease **in this example**, while the recorded history moves from A at θ_0 to B at θ_1. The same-batch comparisons here are illustrative recomputations, not held-out validation. A small step does not guarantee every batch's loss decreases in general. Later lessons define a fixed evaluation protocol and a separate validation split.




Figure 48: Fixed-batch loss curves and the mixed-batch recorded history measure different paths.

Figure 03.22-2 — The horizontal axis counts completed updates. The two solid curves each keep their data fixed while parameters change. The orange dashed history joins A at update count zero to B at count one. It has two entries; the final state at count two has no automatic history entry.

Syntax and control flow before implementation

`batch_starts` is a nested list. `for start_positions in batch_starts:` visits each inner list itself. With `[[0,1],[3,4]]`, the loop variable becomes `[0,1]`, then `[3,4]`. It is not the update index `0,1`, and it is not a single start value.

`make_next_token_batch(...)` returns two tensors; tuple unpacking saves them as `input_ids, target_ids`. `batch_train_step(...)` returns a four-item tuple. Save it as `step_result`; `[0]` selects the pre-update Python float. `losses.append(loss_value)` adds one float to the fresh list.

Function-level setup, the `for` header, and the final `return` use four spaces. Everything inside the loop uses eight. When the outer list is empty, the loop body runs zero times and execution still reaches `return losses`. Returning inside the loop would stop after its first batch and would not handle an empty schedule correctly.

The builder handles target alignment. The step handles gradient clearing, forward/backward, snapshots, and updates. Keep this coordinating loop in normal gradient mode; no outer no-grad context, additional update, or parameter reconstruction is needed.

Seven guided implementation steps

Write only `train_batches`'s marked learner region after completing 03.21.

1. **Create history.** At four spaces, create `losses` with `[]`. Expected initial state: a new empty list; parameter tensors already exist.
2. **Visit scheduled batches.** At four spaces, start `for start_positions in batch_starts:`. Its eight-space body first receives `[0,1]`, then `[3,4]` in the example.
3. **Construct this batch.** At eight spaces, call `make_next_token_batch(token_ids, start_positions, context_length)` once and unpack `input_ids, target_ids`. First shapes `[2, 2]`; use the builder's existing target shift.
4. **Train once.** At eight spaces, call `batch_train_step(embedding_table, input_ids, output_weights, output_bias, target_ids, learning_rate)` once, saving `step_result`. It changes the original parameters to the next state.
5. **Select its old-state loss.** At eight spaces, save `step_result[0]` as `loss_value`. First value `0.7200948493`; second value `0.8737345841`.
6. **Append once.** At eight spaces, use `losses.append(loss_value)`. Store neither the whole tuple nor gradients. After two updates, the list has two floats.
7. **Return after the loop.** At four spaces, return `losses`. An empty schedule gives `[]`. The caller's original parameters retain their final state; do not append a final recomputed loss.

Supplied checks and expected output

After completing both the prerequisite 03.21 and this core, run from the repository root:

```
python exercises/03_22_batch_training_loop.py
```

Expected output:

```
PASS: two different batches, pre-update history, and persistent final parameters
PASS: empty schedule returns a fresh list and preserves values and existing gradient buffers
PASS: supplied batch order, varying batch sizes, repeated starts, and aligned targets
PASS: one builder and one step call per batch, same parameter objects, and normal gradient mode
PASS: separate calls continue from current parameters and keep independent loss histories
PASS: zero learning rate still visits every scheduled batch and records one loss each
PASS: strided source, IDs above 255, dtype preservation, and unchanged source/schedule/random
 ↪  state
Lesson 03.22 checks passed.
```

Before implementation, `NotImplementedError` marks an open learner core. A completed 03.22 loop also needs the completed 03.21 helper to run nonempty schedules. Check-driver initialization and library references are supplied, not additional learner assignments.

Reader questions and understanding checkpoints

Is a batch the whole source sequence? No. The source is `[N]`; an inner start list selects several length-T windows to form $[B_k, T]$. The outer schedule specifies which batch is used at each update.

Does a repeated input ID with different targets mean bad alignment? Not necessarily. Our source includes both $1 \to 0$ and $1 \to 1$. The current-ID baseline must share one distribution for input one across those occurrences. A contextual model can later distinguish occurrences using prior context, while data targets remain the observed next IDs.

Should I initialize parameters inside the loop? No. Preserve the recurrence: the next batch uses what the preceding update learned. A separate call also continues from the current values supplied by its caller.

Is an empty schedule the same as zero learning rate? No. Empty means no batch or step call and no gradient changes. Zero learning rate with a nonempty schedule still builds every batch, computes each loss/gradient, and records the results; parameter values stay unchanged.

Is this an epoch or random sampling? The schedule is simply a supplied ordered list. It does not guarantee covering a dataset once and introduces no randomness. Epoch definitions, shuffling, and random-stream ownership will be introduced explicitly later.

Can I compare a mixed history as validation? These entries use changing training data and changing parameter states. A fixed evaluation set at a given state is a different measurement. If batch sizes vary, averaging batch means also needs deliberate weighting; full evaluation is later work.

Optional independent checkpoints: distinguish N, K, B_k, and T; construct both batches by hand; trace old-state loss timing and shared parameter continuity; explain the mixed-history rise, empty sched-

ule, and zero rate. Try an explanation first, then check it against a small trace.

03.23 Fixed-Parameter Batch Loss Evaluation

To compare model states, we need a measurement that does not train while measuring. Evaluation holds the parameters fixed and combines the losses from all selected positions. When batches have different sizes, weighting by positions is what makes that combined result mean what we intend.

Work through the example before editing 03_23_evaluate_batches.py. The numbered steps below explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

Exact inputs, return, and state

Exact name	Type/shape	Meaning
`embedding_table`, E	Floating tensor `[V,D]`	Supplied token vectors
`token_ids`	Fixed `torch.long` tensor `[N]`	Supplied evaluation source
`output_weights`, W	Floating tensor `[D,V]`	Supplied vocabulary projection
`output_bias`, β	Floating tensor `[V]`	Supplied candidate biases
`batch_starts`	Nonempty `list[list[int]]`	One nonempty start list per evaluation batch
`context_length`, T	Positive integer	Supervised positions per sample

There is no `learning_rate`: the evaluator reads the supplied parameter state. Parameters may have `requires_grad=True` or `False`; preserve those flags. Assume valid IDs, compatible floating dtypes/devices, $N \geq T + 1$, valid starts $0 \leq$ `start` $\leq N - T - 1$, and finite scores in the checks' supported numerical range. No input validation is assigned.

Return one Python float: total position loss divided by total position count. Preserve parameter values/storage/dtype/device/trainability, existing gradient-buffer objects and values, source IDs, nested schedule, caller gradient mode, and random state. Do not backward, clear gradients, update parameters, or call `batch_train_step`/`train_batches`.

Different batches may have different B_k. Every scheduled occurrence counts, including repeated starts and overlapping windows. Evaluation grouping can change without changing the result when it covers the same position occurrences at the same parameter state. Changing or duplicating only some occurrences changes their weighting and can change the metric.

A single fixed parameter state

Let $\theta = (E, W, \beta)$ stay fixed across all K evaluation batches. Batch k has B_k rows, T positions per row, and $n_k = B_k T$ supervised positions. The builder supplies aligned inputs X_k and targets Y_k.

Indices are $k = 0, \dots, K-1$, $b = 0, \dots, B_k - 1$, $t = 0, \dots, T-1$, $d = 0, \dots, D-1$, and candidate $v, j = 0, \dots, V-1$. For each position, the score distribution and target loss are:

$$Z_{k,b,t,v} = \sum_d E[X_{k,b,t}, d] W_{d,v} + \beta_v, \qquad P_{k,b,t,v} = \frac{e^{Z_{k,b,t,v}}}{\sum_j e^{Z_{k,b,t,j}}}$$

$$\ell_{k,b,t} = -\log P_{k,b,t,Y_{k,b,t}}, \qquad \overline{\mathcal{L}}_k = \frac{1}{n_k} \sum_{b,t} \ell_{k,b,t}$$

The stable completed loss helper returns $\overline{\mathcal{L}}_k$, the **mean within this batch**. Our requested overall objective assigns equal weight to every scheduled position:

$$M = \sum_{k=0}^{K-1} n_k, \qquad \mathcal{L}_{\text{eval}} = \frac{1}{M} \sum_{k,b,t} \ell_{k,b,t} = \frac{\sum_k n_k \overline{\mathcal{L}}_k}{\sum_k n_k}$$

This equality follows by multiplying each batch mean by its own count: $n_k \overline{\mathcal{L}}_k = \sum_{b,t} \ell_{k,b,t}$. Sum those position-loss sums, then divide once by the total count. All positions are included equally; no padding, ignored IDs, class weights, or label smoothing are used.

In code, `target_ids.numel()` supplies n_k, `loss.item()*batch_positions` reconstructs the batch's loss sum, and two Python accumulators hold the total sum and count.

For comparison, equal weighting of batch means gives:

$$\mathcal{L}_{\text{batches}} = \frac{1}{K} \sum_k \overline{\mathcal{L}}_k$$

In that metric, one position in batch k gets weight $1/(Kn_k)$, whereas our objective gives every position weight $1/M$. Equal-size batches make these formulas coincide. Unequal sizes generally give different values; accidental equality for particular losses does not make the objectives identical.




Figure 49: Fixed parameters feed each batch mean, which is converted to a sum and aggregated by position count.

Figure 03.23-1 — Follow the two batch rows into the final aggregation. Both rows read the same parameters. Their counts multiply the returned means before summation. The final denominator is six positions.

Complete worked example: two and four positions

Use the hand-picked correctness fixture `fixed-eval-six-pairs-v1`:

```
token_ids = [0,1,0,1,1,0,1]
batch_starts = [[0],[3,4]]
context_length = 2
E = [[1],[2]]
W = [[1,0]]
beta = [0,0]
```

Here $N = 7, T = 2, D = 1, V = 2$. The first batch has one sample; the second has two. Parameters stay at this initial state throughout. In particular, the second batch does **not** use the updated parameters from 03.22's example.

Batch A: start [0], B=1, n=2

```
input_ids  = [[0,1]]
target_ids = [[1,0]]
logits     = [[[1,0],[2,0]]]
```

For input zero, target one has probability $e^{-1}/(1+e^{-1}) \approx 0.2689414214$, giving loss $1 + \log(1 + e^{-1}) \approx 1.3132616875$. For input one, target zero has probability $1/(1+e^{-2}) \approx 0.8807970780$, giving loss $\log(1+e^{-2}) \approx 0.1269280110$.

$$\overline{\mathcal{L}}_A = \frac{1.3132616875 + 0.1269280110}{2} \approx 0.7200948493$$

Multiplying by two positions reconstructs `1.4401896986`. Running totals become `loss_sum=1.4401896986`, `total_positions=2`.

Batch B: starts [3,4], B=2, n=4

```
input_ids  = [[1,1],[1,0]]
target_ids = [[1,0],[0,1]]
logits     = [[[2,0],[2,0]],[[2,0],[1,0]]]
```

These four positions still use the initial `E,W,beta`:

Flat position	Input ID	Target ID	Target probability	Position loss
0	1	1	`0.1192029220`	`2.1269280110`
1	1	0	`0.8807970780`	`0.1269280110`

Flat position	Input ID	Target ID	Target probability	Position loss
2	1	0	`0.8807970780`	`0.1269280110`
3	0	1	`0.2689414214`	`1.3132616875`

The first row is harder: for scores `[2,0]`, target one gives loss $2 + \log(1 + e^{-2}) \approx 2.1269280110$. The four losses sum to `3.6940457206`; their mean is `0.9235114302`.

Running totals now become:

```
loss_sum = 1.4401896986 + 3.6940457206 = 5.1342354192
total_positions = 2 + 4 = 6
```

Thus return:

$$\mathcal{L}_{\text{eval}} = \frac{2(0.7200948493) + 4(0.9235114302)}{6} \approx 0.8557059032$$

Writing the two batch means as L_A and L_B, the same weighted result is:

$$L_{eval} = \frac{2L_A + 4L_B}{6} \approx 0.8557059032.$$

Directly averaging the two batch means instead gives:

$$\mathcal{L}_{\text{batches}} = \frac{0.7200948493 + 0.9235114302}{2} \approx 0.8218031397$$

It overweights each position in the smaller batch relative to a position in the larger batch. Under equal batch weights, the two A positions each receive $\frac{1}{4}$ and the four B positions each receive $\frac{1}{8}$. Under the requested position mean, all six receive $\frac{1}{6}$. Using rounded display values may slightly change final digits; checks and figures calculate with full precision.




Figure 50: The same six losses receive different weights under equal batch weights and equal position weights.

Figure 03.23-2 — Read down each position column. Its loss is unchanged; the weight differs between the two aggregation rows. Each displayed result is the sum of weight × position_loss. Only the position-equal row implements this assignment's objective.

Evaluation state and no-grad scope

Use `with torch.no_grad():` around the evaluation loop. It disables recording ordinary reverse-mode gradient computations for the lookup, projection, and loss operations, while retaining parameter trainability. Its context restores the caller's previous gradient mode when it exits. PyTorch no-grad documentation.

No-grad does not itself prohibit in-place mutation: 03.21 uses it during intentional updates. This evaluator preserves values by performing read-only forward/loss operations. It does not clear existing `.grad`, which may still hold the last training step's derivatives. Those buffers stay intact, while the evaluation's new score/loss tensors have no autograd graph.

Later, an `nn.Module` model may also need `model.eval()` for the evaluation behavior of layers such as Dropout. That setting changes module mode and is separate from gradient tracking. This assignment has plain parameter tensors and does not call `.eval()` on them. Module evaluation documentation.

Evaluation here needs a reporting value, so `.item()` is appropriate after computing the mean tensor. In 03.20, returning `.item()` would have removed the graph needed by a training caller; this evaluator has no backward operation to perform.

Syntax and indentation before coding

`loss_sum = 0.0` initializes a Python float. `total_positions = 0` initializes a Python integer. Both are created fresh for each call. `target_ids.numel()` returns an element count: a tensor with shape `[1,2]` has two elements, and one with shape `[2,2]` has four. It does not sum ID numbers or count vocabulary candidates.

Use four spaces for the initial totals and `with torch.no_grad():`. The `for start_positions in batch_starts:` header sits inside that context at eight spaces. Its batch-building/score/loss/aggregation body uses twelve spaces. Return to four spaces for the final division/return, outside both loop and context.

The nesting applies gradient settings while iterating. `+=` increases each total; multiplication by the batch count first reverses the helper's within-batch mean, so it is not a second averaging operation. A final positive denominator is guaranteed by the nonempty-input assumptions.

Eight guided implementation steps

Write only `evaluate_batches`'s marked learner region.

1. **Create totals.** At four spaces, initialize `loss_sum` to `0.0` and `total_positions` to `0`. Parameters are supplied; keep their values and flags.

2. **Enter evaluation gradient scope.** At four spaces, start `with torch.no_grad():`. Keep this setting local to the context.
3. **Visit batches.** At eight spaces, start `for start_positions in batch_starts:`. The loop body is twelve spaces. In the example, starts are `[0]` then `[3,4]`.
4. **Build aligned IDs.** At twelve spaces, call `make_next_token_batch(token_ids, start_positions, context_length)` once and unpack `input_ids, target_ids`. Shapes are `[1, 2]` then `[2,2]`.
5. **Compute raw scores.** At twelve spaces, call `compute_batch_logits(embedding_table, input_ids, output_weights, output_bias)` once, saving `logits`. Shapes are `[1,2,2]` then `[2,2,2]`, using identical parameter values.
6. **Compute this batch's mean.** At twelve spaces, call `batch_cross_entropy(logits, target_ids)` once, saving `loss`. Means are approximately `0.7200948493` and `0.9235114302`.
7. **Add sum and count.** At twelve spaces, obtain `batch_positions = target_ids.numel()`. Increase `loss_sum` by `loss.item()*batch_positions` and `total_positions` by `batch_positions`. Totals progress from `(1.4401896986,2)` to `(5.1342354192,6)`.
8. **Return the overall position mean.** Back at four spaces, return `loss_sum / total_positions`. The result is a Python float near `0.8557059032`. The original parameter state and stored gradients remain unchanged.

Supplied checks and expected output

Run from the repository root in the existing environment after implementing this core:

```
python exercises/03_23_evaluate_batches.py
```

Expected output:

```
PASS: six-position mean weights unequal batch sizes and returns one Python float
PASS: grouping/order invariance for the same positions and deliberate duplicate-start counting
PASS: each completed helper reused once per batch under no-grad without score/loss graphs
PASS: fixed parameter values/storage/trainability and existing gradient objects/values preserved
PASS: repeated fixed-state results agree and changed supplied parameters are reevaluated
PASS: one-candidate zero loss and stable finite loss for extreme raw scores
PASS: strided source, merged IDs, floating dtypes, untrainable tensors, and caller-mode
↪  restoration
Lesson 03.23 checks passed.
```

`NotImplementedError` before coding indicates the deliberately open learner region. The supplied reference concatenates scheduled position occurrences and calculates one library mean independently of this batch-weight aggregation. The numeric prerequisite helpers are completed; unfinished training exercises are not imported by this driver.

Training, validation, and reader questions

Is calling this function enough to create a validation set? No. It measures the sequence and windows supplied by its caller. Training loss uses data involved in updates; validation loss uses data held out from those updates. Our familiar six-pair fixture demonstrates arithmetic only. A later lesson will implement a reproducible split and evaluation schedule.

Where should a split happen? Separate source texts/documents before constructing overlapping windows, then build windows separately within each chosen partition. Splitting already overlapping windows can place the same token spans in both sets. A future corpus protocol also records tokenizer/data versions and document boundaries.

What should stay fixed for a before/after comparison? Use the same evaluation source, start schedule, target alignment, tokenizer interpretation, weighting, and model behavior. Compare parameter states by running the evaluator separately; each call itself holds one state fixed.

Can I shuffle or regroup these batches? With this deterministic position-independent model and the same multiset of scheduled position occurrences, the position mean is unchanged up to floating-point rounding. Duplicate or drop some occurrences and the weighting changes. Later contextual models also require preserving each sample's context and masks while regrouping samples.

Why assume a nonempty evaluation? A mean over zero positions has no positive denominator. Reporting zero would falsely resemble a perfect score. This exercise assumes valid nonempty schedules rather than assigning an empty-policy implementation; 03.22's empty training history is a different contract.

Does lower evaluation loss prove a useful language model? It shows better target probabilities on this specified protocol. Generalization, generation quality, factual accuracy, and other capabilities need separate datasets and evaluations. The tiny lookup fixture establishes arithmetic and state behavior.

Optional independent checkpoints: derive the count-weighted mean; explain `numel()` and mean-to-sum conversion; distinguish no-grad, trainability, existing gradients, and later module mode; explain fixed-data comparisons and held-out sources. Try an explanation first, then check it against a small trace.

Placement in the course

Lesson 03.24 now connects encoding, the ordered training schedule, this fixed-parameter evaluator, and generation in one byte-baseline run. The evaluator continues to measure the caller-supplied windows; the combined fixture does not introduce a held-out split.

03.24 Connect the small baseline

The pieces of the small language-model baseline are ready to work together. One run will encode text, train on an explicit schedule, evaluate the final parameters, and decode a continuation. Following this path end to end will help us see both what the baseline can do and why the next chapter must add context.

Work through the example before editing 03_24_baseline_pipeline.py. The numbered steps below

explain the interface and guide the core implementation; the supplied setup and check driver remain separate.

Formulas and principles first

Write the parameter state as

$$\theta = (E, W, \beta), \qquad E \in \mathbb{R}^{256\times 1}, \quad W \in \mathbb{R}^{1\times 256}, \quad \beta \in \mathbb{R}^{256}.$$

E is the embedding table, W the vocabulary projection, β the bias. $V = 256$ comes from byte IDs 0–255; $D = 1$ is a teaching choice. Supplied initialization uses ones for E and zeros for W/β; all three tensors are trainable.

Every input position independently looks up and scores its current ID:

$$h_{b,t} = E[X_{b,t}], \qquad z_{b,t} = h_{b,t}W + \beta, \qquad p_{b,t} = \text{softmax}(z_{b,t}).$$

b indexes batch samples, t window positions and v vocabulary candidates. Targets Y are already shifted by one from X; do not shift them again.

Training batch k computes a mean next-token loss and one update:

$$L_k = -\frac{1}{B_k T}\sum_{b=0}^{B_k-1}\sum_{t=0}^{T-1}\log p_{\theta_k}(Y_{k,b,t} \mid X_{k,b,t}), \qquad \theta_{k+1} = \theta_k - \eta\nabla_\theta L_k.$$

η is `learning_rate`, T is `context_length`. 03.21/03.22 already implement these operations. `history[k]` records pre-update L_k; the final parameters are at θ_K.

Evaluation keeps θ_K fixed and aggregates all selected positions:

$$L_{eval} = \frac{\sum_j n_j \overline{L}_j(\theta_K)}{\sum_j n_j}, \qquad n_j = B_j T.$$

j indexes evaluation batches. 03.23 owns target weighting and no-grad; it neither updates parameters nor clears existing gradients.

Generation also keeps θ_K fixed and selects one new ID at a time:

$$x_{new} = \arg\max_{v\in\{0,\ldots,255\}} p_{\theta_K}(v \mid x_{last}).$$

The current lookup baseline conditions only on the last input ID. Passing a growing prefix does not create attention; Chapter 04 introduces earlier context.




Figure 51: One run shares one set of parameters

Read the top row in execution order, then follow final θ_2 into both lower stages. Arrows show data/state transfer, not evaluation-driven updates.

Function contract

```
def run_baseline(
    text: str,
    train_starts: list[list[int]],
    eval_starts: list[list[int]],
    context_length: int,
    learning_rate: float,
    updates: int,
) -> dict:
```

Input	Type and meaning	Fixture
text	Nonempty ASCII str, encoded into N byte IDs; $N \geq T + 1$	`"abababab"`
train_starts	Nonempty list of nonempty start lists; one inner list per batch	`[[0,2]]`
eval_starts	Nonempty nested evaluation start schedule	`[[1,3]]`

Input	Type and meaning	Fixture
context_length	Positive T, input and shifted-target positions per window	`2`
learning_rate	Nonnegative η, passed only to training	`0.2`
updates	Nonnegative integer **repeat count for the entire train_starts schedule**, retaining the existing parameter name	`2`

Every start satisfies $0 \le \texttt{start} \le N - T - 1$. Assume valid inputs; validation is not a separate learner task.

If `train_starts` has M batches, actual parameter-update count is

$$K = \texttt{updates} \times M, \qquad C_{positions} = \texttt{updates} \times T \sum_{m=0}^{M-1} |\texttt{train_starts}[m]|.$$

`[[0],[1,3]] * 2` contains four batches, not two. List multiplication repeats items rather than multiplying their integer starts. Inner lists are shared references;03.22 preserves them, so that repetition is suitable here.

The result dictionary has three fields:

Key	Type	Meaning
`history`	`list[float]`	One pre-update mean per actual training update
`eval_loss`	`float`	Mean under final fixed parameters
`continuation`	`str`	Generated text excluding the prompt

This interface returns reports, not parameter tensors or a checkpoint. Later lessons introduce saved training state.

Complete worked trace

Use the input table above. Encoding gives:

```
text       = "ababab"
position   =  0   1   2   3   4   5
token_ids  = [97, 98, 97, 98, 97, 98]
```

`text.encode("utf-8")` returns bytes, `list(...)` returns integer values, and the long tensor has shape `[6]`. Long is index storage, not a change to byte semantics.

Build the training schedule. `[[0,2]] * 2` gives `[[0,2],[0,2]]`. Both batches visit the same source windows:

```
start0: X=[97,98], Y=[98,97]
start2: X=[97,98], Y=[98,97]
X=[[97,98],[97,98]], Y=[[98,97],[98,97]]
B=2, T=2; both shapes [2,2]
```

Initially E rows are `[1]` and W/β zero, so all 256 logits at each position are zero. Every candidate probability is $1/256$; every target loss is

$$-\log(1/256) = \log 256 \approx 5.5451774445.$$

The mean of four identical losses is still 5.5451774445; neither multiply nor divide it by four again. 03.22 records this loss and updates to θ_1. The second batch uses θ_1 and records 5.3469056593 before updating to θ_2. Two batches × two windows × two targets process eight position occurrences, including repeated data.

Evaluate final θ_2. `eval_starts=[[1,3]]` gives:

```
start1: X=[98,97], Y=[97,98]
start3: X=[98,97], Y=[97,98]
```

These four targets under the final state yield `eval_loss≈5.1473975533`. This is not a third history entry; it occurs after all training updates.

03.24 Schedule, parameter state and logging time




Figure 52: Schedule, state and loss-recording time

θ_0/θ_1 feed training updates and their losses enter history. θ_2 feeds separate fixed evaluation. Different starts still use the same short text, not independent validation.

Generate four new IDs. `token_ids[:1]` is the one-dimensional prompt `tensor([97])`. The generator returns the full prompt plus new IDs, length 1+4=5. The verified run produced:

```
full generated_ids  = [97,98,98,98,98]
remove one prompt ID= [98,98,98,98]
.tolist()           = [98,98,98,98]   # Python integers
bytes(...)          = b"bbbb"
decode(...)         = "bbbb"         # Python string
```

This is an observed run, not an exact output requirement on every platform. The mathematical a/b probabilities are symmetric; tiny rounding or tie choices can select a or b. Checks require the interfaces and four generated byte positions.

The report for this run is approximately:

```
history      = [5.5451774445, 5.3469056593]
eval_loss    = 5.1473975533
continuation = "bbbb"
```

Why not automatically continue abab? This specific initialization gives every embedding the same 1 and balanced a/b targets preserve symmetry. Both a/b probabilities rise from 0.00390625 to about 0.005814517, lowering loss, yet greedy generation can repeat one ID. A current-token model with broken parameter symmetry can learn a→b, b→a; its inability to distinguish different prefixes ending in the same ID is a separate limitation. This fixture checks wiring, not language ability.

Eight implementation steps: learner writes the core

Open 03_24_baseline_pipeline.py, edit only the learner region, and keep **four spaces** for all these function-body steps. Helpers already contain their loops; do not add another training loop.

1. **Encode IDs.** Use `.encode("utf-8")`, `list(...)`, then `torch.tensor(...,dtype=torch.long)` for `token_ids`, shape `[6]`, values `[97,98,97,98,97,98]`.
2. **Initialize once.** Call supplied `initial_parameters()` and unpack `embedding_table,output_weights,output_bias`, shapes `[256,1]`, `[1,256]`, `[256]`. Keep these objects through the run.
3. **Repeat the schedule.** Save `train_starts * updates` as `training_schedule`; fixture `[[0,2],[0,2]]`. Zero repeats gives `[]` without a special branch.
4. **Train.** Call `train_batches` with `embedding_table,token_ids,output_weights,output_bias,training_schedule,context_length,learning_rate`, storing `history`. Do not wrap the pipeline in no-grad; training needs a graph.
5. **Evaluate.** Call `evaluate_batches` with `embedding_table,token_ids,output_weights,output_bias,eval_starts,context_length`, storing `eval_loss`. No learning-rate argument, reinitialization or gradient clearing.
6. **Prompt and generate.** Take `context_ids=token_ids[:1]`, shape `[1]`; indexing with `[0]` gives a scalar and a Python list is not the required tensor. Call `generate_token_ids` with

`embedding_table,context_ids,output_weights,output_bias,4`, storing complete `generated_ids`, shape `[5]`.

7. **Decode only new IDs.** Slice past `context_ids.numel()` prompt IDs. Convert `continuation_ids` via `.tolist()`, `bytes(...)` and `.decode("utf-8",errors="replace")` into `continuation`. Join bytes before decoding, not individually.
8. **Return a dictionary.** Use dictionary syntax `{"name": value}` for the three named fields `history,eval_loss,continuation`, mapped to the saved results. Return at four spaces.

Remove the placeholder `raise NotImplementedError(...)`; retain supplied imports, initialization and check driver.

Boundaries and misconceptions

- Zero repeats returns `history=[]` but still evaluates and generates. Initial evaluation is ln256; the function still executes.
- a/b tie behavior is not a reason to hardcode the example continuation.
- 03.14 returns prompt+continuation; this wrapper reports continuation only.
- `errors="replace"` is a display policy, not a change to targets, generated IDs or parameters.
- Training/evaluation windows overlap in this fixture. Real held-out evaluation requires document splits and a frozen tokenizer.
- Byte IDs can be converted directly to bytes; merged BPE IDs need vocabulary lookup first.
- Initializing per run is different from initializing per batch, which discards learned updates.

Run and check

From the repository root in the existing PyTorch environment:

```
python exercises/03_24_baseline_pipeline.py
```

Final success line:

```
Lesson 03.24 checks passed.
```

Checks cover the fixture's old-state history/final evaluation, zero repeats, and passing the same parameters through real helpers in the correct order. Passing and independent reasoning remain separate records.

Reader questions: list repetition, BPE and the prompt contract

What the list multiplication means

Python chooses the operation from operand types. Here `train_starts` is a Python list. Multiplying a list by a nonnegative integer repeats its sequence; it does not multiply the integers stored inside the list.

```
[1, 2] * 3
# [1, 2, 1, 2, 1, 2]
```

```
[[0, 2]] * 3
# [[0, 2], [0, 2], [0, 2]]
```

An inner list such as `[0,2]` means two source-window starts combined into one batch, not two batches. With a two-batch schedule:

```
train_starts = [[0,2], [1,3]]
updates = 2
training_schedule = [[0,2], [1,3], [0,2], [1,3]]

update1: one batch built from starts [0,2]
update2: one batch built from starts [1,3]
update3: one batch built from starts [0,2]
update4: one batch built from starts [1,3]
```

For this two-repeat example, list multiplication is equivalent to `train_starts + train_starts`. The model is initialized once before the entire schedule; repeating the list does not reset the parameters.

The instructor-chosen name `updates` is imprecise here: the argument is a **schedule repetition count**, better read as `schedule_repeats`. The existing signature is retained so the learner need not change every caller. Actual SGD steps are `len(train_starts)*updates`, not necessarily `updates` itself.

Why this fixture does not call BPE

This 03.24 scaffold deliberately used a byte tokenizer to make stage wiring explicit: `text.encode('utf-8')` followed by integer byte IDs. BPE is an additional learned merge stage over those bytes; the model accepts integer IDs from either representation. A byte-only model is a teaching choice, not a model restriction. The complete prepared pretraining lab in `scripts/pretrain_lab.py` already reuses the Chapter 02 BPE training, encoding and vocabulary serialization helpers.

For a concrete connection, freeze just the learned rule $(97, 98) \to 256$:

```
text "ababab"
byte IDs:       [97,98,97,98,97,98]   N=6, vocabulary size 256
BPE IDs:        [256,256,256]         N=3, vocabulary size 257
vocab[256]:     b"ab"
rejoined bytes: b"ababab"
```

A BPE version must adapt all of these together:

1. **Encoding:** call the frozen `encode_bpe`; train rules on training data only, then reuse identical rules for evaluation and generation prompts.
2. **Model dimensions:** use $V =$ `len(vocab)` for this contiguous vocabulary; E is `[V,D]`, W `[D, V]`, bias `[V]`. The current hardcoded 256 rows cannot represent ID 256.
3. **Windows and accounting:** starts and T refer to token positions after BPE. Here N=3, T=2 allows only start 0, whereas byte N=6, T=2 permits starts 0..3. The original byte schedules cannot simply be reused. Uniform initial loss changes from ln 256 to ln 257.
4. **Decoding:** map each generated ID through `vocab`, join the resulting bytes, then decode.

`bytes([256])` is invalid because 256 is an ID, not one byte value. The strict `decode_bpe` serves valid UTF-8 round trips; generated text still needs an explicit invalid-UTF-8 display policy when arbitrary bytes are emitted.

5. **Checks:** four new tokens need not mean four characters. If all four new IDs are 256, they represent `"abababab"`, eight ASCII characters. A BPE lab must replace the byte fixture's exact losses and four-character assumptions.

This explains where the completed BPE work fits without silently changing the current byte assignment's interface or grading contract.

Why this exercise uses a one-ID prompt

Compare these two choices. The first uses the training window length as the prompt length:

```
context_ids = token_ids[:context_length]
```

With `token_ids=[97,98,97,98,97,98]` and `context_length=2`, this selects `[97,98]`. The exercise explicitly chooses one prompt ID `[97]`, obtained by the slice:

```
context_ids = token_ids[:1]
```

`context_length` determines training/evaluation window width. Prompt length is a separate choice. A two-token prompt is a valid general generation design, but it differs from this exercise's fixed one-token prompt contract; the assertion is checking that contract, not declaring every two-token prompt invalid.

A closer look at IDs, counts, and batch starts

Question: "Does token ID mean the total number of tokens, or all the token IDs? Is `training_schedule` the training batch-start table?"

A token ID is an **identifier**, not a count. `token_ids` holds the IDs at each position of this particular text; it is not the inventory of the full vocabulary. Use the same byte-tokenized example throughout:

```
text:       "ababab"
position:    0   1   2   3   4   5
token ID:   97  98  97  98  97  98
```

Read the two rows vertically: at position 0 the ID is 97; at position 1 the ID is 98. Here 97 identifies the byte token for `a`, and 98 identifies the one for `b`. Neither ID says how many tokens exist. The sequence contains six tokens:

$$N = \text{len}(\texttt{token_ids}) = 6.$$

For the actual one-dimensional tensor, `token_ids.numel()` also gives 6. "All IDs in this text" describes the sequence `[97,98,97,98,97,98]`; "the number of tokens in this text" describes the scalar 6.

The training schedule specifies which window starts form each batch and the order in which batches are used. The exact helper parameter name is `batch_starts`, not "start batches."

```
train_starts = [[0, 2]]
updates = 2
training_schedule = train_starts * updates
# [[0, 2], [0, 2]]
```

Here 0 and 2 are **positions in the sequence**, not token IDs. With `context_length=2`, one inner list `[0,2]` describes two input windows:

Start position	Input positions	Input IDs	Target positions	Target IDs
0	0, 1	97, 98	1, 2	98, 97
2	2, 3	97, 98	3, 4	98, 97

Both rows together form **one batch**. The two inner lists in `training_schedule` request two successive training updates using these starts; the second update continues from the first update's parameters.

The names belong to different places in the call:

Name	Meaning in the actual exercise
`train_starts`	Original ordered table of training batch starts in `run_baseline`.
`training_schedule`	That table repeated `updates` times.
`batch_starts`	Parameter in `train_batches` that receives `training_schedule`.

The caller's `training_schedule` and the helper's `batch_starts` refer to the same passed table. They are not two separately constructed training datasets.

A closer look at one batch versus batch size B

Question: "Is the batch size 2, or is B=1 and T=2? I am getting the counts mixed up."

For the preceding example, **B=2 and T=2**. The outer list in `train_starts=[[0,2]]` contains one batch description; that does not make B=1. "One batch" counts groups. "Batch size B" counts samples within one group. In this exercise, each sample is one input window with its shifted target window.

Keep `token_ids=[97,98,97,98,97,98]` and `context_length=2`:

1. Start 0 selects input positions 0 and 1, giving `[97,98]`.
2. Start 2 selects input positions 2 and 3, also giving `[97,98]`.
3. Stack these two windows as two rows in one input batch.

```
                    T=2 token positions per row
                    t=0     t=1
```

```
sample 0, start 0          97      98
sample 1, start 2          97      98
          two rows: B=2
```

Read vertically to count samples B; read horizontally to count input token positions T within a sample. The equal row contents come from the repeated text; the rows still originate at different source positions.

$$B = \text{len}([0, 2]) = 2, \qquad T = \texttt{context_length} = 2, \qquad \text{shape}(\texttt{input_ids}) = [B, T] = [2, 2].$$

The nested schedule can now be read without conflating these counts:

Schedule	Scheduled batch updates	B within each batch	T within each sample
`train_starts=[[0,2]]`	1	2	2
`training_schedule=[[0, 2],[0,2]]`	2	2	2

Repeating the schedule makes the model process two batches in succession; it does not stack their rows into a single B=4 batch. To obtain **B=1, T=2**, one batch would instead have a single start, for example `[0]`, and its input matrix would be `[[97,98]]`, shape `[1,2]`. The corresponding one-batch schedule is `[[0]]`.

Follow-up: identifying T and B

A useful restatement: "`context_length` determines T, and B is the length of this list." The T correspondence is correct. For B, specify that "this list" means the **inner list of starts for one batch**.

```
context_length = 2
train_starts = [[0, 2]]
```

Here $T = 2$ (`context_length`) and $B = 2$ (`len(train_starts[0])`), giving the two-row, two-column input matrix illustrated above. The outer `len(train_starts)=1` counts scheduled batches, not samples within a batch.

Looking back

A complete loop can update parameters and generate text. Its restricted use of context is now visible rather than hypothetical. The next chapter replaces that restriction with learned attention over a causally permitted prefix.

04 Build a causal Transformer

Attention is an operation on positions, not an unexplained synonym for understanding. Queries compare with keys; the resulting weights combine values. The tensor layouts tell us which positions are compared and which features are transformed. Causal visibility then prevents a training position from reading its future answer.

We build the decoder one responsibility at a time: registered parameters, Q/K/V projections, scaled attention, masking, heads, position information, residual paths, normalization and feed-forward transformations. A shape and a matrix entry are shown separately because confusing them can make an incorrect transpose look plausible. The chapter ends by connecting the components to the familiar training and generation loops.

04.01 Why context matters

Chapter 03 connected training, evaluation, and generation. This lesson begins to exchange information between positions within a sequence.

From supplying positions to using earlier inputs

Connect this to 03.08: trainable embeddings: E **is the embedding matrix, and** E**[0] is the embedding vector for token ID 0.** The example's `[0,0]` is a hand-chosen vector value with dimension $D = 2$.

The new material aggregates embeddings from several positions into a contextual representation. First recall Chapter 03: look up token IDs as embedding vectors and project those vectors into logits. For one sample at position t, this can be written as:

$$u_t = E[x_t], \qquad z_t = u_t W + b.$$

Here x_t is the current token ID, E is the shared embedding table, u_t is the retrieved vector, and z_t contains scores for the next token. With fixed parameters, the same current ID produces the same scores. Earlier inputs do not participate in this position's computation.

For example, `[0, 1]` and `[2, 1]` both end in ID `1`, so the old model reads `E[1]` at both final positions. Putting two positions in a tensor does not automatically make the final position read the earlier one.

The window length T **controls how many input positions are supplied; the computation controls which of them each output can use.** Increasing `context_length` alone does not add contextual interaction to a position-wise lookup model.

We begin with a method that is easy to calculate by hand: at each position, average its own embedding and all earlier embeddings in the window. Call the result the contextual state h_t. A later output layer

could project h_t into logits; this assignment implements only the function that produces these states.

Distinguish their roles: $u_t = E[x_t]$ is the current token's embedding; h_t aggregates embeddings at visible positions into a contextual representation. Both are D-dimensional vectors. With E fixed, equal IDs retrieve equal embeddings, while the aggregated h_t can change with the preceding inputs.

Read the formula first

A **prefix** starts at the beginning of the sequence and ends at a selected position, including that position. Here the sequence is the supplied input window, with positions starting at 0 within that window. The first position's prefix contains only itself; the second position's prefix contains the first two inputs.

$$\boxed{h_t = \frac{1}{t+1} \sum_{j=0}^{t} E[x_j]}$$

Symbol	Meaning
t	Current output-position index, starting at 0
j	Input-position index traversed by the sum, from 0 through t
x_j	Token ID stored at input position j
$E[x_j]$	D-dimensional vector retrieved for that ID
$t+1$	Number of visible positions from 0 through t
h_t	D-dimensional vector formed by averaging corresponding coordinates

The summation symbol adds a sequence of vectors. Expand the first three positions:

$$h_0 = E[x_0], \qquad h_1 = \frac{E[x_0] + E[x_1]}{2}, \qquad h_2 = \frac{E[x_0] + E[x_1] + E[x_2]}{3}.$$

The divisor counts **positions contributing to the mean**, not coordinates within a vector. Even with $D = 8$, position $t = 1$ divides by 2. Every coordinate uses the same position count, so D is preserved.

"Causal" means that a computation depends only on its own and earlier inputs: h_0 cannot use x_1. This restriction still applies when the entire training window is already in memory; otherwise a next-token prediction could read its target directly.




Figure 53: Visible-position weights and different contextual states for the same current token

Read the figure by output row t and input column j. The first row, `[1, 0]`, uses only the first input; the second, `[1/2, 1/2]`, averages the first two inputs. The orange zero blocks a future position. The right-hand panels apply the same embedding table to two sequences. Both end in ID 1, but their averaged states differ. Each coefficient multiplies a whole vector.

These coefficients are fixed rules, not newly trained parameters. They provide a starting point for learning content-dependent aggregation later.

Function contract and dimensions

Use the function and parameter names from the exercise:

```
def prefix_mean(embedding_table: torch.Tensor, input_ids: torch.Tensor) -> torch.Tensor:
```

Variable	Type and shape	Meaning
`embedding_table`	Floating tensor `[V, D]`	Shared lookup table for V tokens, with D coordinates per row
`input_ids`	`torch.long` tensor `[B, T]`	B samples, each with T input positions
Return value	Floating tensor `[B, T, D]`	One prefix-mean vector for each position of each sample

Assume T>0, IDs in `0` through `V-1`, and compatible input devices. Preserve the embedding's floating dtype and device, leave both inputs unchanged, and retain the autograd path to `embedding_table`.

IDs can come from a byte tokenizer, BPE, or another fixed tokenizer. This function only looks up and aggregates vectors; 0, 1, and 2 are three toy IDs chosen for hand calculation.

The complete coordinate-level formula is:

$$H_{b,t,d} = \frac{1}{t+1} \sum_{j=0}^{t} E_{X_{b,j},d}.$$

Here b selects a sample, t an output position, and d a vector coordinate. Only j moves through the prefix of that same sample. Neither samples nor different feature coordinates are mixed.

Our fixture is deliberately small, with $B = T = D = 2$, but these axes have different meanings. A tensor `[B,T,D]=[2,3,4]` would represent two samples, three positions per sample, and four coordinates per position; its divisors would be `[1,2,3]`.

Classroom question: what do the two numbers in `E[0] = [0, 0]` mean?

`E` is the embedding lookup table. `E[0]` retrieves **the row for token ID 0**. The whole vector on the right, `[0, 0]`, contains two coordinates, so its dimension is $D = 2$. It represents one token, not two tokens.

Token ID (row to select)	First coordinate	Second coordinate	Retrieved vector
0	0	0	`[0, 0]`
1	2	0	`[2, 0]`
2	0	4	`[0, 4]`

The 0 inside the left-hand brackets is a **lookup ID**; the two zeros on the right are **vector-coordinate values**. Their equal numerical values are coincidental, and their roles differ. For example, `E[1]=[2,0]` uses ID 1 to retrieve the whole row `[2,0]`. It neither retrieves two tokens nor says that the token occurs twice.

Temporarily picture a two-dimensional vector as a point in a plane: these three tokens sit at `(0,0)`, `(2,0)`, and `(0,4)`. This is an analogy for coordinates, not a physical location. With $D = 3$, one token would have three coordinates; increasing the dimension does not increase the token count.

The fixture's coordinates are chosen by hand for easy arithmetic. No human-readable meaning is assigned to each dimension. A zero does not mean "no meaning," and the first coordinate does not necessarily represent grammar while the second represents another fixed property. If E is trainable, loss gradients adjust its coordinates so that the whole vector becomes useful for prediction. Individual coordinates generally have no predetermined semantic names.

The relationship to understand first is **one token ID → one retrieved vector → D trainable numerical coordinates**. $D = 2$ is a fixture choice; it does not limit vocabulary size V or the number of input positions T.

Classroom question: how do the shapes in `embedding_table[input_ids]` fit?

Consider why `embdded = embedding_table[input_ids]` works when the two input shapes differ so much. This is integer-tensor indexing: each integer in `input_ids` specifies a row of the embedding table and is replaced by that entire D-dimensional row vector. Looking up rows by ID does not require the two input shapes to match.

First retrieve one row: `embedding_table[1]` gives `[2,0]`, shape `[D]=[2]`. Then retrieve a sequence: `embedding_table[[0,1]]` selects rows 0 and 1 in that order, giving `[[0,0],[2,0]]`, shape `[T,D]=[2, 2]`. With a batch, each row of `input_ids` is looked up the same way:

```
embedding_table [V,D] = [3,2]
ID 0 → [0,0]
ID 1 → [2,0]
ID 2 → [0,4]

input_ids [B,T] = [2,2]          embedded [B,T,D] = [2,2,2]
[
    [0, 1],                   → [[0,0], [2,0]],
    [2, 1],                   → [[0,4], [2,0]],
]
```

Precisely, `embedded[b,t,:] = embedding_table[input_ids[b,t],:]`. For example, `input_`

`ids[1,0]=2`, so `embedded[1,0,:]=embedding_table[2,:]=[0,4]`. The B and T structure is preserved, and each position gains D vector coordinates. For this lookup, the result shape is **index-tensor shape + selected-row shape**: `[B,T] + [D] → [B,T,D]`.

$V = 3$ counts the available table rows; it is not a new axis that must appear in the output. Here IDs 0, 1, and 2 are selected, with ID 1 selected at two positions, producing four vectors rather than a single copy of the three-row table. A table `[100,8]` and ID tensor `[2,3]` would give `[2,3,8]`: two samples, three positions each, and eight coordinates per position. Each ID must still be in 0 through 99.

The small indexing examples use Python integer lists to show selection order; the actual `input_ids` parameter is a `torch.long` tensor. The local name `embdded` also works if used consistently; the lesson uses the conventional spelling `embedded`. The worked trace below uses `embedded` for these retrieved vectors.

Complete worked trace: the same ID with different history

Use exactly the fixture from the supplied check driver:

```
embedding_table = [
    [0, 0],   # ID 0
    [2, 0],   # ID 1
    [0, 4],   # ID 2
]

input_ids = [
    [0, 1],   # sample 0
    [2, 1],   # sample 1
]
```

$V = 3$, $D = 2$, $B = 2$, $T = 2$. The value **2 in `input_ids[1,0]` is a token ID**, not a count of two tokens.

Lookup produces shape `[B,T,D]=[2,2,2]`:

```
sample 0: [[0, 0], [2, 0]]
sample 1: [[0, 4], [2, 0]]
```

For sample 0, the first position sees only itself, giving $h_0 = [0, 0]$. The second position sees two vectors:

$$h_1 = \frac{[0,0] + [2,0]}{2} = \frac{[2,0]}{2} = [1,0].$$

For sample 1, the first state is $h_0 = [0, 4]$. Again, the second position divides by two visible positions:

$$h_1 = \frac{[0,4] + [2,0]}{2} = \frac{[2,4]}{2} = [1,2].$$

The function should therefore return:

```
[
```

```
    [[0, 0], [1, 0]],
    [[0, 4], [1, 2]],
]
```

The two final states change from the same `[2,0]` into different `[1,0]` and `[1,2]`. Earlier inputs now participate in the computation. This allows a subsequent output layer to make different predictions; whether its logits actually differ also depends on its parameters.

Turn the sum into tensor operations

Call the lookup result U, compute prefix sums S, and divide by counts C:

$$U_{b,t,:} = E[X_{b,t}], \qquad S_{b,t,:} = \sum_{j=0}^{t} U_{b,j,:}, \qquad C_{0,t,0} = t+1, \qquad H = S/C.$$

`cumsum` means cumulative sum. For example, `[2,5,1]` becomes `[2,7,8]`: every output retains the sum from the start through its position. An ordinary `sum` would usually produce only the total, 8.

For `[B,T,D]`, `cumsum(dim=1)` accumulates positions separately for each sample and coordinate, keeping shape `[B,T,D]`. The fixture gives:

```
sample 0: [[0, 0], [2, 0]]
sample 1: [[0, 4], [2, 4]]
```

Next prepare divisors `[1,2]`: divide the whole vector at position 0 by 1 and the whole vector at position 1 by 2.




Figure 54: Lookup, prefix sums, and division broadcast along positions

Each row in the lookup, prefix-sum and mean boxes is a D-dimensional vector; those panels preserve sample and position structure. The central box contains one scalar count per position, shared across samples. The arithmetic is `prefix sums / counts = prefix means`; counts come from the position count T, not from the numerical values of the prefix sums.

Why reshape counts to `[1,T,1]`?

The intended alignment is:

```
prefix_sums: [B, T, D]
divisors:    [1, T, 1]
result:      [B, T, D]
```

Broadcasting reuses values along size-one axes. The first 1 shares the same counts across samples; the last 1 shares each position's divisor across its coordinates. The T axes align position by position.

Dividing directly by `[T]` aligns from the right. Because $T = D = 2$ in this fixture, the computation may run without an error while applying `[1,2]` to **feature coordinates** instead. The second sample's prefix sum `[2,4]` would incorrectly become `[2/1,4/2]=[2,2]`; the correct result is `[2/2,4/2]=[1,2]`. A runnable shape does not establish correct semantics.

Guided implementation

Open exercises/04_01_context_baseline.py. Edit only the region between `START LEARNER CODE` and `END LEARNER CODE` in `prefix_mean`, removing the placeholder `raise NotImplementedError(...)`. Preserve the signature and supplied check driver.

Each statement in this function uses four spaces of indentation. This tensor route needs no `for` or `if` and creates no model parameters. The operations and expected results below guide you; assemble the function yourself.

1. **Look up vectors as `embedded`.** Use the indexing expression `embedding_table[input_ids]`. The ID shape `[B,T]` becomes `[B,T,D]`, with the values shown above. Average vectors rather than integer IDs.
2. **Compute `prefix_sums`.** Call `.cumsum(dim=1)` on the lookup tensor. Axis 1 is the middle position axis; the result still has shape `[B,T,D]`. The fixture's second sample ends in `[2,4]`. Axis 0 would mix samples; axis 2 would mix features. Neither implements the formula.
3. **Read T and construct `counts`.** `input_ids.shape[1]` gives the number of positions. `torch.arange(start, end)` includes its start and excludes its end, so use start 1 and end `T+1` to obtain 1 through T. Supply `device=embedded.device` and `dtype=embedded.dtype` to match the vectors. Here counts should be floating `[1,2]`, not `[0,1]`, which would divide the first position by zero.
4. **Arrange the divisors.** Call `.reshape(1, T, 1)` on `counts`, optionally naming the result `divisors`. Reshaping reorganizes the same two values; it does not create more visible positions. In `[1,2,1]`, the middle 2 is T, not a separate count for each of two samples.
5. **Divide and return.** Use `/` for element-wise division of `prefix_sums` by `divisors`; broadcasting produces `[B,T,D]`. Use `return` to hand the result to the caller, still indented by four spaces.

Printing does not replace returning.

Keep the graph through lookup, accumulation, and division. Do not call `.detach()`, convert through NumPy, or wrap a result with `torch.tensor(existing_tensor)`. The averaging rule introduces no new trainable parameters, but the embedding table can still receive gradients from a subsequent loss.

What the checks actually establish

Use the existing PyTorch environment and run from the repository root:

```
python exercises/04_01_context_baseline.py
```

A correct implementation should finish with:

```
Lesson 04.01 checks passed.
```

The supplied driver checks the complete numerical fixture above; whether backpropagation through its sum leaves a gradient on E; whether changing the second input preserves the first output; and whether a one-position input returns its own embedding.

These check numerical behavior, causal dependence, and basic gradient connectivity, not model quality. `E.grad is not None` does not establish every exact gradient value.

Optional hand calculation: for a loss L on one h_t, the direct gradient coefficient for a visible input vector is $1/(t+1)$; a future position has coefficient 0. If several positions retrieve the same embedding row, its gradient accumulates contributions from several paths. For this fixture's `H.sum()`, every coordinate of E's three rows has gradient 1.5, 1, and 1.5 respectively.

What averaging preserves and loses

It removes the earlier limitation of ignoring all earlier inputs. However, different orders within the same prefix can still give an identical final state:

$$\frac{E[a] + E[b] + E[c]}{3} = \frac{E[b] + E[a] + E[c]}{3}.$$

Thus `[a,b,c]` and `[b,a,c]` have the same **final state**. Their intermediate states need not match; do not generalize this into all outputs being identical.

Fixed averaging also assigns the same weight to every visible position, without selecting importance based on content. Later attention introduces content-dependent aggregation weights, combined with position representations for order information. Attention alone does not automatically supply all positional information.

After implementation, independently explain why `dim=1` is correct, why counts use `[1,T,1]`, and why changing the second token leaves the first output unchanged. Record your explanation separately from code-check results.

Next, 04.02: registered parameters and model modules organizes `nn.Module`; $Q/K/V$ projections and attention follow.

API references and classroom record

See official cumsum, arange, and PyTorch 2.0 broadcasting rules. The first two are rolling API references; the calls used here were also checked in the existing PyTorch 2.0 runtime. Next lesson: 04.02.

04.02 Registered parameters and modules

This lesson uses familiar calculations to introduce organizing parameters and computation with `nn.Module`.

Why learn Module now?

Chapter 03 passed the embedding table, output weight, and bias separately. As models grow, one model object can own these parameters, make them discoverable by an optimizer, and provide a common saving/loading interface. `nn.Module` is PyTorch's model base class; registration brings submodules and their parameters into the model's management.

Lesson 04.01 studied aggregation across positions. Here a familiar position-wise embedding-to-logits computation illustrates module organization; this `TokenModel` contract has no prefix-mean step. Later $Q/K/V$ and attention lessons introduce contextual computation within the module framework.

Formulas, symbols, and shapes

$$U = E[X], \qquad Z = UW^\top + \beta.$$

Symbol or variable	Shape	Meaning
X / `input_ids`	Long `[B,T]`	B samples with T token IDs each
E / `self.embedding.weight`	Floating `[V,D]`	Embedding table for V tokens
U	Floating `[B,T,D]`	Retrieved embedding at each position
W / `self.head.weight`	Floating `[V,D]`	One output-weight row for each candidate token
β / `self.head.bias`	Floating `[V]`	One bias per candidate token
Z / return value	Floating `[B,T,V]`	Raw scores for all V candidates at every position

`nn.Linear(D,V)` transforms the last dimension D into V while preserving B and T. It stores weights as `[out_features,in_features]=[V,D]`, opposite to Chapter 03's handwritten `[D,V]` weight. Hence the transpose in the formula; calling `self.head(U)` performs the corresponding computation.




Figure 55: Lookup, output layer, and parameter count within a module

Read the figure as one sample with two input positions. Embedding stores six numbers; Linear stores six weights and three biases; the output has three scores per position. $P = 15$ counts trainable scalars, not output positions or parameter tensors.

Read the supplied class

```
class TokenModel(nn.Module):
    def __init__(self, vocab_size: int, width: int):
        super().__init__()
        self.embedding = nn.Embedding(vocab_size, width)
        self.head = nn.Linear(width, vocab_size)

    def forward(self, input_ids: torch.Tensor) -> torch.Tensor:
```

- `class TokenModel(nn.Module)` defines a class inheriting PyTorch's model base class.
- `__init__` runs when constructing an instance. `vocab_size` is positive integer V; `width` is positive integer D.
- `self` is the current model instance. `self.embedding` and `self.head` are its two submodules.
- `super().__init__()` initializes the parent, establishing internal parameter/submodule management.
- `nn.Embedding(V,D)` creates the table; `self.embedding(input_ids)` retrieves rows of its `.weight`.
- `nn.Linear(D,V)` creates the output weight and bias; `self.head(vectors)` maps each D-vector to V logits.
- `forward` describes how existing submodules transform inputs. Normally call `model(input_ids)`; PyTorch's module-call mechanism executes `forward`.

Initialization creates model state; repeated calls use the existing parameters. Creating fresh layers inside every forward would prevent continuous training of the same parameter set.

Complete worked trace: lookup to three scores

This lesson uses a different hand-picked fixture from 04.01. The supplied driver sets the values of E and W separately to:

```
E = [[1,0],       W = [[1,0],       β = [0,0,0]
     [0,1],            [0,1],
     [1,1]]            [1,1]]

X = [[0,2]]       B=1, T=2, V=3, D=2
```

The two input IDs are 0 and 2. Lookup retrieves `[1,0]` and `[1,1]`, giving U shape `[1,2,2]`.

For the first position, dot `[1,0]` with each of W's three rows and add the zero biases:

$$z_0 = [1 \times 1 + 0 \times 0,\ 1 \times 0 + 0 \times 1,\ 1 \times 1 + 0 \times 1] = [1, 0, 1].$$

For the second position, use `[1,1]`:

$$z_1 = [1 \times 1 + 1 \times 0,\ 1 \times 0 + 1 \times 1,\ 1 \times 1 + 1 \times 1] = [1, 1, 2].$$

Return `[[[1,0,1],[1,1,2]]]`, shape `[1,2,3]`. These are logits; later loss or generation steps process them as needed.

E and W merely have equal fixture values. The driver's `copy_` copies values; the tensors remain independent parameters rather than tied instances of one parameter.

Discovering registered parameters

This model contains three parameter tensors:

Parameter name	Shape	Trainable scalars
`embedding.weight`	`[3,2]`	6
`head.weight`	`[3,2]`	6
`head.bias`	`[3]`	3

$$P = VD + VD + V = 3 \times 2 + 3 \times 2 + 3 = 15.$$

`model.parameters()` iterates over these three Parameter objects, making them discoverable by an optimizer. It does not return fifteen separate tensors. Construct the model before constructing its optimizer. A plain tensor attribute does not automatically become a registered Parameter merely because it tracks gradients; the supplied Embedding and Linear modules already handle registration.

Distinguish three actions: `forward` computes outputs; `backward()` on the loss computes gradients; the optimizer's `step()` updates parameters. Module organization does not automatically perform training.

`model.state_dict()` exposes named parameter and persistent-buffer state. A persistent buffer is a registered tensor saved with a module, such as a running statistic, that need not be a trainable parameter. This model has only the three parameter entries in the table. Another model of the same structure can use `load_state_dict(...)` to copy these values and reproduce the outputs. By default, the returned state dictionary shares underlying state storage; an independent historical snapshot requires copying or timely serialization. Full training resumption also needs optimizer and other state, covered later.

Guided implementation

Open 04_02_registered_model.py. Preserve the supplied constructor and driver. Fill only the learner region in `forward`, removing the placeholder `raise`.

1. **Retrieve embeddings.** Inside the method, indent by eight spaces and call `self.embedding(input_ids)`. A local name such as `embedded` holds shape `[B,T,D]`, from input shape `[B,T]`. The fixture yields `[[[1,0],[1,1]]]`.
2. **Compute logits.** At the same indentation, pass the vectors to `self.head`. Its final-axis projection preserves B and T. The fixture yields `[[[1,0,1],[1,1,2]]]`, shape `[B,T,V]`.
3. **Return the result.** Use `return` with eight-space indentation to hand back raw logits. Keep the tensor and its graph connected so the caller can compute a loss and gradients.

The dot after `self` accesses an attribute of this model; parentheses after a module name call that module on its input. No explicit B/T loops, softmax, parameter updates, or `backward()` calls are needed in this method.

Run and understanding checks

From the repository root in the existing environment:

```
python exercises/04_02_registered_model.py
```

A correct implementation should print:

```
Lesson 04.02 checks passed.
```

The driver checks exact fixture logits, the scalar parameter count 15, gradient connectivity to all three parameters, and matching outputs after loading state into another model. Its `with torch.no_grad():` block sets fixture parameters manually; graph recording resumes on leaving the block. `eval()` changes training/evaluation layer mode and has a different purpose.

After implementation, explain why both parameter matrices have shape `[V,D]` while outputs have shape `[B,T,V]`, and why a forward call alone does not change weights. Record explanations separately from code-check results; optional review does not block normal advancement.

Next is 04.03: $Q/K/V$ projections. Official Module and Linear links are rolling references; the basic behavior here was checked in the existing PyTorch 2.0 runtime.

04.03 Query, key and value projections

Method sources

The query/key/value projections used here follow the attention formulation of Vaswani et al., 2017; R04, Section 3.2. The small matrices and hand trace are teaching examples.

Begin with the linear transformation you know

Q, K, and V use familiar vector transformations: **multiply the same input x by three separate weight matrices to obtain three representations.** Here "projection" means a linear transformation; it need not be an orthogonal geometric projection.

Lesson 04.01 assigned fixed equal weights to visible positions. Attention aims to assign weights based on content, requiring representations for matching and content to transmit after matching.

Name	Role here
Query, Q	The representation an output position uses to seek related inputs
Key, K	The representation an input position presents for query matching
Value, values	The content later aggregated using attention weights

"Seeking" and "matching" describe computational roles; the vectors themselves contain numbers. Coordinates have no assigned grammar labels, and no literal natural-language question is written at each position. The value tensor V and the earlier vocabulary-size symbol V are different; code uses `values` to distinguish them.

Formulas and shapes first

X in the formulas corresponds to argument `x`:

$$Q = XW_Q, \qquad K = XW_K, \qquad V_{\text{values}} = XW_V.$$

Argument or result	Type and shape	Meaning
`x`	Floating `[B,T,D]`	Existing vector at each position, from embeddings or a preceding layer
`wq`	Floating `[D,d]`	Query projection weight
`wk`	Floating `[D,d]`	Key projection weight
`wv`	Floating `[D,dv]`	Value projection weight
First return q	Floating `[B,T,d]`	Query vectors


Argument or result	Type and shape	Meaning
Second return k	Floating `[B,T,d]`	Key vectors
Third return values	Floating `[B,T,dv]`	Value vectors

B counts samples, T positions, D input coordinates, d query/key coordinates, and d_v value coordinates. Queries and keys will be dotted together, requiring equal width; values can have another width d_v. Each weight is shared across all samples and positions. Inputs and weights have matching floating dtype and device.

x already contains vectors, not token IDs. Apply matrix multiplication directly rather than looking up embeddings again. The caller supplies these weights, with no bias in this exercise; a complete model can register them using the mechanisms from 04.02.

Figure 1 | Shapes: the size of each axis

Parenthesized numbers are axis sizes. Tensor entries are in Figure 2.



All branches read x. B and T remain; the final width changes from D to d or dv.

Figure 56: Figure 1: three projection branches showing tensor shapes only

Figure 1 shows shapes (sizes) only. Every card explicitly says `shape = ...`; parenthesized numbers specify axis sizes. For example, q's `shape = (1,2,1)` means one sample, two positions, and one coordinate per query vector. These are not three numbers stored inside q.

All three arrows begin at the same x. The middle cards show wq/wk/wv shapes; the right cards show the corresponding output shapes. B and T remain, while the final width changes from D to d or d_v. Actual tensor entries appear in the separate numerical figure below.

Which axis does matrix multiplication contract?

The first branch follows:

$$[B, T, D] \mathbin{@} [D, d] \longrightarrow [B, T, d].$$

The matching D axes participate in a sum; B and T are preserved. For one output coordinate:

$$Q_{b,t,r} = \sum_{f=0}^{D-1} X_{b,t,f} (W_Q)_{f,r}.$$

b selects the sample, t the position, r the output coordinate, and f traverses the D input coordinates. This sum does not traverse other positions, so **projection adds no cross-position aggregation**. If x already contains context, projection retains that source information without reading new positions itself.

The preceding lesson's `nn.Linear` stores `[out_features,in_features]` weights; this function receives matrices laid out for direct right multiplication, `[in_features,out_features]`. An equivalent `nn.Linear(D,d,bias=False)` would store the transpose of this exercise's wq.

Complete worked trace: one sample, two positions

Use the supplied driver's fixture:


```
x = [[[1,2], [3,4]]]       shape [1,2,2]
wq = [[1], [0]]            shape [2,1]
wk = [[0], [1]]            shape [2,1]
wv = [[1,0], [0,1]]        shape [2,2]

B=1, T=2, D=2, d=1, dv=2
```

`[1,2]` and `[3,4]` are floating vectors at two positions; their elements are coordinate values.

Figure 2 | Entries: expand the single sample b=0

Square brackets contain matrix entries. Each row is input × weight = projection.



Matrices show one batch sample. See Figure 1 for the full tensor shapes.

Figure 57: Figure 2: actual entries for sample $b = 0$ and the three matrix products

Figure 2 shows numerical entries only. Square brackets contain the numbers used by the computation. Its three rows are `x @ wq`, `x @ wk`, and `x @ wv`. To make the matrix products readable, it expands only the single sample $b = 0$, omitting the outer batch wrapper. Figure 1 still specifies the full tensors' three-dimensional shapes.

For example, q's complete contents are `[[[1],[3]]]`, while Figure 2 displays the two rows of sample $b = 0$: entry 1 in the first row and entry 3 in the second. Its full `shape` remains `(1,2,1)`. **Shape describes organization; entries describe what is stored.**

The first projection gives:

$$q_0 = [1 \times 1 + 2 \times 0] = [1], \qquad q_1 = [3 \times 1 + 4 \times 0] = [3].$$

Thus q is `[[[1],[3]]]`, shape `[1,2,1]`.

The second projection also begins from x:

$$k_0 = [1 \times 0 + 2 \times 1] = [2], \qquad k_1 = [3 \times 0 + 4 \times 1] = [4].$$

Thus k is `[[[2],[4]]]`, shape `[1,2,1]`.

wv is the identity matrix:

$$v_0 = [1 \times 1 + 2 \times 0,\ 1 \times 0 + 2 \times 1] = [1, 2], \qquad v_1 = [3 \times 1 + 4 \times 0,\ 3 \times 0 + 4 \times 1] = [3, 4].$$

Thus values is `[[[1,2],[3,4]]]`, shape `[1,2,2]`. This hand-picked wv preserves the numbers; a general trainable wv transforms them. Likewise, selecting the first coordinate for q and the second for k is a property of this fixture, not a general rule. Learned projections can combine all input coordinates.

How do Q/K determine matching, and why project V separately?

The next lesson dots query position i with key position j:

$$s_{ij} = q_i \cdot k_j.$$

The fixture's unscaled scores are:

$$QK^\top = \begin{bmatrix} 1 \times 2 & 1 \times 4 \\ 3 \times 2 & 3 \times 4 \end{bmatrix} = \begin{bmatrix} 2 & 4 \\ 6 & 12 \end{bmatrix}.$$

This displays one sample's two-dimensional score table; the actual batched shape is `[1,2,2]`. Row i is the query position and column j the matched position. Later, normalized scores become weights for combining values. Separate matching and transmitted-content representations can learn different coordinate combinations.

These are unmasked scores, not probabilities. Lesson 04.04 covers scaling, softmax, and weighted values; 04.05 enforces causal masking. This assignment returns only the three projections.

Guided implementation

Open 04_03_qkv_projection.py. Its interface is:

```
def project_qkv(
    x: torch.Tensor,
    wq: torch.Tensor,
    wk: torch.Tensor,
    wv: torch.Tensor,
) -> tuple[torch.Tensor, torch.Tensor, torch.Tensor]:
```

Edit only the learner region and remove the placeholder `raise`. Statements in this ordinary function use four-space indentation. The caller has supplied the weights; do not recreate them in the function.

1. **Project queries.** Use `@` for matrix multiplication of `x` and `wq`, optionally naming the result `q`. The fixture gives `[[[1],[3]]]`, shape `[B,T,d]`. Here `@` computes the coordinate-product sums above; $*$ instead performs element-wise multiplication.
2. **Project keys and values.** Independently multiply that same `x` by `wk` and `wv`, optionally naming the outputs `k` and `values`. The fixture gives `[[[2],[4]]]` and `[[[1,2],[3,4]]]`. Both statements have the same indentation as step 1, and all three branches read x.
3. **Return in order.** Return the query, key, and value tensors. Comma-separated expressions form a tuple. The caller receives `q, k, v = project_qkv(...)`, so the query/key/value order matters.

Keep tensor operations and their gradient paths; do not convert through lists/NumPy, detach, or recreate output tensors. Preserve x and all three weights.

Run and check

From the repository root in the existing environment:

```
python exercises/04_03_qkv_projection.py
```

A correct implementation should print:

```
Lesson 04.03 checks passed.
```

The supplied driver checks the three fixture values, verifies that `q.sum()+k.sum()+v.sum()` gives gradient 2 at every x coordinate, and changes to $B = 2$, $T = 3$, $D = 5$, $d = 2$, $d_v = 4$ to check query/value shapes.

After implementation, explain why Q/K have the same width while values may differ, and why every branch starts from x. These review prompts are not additional gates to normal progress.

The original paper, §3.2 describes queries, keys, values, and learned projections. See the verification appendix. Next: 04.04, scaled dot-product attention.

Shapes and entries now have separate figures; shapes use explicitly labeled tuples, while entries use matrices with the sample scope stated. Fixture numbers, formulas, and exercise interfaces remain aligned.

04.04 Scaled dot-product attention

Method sources

Scaled dot-product attention and the square-root key-dimension factor are described in Vaswani et al., 2017; R04, Section 3.2.1. This section derives a small instance rather than reproducing the paper's experiments.

Keep the original check fixture fixed: $B = 1$, $T_q = 1$, $T_k = 2$, $d = 2$, $d_v = 1$. Count vectors separately from numbers per vector, then follow the same inputs through the calculation.

From three projections to information aggregation

The preceding lesson prepared Q, K, and values without adding cross-position interaction. Now each query compares with all supplied keys and combines the corresponding values:

$$\boxed{O = \text{softmax}_{\text{keys}}\left(\frac{QK^\top}{\sqrt{d}}\right)V_{\text{values}}}$$

Separate the raw matches R, scaled scores S, normalized weights A, and output O:

$$R = QK^\top, \qquad S = R/\sqrt{d}, \qquad A = \text{softmax}_{\text{keys}}(S), \qquad O = AV_{\text{values}}.$$

Q/K/values contain floating vectors. d counts query/key coordinates; d_v counts value coordinates. Each row of A allocates one query's weight among input positions, rather than predicting a next token over the vocabulary.

This lesson implements a general **unmasked attention kernel**. Lesson 04.05 adds causal masking.

Interface, axes, and return order

```
def attention(q: torch.Tensor, k: torch.Tensor, values: torch.Tensor) -> tuple[torch.Tensor,
 ↪  torch.Tensor]:
```

Argument or result	Type and full shape	Meaning
`q`	Floating `(...,Tq,d)`	T_q queries, d coordinates each
`k`	Floating `(...,Tk,d)`	T_k keys, d coordinates each
`values`	Floating `(...,Tk,dv)`	T_k value vectors, aligned with keys
`weights` / A	Floating `(...,Tq,Tk)`	Weights over keys for each query
`output` / O	Floating `(...,Tq,dv)`	One aggregated d_v-vector per query

Return **`output, weights`** in that order. The **`...`** denotes matching leading batch-like axes; initially read it as B. Queries/keys share width d, keys/values share position count T_k, and floating dtypes/devices are compatible. Preserve input values and autograd paths.

A closer look at how can I know whether K needs transposing?

The learner noted that a bare `torch.Tensor` annotation did not say what the $Q/K/V$ dimensions were. That annotation cannot establish their layout. The exercise now states the contract directly in `attention`'s docstring: q `(...,Tq,d)`, k `(...,Tk,d)`, values `(...,Tk,dv)`, including intermediate and return shapes.

For a matrix product `(m,n) @ (n,p)`, the inner axes match. Storing each key as a row gives `(Tq,d) @ (Tk,d)`, while scoring each query against each key requires `(Tq,d) @ (d,Tk)`. For example, q `(3, 4)` and k `(5,4)` require K to become `(4,5)`, producing `(3,5)`. If $T_k = d = 2$ happens to allow both numeric sizes, their row/column meanings still distinguish the correct computation.

Self-attention forms queries, keys and values from representations of the same sequence. In the aligned full-sequence calculation, $T_q = T_k = T$; this general function also supports different counts. The hand calculation uses one query and two keys to expose what the weights mean.

Count first: one sample, one query, two key/value pairs


Keep the original check fixture fixed, with $d = 2$ and $d_v = 1$. Count the actual entries in each horizontal vector:

Object	How many vectors	Contents of each vector	Numbers per vector
Q	1 query	[1,0]	2, so $d = 2$
K	2 keys	[0,0] and [1.5537…,0]	2 each, so $d = 2$
V	2 value vectors	[2] and [6]	1 each, so $d_v = 1$

Here 1.5537… denotes the full value $\sqrt{2}\ln 3$. Only its displayed decimal is shortened; the actual input is not replaced by four decimal places.

1 The inputs: one query, two key/value pairs

Row count = how many vectors. Column count = how many numbers per vector.



Full shapes: q=(1,1,2), k=(1,2,2), values=(1,2,1).

1.5537⋯denotes the full value $\sqrt{2}\ln(3)$; only the displayed decimal is shortened.

Figure 58: One sample contains one query and two key/value pairs; count vectors separately from coordinates

The whole outer frame is one input sample, so $B = 1$. Purple contains one query; blue and orange each identify a paired K and V row. Horizontal rulers count numbers per vector; headings count vectors. **Two V rows do not imply $d_v = 2$. Each V row contains one number, so $d_v = 1$.**

The same query compares with two keys: two comparisons, not two queries. These produce two positional weights, then combine two value vectors into one output for this query.

Read each full-shape entry by counting: q `(1,1,2)` means 1 sample, 1 query, 2 numbers per query; k `(1,2,2)` means 1 sample, 2 keys, 2 numbers per key; values `(1,2,1)` means 1 sample, 2 value vectors, 1 number per vector.

Keep this input throughout the main lesson. A separate multi-query, $d_v = 4$ visual extension follows at the end, after this example.

Step 1: match each query with each key

Suppress the batch axis to read the matrix dimensions:

$$(T_q, d) \mathbin{@} (d, T_k) \longrightarrow (T_q, T_k).$$

Keys are stored as `(Tk,d)`, so exchange their final two axes to obtain `(d,Tk)`. In `transpose(-2, -1)`, -1 is the final axis and -2 the next-to-last; batch axes remain untouched.

Element by element:

$$R_{b,i,j} = \sum_{r=0}^{d-1} Q_{b,i,r} K_{b,j,r}.$$

i selects a query, j a key, and r the matching coordinate. Each entry is one query/key dot product; each row contains one query's matches with all T_k keys.

In the original assignment fixture below, $T_k = d = 2$, so numeric shapes remain `(1,2,2)` after transposition, but axis roles and tensor entries still change. Follow symbolic axes rather than only whether size numbers change.

Step 2: why divide by a square root?

$$S = R/\sqrt{d}.$$

As d increases, more coordinate products contribute to a dot product, potentially increasing its typical scale. Large differences can make softmax sharp and gradients small. Under the idealized assumptions of independent zero-mean, unit-variance coordinates:

$$\mathrm{Var}(q \cdot k) = d, \qquad \mathrm{Std}(q \cdot k) = \sqrt{d}.$$

The square-root factor therefore controls scale. Learned coordinates need not satisfy these assumptions exactly, so this is not a variance guarantee for arbitrary vectors. Scaling is also not probability

normalization; softmax subsequently normalizes each row. Read d from `q.shape[-1]` rather than hard-coding 2.

Step 3: softmax across key positions

$$A_{b,i,j} = \frac{\exp(S_{b,i,j})}{\sum_{\ell=0}^{T_k-1} \exp(S_{b,i,\ell})}.$$

For fixed b and i, the denominator spans all key positions. The result remains `(...,Tq,Tk)`, with nonnegative entries and row sums of 1. Normalizing across an axis does not remove it. The final axis here is T_k, hence `dim=-1`.

Normalizing across queries would make different queries compete and change the intended meaning. Equal scores within a row correctly produce uniform weights.

Step 4: aggregate the corresponding values

$$(T_q, T_k) \mathbin{@} (T_k, d_v) \longrightarrow (T_q, d_v), \qquad O_{b,i,c} = \sum_{j=0}^{T_k-1} A_{b,i,j} (V_{\text{values}})_{b,j,c}.$$

c selects a value coordinate; j is the position being aggregated. The same positional weights apply to all coordinates of each value vector. There is one output per query, preserving T_q, and its width is d_v because the content comes from values. This is where cross-position aggregation occurs.

Complete worked trace: one query, two candidate positions

Use exactly the supplied driver's fixture:

```
q = [[[1,0]]]                       shape = (1,1,2)
k = [[[0,0], [sqrt(2)*ln(3),0]]]    shape = (1,2,2)
values = [[[2], [6]]]               shape = (1,2,1)

B=1, Tq=1, Tk=2, d=2, dv=1
```

These numbers are chosen for easy arithmetic, not training results. ln denotes the natural logarithm. Define the numerical constant $a = \sqrt{2}\ln 3 \approx 1.5537$; it abbreviates a matrix entry, not an axis size.

Transpose the keys first:

$$Q = \begin{bmatrix} 1 & 0 \end{bmatrix}, \qquad K = \begin{bmatrix} 0 & 0 \\ a & 0 \end{bmatrix}, \qquad K^\top = \begin{bmatrix} 0 & a \\ 0 & 0 \end{bmatrix}.$$

Raw matches and scaling give:

$$R = [1 \times 0 + 0 \times 0,\ 1 \times a + 0 \times 0] = [0, a], \qquad S = [0, a]/\sqrt{2} = [0, \ln 3].$$

Softmax uses these exponentials and their sum:

$$\exp(S) = [1, 3], \qquad A = \left[\frac{1}{1+3}, \frac{3}{1+3}\right] = [0.25, 0.75].$$




Figure 59: The same query compares with two keys, producing two weights through dot products and scaling

Both branches start from the same q0. Blue produces 0 and orange ln(3); their exponentials are 1 and 3, summing to 4. The positional weights are therefore 25% and 75%. Branch count represents comparisons, leaving the number of queries unchanged.

The weights correspond to values 2 and 6:

$$O = [0.25, 0.75] \begin{bmatrix} 2 \\ 6 \end{bmatrix} = [0.25 \times 2 + 0.75 \times 6] = [5].$$

With the full tensor structure, `output = [[[5]]]`, shape `(1,1,1)`, and `weights = [[[0.25,0.`

75]]], shape (1,1,2). Giving 75% to the second value puts the output closer to 6. These matching weights do not select a token from the vocabulary.




Figure 60: Multiply each positional weight by its paired value and sum the contributions into one output

Blue 0.25 multiplies blue v0=[2]; orange 0.75 multiplies orange v1=[6]. Summing both contributions gives [5]. Each V row has one coordinate and the output retains one coordinate. One query produces one output; the full output.shape is (1,1,1).

Guided implementation

Open 04_04_scaled_attention.py. Edit only the learner region of attention, removing its placeholder raise. This ordinary function uses four-space indentation. math and torch are already imported.

1. **Transpose the keys.** Call .transpose(-2,-1) on k, optionally naming the result k_transposed. Shape changes from (...,Tk,d) to (...,d,Tk). The fixture matrix changes from [[0,0],[a,0]] to [[0,a],[0,0]].
2. **Compute and scale scores.** Use @ to multiply q by transposed keys, then divide by math.sqrt(q.shape[-1]). A local name such as scores holds shape (...,Tq,Tk); the fixture gives [[[0, ln(3)]]].
3. **Obtain weights.** Apply torch.softmax(..., dim=-1) to the scores, optionally naming the result weights. Normalize across T_k while preserving shape; the fixture gives [[[0.25,0.75]]]. Use the supplied softmax operation.

4. **Aggregate values.** Multiply weights by `values` with `@`, optionally naming the result `output`. Contract T_k; the fixture gives `[[[5]]]`, shape `(...,Tq,dv)`.
5. **Return as specified.** Return output followed by weights, separated by a comma to form a tuple. The caller uses `output, weights = attention(...)`; preserve this order.

Keep the tensor graph intact: do not detach, convert through NumPy, or recreate output tensors. Preserve q/k/values. This function creates no projection weights and performs no parameter update.

Run, check, and continue

From the repository root in the existing PyTorch environment:

```
python exercises/04_04_scaled_attention.py
```

Expected success output:

```
Lesson 04.04 checks passed.
```

The driver checks the fixture output and weights, confirms a finite gradient on q, and uses an equal-score case $B = 2, T_q = 3, T_k = 5, d = 4, d_v = 7$ to check output shape, row weight sums, and output values.

Review prompts: why does softmax preserve shape? Why does the first product contract d and the second T_k? Explanations or hand calculations remain separate from code-check evidence.

Source: Attention Is All You Need, §3.2.1.

Visual extension: more queries and a value width different from d

This separate extension does not change the original main-lesson inputs. It uses three queries and four-coordinate value vectors to show the same transposition, normalization and aggregation with different axis sizes.


Draw d and d_v as the number of columns in each row

The query/key width is **the number of entries in each Q or K row**; the value width is **the number of entries in each V row**. Use an additional fixture chosen to expose matrix transformations: $B = 1$, $T = 3$, $d = 2$, $d_v = 4$. Display sample $b = 0$ only. This does not replace the original assignment fixture in the main lesson.

```
a = sqrt(2)*ln(2), c = sqrt(2)*ln(3)
Q = [[1,0], [0,1], [1,1]]                  shape = (3,2)
K = [[0,0], [a,0], [0,c]]                  shape = (3,2)
V = [[0,0,6,12], [6,12,0,0], [12,6,12,6]] shape = (3,4)
```

See Q, K and V: count the coordinates in each row

B=1, T=3, d=2, dv=4 | Sample b=0; $a = \sqrt{2}\ln 2$ and $c = \sqrt{2}\ln 3$ are numerical constants.



Full shapes: q,k=(1,3,2), values=(1,3,4). Metadata labels shapes; cells contain entries.

Figure 61: Actual Q, K and V grids with coordinate counts and aligned positions

Metadata bands label shapes; horizontal rulers explicitly identify $d = 2$ or $d_v = 4$. Cells contain entries, while small numbers above them are column indices. Each horizontal row is one vector: q2=[1,1] has two entries; v2=[12,6,12,6] has four. Numerical constants a and c are approximately 0.9803 and 1.5537, chosen to give simple weights later.

Matching row colors identify the same sequence position: k0 aligns with v0, k1 with v1, and k2 with v2. Q and K multiply corresponding coordinates and sum them, requiring equal row widths. V participates in a weighted sum of whole vectors: its position count must align with K, while its coordinate count may differ.

Projection output columns determine these widths. With the right-multiplication convention from 04.03 and input width D:

$$\begin{aligned} Q &= XW_q, & W_q &\in \mathbb{R}^{D\times d}; \\ K &= XW_k, & W_k &\in \mathbb{R}^{D\times d}; \\ V_{\text{values}} &= XW_v, & W_v &\in \mathbb{R}^{D\times d_v}. \end{aligned}$$

Here Q/K can project to width 2 and V to width 4. These are learned coordinates; do not assign fixed hand-written semantic meanings to individual columns. Full q/k shapes are `(1,3,2)` and values is `(1,3,4)`.


The original assignment's full-shape diagram remains paired with its one-query/two-key example in the main lesson. The additional fixture explains matrix geometry; the original fixture matches the supplied checks.

Transpose a K row, then calculate one score

Transform K rows into columns, then match Q rows


B=1, T=3, d=2 | Sample b=0 throughout; $a = \sqrt{2}\ln 2$, $c = \sqrt{2}\ln 3$.

01 Transpose: preserve each key vector, change its orientation



Orange k1=[a,0]: row 1 of K → column 1 of K^T.

02 One Q row × one K^T column → one score



R[2,1] = q2 · k1 = 1×a + 1×0 = a

Sum over d=2 coordinates; row 2 is [0,a,c], matching q2 with all three keys.

Figure 62: Transpose a K row into a column; a highlighted query row and key column produce one score

In the upper panel, orange k1=[a,0] moves from row 1 of K to column 1 of its transpose, preserving the coordinate order. Shape changes from `(3,2)` to `(2,3)`. The lower panel follows purple q2=[1,1] and the orange key column to orange R[2,1]. Comparing q2 with all three keys gives:

$$R_{2,:} = [1 \times 0 + 1 \times 0,\ 1 \times a + 1 \times 0,\ 1 \times 0 + 1 \times c] = [0, a, c].$$

A query/key dot product contracts two coordinates into one score. Comparing three keys produces three scores. R therefore has $T = 3$ key-position columns, rather than the original $d = 2$ coordinate columns.

Follow the same query into a four-coordinate output


Continue following q2. Scaled scores and normalized weights are:

$$S_{2,:} = [0, a, c]/\sqrt{2} = [0, \ln 2, \ln 3], \qquad A_{2,:} = \frac{[1, 2, 3]}{1 + 2 + 3} = [1/6, 2/6, 3/6].$$

From scores to output: apply each weight across all 4 V columns


Sample b=0; $S = R/\sqrt{2}$. Purple follows q2; V row colors identify key positions.

01 Row-wise softmax after scaling: all shapes remain (3,3)



q2: [1,2,3] ÷ (1+2+3) = [1/6,2/6,3/6]

02 Aggregate: each positional weight multiplies a whole value vector



o2 = (1/6)v0 + (2/6)v1 + (3/6)v2

= [0,0,1,2] + [2,4,0,0] + [6,3,6,3] = [8,7,7,5]

(3,3) @ (3,4) → (3,4): sum over positions, retain V's dv=4 columns. Full output.shape=(1,3,4).

Figure 63: Scaling, row normalization, and multiplying weights by whole value vectors

The upper panel displays every matrix from S through exp(S) to A. In the lower panel, the purple weight row covers three positions, multiplying the blue, orange and green whole V rows. The four result columns retain V's four coordinates.

$$\begin{aligned} o_2 &= \frac{1}{6}[0,0,6,12] + \frac{2}{6}[6,12,0,0] + \frac{3}{6}[12,6,12,6] \\ &= [0,0,1,2] + [2,4,0,0] + [6,3,6,3] \\ &= [8,7,7,5]. \end{aligned}$$

The same positional weight applies to all four coordinates in its value vector; there is no new set of attention weights per column. Width $d = 2$ has already been contracted during matching. Each output row still has $d_v = 4$ entries. Matrix dimensions are `(3,3) @ (3,4) → (3,4)`; restoring the batch axis gives output.shape `(1,3,4)`.

04.05 Causal visibility and isolation

Method sources

The decoder's prevention of attention to subsequent positions is described in Vaswani et al., 2017; R04, Section 3.1. Here the additive mask is made explicit for a small causal self-attention matrix.

Why restrict visibility?

Assume the already-tokenized sequence A, B, C, D. Training inputs and targets are shifted by one position:

Query position i	Current input	Target for this row	Input positions this row may read
0	A	B	0: A
1	B	C	0, 1: A, B
2	C	D	0, 1, 2: A, B, C

Position i should predict the next item from its known prefix. Although training supplies the entire input, row 0 cannot read B at input position 1: that would put its answer into the computation. **Position i itself remains visible because this row predicts position i+1.** Visibility concerns input positions; the target tensor is used to calculate the loss.

Lesson 04.04 compares queries with all supplied keys. Here q, k, and values belong to the same sequence, aligned at the same starting position, with T queries and T keys. Allow only j≤i. This lesson covers that square layout. Later cached generation reuses stored keys and values from earlier calls; its queries and keys can start at different absolute positions, requiring a visibility rule that accounts for that offset.

Formula first: mask before normalization

Start with the same scaled scores as 04.04:

$$S_{b,i,j} = \frac{\sum_{r=0}^{d-1} Q_{b,i,r} K_{b,j,r}}{\sqrt{d}}.$$

Define boolean mask M: **True means blocked**, False means retained.

$$M_{i,j} = (j > i), \qquad \widetilde{S}_{b,i,j} = \begin{cases} S_{b,i,j}, & j \le i, \\ -\infty, & j > i. \end{cases}$$

Then normalize over key positions in each row and combine values:

$$A_{b,i,j} = \frac{\exp(\widetilde{S}_{b,i,j})}{\sum_{\ell=0}^{T-1} \exp(\widetilde{S}_{b,i,\ell})}, \qquad O_{b,i,c} = \sum_{j=0}^{T-1} A_{b,i,j} (V_{\text{values}})_{b,j,c}.$$

b indexes samples, i queries, j keys, r query/key coordinates, and c value coordinates. Local `scores_masked` corresponds to $\widetilde{S}$, `weights` to A, and `output` to O.

Negative infinity works because:

$$\exp(-\infty) = 0.$$

Future positions contribute zero to numerator and denominator; allowed positions renormalize automatically. Masking and softmax preserve the score shape. This order follows the original Transformer's decoder self-attention. Original paper, §3.2.3




Figure 64: Boolean blocking mask, filled scores, and normalized weights

Metadata bands identify each **two-dimensional matrix shape**; cells contain **actual boolean entries, scores, or weights**. Row i selects the query and column j the key. Orange marks future positions, green allowed positions; text and entries also identify the meaning without relying on color. Scores and weights display sample $b = 0$, retaining B in their full tensors. M itself is a two-dimensional table.

Interface and dimensions

```
def causal_attention(q: torch.Tensor, k: torch.Tensor, values: torch.Tensor) ->
 ↪  tuple[torch.Tensor, torch.Tensor]:
```

Argument or result	Type and shape	Meaning
`q`	Floating `(...,T,d)`	T queries with d coordinates each
`k`	Floating `(...,T,d)`	T keys from the same sequence
`values`	Floating `(...,T,dv)`	T value vectors aligned with keys
`scores` / `scores_masked`	Floating `(...,T,T)`	Scores for every query/key pair
`future_mask`	Boolean `(T,T)`	True identifies a future key to block
`weights`	Floating `(...,T,T)`	Weights over keys for each query
`output`	Floating `(...,T,dv)`	An aggregated vector per query

Return **`output, weights`** in that order. T is positive; inputs have equal lengths and aligned starting positions. d and d_v may differ. The **`...`** denotes matching leading axes: initially B, later possibly including head axis H. Inputs use compatible floating types/devices and finite values. Preserve inputs and autograd paths.

Suppress leading axes to read the two matrix products:

$$(T, d) \mathbin{@} (d, T) \longrightarrow (T, T), \qquad (T, T) \mathbin{@} (T, d_v) \longrightarrow (T, d_v).$$

The first contracts d, the second key-position T. The left T retained by the second product is the query position. Equal axis sizes do not make their meanings interchangeable.

Classroom debugging: why does masked_fill report 3 versus 2?

Debugging example: the first driver case fails at `scores.masked_fill(feature_mask, float("-inf"))`. Inspect the operation that created `scores`, not only the line raising the exception. The incorrect expression puts `k.transpose(-2,-1)` to the left of `q`.

The actual fixture has `q` and `k` shaped `(1,3,2)`: one sample, three positions, and two coordinates per query/key. Transposed `k` has shape `(1,2,3)`. Suppress only the leading sample axis to compare the products:

```
submitted: K^T @ Q : (2,3) @ (3,2) -> (2,2)
required:  Q @ K^T : (3,2) @ (2,3) -> (3,3)
```

Matrix multiplication sums over the adjacent inner dimensions and retains the two outer dimensions. The first expression is legal, but sums over positions and leaves two coordinate axes. Attention needs one score for each query-position/key-position pair: row i and column j must contain the dot product of q[i] and k[j], summed over their two coordinates. That requires the second expression, retaining the two position axes. Transposing K and choosing the operand order are both necessary.

The submitted full `scores` shape is `(1,2,2)`, while `feature_mask` is `(1,3,3)`. In the final axis, 2 and 3 are neither equal nor singleton dimensions, so broadcasting fails. **Keep $T = 3$ and $d = 2$; repair the score product.** Changing `length` to 2 would mask coordinate pairs rather than positions and break aggregation over three value rows.

Follow this repair sequence inside `causal_attention`, retaining four-space indentation:

1. **Correct the multiplication order.** Put `q` before `@` and `k.transpose(-2,-1)` after it. Keep division by `math.sqrt(q.shape[-1])`. In the first driver case, `scores.shape` must become `(1,3,3)`.
2. **Use a two-dimensional visibility mask.** In `torch.ones`, change `(1,length,length)` to `(length,length)`, preserving the boolean dtype, device, and `.triu(1)`. The local name `feature_mask` can remain unchanged. Its submitted leading singleton axis can broadcast in this batched fixture and is not the immediate cause of the error; a plain `(T,T)` mask also supports unbatched inputs without adding an output axis.
3. **Inspect stages, then rerun the original driver.** Temporary `.shape` prints should match the following ledger. Remove the prints after diagnosis; leave the supplied driver unchanged.

```
q, k                (1,3,2)
k.transpose(-2,-1)  (1,2,3)
scores              (1,3,3)
feature_mask        (3,3)
scores_masked       (1,3,3)
weights             (1,3,3)
values              (1,3,1)
output              (1,3,1)
```

For this same fixture, q and k contain only zeros, so all nine correct score entries are zero. The blocking-mask figure shows the three-by-three tables: masking and softmax give rows `[1,0,0]`, `[1/2,1/2,0]`, and `[1/3,1/3,1/3]`. Applying them to values `[2,4,8]` gives 2, $\frac{2+4}{2} = 3$, and $\frac{2+4+8}{3} = \frac{14}{3}$. These are contents; the output shape is `(1,3,1)`.

Review reproduced the actual failure.

Mask the same $Q/K/V$ and see multi-coordinate values

To expose d and d_v, reuse the additional visual fixture from 04.04: $B = 1$, $T = 3$, $d = 2$, $d_v = 4$, showing sample $b = 0$. Keep this separate from the original zero-q/k check fixture in the next section; assignment inputs are unchanged.

```
a = sqrt(2)*ln(2), c = sqrt(2)*ln(3)
Q = [[1,0], [0,1], [1,1]]                  shape = (3,2)
```

```
K = [[0,0], [a,0], [0,c]]                    shape = (3,2)
V = [[0,0,6,12], [6,12,0,0], [12,6,12,6]] shape = (3,4)
```




Figure 65: Two matching coordinates per Q/K row and four coordinates per V row

Horizontal rulers show two entries per Q/K row and four per V row. k0 aligns with v0, k1 with v1, and k2 with v2. Query/key dot products require matching coordinate counts; mixing whole V rows only requires aligned positions, so d_v may differ from d. The preceding lesson's full transpose and two-product walkthrough shows the transformations.


Scaled scores, causal weights, and output are:

$$S = \begin{bmatrix} 0 & \ln 2 & 0 \\ 0 & 0 & \ln 3 \\ 0 & \ln 2 & \ln 3 \end{bmatrix}, \qquad A_{\text{causal}} = \begin{bmatrix} 1 & 0 & 0 \\ 1/2 & 1/2 & 0 \\ 1/6 & 2/6 & 3/6 \end{bmatrix}.$$

Add a causal mask: still mix whole 4-coordinate value vectors


B=1, T=3, d=2, dv=4 | Same Q, K and V; only the allowed key positions change.

01 Fill future scores with negative infinity, then normalize over keys



q2 can still read all three positions, keeping weights [1/6,2/6,3/6].

02 Same V, different visible prefixes; output still has dv=4 columns



o0 = v0 = [0,0,6,12]; o1 = (v0+v1)/2 = [3,6,3,6]

(3,3) @ (3,4) → (3,4): masking restricts positions; value width remains 4, not 2.

Figure 66: Mask the same $Q/K/V$, then combine four-coordinate value vectors

The upper panel moves from the boolean True-as-blocked table to filled scores and weights. The lower panel multiplies these weights by the entire V matrix. Metadata labels sizes; cells contain entries. Row 0 reads only v0, row 1 reads the first two vectors, and row 2 still reads all three.

$$O_{\text{causal}} = A_{\text{causal}} V_{\text{values}} = \begin{bmatrix} 0 & 0 & 6 & 12 \\ 3 & 6 & 3 & 6 \\ 8 & 7 & 7 & 5 \end{bmatrix}.$$

For example, row 1 is $\frac{v_0+v_1}{2} = [3, 6, 3, 6]$. Each positional weight applies across all four coordinates of its value vector. Masking does not change $d_v = 4$ into $d = 2$; the full output shape remains `(1,3,4)`. Causal restrictions change readable positions while V's coordinate width survives into the output.

Complete worked trace: $T = 3$ and values 2, 4, 8

Use the actual driver's inputs:

```
q = k = [[[0,0], [0,0], [0,0]]]   shape = (1,3,2)
values = [[[2], [4], [8]]]          shape = (1,3,1)

B=1, T=3, d=2, dv=1
```

These are chosen explanatory inputs, not training results. Zero queries and keys give zero dot products and scaled scores. Displaying sample $b = 0$:

$$S = \begin{bmatrix} 0 & 0 & 0 \\ 0 & 0 & 0 \\ 0 & 0 & 0 \end{bmatrix}, \qquad M = \begin{bmatrix} \text{False} & \text{True} & \text{True} \\ \text{False} & \text{False} & \text{True} \\ \text{False} & \text{False} & \text{False} \end{bmatrix}.$$

Fill, then exponentiate:

$$\widetilde{S} = \begin{bmatrix} 0 & -\infty & -\infty \\ 0 & 0 & -\infty \\ 0 & 0 & 0 \end{bmatrix}, \qquad \exp(\widetilde{S}) = \begin{bmatrix} 1 & 0 & 0 \\ 1 & 1 & 0 \\ 1 & 1 & 1 \end{bmatrix}.$$

Row denominators are 1, 2, and 3, producing:

$$A = \begin{bmatrix} 1 & 0 & 0 \\ \frac{1}{2} & \frac{1}{2} & 0 \\ \frac{1}{3} & \frac{1}{3} & \frac{1}{3} \end{bmatrix}.$$

Row 0 reads one value, row 1 the first two, and row 2 all three. Allowed weights are uniform here because all allowed scores are zero; learned attention need not be uniform.




Figure 67: Matrix-product dimensions, weighted values, and future-value isolation

Separate metadata bands show both operand dimensions and the result dimension; brackets contain entries. The lower comparison changes only position 2 while the first two output rows stay fixed. Full output tensors remain three-dimensional.

Row by row:

$$O_0 = 1 \times 2 = 2, \qquad O_1 = \frac{1}{2} \times 2 + \frac{1}{2} \times 4 = 3, \qquad O_2 = \frac{1}{3}(2 + 4 + 8) = \frac{14}{3}.$$

Full return contents and shapes are:

```
output  = [[[2], [3], [14/3]]]                 shape = (1,3,1)
weights = [[[1,0,0], [0.5,0.5,0], [1/3,1/3,1/3]]]  shape = (1,3,3)
```

Without masking, all three rows average all values and output 14/3. Causal masking changes the allowed aggregation range for each row.

Understand isolation by changing the future

Keep q and k fixed and replace the last value 8 with 800:

$$O'_0 = 2, \qquad O'_1 = 3, \qquad O'_2 = \frac{2 + 4 + 800}{3} = \frac{806}{3} \approx 268.6667.$$

Rows 0 and 1 cannot read position 2, so their outputs remain fixed. This is a forward isolation check. For fixed q and k, also:

$$\frac{\partial O_{b,i,c}}{\partial (V_{\text{values}})_{b,j,c}} = A_{b,i,j} = 0 \quad \text{when } j > i.$$

The original driver backpropagates from row 0 and checks that later values receive zero gradient. This verifies isolation in this attention kernel. The complete model must keep all other layers and data paths causal as well; later assembly lessons check that.

Classroom Q&A: does a deeper feature map still have causal positions?

Question: The first attention calculation can use a causal mask. After features have mixed, have the original sequence order and receptive-field anchors disappeared? How can later layers use the same triangle?

Distinguish position from content. For hidden states `H` shaped `(B,T,D)`, T indexes sequence positions and D indexes coordinates within each representation. Mixing coordinates or gathering context changes the contents of a vector. It does not move its output to a different position. For a fixed batch sample, $h_i^{(\ell)}$ denotes the vector at position i after layer ell. It can summarize multiple tokens while retaining that position index.

The attention operation makes this explicit, with the batch axis suppressed:

$$Q^{(\ell)} = H^{(\ell)}W_q^{(\ell)}, \quad K^{(\ell)} = H^{(\ell)}W_k^{(\ell)}, \quad V^{(\ell)} = H^{(\ell)}W_v^{(\ell)}, \qquad O_i^{(\ell)} = \sum_{j=0}^{i} A_{i,j}^{(\ell)} V_j^{(\ell)}.$$

Projection multiplies feature coordinates, keeping T rows. The weighted sum contracts key position j; query position i survives as the output row. Thus `(T,T) @ (T,dv) -> (T,dv)` retains one output per query. A representation at row 1 can include inputs 0 and 1 without becoming a new row or exchanging places with row 0. Positional encoding supplies positional signals to computations; the retained row index itself follows from these tensor operations.




Figure 68: Position-aligned dependencies through two causal layers and a forbidden backward leak

Read each column as one unchanged sequence position. Each box is a D-coordinate vector, with tensor shape in the separate metadata line. Box labels list **possible input dependencies, not numerical**

vector entries. Gray/teal arrows run from an earlier layer's position j to the next layer's position i, only when j≤i. The orange strip shows what removing the second layer's mask would permit: future input x2 reaches the earlier output through an already contextualized state at position 2.

For three inputs A, B, C, possible dependencies are:

Position	Input state	After one causal layer	After two causal layers
0	A	A	A
1	B	A, B	A, B
2	C	A, B, C	A, B, C

These are dependency bounds, not claims that a vector literally stores the listed tokens or that all dependencies must be nonzero. Later layers build new features from contextualized features. With full-prefix attention, the first layer can already access its entire prefix; depth need not enlarge that maximum temporal span. The representation's position remains anchored at i, and its readable range must never extend beyond i.

Why mask every layer? If layer 2 is unmasked, its row 0 can read layer 1's row 1, which may contain B. The path $B \to h_1^{(1)} \to h_0^{(2)}$ makes B available while position 0 is supposed to predict B from A. Reading a representation of a future token can leak the answer just as reading that token directly can. Applying the first mask does not make every later row safe for every earlier query.

The dependency argument is inductive. Let $\mathcal{D}(h)$ denote the set of input positions that a representation may depend on. Inputs at row i initially depend only on i; fixed positional signals add no dependencies on future input tokens. If every previous row j depends only on its prefix, and the next row i reads only rows j≤i, then:

$$\mathcal{D}(h_i^{(0)}) \subseteq \{i\}, \qquad \mathcal{D}(h_i^{(\ell+1)}) \subseteq \bigcup_{j=0}^{i} \mathcal{D}(h_j^{(\ell)}) \subseteq \{0, \dots, i\}.$$

The query, keys, values and their attention weights all use only those permitted previous-layer states. Standard feature projections, position-wise feed-forward layers, per-position normalization over features, and residual additions at the same position preserve this restriction. A mask cannot repair a separate operation that has already mixed future inputs into an earlier row.

A complete two-layer numerical counterexample

Reuse the original values `[2,4,8]`. At **both** attention calculations choose $q = k = 0$, shape `(1, 3,2)`, and use scalar values, shape `(1,3,1)`. Feed the first output into the second calculation as its `values`. This is a handpicked attention-only example without residual connections or normalization, not a complete trained Transformer.

All allowed scores are equal, so each masked calculation has the same weights A. Removing the second mask instead produces uniform full-sequence weights U. Display sample $b = 0$, with each matrix's shape stated separately:

$$A = \begin{bmatrix} 1 & 0 & 0 \\ 1/2 & 1/2 & 0 \\ 1/3 & 1/3 & 1/3 \end{bmatrix}, \qquad U = \begin{bmatrix} 1/3 & 1/3 & 1/3 \\ 1/3 & 1/3 & 1/3 \\ 1/3 & 1/3 & 1/3 \end{bmatrix}, \qquad \text{shape}(A) = \text{shape}(U) = (3, 3).$$

$$x = \begin{bmatrix} 2 \\ 4 \\ 8 \end{bmatrix}, \qquad y^{(1)} = Ax = \begin{bmatrix} 2 \\ 3 \\ 14/3 \end{bmatrix}, \qquad \text{shape}(x) = \text{shape}(y^{(1)}) = (3, 1).$$

With the second mask, row 0 reads only 2; row 1 averages 2 and 3; row 2 averages all three contextualized values:

$$y^{(2)} = Ay^{(1)} = \begin{bmatrix} 2 \\ (2+3)/2 \\ (2+3+14/3)/3 \end{bmatrix} = \begin{bmatrix} 2 \\ 5/2 \\ 29/9 \end{bmatrix}.$$

Without the second mask, **even row 0** reads all three first-layer rows:

$$z^{(2)} = Uy^{(1)} = \begin{bmatrix} 29/9 \\ 29/9 \\ 29/9 \end{bmatrix}.$$

Both full outputs have shape `(1,3,1)`; shapes alone cannot detect this causal failure. Change only the future input 8 to 800: the first output becomes `[2,3,806/3]`. With both masks the second output is `[2,5/2,821/9]`, retaining its first two entries. Without the second mask, all three outputs become `821/9`, including row 0: a direct numerical demonstration of future leakage.

What is reused? The visibility rule j≤i repeats in each aligned, length-preserving self-attention layer. The actual $Q/K/V$, scores, weights and features are recomputed per layer, not reused. The equal weight matrices in this toy example come only from its chosen zero queries/keys.

Where does this explanation apply? Ordinary decoder self-attention preserves the aligned position axis; it does not introduce a time stride or reorder rows. If an architecture pools, permutes, or offsets positions, visibility must follow actual position correspondence rather than blindly reusing a same-sized triangle. During cached single-token inference, all supplied keys may already be in the permitted prefix, so an explicit square mask may be unnecessary; the causal restriction still applies. This exercise covers square, aligned training inputs. Within one such matrix the last query row has no later key to block, while earlier rows do.

The decoder stack's masked self-attention and its position-wise feed-forward transformations are described in the original Transformer paper, §§3.1–3.3. The dependency proof and numerical counterexample above are the lesson's worked explanation.

Classroom Q&A: can the number of channels shrink?

Question: Can an intermediate layer reduce its channel count? Wouldn't that leave fewer elements?

Yes: reducing feature width D leaves fewer feature coordinates per position. For a tensor `(B,T,D)`, it does not by itself reduce the T positions. The preceding depth diagram chose equal D across its illustrated layers for convenience; its causal argument does not require equal feature widths at every layer.

Take $B = 1, T = 3$, input width 4 and output width 2. Apply the same right-multiplied projection to each position, with batch axis suppressed in the displayed matrices:

$$Z = XW, \qquad (3,4) \mathbin{@} (4,2) \longrightarrow (3,2).$$




Figure 69: Feature-width reduction with row positions preserved and sizes separate from entries

The metadata bands state matrix shapes. Cells contain handpicked feature values, not token IDs. Matching row colors track the same position before and after projection; W's rows index input features rather than positions. The full batched shape changes from `(1,3,4)` to `(1,3,2)`.

```
X = [[1, 2, 3, 4],       W = [[1,0],       Z = [[ 4, 6],
     [5, 6, 7, 8],            [0,1],            [12,14],
     [9,10,11,12]]            [1,0],            [20,22]]
                              [0,1]]
```

Each row uses the same rule: `[a,b,c,d] -> [a+c,b+d]`. Row 0 becomes `[1+3,2+4]=[4,6]`; row 1 becomes `[5+7,6+8]=[12,14]`; row 2 becomes `[9+11,10+12]=[20,22]`. The number of scalar entries

falls from 12 to 6, while all three position rows survive. Each new row depends only on its corresponding old row, so this projection adds no new cross-position dependency.

Such compression is generally not lossless over arbitrary input vectors: `[1,2,3,4]` and `[2,2,2,4]` both map to `[4,6]` under this W, so the original cannot be uniquely reconstructed. A learned narrow projection can still retain useful task information. Reduced feature detail does not imply that sequence positions have disappeared.

If queries and keys then both have shape `(1,3,2)`, their score product is still:

$$\text{shape}(QK^\top) = (1, 3, 3), \qquad (3, 2) \mathbin{@} (2, 3) \longrightarrow (3, 3).$$

The two coordinate axes are contracted; the three query positions and three key positions remain. Use query/key width $d = 2$ for scaling by its square root, and retain a `(3,3)` causal mask. Q and K must share their matching width; the value width may still differ. A compressed future-position representation can continue to contain future information, so narrower channels do not remove the need for causal visibility in later layers.

Reducing T, such as `(1,3,4) -> (1,2,4)`, instead changes the position count. If positions are pooled or merged, their source ranges and allowed reads need an explicit definition; merely resizing an old triangle is insufficient. This course's current attention exercises preserve aligned positions.

Learn two operations before implementing the core

`triu(diagonal=1)` retains the first diagonal above the main diagonal and everything above it, zeroing other entries. Starting with an all-True boolean `(T,T)` table, `.triu(1)` produces M. The 1 is a diagonal offset, not an element count. `.triu(0)` also marks the main diagonal True; because True means blocked here, use 1.

`tensor.masked_fill(mask, value)` returns a tensor with True positions replaced by value and other entries retained. Use `masked_fill` without a trailing underscore to avoid an in-place modification. Here `float("-inf")` supplies floating negative infinity. The boolean mask belongs on the same device as the scores.

The two-dimensional `(T,T)` mask aligns with the final two score axes `(...,T,T)` and broadcasts across leading axes, applying the same visibility rule to each sample. No sample loop is needed. Later scores shaped `(B,H,T,T)` can use this same two-dimensional mask.

This boolean convention comes from **masked_fill's contract**: fill where True. Do not assume all APIs with an argument named mask use the same convention.

Guided implementation

After 04.04, open 04_05_causal_mask.py. Edit only the learner region of `causal_attention`, removing its placeholder `raise`. `torch` and `math` are already imported. Each statement uses four-space indentation inside this function; no new loop or conditional is needed.

1. **Compute scaled scores.** As in 04.04, multiply q by `k.transpose(-2,-1)` and divide by `math.sqrt(q.shape[-1])`, saving `scores`. Shape is `(...,T,T)`; all fixture entries are zero.
2. **Read the position count.** Read T from `q.shape[-2]`, using a local name such as `length`. The final axis is d; the next-to-last is T. Here length is 3; do not hard-code it.
3. **Construct the future mask.** Create a `(length,length)` table with `torch.ones`, specifying `dtype=torch.bool` and `device=q.device`, then call `.triu(1)` and save `future_mask`. The fixture should match M above, True only strictly above the main diagonal.
4. **Fill the scores.** Call `.masked_fill(future_mask, float("-inf"))` on `scores`, saving `scores_masked`. Shape remains `(...,T,T)`; only future cells become negative infinity.
5. **Compute weights.** Apply `torch.softmax(..., dim=-1)` to `scores_masked`, saving `weights`. Fixture rows are `[1,0,0]`, `[0.5,0.5,0]`, and `[1/3,1/3,1/3]`.
6. **Aggregate and return.** Compute `output` with `weights @ values`, shape `(...,T,dv)`, then return `output, weights` in that order. Both statements retain four-space indentation. Fixture output is `[[[2],[3],[14/3]]]`.

Do not recompute projections, create parameters, or update weights inside this function. Keep the tensor operations and autograd paths intact.

Why common mistakes fail

- **Multiplying future scores by zero.** For ordinary finite scores this gives 0, but exp(0)=1, so future positions still receive weight. When future scores already equal zero, nothing changes at all.
- **Zeroing future weights only after softmax.** Fixture row 0 changes from `[1/3,1/3,1/3]` to `[1/3,0,0]`, summing to 1/3 and producing 2/3. Additional correct renormalization can recover the same distribution in exact arithmetic, but this lesson uses the direct mask-before-softmax approach.
- **Blocking the diagonal.** Row 0 may become entirely negative infinity and standard softmax produces NaNs. Keeping the diagonal ensures at least one allowed position per row for finite inputs.
- **Treating True as allowed.** Here True marks a replacement position. The wrong triangle blocks the readable prefix.
- **Forgetting the device.** Place the mask on the input device; its boolean dtype stays distinct from q's floating dtype.

Parallel training and sequential generation

Training already has the observed input sequence and can compute all query rows together. Each row is independently restricted to its prefix when predicting the next token. Parallel computation does not grant future visibility.

In autoregressive generation, the next actual token has not yet been selected. Choose one token using the current prefix, append it, and only then take the next step. This is compatible with parallel training

rows. Later inference lessons cover generation optimizations.

Run, checks, and preparation status

From the repository root in the existing PyTorch environment:

```
python exercises/04_05_causal_mask.py
```

Expected success output:

```
Lesson 04.05 checks passed.
```

The original driver checks `[2,3,14/3]`, exactly zero future weights, unit row sums, unchanged first two rows after changing a future value, and zero gradients from row 0 to future values. Instructor preparation additionally checks $T = 1$, different leading axes, and unequal feature widths; these do not complete the learner core.

Review prompts: why keep the diagonal? Why `.triu(1)` rather than `.triu(0)`? Why is replacing scores with zero insufficient? Explain or calculate after implementation, keeping understanding separate from code results.

Source: Original paper, §3.2.3.

04.06 Multiple attention heads

Method sources

Multi-head attention is defined in Vaswani et al., 2017; R04, Section 3.2.2. Our reshape and transpose traces expose its axes; reshaping alone does not create independent learned projections.

From one attention calculation to multiple heads

Lesson 04.05 calculates a row of positional weights for each query using one set of queries, keys and values. Multi-head attention performs this calculation separately in learned projection subspaces, then concatenates the results for each position.

This exercise projects to total width D and divides it into H groups, each with width:

$$d_h = D/H, \qquad D = Hd_h.$$

H is a positive integer supplied as `heads` and must divide D. Heads partition projected features; every head retains all T positions. Different heads can have different weights, but their weights need not differ at every input or position. No head is assigned a fixed hand-written semantic responsibility.

The preceding lessons allow query/key width d and value width d_v to differ. This exercise chooses an equal-width design: **Q, K and V each have per-head width $d_h = D/H$.** The earlier general interfaces remain valid.

Project independently, then select the corresponding columns for each head:

$$Q = XW_q, \quad K = XW_k, \quad V_{\text{values}} = XW_v, \qquad W_q, W_k, W_v \in \mathbb{R}^{D \times D}.$$

For each head h:

$$S^{(h)} = \frac{Q^{(h)}(K^{(h)})^\top}{\sqrt{d_h}}, \qquad \widetilde{S}^{(h)}_{i,j} = \begin{cases} S^{(h)}_{i,j}, & j \le i \\ -\infty, & j > i, \end{cases}$$

$$A^{(h)} = \text{softmax}_{\text{keys}}(\widetilde{S}^{(h)}), \qquad O^{(h)} = A^{(h)}V^{(h)}, \qquad Y = \text{Concat}_{\text{features}}(O^{(0)}, \dots, O^{(H-1)})W_o.$$

Concatenation restores D coordinates; `wo` mixes their information through a linear transformation. This exercise omits biases, dropout and later residual modules. Original paper, §3.2.2

Read the shape contract before choosing operations

```
def multihead(x: torch.Tensor, wq: torch.Tensor, wk: torch.Tensor, wv: torch.Tensor, wo:
↪  torch.Tensor, heads: int) -> torch.Tensor:
```

`torch.Tensor` identifies a type, not a shape. The following layouts are the caller/function contract and also appear directly in the real function's docstring.

Argument/result	Type and shape	Meaning of the axes
`x`	Floating `(B,T,D)`	B samples, T positions per sample, D numbers per position
`wq`	Floating `(D,D)`	Input width $D \to$ total query width D
`wk`	Floating `(D,D)`	Input width $D \to$ total key width D
`wv`	Floating `(D,D)`	Input width $D \to$ total value width D
`wo`	Floating `(D,D)`	Merged width $D \to$ output width D
`heads`	Positive Python integer H	Number of groups; H divides D
Return	One floating `(B,T,D)` tensor	One output per position; not a weights tuple

Use the preceding right-multiplication convention: `x @ wq` and the other projections are `(B,T,D) @ (D,D)` and do not transpose their weights. All floating inputs use compatible dtypes/devices; preserve inputs and autograd paths. Here x contains vectors, not token IDs.

Keep one worked fixture throughout

All explanations and three figures use this chosen input:

```
B=1, T=3, D=4, H=2, dh=2
x = [[[1,0,0,1],
      [0,1,0,1],
      [1,1,1,0]]]                  shape = (1,3,4)
wq, wk, wv, wo: each equals I4     shape = (4,4)
```

I4 is the four-dimensional identity matrix, with ones on the diagonal and zeros elsewhere. `torch.eye(4)` constructs it:

$$I_4 = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}.$$

Thus $Q = K = V$=x in this fixture. A trainable model learns separate projections; equal fixture values do not identify their definitions. $T = 3$ and $H = 2$ make the numerical shapes visibly different after swapping these axes.

Step 1: group each position's coordinates

Independently project x to `q_flat`, `k_flat` and `v_flat`, each `(B,T,D)`. Every projection reads x directly; k is not projected from q.

Split each position's $D = 4$ entries into $H = 2$ groups of $d_h = 2$ entries. At t0:

```
[1,0,0,1] → head 0: [1,0] ; head 1: [0,1]
```

This is `reshape(B,T,H,dh)`, with the element correspondence:

$$q_{\text{split}}[b, t, h, r] = q_{\text{flat}}[b, t, hd_h + r].$$

It adds grouping to the D coordinates without removing entries or adding samples/positions. Group K and V the same way.




Figure 70: Full projected vectors, groups at each position, then all positions grouped by head

Blue consistently identifies head 0, orange head 1. Each left-hand row contains four coordinates of one position. The middle displays two head vectors separately at each position. On the right each head has a complete three-position matrix. Metadata labels shapes; cells contain entries. Left/middle show the sample $b = 0$ layout, while right-hand matrices select `[b,h]`.

Step 2: why transpose(1,2)?

After reshape, `(B,T,H,dh)` selects position t before head h. To let `causal_attention` treat each head as an independent leading group, rearrange to `(B,H,T,dh)`, selecting the head first and then all positions within it.

$$q_{\text{heads}}[b, h, t, r] = q_{\text{split}}[b, t, h, r].$$

`.transpose(1,2)` swaps T and H. It has a different purpose from the attention helper's `k.transpose(-2,-1)`:

Operation	Axes exchanged	Purpose
`.transpose(1,2)` after splitting	T and H	Group all positions of one head together
K's `.transpose(-2,-1)` inside helper	T and d_h	Turn key rows into columns for query/key dot products

Each head therefore receives:

$$Q^{(0)} = K^{(0)} = V^{(0)} = \begin{bmatrix} 1 & 0 \\ 0 & 1 \\ 1 & 1 \end{bmatrix}, \qquad Q^{(1)} = K^{(1)} = V^{(1)} = \begin{bmatrix} 0 & 1 \\ 0 & 1 \\ 1 & 0 \end{bmatrix}.$$

Both heads retain all three positions, using different projected coordinate slices. Identity projections make these original input columns in the fixture; learned projections can already mix input coordinates before splitting.

Step 3: independent causal attention per head

The helper receives q/k/values shaped `(B,H,T,dh)`, treating B and H as leading axes. Transposing K's final axes produces `(B,H,dh,T)`:

$$(B, H, T, d_h) \mathbin{@} (B, H, d_h, T) \longrightarrow (B, H, T, T),$$

$$(B, H, T, T) \mathbin{@} (B, H, T, d_h) \longrightarrow (B, H, T, d_h).$$

The first product contracts d_h; the second contracts key-position T. Neither sums across heads. The helper reads $d_h = 2$ from `q.shape[-1]`, scaling by $\sqrt{2}$, rather than $\sqrt{D} = 2$. The caller does not scale or mask a second time.

Define:

$$r = 1/\sqrt{2}, \qquad p = \frac{1}{1+e^r}, \qquad \alpha = \frac{1}{2+e^r}, \qquad \beta = \frac{e^r}{2+e^r}.$$

Approximately $p = 0.330238$, α=0.248255, β=0.503490. These abbreviate numerical weights, not shapes.

The scaled, masked score matrices are:

$$\widetilde{S}^{(0)} = \begin{bmatrix} r & -\infty & -\infty \\ 0 & r & -\infty \\ r & r & 2r \end{bmatrix}, \qquad \widetilde{S}^{(1)} = \begin{bmatrix} r & -\infty & -\infty \\ r & r & -\infty \\ 0 & 0 & r \end{bmatrix}.$$

Row-wise softmax gives:

$$A^{(0)} = \begin{bmatrix} 1 & 0 & 0 \\ p & 1-p & 0 \\ \alpha & \alpha & \beta \end{bmatrix}, \qquad A^{(1)} = \begin{bmatrix} 1 & 0 & 0 \\ 1/2 & 1/2 & 0 \\ \alpha & \alpha & \beta \end{bmatrix}.$$




Figure 71: Actual per-head inputs, masked scores, independent weights and outputs

Each horizontal lane is one complete head. Read its $Q/K/V$, scaled masked scores, softmax weights and output from left to right. Every matrix has a shape label; t0/t1/t2 remain sequence positions. Borders track the same position t1. Displayed decimals have four places; computation retains full precision.

At t1, head 0's query [0,1] has dot products 0 and 1 with the first two keys. Scaled scores [0, r] give weights [p,1-p] and output:

$$O_1^{(0)} = p[1,0] + (1-p)[0,1] = [p, 1-p].$$

Head 1's query is [0,1] and both allowed keys are [0,1]. Equal scores receive half the weight each:

$$O_1^{(1)} = \tfrac{1}{2}[0,1] + \tfrac{1}{2}[0,1] = [0,1].$$

The same position can thus use different positional weights in different heads. Equal weights between the two heads at t2 are also valid. Full head outputs are:

$$O^{(0)} = \begin{bmatrix} 1 & 0 \\ p & 1-p \\ \alpha+\beta & \alpha+\beta \end{bmatrix}, \qquad O^{(1)} = \begin{bmatrix} 0 & 1 \\ 0 & 1 \\ \beta & 2\alpha \end{bmatrix}.$$

Step 4: merge each position's heads, then multiply by wo

The helper returns `head_output`, shape `(B,H,T,dh)`. First `.transpose(1,2)` back to `(B,T,H,dh)`, placing all H results for one position together. Then reshape to `(B,T,D)`.

$$\text{merged}_{b,t,:} = \text{Concat}\left(O_{b,0,t,:}, \ldots, O_{b,H-1,t,:}\right).$$

For example, concatenate t0's `[1,0]` and `[0,1]` into `[1,0,0,1]`. Concatenate features; do not turn three positions into six or average the heads.




Figure 72: Concatenate each position's head outputs into four coordinates, then apply output projection

The two left matrices each contain three rows and two columns. The right retains three rows and joins the blue/orange feature slices into four columns. The top labels reverse transposition/reshape shapes; the bottom states output-projection dimensions.

Complete merged and final outputs are:

$$\text{merged} = \begin{bmatrix} 1 & 0 & 0 & 1 \\ p & 1-p & 0 & 1 \\ \alpha+\beta & \alpha+\beta & \beta & 2\alpha \end{bmatrix}, \qquad Y = \text{merged}\, W_o.$$

Here wo=I4, giving the approximate full return tensor:

```
output = [[[1,        0,        0,        1       ],
           [0.330238, 0.669762, 0,        1       ],
           [0.751745, 0.751745, 0.503490, 0.496510]]]
shape = (1,3,4)
```

A shape ledger for every stage

Variable/stage	General shape	Fixture shape
x	`(B,T,D)`	`(1,3,4)`
wq, wk, wv, wo	`(D,D)`	`(4,4)`
q_flat, k_flat, v_flat	`(B,T,D)`	`(1,3,4)`
q_split, k_split, v_split	`(B,T,H,dh)`	`(1,3,2,2)`
q_heads, k_heads, v_heads	`(B,H,T,dh)`	`(1,2,3,2)`
K transposed inside helper	`(B,H,dh,T)`	`(1,2,2,3)`
scores/head_weights inside helper	`(B,H,T,T)`	`(1,2,3,3)`
head_output	`(B,H,T,dh)`	`(1,2,3,2)`
by_position	`(B,T,H,dh)`	`(1,3,2,2)`
merged/final output	`(B,T,D)`	`(1,3,4)`

Eight implementation steps: predict each shape first

After completing 04.05, open 04_06_multihead_attention.py. Edit only the learner region of `multihead`, removing its placeholder `raise`. Imports and the helper are supplied. Each statement uses four-space indentation in this ordinary function; no explicit head loop is required.

1. **Read dimensions.** Unpack the three entries of `x.shape` into `batch,length,width`, then calculate `head_width` using `width // heads`. `//` is integer division; the fixture gives 1, 3, 4 and 2.
2. **Project independently.** Right-multiply x by `wq,wk,wv`, saving `q_flat,k_flat,v_flat`. Each shape is `(batch,length,width)`; identity fixture weights leave x unchanged.

3. **Split the final width.** Call `.reshape(batch,length,heads,head_width)` on each, saving `q_split,k_split,v_split`. Shape becomes `(1,3,2,2)`, with two vectors of length 2 at each position.
4. **Group positions by head.** Apply `.transpose(1,2)` to each split tensor, saving `q_heads,k_heads,v_heads`, shape `(1,2,3,2)`. This swaps T/H, not K's final axes.
5. **Call the existing attention.** Pass the three head tensors to `causal_attention`. Unpack `head_output` and `head_weights`; receive or ignore the latter locally. Fixture shapes are `(1,2,3,2)` and `(1,2,3,3)`. Do not scale, softmax or mask again.
6. **Group heads by position again.** Apply `.transpose(1,2)` to `head_output`, saving `by_position`, shape `(1,3,2,2)`.
7. **Merge head coordinates.** Use `.reshape(batch,length,width)` on `by_position`, saving `merged`, shape `(1,3,4)`. Each row concatenates heads in order. Do not skip the preceding transpose and reshape head-major data directly into the final output.
8. **Project and return.** Compute and return `merged @ wo`, shape `(B,T,D)`. Return one tensor, not the helper's two-result tuple. Perform no parameter updates; preserve inputs and gradient paths.

A transposed tensor may be non-contiguous, so `.view(...)` is not guaranteed to work for its layout. `.reshape(...)` can copy when necessary while preserving gradient connections. It does not repair an incorrect axis order for you. See the official reshape reference; this lesson also verifies the layouts in the existing PyTorch 2.0 runtime.

Checks and remaining work

From the repository root in the existing PyTorch environment:

```
python exercises/04_06_multihead_attention.py
```

After implementing this lesson and its prerequisite, expect:

```
Lesson 04.06 checks passed.
```

The original driver uses random $B = 2$, $T = 3$, $D = 4$ inputs. It checks $H = 2$ output shape, first-position equality to input under identity projections and causality, $H = 1$ equality to single-head causal attention, gradient connectivity, and unchanged earlier outputs after changing a future position. The fixed visual fixture serves hand calculation; the driver is unchanged.

The implementation uses `.view` for fresh projection outputs and `.reshape` after transposing head outputs; use these choices for the illustrated layouts.

Review prompts: with fixed D, what happens to per-head width if H doubles? Why not reshape directly to `(B,H,T,dh)`? Why swap T/H back before merging?

Source: Original paper, §3.2.2.

04.07 Learned absolute position vectors

Method sources

Vaswani et al., 2017; R04, Section 3.5, discusses sinusoidal and learned positional representations. Our learned position table is a specific choice; length-generalization evidence is discussed by Kazemnejad et al., 2023; R29, not guaranteed by adding positions.

Which positional encoding are we learning? Positional encoding describes a purpose; the familiar sine/cosine formula is one particular construction. This assignment uses a **learned absolute position table**. The section "Two ways to produce a position vector" below compares them, works through the sinusoidal formula and explains length limits. Both supply a D-coordinate vector for a position, but obtain its coordinates differently. The exercise does not require writing the sinusoidal generator.

Start with the missing capability, before writing code

Why revisit the motivation? The earlier walkthrough said which operations to write, but did not establish why positional encoding is useful or how its mechanism works. The procedural trace was insufficient. We revisit the reasoning before assigning more implementation.

Sequence order can change a prediction even when the same tokens occur. For a language example, "dog bites person" and "person bites dog" contain the same words but assign different roles. A useful model may need to select the earlier item, the immediately preceding item, or a particular relative position. A token embedding by itself identifies a token; repeated occurrences of that token initially retrieve the same embedding. Giving a tensor an ordered list of rows does not automatically provide a shared dot-product calculation with each row's numeric index.

For the first attention layer on token embeddings alone:

$$q_i = e_i W_q, \qquad k_j = e_j W_k, \qquad v_j = e_j W_v, \qquad s_{ij} = \frac{q_i k_j^\top}{\sqrt{d}}.$$

Here e_i denotes the embedding of the token at position i, not an embedding of the integer i. $Q/K/V$ projections use shared weights at all positions. In this score expression, **the key's index j is not itself an input feature**. Moving the same token to a different row moves its projected key and value; it does not by itself give that key different coordinates.

A fixed query cannot distinguish a paired reordering of its visible keys and values

Compare two symbolic three-token inputs, `A B C` and `B A C`, and inspect only the **first layer's last query C**. The causal mask allows that row to read all three positions in either input. C has the same query in both cases. A and B exchange their keys and values together; C's pair is unchanged.

Visible token	Its key	Its value	Score and weight for the fixed query C
A	k_A	v_A	s_A, a_A
B	k_B	v_B	s_B, a_B
C	k_C	v_C	s_C, a_C

After the swap, the score vector and its softmax weights swap their A/B entries. Their token-associated weights are unchanged because the softmax denominator contains the same three exponentials. The output is therefore:

$$o_C = a_A v_A + a_B v_B + a_C v_C = a_B v_B + a_A v_A + a_C v_C.$$

The numbers multiplying A's value still multiply A's value after it moves. Summation does not retain which of those two items occupied the earlier slot. Thus this **one layer's fixed final-query output** cannot distinguish the two orders, even though the input tensors have different row order. This is a statement about a specific computation, not a claim that the whole output tensor is unchanged under every permutation.

The causal qualification matters. Earlier query rows see different prefixes, so a multi-layer causal network can acquire ordering signals through those asymmetric paths. Do not extrapolate the fixed-query example into a claim that every decoder without explicit positional embeddings is wholly order-blind. Research on NoPE (no positional embedding) decoder Transformers also demonstrates that explicit position embeddings are not the only way to represent position. Kazemnejad et al., NeurIPS 2023

Give the computations an explicit position-dependent input

This lesson chooses learned absolute position vectors. For a token at position i, form:

$$h_i = e_i + p_i.$$

The externally selected row p_i consistently corresponds to position i. It is a D-coordinate floating parameter vector, not the integer i written into every coordinate. Distinct positions have separately stored rows; those rows may learn distinct vectors. The model's computations then receive both token-dependent and position-dependent contributions:

$$q_i = (e_i + p_i)W_q = e_i W_q + p_i W_q, \qquad k_j = (e_j + p_j)W_k = e_j W_k + p_j W_k.$$

This distributive-law expansion is the mechanism: adding P changes the actual numbers used to form Q and K, hence their comparisons. It is not a label attached to a row but ignored during calculation. With the same additive input, values can change too, through $V = HW_v$.

For completeness, the unscaled score can be expanded into four interactions:

$$q_i k_j^\top = (e_i W_q)(e_j W_k)^\top + (e_i W_q)(p_j W_k)^\top + (p_i W_q)(e_j W_k)^\top + (p_i W_q)(p_j W_k)^\top.$$

These terms combine content/content, content/position, position/content and position/position signals. They give learned parameters access to positional associations. They do not impose a fixed distance metric or guarantee that an untrained head will use position correctly.

Mechanism example: two equal tokens, followed all the way to attention weights

This small mechanism illustration is deliberately separate from the assignment's row-selection fixture. Use $B = 1, T = 2, D = d = 2$, one head, identity Q/K projections, and inspect the final query $i = 1$. Both keys are visible under the same causal mask in both calculations.

Without explicit positions, the two occurrences of token A have the same embedding:

```
e_A = [1,0]
H = Q = K = [[1,0], [1,0]]       shape = (2,2), sample b=0
q1 = [[1,0]]                     shape = (1,2)
```

Its two scaled scores and resulting weights are:

$$s_{1,:} = \frac{[1,1]}{\sqrt{2}}, \qquad a_{1,:} = [0.5, 0.5].$$

Now choose illustrative position rows `p0=[0,0]` and `p1=[0,1]`, keeping the token embedding and projection weights unchanged:

```
h0 = [1,0] + [0,0] = [1,0]
h1 = [1,0] + [0,1] = [1,1]
H = Q = K = [[1,0], [1,1]]       shape = (2,2), sample b=0
q1 = [[1,1]]                     shape = (1,2)
```

The final query now makes different comparisons:

$$s_{1,0} = \frac{1 \cdot 1 + 1 \cdot 0}{\sqrt{2}} = \frac{1}{\sqrt{2}}, \qquad s_{1,1} = \frac{1 \cdot 1 + 1 \cdot 1}{\sqrt{2}} = \frac{2}{\sqrt{2}}.$$

$$a_{1,0} = \frac{\exp(1/\sqrt{2})}{\exp(1/\sqrt{2}) + \exp(2/\sqrt{2})} \approx 0.330238, \qquad a_{1,1} \approx 0.669762.$$




Figure 73: Actual features, query, scaled scores and weights with and without position vectors

The figure shows sample $b = 0$ and only the last score/weight row; shape labels are separate from entries. The two position rows use the same token embedding but now lead to different keys. The query changes as well. If $V = H$ too, this query's output changes from `[1,0]` to approximately `[1,0.669762]`. No new token, position, or mask has been added; the comparisons changed because position-dependent values entered the computation.

These numbers are chosen to expose the mechanism, not trained results. The larger self-position weight is a consequence of this toy choice, not a rule that every head must prefer itself. The original Transformer describes adding position vectors before the attention stack and discusses both fixed and learned choices. Original paper, §3.5

Why addition, and where does a position vector get its meaning?

Addition keeps the input width D unchanged, so existing projections can consume it directly. Linear maps distribute over the sum, as shown above, allowing both contributions to influence attention. Concatenation would also be a possible design, but would change the width or require another projection. Addition is a modeling choice, not the only mathematically valid operation.

A sum is not a lossless record of its two addends: in general h alone does not uniquely determine e and p. For example, `[1,0]+[0,1]` and `[0,0]+[1,1]` both give `[1,1]`. Do not justify addition by claiming it guarantees perfect separation or unique token/position pairs. The model jointly learns token vectors, position vectors and downstream weights for its prediction task; the representation need not be decoded back into the two original vectors.

Position rows are parameters initialized once and reused. They are not sampled afresh at each forward pass. The number stored in each coordinate is not a preassigned linguistic rule. The row has a consistent role because input position i always selects p_i in the chosen coordinate system. A position-index vector filled with the scalar i could supply a signal too, but is a different, more constrained design; a learned D-vector supplies independently trainable coordinates.

During language-model training, the target remains the next token. The loss backpropagates through attention and the addition. In $h = e + p$, the derivative with respect to each addend is the upstream derivative, so the selected position row receives gradients from the examples that used it and can be updated by the same optimizer. There is no separate required label saying what the correct position vector must be. Separately stored rows can receive different gradients; their numerical patterns acquire usefulness through that training.

Absolute position means an index relative to the origin used for this input sequence, selected by `offset+t`. It does not necessarily mean a token's index in a whole original document. A learned absolute table does not itself ensure that neighboring vectors are close or that distance j-i is recovered exactly; later structured position schemes impose other relationships.

Keep positional signals and causal visibility distinct

A position vector answers which slot the input occupies; a causal mask restricts which key slots a query may read. P contains parameters, not the actual content of future tokens. Adding P does not enforce

a no-future-read rule, and masking does not explicitly perform the P lookup. Our decoder uses both mechanisms for these different functions. The mask does carry structural ordering information, which is why the earlier single-layer example must be stated with its boundary.

The assignment trace below, `[1,2]+[10,20]=[11,22]`, checks only that the selected vectors were added correctly. It is an implementation check, not by itself a reason for the architecture. Return to that original assignment fixture below only after following the content → position addition → Q/K → scores → weights chain above. No new code task or understanding pass is recorded in this conceptual revisit.

Two ways to produce a position vector

Classroom question, edited: Why does this assignment learn position vectors when the positional-encoding formula I remember contains sine, cosine and 2π? Does the same group of vectors apply regardless of input length, and what is the upper limit?

First separate the position index from the vector it selects or generates. Position p is an integer such as 0, 1 or 2. Its representation PE(p) is a vector of D floating coordinates. Neither is a token ID. The same token at two positions can therefore receive different position vectors.

Construction	Where do the coordinates come from?	Does training update those coordinates directly?
Learned absolute position table, our exercise	Initialize a table P of shape `(M,D)` once; position p selects row P[p]	Yes, when P is registered as a trainable parameter and included in optimization
Fixed sinusoidal absolute encoding	Evaluate a prescribed sine/cosine function at position p	No; downstream learned weights still learn how to use the fixed signal

For both additive constructions, the input is `h = token_vector + position_vector`, with width D preserved. A fixed encoding can be precomputed into a table too; merely seeing a lookup does not establish whether the table is learned. "Positional encoding" and "positional embedding" are sometimes used with different naming conventions, so inspect how the values are produced rather than relying on the name alone.

The original Transformer paper explicitly discusses learned and fixed alternatives and uses the sinusoidal construction below. Our choice of a learned table builds directly on the trainable embedding operations already studied; it is a modeling choice, not an approximation to the sine formula. Attention Is All You Need, Section 3.5

Read the sinusoidal formula one coordinate pair at a time

For an even feature width D, let i run from 0 to $D/2-1$:

$$PE(p, 2i) = \sin\Big(\frac{p}{10000^{2i/D}}\Big), \qquad PE(p, 2i+1) = \cos\Big(\frac{p}{10000^{2i/D}}\Big).$$

- p is the absolute position, typically `offset+t`, starting at 0.
- D is the feature width, called d_{model} in the paper; it is not the current input length T.
- i indexes a **pair of coordinates**. For $D = 4$, $i = 0$ fills coordinates 0 and 1, while $i = 1$ fills coordinates 2 and 3. These are not different token positions.
- Both coordinates in a pair use the same angle. The pair contributes two numbers to **one position vector**, not two token vectors.
- 10000 is a chosen base controlling the spread of wave frequencies. It is neither vocabulary size nor maximum context length.

To remove the nested exponent from the first reading, name the denominator a_i and the angle θ_i:

$$a_i = 10000^{2i/D}, \qquad \theta_i(p) = p/a_i, \qquad \big[PE(p, 2i), PE(p, 2i+1)\big] = [\sin\theta_i(p), \cos\theta_i(p)].$$

Advancing p by one changes this pair's angle by $1/a_i$ radians. A larger a_i therefore makes its coordinates change more slowly. All positions use the same chosen set of speeds; each position inserts its own p.

Where 2π enters, and what a period means

An angle of 2π radians is one complete turn, equivalent to 360 degrees. A quarter turn is $\pi/2$ radians. Following $[\sin\theta, \cos\theta]$ gives `[0,1]` at $\theta = 0$, `[1,0]` at $\theta = \pi/2$, `[0,-1]` at $\theta = \pi$, and `[0,1]` again at $\theta = 2\pi$. This explains the wave's cycle; a token position itself is still an integer index.

For the scaled angle p/a_i to advance by one full turn, p must advance by $\lambda_i = 2\pi a_i$. Consequently, the formula can equivalently be written using a positional period λ_i:

$$\lambda_i = 2\pi\, 10000^{2i/D}, \qquad \sin\left(\frac{p}{a_i}\right) = \sin\left(\frac{2\pi p}{\lambda_i}\right), \qquad \cos\left(\frac{p}{a_i}\right) = \cos\left(\frac{2\pi p}{\lambda_i}\right).$$

These are the same functions with different notation. The original paper's formula leaves 2π implicit inside the period. A tutorial that defines the period explicitly may display 2π in the argument. Do not interpret it as a maximum token count, or as an instruction to multiply every position by 2π without the matching period denominator.

Complete fixed-function example: $D = 4$, positions 0, 1 and 2

For $i = 0$, $10000^{0/4} = 1$; coordinates 0 and 1 are $\sin p, \cos p$. For $i = 1$, $10000^{2/4} = 100$; coordinates 2 and 3 are $\sin(p/100), \cos(p/100)$. Thus:

$$PE(p) = [\sin(p), \cos(p), \sin(p/100), \cos(p/100)].$$

At $p = 1$, the first angle is 1 radian, about 57.30 degrees; the second is 0.01 radians, about 0.573 degrees. Evaluating the functions gives:


$$PE(0) = [0, 1, 0, 1],$$

$$PE(1) \approx [0.8415, 0.5403, 0.0100, 0.99995], \qquad PE(2) \approx [0.9093, -0.4161, 0.0200, 0.99980].$$

A three-position sequence therefore has a selected position matrix of shape `(T,D)=(3,4)`. The matrix contains three rows; each row has four coordinates. Increasing T adds rows rather than adding coordinates to each row.

One position produces one vector with two wave speeds

D=4: coordinates 0,1 use angle p; coordinates 2,3 use p/100. The x-axis ranges differ.



Both panels mark p=1. Actual token positions are integers 0,1,2,⋯; 2π is an angular period.

First 3 rows of the encoding shape = (T,D) = (3,4)

	c=0: sin(p)	c=1: cos(p)	c=2: sin(p/100)	c=3: cos(p/100)
p=0	0.00000	1.00000	0.00000	1.00000
p=1	0.84147	0.54030	0.01000	0.99995
p=2	0.90930	-0.41615	0.02000	0.99980

Cells contain rounded coordinates; shape is separate. Each row belongs to a position, not a token ID.

Figure 74: Two sinusoidal speeds and the corresponding actual $D = 4$ vector entries

How to read the figure: The left plot follows coordinates 0 and 1 through one full cycle over about 6.28 positions. The right follows coordinates 2 and 3 through one cycle over about 628.32 positions: its horizontal scale is 100 times longer. Both mark $p = 1$. The curves are continuous guides; the table evaluates integer token positions only. The cells below show rounded coordinate values, with matrix

shape stated separately. In particular, position 6 is not a full 2π turn and does not equal position 0. One pair's periodicity is not an instruction to wrap the entire position vector or the model's context.

Why use sine and cosine at several speeds?

Using just $\sin p$ loses distinctions even within one cycle: for example, $\sin(\pi/6) = \sin(5\pi/6)$. Adding $\cos p$ distinguishes those two angles. The pair describes a phase around a circle, although it remains periodic. Combining pairs at several speeds supplies several scales of positional variation instead of relying on one repeating scalar. This is a structured representation, not a proof of infinitely many distinct floating-point vectors or of accurate predictions at arbitrary distances.

There is also an algebraic reason for the paired functions. For a fixed displacement Δ, define $\delta_i = \Delta/a_i$ and $\theta = p/a_i$. The addition identities give:

$$\begin{bmatrix} \sin(\theta + \delta_i) \\ \cos(\theta + \delta_i) \end{bmatrix} = \begin{bmatrix} \cos\delta_i & \sin\delta_i \\ -\sin\delta_i & \cos\delta_i \end{bmatrix} \begin{bmatrix} \sin\theta \\ \cos\theta \end{bmatrix}.$$

The same displacement produces the same two-coordinate linear transformation at every starting p for this pair. For two unprojected position vectors, the sine/cosine identity also yields:

$$PE(p) \cdot PE(q) = \sum_{i=0}^{D/2-1} \cos\left(\frac{p-q}{a_i}\right).$$

This dot product depends on displacement p−q. These identities give a concrete motivation for the structure. Actual attention additionally mixes token content and learned Q/K projections, so its scores are not guaranteed to be this pure relative-distance function. The matrix and dot-product identities here are derivations from the displayed construction; they do not certify that a trained model has learned a particular positional behavior.

Does a different input length use the same vectors?

Yes: with model parameters held fixed, reuse the same position-to-vector mapping. Each position takes its own row. A length change does not rescale the coordinate system to fit the new input. Both the learned table and the fixed function follow this rule:

Current input	Position rows used	Selected shape for $D = 4$
$T = 3$, offset=0	P0, P1, P2	`(3,4)`
$T = 5$, offset=0	P0, P1, P2, P3, P4	`(5,4)`
$T = 2$, offset=3	P3, P4	`(2,4)`

P1 names the same vector in the first two inputs; P3 in a continuation is the same vector as P3 in the longer full input. P0 and P1 name whole vectors, not their numerical contents. For fixed sinusoids, computing the same p again returns the same function value. For a learned table, an optimizer update

can change P1 during training; the length comparison above holds for one unchanged parameter state. "Same mapping" does not mean all token positions use one identical vector, or that the contextualized output stays unchanged when additional tokens become visible.




Figure 75: Select different prefixes or continuation rows from one position table

How to read the figure: Each labeled cell names an entire $D = 4$ vector, whose coordinates are not drawn. Green cells are selected. The top two rows reuse P1 even though T differs; the last row starts at P3 because offset=3. Table capacity M, selected row count T, and vector width D are separate quantities.

What actually limits length?

1. **Learned table capacity.** Our `position_table` has M rows, with valid indices 0 through $M-1$. The contract requires `offset + T <= M`. With M=8 and offset=0, T=8 is valid, but T=9 requests nonexistent P8. With offset=6, T=2 is valid; offset=7, T=2 is not. Selection does not automatically wrap back to P0. Adding untrained rows changes the model's parameters and does not by itself supply useful longer-context behavior.
2. **Sinusoidal function versus stored buffer.** The mathematical formula can be evaluated at positions beyond any particular training length; neither 2π nor 10000 is a positional-index ceiling. An implementation may nevertheless precompute only M rows and enforce that buffer's bounds.

Generating additional rows extends the available fixed values; it does not require learning new positional parameters.

3. **Usable model context.** Available vectors alone do not establish reliable language modeling at that length. Training coverage, position generalization, configured attention/mask/cache limits and memory/computation still matter. At very large positions, finite numerical precision also matters. Even a table row that exists may not have been trained adequately. Processing continuation chunks with T=1 does not remove the total-position bound `offset + T <= M` or the model's history limits.

For either construction, holding D fixed makes each position vector the same width regardless of T. A long input uses more position vectors. It does not stretch one vector, automatically repeat an eight-row table, or gain unlimited reliable context merely because a formula returns numbers.

Classroom clarification: The phrase "always use that same group" is correct when it means a fixed table or set of wave frequencies, selected/evaluated at the required positions. It is incorrect when it means the same single vector for every position.

Why choose a learned table when a sinusoid can continue indefinitely?

Classroom question, edited: If sinusoidal positions can always be calculated farther out, why are we using a learned position table? What are the advantages and disadvantages of each?

Constructing a vector at an unseen position and making a useful prediction there are different requirements. The fixed function handles the first without new positional parameters; it does not establish the second. A learned table makes a different trade: its coordinates can adapt directly to the task within the positions covered by the table and training data.

Property	Learned absolute table	Fixed sinusoidal absolute encoding
Position parameters	M×D trainable values, plus training gradients/optimizer state	No trainable parameters in the position function itself
Adaptation	Selected rows move freely under task gradients	Coordinates/frequencies stay fixed; embeddings and downstream weights learn to use them
Built-in structure	No imposed relationship between adjacent rows or displacement	Multi-scale paired waves have the shift identities derived above
Available length	Needs allocated rows; adding untrained rows is not automatic extrapolation	New values can be generated beyond the stored prefix or training length
Generalization	Rare/unseen rows may be poorly trained; position-specific patterns may overfit	Formula availability does not ensure model generalization to unseen lengths
Storage/runtime	Store M×D values; select rows and add	Precompute a buffer for the same selection/addition, or evaluate dynamically

Property	Learned absolute table	Fixed sinusoidal absolute encoding
Prediction quality	Evaluate for the task, data and training budget	Evaluate under matching conditions; the formula alone establishes no universal winner

"No positional parameters" does not mean no learning about position: attention must still learn useful operations on the fixed features. A cached sinusoidal buffer can occupy M×D stored values too, although it needs no position-parameter gradients or optimizer moments. Computing sin/cos every forward is an implementation choice, not an unavoidable runtime disadvantage.

Write task loss as J(θ, P), where θ denotes the other weights. Selected learned rows can be updated:

$$P_{p,:} \leftarrow P_{p,:} - \eta \frac{\partial J}{\partial P_{p,:}}.$$

For fixed sinusoids, PE(p) is prescribed and this positional update is absent; gradients still update θ through addition and the downstream network. With M=8, D=4, the learned design has 32 positional parameters; the fixed generator has zero trainable positional parameters. Both can feed same-width vectors to the same downstream attention architecture.

Our current objective is to understand a complete trainable model within a controlled context length. The learned table reuses the embedding/parameter/gradient concepts already introduced and makes capacity explicit. This is a teaching and baseline choice, not a claim of better prediction quality. A later comparison should hold data, tokenizer, width, depth, training/evaluation protocol and budget fixed, change the positional construction, and report in-range and longer-length behavior separately. Replacing positions in an already trained model changes its inputs; compatibility and quality cannot be assumed without adaptation or retraining.

The original paper reported nearly identical learned/sinusoidal results on its evaluated translation tasks. This is limited to those experiments, not a universal result or evidence of unlimited context. Attention Is All You Need, Section 3.5

Later 05.02 introduces rotary Q/K positions. Although it uses trigonometric functions, rotating queries and keys is a different mechanism from adding sinusoidal vectors. No switch is required to finish this assignment.

Formula before implementation

Let X be the supplied input vectors, P the position table, and o the nonnegative offset:

$$H_{b,t,c} = X_{b,t,c} + P_{o+t,c}.$$

- b indexes one of B samples.
- t indexes one of T local input positions, starting at 0.
- c indexes one of D feature coordinates.
- o+t is the absolute position whose vector is selected from P.

This is **elementwise addition**, not concatenation or matrix multiplication. P's feature width must equal X's D. Addition keeps both T and D unchanged:

$$(B, T, D) + (1, T, D) \longrightarrow (B, T, D).$$

The leading 1 denotes a shared position addend that broadcasts across B samples. P is a table of floating vectors, not a list of integer position IDs, a token vocabulary, or a parameter-count symbol.

Exact function and shape contract

```
def add_positions(x: torch.Tensor, position_table: torch.Tensor, offset: int = 0) -> torch.Tensor:
```

Argument or result	Type and shape	Meaning
`x`	Floating `(B,T,D)`	Already embedded input vectors; not token IDs
`position_table`	Floating `(M,D)`	M available absolute positions, each with D coordinates
`offset`	Nonnegative Python integer o	Absolute position of local row t=0; default 0
`selected`	Floating `(T,D)`	Rows o through o+T-1 of the position table
`position_batched`	Floating `(1,T,D)`	The same rows with a singleton batch axis
Return	One floating `(B,T,D)` tensor	Input plus the corresponding position vectors

Require `offset+T <= M` and compatible floating dtypes/devices. All batch samples use the same offset in this exercise. A separate offset per sample would require a different interface. Preserve input values and gradients for both floating inputs; return one new connected tensor.

The caller supplies P. In a complete model, a learned position table is initialized once and registered as a trainable parameter, then reused across forward passes. This function selects and adds its rows; it neither creates a fresh table nor performs an optimizer update. The fixture below uses chosen values for arithmetic, not a trained table.

Return to the original assignment fixture

The mechanism illustration above is not a replacement for the supplied check. For the following implementation trace, return to the original driver inputs:

```
B=1, T=2, D=2, M=3, offset=1

x = [[[1,2], [1,2]]]             shape = (1,2,2)
position_table = [[ 0, 0],
```

```
                [10,20],
                [30,40]]      shape = (3,2)
```

Each input row has two coordinates. They happen to be identical. T and D both equal 2 here by coincidence; row labels and coordinate labels in the figure distinguish their meanings.

Local position 0 uses P[1], and local position 1 uses P[2]:

Local t	Absolute position offset+t	Input vector	Selected position vector	Output vector
0	1	`[1,2]`	`[10,20]`	`[11,22]`
1	2	`[1,2]`	`[30,40]`	`[31,42]`




Figure 76: Select the exact position rows and add their coordinate values

Read the upper panel from P to the selected rows. Gray P[0] is unused; teal and orange identify the rows for t=0 and t=1. The lower panel displays sample b=0: all three numerical matrices have shape

`(T,D)=(2,2)`. Metadata states sizes; colored cells contain values. The full input and output shapes remain `(1,2,2)`.

Coordinate by coordinate:

$$H_{0,0,:} = [1,2] + [10,20] = [11,22], \qquad H_{0,1,:} = [1,2] + [30,40] = [31,42].$$

So the full result is:

```
[[[11,22], [31,42]]]            shape = (1,2,2)
```

The example vectors `[10,20]` and `[30,40]` are manually chosen. There is no rule that position 1 must contain 10 or 20. A trained table learns useful coordinates from the language-model loss. Different positions are allowed to learn different vectors; uniqueness is not mathematically enforced.

Understand slicing before selecting rows

Python's `table[start:stop]` includes start and excludes stop. Read length T from `x.shape[1]`. For offset=1 and length=2, stop is 3, so `position_table[1:3]` selects rows 1 and 2, not row 3.

The selected tensor is `(T,D)=(2,2)`. Do not select just `position_table[offset]`: that gives one `(D,)` vector which can accidentally broadcast to every position, losing the intended distinction. Do not slice using D; even though T=D in the main fixture, they count different axes.

The bounds are a caller precondition. Python slices can silently truncate past the end; in some cases the shortened result can even broadcast and return a wrong answer without an exception. Keep `offset >= 0` and `offset+T <= M`; this exercise does not require adding a separate validation routine.

What unsqueeze and broadcasting do

`tensor.unsqueeze(0)` inserts a new axis of length 1 at the front. It retains all values and their order:

```
selected            (T,D)   = (2,2)
position_batched    (1,T,D) = (1,2,2)
x                   (B,T,D)
output              (B,T,D)
```

The 0 specifies the new axis location, not a value to insert. The new 1 is a dimension size, not an extra token. Unsqueezing does not copy the table into a new trainable parameter or remove the gradient connection.




Figure 77: Insert a batch axis and share the same position rows across three samples

The top shows the actual selected entries before and after inserting the batch axis. The bottom illustrates the same addend applied to $B = 3$ samples. These are three batch slices, not three sequence positions; each slice still has $T = 2$ rows. Broadcasting does not require explicitly repeating the tensor. Every sample uses $P[1]$ at $t = 0$ and $P[2]$ at $t = 1$ because the interface supplies one shared offset.

PyTorch also permits `(B,T,D)+(T,D)` by implicit leading-axis alignment. The explicit unsqueeze in this lesson makes the intended batch sharing visible; do not interpret it as the only mathematically valid addition syntax.

Why gradients reach the position table

Write `G` for the upstream gradient with the same shape as H. Since addition has derivative 1:

$$\frac{\partial L}{\partial X_{b,t,c}} = G_{b,t,c}, \qquad \frac{\partial L}{\partial P_{o+t,c}} = \sum_{b=0}^{B-1} G_{b,t,c}.$$

Only selected P rows receive contributions from this operation. With the fixture and scalar loss `L=output.sum()`, all entries of G are 1. For $B = 1$:

```
x.grad = [[[1,1], [1,1]]]        shape = (1,2,2)
position_table.grad = [[0,0],
                       [1,1],
                       [1,1]]   shape = (3,2)
```

$P[0]$ was unused, so its gradient is zero. With $B = 3$ and the same summed loss, the selected row gradients become `[3,3]` because three samples contribute; if the loss were averaged instead, its upstream gradients would be scaled accordingly. This is how trainable position vectors can receive learning signals. The addition itself does not update parameters.

Avoid `.detach()`, conversion to Python lists, or rebuilding a tensor with `torch.tensor(...)` from existing values inside this function. Those can sever the needed graph. Use ordinary slicing, unsqueeze and addition; do not wrap the calculation in no-grad mode.

What offset means during continuation

Offset selects the absolute position of the first input row **in this call**. It does not shift token IDs, move entries in memory, or specify batch size.

If five prefix inputs at absolute positions 0–4 have already been processed, the next newly supplied token occupies position 5. A one-token call then uses offset=5 and selects $P[5]$; two newly supplied consecutive tokens use $P[5]$ and $P[6]$. The prediction produced at position 4 chooses a token for position 5; once that token is fed back as an input, it receives position 5. Do not confuse the target being predicted with the current input's position.

A fresh full prompt normally starts at offset=0. In this lesson's original fixture, offset=1 is chosen to exercise nonzero row selection. Cache implementation comes later; `add_positions` does not create or read a cache.

Three numbered implementation steps

Open 04_07_position_embeddings.py. Edit only `add_positions` between the learner markers, replacing the placeholder `raise`. Its function body uses four-space indentation. No loop, conditional, new import, projection, or optimizer is needed.

1. **Read length and select position rows.** Read `x.shape[1]` into `length`. Use a slice starting at `offset` and stopping at `offset+length`, saving `selected`. This selects T whole rows, keeping every feature coordinate. Fixture: `(2,2)` containing `[[10,20],[30,40]]`.
2. **Expose the shared batch axis.** Apply `.unsqueeze(0)` to `selected`, saving `position_batched`. Fixture shape becomes `(1,2,2)`; contents are `[[[10,20],[30,40]]]`. No values change and no manual repetition is needed.
3. **Add and return.** Use elementwise `+` to combine `x` with `position_batched`, and return the resulting tensor at the same four-space indentation. Fixture: `[[[11,22],[31,42]]]`, shape `(1, 2,2)`. Use ordinary addition rather than in-place `+=`; preserve both inputs and gradient paths.

The detailed function docstring and adjacent hints state the same contract and intermediates. They supplement the preceding explanation; you write the three operations and return.

Boundaries and links to earlier concepts

- Token ID and absolute position are separate indexes. Token embeddings select by vocabulary ID; this table selects by offset+t.
- Addition preserves T and D. It does not shrink channels, merge positions, concatenate heads, or change the causal mask.
- Adding a position vector at row t is a local operation. P is a learned parameter, not a vector calculated from future tokens, so this addition does not introduce future-input leakage.
- In the simple model being assembled, add these vectors at the input before the attention stack. Do not add the same table at every layer merely because causal visibility is enforced at every layer.
- A learned table only supplies its allocated M rows; trained behavior at longer unseen positions is not guaranteed. Untrained allocated rows also do not imply successful length generalization.
- Later rotary-position lessons modify queries and keys by a different mechanism. Do not assume they are the same as this addition or combine schemes without an explicit design.

Run, checks and status

Run from the repository root using the existing PyTorch environment:

```
python exercises/04_07_position_embeddings.py
```

After implementation, expect:

```
Lesson 04.07 checks passed.
```

The unchanged supplied driver checks the exact offset=1 output, gradient connectivity to x, zero

gradient for unused $P[0]$, and broadcasting to $B = 3$. No invalid-input exception contract or model-quality result is claimed.

Optional understanding prompts: which table row serves local $t = 1$ when offset=5? Why does `(1,T,D)` broadcast over B without adding positions? Why do selected P-row gradients sum across samples? An explanation or reconstruction is recorded separately from code passing.

Earlier classroom clarifications about position anchors, feature widths and causal visibility are linked from 04.05. Next: 04.08, residuals, normalization and feed-forward layers.

04.08 Residuals, LayerNorm and a position-wise FFN

Method sources

Residual learning is developed in He et al., 2016; R23, LayerNorm in Ba et al., 2016; R05, and GELU in Hendrycks and Gimpel, 2016; R22. The pre-normalization arrangement here is distinct from the original Transformer's post-normalization; see the analysis in Xiong et al., 2020; R21.

The role of this sublayer

Attention combines information from different permitted positions. A feed-forward network, or FFN, transforms the feature coordinates at each position independently. It can process contextual information already gathered by attention, without making a new read from another position.

This exercise combines three operations. LayerNorm prepares the branch input by centering and scaling each position's features. The FFN uses two learned affine maps with GELU between them. A residual connection adds the branch's correction to the original input.

In **pre-norm**, normalization happens inside the branch before its computation. The identity path retains the original x. This lesson implements only the FFN residual sublayer, not a whole decoder block. Lesson 04.09 will connect an attention residual sublayer and this FFN sublayer.

Overall formula and exact interface

Use row-vector notation matching PyTorch's `nn.Linear`:

$$N = \mathrm{LN}(X), \quad U = NW_{\text{up}}^{\top} + b_{\text{up}}, \quad A = \mathrm{GELU}(U), \quad R = AW_{\text{down}}^{\top} + b_{\text{down}}, \quad Y = X + R.$$

N is `normalized`, U is `expanded`, A is `activated`, R is `branch`, and Y is the returned output. No attention scores or softmax occur here.

```
def pre_norm_ffn(x: torch.Tensor, norm: nn.Module, up: nn.Module, down: nn.Module) ->
↪  torch.Tensor:
```

Argument or result	Type and shape	Meaning
`x`	Floating tensor `(B,T,D)`	Existing hidden features, one D-vector per position
`norm`	Supplied `nn.LayerNorm(D)`	Normalize only the last feature axis; preserve `(B,T,D)`
`up`	Supplied `nn.Linear(D,Dff)`	Map each D-vector to Dff coordinates
`down`	Supplied `nn.Linear(Dff,D)`	Restore D coordinates before residual addition
Return	One floating tensor `(B,T,D)`	Original x plus the computed branch

D and Dff are positive widths. B counts samples and T positions. Dff is often wider than D, but the interface also permits a narrower intermediate width. In the file, **`F` is the imported `torch.nn.functional` module**, not an integer width; `F.gelu` names its activation function. We write Dff to avoid confusing these meanings.

The module objects are already created and contain their parameters. For example, `norm(x)` calls that existing module on x; it does not construct a new LayerNorm. Use the supplied objects with compatible dtypes/devices, preserve x and all parameter values, and keep their autograd paths. No initialization, parameter replacement or optimizer step belongs in this function.

LayerNorm: statistics inside each position

For each sample b and position t, calculate over its D feature coordinates:

$$\mu_{b,t} = \frac{1}{D}\sum_{c=0}^{D-1} X_{b,t,c}, \qquad \sigma^2_{b,t} = \frac{1}{D}\sum_{c=0}^{D-1}(X_{b,t,c} - \mu_{b,t})^2.$$

Then apply learned feature-wise gain and bias:

$$N_{b,t,c} = \gamma_c \frac{X_{b,t,c} - \mu_{b,t}}{\sqrt{\sigma^2_{b,t} + \epsilon}} + \beta_c.$$

The denominator uses **population variance**, dividing by D rather than D-1. In manual PyTorch 2.0 arithmetic, `var(..., unbiased=False)` or `correction=0` matches this choice. The assignment calls the supplied LayerNorm instead of implementing these statistics by hand. Gamma and β each have shape `(D,)` and are shared across positions; the means and variances are computed separately at each position. Official LayerNorm contract

Epsilon is a small positive number in the normal model, added inside the square root to avoid a zero denominator. LayerNorm's default is `1e-5`. The worked check deliberately sets eps=0 for exact arithmetic on the nonconstant vector `[1,3]`; retain the module supplied by the caller rather than changing its ϵ.

The normalized values before gain/bias have variance $\sigma^2/(\sigma^2+\epsilon)$. Thus neither positive ϵ nor arbitrary learned gain/bias implies that the final output must have exactly variance 1. Normalization also keeps the input's shape; it does not remove positions or channels.

Hand calculation with the original input

The first driver case uses $B = 1, T = 1, D = 2$, Dff=5:

```
x = [[[1,3]]]                    shape = (1,1,2)
norm = LayerNorm(2, eps=0)
gamma = [1,1], beta = [0,0]
```

The two numbers belong to **one vector at one position**, not two tokens.

$$\mu = (1+3)/2 = 2, \qquad \sigma^2 = ((1-2)^2 + (3-2)^2)/2 = 1.$$

Subtract the mean, divide by the standard deviation, and apply unit gain/zero bias:

$$[1,3] - 2 = [-1,1], \qquad N = [-1,1]/\sqrt{1+0} = [-1,1].$$




Figure 78: Normalize only the coordinates of the original one-position vector

Cells contain the two coordinate values at $b = 0$, $t = 0$; shape metadata remains separate. The statistics box shows exactly which two values contribute. A later sequence with many rows applies this

calculation separately to each row. Combining statistics over T would read other positions and could leak future inputs; `LayerNorm(D)` avoids that.

The FFN changes feature width and applies a nonlinearity

The two affine maps act on the last axis:

```
x / normalized       (B,T,D)
expanded             (B,T,Dff)
activated            (B,T,Dff)
branch / output      (B,T,D)
```

The position count T stays fixed. The original fixture goes from width 2 to 5 and back to 2. Down must restore D so its result can be added coordinate by coordinate to the original input. There is no token pooling, head splitting or token-to-token attention in this branch.

`nn.Linear(in_features,out_features)` stores its weight as `(out_features,in_features)` and applies `input @ weight.T + bias`. Therefore:

$$(B,T,D) \mathbin{@} (D,D_{\text{ff}}) \longrightarrow (B,T,D_{\text{ff}}), \qquad (B,T,D_{\text{ff}}) \mathbin{@} (D_{\text{ff}},D) \longrightarrow (B,T,D).$$

The actual stored `up.weight` is `(Dff,D)`, its bias is `(Dff,)`; `down.weight` is `(D,Dff)`, its bias is `(D,)`. The modules perform these transposes and bias additions internally. Call `up(...)` and `down(...)` directly in the assignment. Earlier $Q/K/V$ exercises supplied already-oriented matrices for right multiplication; this is the storage convention of an `nn.Linear` object. Official Linear contract

GELU is elementwise, with unchanged shape

For each scalar z independently:

$$\text{GELU}(z) = z\Phi(z) = \frac{z}{2}\left(1 + \text{erf}\left(\frac{z}{\sqrt{2}}\right)\right).$$

Phi is the standard normal cumulative distribution function: $\Phi(z)$ is the probability that a normal random variable with mean 0 and variance 1 is at most z. The symbol erf names the error function, which expresses the same cumulative probability through the displayed identity. The output is a transformed feature value, not a token probability. Positive and negative inputs are scaled smoothly; negative outputs can remain negative. You do not need to implement Phi or erf: `F.gelu` is already imported. Use its default `approximate="none"`, matching the supplied checks, rather than requesting the different tanh approximation. Official GELU contract

$$\text{GELU}(-1) \approx -0.158655, \qquad \text{GELU}(0) = 0, \qquad \text{GELU}(1) \approx 0.841345.$$




Figure 79: The exact-form GELU curve with values used in the lesson

The main zero-branch check uses only the point at 0. Points at -1 and 1 explain the function and are used in the explicitly marked supplementary example below. GELU preserves every tensor axis and shape. Without a nonlinearity between the two affine maps, those two maps could be combined into a single affine map; that observation concerns the affine pair, not the whole block including LayerNorm.

Residual addition: keep x and learn a correction

Write the entire FFN branch as $R(X)$:

$$Y = X + R(X), \qquad R(X) = \text{down}(\text{GELU}(\text{up}(\text{norm}(X)))).$$

The original input travels along an identity path. The branch can learn a correction without having to reproduce the full input representation. For one position's vector, its Jacobian is:

$$\frac{\partial y}{\partial x} = I + J_R(x), \qquad \nabla_x L = \nabla_y L + J_R(x)^\top \nabla_y L.$$

For a scalar residual, the same idea is simply:

$$y = x + r(x), \qquad \frac{dy}{dx} = 1 + r'(x).$$

For vectors, the Jacobian entry `(c,r)` is the derivative of branch output coordinate c with respect to input coordinate r. The identity matrix has 1 on its diagonal and 0 elsewhere; for $D = 2$ it is `[[1,0], [0,1]]`. This is the vector version of the scalar derivative's direct 1 contribution.

I is the D-by-D identity matrix, and J_R is the branch Jacobian. This supplies a direct identity contribution to the gradient. It does not guarantee that every gradient in a complete model is bounded or cannot cancel.

In the original first check, **all up/down weights and biases are zero**. Wherever the shown LayerNorm is defined, this makes the branch identically zero with zero derivative. The complete trace is:

```
x           [[[1,3]]]             (1,1,2)
normalized  [[[-1,1]]]            (1,1,2)
expanded    [[[0,0,0,0,0]]]       (1,1,5)
activated   [[[0,0,0,0,0]]]       (1,1,5)
branch      [[[0,0]]]             (1,1,2)
output      [[[1,3]]]             (1,1,2)
```

The five zeros are five features at the same position. Since the whole branch derivative is zero, the residual Jacobian is I and `output.sum().backward()` gives `x.grad=[[[1,1]]]`. A branch merely having value zero at one input would not, on its own, imply a zero derivative; the zero weights in this check establish the stronger condition.




Figure 80: Trace the unchanged input path and the complete zero-branch computation

Read the branch across the top, then down through GELU and back through down. Its shapes and entries occupy separate areas. The orange path carries the original x directly to the plus node; it bypasses normalization. All entries show the original $b = 0$, $t = 0$ fixture.

Pre-norm means `x + FFN(LN(x))`. Post-norm would instead apply normalization after the sum; they are different computations. This assignment uses the former. The placement of LayerNorm and its optimization implications are studied in Xiong et al., ICML 2020. Do not normalize the final sum or add `normalized` in place of the original x.

Supplement: the same input with a nonzero branch

The zero branch is a useful residual check but does not display a nonzero GELU result. For this **separate arithmetic example**, retain x, norm, B, T, D and Dff from above. Change only the projection weights; keep both biases zero:

```
up.weight = [[1,0],          shape = (5,2)
             [0,1],
             [0,0],
             [0,0],
             [0,0]]

down.weight = [[1,0,0,0,0],  shape = (2,5)
               [0,1,0,0,0]]
```

The first two expanded coordinates copy the normalized vector. After GELU, down selects those first two coordinates:

```
normalized = [-1,1]
expanded   = [-1,1,0,0,0]
activated  ≈ [-0.158655,0.841345,0,0,0]
branch     ≈ [-0.158655,0.841345]
output     ≈ [0.841345,3.841345]
```

Supplement: keep the same input; choose nonzero projections

B=1,T=1,D=2,Dff=5; bias=0. Row matrices at b=0,t=0 below.

normalized shape = (1,2)			**up.weight.T** shape = (2,5)						**expanded** shape = (1,5)				
-1	1	@	1	0	0	0	0	=	-1	1	0	0	0
			0	1	0	0	0						

Elementwise GELU: [-1,1,0,0,0] → [−0.158655⋯,0.841345⋯,0,0,0]

activated shape = (1,5)						**down.weight.T** shape = (5,2)			**branch** shape = (1,2)	
-0.1587	0.8413	0	0	0	@	1	0	=	-0.1587	0.8413
						0	1			
						0	0			
						0	0			
						0	0			

Final addition: [1,3] + [−0.158655⋯,0.841345⋯] = [0.841345⋯,3.841345⋯]

Decimals are rounded only for display; full output shape remains (1,1,2).

Figure 81: Actual matrix entries, both transposed weight sizes and the nonzero correction

The figure displays the row-vector products `(1,2) @ (2,5) -> (1,5)` and `(1,5) @ (5,2) -> (1, 2)`. Displayed decimals are rounded; calculations retain full precision. Full tensor shapes retain $B = 1$ and $T = 1$ throughout. This fixture does not replace or change the original supplied driver.

Five numbered implementation steps

Open 04_08_residual_norm_ffn.py. When ready after 04.07, replace only the learner placeholder inside `pre_norm_ffn`. Every statement uses four-space function indentation. No loop, conditional, new module or parameter initialization is needed.

1. **Normalize the branch input.** Call the supplied `norm` on `x`, saving `normalized`. Shape `(B,T,D)`; primary fixture `[[[-1,1]]]`. Keep the original x for the residual.
2. **Apply the first affine map.** Pass `normalized` to `up`, saving `expanded`. Shape `(B,T,Dff)`; primary fixture has five zero coordinates. The module handles its weights and bias.
3. **Apply GELU.** Pass `expanded` to the already-imported `F.gelu`, saving `activated`. Shape is unchanged. The primary zeros stay zero; do not insert softmax or change the approximation option.
4. **Restore feature width.** Pass `activated` to `down`, saving `branch`. Shape returns to `(B,T,D)`; primary fixture `[[[0,0]]]`.
5. **Add the original input and return.** Use ordinary `+` to combine `x` and `branch`, returning one tensor at the same four-space indentation. Primary fixture output `[[[1,3]]]`. Avoid in-place `+=` or replacing x with its normalized version.

The function docstring and numbered comments beside the learner region repeat the contract and intermediate sizes. They guide implementation without filling the core. All module calls remain inside autograd; parameter updates and gradient clearing belong to the training loop, not this forward function.

Position isolation and common pitfalls

Every output row depends only on the matching input row in this sublayer. The shared module parameters are applied independently at each position; sharing parameters does not mean pooling input values. A later row can change without changing an earlier output here. If input rows already carry contextual features, the FFN can transform those features; it does not itself fetch another row.

- Normalize only D with the supplied `LayerNorm(D)`. Normalizing over `(T,D)` changes the computation and can expose future inputs.
- Preserve T when widths change. Dff is not a token count, a head count, or the functional-module alias `F`.
- Keep GELU between up and down. Up/down are affine maps including their supplied biases.
- Do not create new `Linear` or `LayerNorm` objects inside the function; that would discard the supplied learned state.
- Add branch to the original x. Adding it to normalized is a different residual path.
- Keep gradients connected. Do not detach, rebuild tensors from lists, put the calculation in no-grad, or modify inputs/parameters in place.

- Retain the caller's ϵ. eps=0 in the first hand-check is chosen for its nonconstant input; the normal default handles constant vectors and $D = 1$ without division by zero.

Run, preparation evidence and current status

Run when ready in the existing PyTorch environment:

```
python exercises/04_08_residual_norm_ffn.py
```

Expected after implementation:

```
Lesson 04.08 checks passed.
```

The unchanged original driver checks the exact LayerNorm example, zero-branch identity output and identity-path gradient, then compares a nonzero random $B = 2, T = 4, D = 3$, Dff=7 case against the specified composition.

Optional understanding prompts: why must down restore D? Which values contribute to one position's variance? Why is the residual added to x rather than normalized? How can a position-wise FFN process contextual information without newly reading another token?

04.09 Assemble a causal decoder

Method sources

The decoder attention components originate in Vaswani et al., 2017; R04; the decoder-only language-model setting is illustrated by Radford et al., 2019; R25. This small model is not the original encoder–decoder Transformer.

What we are assembling, and why

So far, embedding lookup produces token features, position addition supplies slot-dependent features, causal multi-head attention exchanges information with visible positions, and a pre-norm FFN transforms each position's features. A language model needs these components connected to a vocabulary prediction at every input position.

A decoder block refines an entire sequence representation without changing its `(B,T,D)` layout. A later block receives the contextual features produced by the preceding block. This is greater representation depth, not another batch, another head, another generated token, or a change in T. Blocks have the same architecture but separate trainable weights in this exercise.

This is a **decoder-only** model: there is no separate encoder or encoder-to-decoder cross-attention. In an encoder–decoder design, an encoder first represents a separate input sequence, and cross-attention lets the decoder read those representations. `TinyDecoder.forward` receives token IDs and returns raw logits. Loss calculation, optimizer updates and autoregressive sampling belong to the caller, introduced together in 04.10.

Prerequisites: 04.06 multi-head attention, 04.07 position addition, and 04.08 residual/normalization/FFN. Their actual files are `04_06_multihead_attention.py`, `04_07_position_embeddings.py` and `04_08_residual_norm_ffn.py`. Finish 04.08 before running the assembled implementation.

Formulas before code: one sequence through L blocks

Let X be integer input IDs, E the token embedding table, P the learned position table, and L the block count. For this interface, every call starts at offset=0:

$$H_0 = E[X] + P_{0:T}, \qquad H_0 \in \mathbb{R}^{B\times T\times D}.$$

The position slice is broadcast across B samples. It is added once before the block stack. For each block index ℓ=0,…, L−1:

$$N_\ell = \mathrm{LN}_{1,\ell}(H_\ell), \qquad U_\ell = H_\ell + \mathrm{MHA}_{\ell,\mathrm{causal}}(N_\ell),$$

$$R_\ell = \mathrm{LN}_{2,\ell}(U_\ell), \qquad H_{\ell+1} = U_\ell + \mathrm{FFN}_\ell(R_\ell).$$

Every tensor above has shape `(B,T,D)`. Each LayerNorm uses the last D coordinates independently at each position. The attention branch mixes visible positions; the FFN branch changes features position by position. This supplied FFN has an internal width of 4D:

$$\mathrm{FFN}_\ell(R) = \mathrm{GELU}(RW_{up,\ell}^\top + b_{up,\ell})W_{down,\ell}^\top + b_{down,\ell},$$

$$(B,T,D)\ @\ (D,4D) \longrightarrow (B,T,4D), \qquad (B,T,4D)\ @\ (4D,D) \longrightarrow (B,T,D).$$

The contracted axes are the last input-feature axis and the first axis of the displayed transposed weight. The original H_ℓ and U_ℓ form the two residual paths. The separately normalized branch input is not substituted for either original residual. Each block has its own two LayerNorm modules and $Q/K/V$/output/FFN parameters.


After all blocks, the model uses a separate final LayerNorm and a vocabulary head:

$$F = \mathrm{LN}_f(H_L), \qquad Z = FW_{head}^\top, \qquad (B,T,D)\ @\ (D,V) \longrightarrow (B,T,V).$$


Here F names a mathematical tensor; `F` in the exercise imports is PyTorch's functional module. `self.head` stores its weight as `(V,D)` and applies the transpose internally; `bias=False` means no final head bias. There is no final softmax inside this forward method.

Connect the learned components into a causal language model

B=1, T=3, V=5, D=4, heads=2, layers=2, max_length=8 | Shapes are metadata.



Inside either DecoderBlock: the two layers have the same structure, with independent parameters.



Only the final head maps D=4 hidden coordinates to V=5 candidate scores:

LN(H2) (1,3,4) @ head.weight.T (4,5) → Z (1,3,5)

Each position returns next-token logits. Forward does not sample tokens or apply a final softmax.

Figure 82: Full decoder assembly, block branches, residuals and head multiplication shapes

Read the figure: Follow the top row from IDs through embedding/positions and two distinct blocks to logits. The middle expands one block; both residual additions preserve `(B,T,D)`, and every attention layer retains its causal mask. The bottom labels both operands and the result of the head multiplication. Shape bands describe dimensions; `[[0,1,2]]` is the actual input content. H0/H1/H2 are names of whole tensors, not their numerical entries.

This is a pre-norm teaching architecture. The original Transformer paper illustrates a post-norm encoder-decoder architecture; its diagram is not an exact blueprint for this supplied class. Original Transformer, Pre-LN analysis.

Exact constructor, input and return contract

```
class TinyDecoder(nn.Module):
    def __init__(self, vocab_size: int, width: int, heads: int, layers: int, max_length: int):
        super().__init__()
        self.embedding=nn.Embedding(vocab_size,width)
        self.positions=nn.Parameter(torch.zeros(max_length,width))
        self.blocks=nn.ModuleList([DecoderBlock(width,heads) for _ in range(layers)])
        self.norm=nn.LayerNorm(width)
        self.head=nn.Linear(width,vocab_size,bias=False)

    def forward(self, input_ids: torch.Tensor) -> torch.Tensor:
```

Name	Type / dimensions	Meaning and example
`vocab_size`	Positive integer V	Number of candidate token IDs; $V = 5$ means IDs $0 \ldots 4$
`width`	Positive integer D	Hidden-feature width; $D = 4$
`heads`	Positive integer	Heads per attention layer; 2, so each head has width 2
`layers`	Integer $L \geq 1$	Number of independent decoder blocks; $L = 2$
`max_length`	Positive integer M	Learned position-table capacity; $M = 8$
`input_ids`	`torch.long`, `(B,T)`	$B \geq 1$, $1 \leq T \leq M$, each ID in `[0,V)`; parameters and inputs use compatible devices
Return `logits`	Floating `(B,T,V)`	Unnormalized next-token scores, one V-vector per input position

Require `width % heads == 0`. T may change between calls within the capacity, while D and V remain constructor choices. The interface assumes ordinary unpadded sequences; it has no padding mask, KV cache or offset argument. Do not treat a continuation-only chunk as a cached continuation: this particular forward restarts its positions at zero and sees only its supplied input.

`self.embedding.weight` and `self.head.weight` both have shape `(V,D)` but are separate parameters with different roles. The first looks up a token's features; the second scores vocabulary candidates from contextual features. No weight tying is performed here. The learned positions start at zero in the supplied constructor; separate rows may acquire different values through their gradients during training. Before that training, the all-zero table adds no explicit distinction between positions.

The network accepts token IDs, regardless of whether a preceding tokenizer used bytes or BPE. V must agree with that tokenizer and the output head. The toy IDs here are supplied directly; forward does not encode text or change the tokenizer vocabulary.

What is already supplied, and what you write

`DecoderBlock.forward` already calls checked multi-head attention on `self.norm1(x)`, adds the original x, then calls `pre_norm_ffn` with `self.norm2`, `self.up` and `self.down`. Do not duplicate those branches or add another block-level residual around `block(hidden)`; the block already includes both residuals.

`nn.ModuleList` registers the supplied child modules so that parent parameter traversal, device/dtype changes and `state_dict()` include them. It does **not** automatically execute the stack: you write the iteration in forward. The list comprehension constructs a new `DecoderBlock` for every layer. Repeating references to one existing block would share its parameters and describe a different model. Official ModuleList documentation

Creating modules in `__init__` gives the model persistent parameters. Recreating blocks or the head inside forward would change which weights the optimizer and checkpoint manage. Calling a module uses `module(argument)`; calling `model(input_ids)` invokes its forward machinery and supplies `self` automatically.

Complete small example: two blocks with nonzero causal attention

Retain the original dimensions $V = 5$, $D = 4$, heads=2, $L = 2$, $M = 8$ and input `[[0,1,2]]`, $B = 1$, $T = 3$. The original supplied checks use random initialization and $B = 2$; their exact random outputs are not the hand values below. **For this separate deterministic illustration only**, choose these existing parameter values:

```
embedding.weight, shape (V,D)=(5,4):
ID0 [ 1,-1, 1,-1]
ID1 [ 1, 1,-1,-1]
ID2 [ 1,-1,-1, 1]
ID3 [-1, 1,-1, 1]
ID4 [ 0, 0, 0, 0]

positions: all zero, shape (M,D)=(8,4)
Every LayerNorm: gamma=1, beta=0, eps=1e-5
Both blocks: q=k=zero (4,4); v=o=identity (4,4)
Both blocks: all up/down weights and biases zero
head.weight, shape (V,D)=(5,4):
```

```
[1,0,0,0]
[0,1,0,0]
[0,0,1,0]
[0,0,0,1]
[1,1,1,1]
```

These values demonstrate data flow; do not paste them into the constructor or learner region. Zeroing the FFN branch isolates the two attention residual updates; V and output projections remain nonzero. The general model and supplied driver retain trainable, randomly initialized branches.

Step A: lookup and position addition

The three IDs select three rows. P[0:3] is zero, so the `(B,T,D)=(1,3,4)` tensor H0 has sample $b = 0$:

```
H0[0] = [[1,-1, 1,-1],
         [1, 1,-1,-1],
         [1,-1,-1, 1]]
```

Each row has mean zero and population variance one. Its normalized value is its original row divided by `sqrt(1+1e-5)`.

Step B: why the two-head attention is uniform here

With Q/K projection matrices zero, every allowed scaled score is zero. A causal row with n visible keys therefore gives each weight `exp(0)/(n*exp(0))=1/n`. For both heads and both blocks:

$$A = \begin{bmatrix} 1 & 0 & 0 \\ 1/2 & 1/2 & 0 \\ 1/3 & 1/3 & 1/3 \end{bmatrix}, \qquad A \in \mathbb{R}^{3\times 3}.$$

V's identity projection preserves the normalized features. Each head averages its two feature coordinates using the same A; concatenation restores all four coordinates, and the identity output projection leaves them unchanged. Thus, for this fixture only, full multi-head attention reduces to `A @ LN(H)` for each sample. It is not zero despite zero Q/K.

Step C: the first residual block

Because the FFN branch is zero:

$$H_1 = H_0 + A\,\mathrm{LN}(H_0).$$

For local $t = 1$, the attention branch is the average of normalized rows 0 and 1. Before the small ϵ scaling, that average is `[1,0,0,-1]`; adding the original `[1,1,-1,-1]` gives approximately `[2,1,-1,-2]`. Tracking all rows, rounded to four decimals:

```
H1[0] ≈ [[2.0000,-2.0000, 2.0000,-2.0000],
```

```
         [2.0000, 1.0000,-1.0000,-2.0000],
         [2.0000,-1.3333,-1.3333, 0.6667]]
```

The FFN's normalization still executes, but its zero down/up branch returns zero and leaves this residual state unchanged. In the ordinary model, the FFN generally contributes nonzero values.

Step D: the second block consumes H1, not H0

The same illustrated A now averages normalized **H1** rows. Normalization must be recomputed from each new row; the second block is not a copy of the first block's output and does not restart with embeddings:

$$H_2 = H_1 + A\,\mathrm{LN}(H_1).$$

```
H2[0] ≈ [[3.0000,-3.0000, 3.0000,-3.0000],
         [3.1324, 0.8162,-0.8162,-3.1324],
         [3.2264,-1.7701,-1.5251, 0.0688]]
```

Both blocks retain three position rows and four features per row. The uniform attention fixture happens to choose equal projection settings across layers; the actual constructor stores separate parameters for them.

Step E: final normalization and the vocabulary head

The final LayerNorm gives:

```
F[0] ≈ [[1.0000,-1.0000, 1.0000,-1.0000],
        [1.3685, 0.3566,-0.3566,-1.3685],
        [1.6196,-0.8886,-0.7656, 0.0346]]
```

The displayed head's first four rows select the four features; its last row sums them. Each final normalized row has mean zero here, so that fifth score is zero, up to floating-point rounding:

```
Z[0] ≈ [[1.0000,-1.0000, 1.0000,-1.0000,0.0000],
        [1.3685, 0.3566,-0.3566,-1.3685,0.0000],
        [1.6196,-0.8886,-0.7656, 0.0346,0.0000]]
```

The product is `(3,4) @ (4,5) -> (3,5)` for displayed sample $b = 0$, or `(1,3,4) @ (4,5) -> (1,3,5)` for the full tensor. The dot product for $t = 2$, candidate ID 0 is approximately `[1.6196,-0.8886,-0.7656,0.0346] · [1,0,0,0] = 1.6196`. These five scores are not probabilities and need not sum to one.

One three-position sample through two layers and the vocabulary head

Separate deterministic fixture: Q/K maps=0, V/O maps=I, FFN branch=0, P=0, ϵ=1e-5.

H0 = E[[0,1,2]]

full shape (B,T,D) = (1,3,4); b=0

	c=0	c=1	c=2	c=3
t=0	1.0000	-1.0000	1.0000	-1.0000
t=1	1.0000	1.0000	-1.0000	-1.0000
t=2	1.0000	-1.0000	-1.0000	1.0000

→

H1 = H0 + A @ LN(H0)

full shape (B,T,D) = (1,3,4); b=0

	c=0	c=1	c=2	c=3
t=0	2.0000	-2.0000	2.0000	-2.0000
t=1	2.0000	1.0000	-1.0000	-2.0000
t=2	2.0000	-1.3333	-1.3333	0.6667

Each head, each layer: A=[[1,0,0],[1/2,1/2,0],[1/3,1/3,1/3]], shape=(3,3).

H2 = H1 + A @ LN(H1)

full shape (B,T,D) = (1,3,4); b=0

	c=0	c=1	c=2	c=3
t=0	3.0000	-3.0000	3.0000	-3.0000
t=1	3.1324	0.8162	-0.8162	-3.1324
t=2	3.2264	-1.7701	-1.5251	0.0688

→

Z = LN(H2) @ head.weight.T

full shape (B,T,V) = (1,3,5); b=0

	c=0	c=1	c=2	c=3	c=4
t=0	1.0000	-1.0000	1.0000	-1.0000	0.0000
t=1	1.3685	0.3566	-0.3566	-1.3685	0.0000
t=2	1.6196	-0.8886	-0.7656	0.0346	0.0000

Cells contain rounded values; shapes are above. In Z, c labels candidate token IDs 0⋯4.

Head rows 0⋯3 form I; row 4 is [1,1,1,1]. Full weights and row arithmetic are in the lesson.

Figure 83: Actual intermediate numerical matrices and the final five-candidate logits

Read the figure: First follow H0→H1, then H2→Z; the equations specify that H2 consumes H1. Cells contain rounded numerical entries; shape metadata above each matrix includes the omitted $B = 1$ axis and identifies sample $b = 0$. In hidden states c indexes features; in Z it indexes candidate IDs 0…4. The fifth score is zero because of the chosen head weights and zero-mean final normalization, not a general property of token ID 4.

The generic shape ledger is unchanged by these special weights:

Stage	Generic shape	Worked example
`input_ids`	`(B,T)`	`(1,3)`
`self.embedding` result	`(B,T,D)`	`(1,3,4)`
Selected `self.positions`	`(T,D)`, broadcast as `(1,T,D)`	`(3,4)`, then `(1,3,4)`
After `add_positions`	`(B,T,D)`	`(1,3,4)`
Every decoder block	`(B,T,D)`	`(1,3,4)`
`self.norm` result	`(B,T,D)`	`(1,3,4)`
`self.head` result, returned	`(B,T,V)`	`(1,3,5)`

What one output row predicts

For input IDs `[[0,1,2]]`, row Z[0,0] predicts the token after input position 0 using the prefix `[0]`; row Z[0,1] uses `[0,1]`; row Z[0,2] uses `[0,1,2]`. If the training stream is `[0,1,2,3]`, the aligned targets for those three rows are `[1,2,3]`. The forward method receives the input IDs, not these targets.

Returning all T rows lets training score all those shifted targets in one call. Generation can later select only `logits[:,-1,:]` for the next token. Applying argmax or sampling inside forward would discard information needed for cross-entropy and return the wrong contract.

Cross-entropy accepts unnormalized logits and carries out its stable log-probability calculation internally. With $B = 2$, $T = 3$, $V = 5$, the supplied driver reshapes `(2,3,5)` into `(6,5)` and uses six targets; the five candidate scores for each position stay together. Official CrossEntropyLoss documentation

Why causal isolation and context sensitivity are different checks

Change `[[0,1,2]]` to `[[0,1,4]]`. Earlier output rows $t = 0{,}1$ must remain unchanged: their permitted inputs have not changed. Inductively, every row entering the next block still depends only on its prefix, and per-position LayerNorm/FFN do not introduce future dependencies. Applying the mask at every layer preserves this property. This is checked with unchanged weights and deterministic forward computations; this exercise has no dropout.

Now change `[[0,1,2]]` to `[[3,1,2]]`. The last row is allowed to change because it can read the earlier position 0. A model that ignores all context could pass future isolation, so the supplied random-fixture driver also requires a last-row change in this particular comparison. Sensitivity is a capability, not a guarantee that every parameter setting and every earlier-token change must alter the final logits.

Positions are added once in this model; the causal mask is applied in each attention layer. The loop processes depth, while each block still processes all T positions together. More detailed causal dependency reasoning remains in 04.05.

A complete one-position prefix example for the live walkthrough

Use the deterministic weights above, but take only its first prefix `input_ids=[[0]]`, shape `(B,T)=(1, 1)`. Keep $D = 4$, $V = 5$, heads=2, $L = 2$, $M = 8$. This is a smaller view of the same fixture, not a change to the supplied check or constructor.

Lookup and zero position addition give `H0=[[[1,-1,1,-1]]]`. Each head has one visible key, so its attention weight is 1. With identity V/output projections, attention returns LN(H). The zero FFN branch adds nothing. Keeping the actual epsilon1e-5 and rounding:

$$H_1 \approx [[[2, -2, 2, -2]]], \qquad H_2 \approx [[[3, -3, 3, -3]]].$$

The second block consumes H1 and recomputes normalization. Final LayerNorm brings this row approximately back to `[1,-1,1,-1]`. The specified `(5,4)` head maps four coordinates to five candidate scores:

$$Z \approx [[[1, -1, 1, -1, 0]]], \qquad (1, 1, 4) \mathbin{@} (4, 5) \longrightarrow (1, 1, 5).$$

Scores belong to token IDs 0…4, predicting after the single supplied input; this is not an appended token or feature. Return all positions even though this smaller example has one; the original three-position trace and driver require three output rows. This walkthrough does not certify learner understanding or trained prediction quality. The six steps below use the actual function names and method/loop indentation.

Six guided implementation steps

Open 04_09_decoder_model.py. Edit only `TinyDecoder.forward` between the learner markers. Leave `DecoderBlock`, the constructor, imports and supplied driver unchanged. The following plan specifies operations without replacing your implementation.

1. **Look up input features.** Call the existing `self.embedding` module on `input_ids`, using the syntax `module(argument)`, and save the tensor as `hidden`. The method body uses eight spaces of indentation. Expect `(B,T,D)`; the example is `(1,3,4)`. Calling the module is different from constructing another `nn.Embedding`.
2. **Add positions.** Pass `hidden` and `self.positions` to the existing `add_positions` helper, leaving its default offset at zero, and replace `hidden` with its return. Keep eight-space indentation. Expect H0 with the same shape; do not add integer IDs, all M rows, or a second position signal inside the block loop.
3. **Run every block in order.** `for block in self.blocks:` takes the next module from the ModuleList at each iteration. Put that loop header at eight spaces. Its body has twelve spaces:

call the current block on the current `hidden` and assign the returned tensor back to `hidden`. With $L = 2$, the first iteration produces H1 and the next consumes H1 to produce H2. Do not keep feeding H0, ignore the return, add another residual, or return inside the loop.

4. **Normalize the final hidden state.** After the loop, return to eight-space indentation. Apply the existing `self.norm` to the latest `hidden`, saving the normalized tensor. Shape remains `(B,T,D)`. This is the final normalization, in addition to the separate norms already inside each block.
5. **Compute vocabulary scores.** Apply the existing `self.head` to that normalized tensor and save `logits`. It handles its stored weight transpose and preserves B/T automatically: expect `(B,T,V)` . Do not flatten for this call, manually transpose the hidden state, apply softmax, or choose token IDs.
6. **Return all logits.** At eight-space indentation after the loop, return the one `logits` tensor. For the worked input, its shape is `(1,3,5)`; the original two-sample driver expects `(2,3,5)`.

`for` repeats only its indented body. Returning to eight spaces ends that loop body; `return` then ends the whole forward call. No new conditional, break, continue, optimizer, mask construction or nested batch/position loop is needed.

Parameters and checkpoint check

Registration makes `embedding.weight`, `positions`, names such as `blocks.0.q`, both blocks' norms/FFN modules, final norm and head visible in `named_parameters()` and `state_dict()`. A checkpoint stores weights; it does not make a second model share live parameter objects with the first. Construct the same dimensions, then load the saved state to reproduce its output under the same computation settings.

Optional arithmetic audit for this exact architecture: a block has four bias-free $D\times D$ projection matrices, two LayerNorms with gain/bias, and `Linear(D,4D)` / `Linear(4D,D)` including biases. Its parameter count is $12D^2 + 9D$; the whole untied model has:

$$N = 2VD + MD + L(12D^2 + 9D) + 2D.$$

For $V = 5$, $D = 4$, $L = 2$, $M = 8$, $N = 536$. Heads split existing coordinates and do not multiply the number of these projection matrices. This is a source-derived audit, not an experiment result or a universal Transformer parameter formula.

Run, checks and preparation status

Run after completing 04.08 and this learner region:

```
python exercises/04_09_decoder_model.py
```

Expected success output:

```
Lesson 04.09 checks passed.
```

An unfinished 04.08 can produce `learner TODO or an unfinished prerequisite`; that identifies missing exercise code, not an environment installation problem. Reuse the existing environment.

The unchanged supplied driver checks $B = 2$, $T = 3$, $V = 5$ output shape, unchanged earlier outputs when the final input changes, a changed final output for its earlier-token perturbation, gradient connectivity for all registered parameters, and state-dictionary round-trip output equality. `grad is not None` does not prove every gradient is nonzero or that the model has learned language.

The deterministic NumPy trace agrees with supplied Torch blocks.

04.10 Train and generate with the tiny Transformer

Method sources

The adaptive optimizer used in this section is Adam, introduced by Kingma and Ba, 2015; R09. The training fixture and its stopping checks do not reproduce the original paper's benchmarks.

What this lesson connects

This assumption permits teaching the next lesson; it is not evidence that the actual 04.09 file has passed.

04.09 assembles token IDs → hidden features → causal blocks → logits. This lesson adds shifted targets, a loss, automatic gradients and an optimizer, then uses the trained model to generate one token at a time. The model already exists when `fit_tiny` is called; update that same object rather than constructing another decoder.

First fit one small consistent batch repeatedly. This is a wiring diagnostic: can the complete computation learn its supplied mapping? A failure suggests inspecting target alignment, masks, registered parameters, gradients and the optimizer, as well as data consistency, model capacity and the learning rate. It does not by itself prove a particular bug. Success on this reused batch is not held-out generalization or evidence of a useful language model.

Formula first: logits, targets and mean cross-entropy

Let X and Y have shape `(B,T)`, with Y already containing the next-token target for each input position. One forward call produces $Z = f_\theta(X)$, shape `(B,T,V)`. For target y=Y[b, t]:

$$p_{b,t,v} = \frac{e^{Z_{b,t,v}}}{\sum_{j=0}^{V-1} e^{Z_{b,t,j}}}, \qquad \ell_{b,t} = -\log p_{b,t,y} = -Z_{b,t,y} + \log \sum_{v=0}^{V-1} e^{Z_{b,t,v}}.$$

There are $B{\times}T$ target positions, so the mean objective is:

$$L = \frac{1}{BT} \sum_{b=0}^{B-1} \sum_{t=0}^{T-1} \ell_{b,t}.$$

The implementation sends **raw logits**, not softmax probabilities, to `F.cross_entropy`; it performs the stable log-probability calculation internally. Reshape logits into `(B*T,V)` and targets into `(B*T,)`, retaining all V candidates together for each position. The row correspondence is $q = bT+t$. `reshape(-1,V)` infers BT; `-1` does not mean an extra dimension or a negative size. Do not flatten logits into a single candidate-free vector. Official cross-entropy documentation

Classroom follow-up: where is softmax if it is never called

After passing04.10, the learner asked how `loss = F.cross_entropy(logits_flat, target_flat)` computes a probability-based loss without an explicit softmax. This interface takes raw scores and includes the mathematics of softmax normalization. For this lesson's integer targets, no weighting/ignored positions, default mean reduction and no label smoothing, it is mathematically equivalent to:

```
loss = F.cross_entropy(logits_flat, target_flat)

# Equivalent expanded calculation for understanding:
log_probs = F.log_softmax(logits_flat, dim=-1)
loss_expanded = F.nll_loss(log_probs, target_flat)
```

$N = BT$ and `log_probs` still has shape `(N,V)`. NLL means negative log-likelihood; `F.nll_loss` selects each row's true-target log-probability, negates it and averages by default. This describes mathematical equivalence, not a requirement to materialize ordinary probabilities or call a fixed sequence of Python functions internally. Official explanation.

For one row of raw scores z and true target y:

$$p_v = \frac{e^{z_v}}{\sum_j e^{z_j}}, \qquad \log p_v = z_v - \operatorname{logsumexp}(z), \qquad \ell = -\log p_y = -z_y + \operatorname{logsumexp}(z).$$

Complete small example, separate from the original binary batch: logits=`[[2,1,0]]` with shape `(1,3)`, target=`[0]` with shape `(1,)`. Columns represent candidate IDs 0,1,2. Target0 selects a candidate; it does not request a numeric model output of zero.

```
softmax probabilities: [[0.66524096, 0.24472847, 0.09003057]]  shape (1,3)
log probabilities:     [[-0.40760596,-1.40760596,-2.40760596]] shape (1,3)
select true ID0:        -0.40760596                          shape (1,)
negative and mean:      0.40760596                           scalar, shape ()
```

With one row the mean is that row's loss; the original batch averages eight target losses. `cross_entropy(softmax(logits), target)` treats probabilities as new logits and normalizes again, changing the objective and gradients. This example's correct loss is approximately0.407606; passing softmax first gives approximately0.797190.




Figure 84: Floating-point paths through probabilities versus direct log-probabilities

Read the figure: This reuses03.10's separate extreme example: logits=`[1000,0,-1000]`, targetID2. The left path rounds ordinary probabilities to `[1,0,0]`, making `-log(0)` infinite. Stable log-probabilities on the right are `[0,-1000,-2000]`, giving finite target loss 2000. Keep this example separate from the preceding `[2,1,0]` arithmetic. Both paths define the same mathematical loss; rounding changes the computed results. This explains the greater numerical stability of computing log-softmax directly.

`loss.backward()` propagates gradients through internal normalization into the model; the softmax mathematics is still present. Attention softmax normalizes over key positions; this normalization is over V vocabulary candidates and has a different role. Compute softmax when sampling or inspecting probabilities; greedy argmax preserves the ordering of finite scores and can select directly from logits.

Complete batch example and teacher forcing

The supplied driver constructs `TinyDecoder(2,8,2,1,16)`: $V = 2$, $D = 8$, heads=2, $L = 1$, $M = 16$. Its $B = 2$, $T = 4$ batch is:

```
input_ids  X = [[0,1,0,1], [1,0,1,0]]    shape (2,4)
target_ids Y = [[1,0,1,0], [0,1,0,1]]    shape (2,4)
```

The first row can be read from the five-ID stream `[0,1,0,1,0]`: take its first four IDs as X and its last four as Y. The second row uses `[1,0,1,0,1]`. $Y = 1 - X$ is a convenient property of this alternating binary fixture, not a general target-construction rule for text.

Only X enters the decoder. Training uses the true preceding input tokens; this is teacher forcing. At $t = 0$ the causal model sees `[0]` and predicts target1, at $t = 1$ it sees `[0,1]` and predicts target0, and so on. Although all true input positions are supplied at once, the causal mask prevents a row from reading later inputs. The labels enter the loss, not the attention computation. Y is already aligned; shifting it again would change the task.

The model's logits are `(2,4,2)`, reshaped to `(8,2)`. Targets become:

```
[1,0,1,0,0,1,0,1]                    shape (8,)
```

For an **illustrative uniform prediction**, every row gives its true target probability 0.5. Each row contributes `-ln(0.5)=ln(2)≈0.693147`; averaging eight equal contributions gives the same 0.693147. If all true-target probabilities were 0.75, the mean would instead be `-ln(0.75)≈0.287682`. These are arithmetic examples, not the actual random initialization's measured loss or a promised training trajectory.

Eight input positions, eight shifted targets, one mean loss

B=2, T=4, V=2 | Actual token IDs above; hypothetical uniform probabilities below.

input_ids = X

shape = (B,T) = (2,4)

	t=0	t=1	t=2	t=3
b=0	0	1	0	1
b=1	1	0	1	0

target_ids = Y

shape = (B,T) = (2,4)

	t=0	t=1	t=2	t=3
b=0	1	0	1	0
b=1	0	1	0	1

Only X enters the model. Y already holds next-token targets; send it directly to the loss.

reshape: (B,T,V)=(2,4,2) → (8,2)

q=b*T+t	ID0	ID1	target
q=0 (0,0)	0.5	0.5	1
q=1 (0,1)	0.5	0.5	0
q=2 (0,2)	0.5	0.5	1
q=3 (0,3)	0.5	0.5	0
q=4 (1,0)	0.5	0.5	0
q=5 (1,1)	0.5	0.5	1
q=6 (1,2)	0.5	0.5	0
q=7 (1,3)	0.5	0.5	1

Select the true target in each row

$\text{loss}[q] = -\ln(0.5) \approx 0.693147$

L = (loss[0] + ⋯+ loss[7]) / 8

L ≈ 0.693147, rather than 8 × 0.693147

Green cells follow targets. This table shows probabilities; fit_tiny sends raw logits to cross-entropy.

Figure 85: The actual shifted batch, flattened position order and an illustrative uniform cross-entropy

Read the figure: The upper cells contain actual token IDs, with B as rows and T as columns. The lower table changes meaning: each row is one flattened `(b,t)` position, and its two columns are hypothetical candidate probabilities. Green selects the true target; the adjacent loss box averages all eight terms. Shape metadata and cell contents are labeled separately.

Why Adam, and what it remembers

Start with the purpose: smoother directions and coordinate-wise scaling

Plain gradient descent updates parameters directly from this iteration's gradient:

$$g_s = \nabla_\theta L_s(\theta_{s-1}), \qquad \theta_s = \theta_{s-1} - \eta g_s.$$

Theta denotes model parameters and η the learning rate. Gradients can fluctuate between batches, and their scales can differ substantially across parameters. Adam adds two memories to this update: **an exponential moving average m of gradients to smooth direction, and an exponential moving average v of squared gradients to estimate recent scale.** It divides the former by the square root of the latter, then applies the learning rate. It still needs gradients from backward; it does not replace differentiation.

Coordinate-wise scaling means each parameter coordinate has its own m, v and multiplier. A weight with shape `(8,8)` has m and v of shape `(8,8)`, updated element by element, rather than one shared average for the whole table. This differs from LayerNorm, which normalizes activations along a feature axis.

Define every symbol, including the β superscripts

Symbol	Meaning	Setting or example here
s	Update number, starting at 1; not sequence position T or the total update budget	s=1 for update 1, s=2 for update 2
g_s	Current loss gradient evaluated at the pre-update parameters θ_{s-1}	Illustrative g_1=0.2
β_1	Fraction of the previous m retained; the new gradient receives1-β_1	0.9:90% previous statistic+10% new gradient
β_2	Fraction of the previous v retained; the new squared gradient receives1-β_2	0.999:99.9% previous statistic+0.1% new square
β_1^s, β_2^s	β_1 and β_2 each raised to power s, for startup bias correction	At s=2:0.81 and 0.998001
m_s, v_s	The two accumulated statistics through update s for that coordinate	m_0=v_0=0

Symbol	Meaning	Setting or example here
$\widehat{m}_s$, $\widehat{v}_s$	Statistics corrected for zero initialization, written with hats	Not new model parameters
η, ϵ	Base learning rate and small positive denominator stabilizer	0.03 and 1e-8

Subscripts1 and 2 distinguish the two betas; superscript s means **exponentiation**, not β_1 multiplied by s or another trainable parameter. Betas remain fixed here while s increases:

$$\beta_1^s = (0.9)^s, \qquad \beta_2^s = (0.999)^s.$$

Update number s	β_1^s	β_2^s
1	0.9	0.999
2	0.81	0.998001
3	0.729	0.997002999

Python exponentiation is `beta_1 ** s`; `^` is bitwise XOR in Python, so `beta_1 ^ s` does not implement the mathematical power. Betas closer to 1 generally retain longer history and respond more slowly to new gradients. They are optimizer hyperparameters, not learned by backward. This explanation assumes every parameter participates each iteration; PyTorch actually maintains update counters per parameter.

First memory m: smooth the direction

$$m_s = \beta_1 m_{s-1} + (1-\beta_1) g_s = 0.9 m_{s-1} + 0.1 g_s.$$

For example, if the previous m is 0.2 and the current gradient suddenly becomes-0.2, the new m is 0.9×0.2+0.1×(-0.2)=0.16. The current gradient has changed sign, but the historical direction has not flipped immediately. This can soften a fluctuation, but it also creates lag when direction changes. Adam does not necessarily follow the current negative gradient or decrease the loss at every step.

Second memory v: track magnitude without sign cancellation

$$v_s = \beta_2 v_{s-1} + (1-\beta_2) g_s^2.$$

Here g_s^2 is an element-wise square. Both+0.2 and-0.2 square to 0.04, so v tracks magnitude without cancellation from opposite signs. It is a second raw moment estimate: **a smoothed statistic of squared gradients, not a second derivative or a mean-centered variance.** The square root returns it to the gradient's units, giving a scale similar to recent RMS.

Why divide by $1-\beta^s$

Adam starts at m_0=v_0=0. That zero means no gradients have been observed yet. Temporarily prescribe a constant gradient0.2 at every update to isolate the startup effect; this is not a measured network trajectory.

At update 1, m_1=0.9×0+0.1×0.2=0.02. Although the observed gradient is 0.2, the raw statistic is only 0.02 because90% of the weight still belongs to the initial zero. At update 2, m_2=0.9×0.02+0.1×0.2=0.038, still well below0.2.

Expanding the recurrence reveals the correction denominator:

$$\begin{aligned} m_1 &= 0.1g_1, \\ m_2 &= 0.09g_1 + 0.1g_2, \\ m_3 &= 0.081g_1 + 0.09g_2 + 0.1g_3. \end{aligned}$$

The observed gradients have total weights0.1,0.19 and 0.271, respectively:$1-0.9^1$,$1-0.9^2$ and $1-0.9^3$. In general, the initialization contributes $\beta_1^s\ m_0$ before setting m_0 to zero, and the gradient terms have total weight:

$$m_s = \beta_1^s m_0 + (1-\beta_1)\sum_{k=1}^{s}\beta_1^{s-k}g_k, \qquad (1-\beta_1)\sum_{k=1}^{s}\beta_1^{s-k} = 1-\beta_1^s.$$

With m_0=0, dividing by the total observed-gradient weight produces a weighted average whose weights sum to 1. The same derivation applied to squared gradients gives v's correction:

$$\widehat{m}_s = \frac{m_s}{1-\beta_1^s}, \qquad \hat{v}_s = \frac{v_s}{1-\beta_2^s}.$$

The first two constant-gradient updates can be checked completely:

Quantity	Update1, s=1	Update2, s=2
Prescribed gradient g_s	0.2	0.2
Uncorrected m_s	0.02	0.038
$1-\beta_1^s$	0.1	0.19
Corrected $\widehat{m}_s$	0.2	0.2
Uncorrected v_s	0.00004	0.00007996
$1-\beta_2^s$	0.001	0.001999
Corrected $\hat{v}_s$	0.04	0.04

For instance, v_2=0.999×0.00004+0.001×0.04=0.00007996; dividing by 0.001999 gives 0.04. This corrects **statistical bias from zero initialization**, not a model bias parameter, dataset bias or a prediction error. Constant gradients recover the constant value; changing gradients still produce a weighted recent average, not knowledge of a true optimal gradient. As s grows, both β^s terms approach0 and the correction denominators approach1.




Figure 86: Two memory paths for direction and scale, with startup weight correction

Read the figure: The upper flow splits g into signed-gradient memory m and squared-gradient memory v, then combines them into an update. The lower panel uses β_1=0.9 to show the first three sets of raw weights. Gray belongs to the initial zero; colors belong to observed gradients. Divide by the colored total1-β_1^s. Gray does not represent zero-gradient samples or parameter values. The v branch independently applies the same correction with β_2=0.999.

Combine direction and scale into a parameter update

$$\theta_{s,i} = \theta_{s-1,i} - \underbrace{\frac{\eta}{\sqrt{\hat{v}_{s,i}} + \epsilon}}_{\text{coordinate scaling factor}} \underbrace{\widehat{m}_{s,i}}_{\text{smoothed gradient}} .$$

Each coordinate has its own denominator. **Holding $\widehat{m}_s$ fixed**, a larger $\hat{v}_s$ means a smaller update magnitude. But both memories depend on gradients; a larger current gradient does not necessarily mean a smaller Adam update. Multiplying the whole gradient history by a positive constant scales both numerator and the main denominator term, approximately canceling when ϵ is negligible. Eta still controls overall step size; Adam does not remove the need to choose a learning rate.

For the first scalar update, prescribe θ_0=1, g_1=0.2 and η=0.03. The table gives $\widehat{m}_s$=0.2 and $\hat{v}_s$=0.04, hence:

$$\theta_1 = 1 - 0.03\frac{0.2}{\sqrt{0.04} + 10^{-8}} = 1 - 0.03\frac{0.2}{0.2 + 10^{-8}} \approx 0.97.$$

Plain SGD gives 1-0.03×0.2=0.994. If update 2 is also **prescribed** gradient0.2, corrected statistics remain0.2 and 0.04, and the parameter becomes approximately0.94. A real model must recompute gradients at its new parameters; the gradient need not remain constant. A first gradient-0.2 gives negative $\widehat{m}_s$ with a positive denominator, so subtracting the negative update increases the parameter. Later direction follows smoothed m. Epsilon is outside the root here, unlike the LayerNorm variance expression.

This exercise uses Adam defaults β_1=0.9, β_2=0.999 and ϵ=1e-8, with no weight decay. These formulas describe standard Adam from the original paper; students do not implement the optimizer itself. Adam paper, official optimizer documentation.

Create **one optimizer before the training loop** so m/v persist across its updates. Recreating Adam each iteration loses its history. This simple helper does create a new optimizer on each separate `fit_tiny` call; it is not a resume-training interface that preserves optimizer state across calls.

The code responsibilities are separate: `loss.backward()` computes g; `optimizer.step()` updates m, v and the counter s, then changes parameters; `optimizer.zero_grad(...)` clears parameter `.grad` while retaining optimizer statistics. You call these interfaces; the assignment's eight-step implementation plan stays the same.




Figure 87: First scalar Adam update and the position of loss recording within an iteration

Read the figure: The upper flow is a chosen scalar gradient, not measured decoder weights. The lower flow shows the real loop order: compute loss, record a Python float, backpropagate, then update parameters. A history of length80 contains losses before updates 1…80; it does not include a new forward evaluation after update 80.

Exact function contract and side effects

```
def fit_tiny(model: nn.Module, input_ids: torch.Tensor, target_ids: torch.Tensor, steps: int,
↪  learning_rate: float) -> list[float]:
```

Name	Type / shape	Meaning
`model`	Existing compatible `nn.Module`	Registered trainable parameters; forward returns raw `(B,T,V)` logits
`input_ids`	`torch.long`, `(B,T)`	Already prepared token IDs; $B \geq 1$, $T \geq 1$, IDs valid for the model
`target_ids`	`torch.long`, same `(B,T)`	Already shifted labels, each in `[0,V)`; not one-hot vectors
`steps`	Nonnegative Python integer	Number of optimizer updates over the same batch
`learning_rate`	Positive float	Adam step size; original fixture uses0.03
Return `history`	Python `list[float]`	One scalar mean loss before each update; length exactly `steps`

Inputs and model use compatible devices. T must respect the decoder's position capacity. Reuse the passed model and parameter objects; do not change input or target tensors. The function calls `model.train()` and leaves it in training mode. It updates model parameters in place through the optimizer. A zero-step call returns `[]` and does not update parameter values, although setting the training-mode flag is still a side effect.

Do not create a new model, return a replacement model, construct labels, sample inputs or implement a tokenizer in this helper. V comes from the returned logits' last axis; `input_ids.max()+1` need not equal vocabulary size.

Training mode, gradients and parameter updates

`model.train()` switches the module's training-mode flag; it does not itself calculate a loss, run backward, or update parameters. The actual update requires the forward → loss → backward → optimizer-step sequence. In this exercise there is no dropout, but retaining the mode call makes the helper's intent explicit.

`loss.backward()` calculates parameter gradients. `optimizer.step()` reads those gradients and changes the parameters. `optimizer.zero_grad(set_to_none=True)` clears old gradients while preserving Adam's running moments. Each operation has a separate job.

`loss.item()` extracts a Python float for recording. It does not replace or detach the original `loss` tensor unless the programmer overwrites that variable. Append the float to history, then backpropagate through the retained tensor. A Python float has no `.backward()` method.

The chat preview follows the existing worked batch, mean-loss arithmetic, separately labeled scalar Adam example, eight guided steps and full-prefix generation diagram below.

Eight guided implementation steps

Edit only `fit_tiny` between the learner markers in 04_10_train_tiny_transformer.py. Keep the imports and supplied driver unchanged.

1. **Prepare persistent state at four-space indentation.** Construct `torch.optim.Adam` from `model.parameters()` and the supplied `learning_rate`; save it as `optimizer`. Use its default zero weight decay. Call `model.train()` and create an empty `history` list. Do this once per function call, outside the update loop.
2. **Start the loop.** Use `for _ in range(steps):` at four spaces. The body has eight spaces. `range(0)` has no iterations, so the later return can still return the empty list. `_` is an unused loop-counter name.
3. **Clear old gradients.** Inside the loop, call `optimizer.zero_grad(set_to_none=True)`. PyTorch normally accumulates gradients; clearing them makes this iteration differentiate its own loss. Resetting `.grad` is different from deleting Adam's moment state. Do not rebuild the optimizer.
4. **Run the current model.** Call `model(input_ids)` and save `logits`, shape `(B,T,V)`. Read V from `logits.shape[-1]`; reshape scores to `(-1,V)` and labels to `(-1)`. In the fixture, expect `(8, 2)` and `(8,)`. Forward must run again after each update to use the current weights.
5. **Compute and record the loss.** Pass the reshaped raw logits and labels to `F.cross_entropy`, saving the scalar `loss`. Append `loss.item()` to history before the update; `.item()` produces a Python float without retaining that computation graph in the list. Keep the tensor `loss` for backpropagation.
6. **Backpropagate once.** Call `.backward()` on the loss tensor. This fills gradients for the registered model parameters; it does not itself change their values. Do not backpropagate through the extracted Python float or run the training forward under `no_grad`.
7. **Update once.** Call `optimizer.step()` after backward. It reads the current gradients, updates moments and modifies the same model parameters. The next iteration returns to gradient clearing and a fresh forward. Both operations in steps6/7 stay at eight spaces.
8. **Return after the loop.** At four spaces, return the complete `history`. For steps0 expect `[]`; steps80 must produce80 Python floats. Returning inside the loop would stop training after one update.

The loss need not decrease on every single step. The original fixture checks final versus initial recorded loss and a threshold; it does not demand monotonic descent. Its learning rate is a diagnostic setting, not a recommendation for larger training runs.

Generation: use the last row and grow the prefix

After fitting, the supplied driver switches to evaluation mode and wraps generation in `torch.no_grad()`. `.eval()` controls mode-dependent module behavior; `no_grad()` disables graph recording. They serve different purposes, even though this tiny decoder has no dropout. During fitting, gradients must remain enabled.

For a current prefix of k IDs, forward returns `(1,k,V)`. Select `[0,-1]`: sample0, its final input position, all V candidates. Greedy generation chooses:

$$x_k = \operatorname*{argmax}_{v \in \{0,\ldots,V-1\}} Z_{0,k-1,v}.$$

Append that integer to the Python prefix and run forward again on the entire longer prefix. Argmax needs no softmax because softmax preserves score ordering. This exercise has no KV cache; each iteration recomputes the whole prefix and uses positions starting at 0 consistently.

For the fitted alternating fixture, the supplied expectation is:

```
prefix [0]         -> logits (1,1,2) -> last row t=0 -> ID1
prefix [0,1]       -> logits (1,2,2) -> last row t=1 -> ID0
prefix [0,1,0]     -> logits (1,3,2) -> last row t=2 -> ID1
prefix [0,1,0,1]   -> logits (1,4,2) -> last row t=3 -> ID0
prefix [0,1,0,1,0] -> logits (1,5,2) -> last row t=4 -> ID1
returned prefix: [0,1,0,1,0,1]
```

Generation grows the input prefix and selects only its final logit row

After fitting, the supplied check expects 0,1,0,1,0,1. This illustrates its generation loop.

	Current prefix	Returned logits shape	Final row t	New ID
1	[0]	(1,1,2)	0	1
2	[0, 1]	(1,2,2)	1	0
3	[0, 1, 0]	(1,3,2)	2	1
4	[0, 1, 0, 1]	(1,4,2)	3	0
5	[0, 1, 0, 1, 0]	(1,5,2)	4	1

logits[0,-1]: shape=(V,)=(2,) → argmax → one integer ID → append to prefix

Final list: [0, 1, 0, 1, 0, 1]

Each call recomputes its full prefix, without KV cache. Maximum input T=5; final list length=6; M=16.

Figure 88: Five growing-prefix calls, their output shapes and last-row selections

Read the figure: Each line is a new forward call. The first column is actual prefix content; the next is shape metadata, followed by the selected position index and appended ID. The initial token plus five generated tokens yields six IDs. Here the longest actual forward input has five IDs and $M = 16$. Before another call, check that its supplied prefix fits capacity; there is no automatic truncation, wraparound or cache. This small success beyond the four training positions is not a general long-context claim.

The sampling loop is supplied check code, not another core to implement in this lesson. Teacher forcing uses true preceding tokens during training; generation conditions on the IDs it has already chosen. Errors can therefore affect later choices. A two-ID toy sequence has no general text-decoding stage; a real tokenizer later needs a matching decode function.

Run and interpret the supplied checks

After completing 04.09 and this helper, run in the existing environment:

```
python exercises/04_10_train_tiny_transformer.py
```

Expected success output:

```
Lesson 04.10 checks passed.
```

The unchanged driver uses seed 10, a zero-step call with unchanged parameter values, then80 Adam updates on the same batch at lr0.03. It requires80 losses, the final recorded loss below0.15 and below the first, and greedy output `[0,1,0,1,0,1]`. With80 updates there are 640 supervised token positions counted with repetition. The threshold is an acceptance criterion for this fixture; it is not a validation or language-quality score.

Further preparation compared zero/one/multiple steps with independent per-row log-sum-exp loss and Adam trajectories, non-contiguous inputs, float64, model/parameter identity, input preservation and the first scalar Adam update. Arithmetic figures and bilingual links/formulas were checked.

Later lab and classroom record

Once the wiring diagnostic passes, a separate real-text experiment can use licensed data, a fixed train/validation split, tokenizer/data versions, a portable configuration, a training budget and fixed evaluation prompts. Record the full code commit, validation loss, generated samples and conclusions; keep large weights/data outside Git. Do not rename the repeated-batch training loss "validation loss."

Looking back

The decoder is now a working composition of familiar operations. Modern variants change some of those operations and their numerical behavior; they do not remove the need to check their contracts.

05 Choose reliable model components

A model diagram does not tell the whole numerical story. Normalization defines which statistics are removed, positional rotations define how coordinate pairs interact, and a gated feed-forward layer defines two branches whose elementwise product must be aligned. Optimization adds its own state and time conventions.

This chapter revisits the decoder with RMSNorm, rotary position embeddings and SwiGLU, then follows initialization, AdamW, scheduling, clipping and checkpoint recovery. The aim is to understand what each replacement preserves and what it changes. In particular, a checkpoint is a continuation of a process, not merely a copy of model weights.

05.01 RMS normalization

Method sources

Root mean square normalization (RMSNorm) is introduced by Zhang and Sennrich, 2019; R06. The exercise implements the full-feature RMS statistic, with explicit ϵ, axis and dtype choices; it does not implement partial RMSNorm.

From the first decoder to a different normalization choice

The first decoder uses LayerNorm inside pre-norm branches and before the vocabulary head. Chapter 05 studies alternative components that can fit the same causal residual structure. Here we examine RMSNorm; later05.04 composes the validated pieces into another baseline. Learning this alternative does not imply that the earlier model was incorrect or that a replacement always improves quality.

Normalization gives later projections features with a controlled magnitude. RMSNorm obtains a shared scale from each feature row and allows learned per-coordinate gains. Its central difference from LayerNorm is that it does not subtract the row mean. Removing centering simplifies the calculation; runtime and model quality still depend on the implementation and experiment. Original RMSNorm paper, authors' explanation and formula.

Prerequisites are last-axis reductions/broadcasting, gradients, and 04.08 LayerNorm. This is a standalone tensor function with no dependency on04.10's implementation. Use the existing environment; this assignment does not depend on a newer built-in RMSNorm module.

RMSNorm now operates on hidden **features**: each `(b,t)` row has D coordinates and receives its own magnitude adjustment. Softmax instead converts V candidate scores into probabilities summing to 1. RMSNorm's coordinates are not candidate probabilities; normalization here controls feature magnitude. Keep the axes and purposes distinct while reading the formulas.

Formula first: root mean square, then learned gain

For one feature row x containing D coordinates, define its mean square and stabilized denominator:

$$a = \frac{1}{D}\sum_{j=0}^{D-1} x_j^2, \qquad r = \frac{1}{\sqrt{a+\epsilon}}, \qquad y_i = g_i x_i r.$$

- x_i is feature coordinate i, not a token ID or a probability.
- D counts features in a row; it is not B, T, vocabulary size or layer count.
- a is one scalar shared by the D coordinates of that row.
- ϵ is the positive `eps`, inside the square root; default1e-6.
- r is the reciprocal stabilized RMS, called `inverse_rms` in the hints.
- g_i is `gain[i]`, a supplied trainable-capable feature multiplier. This function has no additive bias.

"Root mean square" describes square → mean → square root. The exact RMS is sqrt(a); this implementation uses sqrt(a+ϵ) to avoid a zero denominator. `torch.rsqrt(z)` computes1/sqrt(z), so it combines the root and reciprocal operations. Official rsqrt documentation

Let u=x*r be the vector before gain. It is multiplied by one positive scalar, preserving that row's direction when nonzero. Nonuniform or negative gains can change the final direction or signs. With positive ϵ:

$$\frac{1}{D}\sum_i u_i^2 = \frac{a}{a+\epsilon}.$$

This is close to 1 when a is much larger than ϵ. RMS normalization does not generally make the mean zero, set each coordinate to 1, limit every output to[-1,1], or produce probabilities. After arbitrary gain, even its mean square need not be near1. Its Euclidean length without gain is approximately sqrt(D), not generally1.

Complete original fixture, with every intermediate value

The supplied driver's first input is `x=[[3,4]]`, shape `(1,2)`, using float64. `gain=[1,2]`, shape `(2,)`; eps=0.000001. $D = 2$:

```
square:          [[9,16]]                shape (1,2)
mean_square:     [[12.5]]                shape (1,1)
mean_square+eps: [[12.500001]]            shape (1,1)
denominator:    [[3.53553405...]]         shape (1,1)
inverse_rms:    [[0.28284270...]]         shape (1,1)
normalized:     [[0.84852810,1.13137080]]  shape (1,2)
output:         [[0.84852810,2.26274161]]  shape (1,2)
```

In particular, the final second coordinate is `4/sqrt(12.500001)*2`, not `4/sqrt(12.500001)`. Gain multiplies features individually; it is not a second normalization statistic.




Figure 89: Exact RMSNorm arithmetic, learned gain and a separately labeled LayerNorm comparison

Read the figure: The first row computes one scalar statistic from two features; the next multiplies both features by its reciprocal denominator and then by the two gains. Metadata bands give shapes; values occupy their own area. The bottom is a **separate comparison using gain=[1,1] on both sides**, not the primary output with gain=[1,2].

Compare LayerNorm under matched settings

For a row mean mu and population variance sigma²:

$$\mu = \frac{1}{D}\sum_j x_j, \qquad \sigma^2 = \frac{1}{D}\sum_j (x_j - \mu)^2, \qquad \frac{1}{D}\sum_j x_j^2 = \sigma^2 + \mu^2.$$

The normalization cores, before gains or bias, are:

$$u_i^{\mathrm{LN}} = \frac{x_i - \mu}{\sqrt{\sigma^2 + \epsilon}}, \qquad u_i^{\mathrm{RMS}} = \frac{x_i}{\sqrt{\sigma^2 + \mu^2 + \epsilon}}.$$

For x=[3,4], mu=3.5 and sigma²=0.25. With unit gain, no LayerNorm bias and the same eps1e-6:

Stage	LayerNorm	RMSNorm
Numerator	`[-0.5,0.5]`	`[3,4]`
Denominator	`sqrt(0.250001)`	`sqrt(12.500001)`
Output	approximately `[-0.999998,0.999998]`	approximately `[0.848528,1.131371]`

Adding the same constant to every coordinate cancels under LayerNorm centering, but generally changes RMSNorm's result. For mean-zero inputs, the two cores agree when ϵ matches; complete outputs also require matched gains and zero LayerNorm bias. Neither construction alone determines which will train better on a task.

Positive rescaling has a different property. For a positive scalar c, fixed gains and a=mean(x^2):

$$\frac{cx}{\sqrt{c^2 a + \epsilon}} = \frac{x}{\sqrt{a + \epsilon/c^2}}.$$

With epsilon0 this is exact positive scale invariance; with our positive ϵ it is approximate when the mean square dominates ϵ. Near zero that approximation can fail. A negative c also reverses the normalized direction before gain; do not call arbitrary signed scaling invariant.

Which axes are reduced, and what keepdim preserves

For an input `(B,T,D)`, compute statistics over the final D coordinates independently for each `(b,t)` row:

$$(B,T,D) \xrightarrow{\text{square}} (B,T,D) \xrightarrow{\text{mean}(-1,\text{keepdim=True})} (B,T,1).$$

Multiplication then broadcasts `(B,T,1)` across D features, and `gain` of shape `(D,)` across all B/T rows. No position is mixed with another, so this normalization preserves prefix-only dependencies in a causal network.

The same rule works for general `(...,D)`: for `(D,)` the retained statistic has shape `(1,)`, for `(N,D)` it is `(N,1)`. Without `keepdim=True`, `(B,T)` may fail to broadcast or silently align with the wrong axes when some sizes coincide. Shape success alone is not sufficient evidence that the intended axis was reduced.

For the figure's sample $b = 0$, take three position rows `[3,4]`, `[0,0]`, `[-3,4]`. Their mean squares are 12.5,0,12.5 separately; with gain=[1,2], the outputs are approximately `[0.8485,2.2627]`, `[0,0]`, `[-0.8485,2.2627]`. The complete input/output shape is `(1,3,2)`; statistics are `(1,3,1)`.




Figure 90: Independent position statistics and the order of float16-to-float32 computation

Read the figure: The upper panel displays only sample $b = 0$; each t row keeps its own statistic. The zero row has denominator sqrt(eps) and remains zero. The lower panel is a separate float16 example with every feature1000, explaining dtype changes rather than changing the upper example's values.

Why widen before the square

Float16 can represent1000, but1000²=1,000,000 exceeds its largest finite value 65504. A float16 square can overflow before the subsequent mean. Casting an already overflowed value to float32 does not restore it. The sequence must be:

```
float16/bfloat16 x -> float32 working tensor
-> square -> mean over D -> add eps -> reciprocal square root
-> multiply working x -> cast normalized tensor back to x.dtype
-> multiply matching-dtype gain
```

For x filled with 1000 and gain all1, the float32 mean square is 1,000,000; inverse RMS is approximately0.001, giving output approximately1 in the original dtype. For bfloat16, the conversion also improves statistic precision; its range differs from float16. Do not claim that1000² overflows bfloat16 too.

Keep float32 inputs in float32 and float64 inputs in float64. An unconditional `.float()` would reduce the precision of float64 inputs. Floating `.to(...)` conversions remain in the autograd graph; do not detach them. This wider working statistic protects this calculation for the illustrated range, not every possible floating value or the rest of a network. Final low-precision values or extreme gains can still exceed their representable range.

Function contract and dtype contract

```
def rmsnorm(x: torch.Tensor, gain: torch.Tensor, eps: float = 1e-6) -> torch.Tensor:
```

Name	Type / shape	Meaning
`x`	Floating tensor `(...,D)`, $D \geq 1$	Feature rows; float16, bfloat16, float32 or float64
`gain`	Floating `(D,)`, same dtype/device as x	One multiplier per feature, broadcast across leading axes
`eps`	Positive Python float	Added to mean square inside the square root; default1e-6
Return	Same shape/dtype/device as x	Normalized and gain-scaled tensor with gradients preserved

The matched gain dtype is part of this exercise's same-output-dtype contract. Multiplying half-precision normalized values by a float32 gain can promote the output, so mixed-dtype gains are outside this interface rather than something to guess about. Input and gain values are preserved. The function does not create a parameter or optimizer; the caller supplies gain and can register it as a parameter. The original driver uses `requires_grad=True` to check gradient connectivity.

At x=0, ϵ makes the denominator positive: sqrt(1e-6)=0.001. The output is zero for finite gain, but zero output does not mean zero input gradient. For $D = 1$, RMSNorm still approximately preserves a nonzero input's sign before gain; the centering core of LayerNorm instead gives zero.

Six guided implementation steps

With04.10 checked, open 05_01_rmsnorm.py. Follow the worked example first, then edit only the learner region in `rmsnorm`, retaining the supplied driver.

1. **Choose a working dtype.** At four-space indentation, test membership of `x.dtype` in `(torch.float16, torch.bfloat16)` using `if ... in ...:`. `in` tests membership of that tuple; an if-body uses eight spaces. Choose `torch.float32` for those two input types. An `else:` at four spaces handles the remaining types, choosing `x.dtype` in its eight-space body. Save the choice as `work_dtype`.
2. **Make the working tensor.** Return to four spaces and call `x.to(work_dtype)`, saving `work`. Shape stays `(...,D)`; only working precision changes. Do this before squaring. Preserve the original x and its dtype for the final cast.
3. **Compute mean square.** Use `.square()` and `.mean(dim=-1,keepdim=True)` on `work`, saving `mean_square`. For x shape `(1,2)` with[3,4], expect shape `(1,1)` and 12.5. No mean subtraction or reduction over T is needed.
4. **Form inverse RMS.** Add the supplied `eps` to `mean_square`, then apply `torch.rsqrt`, saving `inverse_rms`. Same statistic shape; the fixture is approximately0.28284270. Adding ϵ after rsqrt would change the function.
5. **Normalize and restore dtype.** Multiply `work` by `inverse_rms`, letting broadcasting recover `(..,D)`. Save `normalized`, then cast that tensor back to the original `x.dtype`. The fixture before gain is approximately[0.84852810,1.13137080]. Do not cast the large squared statistic back to float16.
6. **Apply gain and return.** At four spaces, multiply the normalized tensor by the supplied `gain` and return one tensor. Original fixture: approximately[[0.84852810,2.26274161]], shape `(1,2)` , dtype float64. Use ordinary multiplication; no in-place modification, manual loops over rows, detach, item conversion or parameter update is needed.

Optional gradient derivation

For one row with r=(a+ϵ)^(-1/2), the chain rule gives:

$$\frac{\partial r}{\partial x_j} = -\frac{x_j}{D} r^3, \qquad \frac{\partial y_i}{\partial x_j} = g_i \left(\delta_{ij} r - \frac{x_i x_j}{D} r^3 \right), \qquad \frac{\partial y_i}{\partial g_i} = x_i r.$$

δ_{ij} is 1 for $i = j$ and 0 otherwise. Coordinates within a row influence the shared scale, so a gradient is not just gain divided by RMS. For the original fixture and loss=sum(output), input gradients are approximately[-0.0905,0.0679], and gain gradients approximately[0.8485,1.1314]. Shared gain gradients sum contributions from all leading rows. At a zero row, its input derivative is the diagonal gain/sqrt(eps), while its gain derivative is zero. Autograd handles this; the optional derivation checks the mechanism without adding manual differentiation to the exercise function.

Run, checks and preparation status

In the existing environment:

```
python exercises/05_01_rmsnorm.py
```

Expected after implementation:

```
Lesson 05.01 checks passed.
```

The unchanged driver checks the exact float64 gain-scaled example, input/gain gradient connectivity, zero rows and finite float16 outputs with preserved dtype for1000-valued inputs. Additional checks compared independent row arithmetic, rank1/2/3 inputs, non-contiguous float64 tensors, analytic gradients, finite-difference gradcheck, four supported dtypes, zero/large rows and preserved inputs/gain. The four localized figure previews, source arithmetic, bilingual formulas and manuscript links were checked.

05.02 RoPE, rotary query and key positions

Method sources

Rotary position embedding (RoPE) is introduced in RoFormer by Su et al., 2021; R07, Sections 3.2 and 3.4.2. The pairwise rotations of Q/K and the relative-position dot-product argument below follow that construction; the concrete vectors and diagrams are our teaching examples.

RoPE applies a position-dependent rotation to projected query and key vectors before attention compares them. We first follow one vector's coordinate pairs; the relative-position derivation later in this lesson explains why these rotations are useful.

Follow-up: pair four concrete numbers before introducing symbols

Question: ω_i, base, the negative exponent and $p\omega_i$ appeared too abruptly. What is a feature pair? Are alternate entries selected and then rotated? This identifies a missing bridge in the explanation, not demonstrated understanding or completion. We rebuild the bridge from concrete values.

One vector, four coordinates, two pairs

Inspect one position and one head's vector`[1,2,3,4]`, shape`(4,)`. Entries are four floating feature values, not four tokens. Coordinate indices start at 0:

```
coordinate index: 0   1   2   3
actual value:     1   2   3   4
pairs:           [1, 2] [3, 4]
pair index:        i=0    i=1
```

A feature pair simply means two feature coordinates grouped together; it introduces no new tensor


type. A two-dimensional rotation needs two coordinates, so this implementation decomposes a longer vector into two-coordinate pieces. This is a chosen computational convention, not an assertion that those features have naturally paired semantics. Pair0 consists of coordinates0,1; pair1 consists of 2,3. Rotate each pair using the two-dimensional rule and restore the original coordinate order.

Selecting alternate entries describes the implementation's auxiliary slices:

```
even = [1,3]  # values from coordinates 0,2
odd  = [2,4]  # values from coordinates 1,3

same column 0: even[0], odd[0] -> [1,2]
same column 1: even[1], odd[1] -> [3,4]
```

Even/odd refers to coordinate-index parity, not value parity. The first entry at coordinate 0 is even-indexed; the second at coordinate 1 is odd-indexed. Even and odd are two calculation containers. Their matching columns reconstruct the original pairs; the values 1,3 inside even are not a pair rotated together. Code computes all first coordinates and all second coordinates in parallel, then reinterleaves them. The mathematics still rotates each original pair independently.



d=4, base=10000 → $\omega_0 = 1$; $\omega_1 = 1/\sqrt{10000} = 0.01$. ω is radians gained per position.

Pair i	Original pair	Speed ω_i	Position p	Angle $p\omega_i$
0	[1,2]	1	3	3
1	[3,4]	0.01	3	0.03

Choose pairs, choose their speeds, then multiply position by speed to get each angle.

Rotate [1,2] and [3,4]; [1,3] is an auxiliary slice, not a pair rotated together.

Figure 91: Coordinate indices, values, original pairs and matching slice columns

Read the figure: The upper indices and values are separate; colors identify the original pairs. Each middle column is one pair, with even on the first row and odd on the second. Only the bottom introduces pair speeds and angles at position 3. Read the upper half first.

How to read ω_i, and what base controls

The symbol resembling "Wi" is the Greek letter ω with subscript i, written ω_i. It is not a newly introduced W weight matrix. Name the quantities one at a time:

Notation	Meaning	Value in this example
d	Number of coordinates in this per-head vector	4
i	Pair index, starting at 0	0 or1
base	Fixed hyperparameter selecting rotation speeds	Default10000
ω_i	Radians turned per position step by pair i	1 or0.01
p	Absolute position of the current vector	3 in this complete example
$p\omega_i$	Position times speed, giving the rotation angle	3 or0.03 radians

Read ω as angular speed before reading the formula:

$$\omega_i = \text{base}^{-2i/d}, \qquad \theta_{p,i} = p \times \omega_i.$$

The base 10000 is a common configuration for this construction, not a vocabulary limit or a maximum forced by mathematics. Once base and d are chosen, they determine fixed speeds; backward does not learn them in this assignment. With default base>1, later pairs turn more slowly, providing changes at different distance scales. Different speeds are a design for multiple scales, not a prerequisite for the ability to rotate.

Work through the negative exponent without skipping steps

For this example $d = 4$ and base 10000:

$$\omega_0 = 10000^{-2\times 0/4} = 10000^0 = 1,$$

$$\omega_1 = 10000^{-2\times 1/4} = 10000^{-1/2} = \frac{1}{\sqrt{10000}} = \frac{1}{100} = 0.01.$$

We have assigned speed1 to pair0 and speed0.01 to pair1. Both pairs share position $p = 3$, the fourth position when counting from 0:

$$\theta_{3,0} = 3 \times 1 = 3, \qquad \theta_{3,1} = 3 \times 0.01 = 0.03.$$

The expression $p\omega_i$ is simply multiplication, not another mysterious variable. These angles are radians, without an extra factor of 2π.

Finish rotating the same four-dimensional vector

Keep input `[1,2,3,4]` at position 3. Rotate pair0 `[1,2]` by 3 radians and pair1 `[3,4]` by 0.03 radians:

```
pair 0:
  first  = 1*cos(3) - 2*sin(3) = -1.27223251
  second = 1*sin(3) + 2*cos(3) = -1.83886499
pair 1:
  first  = 3*cos(.03) - 4*sin(.03) = 2.87866810
  second = 3*sin(.03) + 4*cos(.03) = 4.08818664
output = [-1.27223251,-1.83886499,2.87866810,4.08818664]
```

The output still has four coordinates and squared length30. In the sliced implementation, rotated even is `[-1.27223251,2.87866810]` and rotated odd is `[-1.83886499,4.08818664]`; interleaving produces the final vector.

This follow-up uses vector `[1,2,3,4]`; the original $d = 2$ fixture and the wider $d = 4$ vector `[1,0,2,0]` appear in separately labeled examples later in this lesson. This section follows only `[1,2,3,4]` to completion. Establish pairs, speeds, position-times-speed and independent rotations before the later matrix/relative-position derivation. Reading the follow-up does not require immediately finishing code.

Follow-up: trace an implementation line by line

Walkthrough goal: Explain the implementation without assumed background, line by line, and illustrate `inv_freq = base**(-pair_coords/d)` specifically. Use one input throughout and distinguish dimensions, indices and values. No new training, tokens or attention operations are introduced here.

Fix the input and the purpose first

The complete example input is:

```
x = torch.tensor([[[[1., 2., 3., 4.]]]])
positions = torch.tensor([3])
base = 10000.
```

The **shape of x is `(1,1,1,4)`**: $B = 1$ sample, $H = 1$ head, $T = 1$ row and $d = 4$ feature coordinates. The nested brackets place one four-coordinate vector in the four-axis interface. Its actual values are `x[0,0,0]=[1,2,3,4]`, a Q or K feature vector, not four token IDs.

$T = 1$ means one supplied row. `positions=[3]` says its absolute position is 3, the fourth position when counting from 0. Row count and position value are different quantities. Rotate `[1,2]` and `[3,4]`

separately using their position-dependent angles, then restore the original coordinate order.

Lines 1–5: prepare working precision and compute each pair's speed

Line1: `x = x.to(work_dtype).` `.to(...)` converts the numeric type, for example float16 to float32; it does not tokenize x or move token positions. Shape and mathematical meaning stay the same, although precision/representable range can change. Floating conversions preserve gradients. The preceding if/else selects float64 work for float64 input and float32 otherwise. This line rebinds the local name x to the conversion result; it does not change the caller's original tensor dtype in place. Subsequent `x.dtype` reads inside this function nevertheless see the working type. That matters at return time.

Line2: `d = x.shape[-1].` `.shape` reads axis lengths. Index `-1` means the last axis, so d is the integer4. This does not read the last feature value 4: that equality is incidental. With values `[9,8,7,6]`, d would still be4.

Line3: create pair_coords.

```
pair_coords = torch.arange(start=0, end=d, step=2,
                           dtype=work_dtype, device=x.device)
```

`arange` generates a stepped sequence. Start at 0, stop before end=4, increment by 2: `[0.,2.]`, shape `(2,)`. These are the **starting coordinate indices** of the two pairs, not feature values selected from x and not pair indices `[0,1]`. dtype prepares floating arithmetic; device keeps the new tensor on the same computational device as x.

Line4: `inv_freq = base**(-pair_coords/d).` Evaluate the parentheses, then exponentiate; this is not multiplication by base.

```
pair_coords         = [0, 2]        shape (2,)
-pair_coords / d     = [0, -0.5]     shape (2,)
10000 ** [0, -0.5]  = [1, 0.01]     shape (2,)
```




Figure 92: Pair starting indices become speeds through negation, division and exponentiation

Read the figure: Indices sit outside the upper cells; x feature values sit inside. The three middle cards process indices only. Their columns retain pair0/pair1 throughout. The lower cards expand both calculations. Position multiplication at the bottom belongs to the next operation, not to inv_freq itself.

Python ∗∗ means exponentiation and acts elementwise on this tensor. Pair0 starts at coordinate 0, pair1 at coordinate 2:

$$\omega_0 = 10000^{-0/4} = 10000^0 = 1, \qquad \omega_1 = 10000^{-2/4} = 10000^{-1/2} = \frac{1}{\sqrt{10000}} = \frac{1}{100} = 0.01.$$

A negative exponent takes the reciprocal; exponent1/2 takes the square root. pair_coords already equals2i, so `-pair_coords/d` does not omit a factor of 2. inv_freq is a conventional variable name; here read it as radians turned per position step. Its relationship to a period is `period=2*pi/inv_freq`; do not take another reciprocal in this line.

This exponential schedule decreases successive speeds by a fixed ratio, providing different scales of positional variation. It is a design choice, not the only possible speed schedule.

This computation uses only base, d and coordinate indices, not x's feature values or positions. Changing the feature values while keeping width and base fixed leaves these speeds unchanged. Different positions reuse the speeds but multiply them by their own position values to obtain different angles.

Line5: `positions = positions.to(work_dtype).` Convert integer positions `[3]` to floating `[3.]` for angle arithmetic; shape stays `(1,)` and absolute position stays 3.

Lines 6–8: position times speed gives angles, then sine and cosine

Line6: `position_angles = positions[:,None] * inv_freq[None,:].` In indexing, `:` selects all entries and `None` inserts an axis of length1; it does not insert an empty data value.

```
positions                [3.]            shape (1,)
positions[:,None]        [[3.]]          shape (1,1)
inv_freq                 [1.,0.01]       shape (2,)
inv_freq[None,:]          [[1.,0.01]]     shape (1,2)
product                  [[3.,0.03]]     shape (1,2)
```

Here ∗ is elementwise multiplication with broadcasting, allowing position 3 to multiply both speeds. The complete angle rule is:

$$\theta_{p,i} = p\omega_i, \qquad [3 \times 1,\ 3 \times 0.01] = [3,\ 0.03].$$

Generally `(T,1)` times `(1,d/2)` produces `(T,d/2)`, one position per row and one pair per column. This is not matrix multiplication `@`. Conceptually broadcasting reuses entries along size1 axes to match sizes; it adds no tokens. Angles use radians:3 radians is about 171.9 degrees, not3 degrees.

Line7: `cos_angles = position_angles.cos().` Apply cosine to every angle; no hand calculation of trigonometric functions is required. The approximate values are `[[-0.98999250,0.99955003]]`, still shape `(1,2)`.

Line8: `sin_angles = position_angles.sin()`. Apply sine to the same angles, giving approximately `[[0.14112001,0.02999550]]`, also `(1,2)`. Together these tables supply the two coefficients needed by each rotation.

Lines 9–12: select coordinates and rotate each original pair

Line9: `even = x[...,0::2]. ...` keeps preceding B, H, T axes. On the last axis, `0::2` starts at 0 and takes every second entry to the end. Coordinates0,2 have values `[1,3]`; the complete slice shape is `(1,1,1,2)`.

Line10: `odd = x[...,1::2]`. Starting at 1 selects coordinates1,3 with values `[2,4]`, also `(1,1,1,2)`. Even/odd describes **index** parity. The values 1,3 inside even are not rotated together; match the columns:

	pair 0	pair 1
even value	1	3
odd value	2	4
angle	3	0.03

Line11: `rotated_even = even*cos_angles - odd*sin_angles`. A pair `[a,b]` rotates to a first coordinate $a\cos\theta - b\sin\theta$. Compute both pairs' first output coordinates together:

$$a'_0 = 1\cos 3 - 2\sin 3 \approx -1.27223251,$$
$$a'_1 = 3\cos 0.03 - 4\sin 0.03 \approx 2.87866810.$$

rotated_even displays `[-1.27223251,2.87866810]`, with full shape `(1,1,1,2)`. Right-alignment treats an angle table `(T,d/2)` as `(1,1,T,d/2)`, sharing that position's angles across B, H; the final T, d/2 axes must correspond.

Line12: `rotated_odd = even*sin_angles + odd*cos_angles`. The second output coordinate is $a\sin\theta + b\cos\theta$:

$$b'_0 = 1\sin 3 + 2\cos 3 \approx -1.83886499,$$
$$b'_1 = 3\sin 0.03 + 4\cos 0.03 \approx 4.08818664.$$

rotated_odd displays `[-1.83886499,4.08818664]`, with the same shape. Both lines read the original even/odd slices; line 12 does not read rotated_even. Neither line mixes pair0 with pair1. $*$ still means corresponding-element products, not a dot product.

Why these formulas? Regard `[a,b]` as a two-dimensional arrow. After rotation, the original horizontal contribution a becomes `[a*cos(theta),a*sin(theta)]`; the original vertical contribution b becomes `[-b*sin(theta),b*cos(theta)]`. Adding contributions gives these two equations. The rotation diagram in the later "Complete original fixture: $d = 2$" section illustrates this rule; the signs are not arbitrary choices made to match shapes.

Lines 13–14: restore coordinate order and the original dtype

First half of line 13: `torch.stack([rotated_even,rotated_odd],dim=-1).` stack inserts an axis; dim=-1 puts the new axis last. It places the matching first/second outputs together. Displaying only the values after omitting B, H, T:

```
[[-1.27223251, -1.83886499],   # pair 0: [new first, new second]
 [ 2.87866810,  4.08818664]]   # pair 1: [new first, new second]
```

Full shape changes from `(1,1,1,2)` to `(1,1,1,2,2)`; its final axes count pairs and coordinates per pair. It does not place the whole rotated_even row before rotated_odd; directly concatenating the slices changes coordinate order.

Second half of line 13: `.flatten(start_dim=-2).` -2 means the second-to-last axis, and the default end is the final axis. Merge only `(two pairs,two coordinates per pair)=(2,2)` into4. B, H, T remain unchanged; this does not flatten the entire tensor into one long list.

```
x_rope[0,0,0] = [-1.27223251,-1.83886499,2.87866810,4.08818664]
x_rope.shape  = (1,1,1,4)
```

Rotation changes values, not token order, row count, head count or width. The squared output length remains approximately30, matching$1^2+2^2+3^2+4^2$.

Line14: `return x_rope.to(x.dtype)` has a dtype-restoration issue. Line1 already rebound local x, so x.dtype now reads the working dtype instead of the original input dtype. Float16/bfloat16 input therefore returns float32, violating this lesson's original-dtype contract. Float32/float64 fixtures hide the issue. The rotation formula itself is not the cause.

To preserve the original dtype, make two small edits at four-space function indentation, retaining the intermediate rotation:

1. **Before** `x = x.to(work_dtype)`, save `original_dtype = x.dtype`. This records a type label without converting numbers.
2. Change the last line to `return x_rope.to(original_dtype)`, restoring the saved type after arithmetic.

The implementation plan below suggests storing the working tensor as work, which leaves the original x.dtype available at return time. This implementation reuses the name x and therefore needs a separate saved dtype. Both variable organizations work if the original type is retained. The earlier guidance did not explicitly explain rebinding's consequence; both languages now do.

Additional dtype checks observed float16→float32 and bfloat16→float32: the original driver does not cover that output-type requirement. This update changes notes and figures only, leaving exercise code for the learner to adjust.

Why study another position representation

Lesson 04.07 adds a position vector to input features: $h_p = e_p + P_p$. Here we inject position differently: first project Q and K, then rotate their features according to their positions. Attention comparisons can

consequently depend on content and relative displacement. RoPE means Rotary Position Embedding. Original RoFormer paper

Fix two content vectors $q = k$=[1,0]. Without a position transformation their dot product is always1, regardless of where they are placed. We want the comparison of these fixed contents to change with displacement: the immediately previous position and a position three steps earlier can receive different scores. RoPE writes position into the comparison through deterministic rotation angles.

A causal mask determines which keys are visible; position representations supply positional signals for comparing visible contents. Neither replaces the other. This fixed-vector example does not imply that a multilayer causal network cannot obtain ordering information through other paths.

What each of the four input axes counts

The exact function is:

```
def apply_rope(x: torch.Tensor, positions: torch.Tensor, base: float = 10000.) -> torch.Tensor:
```

Name	Type / shape	Meaning
x	Floating `(B,H,T,d)`	One projected, head-split Q or K tensor, not token IDs
B	Positive dimension	Samples
H	Positive dimension	Attention heads
T	Positive dimension	Number of position rows in this call
d	Positive even dimension	Width per head; usually $d = D/H$ after splitting
positions	Integer `(T,)`, same device as x	Absolute positions shared across B and H in this interface
base	Positive Python float, default10000	Determines pair frequencies; fixed, not learned here
Return	Same shape/dtype/device as x	Rotated features at each position, with gradients preserved

d denotes per-head width, not total hidden width D or vocabulary size V. $T = 2$ means two supplied rows: positions may be `[0,1]` or `[10,11]`. A tensor row index and its absolute position value are distinct.

Supported x dtypes are float16, bfloat16, float32 and float64; torch.long is recommended for positions. Positions are normally nonnegative token indices; the rotation formula is also defined for negative integers. This interface does not implement a different two-dimensional position table for every sample or add an input-validation assignment.

Two-dimensional rotation changes features, not token rows

Treat two adjacent feature coordinates a, b as an arrow in a plane. Counterclockwise rotation by θ gives:

$$a' = a\cos\theta - b\sin\theta, \qquad b' = a\sin\theta + b\cos\theta.$$

Equivalently, as matrix multiplication:

$$\underbrace{\begin{bmatrix} a' \\ b' \end{bmatrix}}_{(2,1)} = \underbrace{\begin{bmatrix} \cos\theta & -\sin\theta \\ \sin\theta & \cos\theta \end{bmatrix}}_{R(\theta),\ (2,2)} \underbrace{\begin{bmatrix} a \\ b \end{bmatrix}}_{(2,1)}.$$

Column vectors explain the geometry here; code evaluates the two coordinate equations without constructing a large rotation matrix or exchanging $B/H/T$ axes. Rows remain at their original positions. Floating feature coordinates within each row change.

Angles are in **radians**:1 radian is approximately57.3 degrees, and one full turn is 2π radians. `torch.sin` and `torch.cos` take radians. Our angle formula already specifies radians; do not add a factor of 2π.

Why is length preserved? Expand the squares, cancel the cross terms and use $\cos^2\theta + \sin^2\theta = 1$:

$$(a')^2 + (b')^2 = (a^2 + b^2)(\cos^2\theta + \sin^2\theta) = a^2 + b^2.$$

Preserving each pair's length preserves the full d-dimensional norm. Rotation does not normalize length to 1. Floating arithmetic preserves it within tolerance.

Complete original fixture: $d = 2$

The supplied driver uses $B = H = 1, T = 2, d = 2$:

```
x[0,0] = [[1,0],
          [1,0]]      full x shape (1,1,2,2)
positions = [0,1]     shape (2,)
```


There is one feature pair with angular frequency ω=1. Positions0 and 1 therefore have angles0 and 1:

$$R(0)\begin{bmatrix} 1 \\ 0 \end{bmatrix} = \begin{bmatrix} 1 \\ 0 \end{bmatrix}, \qquad R(1)\begin{bmatrix} 1 \\ 0 \end{bmatrix} = \begin{bmatrix} \cos 1 \\ \sin 1 \end{bmatrix} \approx \begin{bmatrix} 0.54030231 \\ 0.84147098 \end{bmatrix}.$$

The two returned rows are`[1,0]` and`[0.54030231,0.84147098]`; full shape remains`(1,1,2,2)`. Both squared lengths are 1. Equal content obtains different directions at different positions.

RoPE rotates feature coordinates: token rows and shape stay fixed

Original fixture: x shape=(1,1,2,2), both rows [1,0], positions=[0,1].



Position p=1 → angle 1 radian, about 57.3°

R(1) size = (2,2)			x pair size = (2,1)		rotated size = (2,1)
0.54030231	-0.84147098	×	1	=	0.54030231
0.84147098	0.54030231		0		0.84147098

$$a' = a\cos\theta - b\sin\theta$$

$$b' = a\sin\theta + b\cos\theta$$

Values change; B, H, T and d sizes do not.

Rotation preserves length; it does not turn every vector into a unit vector.

[1,0]: $1^2+0^2=1 \rightarrow \cos^2(1)+\sin^2(1)=1$

Figure 93: Original two-dimensional vectors, angle, components and preserved length

Read the figure: The left panel uses actual geometric coordinates: orange for position 0, teal for position 1. Dashed projections show cos1 and sin1. The matrix size is labeled separately from vector values on the right. Position1 does not mean one degree or moving row 0 into row 1.

Wider vectors: pairs, frequencies and position angles

For pair index $i = 0,\ldots,$ d/2-1, fix adjacent coordinate pairs`(0,1),(2,3),...`. Pair i uses:

$$\omega_i = \text{base}^{-2i/d}, \qquad \theta_{p,i} = p\omega_i.$$

ω_i is radians gained per position step. Position p comes from positions, not necessarily the local row index. Frequency depends on the pair, not token content or head number. For default base 10000 and $d = 4$:

Pair index i	Feature coordinates	Exponent -2i/d	ω_i	Angle at $p = 1$
0	(0,1)	0	1	1 radian
1	(2,3)	-1/2	0.01	0.01 radian

The second frequency is 0.01, not0.0001. `torch.arange(0,d,2)` produces each pair's first coordinate 2i, namely`[0,2]` for $d = 4$. The code exponent is therefore`-pair_coords/d`; do not multiply by 2 again.

Different frequencies change direction at different distance scales. The period is $\lambda_i = 2\pi/\omega_i$: approximately 6.283 and 628.319 positions for these pairs. With the default `base > 1`, later pairs turn more slowly. A pair does not identify arbitrary distant positions without ambiguity, and distance does not make every score decrease monotonically.

A numeric example showing both frequencies

This example is separate from the original $d = 2$ fixture. Let $B = H = 1, T = 3, d = 4$, each row initially`[1,0,2,0]`, and positions=`[0,1,2]`:

```
inv_freq = [1,0.01]                    shape (2,)
angles   = [[0,0],                     shape (3,2)
            [1,0.01],
            [2,0.02]]
output[0,0] = [[ 1,          0,          2,          0         ],
               [ 0.54030231, 0.84147098, 1.99990000, 0.01999967],
               [-0.41614684, 0.90929743, 1.99960001, 0.03999733]]
full output shape (1,1,3,4)
```

At position 1, the first pair`[1,0]` turns1 radian; the second`[2,0]` turns only 0.01 radians. Each row still has squared length$1^2+2^2 = 5$. The second pair retains length2; rotation is not RMSNorm.

Two pairs, two frequencies: angle columns differ from output columns

Separate example: x shape=(1,1,3,4), each row [1,0,2,0]; positions=[0,1,2], base=10000.

inv_freq = [1,0.01] (0,1): ω=1 (2,3): ω=0.01

	angles: shape (3,2)			output[0,0]: shape (3,4)			
	pair 0	pair 1		coord 0	coord 1	coord 2	coord 3
p=0	0	0	→	1.00000000	0.00000000	2.00000000	0.00000000
p=1	1	0.01		0.54030231	0.84147098	1.99990000	0.01999967
p=2	2	0.02		-0.41614684	0.90929743	1.99960001	0.03999733

Full output shape=(1,1,3,4); each row keeps squared norm 5. Values below show only p=1, rounded.

Rotated even/odd slices
shape = each: (1,1,3,2)
even′: [0.5403,1.9999]
odd′: [0.8415,0.0200]

→

stack(dim=-1)
shape = (1,1,3,2,2)
[[0.5403,0.8415],
[1.9999,0.0200]]

→

flatten(start_dim=-2)
shape = (1,1,3,4)
[0.5403,0.8415,
1.9999,0.0200]

Different angular speeds: 1 or 0.01 radian per position step, rather than one frequency per head.

Periods $\lambda = 2\pi/\omega$: about 6.283 and 628.319 positions. Angle $\theta = p\omega$ needs no extra factor of 2π.

Stack keeps pairs adjacent; direct cat groups every even coordinate before every odd coordinate.

Figure 94: Two-frequency angle/output tables and slice/reinterleave shape changes

Read the figure: The upper tables show only`b=0,h=0`; full shapes are labeled separately. Angle columns represent feature pairs, while output columns represent individual feature coordinates. The lower flow starts from the rotated even/odd slices, inserts the stack axis and flattens the last two axes. Shape metadata is outside value cells.

Why absolute rotations introduce relative position

Fix content vectors q, k at positions p, r. Each feature pair has angles $p\omega$ and $r\omega$. Their transformed dot product is:

$$\tilde{q}_p = R(p\omega)q, \qquad \tilde{k}_r = R(r\omega)k,$$


$$\tilde{q}_p^{\mathsf{T}}\tilde{k}_r = q^{\mathsf{T}}R(p\omega)^{\mathsf{T}}R(r\omega)k = q^{\mathsf{T}}R((r-p)\omega)k.$$

The first equality uses the transpose-of-a-product rule. The second uses the fact that a rotation's transpose reverses the rotation: undo $p\omega$, then turn $r\omega$, leaving(r-p)*ω. Contributions from multiple feature pairs add, retaining dependence on displacement. Original two-dimensional and general construction

The driver again uses $q = k$=[1,0], $d = 2$. At $p = 1$, $r = 3$ the dot is cos(3-1)=cos2≈-0.41614684. Adding5 to both gives positions 6,8; the angle difference and dot remain the same.

Absolute directions differ; equal displacement gives the same dot

Fixed content q=k=[1,0], d=2, ω=1. Teal is rotated q; orange is rotated k.



$$R(p\omega)^{\mathsf{T}} R(r\omega) = R((r-p)\omega)$$

Both dots are approximately −0.41614684. Negative scores are valid; mask and softmax still follow.

The identity fixes q, k and frequencies; it does not assert shift invariance for every whole model.

Figure 95: Different absolute angles, equal angle difference and equal dot product

Read the figure: Absolute arrow directions differ between the two circles, but their angular separation and dot product match. This holds for fixed original q, k and frequencies. It does not prove arbitrary whole models are invariant to absolute position shifts; other position mechanisms or changed contents can affect results.

Negative dot products are valid. The original attention pipeline still divides by sqrt(d), applies the causal mask and takes softmax over keys. RoPE itself produces neither probabilities nor a mask and does not mix values.

Where it belongs in the model, and how it differs from a position table

```
hidden (B,T,D)
  -> Q/K/V projections and head split
  -> Q,K: (B,H,T,d) -> apply_rope separately
  -> rotated Q @ rotated K.transpose(-2,-1) / sqrt(d)
  -> causal mask -> softmax over keys -> multiply unrotated V
```

This design rotates Q and K, not V; V may still have a different feature width. Q and K must use consistent pairing, d and frequencies. Lesson 05.04 later assembles these pieces; the completed04.09 decoder is not changed here.

Position method	Injection mechanism	Trainable position table
Learned absolute positions in04.07	Add P_p to input features	Yes
Fixed sine/cosine position vectors	Generate a vector and add it to features	No
RoPE here	Rotate projected Q/K feature pairs by position	No

Although both fixed methods use trigonometry, adding a vector differs from rotating one. RoPE angles can be computed beyond a finite table's row count; this does not guarantee useful behavior beyond training lengths. Attention cost, numerical precision, the training distribution and application configuration still constrain usable context.

Working precision, broadcasting and reinterleaving

Keep float64 inputs in float64 work; use float32 work for float16/bfloat16/float32 inputs. Convert positions before computing angles and x before multiply/add arithmetic; restore the saved original input dtype only at the end. Floating conversions preserve gradients; do not detach. Fixed base and integer positions are not learned parameters here.

This avoids first losing angle information in low precision, but does not ensure accuracy at arbitrary positions: sufficiently large consecutive integers are not all distinguishable in float32, and trigonometric rounding affects phase. Being able to evaluate a formula does not provide infinite context.

The full shape ledger is:

```
x/work                    (B,H,T,d)
pair_coords/inv_freq       (d/2,)
positions[:,None]          (T,1)
inv_freq[None,:]           (1,d/2)
angles/cos/sin             (T,d/2)
even/odd                   (B,H,T,d/2)
rotated_even/rotated_odd   (B,H,T,d/2)
stack(...,dim=-1)          (B,H,T,d/2,2)
flatten(start_dim=-2)      (B,H,T,d)
```

In indexing, `None` inserts a singleton axis, `...` retains all preceding axes, and `0::2` selects every second coordinate starting at 0. Broadcasting `(T,d/2)` conceptually adds two leading singleton axes, sharing angles across samples and heads. No hand-written loops are needed.

Stack adds an axis containing $[\text{even}_i, \text{odd}_i]$ for each pair. Flattening the last two axes restores `[even_0,odd_0,even_1,odd_1]`. Direct concatenation instead gives `[even_0,even_1,odd_0,odd_1]`: the shape can be correct while the convention is wrong. Adjacent-pair and half-split layouts can be related under consistent weight/convention changes, but cannot be swapped arbitrarily within one model.

Eight guided implementation steps

Open the shared exercise and edit only the learner region in `apply_rope`, preserving its driver. Compare each step with the shapes and values above:

1. **Read width and choose work dtype.** At four spaces read d from `x.shape[-1]`. Use a four-space `if x.dtype == torch.float64:` with an eight-space body selecting float64; a four-space `else:` has an eight-space body selecting float32. Save work_dtype. Remaining steps return to four spaces; no for-loop is needed.
2. **Prepare work and coordinates.** If rebinding x, first save original_dtype=x.dtype. Save work with `.to(work_dtype)`. Use `torch.arange(0,d,2,device=x.device,dtype=work_dtype)` for pair_coords. At $d = 4$ values are `[0,2]`, shape `(2,)`.
3. **Compute frequencies.** Python power ** expresses `base**(-pair_coords/d)`; save inv_freq. At $d = 4$ expect `[1,0.01]`.
4. **Build angles for all rows and pairs.** Convert positions to work dtype, use `[:,None]` for `(T,1)`, and multiply by `inv_freq[None,:]` of shape `(1,d/2)`. Save angles. The original fixture gives `[[0],[1]]`.
5. **Compute trigonometry and split coordinates.** `.cos()` and `.sin()` keep shape. Take even and odd with `work[...,0::2]` and `work[...,1::2]`, each `(B,H,T,d/2)`.
6. **Create both rotated tensors.** even *cos minus odd* sin gives rotated_even; even *sin plus odd* cos gives rotated_odd. Both equations use the original slices; do not overwrite even before computing odd. The original $p = 1$ fixture gives cos1 and sin1.
7. **Restore interleaving.** With even result first, use `torch.stack((...),dim=-1)` to obtain `(B,H,T,d/2,2)`. Then `.flatten(start_dim=-2)` merges only the last two axes and restores the original shape.

8. **Restore dtype and return.** Return one tensor in the original x.dtype. Preserve device, input values and gradients; no in-place writes, detach, item conversion or parameter update.

Run, original checks and preparation verification

```
python exercises/05_02_rotary_positions.py
```

Expected after implementation:

```
Lesson 05.02 checks passed.
```

The original driver checks exact $d = 2$ rotation, norm preservation and gradient connectivity; float64 norms with shape`(2,3,4,6)`; and dot products at positions(1,3)/(6,8). Since $d = 2$ has only one frequency, it cannot alone test frequency variation; the manuscript therefore adds the $d = 4$ example.

Additional checks can cover explicit block rotation matrices, non-default bases, varied dimensions, non-contiguous inputs, four dtypes, position offsets, norm/dot identities, input gradients against explicit matrices and finite differences.

Cache-position preview and classroom record

Later, cache each key after rotating it once at its original absolute position. If retained keys are at 10,11,12, the next query is at 13, not3 merely because three keys remain. Do not rotate an already rotated key again or reset only the new query to 0. This assumes fixed base and consistent frequencies; later lessons handle cache details.

05.03 SwiGLU, gated feed-forward networks

Method sources

The Swish-gated linear-unit variant, SwiGLU, is described by Shazeer, 2020; R08. Our separate gate/value projections and chosen hidden width are explicit implementation choices, not a universal optimal ratio.

From an ordinary FFN to two input branches

Lesson 04.08 projects to an intermediate width, applies GELU and projects back. SwiGLU adds a parallel projection: the same input produces content and input-dependent multipliers that regulate that content coordinate by coordinate, followed by the final projection. This is a learnable multiplicative interaction. GLU Variants Improve Transformer

Gating here means coordinate-wise modulation, not a Python if-statement or one scalar per token. Each input feature row gets its own row of multipliers. Attention exchanges information between positions; this function applies the same feature computation independently at every position, preserving

leading axes such as B, T.

This lesson implements one bias-free tensor function. Later composition handles RMSNorm, residuals and causal attention; the completed04.09 model is not rewritten here.

Function contract: three names denote weight matrices

```
def swiglu(x: torch.Tensor, gate: torch.Tensor, up: torch.Tensor, down: torch.Tensor) ->
↪  torch.Tensor:
```

Name	Type / shape	Meaning
x	Floating `(...,D)`	Input features, with last-axis width D
gate	Floating `(D,F)`	Weight matrix producing gate preactivations
up	Floating `(D,F)`	Separate weight matrix producing content
down	Floating `(F,D)`	Weight matrix mapping gated features back to D
Return	Floating `(...,D)`	Original leading axes and feature width, with gradients

D, F are positive dimensions; F is intermediate width and need not equal D or4D. Inputs share dtype/device on a backend supporting these operations. The driver and preparation use float32/float64. The caller supplies/registers weights; this function creates no parameters and preserves input/weight values.

Distinguish the two uses of F: F in shape notation denotes intermediate width. In code, `F.silu` uses the namespace imported by`from torch.nn import functional as F`. Do not overwrite that Python namespace with an integer `F`.

First learn SiLU: sigmoid times its input

For a real scalar a:

$$\sigma(a) = \frac{1}{1 + e^{-a}}, \qquad \mathrm{SiLU}(a) = a\sigma(a).$$

Sigma denotes sigmoid, mapping a scalar between0 and 1. It differs from softmax normalization over a candidate axis. SiLU then multiplies by a itself, changing the output range. Official SiLU documentation


Input a	sigmoid(a)	SiLU(a)=a*sigmoid(a)
-2	0.11920292	-0.23840584

Input a	sigmoid(a)	SiLU(a)=a*sigmoid(a)
-1	0.26894142	-0.26894142
0	0.5	0
1	0.73105858	0.73105858
2	0.88079708	1.76159416

SiLU may be negative or exceed1. Its gate values are not probabilities: they can suppress, amplify or reverse content signs. Smoothness does not imply monotonicity; the value decreases slightly from input-2 to-1. `F.silu` computes the complete a*sigmoid(a), not sigmoid alone.

Sigmoid differs from SiLU: SiLU also multiplies by its input

Gate values may be negative or exceed 1; the two plots have separately labeled vertical ranges.



a	-2	-1	0	1	2
sigmoid(a)	0.11920292	0.26894142	0.50000000	0.73105858	0.88079708
SiLU(a)	-0.23840584	-0.26894142	0.00000000	0.73105858	1.76159416

At a=0, sigmoid=0.5 but SiLU=0. Sigmoid alone defines a different function.

Figure 96: Different sigmoid/SiLU ranges, coordinate points and numeric table

Read the figure: Each curve has its own labeled vertical axis: sigmoid on the left, SiLU on the right. At a=2 the values are approximately0.880797 and 1.761594, respectively. The lower table retains negative values and the zero point; these are different functions.

Compose SwiGLU: each formula step maps to a variable

Compute two matrix projections, apply coordinate-wise gating and project back:

$$\text{SwiGLU}(x) = [\text{SiLU}(x\,\text{gate}) \odot (x\,\text{up})]\,\text{down}.$$

Juxtaposition with a matrix denotes matrix multiplication, written`@` in code. The circled dot denotes element-wise multiplication, written$*$.

Intermediate	Calculation	Shape
gate_pre	x projected through gate	`(...,F)`
content	The same original x projected through up	`(...,F)`
gate_values	Element-wise SiLU of gate_pre	`(...,F)`
gated	Element-wise gate_values times content	`(...,F)`
output	gated projected through down	`(...,D)`

For intermediate coordinate f in one row, first mix the D input features, then gate:

$$a_f = \sum_{j=0}^{D-1} x_j\,\text{gate}_{j,f}, \quad c_f = \sum_{j=0}^{D-1} x_j\,\text{up}_{j,f}, \quad z_f = \text{SiLU}(a_f)c_f, \quad y_k = \sum_{f=0}^{F-1} z_f\,\text{down}_{f,k}.$$

a, c, z are rows of gate_pre, content, gated. Index j denotes input coordinates, f intermediate coordinates and k output coordinates. The sums correspond to matrix projections; the middle product does not sum across coordinates. Both gate and up read the original x in parallel.

Complete original scalar fixture

All tensors have shape`(1,1)`: x=`[[1]]`, gate=`[[2]]`, up=`[[3]]`, down=`[[4]]`, with $D = F = 1$.

```
1. gate_pre   = 1*2 = 2
2. content    = 1*3 = 3
3. sigmoid(2) = 1/(1+exp(-2)) ≈ 0.88079708
   gate_values= 2*sigmoid(2) ≈ 1.76159416
4. gated      ≈ 1.76159416*3 ≈ 5.28478247
5. output     ≈ 5.28478247*4 ≈ 21.13912987
```

Matrix and element-wise multiplication look numerically identical in this special one-dimensional example. The next example uses unequal D, F to distinguish them. The driver's expected24/(1+exp(-2)) matches this trace.




Figure 97: Scalar input, parallel branches, SiLU, element-wise gate and final projection

Read the figure: The same x branches into gate and up. The upper path produces2, then applies SiLU; the lower path produces content3 directly. They merge by multiplication before down. Shapes and values are separate; all shapes happen to match in this fixture.

$D = 2, F = 3$: distinguish full matrices, sizes and values

This example is separate from the scalar fixture. Use one row with $B = T = 1$ and full x shape`(1,1,2)`; the displayed row is`[1,2]`:

```
gate = [[1,0, 1],     shape (2,3)
        [0,1,-1]]
up   = [[2, 1,0],     shape (2,3)
        [0,-1,2]]
down = [[1, 0],       shape (3,2)
        [0, 1],
        [1,-1]]
```

Follow this row through the computation:

```
gate_pre   = [1,2] @ gate = [1,2,-1]
content    = [1,2] @ up   = [2,-1,4]
gate_values= [0.73105858,1.76159416,-0.26894142]
gated      = [1.46211716,-1.76159416,-1.07576569]
output     = [0.38635147,-0.68582847]
```

Gate preactivation0 is $1 \times 1 + 2 \times 0 = 1$; preactivation2 is $1 \times 1 + 2 \times (-1) = -1$. Output0 is $1.46211716 + (-1.07576569) = 0.38635147$; output1 is $-1.76159416 - (-1.07576569) = -0.68582847$.

The four intermediates all have full shape`(1,1,3)`; output restores`(1,1,2)`. A negative third gate value times positive content4 produces a negative intermediate. These are not probabilities.

A complete unequal-width example: D=2 → F=3 → D=2

B=T=1; full x shape=(1,1,2), displayed row [1,2]. Weight sizes are outside the tables.

gate
size = (2, 3)

1	0	1
0	1	-1

up
size = (2, 3)

2	1	0
0	-1	2

down
size = (3, 2)

1	0
0	1
1	-1

Each intermediate row has three features, aligned by intermediate coordinate.

	f=0	f=1	f=2	shape
gate_pre = x @ gate	1.00000000	2.00000000	-1.00000000	(1,1,3)
content = x @ up	2.00000000	-1.00000000	4.00000000	(1,1,3)
gate_values = SiLU(gate_pre)	0.73105858	1.76159416	-0.26894142	(1,1,3)
gated = gate_values * content	1.46211716	-1.76159416	-1.07576569	(1,1,3)

gated @ down: (1,1,3) @ (3,2) → (1,1,2)

output		
	0.38635147	-0.68582847

The final matrix projection mixes three intermediate features into two outputs:

y0 = 1.46211716 + (-1.07576569) = 0.38635147

y1 = -1.76159416 - (-1.07576569) = -0.68582847

Figure 98: Unequal D/F, full weight tables, branch values and shape flow

Read the figure: Upper tables contain actual weight values, with size outside their cells. Middle rows align three intermediate coordinates. The last row uses down to restore two outputs. The3 in`(1, 1,3)` is a width, not a value inside a cell.

Adding a second row`[0,1]` gives approximately`[-0.53788284,-0.19317574]` for that row without changing the first row's output. Weights are shared, but forward computation does not mix positions.

Five guided implementation steps

Open the shared exercise and edit only the learner region in`swiglu`. Every statement uses four-space function indentation. No loop, branch, no_grad scope or new parameter is needed.

1. **Project the gate branch.** Apply matrix multiplication`@` between original x and supplied gate; save gate_pre. `(...,D)@(D,F)` gives`(...,F)`; the scalar fixture gives`[[2]]`.
2. **Project the content branch.** Separately multiply the same original x by up; save content. Same shape; scalar value`[[3]]`. Do not feed gate_pre into the content projection.
3. **Apply SiLU.** Pass gate_pre to the existing`F.silu`, saving gate_values. Shape stays fixed; scalar value approximately`[[1.76159416]]`. The namespace `F` is already imported.
4. **Multiply element-wise.** Use$*$ between gate_values and content, saving gated. Shape remains`(.. ,F)`; scalar value approximately`[[5.28478247]]`. Do not use matrix multiplication`@` here.
5. **Project back and return.** Multiply gated by down using`@`, then return that result. `(...,F)@(F, D)` gives`(...,D)`; scalar value approximately`[[21.13912987]]`. Return the tensor with gradients preserved.

The contracting dimensions determine matrix compatibility. Supplied weights already have`(D,F)` and`(F,D)` orientation; no transpose is needed. Implement the FFN alone without a residual, normalization, softmax, parameter update or`.item()` conversion.

Optional: learning through both branches and zero outputs

SiLU has derivative:

$$\text{SiLU}'(a) = \sigma(a) + a\sigma(a)(1 - \sigma(a)).$$

Multiplication sends gradients into both branches, then through their matrix projections to weights and x. Autograd handles this; manual backward is not assigned. With gate matrix zero, gate_pre=0 and SiLU(0)=0, so the output is zero. But SiLU'(0)=1/2, so gate weights may still receive nonzero gradients. Zero output does not establish that every weight stops learning.

Optional: parameter budgets and intermediate width

Without biases, the three matrices contain DF+DF+$FD = 3DF$ parameters. A conventional two-matrix FFN with the same intermediate width uses2DF; same-width SwiGLU therefore uses1.5 times as many weight parameters. Matching budgets suggests:

$$3DF_{\text{SwiGLU}} \approx 2DF_{\text{plain}}, \qquad F_{\text{SwiGLU}} \approx \frac{2}{3}F_{\text{plain}}.$$

For plain width 4D this is approximately8D/3, rounded to a suitable integer. It is a budget choice, not a width hard-coded in the function. The original paper adjusts intermediate width for its comparisons; replacing a component alone does not promise better quality. Original paper

Run, original checks and preparation status

```
python exercises/05_03_swiglu.py
```

Expected after implementation:

```
Lesson 05.03 checks passed.
```

The driver checks the scalar fixture, a positive input gradient and zero output for a zero gate matrix. Additional checks can cover independent coordinate sums, unequal D/F, varied leading axes, non-contiguous float64, analytic and finite-difference gradients for all four tensors, row independence, zero-gate gradients and preserved inputs.

05.04 Compose the modern baseline

Method sources

The combined model uses RMSNorm Zhang and Sennrich, 2019; R06, RoPE Su et al., 2021; R07 and SwiGLU Shazeer, 2020; R08. Input/output embedding weight tying is studied by Press and Wolf, 2017; R26. This combination and its parameter shapes are the book's own teaching architecture.

What this lesson builds and why the pieces belong together

You have learned each component; now make one trainable causal block from them. Attention lets a position read its visible prefix. RMSNorm prepares a branch's feature scale. SwiGLU transforms each position's features independently. Residual additions retain a direct route for the current representation while adding a learned change.

Compare the chosen04.09 design with this chosen baseline:

Component	Earlier decoder	Modern baseline here
Position mechanism	Add a learned position table	Rotate projected Q, K using RoPE
Branch normalization	LayerNorm	RMSNorm with learned feature gains
Position-wise FFN	Linear → GELU → Linear	Parallel gate/up → SiLU gating → down
Residual structure	Two pre-norm residual branches	Same two-branch structure

Component	Earlier decoder	Modern baseline here
Vocabulary head	Separate bias-free Linear	Separate or tied to token embeddings

These are modeling choices, not a claim that every newer architecture uses this combination or that replacing components automatically improves language quality. This exercise does not reproduce all details of any named production model.

Prerequisites: 05.01 RMSNorm, 05.02 RoPE, 05.03 SwiGLU, 04.05 causal attention, and 04.06 split/merge heads.

The exact learner interface and every registered weight

You implement only `ModernBlock.forward(self, x)` in `05_04_modern_model.py`. The constructor and `ModernLM` are supplied. The constructor arguments are `width`, `heads`, `hidden`, written D, H, F in formulas. F is a size symbol here; the imported Python namespace `F` still denotes torch.nn.functional.

Object	Type / shape	Meaning
x	Floating tensor `(B,T,D)`	Features entering this block; not token IDs
B, T	Positive axis lengths	Samples and positions supplied in this call
self.heads	Python integer H	Number of attention heads
$d = D/H$	Positive even integer	Q/K width within one head; D must be divisible by H
self.gain1, self.gain2	Separate nn.Parameter tensors `(D,)`	RMSNorm gains for the two branches
self.q, self.k, self.v, self.o	Separate nn.Parameter tensors `(D,D)`	Raw matrices in the row-vector x @ weight convention
self.gate, self.up	Separate nn.Parameter tensors `(D,F)`	SwiGLU gate/content projections
self.down	nn.Parameter tensor `(F,D)`	SwiGLU projection back to D
Return	Floating tensor `(B,T,D)`	Updated features, preserving input values and the gradient graph

F need not equal D or4D. Use compatible floating input/parameter dtype and device; the lesson verifies float32/float64. Low-precision training requires later dedicated validation. There is no padding mask, position offset or KV cache in this interface. T must be positive, and all supplied rows are treated as actual tokens. No optimizer step occurs in forward.

`nn.Parameter` registers a trainable tensor. The constructor's `setattr(self,name,value)` creates attributes such as self.q from string names; it is already supplied. self.q is a weight, while your local projected q is a feature tensor. Unlike an nn.Linear module, this raw tensor is used as `normalized @ self.q`, without transposing it. The final supplied nn.Linear vocabulary head has its own `(V,D)` storage convention and handles its transpose internally.

First understand the two pre-norm residual equations

For one feature row z and a learned gain g, default eps=1e-6:

$$\mathrm{RMS}(z;g)_j = \frac{z_j}{\sqrt{\frac{1}{D}\sum_{k=0}^{D-1} z_k^2 + \epsilon}}\, g_j.$$

Now name every block state:

$$Z = \mathrm{RMS}(X;g_1), \quad U = X + \mathrm{MHA}_{\mathrm{RoPE}}(Z), \quad R = \mathrm{RMS}(U;g_2), \quad Y = U + \mathrm{SwiGLU}(R).$$

X is the original input; U is the result after attention; Y is the result after the FFN. Normalize only the input to each branch. The first residual adds X, not Z. The second adds the updated U, not the old X and not normalized R. gain1/gain2 are independently learned even though both start as ones. The direct residual route has an identity derivative plus the branch derivative; this helps provide a gradient route, but does not guarantee stable training for arbitrary settings.




Figure 99: Shape map with separate original-X and updated-U residual bypasses

Read the figure: Orange carries the original X around the attention branch. Blue carries U around the FFN branch. Main-flow boxes show shapes, not matrix entries. T and D stay unchanged across both additions; only internal attention heads and FFN widths change layout.

Project, split, rotate and attend: track all four axes

Project Z independently through the three raw matrices. Each projection keeps `(B,T,D)`. Split each row's D features into H groups of d and move heads ahead of positions:

```
Z @ self.q / self.k / self.v     (B,T,D)
reshape(B,T,H,d)                 (B,T,H,d)
transpose(1,2)                  (B,H,T,d)
```

Here slash-separated names denote three separate projections, not division. reshape groups adjacent features; transpose swaps the head and position axes. Their sizes may coincidentally match, but their meanings differ. No token order is shuffled. Do not directly reshape `(B,T,D)` into `(B,H,T,d)` without the intermediate layout change.

Create `positions=torch.arange(T,device=x.device)`, shape `(T,)`, values 0 through T-1. For each Q/K pair i, RoPE uses the per-head width d:

$$\omega_i = 10000^{-2i/d}, \qquad \theta_{t,i} = t\omega_i.$$

Pass each of q, k to apply_rope with the same positions, keeping `(B,H,T,d)`. Do not rotate v in this design. Each head has d/2 frequency pairs; heads do not receive just one scalar frequency each unless $d = 2$. Do not add the old learned absolute position table as well in this baseline.

For each sample and head, query row t compares with key row r:

$$S_{t,r} = \frac{\tilde{q}_t \cdot \tilde{k}_r}{\sqrt{d}}, \qquad \bar{S}_{t,r} = \begin{cases} S_{t,r} & r \le t, \\ -\infty & r > t, \end{cases} \qquad A_{t,r} = \frac{\exp(\bar{S}_{t,r})}{\sum_j \exp(\bar{S}_{t,j})}, \qquad C_t = \sum_r A_{t,r} v_r.$$

The supplied causal_attention already handles scaling, masking, softmax and weighted values. It returns **two tensors**: context `(B,H,T,d)` and weights `(B,H,T,T)`. Unpack both; feed context into the merge. Do not apply another softmax, divide by sqrt(d) twice, or treat returned weights as features. RoPE adds a position-dependent comparison; the mask still prevents reading future tokens.

Merge heads, add attention, then run the second branch

Merge is the reverse layout change:

```
context                          (B,H,T,d)
transpose(1,2)                   (B,T,H,d)
reshape(B,T,D)                   (B,T,D)
merged @ self.o                  (B,T,D)
U = original X + branch          (B,T,D)
```

Use reshape after transpose, or contiguous().view after transpose if you choose view. A direct view on a non-contiguous tensor may fail; more importantly, merging the wrong axes can give plausible sizes with incorrect contents. self.o mixes the concatenated head coordinates without mixing positions.

Normalize U with gain2 and call swiglu with R, self.gate, self.up, self.down:

$$\text{SwiGLU}(R) = [\text{SiLU}(R\,\text{gate}) \odot (R\,\text{up})]\,\text{down}.$$

Both projections read the same R. `@` is matrix multiplication, $*$ is coordinate-wise multiplication. The branch expands `(B,T,D)` to two `(B,T,F)` tensors, gates them, then returns `(B,T,D)`. Add this returned change to U, yielding Y. swiglu itself adds no residual, so add exactly one here.

A complete numeric example with specified weights

The supplied original driver uses random $D = 8$, $H = 2$, $F = 16$. To make every entry readable, this **separate arithmetic example** uses $B = 1$, $T = 2$, $D = 4$, $H = 2$, $d = 2$, $F = 3$. Set gain1=gain2=ones, $q = k = v$=I4 and o=0.5*I4; positions=[0,1], base 10000, eps1e-6. I4 denotes the 4×4 identity matrix. Each head now has one pair with ω=1; 05.02's wider-vector example covers multiple frequencies.

Choose these FFN weights, all separate tensors:

```
gate  shape=(4,3)
[ 1.00000000, 0.00000000, 0.00000000 ]
[ 0.00000000, 1.00000000, 0.00000000 ]
[ 0.00000000, 0.00000000, 1.00000000 ]
[ 0.00000000, 0.00000000, 0.00000000 ]
```

```
up  shape=(4,3)
[ 1.00000000, 0.00000000, 0.00000000 ]
[ 0.00000000, 1.00000000, 0.00000000 ]
[ 0.00000000, 0.00000000, 1.00000000 ]
[ 1.00000000, 0.00000000, 0.00000000 ]
```

```
down  shape=(3,4)
[ 0.10000000, 0.00000000, 0.00000000, 0.10000000 ]
[ 0.00000000, 0.10000000, 0.00000000, -0.10000000 ]
[ 0.00000000, 0.00000000, 0.10000000, 0.10000000 ]
```

Input, first RMSNorm and head coordinates

```
X[0]  full shape=(1,2,4)
[ 1.00000000, 0.00000000, 0.00000000, 1.00000000 ]
[ 0.00000000, 1.00000000, 1.00000000, 0.00000000 ]
```

```
Z[0]  full shape=(1,2,4)
[ 1.41421215, 0.00000000, 0.00000000, 1.41421215 ]
```

```
[ 0.00000000, 1.41421215, 1.41421215, 0.00000000 ]
```

Each X row has mean square0.5. Divide by sqrt(0.500001), giving c≈1.41421215. Because projection weights are identity, the full Q, K, V equal Z before splitting. Head 0 receives coordinates0,1, while head 1 receives2,3. At position 0 there is no rotation; at position 1 each pair rotates by 1 radian. V remains unrotated:

```
rotated Q = rotated K, head 0  slice shape=(2,2)
[ 1.41421215, 0.00000000 ]
[ -1.19001849, 0.76410208 ]
```

```
rotated Q = rotated K, head 1  slice shape=(2,2)
[ 0.00000000, 1.41421215 ]
[ 0.76410208, 1.19001849 ]
```

For head 0 at position 1, `[0,c]` becomes `[-c*sin(1),c*cos(1)]`. Head 1's `[c,0]` becomes `[c*cos(1),c*sin(1)]`. These are different input pairs, explaining their different matching scores.

Scores, causal weights and each head's output

```
masked scaled scores, head 0  slice shape=(2,2)
[ 1.41421073, -inf ]
[ -1.19001730, 1.41421073 ]
```

```
weights, head 0  slice shape=(2,2)
[ 1.00000000, 0.00000000 ]
[ 0.06886681, 0.93113319 ]
```

```
context, head 0  slice shape=(2,2)
[ 1.41421215, 0.00000000 ]
[ 0.09739227, 1.31681987 ]
```

```
masked scaled scores, head 1  slice shape=(2,2)
[ 1.41421073, -inf ]
[ 1.19001730, 1.41421073 ]
```

```
weights, head 1  slice shape=(2,2)
[ 1.00000000, 0.00000000 ]
[ 0.44418523, 0.55581477 ]
```

```
context, head 1  slice shape=(2,2)
[ 0.00000000, 1.41421215 ]
[ 0.78604000, 0.62817215 ]
```

In the score and weight tables, rows are query positions and columns are key positions. In each context table, rows are query positions and columns are that head's value-feature coordinates. The first row can see only key 0, so its weights are exactly[1,0]. For head 0 row 1, scores are about[-

1.19001730,1.41421073], and the first weight is 1/(1+exp(2.60422804))≈0.06886681. Its output is 0.06886681*[c,0]+0.93113319*[0, c]. Head 1 uses a different score pair and therefore a different weighted sum.

One numeric example: compute each head, then merge in original order

B=1, T=2, D=4, H=2, d=2; before rotation Q=K=V=Z, positions [0,1], eps=0.000001.

X[0] : (2,4)

1.000000	0.000000	0.000000	1.000000
0.000000	1.000000	1.000000	0.000000

Z[0] = RMSNorm(X)[0] : (2,4)

1.414212	0.000000	0.000000	1.414212
0.000000	1.414212	1.414212	0.000000

head 0

rotated Q = K
slice shape = (2,2)

1.414212	0.000000
-1.190018	0.764102

unrotated V
slice shape = (2,2)

1.414212	0.000000
0.000000	1.414212

masked scaled scores
slice shape = (2,2)

1.414211	−∞
-1.190017	1.414211

softmax → weights
slice shape = (2,2)

1.000000	0.000000
0.068867	0.931133

context = weights @ V
slice shape = (2,2)

1.414212	0.000000
0.097392	1.316820

head 1

rotated Q = K
slice shape = (2,2)

0.000000	1.414212
0.764102	1.190018

unrotated V
slice shape = (2,2)

0.000000	1.414212
1.414212	0.000000

masked scaled scores
slice shape = (2,2)

1.414211	−∞
1.190017	1.414211

softmax → weights
slice shape = (2,2)

1.000000	0.000000
0.444185	0.555815

context = weights @ V
slice shape = (2,2)

0.000000	1.414212
0.786040	0.628172

merged[0]: each row contains head 0 coordinates, then head 1 coordinates.

slice shape (2,4)

1.414212	0.000000	0.000000	1.414212
0.097392	1.316820	0.786040	0.628172

Scores/weights: query rows, key columns. Context: query rows, feature columns. −∞ gives zero weight.

Displayed entries are slices; full Q/K/V and context have shape (1,2,2,2).

Figure 100: Rotated Q/K, unchanged V, causal scores, weights, per-head outputs and merged entries

Read the figure: All small head tables display `(T,d)` or `(T,T)` slices, explicitly labeled. The full tensors still include B, H. Bottom rows concatenate head 0's two outputs followed by head 1's two outputs. Here $H = T = d = 2$ numerically; the axis meanings remain distinct.

Merge, first residual and the second RMSNorm

```
merged[0]  full shape=(1,2,4)
[ 1.41421215, 0.00000000, 0.00000000, 1.41421215 ]
[ 0.09739227, 1.31681987, 0.78604000, 0.62817215 ]
```

```
U[0]  full shape=(1,2,4)
[ 1.70710607, 0.00000000, 0.00000000, 1.70710607 ]
[ 0.04869614, 1.65840994, 1.39302000, 0.31408607 ]
```

```
R[0]  full shape=(1,2,4)
[ 1.41421308, 0.00000000, 0.00000000, 1.41421308 ]
[ 0.04449106, 1.51520054, 1.27272793, 0.28696366 ]
```

For example, U at position 1 is `[0,1,1,0] + 0.5*[0.09739227,1.31681987,0.78604000,0.62817215]`. R is a new normalization of this U, not a reused Z. Keep U available for the next addition.

Parallel projections, gating and the final residual

```
gate_pre[0]  full shape=(1,2,3)
[ 1.41421308, 0.00000000, 0.00000000 ]
[ 0.04449106, 1.51520054, 1.27272793 ]
```

```
content[0]  full shape=(1,2,3)
[ 2.82842615, 0.00000000, 0.00000000 ]
[ 0.33145472, 1.51520054, 1.27272793 ]
```

```
gate_values[0]  full shape=(1,2,3)
[ 1.13763487, 0.00000000, 0.00000000 ]
[ 0.02274031, 1.24220784, 0.99426698 ]
```

```
gated[0]  full shape=(1,2,3)
[ 3.21771622, 0.00000000, 0.00000000 ]
[ 0.00753738, 1.88219398, 1.26543137 ]
```

```
ffn_branch[0]  full shape=(1,2,4)
[ 0.32177162, 0.00000000, 0.00000000, 0.32177162 ]
[ 0.00075374, 0.18821940, 0.12654314, -0.06092252 ]
```

```
Y[0]  full shape=(1,2,4)
[ 2.02887770, 0.00000000, 0.00000000, 2.02887770 ]
```

```
[ 0.04944988, 1.84662934, 1.51956314, 0.25316355 ]
```

At position 0, gate_pre's first coordinate is c2≈1.41421308 and content's first coordinate is 2*c2. Thus gated is `[SiLU(c2)*(2*c2),0,0]≈[3.21771622,0,0]`. Multiplying by down gives `[0.32177162,0,0,0.32177162]`. Adding U gives the displayed Y. At position 1, all three intermediate coordinates contribute; down's negative entry makes the fourth branch coordinate negative. Negative feature updates are valid.

Finish both residuals: D=4 → F=3 → D=4

Same fixture and weights, eps=0.000001. Entries show sample [0], two rows, rounded to six decimals.

U = X + merged @ o full shape = (1,2,4)	1.707106	0.000000	0.000000	1.707106
	0.048696	1.658410	1.393020	0.314086
R = RMSNorm(U, gain2) full shape = (1,2,4)	1.414213	0.000000	0.000000	1.414213
	0.044491	1.515201	1.272728	0.286964
gate_pre = R @ gate full shape = (1,2,3)	1.414213	0.000000	0.000000	
	0.044491	1.515201	1.272728	
content = R @ up full shape = (1,2,3)	2.828426	0.000000	0.000000	
	0.331455	1.515201	1.272728	
gate_values = SiLU(gate_pre) full shape = (1,2,3)	1.137635	0.000000	0.000000	
	0.022740	1.242208	0.994267	
gated = gate_values * content full shape = (1,2,3)	3.217716	0.000000	0.000000	
	0.007537	1.882194	1.265431	
ffn_branch = gated @ down full shape = (1,2,4)	0.321772	0.000000	0.000000	0.321772
	0.000754	0.188219	0.126543	-0.060923
Y = U + ffn_branch full shape = (1,2,4)	2.028878	0.000000	0.000000	2.028878
	0.049450	1.846629	1.519563	0.253164

Each table: position 0 then position 1. The final residual adds U, not X or normalized R.

Figure 101: All second-branch intermediate entries, their full shapes and the updated-U residual

Read the figure: Each table contains the same two token rows, never dimension labels inside the value cells. Full shape is printed separately. $F = 3$ differs from $D = 4$, so the expansion/projection is visible. The final addition uses U. Figures round to six decimals; text rounds to eight; calculations retain full precision and eps throughout.

From one block to ModernLM and raw vocabulary logits

Supplied ModernLM embeds integer input_ids `(B,T)`, applies each registered block sequentially, then final rmsnorm with self.gain and an nn.Linear head. Return shape is `(B,T,V)`, with raw next-token logits for every supplied row. Its constructor arguments are vocab_size, width, heads, hidden, layers, tied=False. Require layers>=1 for the intended stacked decoder; IDs are torch.long in[0, V), with matching model device and positive B, T. This exercise adds no validation task.

`nn.ModuleList` registers blocks, but the supplied for-loop actually runs them. Each block owns different parameters; depth is not a loop over token positions. No extra residual surrounds an entire block call. The final self.gain is separate from each block's gain1/gain2.

With `tied=True`, the supplied assignment `self.head.weight=self.embedding.weight` shares **the same Parameter object**, not merely equal initial numbers. E has shape `(V,D)`: input IDs select E rows, while the output head computes final_normalized @ E.T. Both uses contribute gradients to the shared E. The nn.Linear call handles the transpose; do not manually transpose its registered weight or create a second embedding.

Continue the same numeric example with one block, $V = 3$, final gain ones and tied weights:

```
E  shape=(3,4)
[ 1.00000000, 0.00000000, 0.00000000, 1.00000000 ]
[ 0.00000000, 1.00000000, 1.00000000, 0.00000000 ]
[ 1.00000000, -1.00000000, 0.00000000, 0.00000000 ]
```

```
final_normalized[0]  full shape=(1,2,4)
[ 1.41421322, 0.00000000, 0.00000000, 1.41421322 ]
[ 0.04111677, 1.53544241, 1.26349216, 0.21050139 ]
```

```
logits[0]  full shape=(1,2,3)
[ 2.82842644, 0.00000000, 1.41421322 ]
[ 0.25161817, 2.79893456, -1.49432563 ]
```

`input_ids=[[0,1]]` selects E's first two rows, reproducing X above. The first logit at position 1 is $0.04111677 + 0.21050139 \approx 0.25161817$. The second is $1.53544241 + 1.26349216 \approx 2.79893456$. The third is $0.04111677 - 1.53544241 \approx -1.49432563$. These three columns are candidate vocabulary scores, not three new input positions. Do not apply softmax before the later F.cross_entropy training call.

From input IDs to candidate scores: reuse the same E at both ends

This fixture: V=3, D=4, one block, tied=True. input_ids=[[0,1]] retrieves X from the prior figures.

E = embedding.weight = head.weight : (3,4)

ID 0	1	0	0	1
ID 1	0	1	1	0
ID 2	1	-1	0	0

Input selects rows by ID; output dots final features with candidate rows. Both use one Parameter.

N = final RMSNorm(Y)
shape = (1,2,4)

1.414213	0.000000	0.000000	1.414213
0.041117	1.535442	1.263492	0.210501

@

E.T
shape = (4,3)

1	0	1
0	1	-1
0	1	0
1	0	0

=

logits = N @ E.T
shape = (1,2,3)

2.828426	0.000000	1.414213
0.251618	2.798935	-1.494326

Tying aliases one parameter, not a one-time value copy. Output remains logits; no softmax here.

Fixture parameter counts: block 108, final gain 4, E 12; tied total 124, untied total 136.

V=3 is a toy choice. A real tokenizer determines V; the block neither tokenizes nor samples.

Figure 102: Shared embedding/head parameter, final normalization, matrix dimensions and complete logits

Read the figure: The upper E table is one parameter used in two places. The lower product displays sample0's normalized rows times E.T, keeping $T = 2$ and changing $D = 4$ into $V = 3$. There is no learned position table here. Real tokenizer outputs can enter through IDs after matching V; the block does not train BPE, decode bytes or sample tokens.

Parameter budget: what weight tying saves

A block has four $D{\times}D$ attention matrices, three DF-sized FFN matrices, and two D-sized gains:

$$P_{\text{block}} = 4D^2 + 3DF + 2D, \qquad P_{\text{tied}} = LP_{\text{block}} + D + VD, \qquad P_{\text{untied}} = LP_{\text{block}} + D + 2VD.$$

No bias or position-table parameters are present in this supplied design. In our numeric example:108 per block,4 final gain,12 embedding, totaling124 tied or136 untied. In the supplied ModernLM(7,8,2,16,2, tied=True) driver:656 per block,8 final gain,56 embedding, totaling1376 tied versus1432 untied. Tying saves VD parameters and constrains input/output representations; it does not guarantee lower loss. The constructor already implements this choice.

Eight guided steps for the learner region

Open the real exercise and edit only ModernBlock.forward between its markers. Ordinary method statements use **eight spaces**; it is inside a class. No new for-loop or parameter initialization is required. Keep x as the original residual state. The following names Z/U/R are suggested local names, not extra attributes.

1. **Read sizes and normalize.** Unpack `B,T,D=x.shape`; read H from self.heads and d via integer division `D//H`. Call rmsnorm with x, self.gain1 and save Z, `(B,T,D)`. Fixture row 0 becomes[c,0,0, c]. `//` gives an integer width suitable for reshape.
2. **Project and split three times.** Use `@ self.q`, `@ self.k`, `@ self.v` on the same Z. For each result use `.reshape(B,T,H,d).transpose(1,2)`, saving local q, k, v. Fixture full shape `(1, 2,2,2)`; head 0 row 0 is[c,0], head 1 row 0[0, c]. Do not use nn.Linear call syntax on a raw Parameter.
3. **Make positions and rotate only q, k.** Use torch.arange(T, device=x.device), obtaining[0,1]. Pass q and positions to apply_rope, then independently k and positions. Reassign the local projected tensors, preserving v. Keep the default base consistent.
4. **Call the supplied attention and unpack.** Assign its two outputs to context and weights, or use `_` for unused weights. `_` is an ordinary name signaling deliberate non-use. Context is `(B,H,T,d)` ; weights is `(B,H,T,T)`. No additional mask/softmax/scale is needed.
5. **Merge and project.** Transpose context's axes1,2, then reshape to `(B,T,D)`. Multiply that result by self.o using `@`. In the fixture the branch is 0.5 times the displayed merged values.
6. **Make the first residual state.** Add original x to the attention branch; save U, still `(B,T,D)`. Fixture row 0 is`[1.70710607,0,0,1.70710607]`. Do not add normalized Z instead.

7. **Make the second branch.** Call rmsnorm on U, self.gain2 and save R. Call swiglu with R, self.gate, self.up, self.down. Its return is an FFN change `(B,T,D)`, not the final residual state. Fixture row 0 change is `[0.32177162,0,0,0.32177162]`.
8. **Return the second residual.** At eight spaces return U plus the FFN change. Fixture row 0 is `[2.02887770,0,0,2.02887770]`. Preserve all T rows and the gradient graph. Do not detach, overwrite input values, update weights, return attention weights or produce token IDs.

Hints guide your own implementation; the lesson does not insert a completed forward method. Leave the supplied ModernLM and check driver intact.

Run command, checks and preparation evidence

```
python exercises/05_04_modern_model.py
```

After implementation and functional prerequisites, expect:

```
Lesson 05.04 checks passed.
```

An unfinished dependency raises learner TODO; it is not evidence of an environment problem. The original driver checks block shape at $B = 2, T = 3, D = 8$, future isolation after perturbing the final input row, graph connectivity for all registered block parameters, identity when attention/FFN matrices are zero, tied parameter identity, and full-model logit shape. Zero branch weights leave both residual routes intact, so output equals x even though RMSNorm gains need not be zero.

It checks the original driver using actual prerequisites in float32, the complete independent NumPy trace in float64, unequal axes/widths, non-contiguous inputs, zero branches, causal isolation/context sensitivity, input/parameter preservation, gradients and parameter-count/tied-object identities. No corpus training or quality result is claimed.

Why the causal mask still works after multiple blocks

At a row t, RMSNorm, feature projections, RoPE, SwiGLU and residual additions do not read another row. Causal attention reads only rows at r<=t. If each input row r already depends only on its own prefix, row t can still depend only on its prefix after this block. Repeating blocks preserves that property. Changed feature values or feature widths do not move the token axis.

This forward always recomputes a complete supplied sequence and numbers it0..T-1. It does not implement offsets or cached decoding. Later caches must retain absolute positions; do not restart only a newly supplied cached token at 0. Having no finite learned position table does not imply unlimited usable context: quadratic attention work/storage, precision and training lengths still matter.

Immediately after causal_attention, context is (B, H, T, dv), where this implementation uses $d_v = D$//self.heads for $Q/K/V$ alike. After transpose(1,2) it is (B, T, H, dv), then reshape yields (B, T, D). This order places every head's result for one position together before the feature coordinates are merged.

05.05 AdamW, initialization and weight decay

Method sources

Adam's moment estimates and bias correction come from Kingma and Ba, 2015; R09; decoupled weight decay comes from Loshchilov and Hutter, 2019; R10. For fan-based initialization motivation, see Glorot and Bengio, 2010; R38. Our constructor's inverse-square-root fan scaling is not a claim to implement the exact Glorot initialization prescription.

What you implement, and where it belongs in training

The model's forward pass produces predictions. A loss measures error, and backward computes gradients. An optimizer then decides how to use those gradients to change parameters. Lesson 04.10 called PyTorch Adam; here you implement one simplified, dense AdamW update yourself. Review the earlier Adam explanation if moments or powers are unfamiliar.

There are two different timescales in the title:

Operation	When	Purpose
Initialize model weights	Once when building a new run	Choose starting scales and break unwanted symmetry
Update with AdamW	After each chosen gradient computation	Change existing parameters and retain optimizer memories

This assignment implements only the second row. Initialization is explained later using the actual 05.04 constructor; do not reinitialize the model every step or edit its constructor for this exercise. The supplied gradient already exists: this function neither calls backward nor constructs a model, computes a loss, clips gradients or selects a learning-rate schedule.

Function contract: inputs, persistent state and return value

```
def adamw_update(parameter: torch.Tensor, gradient: torch.Tensor,
                 first: torch.Tensor, second: torch.Tensor, step: int,
                 learning_rate: float, beta1: float, beta2: float,
                 eps: float, decay: float) -> None:
```

Parameter	Type / meaning	Changed by this call?
parameter	Dense floating tensor of trainable values, any nonempty shape	Yes, in place
gradient	Same-shape/dtype/device tensor of the supplied loss gradient	No

Parameter	Type / meaning	Changed by this call?
first	Same-shape/dtype/device buffer for the previous signed-gradient average	Yes, in place
second	Same-shape/dtype/device buffer for the previous squared-gradient average	Yes, in place
step	Positive Python integer: this parameter's update count, starting at 1	No
learning_rate	Nonnegative Python scalar, written η	No
beta1, beta2	Fixed averaging coefficients in [0,1)	No
eps	Positive scalar added after the square root	No
decay	Nonnegative weight-decay coefficient, written λ	No
Return	None; the caller observes mutated tensors	No new parameter returned

Use finite, real float32/float64 tensors with separate, non-overlapping storage for parameter, gradient, first and second. Buffers are ordinary non-differentiable optimizer state; second is nonnegative. At the start of a new run, initialize first and second to zeros. At later calls, supply the preceding buffers and the correct update count. A matrix parameter has a matrix of moments, one value per coordinate; do not reduce over rows, tokens or all weights.

step is not the token count T or epoch number. Gradient accumulation adds gradients from several smaller batches, called microbatches, before one optimizer update. Increment step when this parameter is actually updated, not for every microbatch. This tensor-only interface has no gradient=None skip logic. An explicitly zero gradient still participates in the update.

Name the symbols before reading the formulas

Formula	Actual argument / interpretation
θ_{t-1}, θ_t	parameter before / after the call
g_t	gradient supplied for update t
m_{t-1}, m_t	first before / after updating its buffer
v_{t-1}, v_t	second before / after updating its buffer
β_1, β_2	beta1, beta2: fractions of the previous memories retained
t	step: 1,2,3,… for this parameter
η, λ, ϵ	learning_rate, decay, eps
$\widehat{m}_t$, $\hat{v}_t$	Temporarily bias-corrected values, not replacement buffer states

In β_1^t, the subscript 1 selects beta1 and the superscript t means exponentiation. At $t = 2$, beta1=0.9 gives $0.9^2 = 0.81$; beta2=0.99 gives $0.99^2 = 0.9801$. In Python write `beta1 ** step`, not `beta1 * step` and not `beta1 ^ step`; ^ is not Python exponentiation. The β values stay fixed while their powers change with t.

Two gradient memories: direction and squared scale

Compute a weighted average of signed gradients and a separate weighted average of their elementwise squares:

$$m_t = \beta_1 m_{t-1} + (1 - \beta_1) g_t, \qquad v_t = \beta_2 v_{t-1} + (1 - \beta_2) g_t^2.$$

For beta1=0.9, first keeps 90% of its old value and adds 10% of the current gradient. It can be positive or negative; it smooths direction rather than obeying only the newest sign. With beta2=0.99, second keeps 99% of its old value and adds 1% of the squared gradient. Squaring makes negative gradients contribute positively to scale.

v is a raw second-moment estimate, not a second derivative or an exact variance: variance would subtract the square of the mean. Dividing by $\sqrt{\widehat{v}_t} + \epsilon$ scales each coordinate using its own gradient history. It is not a probability normalization or a sum-to-one operation, and does not guarantee identical parameter displacements or monotonically decreasing loss.

Why startup correction divides by 1 minus a power

Both buffers start at zero. For a constant gradient g, unrolling the first recurrence gives a geometric sum:

$$m_t = (1 - \beta_1)(1 + \beta_1 + \cdots + \beta_1^{t-1}) g = (1 - \beta_1^t) g.$$

At $t = 1$ with beta1=0.9, the uncorrected memory is only 0.1g. The missing weight came from the zero initial state. Divide by the observed-gradient weight to remove this startup attenuation; apply the same reasoning to squares:

$$\widehat{m}_t = \frac{m_t}{1 - \beta_1^t}, \qquad \hat{v}_t = \frac{v_t}{1 - \beta_2^t}.$$

step	1-beta1**step, beta1=0.9	1-beta2**step, beta2=0.99
1	0.1	0.01
2	0.19	0.0199
3	0.271	0.029701

Correction also normalizes the accumulated weights for varying gradients; it does not predict the true current gradient or guarantee an unbiased estimate of a changing underlying mean. Keep the **un-**

corrected m_t, v_t in first, second for the next recurrence. Compute $\widehat{m}_t$, $\widehat{v}_t$ in new temporary tensors. Dividing first or second in place by its correction denominator corrupts the next update. step=0 would give zero denominators, so valid counts start at 1.

AdamW: shrink the old parameter separately, then subtract an adaptive change

Separate the two contributions:

$$\theta_{\text{decayed}} = (1 - \eta\lambda)\theta_{t-1}, \qquad \Delta_t = \eta \frac{\widehat{m}_t}{\sqrt{\widehat{v}_t} + \epsilon}, \qquad \theta_t = \theta_{\text{decayed}} - \Delta_t.$$

The adaptive term follows gradient memories. Weight decay acts on the old parameter itself and does not enter those memories. This is the decoupled rule used here, with eps outside the square root. Official AdamW algorithm

For η=0.1, λ=0.1, multiply old parameters by 0.99: 1 becomes 0.99 and -2 becomes-1.98. Both move toward zero before the adaptive contribution. This shrink interpretation assumes a usual factor between0 and 1; arbitrary nonnegative hyperparameters do not guarantee shrinkage. Decoupled means separate from gradient moments, not independent of learning rate: $\eta\lambda$ still determines this step's decay.

The minus sign applies to the signed adaptive term. Subtracting a negative term increases a parameter. Momentum may disagree with the newest gradient sign, as the two-step trace below demonstrates. Performing the adaptive subtraction first and multiplying the entire result by 0.99 afterward would also decay the new adaptive change; that is a different equation.

Full scalar calculation before writing code

Take coordinate 0 of the original driver, represented as a one-entry tensor of shape(1,): old $p = 1$, $g = 2$, first=second=0, step=1, learning_rate=0.1, beta1=0.9, beta2=0.99, eps=1e-8, decay=0.1.

```
1. first       = 0.9*0 + 0.1*2       = 0.2
2. second      = 0.99*0 + 0.01*(2*2) = 0.04
3. first_hat   = 0.2/(1-0.9**1)      = 2
4. second_hat  = 0.04/(1-0.99**1)     = 4
5. denominator = sqrt(4) + 1e-8      = 2.00000001
6. adaptive    = 0.1*2/2.00000001    = 0.0999999995
7. decayed     = (1-0.1*0.1)*1       = 0.99
8. new p       = 0.99-adaptive       = 0.8900000005
```

Persist first=0.2, second=0.04 and the new p. The supplied gradient stays 2; the function returns None. Numbers are shown rounded, while calculations retain eps. Plain SGD without decay would give $1 - 0.1 \times 2 = 0.8$; AdamW's history-based scaling defines a different update.




Figure 103: Separate gradient-memory and parameter-decay paths, bias corrections and scalar result

Read the figure: The upper input is a gradient and feeds both memory buffers. The lower input is the old parameter and feeds decay. Only at the final subtraction do the paths meet. Shape labels are outside numeric entries; every box in this slice describes one parameter coordinate. Persistent buffers and temporary corrected values have different roles.

Both coordinates and both steps of the original driver

Every vector has shape(2,), representing two parameter coordinates, not two token positions. Start p=[1,-2], first=[0,0], second=[0,0]. Supply g1=[2,-1], then g2=[-0.5,3], retaining all three updated tensors between calls. Hyperparameters stay unchanged.

Step 1: update both coordinates independently

Quantity	Coordinate 0	Coordinate 1
Parameter before	1.00000000000	-2.00000000000
Current gradient	2.00000000000	-1.00000000000
First moment buffer	0.20000000000	-0.10000000000
Second moment buffer	0.04000000000	0.01000000000
Temporary first_hat	2.00000000000	-1.00000000000
Temporary second_hat	4.00000000000	1.00000000000
Decayed parameter	0.99000000000	-1.98000000000
Adaptive change	0.09999999950	-0.09999999900
Parameter after	0.89000000050	-1.88000000100

Coordinate1's adaptive term is negative, so subtracting it raises its parameter from the decayed -1.98 to about-1.88. Both moment coordinates persist. No averaging across the two coordinates occurs.

Step 2: reuse the first step's actual moments

Now $1-0.9^2=0.19$ and $1-0.99^2=0.0199$. For coordinate 0, `first=0.9*0.2+0.1*(-0.5)=0.13` and `second=0.99*0.04+0.01*0.25=0.0421`. For coordinate 1, `first=0.9*(-0.1)+0.1*3=0.21` and `second=0.99*0.01+0.01*9=0.0999`.

Quantity	Coordinate 0	Coordinate 1
Parameter before	0.89000000050	-1.88000000100
Current gradient	-0.50000000000	3.00000000000
First moment buffer	0.13000000000	0.21000000000
Second moment buffer	0.04210000000	0.09990000000
Temporary first_hat	0.68421052632	1.10526315789
Temporary second_hat	2.11557788945	5.02010050251

Quantity	Coordinate 0	Coordinate 1
Decayed parameter	0.88110000049	-1.86120000099
Adaptive change	0.04704085846	0.04932981491
Parameter after	0.83405914204	-1.91052981590

Although coordinate 0's current gradient is-0.5, its first_hat remains positive. AdamW still subtracts a positive adaptive change this step. This is the effect of direction memory, not a sign error. The trace would differ if buffers were reset or corrected buffers were saved as persistent state.

Two updates: carry both moment buffers forward with the parameter

All original-fixture tensors have shape=(2,). Table columns are parameter coordinates, not tokens.

step = 1

$1-\beta_1^{\text{step}} = 0.10; \quad 1-\beta_2^{\text{step}} = 0.0100$

	coord 0	coord 1
p before	1.00000000	-2.00000000
gradient	2.00000000	-1.00000000
first m	0.20000000	-0.10000000
second v	0.04000000	0.01000000
$\widehat{m}$	2.00000000	-1.00000000
$\hat{v}$	4.00000000	1.00000000
decayed p	0.99000000	-1.98000000
adaptive change	0.10000000	-0.10000000
p after	0.89000000	-1.88000000

step = 2

$1-\beta_1^{\text{step}} = 0.19; \quad 1-\beta_2^{\text{step}} = 0.0199$

	coord 0	coord 1
p before	0.89000000	-1.88000000
gradient	-0.50000000	3.00000000
first m	0.13000000	0.21000000
second v	0.04210000	0.09990000
$\widehat{m}$	0.68421053	1.10526316
$\hat{v}$	2.11557789	5.02010050
decayed p	0.88110000	-1.86120000
adaptive change	0.04704086	0.04932981
p after	0.83405914	-1.91052982

Step 2, coordinate 0: g=−0.5 but m=0.13 remains positive, so the adaptive term is still subtracted.

Compute coordinates independently; do not average tokens. Step starts at 1; do not reset moments each update.

Figure 104: Every persistent and temporary vector across both updates, with coordinate labels separate from values

Read the figure: Left is step 1, right step 2. Each table has two coordinate columns and the same row meanings. Green rows identify stored states; temporary corrected states remain separate. The original driver compares both parameter trajectories and final memories with PyTorch AdamW, not just the final scalar.

Why adding L2 to Adam's gradient changes the algorithm

An L2 penalty adds a cost for large parameter values: $\|\theta\|_2^2$ is the sum of all squared parameter coordinates. With $L(\theta)$ as the task loss and $J(\theta)$ as the penalized objective:

$$J(\theta) = L(\theta) + \frac{\lambda}{2}\|\theta\|_2^2, \qquad \nabla J = g + \lambda\theta.$$

For plain SGD without momentum, subtracting $\eta(g + \lambda\theta)$ equals decaying θ and subtracting ηg. Adam transforms the supplied gradient using coordinate histories; feeding $g + \lambda\theta$ into that transformation changes both memories. It is generally different from AdamW's separate parameter decay. Decoupled Weight Decay Regularization

Use a separate fresh example $p = 1$, $g = 0$, $m = v = 0$, step 1, with the same coefficients. Adam plus this L2 penalty uses effective gradient0.1, so $m = 0.01$, $v = 0.0001$, $\widehat{m}_t$=0.1, $\widehat{v}_t$=0.01. Its adaptive decrement is about 0.1 and new p≈0.90000001. AdamW keeps $m = v = 0$, has no adaptive decrement, and gives $p = 0.99$ through decay alone.

Why is Adam plus L2 different from AdamW? A zero-gradient example

Separate fixture: p=1, g=0, m=v=0, step=1; other settings unchanged. Here g is an explicit zero tensor.

Adam + L2	
effective gradient	0 + .1×1 = 0.1
first m	0.01
second v	0.0001
$\widehat{m}/\sqrt{\widehat{v}}$	0.1 / 0.1 ≈ 1
new parameter	≈ 0.90000001

AdamW	
effective gradient	0
first m	0
second v	0
adaptive change	0
new parameter	(1−.1×.1)×1 = 0.99

Left: adding λp to the gradient changes m and v. Right: parameter decay stays outside gradient memories.

Old momentum can move a zero-gradient parameter. This fixture sets old m=v=0 to isolate the difference.

This function receives a gradient tensor; it does not implement optimizer skipping for gradient=None.

Figure 105: Same zero-gradient input, different moment states and different parameter changes

Read the figure: This is explicitly a new comparison fixture, not step 3 of the prior trace. Both sides start from the same zero memories. A zero gradient with nonzero previous first can still move a parameter; gradient=None is a separate optimizer case not implemented by this function.

Initialization: why the previous constructor divides by sqrt(fan-in)

For the row-vector convention in 05.04, x is(1, n), W is(n, m), y=x@W is(1, m). fan-in n counts terms contributing to one output feature, not the output width m:

$$y_j = \sum_{i=0}^{n-1} x_i W_{ij}, \qquad \mathrm{Var}(y_j) = n\ \mathrm{Var}(x_i)\,\mathrm{Var}(W_{ij}).$$

This equality assumes independent zero-mean inputs with common variance q, independent zero-mean weights with common variance σ_W^2, and independence between weights and inputs. Each product contributes $q\sigma_W^2$ and cross covariances vanish under these assumptions. If $q = 1$ and weight standard deviation is 1, output variance is n. Choosing weight variance1/n, hence **standard deviation1/sqrt(n)**, makes this simplified output variance1.

Do not confuse variance and standard deviation: for $n = 4$, standard deviation0.5 means variance0.25. Dividing randn by sqrt(n) scales its standard deviation, not its realized entries' sample variance to an exact prescribed number. Zero mean and variance describe a random distribution; individual samples can be positive or negative and their empirical statistics vary.

Actual 05.04 raw matrix	Shape	fan-in	Supplied standard-deviation scale
q, k, v, o	(D, D)	D	$1/\sqrt{D}$
gate, up	(D, F)	D	$1/\sqrt{D}$
down	(F, D)	F	$1/\sqrt{F}$

This explains the supplied randn/sqrt(width) and randn/sqrt(hidden) choices; it is not a universal optimum for gated, normalized attention networks. nn.Linear stores its matrix transposed relative to raw x@W. Fan-based initialization APIs assume that Linear storage convention, so check matrix orientation before using them on raw Parameters. Official initialization notes

Depth scaling is a separate optional approximation

If 2L residual branch changes were independent, zero-mean and each had variance s^2, multiplying each by α would give:

$$\mathrm{Var}\left(\sum_{r=1}^{2L} \alpha \Delta h_r\right) = 2L\alpha^2 s^2.$$

$\alpha = 1/\sqrt{2L}$ keeps this simplified summed-change variance at s^2. Real branches are correlated and include nonlinear gates, normalization and input-dependent attention, so this is a motivation for


possible scaling, not a guarantee or a prescription added to 05.04. Variance of the entire hidden state also includes its input and covariance terms. Record and inspect actual activation/gradient statistics when running later experiments; this lesson makes no measurements of those statistics.

Initialization sets starting scales: width and depth create different sums

Assume independent zero-mean inputs / residual changes with variance 1. Curves are analytical, not training measurements.

input x	@	weight W	=	output y
shape = (1,n)		shape = (n,m)		shape = (1,m)

$$y_j = \sum_{i=0}^{n-1} x_i W_{ij}, \qquad \mathrm{Var}(y_j) = n\,\mathrm{Var}(W_{ij})\,\mathrm{Var}(x_i)$$



Width n / input count	4	64	1024
Weight standard deviation $1/\sqrt{n}$	0.5	0.125	0.03125

Prior q/k/v/o/gate/up have fan-in D; down has fan-in F. Standard deviation differs from variance.

Depth scaling is an optional design idea, not a model-edit task here; gating, correlation and normalization alter statistics.

Figure 106: Separate tensor dimensions, fan-in variance prediction, residual-depth approximation and standard-deviation table

Read the figure: Top boxes show shapes. Left chart varies input width n; right chart varies depth L. Both axes use logarithmic scales and depict analytical values under the stated assumptions. Green curves stay at 1 because of the respective scaling choice, not because every real model activation is exactly 1. Bottom table lists weight standard deviation, not variance.

Which parameters to decay is a configuration choice

A common configuration decays matrix weights while leaving normalization gains and biases without decay. This is a convention to test and record, not a theorem or a mandatory optimum; embedding treatment varies. Tied embedding/head weights from 05.04 represent one Parameter and must not be independently updated twice. This single-tensor function only uses the decay value given by its caller; parameter groups are not another learner task here.

Initializing every hidden weight identically can preserve unwanted symmetry, so the all-zero branch identity check in 05.04 is not a general training recipe. Some selected biases, position tables or residual projections can deliberately start at zero in specific designs; this does not justify resetting all model weights or optimizer moments each step.

In-place updates, no_grad and the eight implementation steps

The caller retains references to parameter, first, second. `buffer = expression` rebinds a local name and does not replace the caller's tensor contents. Methods ending in _, such as mul_ or add_, mutate that tensor in place. Here this is required, whereas earlier forward exercises intentionally avoided in-place input changes.

Use `with torch.no_grad():` to stop recording the optimizer's mutation in the computation graph. It does not erase already computed gradients or permanently set requires_grad=False. Do not use .data or detach as a substitute for writing the update correctly. This exercise leaves parameter.grad and gradient unchanged; gradient clearing belongs to the outer training loop. Buffers remain available across future calls/checkpoints.

Open the actual exercise and edit only adamw_update between its markers. Remove the placeholder after reading the trace. Ordinary function statements use four spaces; the body of with uses eight. The function itself needs no loop over coordinates.

1. **Enter the update context.** At four spaces write `with torch.no_grad():`. Put mutations/calculations inside at eight spaces. with limits this mode to the indented region and restores the previous mode afterward.
2. **Update first in place.** Use mul_ to keep beta1 times its old contents, then add_ a scaled gradient. Generic syntax is `buffer.add_(other, alpha=coefficient)`. Match beta1*old_first+(1-beta1)*gradient. Scalar fixture ends with 0.2.
3. **Update second in place.** First keep beta2 times its old contents using mul_. Then add the scaled elementwise gradient square. Generic `buffer.addcmul_(a,b,value=c)` means buffer += c*a*b. Here both input factors are the same gradient; use coefficient1-beta2. Fixture ends with 0.04. Do not square first instead.

4. **Make corrected temporary values.** Use `** step` in each scalar denominator and ordinary `/` to save new first_hat, second_hat. Do not use div_ on persistent buffers. Fixture values 2 and 4; the next call must still receive0.2 and 0.04.
5. **Build the denominator.** Use `.sqrt()` on second_hat, then add eps. Shape stays the same as parameter. Fixture value 2.00000001. Do not put eps inside sqrt or use sqrt(first_hat).
6. **Apply decoupled decay in place.** Multiply parameter by 1-learning_rate*decay with mul_. Fixture p becomes 0.99. This multiplication uses the old parameter before its adaptive subtraction, and never modifies gradient.
7. **Subtract the adaptive contribution in place.** Generic `buffer.addcdiv_(a,b,value=c)` means buffer += c*a/b. Use corrected first as numerator, the prepared denominator, and a negative learning-rate coefficient. Alternatively subtract a separately formed adaptive tensor in place. Fixture result0.8900000005.
8. **Return None.** After the context return to four spaces and use `return None`, or allow the function to finish implicitly. Do not return parameter or moments. The driver observes their changed contents directly. It calls you again with step 2, retained buffers and a new gradient.

Only the learner fills the core; no completed update function is supplied in the lesson. The new detailed hints sit next to the learner region and preserve the original check driver.

Run, original checks and preparation evidence

```
python exercises/05_05_adamw_initialization.py
```

After implementation, expect:

```
Lesson 05.05 checks passed.
```

This function has no unfinished model dependencies. The original driver performs both updates in float64 against torch.optim.AdamW, checks the return is None, checks gradient is unchanged and compares final first/second buffers with exp_avg/exp_avg_sq. It does not prove every boundary or initialization choice is correct.

Additional checks can cover scalar and vector arithmetic, the unchanged driver, float32/float64 and non-contiguous matrix updates, preserved object/storage identity and gradients, zero gradients, zero decay, zero learning rate and β endpoints0 against independent arithmetic and the installed PyTorch optimizer. With learning_rate=0, parameters do not move but moments still update on a supplied gradient.

This exercise covers dense real-valued, non-differentiable optimizer steps, not sparse gradients, mixed-precision master weights, AMSGrad, maximize, capturable/fused execution or complete parameter-group policies. Initialization charts are analytic illustrations, not empirical quality/performance claims. In a real run, save model parameters, both moments and update counts; recovering only parameters restarts a different optimizer trajectory. Lesson 05.07 develops full resume state.

05.06 Learning-rate schedules and global gradient clipping

Method sources

For cosine annealing, see SGDR Loshchilov and Hutter, 2017; R27; for gradient-norm clipping, see Pascanu et al., 2013; R28. Our schedule uses warmup followed by one cosine decay, without SGDR's warm restarts; it also differs from the inverse-square-root schedule in the original Transformer.

Two controls around the optimizer, with different jobs

Lesson 05.05 explains how AdamW changes parameters using gradients, memories and weight decay. This lesson prepares that update: choose the learning rate for the current update index and limit the global gradient length. The helper returns a rate and changes existing gradient buffers, while leaving all parameter values untouched.

Control	Input	Output / effect
Learning-rate schedule	Update index and chosen horizon	One Python floating learning rate
Global norm clipping	Existing parameter gradients and max_norm	Scale all gradients together only if their joint norm is too large
Optimizer update, outside this function	Prepared gradients and assigned learning rate	Change parameters and optimizer state

Warmup provides smaller initial rates when warmup>1, giving early representations and optimizer memories time to develop. A decreasing rate can make later changes smaller. These are design motivations, not guarantees of stable training or superior loss. Clipping limits an unusually large gradient's magnitude while retaining its direction; it does not solve every source of unstable updates.

Function contract and side effects

```
def scheduled_clip(parameters: list[torch.Tensor], step: int,
                   warmup: int, total: int, peak: float,
                   minimum: float, max_norm: float) -> tuple[float, float]:
```

Argument	Meaning / requirement
parameters	A list of distinct floating parameter tensors, each with .grad as a matching dense real tensor or None
step	Python integer s, a zero-based update index; 0<=step<=total
warmup	Integer w, number of warmup indices; 1<=warmup<total
total	Integer S, the final allowed schedule index, not automatically a count of calls

Argument	Meaning / requirement
peak	Maximum nonnegative learning rate
minimum	Minimum rate of the cosine phase, with 0<=minimum<=peak
max_norm	Positive scalar c, the maximum combined gradient L2 norm
Return	`(lr, original_global_grad_norm)`, both Python floats

Only existing .grad contents may change. Preserve parameter values, gradient objects, their shapes, dtypes and devices, and None gradients. Do not create gradients, update Adam moments, call backward or assign optimizer learning rates here. The caller handles those operations. Different parameters and gradient buffers can have different shapes. Avoid duplicated parameters or overlapping gradient storage; tied weights must be included once.

This lesson uses finite gradients whose accumulated squares are representable in float64, and a backend supporting those statistics. Native float32/float64 updates are reviewed. It does not implement sparse gradients, NaN/Inf policy or distributed norm reduction. No extra input-validation task is added.

Define the counters before the schedule formula

Write step=s, warmup=w, total=S, peak=$\eta_{\max}$, minimum=$\eta_{\min}$. s counts optimizer-update positions, not tokens T, batch size B or model depth. In 05.05, AdamW's own step=t starts at 1; this helper's schedule index starts at 0. When one update happens each round, t=s+1. With accumulation or skipped updates, track actual update progress explicitly; do not advance solely because another microbatch was read.

The exact assignment schedule is:

$$\eta_s = \begin{cases} \eta_{\max}\dfrac{s+1}{w}, & 0 \le s < w, \\ \eta_{\min} + \dfrac{\eta_{\max} - \eta_{\min}}{2}\left[1 + \cos\left(\pi\dfrac{s-w}{S-w}\right)\right], & w \le s \le S. \end{cases}$$

There are two branches, not two learning rates multiplied together. Python's `if step < warmup:` selects the first; `else:` selects the second. Use Python math.cos and math.pi for these scalar calculations. The function does not create a tensor of learning rates or sample a token.

Warmup: why s+1, and why the peak appears twice

During warmup, s=0 gives peak/w. s=w-1 gives peak. The +1 makes the first rate positive when peak>0, rather than starting at 0. For w=2, the two warmup calls produce0.05 and 0.1. If w=1, the sole warmup call already uses peak.

At s=w the cosine branch begins at its own progress0 and also gives peak. Thus this exercise intentionally has consecutive peak values at w-1 and w. Preserve the supplied definition instead of silently changing one index to produce a different schedule.

Endpoint versus update count: With total=6, valid samples are 0..6, seven points. A loop over range(total) would use0..5; the endpoint sample6 may be inspected without performing another optimizer update. Do not add a seventh training update simply to reach a plotted endpoint. To apply minimum on the final actual update, align S with that update's index in the chosen training loop. The name total is retained to match the real exercise.

Cosine decay: derive the three transformations

First normalize remaining progress, then map it to half a circle:

$$u = \frac{s - w}{S - w} \in [0, 1], \qquad \phi = \pi u, \qquad a(u) = \frac{1 + \cos \phi}{2}.$$

At $u = 0$, $\cos 0 = 1$ and a=1. At $u = 0.5$, $\cos(\pi/2) = 0$ and a=0.5. At $u = 1$, $\cos \pi = -1$ and a=0. Scaling and shifting this coefficient gives $\eta_{\text{min}} + (\eta_{\text{max}} - \eta_{\text{min}})a$. It starts at peak and finishes at minimum; between them it follows a smooth half-cosine rather than a constant decrement. Angles are in radians. Official cosine-schedule formula

Our function is a stateless, explicitly indexed schedule with a warmup branch. It is not a direct call to a stateful PyTorch scheduler; its index boundaries are defined above. Do not continue past S: the formula would eventually rise again, outside this contract. Equal peak/minimum gives a constant cosine phase; both zero gives zero learning rate throughout.

Complete schedule example, including the original call

Choose warmup=2, total=6, peak=0.1, minimum=0.01:

step s	Phase	Cosine progress u	Learning rate
0	Warmup	—	0.05000000000
1	Warmup	—	0.10000000000
2	Cosine	0	0.10000000000
3	Cosine	0.25	0.08681980515
4	Cosine	0.5	0.05500000000
5	Cosine	0.75	0.02318019485
6	Cosine	1	0.01000000000


The original check calls step=4. It lies in the cosine phase:

```
progress = (4-2)/(6-2) = 0.5
angle    = pi*0.5     = pi/2
cosine   = cos(pi/2)  = 0
lr       = 0.01 + 0.5*(0.1-0.01)*(1+0)
         = 0.055
```

Displayed decimal values are rounded; floating cosine(pi/2) can be extremely close to, rather than exactly, zero.

Warm up, then follow half a cosine: one learning rate per update index

warmup=2, total=6, peak=0.1, minimum=0.01. Dots are discrete calls; lines connect them for reading.



Calculate s=4

progress=(4−2)/(6−2)=0.5

angle $= \pi \times 0.5 = \pi/2$

$\cos(\pi/2) = 0$

lr=.01 + .5×(.1−.01)×1

lr=0.055

step s	0	1	2	3	4	5	6
lr	0.05000000	0.10000000	0.10000000	0.08681981	0.05500000	0.02318019	0.01000000

Both s=1 and s=2 reach peak: this follows the exact two-piece exercise rule.

total is the endpoint index: 0..6 contains seven points; range(total) uses only 0..5.

The plot requests no extra training update. Learning rate follows update index, not token position.

Figure 107: Exact discrete schedule samples, warmup/cosine boundary and step 4 arithmetic

Read the figure: Horizontal axis is optimizer-update index, vertical axis is a scalar learning rate. Orange background marks warmup; the dashed boundary at 2 starts cosine progress. Dots at 1 and 2 both equal peak. The table explicitly includes the endpoint6 without claiming seven training updates occurred.

Global gradient norm: combine entries, not parameter values

Suppose parameter i has gradient tensor $g^{(i)}$. Conceptually flatten and concatenate all existing gradients into a vector G. Its length is:

$$n = \|G\|_2 = \sqrt{\sum_{i:\, g^{(i)} \neq \text{None}} \sum_j \left(g_j^{(i)}\right)^2}.$$

j ranges over every entry of a gradient tensor, regardless of its shape. Sum squared entries, not signed entries or separate tensor norms. There is no division by the number of parameters or tokens. No actual concatenation allocation is required. This joint-gradient interpretation is also used by PyTorch global norm clipping.

None means no gradient tensor is present; skip it. A zero gradient tensor exists and contributes zero. With an empty list or all None gradients, $n = 0$. Convert each gradient to float64 **before** squaring and summing, so a narrower dtype does not overflow before accumulation. For example, a float16 value 1000 is finite, while its square is too large for float16; casting the already overflowed square afterward cannot recover it. This protects the statistic, not every mixed-precision training operation.

One common factor preserves the joint direction

For c=max_norm, define:

$$\alpha = \begin{cases} c/n, & n > c, \\ 1, & 0 \leq n \leq c, \end{cases} \qquad \tilde{g}^{(i)} = \alpha g^{(i)}.$$

Only scale when n>c. That condition also guarantees n>0, so the division is safe without adding eps. If gradients are already short enough, do not enlarge them to reach c. Since every coordinate gets the same positive multiplier, the combined nonzero direction is unchanged and the new norm is α*n<=c, subject to rounding. Return the saved **original** n for diagnosis, not the length after clipping.

The installed PyTorch clipping utility uses a small denominator stabilizer, giving tiny differences near thresholds. This exercise uses the exact piecewise factor above, with the zero case handled by its branch; comparisons with the utility allow its small numerical difference.

The original function call, all the way to its return

The original driver supplies:

```
parameter p values: [1,1]       shape (2,)
p.grad:            [3,4]       shape (2,)
parameter q values:[1]         shape (1,)
q.grad:            None
step=4, warmup=2, total=6, peak=.1, minimum=.01, max_norm=2
```

The schedule gives lr=0.055 as derived above. For clipping:

```
squared norm = 3**2 + 4**2 = 25
original norm = sqrt(25)  = 5
5 > 2, so factor         = 2/5 = 0.4
new p.grad               = [3*0.4,4*0.4] = [1.2,1.6]
```

```
new gradient norm        = sqrt(1.2**2+1.6**2) = 2
return                   = (0.055,5.0)
```

p remains[1,1], q remains[1], q.grad remains None. The returned 5 is not a failure to clip; it is deliberately the norm before clipping. The caller can use it to tell how large the incoming gradient was. Both returned objects are Python floats, not parameter tensors or losses.



Figure 108: Parameter values versus gradients, squared-norm accumulation, one factor and the original-norm return

Read the figure: Parameter values are shown separately from .grad values. Only the latter enter squares and are scaled. q.grad=None is skipped without allocating zeros. Bottom rows distinguish changed gradient entries, unchanged parameters and the pre-clipping diagnostic.

Why clipping each parameter separately changes the result

Use a separate geometric example with two scalar parameters, gradients3 and 4, c=2. Global clipping produces[1.2,1.6], length2, preserving the ratio4/3. Clipping each scalar independently to magnitude2 produces[2,2], length sqrt(8)>2, and changes the ratio to 1. Coordinate-wise truncation to[-2,2] also gives a different result from global norm clipping.




Figure 109: Same joint vector, radial global clipping versus separately clipped coordinates

Read the figure: The circle has radius2. The correct clipped vector lies on the original ray and on the circle. Separately clipped[2,2] lies outside the circle and points elsewhere. The axes here are two parameter-gradient coordinates, not token positions or tensor sizes.

For plain SGD without momentum or decay:

$$\|\Delta\theta_{\text{SGD}}\|_2 = \eta\|\widetilde{G}\|_2 \le \eta c.$$

AdamW also uses old moments, adaptive division and independent decay, so the same displacement bound does not follow. For one fresh Adam coordinate with $g = 0.01$, $c = 0.1$, no clipping occurs; its first adaptive change is *η0.01/(0.01+eps), approximately η, which exceeds η*c. Clipping limits the gradient input, not every optimizer's eventual parameter movement or future loss.

Put the helper in the training loop correctly

After backward produces gradients, call scheduled_clip, assign its returned rate to the optimizer, then execute the optimizer update. Returning a number alone does not change an optimizer's configuration. Given an existing model and optimizer, the integration pattern is:

```
lr, original_norm = scheduled_clip(
    list(model.parameters()), step, warmup, total, peak, minimum, max_norm
)
for group in optimizer.param_groups:
    group["lr"] = lr
optimizer.step()
```

An optimizer parameter group is a collection of parameters with shared update settings, stored as a dictionary in `optimizer.param_groups`. The loop changes each group's learning-rate field before step. This simple example applies the same rate to all groups; policies with different group rates need an explicit design. It is outside the learner helper. Clear gradients before the next accumulation window, not before clipping the current ones.

If using gradient accumulation, combine all microbatch contributions before one clipping operation. Clipping each microbatch before adding is generally different from clipping their sum. Automatic mixed precision (AMP) uses lower precision for selected operations. Its optional loss scaling multiplies the loss to keep small gradients representable; unscaling divides those gradients by the same scale. If using this later, first unscale the accumulated gradients, then clip, then perform the scaled optimizer-step protocol. Otherwise, clipping would compare the scaled norm with a threshold intended for the original gradients. This ordering is described in the official AMP clipping example; do not add AMP setup to this exercise.



Figure 110: Backward, optional unscale, schedule/clipping, learning-rate assignment and optimizer update order

Read the figure: The optional AMP stage is skipped without scaled gradients. The highlighted helper changes .grad only. The following optimizer step changes parameter values. Keep zero-based schedule s separate from one-based Adam t. No model training or optimizer state mutation happens inside this helper.

Eight guided implementation steps with exact indentation

Open the actual exercise and edit only scheduled_clip between the learner markers. It is a top-level function: ordinary statements use four spaces. Each if/else/for/with block adds four spaces. The final return belongs outside every loop and condition.

1. **Warmup branch.** At four spaces use `if step < warmup:`. Its eight-space body computes peak*(step+1)/warmup and saves lr. Example step 0 gives 0.05, step 1 gives 0.1. Python `/` returns a floating result.
2. **Cosine branch.** At four spaces add `else:`. At eight spaces compute `progress=(step-warmup)/(total-warmup)`, then use `math.cos(math.pi*progress)` in the stated formula. Example step 4 gives 0.055. Do not change the boundary to <=.
3. **Collect existing gradients.** Back at four spaces create an empty list. Use `for parameter in parameters:`; its body has eight spaces. At eight spaces test `if parameter.grad is None:` and at twelve spaces use `continue` to skip that parameter. Back at eight spaces append its .grad tensor. `is None` tests absence, not whether entries equal0; continue starts the next iteration.
4. **Accumulate squared entries.** At four spaces initialize a Python float squared_norm=0.0, then loop over the collected gradients. At eight spaces detach a read-only statistics view, convert to torch.float64, square, sum all entries, and use .item() to read the scalar into the accumulator. sum() without an axis reduces all entries of that tensor. Original fixture gives 9+16=25. The .item() here is a diagnostic reduction, not a model feature or differentiable loss.
5. **Save the original norm.** At four spaces apply math.sqrt to the sum. Keep this Python float as original_norm. An empty list or all zeros gives 0 naturally. Do not overwrite it after scaling.
6. **Decide whether clipping is needed.** At four spaces use `if original_norm > max_norm:`. At eight spaces compute factor=max_norm/original_norm. It is below1; the original fixture gives 0.4. No division occurs for a zero or already-small norm.
7. **Scale existing gradient buffers in place.** Inside that if, write `with torch.no_grad():` at eight spaces, then a gradient loop at twelve spaces and each `gradient.mul_(factor)` at sixteen spaces. The underscore changes the original .grad entries; `gradient = gradient*factor` would only rebind a local name. Keep gradient objects, shapes and parameter values intact.
8. **Return both Python floats.** At four spaces return lr, original_norm as a tuple after all loops/conditions. Original result(0.055,5.0), not(0.055,2.0). Returning inside a loop would miss later gradients or return nothing for an empty list.

The supplied comments repeat these steps with shapes and intermediate values. They guide your own implementation; the core stays unfilled until you write it.

Run, original driver and preparation verification

```
python exercises/05_06_schedule_clipping.py
```

Expected after implementing this standalone function:

```
Lesson 05.06 checks passed.
```

The original driver checks the full step 4 call, lr0.055, original norm 5, clipped gradient[1.2,1.6], unchanged parameter values, preserved None, and empty-list schedule endpoints0 and 6. It does not test every possible shape, schedule boundary or integration policy.

Additional independent calculations can check all seven sample rates and other warmup/horizon boundaries, flat/zero schedules, global multi-tensor/matrix arithmetic, None/zero/equal/below-threshold cases, original-norm returns, preserved gradient identities and parameters, non-contiguous float32/float64, float64-before-square behavior and approximate agreement with the installed clipping utility. The exercise driver remains unchanged. These are arithmetic checks, not corpus training or a claim of improved model quality.

05.07 Exact checkpoint and resume

What should happen when training stops?

Imagine finishing update 1, stopping the program, and later continuing with update 2. Loading the weights restores the model's current predictions. Continuing the same training trajectory also requires the optimizer's memories, progress and future random choices. A checkpoint is a snapshot of the state needed for that continuation.

Lessons05.05–05.06 explain AdamW memories and update-indexed learning rates. Here we preserve state rather than compute another gradient or parameter update. Start with a tiny linear model so every saved value can be inspected; a language model has many more tensors but the same question: what determines its next update?

This lesson constructs an **independent in-memory dictionary**. Saving that dictionary to disk is a separate operation explained later on this page.

Define the state before writing a formula

Let s be the number of completed optimizer updates. Write:

$$\mathcal{C}_s = (\Theta_s, O_s, s, R_s^{\text{cpu}}, R_s^{\text{sampler}}).$$

Symbol	Meaning	Returned key
Θ_s	Model parameters and persistent buffers at capture	model
O_s	Optimizer state and parameter-group settings	optimizer
s	Completed update count, supplied by the caller	step
R_s^{cpu}	Current default CPU random-generator state	torch_rng
R_s^{sampler}	Current state of the separately supplied CPU Generator	sampler_rng

A buffer is a stored tensor registered with a module that need not be a trainable parameter, such as a running statistic. Model state_dict includes persistent buffers as well as parameters. Our nn.Linear fixture has weight and bias but no such buffers. Module state_dict reference

For this fixture, with the same next input, update code and execution settings, the target is:

$$\text{next}(\text{restore}(\mathcal{C}_s)) = \text{next}(\text{original state after } s \text{ updates}).$$

This is a condition to verify, not a promise that these five fields cover every possible training program. The next-input position, additional generators and other state must be added when the program uses them.



Figure 111: Five checkpoint fields, types and progress

Read the five cards as dictionary entries, not as five tensors with a common shape. step is an integer. RNG means random number generator. Its checkpoint entries are byte tensors encoding internal generator state; their lengths are implementation details, not vocabulary sizes or hidden dimensions. Shape metadata appears outside numerical values.

Why model weights alone do not recover AdamW

For each parameter coordinate, AdamW uses the gradient's moving memories:

$$m_{s+1} = \beta_1 m_s + (1-\beta_1) g_{s+1}, \qquad v_{s+1} = \beta_2 v_s + (1-\beta_2) g_{s+1}^2.$$

The next parameter value also uses bias correction and decay:

$$\widehat{m}_{s+1} = \frac{m_{s+1}}{1-\beta_1^{s+1}}, \quad \widehat{v}_{s+1} = \frac{v_{s+1}}{1-\beta_2^{s+1}}, \quad \theta_{s+1} = (1-\eta\lambda)\theta_s - \eta \frac{\widehat{m}_{s+1}}{\sqrt{\widehat{v}_{s+1}} + \epsilon}.$$

Here every fixture parameter receives one gradient per update, so its optimizer counter equals s. In a more general model, a parameter with no gradient may have a different internal counter. Preserve the optimizer's own counters instead of recreating them from the outer step.

Equal θ and equal next gradient do not imply equal next θ when m, v or the internal counter differs. PyTorch's AdamW state names are exp_avg for m, exp_avg_sq for v and step for its per-parameter update count. optimizer.state_dict also retains param_groups, including learning rate, betas, eps, weight_decay and parameter identifiers. Those identifiers are not token IDs or portable tensor names. Optimizer state_dict reference

The numerical continuation diagram below accompanies these formulas. Reading that comparison before the implementation makes the reason for saving O_s concrete.

Exact function, inputs, output and side effects

```
def checkpoint_state(model: nn.Module, optimizer: torch.optim.Optimizer,
                     step: int, sampler: torch.Generator) -> dict:
```

Input	Type and meaning
model	Existing nn.Module; read its state_dict, do not replace or train it
optimizer	Existing optimizer attached to model parameters; read its current state_dict
step	Nonnegative Python int; number of completed updates, not the index of a token
sampler	Caller-owned CPU torch.Generator; capture its current state without drawing samples

Input	Type and meaning
Return	A dictionary with exactly model, optimizer, step, torch_rng and sampler_rng

Each model tensor retains its own shape and dtype. AdamW's moment tensors match their corresponding parameter shapes; internal step counters are scalar tensors in the installed fixture. The returned dictionary is recursively copied so its mutable tensors do not share storage with the original live model or optimizer. Do not copy the live Module or Optimizer objects themselves.

Capture at an optimizer-update boundary with no pending gradient accumulation. The helper must not call forward, backward, optimizer.step, zero_grad, manual_seed or a random drawing function. It must not change parameter values, existing gradients, optimizer memories or either generator position. No loop, if branch or input-validation exercise is needed for this fixed contract.

Complete original example: follow both parameters

The supplied driver uses torch.manual_seed(17), nn.Linear(1,1), AdamW with lr=.02 and an independent Generator seeded7. The optimizer defaults here are betas=(.9,.999), eps=1e-8 and weight_decay=.01. All arithmetic below records the existing PyTorch2.0 CPU float32 fixture; printed values are rounded, and should not be hard-coded into your implementation.

A Linear(1,1) still has **two parameters**:

Item	Shape	Initial contents
weight	(1,1)	[[-0.1315175295]]
bias	(1,)	[0.0702191591]
Input x	(1,1)	[[1.0]]
Target	Scalar 2, broadcast to prediction	2.0
Prediction wx+b	(1,1)	[[-0.0612983704]]
Loss	Scalar tensor, shape=()	4.2489509583

For this one-entry mean squared loss:

$$\hat{y} = w \cdot 1 + b, \quad L = (w + b - 2)^2, \quad \frac{\partial L}{\partial w} = 2(w + b - 2) \cdot 1, \quad \frac{\partial L}{\partial b} = 2(w + b - 2).$$

The two gradients coincide because x=1, not because weight and bias are the same parameter. The first gradient is approximately -4.12259674. Both AdamW memories start at zero; update 1 gives m1≈-0.41225967 and v1≈0.01699581 **for each parameter**, and each optimizer counter becomes 1.

Moment in the run	w	b	Per-parameter m	Per-parameter v	Internal count
Before training	-0.13151753	0.07021916	0, conceptually	0, conceptually	0, conceptually
After update 1, save C1	-0.11149123	0.09020511	-0.41225967	0.01699581	1
After update 2	-0.09148012	0.11017589	-0.77529091	0.03332120	2

Before the first step PyTorch's AdamW state dictionary is empty: it creates the memory entries lazily. Saving step=0 is valid; do not assume that state already contains moment keys.

Now freeze C1 with step=1. Recompute the next gradient from the updated w and b:

$$L_1 \approx 4.08559704, \qquad g_2 \approx -4.04257202,$$

$$m_2 = .9(-.41225967) + .1(-4.04257202) \approx -.77529091,$$

$$v_2 = .999(.01699581) + .001(-4.04257202)^2 \approx .03332120.$$

Bias correction uses powers beta1^2 and beta2^2. With the saved weight decay and learning rate, update 2 reaches the third table row. The driver always zeroes gradients before its next backward call, so no old gradient is accidentally accumulated.

Match the next update across two routes: values from the original check

CPU float32; input [[1]], target 2; AdamW lr=.02, betas=(.9,.999), eps=1e−8, decay=.01.

Capture C_1 after update 1; next, recompute the gradient for the same input

w=−0.11149123 b=0.09020511 m=−0.41225967 v=0.01699581 count=1

w and b each own m, v and count; their values happen to match in this fixture.

A: continue the original objects

L=4.08559704, g_w=g_b=−4.04257202

w_2=−0.09148012, b_2=0.11017589

m_2=−0.77529091, v_2=0.03332120

Optimizer count = 2

B: recreate, then restore all five fields

L=4.08559704, g_w=g_b=−4.04257202

w_2=−0.09148012, b_2=0.11017589

m_2=−0.77529091, v_2=0.03332120

Optimizer count = 2

A and B match parameters/memories; subsequent draws also match within each RNG stream.

Restore weights but reset AdamW: even with the same gradient, the next result differs.

w=−0.09146895, b=0.11018707, count=1. A small difference still changes the training trajectory.

Figure 112: Original continuation versus restored continuation

Read from the shared C1 card into two routes. A updates the original objects. B creates new objects, restores C1, then performs the same update. Both recover w2≈-0.09148012 and b2≈0.11017589. m and v are listed once to save space; each parameter owns its own entries.

Counterexample: Reload w1, b1 into a fresh AdamW but omit the saved optimizer state. Its first memories become m≈-0.40425721, v≈0.01634239 and its internal count is 1. The same next gradient now produces w≈-0.09146895, b≈0.11018707. This difference is small in the fixture, but the trajectory has changed. Compare optimizer state as well as weights; a loose numerical tolerance could conceal a small error.

Why state_dict alone is not a frozen in-memory snapshot

state_dict returns a dictionary whose tensor entries refer to live parameter/buffer storage; the usual default detaches them from autograd. Two separate properties matter:

Operation	What it separates	What may remain shared
Assignment, saved = model.state_dict()	Gives a named mapping	Tensor storage with the live model
dict(saved) or saved.copy()	Copies the outer dictionary	Nested tensors and containers
tensor.detach()	Disconnects autograd history	Original tensor storage
copy.deepcopy(state_bundle)	Recursively copies this state-dictionary bundle	No mutable tensor storage with the original live state

For an ordinary state_dict with tensor/numeric entries, deepcopy handles nested dictionaries, lists and tensors. It is not a request to copy an arbitrary live computation graph. A clone of one weight would protect only that weight; copying the whole bundle also protects optimizer memories and all other model entries.




Figure 113: Shallow storage aliases versus independent deep snapshots

At capture both routes display weight=-0.11149123. After original update 2, a shallow saved reference displays -0.09148012; the deep snapshot still displays -0.11149123. The shape is (1,1) throughout. This figure concerns storage identity, not a reshape or matrix multiplication. The same argument applies to nested exp_avg and exp_avg_sq. Official saving tutorial: best-state snapshot

A random seed does not record how far a stream has advanced

A pseudorandom generator is a deterministic state machine: drawing numbers changes its internal state. A seed chooses a starting state; get_state records the current one, and set_state resumes from it.

$$(u_t, R_{t+1}) = \text{draw}(R_t).$$

R_t is generator state before a draw; u_t is the returned random value or tensor. This t counts random operations conceptually, not optimizer steps. Different operations can consume different amounts of generator state, so do not reconstruct the cursor by merely counting calls.

In a **separate illustration**, initialize a CPU Generator with seed 7, draw three numbers, and then capture its state S:

```
First three:                [0.53492254, 0.19880319, 0.65921170]
Capture S before next draw.
Next three:                 [0.65689027, 0.23276156, 0.42506140]
Restore S, then draw again: [0.65689027, 0.23276156, 0.42506140]
Reset seed7, draw again:    [0.53492254, 0.19880319, 0.65921170]
```

Resetting the seed goes back to the start instead of continuing after the first three numbers. In the original driver the sampler has not drawn anything before C1; there its saved sampler state happens to be the seed's initial state. The separate illustration shows why that coincidence cannot be assumed in training.



Figure 114: Seed, saved cursor and correct reconstruction order

Read rows2–3 as matching **next** draws. Below them, recreate objects before restoring the two RNG states. nn.Linear initialization consumes the default CPU RNG. Restoring RNG first and then constructing nn.Linear would advance the restored stream again.

The exercise has two independent streams:

How numbers are requested	Capture	Restore
torch.rand(3), default CPU stream	torch.get_rng_state()	torch.set_rng_state(…)
torch.rand(3, generator=sampler)	sampler.get_state()	sampler.set_state(…)

get_rng_state covers the default **CPU** generator, not every accelerator and not the separate sampler. Both results are uint8 state tensors; retain them intact. CPU RNG state, Generator state API

In the original driver after update 2, sampler draws≈`[.53492254,.19880319,.65921170]`, while the default stream draws≈`[.83020872,.12386358,.02932107]`. Restored draws must match within each stream; the two different streams do not need matching values. The regression updates themselves consume no randomness. This driver separately checks generator continuity; it does not exercise dropout or randomized data loading.

Read the supplied restore_state before implementing capture

The helper above the learner region already loads state; leave it unchanged. It performs these actions in order:

1. model.load_state_dict restores model tensor values into an already constructed matching module.
2. optimizer.load_state_dict restores memories, counters and group settings into an optimizer attached to that new model's parameters.
3. torch.set_rng_state restores the default CPU stream; sampler.set_state restores the separate stream.
4. return state['step'] gives the caller the completed-update count.

Create the new optimizer from the **new** model parameters, with compatible groups and parameter order. Passing the old model's parameters would attach updates to the wrong objects. A state_dict does not create the model architecture; preserve configuration and module code separately. The supplied default model.load_state_dict uses copying semantics; no newer assign-based loading API is needed.

After loading step=1, the next global optimizer update is update 2; if integrating05.06 with exactly one update per iteration, its next zero-based schedule index is 1. Do not increment the saved completed count during capture or restore. The optimizer's own step tensors arrive through its state_dict. An independently stateful scheduler needs its own state; a stateless schedule needs the saved index plus its original configuration.

Guided implementation: build one package, then copy it

Edit only checkpoint_state in the actual assignment, between START LEARNER CODE and END LEARNER CODE. The function body uses four spaces. A multiline dictionary is an expression inside braces, not a new control-flow block; indent entries another four spaces for readability, then return to four spaces for return.

1. **Start a temporary dictionary.** Choose a local name such as state. Syntax is `state = { ... }`; a key/value entry has the form `'name': expression,`. Do not write the literal ellipsis as your implementation.
2. **Add the model entry.** Its exact key is 'model'; call model.state_dict() with parentheses. At capture this includes weight shape(1,1) and bias shape(1,), not one stacked tensor. A method reference without () is not the saved state.
3. **Add the optimizer entry.** Key 'optimizer', value from optimizer.state_dict(). Retain both state and param_groups; do not manually list only m and v or rebuild defaults.
4. **Record progress.** Key 'step' receives the provided Python integer step unchanged. For the driver that value is 1; for a fresh run it can be0. Use the argument rather than a hard-coded1, step+1 or optimizer.step().
5. **Capture the default stream.** Key 'torch_rng' receives torch.get_rng_state(). This reads the current generator state without drawing random numbers. Do not use torch.rand or manual_seed.
6. **Capture the separate stream.** Key 'sampler_rng' receives sampler.get_state(). This is a method on the supplied object, distinct from the default generator call. Close the dictionary brace at the function-body indentation.
7. **Make the deep snapshot.** Use copy.deepcopy on the entire temporary dictionary and return that copied object. copy is already imported. Copying only the outer dict or only the model entry leaves other live state exposed.
8. **Remove the placeholder raise and read the driver.** Leave restore_state and run_checks untouched. Confirm your helper only reads state and returns an independent package; all training and random draws belong to the driver.

There is no need to reproduce AdamW's formulas inside this helper. They explain why optimizer memories must be saved; the optimizer already knows how to export them.

Run and interpret the checks

```
python exercises/05_07_checkpoint_resume.py
```

After your implementation is complete, expect:

```
Lesson 05.07 checks passed.
```

The supplied driver trains once, captures C1, trains again, records model values and both random draws, creates new objects, restores, and replays. It checks step=1, matching next parameters, unchanged saved model values after original continuation, and matching draws from both generators. Its

close helper uses numerical tolerance, not a general proof of bitwise equality. It does not explicitly assert every saved optimizer memory's storage independence; the recursive-copy contract still requires it.

What a real training checkpoint must add

The five keys are sufficient for this CPU regression fixture with its fixed input and supplied update function. Expand the checkpoint schema with actual program state when needed:

Additional responsibility	What must remain consistent
Model definition and configuration	Architecture, dimensions, weight sharing, module code and train/eval mode; mode is not in ordinary state_dict
Learning-rate schedule	Original configuration/index or stateful scheduler state; loading order must follow that scheduler's API
Mixed precision / gradient scaling	Scaler state and matching precision/execution policy
Randomness	Used accelerator generators, Python/NumPy generators, explicit generators and per-rank states
Data stream	Data/tokenizer versions, split/order, sampler permutation and cursor; a Generator alone does not describe an already created permutation
Accumulation	Save at a completed update boundary; mid-accumulation recovery additionally needs pending gradients and microbatch position
Provenance	Full code commit, portable configuration, budget, checkpoint artifact ID/checksum and evaluation protocol

After optimizer.step, .grad may still exist. The fixture's next update calls zero_grad, so stale gradient tensors are not needed in C1. state_dict does not preserve the live autograd graph or ordinary .grad fields. Reconstruct training mode explicitly when the model uses dropout or mode-dependent layers.

Data-loader prefetching and worker-local randomness need a deliberate replay policy. Multi-device exact continuation additionally depends on execution settings and deterministic operations. Full reproducibility is not guaranteed across software versions or devices even with seeds restored; test a resumed update under the same intended conditions. This lesson makes no multi-device exactness claim. PyTorch reproducibility notes

From in-memory snapshot to an optional file

Once checkpoint_state is implemented, torch.save can serialize its returned dictionary; torch.load restores that dictionary, after which the supplied restore_state installs it into new objects. The file extension does not decide which fields were saved. Keep checkpoint files in the ignored checkpoints/ directory and keep weights outside Git. This optional step is not required by the original driver.

For a reliable writer, serialize to a temporary file in the same destination directory and then replace the final path after serialization succeeds. This avoids exposing a partially written final file under the usual same-filesystem replace semantics; it does not alone guarantee durability after power loss. Load your own checkpoint artifacts using options supported by the installed version; newer tutorial defaults need not match PyTorch2.0. Capture a small portable manifest alongside the artifact. Chapter 06 develops data/tokenizer provenance rather than embedding personal connection details in training records.

Review questions

Before moving on, try explaining: why do equal weights permit different next AdamW updates; why does detach not freeze storage; why must model creation precede RNG restoration; and what does step=1 tell the caller to do next? A useful later reconstruction test is to write the five-key contract from memory, then compare uninterrupted and resumed updates without changing the supplied driver.

Looking back

We have a model and a recoverable update rule. Their results still depend on exactly which text became which targets. The next chapter makes that data path explicit.

06 Turn documents into pretraining

A corpus begins as records: text accompanied by identity, provenance and perhaps language or license information. Token packing begins later, after the caller extracts text, chooses a split and applies a frozen tokenizer. A dictionary, a string and a list of token IDs therefore represent different stages of the same document.

We preserve that distinction through manifests, stable document splitting, normalization and deduplication, tokenizer freezing, EOS concatenation, padding masks and a complete pretraining loop. The central accounting unit is an observed next-token target. Dataset size, tensor storage and the number of times a target is sampled are related, but they are not interchangeable measures.

06.01 Data provenance and fingerprints

Method sources

The SHA-256 fingerprint uses the Secure Hash Standard NIST, 2015; R41. A checksum establishes byte identity, not provenance rights, text quality or correct train/validation separation. The manifest schema here is a teaching design.

From preserving training state to identifying training data

A checkpoint tells us where training stopped. To continue or compare an experiment, we also need to know exactly which data it used. A file called training.txt may change while keeping its name. If its contents change, the same model code and seed no longer describe the same experiment.

We will build a manifest: a small inventory of document identities, content fingerprints and byte counts, together with source metadata. Keep the actual corpus separately; this inventory lets a later reader check which version was intended. It does not train a model or download any data.

This lesson reconnects with Chapter 01's UTF-8 bytes. No new tensor operation, attention formula or tokenizer implementation is needed. The assignment uses Python dictionaries, lists, a for loop and the standard-library hashlib module; the supplied common course imports still use the existing environment.

Define the three transformations before coding

For document d, let text_d be its Python string. Define:


$$b_d = \text{UTF8}(text_d), \qquad n_d = \text{len}(b_d), \qquad h_d = \text{hex}(\text{SHA256}(b_d)).$$

Symbol	Meaning	Python type
d	Document position, not a feature dimension	Conceptual index
text_d	Original document text	str
b_d	Text encoded as an ordered byte sequence	bytes
n_d	Number of encoded bytes, not their numeric sum	int
h_d	SHA-256 fingerprint displayed in hexadecimal	str, length64

The pipeline is **text → UTF-8 bytes → byte count and fingerprint**. Count and fingerprint both use the same encoded bytes. Encode once, then reuse that bytes object. Do not count the text characters for n_d, and do not hash a printed dictionary representation.

Fix the bytes before hashing: character count differs from byte count

Original documents d1="a", d2="你". Byte cells contain values; lengths are outside the cells.



The three UTF-8 bytes of 你 each contain 8 bits:

228 = 11100100 189 = 10111101 160 = 10100000

3 bytes = 24 bits. These are not three tokens or embedding coordinates; no tensor shape is involved.

Figure 115: Exact UTF-8 bytes and full SHA-256 fingerprints

Read each row from left to right. Decimal numbers inside cells are byte values; lengths are outside the cells. For these examples len('a')=len('你')=1, while UTF-8 lengths are 1 and 3. Python str length counts code points, which need not equal the number of visible characters for every Unicode string. This is a byte sequence, not an embedding matrix, so there is no tensor shape to infer.

What SHA-256 contributes

SHA-256 deterministically maps input bytes to a fixed-size digest. The same bytes give the same digest. A different digest proves the byte sequences differ; an equal digest is practical content-identity evidence, rather than a mathematical guarantee of uniqueness. There are finitely many256-bit outputs and more possible inputs, so collisions are possible in principle.

The digest is not a reversible encoding of the document. UTF-8 decoding recovers text from its bytes; a SHA-256 digest does not provide the original bytes for decoding. A short fingerprint cannot hold the complete contents of every arbitrarily long document.

Two output representations are useful:

$$256 \text{ bits}/8 = 32 \text{ bytes}, \qquad 32 \text{ bytes} \times 2 = 64 \text{ hexadecimal characters}.$$

One hexadecimal character represents4 bits; two represent one byte. hashlib.sha256(raw) constructs a hash object. Its digest() returns 32 bytes; hexdigest() returns 64 lowercase hexadecimal characters, which this exercise records. Python hashlib documentation

The256 here is the digest's **bit length**. Chapter 01's256 possible byte values comes from 2^8 and is a different quantity. Neither determines a BPE vocabulary size. A document's n_d can be0,1,3 or much larger while h_d always has 64 hexadecimal characters.

Function contract and data ownership

```
def data_manifest(documents: list[dict], source_id: str,
                  license_id: str) -> dict:
```

Argument	Meaning and contract
documents	Ordered list of dictionaries, each containing id:str and text:str; IDs are unique portable labels
source_id	Nonempty neutral identifier for the data source or source revision; example toy-v1
license_id	Nonempty metadata label supplied by the caller; example self-authored for this original toy text
Return	New dict containing source_id, license_id and documents

Each returned documents entry contains exactly id, sha256 and bytes. id is copied from the input; sha256 is the full fingerprint string, and bytes is a Python integer. The outer source_id and license_id

are preserved unchanged. The key ‘bytes’ is a field name, not a call to Python’s bytes constructor.

Do not modify, sort or remove input documents. Do not add fields to their dictionaries. Build a fresh output list and a fresh entry for each document. The output contains no raw text, input dictionaries, paths, connection settings or private infrastructure mappings. No validation branch is added: unique IDs and the stated input types are supplied conditions.

A source label describes provenance; a content hash describes bytes. A license label records supplied metadata. Computing a hash neither checks the label’s accuracy nor grants permission, assesses quality or anonymizes short guessable content. Hashes should not be treated as a privacy transformation.




Figure 116: Input documents and exact output fields

Read the upper list in order, then the new lower list. Only hash prefixes are shown in this diagram to

keep the table readable; the actual function must return all64 characters. The input text field is used to compute the fingerprint and is omitted from the output.

Complete original example: a and 你

The supplied driver uses:

```
documents = [
    {'id': 'd1', 'text': 'a'},
    {'id': 'd2', 'text': '你'},
]
source_id = 'toy-v1'
license_id = 'self-authored'
```

For d1, read document[‘text’] as ‘a’. Encoding produces b’a’, whose sole byte has decimal value 97. Therefore len(raw)=1. Do not use sum(raw), which would give97 instead of 1. Its full hash is:

```
ca978112ca1bbdcafac231b39a23dc4da786eff8147c4e72b9807785afee48bb
```

For d2, encoding produces b’\xe4\xbd\xa0’. That display uses hexadecimal escapes for three byte values:

```
Hexadecimal:  E4          BD          A0
Decimal:      228         189         160
Bits:         11100100    10111101    10100000
```

Thus len(raw)=3, representing24 bits. The three bytes jointly encode this one Chinese character. Its full hash is:

```
a0c7716669b5ded0d8051abfc232b828d489f7d889b2928eefcf43f0b8f495d6
```

After processing d1, the output list has one entry. After d2, it has two entries in the same order. The complete returned value is:

```
{
    'source_id': 'toy-v1',
    'license_id': 'self-authored',
    'documents': [
        {
            'id': 'd1',
            'sha256': 'ca978112ca1bbdcafac231b39a23dc4da786eff8147c4e72b9807785afee48bb',
            'bytes': 1,
        },
        {
            'id': 'd2',
            'sha256': 'a0c7716669b5ded0d8051abfc232b828d489f7d889b2928eefcf43f0b8f495d6',
            'bytes': 3,
        },
    ],
}
```

This is the expected data structure, not a filled implementation. The function takes arbitrary supplied documents; do not hard-code the example strings, IDs, lengths or hashes.

Byte-exact changes: newlines, empty text and normalization

A newline is data. The string ‘a\n’ contains a plus one newline; it is not the literal two-character sequence backslash+n. UTF-8 bytes are[97,10], giving byte count 2 and this fingerprint:

```
87428fc522803d31065e7bce3cf03fe475096631e5e07bbd7a0fde60c4cf25c7
```

One added newline changes this fingerprint: hash the exact bytes

This helper does not strip, clean or normalize Unicode. Record the exact text.encode("utf-8") bytes.

Python text repr	Byte values (decimal)	Bytes	First 12 hash digits
`'a'`	`[97]`	1	`ca978112ca1b...`
`'a\n'`	`[97, 10]`	2	`87428fc52280...`
`'a\r\n'`	`[97, 13, 10]`	3	`8e4621379786...`
`''`	`[]`	0	`e3b0c44298fc...`

\n is one byte, 10; \r\n is two bytes, 13 and 10. Empty text still has a valid SHA-256.

Fixed output width: 256 bits ÷ 8 = 32 bytes; 32 × 2 = 64 hexadecimal characters.

Input length may vary; 64 is the hash-string length, not the text byte count or token count.

Different hashes imply different bytes; equal hashes are practical evidence, not absolute mathematical uniqueness.

A fingerprint does not decode text, measure quality or verify permission; record provenance and processing separately.

Figure 117: Newline-sensitive bytes, counts and fixed-width hashes

The rows compare ‘a’, ‘a\n’, ‘a\r\n’ and empty text. These four byte sequences have distinct fingerprints. The bottom formula concerns output representation length, not input length. An empty document still gets a hash; an empty list of documents produces an empty documents list with the supplied outer metadata.

Do not call strip(), replace newlines or normalize Unicode inside this helper. For example, ‘\u00e9’ and ‘e\u0301’ can look alike but encode to[195,169] and[101,204,129]. They have different content fingerprints. If a later cleaning policy intentionally normalizes them, record that transformation and fingerprint the chosen stage explicitly. This function identifies the exact UTF-8 bytes of the received Python text; it does not recover original file bytes lost through earlier decoding, newline conversion or cleaning.

Changing a document’s id without changing its text leaves its content hash unchanged. Two different IDs with identical text have identical hashes and remain two output entries. Reordering input documents reorders the output entries; each individual content hash is unchanged. This assignment does not produce a single aggregate hash for the entire corpus or its ordering. A later experiment record must preserve the ordered manifest/version as well.

Read the two Python operations before the loop

`document['text']` retrieves a value by its dictionary key; it does not remove it. `text.encode('utf-8')` returns bytes. Method parentheses execute the operation. New syntax used for hashing is a chain of two operations:

```
hashlib.sha256(raw)      → a hash object
that_object.hexdigest() → its hexadecimal fingerprint string
```

The full expression hashlib.sha256(raw).hexdigest() is the corresponding API call, not the whole assignment. hashlib is already imported. String encoding reference

A for loop visits one dictionary at a time. Its body is indented one level. list.append(entry) adds one entry in place and returns None: do not assign that return value back to the list. The final return belongs after the loop, so an empty input still returns the correct outer dictionary.

Guided implementation in eight steps

Edit only data_manifest in the actual assignment, inside START LEARNER CODE and END LEARNER CODE. Function-body statements use four spaces; the for body uses eight. Multiline dictionary fields can use another four spaces for readability without creating a control-flow block.

1. **Create an empty result list.** A name such as entries can hold []. Place it before the loop at four spaces. Its initial length is 0.
2. **Visit each input document.** The syntax is `for document in documents:`. The colon starts the repeated body; indent that body to eight spaces. The first document has id=‘d1’, the second id=‘d2’.
3. **Encode that document once.** Retrieve document[‘text’], then call .encode(‘utf-8’). Store the

returned bytes in a local name such as raw. The example first produces[97], then[228,189,160] when inspected as a list.

4. **Count the encoded bytes.** Use len(raw) and store a Python integer, for example byte_count. The intermediate results should be1 and 3; len(document[‘text’]) would give1 for both.
5. **Compute the full fingerprint.** Feed raw to hashlib.sha256, then call hexdigest(). Keep the entire64-character string. Do not hash the ID, the dictionary’s printed representation or a concatenation with source metadata.
6. **Build and append one fresh entry.** Its exact keys are ‘id’, ‘sha256’ and ‘bytes’. Use the original document ID, computed hash and byte_count. Create this dictionary inside the loop and call entries.append(entry) as a statement. List lengths become1, then2.
7. **Return the outer dictionary after the loop.** Dedent to four spaces. Its keys are ‘source_id’, ‘license_id’ and ‘documents’; values are the two unchanged arguments and the completed entries list. With documents=[], the loop body runs zero times but this return still runs.
8. **Remove the placeholder raise and keep the driver unchanged.** Confirm no text was stripped, no input dictionary modified, no documents sorted and no private path inserted. The driver owns test setup; you own only this transformation.

Run and interpret the checks

```
python exercises/06_01_data_manifest.py
```

Expected after implementation:

```
Lesson 06.01 checks passed.
```

The original driver checks input preservation, byte lengths1/3, the exact hash for ‘a’, source_id, empty document lists and a changed newline hash. It does not explicitly assert every output key, license_id, every complete hash, ordering or fresh-object independence; those remain part of the stated contract. This lesson has no unfinished model-function dependency.

How the manifest joins the training experiment

Keep corpus data outside Git and commit a portable manifest only after its metadata is reviewed. A source ID is a neutral reference, not a hostname, account or local path. Keep any required private storage mappings in ignored configuration. Hashes can still reveal guessed short content, so omitting text is not by itself an anonymity guarantee.

For the eventual experiment, record the ordered data manifest/version, cleaning code revision, tokenizer version/checksum, model/training configuration, full code commit, budget, checkpoint artifact and evaluation protocol. The small return value here is one component of that record; it does not add all those fields automatically. It also does not replace storing the dataset itself in an appropriate data store.

Lesson 06.02 next splits by document before forming windows. Lesson 06.03 handles cleaning and deduplication;06.04 freezes the tokenizer,06.05 prepares packing/masks, and 06.06 connects a pretrain-

ing experiment. BPE still enters at tokenization: fingerprinting the source text happens earlier and does not require token IDs.

Review questions

Try explaining why len(‘你’) and len(‘你’.encode(‘utf-8’)) differ; why a 64-character digest does not mean the document has 64 bytes; why a newline matters; and why identical content under two IDs should keep two records here. A later independent reconstruction should produce the schema without copying the completed example into code.

06.02 Split by document before windows

Decide what counts as held-out data

A validation set should help assess behavior on data excluded from model fitting. Training data supplies gradient updates; validation data supplies held-out measurements and can guide model selection. A final test set has a separate role and should not be repeatedly used to choose settings. This helper creates only train and validation, not a test split or an entire evaluation protocol.

Lesson 06.01 identified exact document bytes. Now we assign each complete document to one side before creating training windows. Randomly dividing overlapping windows can place almost the same passage in both sets. Different window IDs do not make those passages independent. This is one form of data leakage, where the evaluation setup exposes information that should have been held out. Official guidance on splitting before learned preprocessing

This lesson combines a concrete overlap example with a deterministic content-based partition. No model training, corpus download, new package or random-generator state is needed.

Start with the next-token windows you already know

For a token sequence z of length L, context length T and start s:

$$X_s = z[s : s + T], \qquad Y_s = z[s + 1 : s + T + 1], \qquad 0 \le s < L - T.$$

Here s is a source-window start, not the optimizer update index from 05.06. A single window has T inputs and T next-token targets. Display them as one-dimensional arrays with shape(T,); batching would later produce(B, T). Do not interpret token values as shape lengths.

Take one document with token IDs[10,11,12,13,14,15], $T = 3$:

Window	Start	Input X, shape(3,)	Target Y, shape(3,)
A	0	[10,11,12]	[11,12,13]
B	1	[11,12,13]	[12,13,14]

If A enters training and B enters validation, two source transitions occur in both:11→12 and 12→13. The complete visible prefixes can differ because the windows start at different places; that does not remove the shared passage and target positions. This example establishes overlap, not a measured amount of model-loss improvement.

Splitting overlapping windows can put the same supervision on both sides

Separate illustration: one document has token IDs=[10,11,12,13,14,15], context length T=3.

Source index	0	1	2	3	4	5
Token ID values	10	11	12	13	14	15

Window A: training

start=0; shape(X)=shape(Y)=(3,)

`X=[10,11,12] Y=[11,12,13]`

Window B: validation

start=1; shape(X)=shape(Y)=(3,)

`X=[11,12,13] Y=[12,13,14]`

Supervised pairs	10→11	11→12	12→13	13→14	14→15
A: train	included	shared	shared	—	—
B: validation	—	shared	shared	included	—

Two of the validation window's three supervised pairs also occur in training: 11→12 and 12→13.

Different window IDs do not establish independence. Assign whole documents before making windows.

Figure 118: Source indices, token values, windows and shared transitions

Read the source-index row separately from token contents. The bottom two rows highlight the same two transitions on both sides. Keep the entire document on one side to prevent this particular within-document overlap. Common tokens can still occur in both splits; that is expected. The objective is to separate data units, not vocabularies.

Specify the content-based partition mathematically

Let f=validation_fraction and q=seed. For each document d:

$$p_d = \text{UTF8}(q) \parallel [0] \parallel \text{UTF8}(text_d),$$

$$H_d = \text{SHA256}(p_d).\,\text{hexdigest}(), \quad n_d = \text{int}(H_d, 16), \quad u_d = \frac{n_d}{2^{256}}.$$

The symbol || denotes byte concatenation, not multiplication or a logical operator. [0] denotes one zero-valued byte. H is a 64-character hexadecimal string; n is the same digest interpreted as a non-negative integer. Since0<=n<=2^256-1, the mathematical score satisfies0<=u<1. Python's ** means exponentiation; ^ does not.

For the mathematical rule:

$$d \in \mathcal{V} \iff u_d < f, \qquad d \in \mathcal{T} \iff u_d \geq f.$$

T and V here name the training and validation sets, not sequence length or vocabulary size. In code, use the list names train and validation to avoid that notation collision. A comparison exactly on the interior threshold belongs to training because the rule uses strict <.

A fixed hash protocol: seed bytes + a zero-byte separator + text bytes

Original fixture: seed="v1", text="a"; id is excluded. Cells contain bytes, not tensor dimensions.

seed.encode("utf-8")			b'\x00'		text.encode("utf-8")
118	49	+	0	+	97

Concatenated payload `[118, 49, 0, 97]`

↓

SHA-256 → hexdigest()

```
ad9799e8f62da609cdf1fe8e7dfaead172cf5825aefbbc1fabb4343ab6cd2db7
```

n = int(hex_digest, 16)

```
78517978959510909447554025451496255252185340594206639161624781576130937040311
```

u = n / 2**256 = 0.678094500900

u < 0.5 is False → train. Identical text under d1 and d9 gets exactly the same u.

0 is a zero byte, not the character "0" (byte value48); 2**256 counts possible hash integers.

Figure 119: Exact seed framing, full digest, integer and score

Read seed bytes, separator and text bytes as three pieces of one payload. For seed=‘v1’ and text=‘a’, they concatenate to[118,49,0,97]. The figure gives the full digest and integer before the normalized score. This seeded digest differs from 06.01’s unseeded content fingerprint; do not substitute one for the other.

Classroom Q&A: why divide the hash integer by 2^256?

A common question is what principle lies behind $u = \text{int}(h, 16)/2^{256}$. The division changes the scale of a deterministic hash number; it does not learn a model parameter or measure document quality.

Start with the representations. SHA-256 produces a digest of 256 bits, or32 bytes. hexdigest displays those bits as64 hexadecimal digits: each hex digit encodes4 bits, so64×4=256. `int(h,16)` interprets that same bit pattern as a nonnegative integer;16 means the input numeral is written in base 16. This conversion is not another hash and does not encode the original text again. Python hash representations

A bit has two possible values. With k bits there are 2^k patterns. Their unsigned integer values start at 0 and end at 2^k−1, because0 is also one of the patterns. For a small **separate four-bit example**, the range is 0…15, containing16 values. Suppose its hexadecimal representation is ‘c’:

```
hex 'c' = binary 1100 = integer 12
int('c',16) = 12
2**4 = 16
u = 12/16 = 0.75
```

Scale the integer range between 0 and 1: start with 4 bits, then use 256 bits

Separate 4-bit teaching example: h="c". The real assignment still uses all 64 hexadecimal digits.

Three representations of the same value:

hex c = binary 1100 = integer 12

Binary digit contents	1	1	0	0	
Integer place weights	8	4	2	1	n=8+4=12
Divide every weight by 16	1/2	1/4	1/8	1/16	u=12/16=.75

4 bits → 16 possibilities; n=0⋯15 → u=0/16⋯15/16, mathematically below 1.



Labels are integers n. Left-half dots satisfy n<8, hence u<.5. c=12 is on the train side.

SHA-256: 256 bits → 2^{256} possibilities → n/2^{256}. Here 256 is digest width, not document length.

This is a reproducible split score, not text quality or model confidence. Floating division can round.

Figure 120: Four-bit integer range, binary place weights and normalized scores

Read the bits1,1,0,0 separately from their positional weights8,4,2,1. They represent8+4=12. Divide those weights by 16 and they become1/2,1/4,1/8,1/16; the same bits now represent1/2+1/4=.75. You can think of moving a binary point to the left of all four digits: binary1100 becomes binary0.1100. This explains scaling without needing to memorize a huge decimal integer.

For every four-bit pattern, division by 16 gives one of:

$$0,\ \frac{1}{16},\ \frac{2}{16},\ \ldots,\ \frac{15}{16}.$$

There are still16 possible scores, equally spaced, with the last below1. At validation_fraction=.5, integers0…7 give u<.5 and enter validation;8…15 enter train. Our separate example $n = 12$ gives.75, so it enters train. This is an arithmetic analogy, not a replacement four-bit tokenizer/hash implementation.

Now replace4 with 256:

$$0 \le n \le 2^{256} - 1 \quad \Longrightarrow \quad 0 \le \frac{n}{2^{256}} \le 1 - 2^{-256} < 1.$$

Thus the original formula is simply **integer divided by the number of representable digest values**. The number256 here is the digest width in bits. It is not the number of documents, a byte's maximum value, a token count or a vocabulary limit. Do not divide by 256 or by the 64 displayed hex digits.

For the real seed='v1', text='a' fixture, the full hash integer already shown above gives u≈.6780945009; since that is at least.5 it enters train. Identical seed/text reproduces the same score. Across varied content groups we use hash scores as approximately spread across the interval; this is a split-design assumption, not a promise that every dataset or small sample has equal counts. A given document's score is a deterministic number, not its probability of being correct, text quality, a model confidence or a fresh random draw.

Why not divide by 2^256−1? That would map the largest integer to exactly 1 and define a different normalization. This protocol uses2^256 so the mathematical range is half-open[0,1), making a threshold $f = 1$ conceptually include all scores. Python's finite-precision float division adds a separate implementation concern: distinct exact ratios may round to the same float, and the maximum ratio rounds to 1.0. Python floating-point explanation

A controlled test supplied an all-ones256-bit digest, represented by 64 'f' digits. This tests a possible digest value without searching for a document that hashes to it. In the existing environment:

```
(2**256 - 1) / 2**256 == 1.0  # True: rounding of a ratio mathematically below1
```

If routing uses only `u < validation_fraction`, then validation_fraction=1.0 makes this comparison 1.0<1.0. It is False, so that test document enters train. The fraction1 contract requires validation. Handle that endpoint explicitly: use `validation_fraction == 1.0 or u < validation_fraction` as the branch condition. `or` makes the condition true when either part is true. Keep the existing append branches and the loop-external return; change neither the normalization nor strict< for interior fractions.

Why content, a seed and a separator each matter

Content chooses the group. The ID is excluded from the hash. Identical text under different IDs therefore stays on one side. Hashing an arbitrary document ID would separate exact duplicates if their IDs differ. Distinct input IDs do not imply distinct content.

The seed names a reproducible partition choice. Use a fixed public string such as'v1'. It becomes part of the hashed bytes; do not call random.seed, torch.manual_seed or random.shuffle. Repeating the same seed/content/protocol repeats the same score without advancing a generator. Changing the seed may change membership; do not search seeds for a preferred validation result.

The separator fixes the boundary. Without it, seed='ab', text='c' and seed='a', text='bc' both produce b'abc'. With a zero byte they produce b'ab\x00c' and b'a\x00bc'. b'\x00' is one byte with value 0; b'0' has value 48. The payload must match exactly. In this teaching protocol choose seeds without embedded NUL characters; the text may contain NUL. This is a framing condition, not a request to build an escaping/validation subsystem.

Hash bytes directly using hashlib, as in06.01. A64-digit hexadecimal digest is interpreted using int(hex_digest,16), where16 is the numeric base. For a tiny syntax example, int('10',16)=16 and int('ff',16)=255. The real digest is longer but follows the same rule. Python hash API, Integer conversion

Function contract and object ownership

```
def split_documents(documents: list[dict], validation_fraction: float,
                    seed: str) -> tuple[list[dict], list[dict]]:
```

Argument / return	Contract
documents	Ordered list of dictionaries with unique id:str and text:str; exact duplicate text is allowed
validation_fraction	Python float f in[0,1]; a threshold, not a promised realized count
seed	Fixed public string, with no embedded NUL under the framing convention above
Return	Tuple(train, validation), in that order; both are fresh lists

Append the original document dictionaries to their chosen output lists. Do not return only IDs, token arrays or manifest entries. This is a shallow partition: it does not mutate those dictionaries or create deep copies. A caller later editing an output document would also edit that original dictionary. The helper itself only reads them.

Preserve relative input order inside each output. Each input occurrence appears exactly once in one of the two lists; do not sort, remove duplicates, edit IDs/text or modify the input list. With no documents, return two distinct empty lists. The function does not create windows, fit BPE, check source licenses or remove near duplicates.

Complete original worked example

The unchanged supplied driver uses:

```
documents = [
    {'id': 'd1', 'text': 'a'},
    {'id': 'd2', 'text': 'b'},
    {'id': 'd9', 'text': 'a'},
]
validation_fraction = 0.5
seed = 'v1'
```

For the first document, seed UTF-8 bytes are[118,49], separator[0], and text bytes[97]. The payload b’v1\x00a’ has this full digest:

```
ad9799e8f62da609cdf1fe8e7dfaead172cf5825aefbbc1fabb4343ab6cd2db7
```

Its integer value is:

```
78517978959510909447554025451496255252185340594206639161624781576130937040311
```

Divide by 2**256 to obtain u≈0.6780945008996954. Since0.6780945<0.5 is False, append d1 to train. Now train IDs=[d1], validation IDs=[].

For d2, b’v1\x00b’ hashes to:

```
cfba2d1e3b52d4e9527539e1837c762a6a5f54a4e85ca4c7f93777eced22ed6f
```

Its score is≈0.8114345740135137, so append d2 to train. Now train IDs=[d1, d2]. Finally d9 has the same text as d1, so its payload/hash/score are exactly the same; append it to train too.

Input position	ID	Text	Score u, rounded	u<0.5	Destination
0	d1	a	0.6780945009	False	train
1	d2	b	0.8114345740	False	train
2	d9	a	0.6780945009	False	train

The complete return value is:

```
(
    [
        {'id': 'd1', 'text': 'a'},
        {'id': 'd2', 'text': 'b'},
        {'id': 'd9', 'text': 'a'},
    ],
    [],
)
```

This original example gives **no validation documents**, despite f=.5. That is the correct result, not an implementation failure. Choosing a fixed threshold does not force half of three documents into

validation. For $f = 0$ the result is(all documents,[]); for $f = 1$ it is([], all documents). Do not train a real experiment with an empty validation set merely because this toy checker permits one.

An extended example with both outputs nonempty


To show both branches, add d3 with text'e' and d4 with text'f' after d9. This is an explicitly extended illustration, not a silent change to the supplied driver:

ID	Text	Score u, rounded	Destination at f=.5
d1	a	0.6780945009	train
d2	b	0.8114345740	train
d9	a	0.6780945009	train
d3	e	0.2701366487	validation
d4	f	0.0854167698	validation

The output IDs are train=[d1, d2, d9], validation=[d3, d4]. Entries still contain the original dictionaries. Reverse or reorder the input, and membership stays the same; the order within each returned list follows the new input order.

Partition by a fixed threshold: identical content stays together, counts can vary

Extended fixture: a,b,a,e,f. The original driver has only a,b,a; at fraction=.5 all three enter train.



Input order	train: 3	validation: 2
d1, d2, d9, d3, d4	d1, d2, d9	d3, d4
After reordering		
d4, d9, d2, d3, d1	d9, d2, d1	d4, d3

Membership is unchanged; each output preserves relative input order. Partitioning is not sorting or deduplication.

fraction=0 means all train; fraction=1 means all validation; empty input returns two fresh empty lists.

Figure 121: Threshold, shared-content groups and relative-order preservation

Read the horizontal axis as the content-derived score, not a token position. Points left of.5 validate. One point for'a' represents both d1 and d9. The tables show membership stability and changed relative ordering as two separate properties.

For N documents, the realized count is:

$$N_{\text{val}} = \sum_{i=1}^{N} \mathbf{1}[u_i < f].$$

The indicator contributes1 when its condition is true and 0 otherwise. There is no rounding-to-fN step in this algorithm. Hash scores can be viewed as approximately uniform across varied content groups for split planning, but exact duplicates share a score and move together. Counts, token budgets and source composition must be measured after partitioning. Increasing f with seed/content fixed can only add validation members. Adding a new document does not move existing documents unless the seed, text or protocol changes.

Handle fraction endpoints without teaching a floating-point accident

Mathematically u<1, so $f = 1$ must send every document to validation. Python floating division can round an extremely large hash ratio up to 1.0: `(2**256-1)/2**256` evaluates to 1.0 in the existing environment. Preserve the $f = 1$ contract explicitly rather than relying on a rounded score to remain below1.

An understandable routing condition is: **if f is exactly 1, or u<f, choose validation; otherwise choose train**. Python's or is true when either condition is true and evaluates the second only if needed. At $f = 0$, a nonnegative score never satisfies u<0, so all documents train. No input-validation task is added.

For interior fractions the lesson uses ordinary floating scores and strict comparison. An advanced implementation can compare integers using the fraction's as_integer_ratio rather than rounding u, but that is not required here. Record realized membership and the partition protocol rather than promising bit-exact mathematical thresholds for every floating edge. The figure's printed rounded scores are explanatory; never classify by those displayed decimal strings.

Guided implementation in eight steps

Edit only split_documents in the real assignment, between START LEARNER CODE and END LEARNER CODE. Use four spaces inside the function, eight inside the for loop and twelve inside each routing branch. A return after the loop goes back to four spaces.

1. **Create two separate empty lists.** Name them train and validation. Do not bind both to the same list. Encode seed once as UTF-8 outside the loop because it is unchanged for every document.
2. **Visit documents in their original order.** Syntax:`for document in documents:`. The colon starts the loop body. The first iteration sees d1, then d2, then d9 in the original fixture.
3. **Assemble the payload bytes.** Encode document['text'] as UTF-8, then concatenate the encoded

seed, b'\x00' and encoded text using+. All three operands must be bytes. For d1, inspecting list(payload) gives[118,49,0,97].

4. **Compute the hexadecimal digest.** Use hashlib.sha256(payload).hexdigest(), retaining all64 digits. No random draw, document ID or list position is included.
5. **Convert the digest to an integer.** Use int(hex_digest,16). This means parse in base 16; do not use int(hex_digest) or the integer value of a short prefix.
6. **Compute the normalized score.** Divide that integer by 2**256. For'a', u≈0.6780945009. Do not divide by 256,64 or the number of input documents; do not use2^256.
7. **Route the whole document.** Choose validation when `validation_fraction == 1.0` or `u < validation_fraction`; otherwise train. Use `if`/`else` at eight spaces and `append(document)` at twelve. For the original fixture all three go to train. For the extension, `'e'` enters validation. `append` mutates its list and returns `None`, so do not assign the return value back to the list.
8. **Return the two lists after the loop.** Dedent to four spaces and return train, validation in that order. Empty input still reaches this return. Remove the placeholder raise and leave the supplied driver unchanged.

These hints explain the implementation without placing a completed function in the learner region. Do not add BPE fitting, cleaning, shuffling or tensor batches to this helper.

Run and interpret the checks

```
python exercises/06_02_document_splits.py
```

Expected after implementation:

```
Lesson 06.02 checks passed.
```

The original driver checks fractions0/1, total document count, same-side assignment for the two'a' documents and validation-membership stability after reversing input. It does not check the exact seeded protocol, every output order, non-mutation or both nonempty branches. An incorrect always-train implementation for interior f can pass those original assertions, because their original example is all train. The complete contract and extended worked example therefore matter.

Put BPE and deduplication in the right part of the pipeline




Figure 122: Document partition, training-only fitting and frozen-tokenizer application

Keep whole documents separated, then learn tokenizer rules only from training text and apply that same frozen tokenizer to both sides. BPE training learns frequencies and merges; encoding with fixed rules applies an already learned transformation. Fitting separate train and validation tokenizers would produce different token spaces, while fitting on the combined corpus exposes validation information to a learned preprocessing step.

This helper keeps exact duplicates on one side but does not delete them. Lesson 06.03 handles cleaning and deduplication. If later normalization merges different strings into the same canonical content, reconcile grouping/membership so those equivalents cannot cross the boundary; simply cleaning independently after a raw-text split does not guarantee that. Near duplicates, related documents and benchmark contamination require a broader grouping/audit policy. For a subject-, source- or time-based evaluation objective, choose the appropriate grouping unit rather than assuming raw-text hashing solves it.

Windowing and packing must remain within each final split. Do not concatenate train and validation before making windows. A tokenizer trained elsewhere can be frozen, but that alone does not establish that its original training corpus was uncontaminated. Chapter 07 later specifies evaluation protocols.

For experiment provenance, record the full code commit, split algorithm/version, seed, threshold, ordered document IDs/content fingerprints, data-processing revision, tokenizer version, realized counts/token budgets and evaluation protocol. Keep real corpus data and private storage mappings outside committed teaching material. No dataset is fetched or language model trained in this lesson.

Review questions

Try explaining why two different windows may still leak a passage, why IDs are excluded from this hash, why f=.5 gives no validation examples in the original fixture, and why order-independent membership does not mean sorted outputs. A useful later reconstruction is to predict the extended fixture's two lists before executing your own code.

06.03 Cleaning and deduplication

Method sources

The text-representation standards are Unicode Consortium, 2024; R01 and Yergeau, 2003; R02. Normalization and duplicate-key choices below are explicit corpus policies; Unicode conformance alone does not establish semantic equivalence or dataset quality.

Decide which differences the data policy should preserve

Two documents can display the same word while using different Unicode code points. Another pair may differ only in repeated spaces or line breaks. A cleaning policy specifies which of those differences to remove. Deduplication then checks equality under that policy and keeps one representative.

The policy in this assignment is explicit: normalize Unicode to NFC, collapse whitespace to single

spaces, remove leading/trailing whitespace, reject short results, then retain the first occurrence of each remaining exact string. It is designed for the small prose fixture. It does not judge truth, usefulness, language, toxicity, licensing or overall document quality. A different corpus may require preserving indentation, layout or other distinctions.

Lessons06.01–06.02 identify exact bytes and partition content. This lesson deliberately changes text, so raw and cleaned fingerprints can differ. Version the transformation and reconcile canonical-content groups across train/validation boundaries before interpreting held-out results.

Formulas before implementation

For input document i with text t_i, define:

$$n_i = \text{NFC}(t_i), \qquad c_i = \text{join}_{\text{space}}(\text{split}_{\text{whitespace}}(n_i)).$$

Here n_i and c_i are strings, not tensors or byte counts. Let m=min_characters, and let S_i contain cleaned strings already retained before document i:

$$k_i = \left[\text{len}(c_i) \geq m\right] \wedge \left[c_i \notin S_i\right],$$

$$S_0 = \emptyset, \qquad S_{i+1} = \begin{cases} S_i \cup \{c_i\}, & k_i \text{ is true,} \\ S_i, & k_i \text{ is false.} \end{cases}$$

If k_i is true, append a fresh dictionary containing the original id and cleaned text. Otherwise skip this document and continue scanning. Outputs follow the order of first qualifying appearances. The comparison is >=m; a cleaned length exactly equal to the minimum passes.

The next three figures expand the normalization, whitespace and state-update parts of these formulas separately. There is no matrix multiplication or tensor shape hidden in this helper.

NFC: canonical equivalence before exact comparison

Unicode can represent the accented word café as either:

```
"cafe\u0301": c, a, f, e, COMBINING ACUTE ACCENT
Code points: U+0063 U+0061 U+0066 U+0065 U+0301
Length: 5 code points; UTF-8: 6 bytes

"caf\u00e9": c, a, f, LATIN SMALL LETTER E WITH ACUTE
Code points: U+0063 U+0061 U+0066 U+00E9
Length: 4 code points; UTF-8: 5 bytes
```

These strings are canonically equivalent. NFC, Normalization Form C, applies canonical normalization with composition; this example combines e plus the acute accent into é. Use unicodedata.normalize('NFC', text). It returns a string and leaves the original input object unchanged. NFC

does not guarantee that every combining sequence becomes a single code point. Python normalization API, Unicode normalization specification




Figure 123: Code-point values, canonical composition and separate length metadata

Read cell contents as code points and the labels beneath as their U+ identifiers. The dotted circle only makes the isolated accent visible; it is not an extra character in the input. The figure isolates the core word; outer spaces in the actual first document remain after NFC and are handled by the next operation.

NFC preserves case and accents here: café, cafe and CAFÉ remain distinct strings. It also differs from compatibility normalization, NFKC. For example, fullwidth A stays distinct from ASCII A under NFC. Choosing NFC is a policy choice, not a request to lowercase, transliterate or remove accents.

Whitespace collapse: understand split and join independently

The assignment uses the no-argument string method split(). It treats runs of recognized whitespace as separators and discards empty edge chunks. Those chunks are ordinary strings, not BPE tokens. Then ' '.join(chunks) places one ASCII space between adjacent chunks.

For the original third document:

```
Input:             "a\n\tb"
NFC result:        "a\n\tb"
split() result:    ['a', 'b']
' '.join(...) :    'a b'
Cleaned length:   3
```

The newline has code point U+000A, the tab U+0009. The result contains one U+0020 space. A whitespace-only string splits to[]; joining that empty list produces' '. No extra strip() is needed after this exact split/join operation. Python split/join semantics




Figure 124: Whitespace characters, split chunks and the single-space result

The top row shows actual characters with escaped displays for newline and tab. The middle box contains a list of chunks. The bottom row is the resulting string, with count metadata underneath. These are three different kinds of object; do not return the middle list as the cleaned text.

split(' ') is a different operation: it uses a literal-space separator and can retain empty chunks. It also does not split a newline/tab sequence the way split() does. Replacing only double spaces misses other whitespace and long runs. Use the specified no-argument operation.

This removes paragraph boundaries, indentation and repeated spaces. It can damage code, tables and poetry. The toy policy makes those losses visible; it does not recommend applying this transformation blindly to every training domain. Zero-width characters are not automatically all whitespace, and this helper is not a general invisible-character sanitizer.

Function contract, return structure and ownership

```
def clean_deduplicate(documents: list[dict],
                      min_characters: int = 1) -> list[dict]:
```

Input / output	Contract
documents	Ordered list of dictionaries containing id:str and text:str; IDs are stable document labels
min_characters	Positive Python int m; compare with len of the cleaned string
Return	New list of new dictionaries, each containing exactly id and text
id field	Preserve the first retained occurrence's original ID
text field	Store the cleaned canonical string, not the original spelling

The driver uses unique IDs, including the strings'0','1','2','3'. Duplicate detection uses cleaned text, not ID. The input list and all input dictionaries/content must remain unchanged. Output dictionaries must be fresh, unlike06.02's shallow partition of original dictionaries. Strings are immutable; no deep copy of each string is required. Extra input metadata is not copied into this assignment's two-field output.

Despite the argument's name, Python len(str) counts Unicode code points, not UTF-8 bytes, BPE tokens or general user-perceived grapheme clusters. For cleaned café, len=4 and UTF-8 length=5. For'a b', len=3 includes the internal space. Measure after cleaning: outer whitespace must not allow short content to pass. No new input-validation task is added.

Complete original trace, one document at a time

The unchanged supplied driver creates:

```
documents = [
    {'id': '0', 'text': '  cafe\u0301  '},
    {'id': '1', 'text': 'café'},
    {'id': '2', 'text': 'a\n\tb'},
    {'id': '3', 'text': ' '},
]
```

Use the default min_characters=1. At the start seen=set() and result=[].

Document0: NFC changes' cafe\u0301 ' into' café ', retaining the four edge spaces. split() produces['café']; joining gives'café'. Its cleaned length4 passes1 and it is not in seen. Add'café' to seen; append a new dictionary with id'0'.

Document1: NFC and whitespace collapse leave'café'. Length4 passes, but seen already contains that cleaned text. Skip this occurrence. The first ID remains'0'; do not replace it with'1'.

Document2: NFC leaves'a\n\tb'; split/join gives'a b'. Length3 passes and the text is new. Add it to seen and append a fresh dictionary with id'2'.

Document3: A space splits to[], then joins to' '. Length0 fails the positive minimum, so skip it without adding it to seen. Processing ends after the loop.

Canonicalize first, then check length and duplicates: retain the first occurrence

Four original documents; min_characters=1. seen stores retained cleaned text, not document IDs.

id	Raw text repr	Cleaned text	len	seen before	Decision
0	`" cafe\u0301 "`	'café'	4	set()	**keep**
1	`"café"`	'café'	4	{'café'}	**duplicate**
2	`"a\n\tb"`	'a b'	3	{'café'}	**keep**
3	`" "`	"	0	{'café', 'a b'}	**too short**

Final seen = {café, a b}; output retains IDs0 and2 in fresh dictionaries.

min_characters=1 → [{'id':'0','text':'café'}, {'id':'2','text':'a b'}]

min_characters=4 → [{'id':'0','text':'café'}]

Measure length after cleaning: café has4 code points and5 bytes; a b has3 code points.

Figure 125: Original four-row state trace and two minimum-length results

Read seen before each row's decision. It contains only previously retained canonical text. In Python the empty set is set(); {} creates an empty dictionary. Nonempty set displays here illustrate membership, not output order.

The complete return value is:

```
[
    {'id': '0', 'text': 'café'},
    {'id': '2', 'text': 'a b'},
]
```

With min_characters=4, document0 still passes at equality, document1 remains a duplicate, document2 now fails because3<4 and document3 fails because0<4. The complete result is:

```
[{'id': '0', 'text': 'café'}]
```

Empty input gives[]. An all-whitespace corpus also gives[] for any positive minimum. Do not hard-code these strings or IDs; they explain the supplied fixture.

Track retained strings with a set, preserve order with a list

seen answers whether cleaned content was retained earlier; result records which representatives were retained and in what order. A set keeps unique members and supports membership tests; it is not the ordered output.

Use seen=set() outside the loop, cleaned in seen to test, and seen.add(cleaned) after both rejection checks pass. Do not reset seen on every iteration, add the raw text instead, or track only document IDs. Applying exact deduplication before normalization would miss the original pair's equivalence.

continue skips the rest of the current for iteration and resumes at the next document. It does not exit the whole function or loop. break would end the scan and lose later valid documents; return inside the loop would return too early. A row can be rejected with one condition combining shortness or prior membership, or two separate if checks. The plan below separates them for readability.

The first-occurrence rule depends on input order. Swapping two equivalent inputs can change the retained ID while preserving the cleaned content set. It does not select the best licensed/highest-quality/source-priority representative. In production that choice needs its own policy and audit trail.

Why deduplication changes training weight

For an illustrative objective averaging one loss per document, let N be the number of length-qualified documents before deduplication and ℓ_i the loss for document i. Group identical canonical text under index g; n_g is the number of documents in that group and $\bar{\ell}_g$ their mean loss. Repeated groups then receive weight proportional to multiplicity:

$$L = \frac{1}{N}\sum_{i=1}^{N} \ell_i = \sum_g \frac{n_g}{N}\bar{\ell}_g.$$

If the same canonical text appears twice and another once, their document weights are 2/3 and 1/3; after keeping one each they become1/2 and 1/2. This explains how repetition changes sampling emphasis without claiming all repetition is undesirable. Real language-model training often averages token losses and uses a sampling/packing policy, so document length and sampling decisions also affect the effective weights. Deduplication alone does not guarantee a better model or remove every form of memorization.

The three length-qualified rows in the preceding state trace give this concrete illustration:

Canonical text	Before deduplication	After deduplication
café	2 of 3 documents: weight2/3	1 of 2 documents: weight1/2
a b	1 of 3 documents: weight1/3	1 of 2 documents: weight1/2

For this small exact-string set, membership compares actual cleaned strings. Python may hash strings internally, but set membership still resolves equality; it is not an unchecked digest-only identity rule. Corpus-scale near-duplicate indexing is a later extension, not a requirement to implement MinHash or similarity thresholds here.

Keep canonical groups separated across train and validation

For a new experiment, the fixed cleaning policy can identify canonical content groups before content-based partitioning. Keep one representative or ensure every equivalent member stays on the same side, then fit tokenizer rules only on training text. This deterministic per-document policy does not learn statistics from held-out examples; any later fitted filters or transformations must still respect the training-only fitting boundary.


A concrete counterexample uses06.02's seed='v1', fraction=.5:

Original text	Raw-text score	Original side	Cleaned text
'café'	0.5363690129	train	café
'café'	0.0129355996	validation	café

Cleaning each split separately leaves the same canonical text on both sides, because their local seen sets never see each other. For a fresh canonical-content split, both become café, the first representative is retained, and its canonical score0.0129355996 puts it in validation. Only one toy document remains; this is a conflict illustration, not a viable training corpus.

Cleaning can merge content across splits: separate per-split deduplication is insufficient

Separate two-document counterexample: Lesson06.02 seed="v1", fraction=.5. Right side is a fresh-run workflow.



For existing frozen splits, document the cross-split conflict policy; do not silently change held-out membership.

Retain raw/cleaned fingerprints and the policy version. Exact deduplication does not detect every paraphrase.

Figure 126: Verified cross-split duplicate counterexample and canonical-group workflow

If splits are already frozen, apply a documented conflict policy instead of silently changing held-out membership. For example, a policy can preserve the held-out set and remove matching training copies, while recording that change. Combining existing splits and blindly keeping the first row may delete held-out examples or alter the evaluation population. Any repartition produces a new dataset/evaluation version. The core function has no split labels and cannot enforce these cross-split decisions by itself.

Exact canonical equality does not catch all near duplicates, paraphrases, related source documents or benchmark contamination. Keep raw text artifacts separately and record raw/cleaned fingerprints, original-to-representative ID mappings, transformation order/version, Unicode database/runtime version, minimum length, ordering rule, input/output counts and removal reasons. The current function returns only the requested cleaned records; it does not create that audit manifest automatically.

Guided implementation in eight steps

Edit only clean_deduplicate in the actual assignment, between START LEARNER CODE and END LEARNER CODE. Function-body statements use four spaces, the for body eight and conditional bodies twelve.

1. **Create persistent containers.** At four spaces initialize seen with set() and result with[]. They must be outside the loop so earlier retained content remains remembered.
2. **Visit each document in order.** Write `for document in documents:` at four spaces. Its repeated body starts at eight. The original IDs arrive as'0','1','2','3'.
3. **Normalize Unicode.** Read document['text'] and call unicodedata.normalize('NFC', text), storing a local normalized string. For the first row the result is' café ', with spaces still present. unicodedata is already imported.
4. **Collapse whitespace.** Call normalized.split() with no separator; then ' '.join(…) to form a cleaned string. The first row becomes'café'; the third'a b'; the last' '. Preserve this string for every later check and output.
5. **Reject short cleaned content.** At eight spaces test len(cleaned)<min_characters. At twelve spaces continue to the next document. Use strict< so length exactly m passes. Do not count encoded bytes or raw text.
6. **Reject already retained cleaned content.** Back at eight spaces, test cleaned in seen. A twelve-space continue skips the duplicate. In the original trace row 1 is skipped while row 2 remains reachable.
7. **Record an accepted representative.** Back at eight spaces, add cleaned to seen, then append a new dictionary with exactly'id' from document['id'] and'text' as cleaned. Do not append the original dictionary or update its text in place. add and append change their containers and return None; do not reassign containers to those return values.
8. **Return after the loop.** Dedent to four spaces and return result. Remove the placeholder raise, preserve the supplied driver, and confirm empty input still reaches this return.

The hints explain the API calls and flow without filling the learner core. This function does not need a tensor, RNG, SHA-256 digest, sorting, lowercasing or extra normalization form.

Run and interpret the checks

```
python exercises/06_03_clean_deduplicate.py
```

Expected after implementation:

```
Lesson 06.03 checks passed.
```

The original driver checks the complete default output, unchanged input, the minimum4 result and empty input. It does not explicitly cover all Unicode forms, case preservation, fresh dictionary identity, input-order representative changes or cross-split reconciliation. Those requirements and boundaries remain part of the documented contract.

The computation and original driver are preserved.

Review questions

Try explaining why the original first two texts become equal, why café passes minimum4 but'a b' does not, why an empty set is written set(), why continue cannot be replaced by break, and why two independent per-split seen sets miss the cross-split example. A useful later reconstruction is to trace seen and result before running your own implementation.

06.04 Frozen tokenizer and special IDs

Method sources

The learned subword vocabulary context is Sennrich et al., 2016; R03, with a byte-level language-model variant in Radford et al., 2019; R25. Freezing this book's tokenizer and checking exact round trips are additional experiment-identity requirements.

Give every model input a stable meaning

Chapter 02 built a byte-level BPE tokenizer. Its training phase learned merge rules and allocated IDs. Its encoding phase applied those existing rules to new text. This lesson puts that encoder into a document pipeline and adds an explicit end-of-sequence token, **EOS**.

Why freeze the tokenizer? The model learns what particular IDs mean. If ID 256 meant the bytes b'ab' during training but meant b'ac' during validation, looking up the same embedding row would no longer represent the same content. A valid comparison needs the same tokenizer version, including its vocabulary, merge order, preprocessing policy and special-ID mapping. Fit learned tokenization rules on training data, then reuse the fixed artifact for validation and inference.

Here **frozen tokenizer** means its rules and ID assignments stay fixed. The model's embedding vectors and prediction weights can still train. Freezing this mapping is different from disabling gradients for an embedding parameter.

Prerequisites are the actual completed 02.05 encoder, 02.06 decoder, Python lists and for loops. The supplied encode_bpe helper is already loaded in the exercise. No new environment, download, tokenizer training or tensor implementation is needed. Lessons06.01–06.03 identify, partition and clean documents; this helper receives their text strings.

Define ordinary IDs and the appended structural ID

Let M denote the fixed learned BPE merge rules. For document index d, define:

$$u_d = \text{encode_bpe}(text_d, M), \qquad z_d = u_d \| [e], \qquad |z_d| = |u_d| + 1.$$

Symbol	Meaning	Actual Python object
text_d	One document's ordinary text	str, one element of texts
M	Fixed pair-to-new-ID rules, with earlier allocated IDs having earlier merge priority	merges: dict[tuple[int, int], int]
u_d	Ordinary BPE IDs, before any structural marker	A fresh list[int] from encode_bpe
e	Reserved EOS ID, outside the ordinary vocabulary	eos_id: int
z_d	The complete document IDs, with one EOS appended	list[int]
d	Document index; unrelated to embedding width D	Conceptual index

The symbol $\|$ means sequence concatenation: keep the ordinary IDs in order, then add one integer e at the end. It is not arithmetic addition. For example, [256,256] concatenated with [257] gives [256,256,257], not [513,513].

Precondition: e is not any byte-token or learned-merge ID. Therefore the ordinary encoder never emits e, and appending it introduces exactly one structural EOS per document. No text matching or special-token parser is used by this course's encode_bpe. Recognition of special spellings in external libraries depends on their configuration; do not assume their defaults match this exercise.

EOS means **end of sequence**; here it marks a document ending. PAD means **padding**, used to fill otherwise unused tensor positions later. BOS means **beginning of sequence**. Conversation role markers can identify roles such as user or assistant. These are possible structural conventions; this assignment inserts only EOS and does not add PAD, BOS or role tokens.

Follow the complete original example

Use exactly the original fixture:

```
texts = ['abab', 'ac', '']
```

```
merges = {(97, 98): 256}
eos_id = 257
```

This tokenizer has **one learned rule**: (97,98) becomes 256, whose bytes are b'ab'. The base byte IDs 0 through255 remain ordinary tokens. In some Chapter 02 training examples a second rule also allocated257; that is a different tokenizer version. If257 were a learned token, we could not also reserve it as EOS. Do not import that second rule into this fixture.



Figure 127: Document-by-document bytes, fixed BPE IDs and appended EOS

Read each row left to right. Gray cells are byte IDs before merging; teal cells are ordinary BPE IDs; orange cells are appended EOS. The numbers in cells are contents. Length labels sit outside the cells. The output is a nested list with lengths3,3,1, not a tensor with shape(3,3).

For document0, text is ‘abab’.

1. UTF-8 produces bytes with values [97,98,97,98].
2. Apply the learned (97,98) rule at both non-overlapping occurrences: [256,256]. There is no rule for (256,256), so encoding stops. It cannot invent another token.
3. Append the single reserved integer257: [256,256,257]. The outer result becomes [[256,256,257]].

For document1, ‘ac’ produces [97,99]. There is no learned (97,99) rule, so the body stays [97,99]. Appending257 gives [97,99,257]. The outer result now has two document lists.

For document2, the empty string produces no bytes and no ordinary IDs: []. It is still a document, so appending257 gives [257]. The final return is:

```
[[256, 256, 257], [97, 99, 257], [257]]
```

The original texts and merges stay unchanged. Each inner list is fresh. Repeated documents can have equal list contents while remaining different list objects.

An empty corpus is different from an empty document:

```
texts=[]    → []       # zero documents, no loop iterations
texts=['']  → [[257]]  # one document, one EOS
```

Literal text and structural EOS take different paths

Suppose the document literally contains the five characters ‘<eos>’. Its visible spelling does not instruct our byte encoder to insert a control ID.

$$\mathrm{UTF8}(\texttt{"<eos>"}) = [60, 101, 111, 115, 62], \qquad z = [60, 101, 111, 115, 62, 257].$$




Figure 128: Literal five-character spelling versus the appended structural ID

Read downward: five characters become five ordinary byte IDs because the single ab rule does not match. The formatter then appends257. There are six output IDs: five body IDs and one EOS. Decoding only the body returns the literal text ‘<eos>’. The final 257 carries document structure; it was not produced from those five characters.

Similarly, ‘你’ produces ordinary IDs [228,189,160] under this fixture, followed by 257. Byte-level BPE supports this text using its base byte vocabulary without inventing a learned merge. The three ordinary bytes must be joined before UTF-8 decoding.

Special-token insertion should be an explicit formatting policy. External tokenizers often express structural insertion as post-processing; the configured spelling-to-ID mapping must agree with the vocabulary. The course’s append step is our small explicit version of that policy. Official Tokenizers template-processing explanation

Calculate model vocabulary capacity before lookup

Let $\mathcal{J}$ contain all allocated ordinary and reserved IDs. Since a table with V rows has indices0 through $V-1$, every allocated ID must satisfy:

$$0 \le i < V_{\text{model}} \quad (i \in \mathcal{J}), \qquad V_{\text{model}} \ge 1 + \max \mathcal{J}.$$

For this fixture, ordinary IDs are 0…256 and EOS is 257. The smallest sufficient capacity is 258. This is a capacity calculation, not an upper limit of 256 or258 for language models. If IDs have gaps, counting mapping entries is insufficient: the table must still cover the largest allocated ID.

Separate ID, row count and vector width: max ID 257 needs at least 258 rows

Schematic uses D=4. Cells contain symbolic vector components, not measured weights or shape metadata.

Allocated ID meanings

0⋯255: base byte tokens

256: merged token, bytes b"ab"

257: EOS structural token

$V_{\text{model}} \geq 1 + \max \mathcal{I} = 258$

Embedding table E: shape = (258,4)

	d=0	d=1	d=2	d=3
0	$e_{0,0}$	$e_{0,1}$	$e_{0,2}$	$e_{0,3}$
…	…	…	…	…
255	$e_{255,0}$	$e_{255,1}$	$e_{255,2}$	$e_{255,3}$
256	$e_{256,0}$	$e_{256,1}$	$e_{256,2}$	$e_{256,3}$
257	$e_{257,0}$	$e_{257,1}$	$e_{257,2}$	$e_{257,3}$

257 is an ID; 258 is minimum row count; D=4 is row width. Middle rows omitted: the actual table has 258 rows, not 5.

[256,256,257]: sequence length L=3 → embedding lookup shape=(3,4).

ID 256 selects the same row twice; the model needs at least 258 logits per position.

If PAD=258 is additionally reserved, minimum capacity becomes 259; D need not change.

The ID mapping/rules are frozen; the embedding parameters can still train.

Figure 129: Allocated IDs, symbolic embedding rows and dimensions

Read the left panel as ID meanings. On the right, an illustrative embedding table has shape(258,4); only selected rows are drawn. The dots omit rows, not features. Cell symbols such as $e_{257,0}$ stand for parameter values, not measured weights. Shape is printed above the table.

Quantity	This example	Meaning
Largest allocated ID	257	An integer used to select a row or target class
Minimum V_{model}	258	Number of available ID rows/classes
Embedding width D	4, chosen only for the diagram	Number of coordinates per embedding vector
Sequence length for ‘abab’ with EOS	3	Number of positions in this document

With $E \in \mathbb{R}^{258\times D}$, looking up [256,256,257] gives a tensor with shape(3, D). The repeated256 selects the same embedding row twice. For batches later, IDs have shape(B, T), embeddings(B, T, D), and logits(B, T, V_model). Do not confuse any of these axes just because two numerical sizes happen to match. PyTorch names the embedding row count num_embeddings and the width embedding_dim. Official Embedding reference

If we additionally reserve PAD=258 in a future configuration, minimum capacity becomes 259 while D may stay the same. That extension is not in the current fixture or function. Updating an existing trained model’s vocabulary requires a coordinated artifact/table change; this assignment performs none of that resizing.

Connect EOS to the next-token objective

EOS is represented by its own prediction class. For a document sequence z with length L, form the familiar shifted pairs:

$$X = z[:-1], \qquad Y = z[1:], \qquad |X| = |Y| = L - 1.$$


For z=[256,256,257], X=[256,256] and Y=[256,257]. The second position sees the prefix [256,256] and is trained to predict EOS:

$$\ell_{\text{last}} = -\log p_\theta(257 \mid 256, 256).$$

EOS becomes a prediction target: connect document endings to next-token training

Same "abab" document, encoded z=[256,256,257]. This shows a within-document shift only.

$$X = z[:-1], \qquad Y = z[1:]$$



$$\ell_{\text{last}} = -\log p_\theta(257 \mid 256, 256)$$

The final body position learns to predict EOS; 257 is not a UTF-8 byte value.

Handle structural IDs first; join ordinary-token bytes, then UTF-8 decode.

EOS itself does not reset attention or caches; a generation loop must check whether to stop.

Figure 130: EOS as the final next-token target

The arrows align each input position with its next-token target. Orange marks the final EOS target. This is a document-local illustration: an empty document z=[257] has zero such local pairs. Later packing defines transitions in a concatenated stream and may differ at document boundaries.

EOS does not itself stop a Python generation loop, reset a KV cache or enforce an attention boundary. The generation code checks eos_id to decide when to stop, as in03.17. Lesson 06.05 explicitly chooses a packing policy that allows cross-document context; its toy IDs are a different fixture. An isolation policy would need corresponding masks/position/cache handling. Our function only returns document lists.

Define the exact assignment interface

```
def encode_documents(
    texts: list[str],
    merges: dict[tuple[int, int], int],
    eos_id: int,
) -> list[list[int]]:
```

texts is an ordered list of ordinary Unicode strings, including possibly ' '. merges contains fixed learned ordinary pair-to-ID rules. eos_id is a Python integer reserved outside the ordinary vocabulary. The stated valid-input assumptions do not require new validation branches.

Return a new outer list with one fresh list[int] per input document, in the same order. Each list contains encode_bpe(text, merges)'s ordinary IDs followed by one eos_id. Lengths can differ. Preserve texts and merges; do not clean, sort, deduplicate, split, concatenate documents, pad, train new rules or convert the result to tensors here.

The supplied line encode_bpe=load('02_05_bpe_encode.py','encode_bpe') loads the actual previous encoder. Use that function and these parameter names. You are connecting an existing encoder to document formatting, not rewriting Chapter 02.

Guided implementation beside the learner region

Edit only the learner region in the shared exercise. Its detailed English comments repeat these steps. Write the implementation yourself; the supplied run_checks stays intact.

1. **Create the outer result list.** At four spaces inside encode_documents, initialize a new empty list, for example result. It initially holds zero documents. It must not be the input texts list.
2. **Start the document loop.** At four spaces use for text in texts: . The colon starts a repeated body; indent that body to eight spaces. text is a string such as 'abab', not a document dictionary or token ID. for runs once per element; with texts=[], it runs zero times.
3. **Encode one body with fixed rules.** Inside the loop call encode_bpe(text, merges) and save its returned fresh list, for example ids. For the first document the intermediate value is [256,256]. Do not call train_bpe or modify merges.
4. **Append the structural ID to that inner list.** Still at eight spaces, use the inner list's .append method with eos_id, an integer. The first ids becomes [256,256,257]; for empty text [] becomes

[257]. No string comparison to '<eos>' is needed.

5. **Append the whole inner list to the outer list.** Still inside the loop, add ids as one element of result. After the first iteration result is [[256,256,257]], not [256,256,257]. Append preserves the document grouping; extending result with ids would flatten it.
6. **Return after all documents.** Dedent to four spaces and return result outside the loop. The final value is the three-list example above. The return must also execute for zero iterations; placing it inside the loop returns only the first document and fails empty input.
7. **Keep mutations local.** .append changes its list in place and returns None. Use the two append calls as separate statements. Do not assign their return values or write result.append(ids.append(eos_id)), which would append None to the outer list. Only fresh output lists change; texts and merges do not.
8. **Remove the placeholder raise and run the unchanged driver.** Preserve the supplied helper import, START/END markers and driver. No new if, continue, break, special-token detector or tensor dimension is needed for this wrapper.

Decode ordinary bytes after interpreting structure

The existing02.06 decode_bpe expects ordinary token IDs present in its byte vocabulary. Its entry256 maps to b'ab'; it has no ordinary byte entry for the reserved257 in this fixture. Feeding the full [256,256,257] directly to that decoder therefore raises KeyError.

For a known single document produced by this wrapper, identify and remove its final EOS as structure, decode the remaining ordinary [256,256], and recover 'abab'. For a stream containing several structural markers, interpret those markers according to its format and decode the ordinary spans; do not blindly discard arbitrary integers. Join the vocabulary's byte chunks before UTF-8 decoding, particularly for multi-byte text such as '你'.

Do not call bytes([256,256,257]): bytes accepts raw byte values 0…255, whereas these are vocabulary IDs. Token256 maps to two bytes through the vocabulary; EOS257 represents structure. Literal body bytes for '<eos>' should remain and decode back to those characters.

Run, inspect and record evidence

```
python exercises/06_04_frozen_tokenizer.py
```

After implementation and completed BPE prerequisites:

```
Lesson 06.04 checks passed.
```

The unchanged original driver checks the three-document output, unchanged merges, a non-special literal '<eos>' body and empty texts. It does not explicitly check Unicode round trips, all fresh-list identities, training/validation reuse, embedding capacity or decoding. Those are explained contracts and targeted preparation checks, not claims that the driver alone proves them. An unfinished prior BPE helper is a learner prerequisite, not a reason to install a new environment.

Before running your own extra examples, predict outputs for [’ ‘,’abab’], [‘你’] and two copies of ‘<eos>’. Explain which list changes at each append, why257 cannot also mean b’abab’, and why freezing the tokenizer does not freeze E.

For future experiments, version the vocabulary/merges, special-ID mapping, preprocessing policy, implementation commit and tokenizer artifact checksum together. Pair that record with the data version, model vocabulary capacity and checkpoint. The fixture here is toy-frozen-bpe-eos-v1: UTF-8 bytes, one (97,98)→256 rule, EOS257, and no normalization in this helper. It has no external corpus, trained language-model checkpoint, training budget or language-quality evaluation.

06.05 Packing and supervision masks

Turn document lists into rectangular next-token batches

Lesson 06.04 returns one token list per document, including its EOS. The lengths can differ. A model batch needs a rectangular input tensor, a matching target tensor and a clear statement of which targets are real. Packing groups token transitions into fixed-width rows, reducing space wasted at document ends; padding fills any unused slots in the final row.

This first policy is intentionally explicit: concatenate the documents within one split, preserve their existing EOS tokens, then divide adjacent input/target pairs into rows. Context across a document boundary is permitted inside a row. EOS marks an ending but does not itself block attention. Training and validation must be packed separately. This helper never combines their streams, learns BPE rules, adds EOS again, trains a model or downloads data.

Prerequisites are Python lists/slices/loops, the shifted next-token pairs from 03.19, tensor shape/dtype, causal attention and the structural-ID concepts in06.04. No unfinished model function is called. The assignment creates data tensors only; the next lesson consumes the supervision mask in the loss.

First resolve the handoff: what does documents contain here?

Earlier lessons use **document** for a piece of source material. Its Python representation changes as it moves through the pipeline. The repeated parameter name did not make that transition clear enough. A document record is not passed directly from 06.03 into pack_tokens.

Stage	Exact interface	One element actually contains
06.03 cleaning	clean_deduplicate(documents, …)	A dict such as {“id”:“A”,“text”:“abab”}
Caller extracts text	[record[“text”] for record in records]	A str such as “abab”
06.04 encoding	encode_documents(texts, merges, eos_id)	Input str; output one list[int] per document
06.05 packing	pack_tokens(documents, context_length, pad_id)	A list[int], such as [256,256,257]

Stage	Exact interface	One element actually contains
06.06 training	pretrain(model, x, y, mask, updates, learning_rate)	Already packed tensors, not document dictionaries

Documents do not change type automatically: the caller connects records, texts and token lists

The same A/B documents: 06.03 returns records; 06.04 receives texts; 06.05 receives encoded ID lists.

1. records: list[dict]

[{"id":"A","text":"abab"}, {"id":"B","text":"ac"}]

↓ [record["text"] for record in records]

2. texts: list[str]

["abab", "ac"]

↓ encode_documents(texts, merges={(97,98):256}, eos_id=257)

3. token_documents: list[list[int]]

[[256,256,257], [97,99,257]]

pack_tokens loops over one list[int] at a time; document is not a record dictionary here.

extend([256,256,257])

→ [256,256,257] adds integer IDs

extend({"id":"A","text":"abab"})

→ ["id","text"] adds keys!

A variable name does not determine its type; inspect the object passed by the caller.

Metadata stays in records/manifests; pack_tokens returns no document-ID mapping. Track it separately if needed.

Figure 131: The same records become texts and token lists through explicit caller operations

Read the three numbered boxes from top to bottom as source records, extracted text strings and encoded token-ID lists. The arrows name the operations that connect them. Python does not change a dictionary into token IDs because a variable is named document. The caller must perform the extraction and encoding explicitly.

For a complete small handoff, assume these are the already cleaned records from one split:

```
records = [{"id": "A", "text": "abab"},
           {"id": "B", "text": "ac"}]
texts = [record["text"] for record in records]
merges = {(97, 98): 256}
token_documents = encode_documents(texts, merges, eos_id=257)
x, y, mask = pack_tokens(token_documents, context_length=3, pad_id=258)
```

This is supplied **caller wiring**, not a replacement for either exercise function. Read the list comprehension as: visit each record dictionary, look up its "text" value, and collect those strings into a new list. texts becomes ["abab","ac"]. The unchanged 06.04 helper then returns token_documents=[[256,256,257],[97,99,257]]. The id metadata remains in records; pack_tokens neither receives it nor returns a document-ID provenance map. Keep such mappings separately when an experiment needs them.

Inside your existing function, the first loop iteration assigns `document=[256,256,257]`. `stream.extend(document)` adds those three integers. The second iteration assigns `document=[97,99,257]` and appends those three integers to the same fresh stream. The final value is `[256,256,257,97,99,257]`. The name `document` could locally be `token_ids_for_one_document`; the object would still be the same `list[int]`. The public signature stays unchanged so existing calls and checks remain aligned.

What if a dictionary were passed directly? Python iterates its keys:

```
wrong_stream = []
wrong_stream.extend({"id": "A", "text": "abab"})
# wrong_stream is ["id", "text"], not text bytes or token IDs.
```

That is outside pack_tokens' input contract and would fail later when these strings are converted to long tensors. The annotation list[list[int]] describes the required input; it does not automatically extract text or encode it. Changing the packing loop to document["text"] would instead break the current valid token-list input and still leave text unencoded. Official Python list/dictionary behavior

The original packing driver uses [[1,2,4],[3,4]], a separate hand-written ID fixture. It does not call a tokenizer and therefore does not demonstrate this handoff. Its EOS4/PAD0 must not be mixed with the continuous BPE example's EOS257/PAD258. Keep the simple driver for checking packing, and use the continuous example to understand how the real components connect. The next 06.06 lesson carries exactly these BPE IDs into the loss.

Count source pairs before choosing a batch shape

Write the concatenated stream as s with N token IDs. A target requires the next source token, so there are $P = N-1$ valid adjacent pairs:

$$s = \text{concat}(documents), \quad N = |s|, \quad P = N - 1, \qquad (s_j, s_{j+1}) \quad \text{for } 0 \le j < P.$$

Symbol	Meaning	Example
s	Flat Python list of token IDs	[1,2,4,3,4]
N	Number of source tokens, including existing EOS	5
P	Number of valid adjacent pairs	4
T	context_length, the output row width	3
B	Number of output rows, calculated from P and T	2
b, t	Zero-based output row/column indices	$b = 0,1$; $t = 0,1,2$
p	pad_id, the fill value	0

An ID value is not a size. In this fixture,4 means EOS. Separately, P happens to equal4. Those numbers have different roles. The toy vocabulary is also different from 06.04's byte/BPE IDs; do not interpret4 as EOS257 or add another marker.

Count adjacent transitions first: 5 source tokens give 4 input/target pairs

Original documents=[[1,2,4],[3,4]]; 4 is EOS, 0 is PAD. Token values are not counts.

Document A **Document B**

s[0]	s[1]	s[2]	s[3]	s[4]
1	2	4	3	4
		EOS		EOS

Source-pair index j	Input → next target	Output slot (b,t)
j=0: s[0] → s[1]	1 → 2	(0,0)
j=1: s[1] → s[2]	2 → 4	(0,1)
j=2: s[2] → s[3]	4 → 3	(0,2)
j=3: s[3] → s[4]	3 → 4	(1,0)

At j=2,4→3 crosses documents: this lesson explicitly permits it. EOS does not mask attention.

Final s[4]=4 is a target only; s[5] does not exist, so there is no fifth valid pair.

Figure 132: Source indices and all four adjacent transitions

Read the source positions s[0]…s[4] separately from their token contents. The lower table lists transitions by source index j. Even if two pairs have equal values in another example, their source positions still count separately. The final token s[4] can be a target but has no next token, so it cannot create another valid pair.

Each row holds at most T pairs. To retain a partial final row, round the row count upward:

$$B = \left\lceil \frac{P}{T} \right\rceil = \left\lfloor \frac{P + T - 1}{T} \right\rfloor.$$

For positive integers, Python `(P + T - 1) // T` computes this without floating division; `//` is floor division. Here `(4+3-1)//3=2`. Using `P//T=1` would drop the last pair. B is not the number of documents: the same two documents with $T = 1$ require four rows.

Define the three outputs without indexing beyond the stream

Let j=bT+t. Define the supervision mask and padded contents piecewise:

$$m_{b,t} = \mathbf{1}[j < P], \qquad X_{b,t} = \begin{cases} s_j & j < P \\ p & j \geq P, \end{cases} \qquad Y_{b,t} = \begin{cases} s_{j+1} & j < P \\ p & j \geq P. \end{cases}$$

The indicator is 1/True when that source pair exists and 0/False otherwise. The formula deliberately does not read s[j] or s[j+1] at padded positions. X, Y are torch.long tensors; mask is torch.bool. All three shapes are(B, T). Their cell contents are IDs or booleans, not dimensions or embedding vectors.

For row b, its start and number of real pairs are:

$$a_b = bT, \qquad n_b = \min(T, P - a_b).$$

Fill only its first n_b slots. In Python's end-exclusive slices, those bodies are:

```
X row prefix ← stream[start : start+n]
Y row prefix ← stream[start+1 : start+n+1]
mask prefix  ← True
```

The shifted slices have exactly the same length n. There is no need to pad the stream first or invent a final EOS→PAD target.

Complete original worked example

Use the exact supplied inputs:

```
documents = [[1, 2, 4], [3, 4]]
context_length = 3
pad_id = 0
```

Concatenation preserves existing markers: stream=[1,2,4,3,4]. Therefore $N = 5$, $P = 4$, $T = 3$, $B = 2$. Initialize X and Y to zero-filled long tensors with shape(2,3), and mask to a false bool tensor of the same shape. These must be separate tensors.

j	Source transition	Row b	Column t	Real target?
0	1→2	0	0	True
1	2→4	0	1	True
2	4→3	0	2	True
3	3→4	1	0	True

Row0 starts at 0. There are min(3,4−0)=3 pairs left to place. The input slice stream[0:3] is[1,2,4], and target slice stream[1:4] is[2,4,3]. Mark all three mask cells True.

Row1 starts at 3. There are min(3,4−3)=1 pair to place. The input slice stream[3:4] is[3], and target slice stream[4:5] is[4]. Write only column 0 and mark it True. Leave columns1 and 2 padded and False.

```
X = [[1, 2, 4],
     [3, 0, 0]]
Y = [[2, 4, 3],
     [4, 0, 0]]
mask = [[True, True,  True],
        [True, False, False]]
```

These are printed contents; the returned objects are tensors. The return order is(X, Y, mask).

Group pairs into rows, then pad: contents, shape and dtype are separate

N=5, P=N−1=4, T=3, B=ceil(4/3)=2. Each row holds at most 3 source pairs.

X: shape=(2,3), dtype=torch.long

	t=0	t=1	t=2
b=0	1	2	4
b=1	3	0	0

Y: shape=(2,3), dtype=torch.long

	t=0	t=1	t=2
b=0	2	4	3
b=1	4	0	0

Row 0: j=0,1,2. Row 1: j=3 plus two padding slots.

mask: shape=(2,3), dtype=torch.bool

True	True	True
True	False	False

True = target exists; include its loss

False = padding slot; exclude its loss

4 valid slots / 6 total slots; every original adjacent pair appears exactly once.

B counts rows. The same two documents need four rows when T=1.

Figure 133: Packed input, shifted target and supervision-mask tensors

The two upper tables contain integer IDs; the bottom table contains booleans. Teal cells hold real pairs; gray cells are padding. Shape and dtype appear above the tables. There are four valid target slots out of six allocated slots. A valid source transition appears once, even though a token can naturally occur as one pair's target and the next pair's input. Do not deduplicate repeated IDs or pairs.

With the same stream, $T = 2$ gives $B = 2$ with no padding; $T = 4$ gives $B = 1$; $T = 8$ gives $B = 1$ with four padded slots. These are changes to row layout, not to the four underlying source pairs.

Explain what cross-document context does and does not mean

The pair4→3 crosses from document A's EOS to document B's first token. This policy intentionally includes that target. In row 0, predicting3 can use the prefix[1,2,4]. EOS does not reset the causal attention calculation or stop training.

Rows are independent contexts for the ordinary batched decoder: row 1 begins with 3, so predicting its next4 uses that row's prefix[3], not a carried cache from row 0. Covering every adjacent pair once does not preserve unlimited context across row boundaries. This helper supplies no KV cache, segment IDs, position resets or block-diagonal document attention masks.

If an experiment requires document isolation or different boundary targets, it must define and test that policy explicitly. Simply excluding an EOS→next-document loss would still not stop later positions from attending to preceding-document inputs inside the same row. A loss mask controls supervision; attention masking controls visibility.

Derive validity from source positions, not token values

An output pad cell is recognizable from its construction history: no source pair was written there. Its numeric value alone is insufficient. The original second check deliberately includes a real0 token despite pad_id=0. Here is a separate example that exposes both input and target confusion:

```
documents=[[2,0,3]], T=3, pad_id=0
X    = [[2,0,0]]
Y    = [[0,3,0]]
mask = [[True,True,False]]
```

The same value 0 can be valid or padding: use position, not token identity

Separate synthetic counterexample: documents=[[2,0,3]], T=3, pad_id=0; a real token intentionally equals 0.

	t=0	t=1	t=2
X: shape=(1,3)	2	0	0
Y: shape=(1,3)	0	3	0
mask: shape=(1,3)	True	True	False

Two real transitions: 2→0 and 0→3

Y[0,0]=0 is a valid target; X[0,1]=0 is a valid input.

Only slot 2 has no source pair. Neither X!=0 nor Y!=0 expresses this validity rule.

Real vocabularies usually reserve PAD separately; this fixture tests length-based masking.

Figure 134: Valid zero IDs versus padded zero cells

Read each variable as a separate tensor of shape(1,3). Green columns represent the real pairs2→0 and 0→3. The last gray column has no pair. Y[0,0]=0 is a valid target, and X[0,1]=0 is a valid input. Consequently neither `X != pad_id` nor `Y != pad_id` expresses this helper's contract. A production vocabulary usually reserves PAD outside ordinary text; the synthetic collision tests whether validity truly comes from lengths.

The mask here means **True: include this target's loss**. In04.05 the future-position mask used True to mark scores to overwrite with negative infinity. Boolean conventions belong to each operation; the word mask alone does not establish what True means.

Normalize the loss by valid targets

For model logits with shape(B, T, V), let each unreduced cross-entropy be:

$$\ell_{b,t} = -\log \text{softmax}(logits_{b,t})_{Y_{b,t}}, \qquad L = \frac{\sum_{b,t:m_{b,t}=1} \ell_{b,t}}{\sum_{b,t} m_{b,t}}.$$

The denominator counts valid targets, not all allocated positions or documents. In the next lesson, cross-entropy with reduction='none' supplies per-position losses; selecting `losses[mask].mean()` computes this objective. Flattening the logits/targets for cross-entropy must preserve their matching row/column order, then restore losses to shape(B, T). Official cross-entropy API

Select valid positions before averaging: the loss denominator is 4, not 6

Reuse the original mask. The losses below are chosen arithmetic values, not measured model outputs.

Per-position losses ℓ: shape=(2,3)

0.2	0.4	0.6
0.8	9.0	9.0

ℓ[mask] = [0.2,0.4,0.6,0.8]

$L = (0.2 + 0.4 + 0.6 + 0.8)/4 = 0.5$

Zeroing padding losses, then averaging all six slots, is still wrong:

$(0.2 + 0.4 + 0.6 + 0.8 + 0 + 0)/6 = 1/3$

$$L = \frac{\sum_{b,t:m_{b,t}=1} \ell_{b,t}}{\sum_{b,t} m_{b,t}}$$

This supervision mask: shape=(B,T); True selects a target loss.

A causal attention mask instead controls query/key visibility, commonly across (T,T).

Excluding a loss does not block attention to an input. Specify each mask's purpose and boolean convention.

Figure 135: Selected loss values and the correct denominator

The diagram uses chosen losses[[.2,.4,.6],[.8,9,9]], not actual model measurements. The valid four values sum to 2, so $L = 2/4$=.5. Averaging all six gives 20/6. Even replacing padded losses with zero then averaging all six gives 2/6=1/3, which still scales the loss incorrectly. Select valid positions before averaging; do not try to remove padding after reduction. Boolean selection also avoids relying on zero times a potentially nonfinite padded loss.

If cross-entropy is evaluated on all cells before selection, padded Y must still be a valid class ID, as PAD0 is here, or be handled by an explicit ignore-index policy. A negative ignore label is not a valid input embedding index. Ignoring every target equal to 0 would also discard the legitimate target0 in the synthetic counterexample. This assignment creates the data/mask only;06.06 wires the masked training objective.

Exact assignment interface

```
def pack_tokens(
    documents: list[list[int]],
    context_length: int,
    pad_id: int,
) -> tuple[torch.Tensor, torch.Tensor, torch.Tensor]:
```

Documents are ordered token-ID lists with EOS already included. Their total length N is at least 2. context_length is a positive Python integer T. pad_id is an integer fill value; a real tokenizer normally reserves it, but the supplied synthetic check permits a real token with the same number. Preserve the input lists and every input occurrence.

Return three fresh independent tensors, X, Y, mask, with shapes(B, T), dtypes long, long, bool. This course constructs them on CPU from Python lists; no device argument or new environment is added. Only the first n valid slots in each row are written. Under $N \geq 2$ there is at least one valid pair. Behavior for total length0/1 or nonpositive T is outside this assignment's valid-input contract; no new validation task is required.

Guided implementation in ten steps

Edit only the learner region in the real assignment. The function body uses four spaces; a loop body adds four more. Keep the supplied driver unchanged and write the core yourself.

1. **Flatten into a fresh list.** At four spaces create `stream=[]`. Loop over `documents` and use `stream.extend(document)` at eight spaces. extend adds each document's integers; append would leave a list of lists. The original example becomes[1,2,4,3,4]. This changes stream, not documents.
2. **Name the sizes after flattening.** Back at four spaces compute N=len(stream), $P = N-1$ and T=context_length. Expect5,4,3. Count all tokens, including existing EOS; do not append another EOS or use len(documents) as N.
3. **Compute the row count.** At four spaces calculate B using integer ceiling division `(P+T-1)//T`. Expect2. `//` rounds downward after the numerator adjustment; `P//T` alone would lose the final

pair.

4. **Allocate separate input and target tensors.** At four spaces use torch.full with shape tuple(B, T), fill value pad_id and dtype=torch.long for each tensor. Both start as two rows of three zeros. Do not bind X and Y to the same tensor object. Official torch.full reference
5. **Allocate the bool mask.** At four spaces use torch.zeros with the same shape and dtype=torch.bool. All cells start False; these are target-validity flags, not token IDs.
6. **Enumerate row starts.** At four spaces loop over `enumerate(range(0,P,T))`, receiving row index b and source start. range includes0, excludes P, and advances by T. enumerate pairs each start with its row counter. The example visits($b = 0$, start=0), then($b = 1$, start=3); inside this loop use eight spaces.
7. **Count this row's real pairs.** Inside the loop compute n=min(T, $P-$start). Expect3, then1. This prevents reading a nonexistent final next token.
8. **Fill the two row prefixes.** Still at eight spaces convert each stream slice to a long tensor and assign to row prefix `[b,:n]`. Inputs use `[start:start+n]`; targets use `[start+1:start+n+1]`. For row 1, the two assigned lists are[3] and[4]. Leave the remaining cells padded.
9. **Mark those same slots valid.** Still inside the loop assign True to mask[b,:n]. Row0 becomes[True, True, True]; row 1 becomes[True, False, False]. Do not calculate validity from equality to pad_id.
10. **Return after the loop.** Dedent to four spaces and return X, Y, mask in that order. Remove the placeholder raise, preserve START/END markers and driver, and confirm inputs have not changed. The operation builds examples; it does not run the model or average losses yet.

Run, explain and record evidence

```
python exercises/06_05_packing_masks.py
```

After implementation:

```
Lesson 06.05 checks passed.
```

The original driver verifies the exact padded example, a divisible-length example with a real0 input, mask count/all, shapes there and long/bool dtypes. It does not check every T, all input ownership, a real0 target, every source-pair mapping or downstream loss/attention behavior.

Before implementing, predict the $T = 8$ result and explain why the final source EOS has no valid input/target pair of its own. After passing, reconstruct the position-to-slot mapping and distinguish the supervision mask(B, T) from query/key visibility(T, T), which may have broadcast batch/head axes.

Fixture toy-packed-pairs-eos4-v1 uses the exact two document lists, EOS4, PAD0, T3, full retention of $N-1$ source pairs and cross-document context allowed inside each row. The zero-collision and chosen-loss examples are explicitly separate. There is no external dataset/tokenizer artifact, language-model checkpoint, training budget or quality evaluation. A real run must version its tokenizer, packing/boundary policy, data, code commit, budget and evaluation protocol, and measure token utilization rather than claiming a speed gain from this toy calculation.

Dictionaries and token lists

Question: Earlier documents were dictionaries. Why does the new function directly run for document in documents and stream.extend(document)?

Answer: The representation changed at the caller: a record dictionary supplies its text string to 06.04, which returns one token-ID list per document.06.05 receives those lists. At this handoff, follow the value's type rather than inferring it from the shared variable name.

06.06 A complete pretraining experiment

Connect data preparation to a training objective

Pretraining learns to predict the next token from observed text prefixes. The targets come from shifting the token stream, rather than human-written class annotations. This is self-supervised learning: the data supplies its own prediction targets. During teacher forcing the model receives the observed preceding tokens, not tokens sampled from its own predictions.

Lessons06.01–06.05 define data identity, splits, cleaning, a frozen tokenizer and packed inputs/targets with a supervision mask. This lesson connects those tensors to a model, a differentiable objective and persistent optimizer updates. The exercise implements one fixed-batch training loop. A complete recorded corpus experiment additionally needs the data/artifact/evaluation workflow described later; this function alone does not implement that whole workflow.

Reuse04.10's forward/backward loop,05.05's AdamW concepts and 06.05's valid-target mean. The supplied driver loads the actual04.09 TinyDecoder; your function accepts the passed model and does not construct another one. Its test does not call the 06.04/06.05 data helpers because x, y, mask are provided directly. Use the existing environment; no new package or data download is needed.

Keep one example continuous from source records to training tensors

Before using the small two-class check driver, connect the functions you have already written. The 06.05 handoff starts with records A="abab" and B="ac", extracts texts, and runs the frozen one-rule BPE encoder. Its result is:

```
token_documents = [[256,256,257], [97,99,257]]
stream          = [256,256,257,97,99,257]
```

IDs 0…255 represent ordinary bytes,256 represents b"ab", and 257 is EOS. We now explicitly reserve a new PAD ID 258. The model needs capacity for indices 0…258, so choose $V = 259$ or larger. This is a vocabulary-capacity change relative to an EOS-only example, not an embedding-width change. The model is constructed by the caller; pretrain receives that existing model.

For $T = 3$, there are $N = 6$ source IDs and $P = N-1$=5 adjacent targets. Your completed pack_tokens computes B=ceil(5/3)=2 and returns:

```
x    = [[256,256,257],
```

```
        [ 97, 99,258]]
y    = [[256,257, 97],
        [ 99,257,258]]
mask = [[True,True, True],
        [True,True,False]]
```

The five real pairs are 256→256,256→257,257→97,97→99,99→257. The EOS257→97 pair crosses the document boundary under the explicitly chosen packing policy. The final padded slot is 258/258/False; it is not a sixth source pair. Inputs, targets and mask already align, so pretrain must not shift them again. The shape of each input tensor is(2,3); the five valid targets are a count, not another tensor axis.

Keep the same BPE IDs: lists → packed tensors → position losses → five selected targets

Continuous example: ordinary IDs 0⋯256, EOS257, PAD258, minimum V=259; T=3,N=6,P=5,B=2.

stream = [256,256,257,97,99,257] → (X,Y,mask)

X: shape=(2,3)

long

t=0	t=1	t=2
256	256	257
97	99	258

Y: shape=(2,3)

long

t=0	t=1	t=2
256	257	97
99	257	258

mask: shape=(2,3)

bool

t=0	t=1	t=2
True	True	True
True	True	False

logits: (2,3,259) → (6,259) y: (2,3) → (6,) CE(none): (6,) → (2,3)

Analytic baseline only: suppose every logit is zero, giving target probability 1/259.

ln 259	ln 259	ln 259
ln 259	ln 259	ln 259

→ **losses[mask]: shape=(5,)**

[ln 259, ln 259, ln 259, ln 259, ln 259]

$$K = 5, \qquad L = \frac{5 \ln 259}{5} = \ln 259 \approx 5.556828$$

The final PAD is a legal class, but its position loss is excluded; the denominator is 5, not 6.

Here K=5,V=259; the original driver separately uses K=3,V=2. Infer sizes; do not hard-code them.

Figure 136: The same BPE IDs continue through packed tensors and a five-target analytic objective

Read the upper tables as actual ID/boolean contents; shapes and dtypes appear above them. Orange is EOS, gray is padding. Then follow the shape line through cross-entropy into five selected losses. The figure's zero logits are an **analytic baseline**, not an assertion that the actual decoder initially produces zero scores.

For that baseline, take $Z = 0$ with shape(2,3,259). At every position, all 259 classes have equal probability 1/259, including the correct class. Each unreduced loss is −ln(1/259)=ln259. We must retain six position losses long enough to apply the matching mask, then average only five:

$$K = 5, \qquad \ell_{b,t} = \ln 259, \qquad L = \frac{5 \ln 259}{5} = \ln 259 \approx 5.556828062.$$

If excluded losses were zeroed and all six cells averaged, the result would be 5ln259/6≈4.630690051: smaller only because of a wrong denominator. Ordinary averaging of all six happens to give the right numeric baseline here because every loss equals ln259; changing excluded logits exposes that accidental agreement. This is why one passing symmetric example cannot establish the mask contract.

The original driver is a **different fixture**: $V = 2$, $K = 3$, x/y alternate 0 and 1, and its entire second row is deliberately excluded. Here $V = 259$, $K = 5$, and only one slot is padding. pretrain must support both by reading the actual logits and mask; do not hard-code V2, K3 or a whole-row selection. The continuous fixture's legal PAD 258 target can be evaluated before selection, but its own position loss is excluded. At selected positions, the PAD output class still participates in the ordinary 259-way softmax denominator; excluding padding positions does not remove a vocabulary column.

For the continuous baseline, one selected output position has gradient −258/1295≈−.199227799 at its correct class, and 1/1295≈.000772201 at every other class. All 259 direct logit gradients at the excluded position are 0. The gradient denominator is $K = 5$; it is neither the vocabulary size259 nor allocated position count 6. The general gradient formula below explains these numbers.

What one update changes, and what it leaves as training data

At update s, parameters θ_s produce current logits. The observed x, aligned y and bool mask are the same supplied tensors on every repetition of this exercise. The loss changes because the parameters change, not because the function replaces the correct labels with its predictions:

$$Z_s = f_{\theta_s}(x), \qquad L_s = L(\theta_s; x, y, m), \qquad \theta_{s+1} = \text{AdamWStep}(\theta_s, \nabla_\theta L_s; \text{optimizer state}).$$

Read this as a sequence. Forward computes scores; cross-entropy compares them to the fixed targets; backward computes how each trainable parameter affects the selected mean loss; optimizer.step changes those parameter values. The optimizer's moments also evolve. A differentiable computation graph connects the tensor loss to the model parameters. Logging loss.item() produces a separate float; it is not the object to differentiate.

This is teacher-forced next-token training, so there is no argmax, random sampling or UTF-8 decoding inside the update. The model can process all causally masked positions in a row together; it does not need a Python generation loop to train each target. Sampling belongs to inference. The exercise

repeats one fixed batch as a small diagnostic; a corpus trainer would additionally supply a defined batch schedule and held-out evaluation.

Define predictions, target selection and the mean loss

Let θ denote the model parameters, Z its raw logits and K the number of selected targets:

$$Z = f_\theta(x) \in \mathbb{R}^{B\times T\times V}, \qquad K = \sum_{b,t} m_{b,t} > 0.$$

Symbol	Meaning	Supplied fixture
x	Input token IDs, torch.long(B, T)	[[0,1,0],[1,0,1]]
y	Already aligned next-token targets, torch.long(B, T)	[[1,0,1],[0,1,0]]
m / mask	Target-selection flags, torch.bool(B, T)	First row True, second row False
B, T, V	Batch rows, input positions, vocabulary classes	2,3,2; equal B/V values do not identify their axes
Z	Floating logits for every position/class	Shape(2,3,2), not sampled IDs
K	Number of valid/selected target positions	3, not $B\times T = 6$

For each position, softmax defines the model distribution and cross-entropy reads the probability of its target:

$$p_{b,t,c} = \frac{\exp Z_{b,t,c}}{\sum_{j=0}^{V-1} \exp Z_{b,t,j}}, \qquad \ell_{b,t} = -\log p_{b,t,y_{b,t}}, \qquad L(\theta) = \frac{1}{K} \sum_{b,t:m_{b,t}=1} \ell_{b,t}.$$

Here c/j index output classes; b/t index input positions. The sum selects target losses, not embedding features. Use natural logarithms. PyTorch cross_entropy takes raw logits and computes the stable log-softmax/cross-entropy calculation internally; do not apply softmax first. reduction='none' preserves individual losses. Official cross-entropy definition

Start with inputs and targets: row 1 has real token IDs, but its targets are excluded

Original driver: x=[[0,1,0],[1,0,1]], y=1−x ; mask selects only row 0. B=2,T=3,V=2.

x: shape=(2,3)

long

	t=0	t=1	t=2
b=0	0	1	0
b=1	1	0	1

y: shape=(2,3)

long

	t=0	t=1	t=2
b=0	1	0	1
b=1	0	1	0

mask: shape=(2,3)

bool

	t=0	t=1	t=2
b=0	True	True	True
b=1	False	False	False

True selects a target;False excludes it. The second row is not padding.

$$K = \sum_{b,t} m_{b,t} = 3, \qquad BT = 6$$

$$L = \frac{\ell_{0,0} + \ell_{0,1} + \ell_{0,2}}{3}$$

Teacher forcing uses observed prefixes. Targets are already shifted; do not shift them again in pretrain.

The mask selects target losses; it neither blocks attention nor turns model outputs into sampled IDs.

Figure 137: Original input/target/mask contents and valid-target count

Read the three tables as separate tensors. Shape and dtype sit above their contents. The mask cells show their actual True/False values. The second row contains real0/1 tokens; it is deliberately excluded from supervision, not padded. A mask can select targets for reasons beyond padding. In the first row, y[0,1]=0 is still a valid target; ignoring every class 0 would change the objective.

Preserve position alignment when calling cross-entropy

For this interface, flatten only the batch and position axes:

$$q = bT + t : \qquad (B, T, V) \to (BT, V), \quad (B, T) \to (BT), \quad (BT) \to (B, T).$$

The final vocabulary axis stays together. `.reshape(-1,V)` infers BT while retaining V candidates per position; `y.reshape(-1)` gives matching target order. With reduction='none', cross-entropy returns BT losses. `.reshape_as(y)` restores the(B, T) target layout before mask selection. reshape supports non-contiguous inputs; do not assume view is always valid.

Flatten positions while keeping classes together: each target matches its logits row

Original x/y/mask; zero logits below are an analytic baseline, not measured random TinyDecoder outputs.

logits: (2,3,2) → (6,2) y: (2,3) → (6,) losses: (6,) → (2,3)

q	(b,t)	logits contents	y	mask	CE
0	(0,0)	[0,0]	1	True	ln 2 ≈ .693147
1	(0,1)	[0,0]	0	True	ln 2 ≈ .693147
2	(0,2)	[0,0]	1	True	ln 2 ≈ .693147
3	(1,0)	[0,0]	0	False	ln 2 ≈ .693147
4	(1,1)	[0,0]	1	False	ln 2 ≈ .693147
5	(1,2)	[0,0]	0	False	ln 2 ≈ .693147

[0,0] → softmax → [1/2,1/2]

L = (ln 2 + ln 2 + ln 2) / 3 = ln 2 ≈ 0.693147

Zeroing the last three losses, then averaging six slots, gives ln 2 / 2: the wrong denominator.

cross_entropy receives raw logits and handles log-softmax internally; do not softmax first.

Figure 138: Exact six-position alignment and the uniform-logit baseline

Read each row as one original(b, t) position, one vector of V class scores, one target and its mask flag. $q = 0$,1,2 are selected; $q = 3$,4,5 are not. A direct cross_entropy call on unpermuted(B, T, V) does not express this layout: that API normally interprets its second axis as classes. Preserve the documented flattening instead of hoping equal dimensions make an incorrect call work.

For an explicitly uniform-logit example, every position has scores[0,0]. Its probabilities are[.5,.5], so every position loss is ln2≈.693147. The selected three losses sum to 3ln2, giving L=ln2. Zeroing the excluded three and averaging all six gives ln2/2, the wrong denominator. The randomly initialized TinyDecoder is not guaranteed to output zeros; this is an analytic baseline, not its measured first loss.

See the gradient that makes prediction improve

For finite logits, the direct gradient at an output score is:

$$\frac{\partial L}{\partial Z_{b,t,c}} = \begin{cases} (p_{b,t,c} - \mathbf{1}[c = y_{b,t}])/K, & m_{b,t} = 1, \\ 0, & m_{b,t} = 0. \end{cases}$$

A selected target's correct class gets p−1; other classes get p. At uniform probabilities with $K = 3$, each selected position contributes±1/6. Gradient descent moves correct-class scores upward and incorrect-class scores downward through the model's parameters.

A zero direct gradient at an excluded output does not block attention to its input, nor freeze shared parameters. An earlier input can affect a later selected prediction even when its own target is excluded. The tiny driver uses independent batch rows, so changing only the excluded second row's targets leaves its compared trajectories unchanged. Changing input context is a different intervention; stochastic models also require matched random streams for trajectory comparisons.

Work through a complete separate one-update diagnostic

To make one update calculable, use a separate two-class lookup model: W has shape(2,2), rows are input IDs and columns are output-class scores. It directly returns $Z = W[x]$. This diagnostic is not TinyDecoder's embedding and does not replace the assignment model. Initially W_0 is all zeros. Use the same x, y, mask as the original fixture.

Only the first row contributes. Its three supervised mappings are 0→1,1→0,0→1. Therefore:

$$L(W_0) = \ln 2, \qquad \nabla_W L = \begin{bmatrix} 1/3 & -1/3 \\ -1/6 & 1/6 \end{bmatrix}.$$

Input0's row accumulates two contributions; input1's row accumulates one. Both are still divided by the common selected-target count 3. The negative entries belong to correct target classes. This is a gradient matrix, not a probability table.

AdamW uses the current gradient and its persistent first/second-moment memories. Reusing05.05's notation, one optimizer step is schematically:

$$\theta_s = (1 - \eta\lambda)\theta_{s-1} - \eta\frac{\hat{m}_s}{\sqrt{\hat{v}_s} + \epsilon}.$$

η is learning_rate; λ=.01 is decoupled weight decay; the corrected moments summarize gradients and squared gradients. Use torch.optim.AdamW rather than implementing this formula again. This exercise uses its ordinary defaults β_1=.9,β_2=.999,ϵ=1e−8, with explicit weight_decay=.01 for the passed parameter iterable. Production parameter-group decay policies are a separate choice. Official AdamW reference

Separate two-class lookup diagnostic: from loss gradients to one AdamW update

Rows are input IDs; columns are output classes. W supplies logits directly, not TinyDecoder embeddings.

W_0: shape=(2,2)			$\nabla_W L$: shape=(2,2)			$W_1 \approx$: shape=(2,2)		
	class 0	class 1		class 0	class 1		class 0	class 1
0	0	0	0	1/3	−1/3	0	−.03	+.03
1	0	0	1	−1/6	1/6	1	+.03	−.03

Input 0 occurs twice and input 1 once; all three valid targets contribute to the mean gradient.

AdamW: lr=.03, decay=.01, β=(.9,.999), ϵ=1e−8; initial W_0=0.

$\hat{m}_1 = g, \quad \hat{v}_1 = g^2, \quad W_1 = -.03\, g/(|g| + 10^{-8})$

history[0] = L(W_0) = 0.693147⋯; L(W_1) ≈ 0.663597114

Afterward the correct-class probability is about .514996. Initial zero weights make this first decay term zero.

This is one step of a separate arithmetic model, not a replacement model or a language-capability evaluation.

Figure 139: Separate lookup logits, analytic gradient and first AdamW update

At the first step, the corrected first moment is g and corrected second moment is g^2. Since W_0=0,

this first decay term is zero. With learning_rate=.03, each coordinate becomes−.03g/(|g|+1e−8), giving approximately:

```
W ₁ = [[−.03,+.03],
       [+.03,−.03]]
```

The tiny differences from the displayed values come from ϵ. Both correct-class probabilities are about.514996. The recomputed masked loss is about.663597114, lower than ln2. `history[0]` should still contain the pre-update loss.693147181. This is a checked float64 arithmetic example, not a trained language-model quality claim, and one successful update does not imply every future update decreases loss.

Keep one optimizer alive through all updates in a call


Construct AdamW once before the loop. Recreating it inside the loop would reset its moment estimates every update. Clearing `.grad` is different: zero_grad removes accumulated parameter gradients while retaining optimizer memory.

The update order is: clear previous gradients, run a new forward pass, calculate selected mean loss, record its numerical value, backpropagate that tensor loss, then step the optimizer. backward calculates gradients; step changes parameter values. Do not use no_grad for training forward/loss/backward, detach the training loss or replace model parameter objects.

`model.train()` sets training mode for relevant modules such as dropout; it does not enable autograd by itself or run optimization. `model.eval()` also does not disable autograd by itself. This function expects ordinary gradient-enabled execution. PyTorch autograd/mode distinction

Create the optimizer once: record pre-update loss, then backward and step

Each pretrain call creates one AdamW; all updates within that call share its first/second-moment state.



Repeat updates times, building a fresh forward graph. zero_grad does not erase AdamW moments.

h[0]=L(θ_0) → update1 → h[1]=L(θ_1) → ⋯→ h[79]=L(θ_{79}) → update80 → θ_{80}

Return 80 pre-update floats; L(θ_{80}) is not recorded automatically. updates=0 skips forward/backward/step.

Figure 140: One optimizer lifetime, update sequence and history timing

Read the flow from left to right on the upper row, then right to left on the lower row. Repeat the cycle updates times. `loss.item()` extracts a Python float for history; keep the original scalar tensor named loss for backward. Appending the tensor instead would retain graph-connected objects unnecessarily. After80 updates, the model holds θ_{80} but history[79] describes $L(\theta_{79})$, before update 80. A final loss at θ_{80} requires a separate evaluation.

Every call creates a fresh optimizer. Calling pretrain twice on the same model preserves its weights but resets optimizer memory between calls; this is not an exact-resume interface. The return value contains no optimizer state. Use05.07's fuller checkpoint concepts for later real continuation.

Exact assignment interface and boundaries

```
def pretrain(model: nn.Module, x: torch.Tensor, y: torch.Tensor,
             mask: torch.Tensor, updates: int,
             learning_rate: float) -> list[float]:
```

model is the existing registered causal module, returning floating logits(B, T, V). x and y are long(B, T), already aligned, and mask is bool(B, T) selecting at least one target. Input/target IDs are legal for the model vocabulary, including any excluded entries evaluated before selection. T fits model capacity and devices are compatible. updates is a nonnegative integer; learning_rate is positive. No new validation task is required.

Return a new list of exactly updates Python float pre-update losses, modifying the same passed model with AdamW(weight_decay=.01). Preserve input tensors and parameter identities. Set training mode and leave it set. For updates=0 return[] without forward, backward or optimizer steps; mode can change, while weights remain unchanged. The function does not promise to restore initial mode, return checkpoints, sample tokens, validate, add schedules/clipping/AMP or load data.

Check each intermediate object before writing the loop

The function body has two indentation levels: four spaces for setup/return, eight for each update. Inside the update, the model produces tensors; the final history stores Python floats. Keep those roles distinct:

Local role	General shape/type	Original driver	Continuous BPE example
x, y	long(B, T)	(2,3)	(2,3)
mask	bool(B, T)	(2,3), $K = 3$	(2,3), $K = 5$
logits	Floating(B, T, V)	(2,3,2)	(2,3,259)
logits flattened for CE	Floating(B*T, V)	(6,2)	(6,259)
y flattened for CE	long(B*T,)	(6,)	(6,)
CE with reduction='none'	Floating(B*T,)	Six individual losses	Six individual losses
Losses restored to y layout	Floating(B, T)	(2,3)	(2,3)
Losses selected with mask	Floating(K,)	(3,)	(5,)
Their mean loss	Floating scalar tensor, shape()	ln2 for zero logits	ln259 for zero logits

Local role	General shape/type	Original driver	Continuous BPE example
loss.item() for history	Python float, no tensor shape	Approximately .693147	Approximately 5.556828

The numbers in the last two columns are analytic zero-logit cases. In your actual run the model predicts its own logits; do not replace them with zeros. No embedding-width axis D appears at the function boundary: the model handles embeddings and attention internally, then returns V output scores per position.

For flattening, read `.reshape(-1,V)` as: infer the number of position rows, but keep exactly V class columns. `.reshape(-1)` on y preserves the same order. `.reshape_as(y)` means use y's shape, not its values. Finally boolean indexing selects only positions where mask is True. You cannot select from the already-reduced scalar returned by the default cross-entropy reduction; individual losses must still exist at selection time.

`loss.backward()` applies the chain rule through the actual model. For any parameter coordinate θ_r:

$$\frac{\partial L}{\partial \theta_r} = \sum_{b,t,c} \frac{\partial L}{\partial Z_{b,t,c}} \frac{\partial Z_{b,t,c}}{\partial \theta_r}.$$

Thus the model's attention/FFN/embedding parameters receive gradients through their effects on logits. In the separate lookup diagnostic W itself stores logits; in TinyDecoder, a logit is a computed output rather than a parameter you manually overwrite. AdamW updates model.parameters(), not the observed token IDs or target tensor. The detailed first-step lookup calculation above makes the arithmetic visible without pretending to expose every decoder parameter.

Guided implementation in ten steps

Edit only the learner region in the real exercise. Keep the supplied model loader and run_checks intact. Ordinary function statements use four spaces; the update loop body uses eight.

1. **Create one optimizer at four spaces.** Use torch.optim.AdamW on model.parameters(), lr=learning_rate and weight_decay=.01. Do this before the loop, so optimizer memories persist. Do not create another model or call the earlier04.10 trainer, which has a different optimizer/objective.
2. **Set mode and initialize history at four spaces.** Call model.train() and create an empty list. model.train acts on the existing module; history will contain floats, not logits or loss tensors.
3. **Start the loop at four spaces.** `for _ in range(updates):` repeats exactly updates times. `_` is an intentionally unused loop counter. range(0) runs zero times. All per-update work below uses eight spaces.
4. **Clear gradients inside the loop.** Call optimizer.zero_grad(set_to_none=True). This removes old `.grad` values, including stale gradients from before this function call, without resetting moments or parameters.

5. **Compute current raw logits.** Call model(x); expect(B, T, V), or(2,3,2) in the driver. Read V from logits.shape[-1]. y is already shifted; do not shift, generate or sample again.
6. **Compute individual position losses.** Reshape logits to(-1, V) and y to(-1); call F.cross_entropy with reduction='none', then reshape its returned vector with reshape_as(y). Expect(6,2),(6,) and then(2,3). Keep autograd connected and class columns together.
7. **Select and average.** Use the bool mask to select per-position losses, then .mean(). In the uniform example, three selected values each equal ln2, so the scalar loss is ln2. Do not multiply by mask then mean all slots or ignore every target0.
8. **Record the numerical loss before updating.** Append loss.item() to history, still at eight spaces. The list length increases by one; preserve the original scalar loss tensor for the next step. append returns None, so do not reassign history to that return.
9. **Backpropagate, then update.** Call loss.backward(), then optimizer.step(), in this order inside the loop. Do not wrap the forward/backward path in no_grad or recreate optimizer state each iteration.
10. **Return after the loop.** Dedent to four spaces and return history. With updates=80 it has 80 floats; with 0 it is[]. Remove the placeholder raise, preserve START/END and driver, and do not add an automatic final loss to the returned history.

Run and interpret the actual supplied driver

```
python exercises/06_06_pretrain_run.py
```

After implementation and completed04.09 dependencies:

```
Lesson 06.06 checks passed.
```

The driver fixes seed 26, creates TinyDecoder(V2, width 8, heads2, layers1, max_length8), and clones its initial model. On the original alternation x/y/mask it runs80 updates at learning_rate=.03 and requires the last recorded loss below.15. Its second clone receives different legal y values only at mask-False positions; histories and final parameters must match within the supplied tolerance. It also checks updates 0 returns[]. The test does not modify masked x or prove held-out language ability.

Temporary reference preparation passed those checks and independent selected-log-softmax trajectories, the analytic lookup update, non-contiguous unequal-axis cases, dtype/mode/ownership/stale-gradient checks and zero-update boundaries.

From this primitive to a recorded experiment

The existing lab driver additionally requires completed02/05/06 components and 07.02 evaluation plus07.04 inference dependencies. Do not fill those future learner regions merely to force this lab to run now. The06.06 exercise itself can be done with its supplied fixed tensors.

For the later lab, follow this order: canonicalize/group content, freeze document splits, fit BPE only on train, reserve EOS/PAD consistently, encode both sides with that same tokenizer, and pack each

split separately. Construct a model with capacity for every reserved ID. Measure fixed held-out loss before and after a budgeted training run, then inspect fixed-prompt samples. A low training loss on one repeated batch is an overfit diagnostic; held-out behavior answers a different question. Pretraining is also different from instruction tuning: this objective does not itself define a chat template or assistant behavior.

After prerequisites are complete, the existing self-authored integration command is:

```
python scripts/pretrain_lab.py --updates 30 --output outputs/pretrain-toy
```

The driver uses a small ModernLM, not the TinyDecoder of the assignment check. It saves ignored tokenizer/data-manifest/model/summary artifacts. Its model.pt contains model weights/config/update count, not the full optimizer/RNG/sampler bundle needed for exact resume. The function pretrain likewise returns only history. Do not claim05.07-style recovery from that weights snapshot alone.

Experiment record	What to retain
Code and data	Full clean code commit, data/cleaning/split versions, portable document identities and fingerprints
Tokenizer and packing	Artifact checksum, merge/special mapping, model capacity, boundary/target-mask policy
Configuration and budget	Model/optimizer/seed settings, updates and selected-target exposures
Evaluation	Frozen held-out documents/tokenizer/mask, valid-target-weighted loss before/after, fixed prompts
Artifacts and conclusion	Checkpoint/checksums, training history, measurements, limits and what the result supports

For the original assignment diagnostic,80×3=240 selected-target exposures reuse the same three targets; that is not240 distinct training tokens. A real corpus run must distinguish repeated exposures, distinct data size and generated tokens, and record its own budget/results. Keep large data/weights outside Git and private storage mappings in ignored configuration. No external corpus experiment or capability evaluation has been executed as part of preparing this lesson.

Looking back

A training run can now state what it learned from and how its updates were formed. Chapter07 asks how to evaluate that process and use its saved model for generation without changing the comparison conditions.

07 Measure and use the model

A small loss and a fluent sample answer different questions. Loss summarizes the probability of known targets under a defined protocol; a generated sample reveals behavior under a decoding policy. Neither can be compared meaningfully without preserving tokenization, target masks, aggregation rules and data ownership.

We derive token-aware metrics before defining a fixed evaluation protocol. We then cache attention keys and values so that generation can reuse an unchanged prefix. Correct caching requires absolute position alignment and explicit causal visibility. The final interface keeps sampling, EOS handling and state ownership visible to the caller.

07.01 Token-aware language metrics

Method sources

For cross-corpus language-model fit and normalized metrics, see Paloma Magnusson et al., 2024; R30. Byte-level probability subtleties are examined by Phan et al., 2024; R31. Dividing observed token NLL by UTF-8 bytes is a declared evaluation convention; it is not automatically an exact marginal probability over every tokenization of a byte string.

Reading route for this guided session

The central question is: **given the probabilities assigned to the observed text, how do we report a score with a meaningful denominator?** The code is short; this lesson is about the meaning of the numbers.

Follow the continuous two-token example first, then read the formal sections beside their illustrations. The route is **correct-target probability → summed negative log-likelihood → mean token loss → perplexity → bits per byte → fair aggregation and comparison → implementation**. The document-type handoff from the earlier question remains near the end as classroom reference.

Three distinctions organize the lesson: a loss **sum** versus a **mean**; the number of scored token **occurrences** versus vocabulary size; and original UTF-8 **bytes** versus token-ID storage.

One continuous walkthrough: from your training loss to all three metrics

Purpose:06.06 trains the model; 07.01 describes probability scores with three scalar metrics. The model's forward pass and cross-entropy computation have already happened. This helper receives their totals and returns a new dictionary. It does not receive the document records or build another model.

Your completed 06.06 code contains:

```
valid_loss = loss[mask]
loss_val = valid_loss.mean()
```

valid_loss holds one loss for each selected target occurrence. Repeated token IDs still count as separate occurrences. loss_val is their mean. For 07.01, retain the **sum and count before averaging**; the argument nll_sum must receive the sum, not loss_val. For a selected-loss tensor, .sum().item() yields its scalar total and .numel() counts its elements. These operations describe the selected targets; align the ordinary-text selection discussed below before using that total for this BPB protocol.

Use one separate, constructed scoring example throughout the following metric calculations. The scored ordinary text is "abcd": four UTF-8 bytes, split by an illustrative fixed tokenizer into b"ab" and b"cd". This tokenizer example is **independent of the one-rule BPE handoff in the classroom reference below**, which learns only "ab". The byte chunks name contents, not numeric token IDs. Assume fixed preceding context allows both text tokens to be scored; no structural EOS or PAD is a scored target in this example.

Scored target	Model probability of the correct target	Cross-entropy contribution
First text chunk b"ab"	$1/2$	$-\ln(1/2) = \ln 2 \approx 0.693147$
Second text chunk b"cd", given its prefix	$1/8$	$-\ln(1/8) = 3\ln 2 \approx 2.079442$

The probabilities are supplied for arithmetic practice, not measured model outputs. The familiar selected-loss tensor would therefore contain approximately [0.693147,2.079442]. This gives all three inputs:

```
nll_sum    = ln2 + 3ln2 = 4ln2 ≈ 2.772588722
tokens     = 2 scored target occurrences
utf8_bytes = 4 original scored text bytes
```

First output: loss is the mean you already know

Divide total loss by scored-target count: $(4\ln 2)/2 = 2\ln 2 \approx 1.386294361$. This is precisely the operation valid_loss.mean() performed. tokens=2 means **two scored targets**, not ID 2, vocabulary size2, document count or embedding width. The byte denominator is not needed for this output.

Second output: ppl puts the mean loss on another scale

Perplexity (PPL) is $\exp(L)$. Here $\exp(2\ln 2) = 4$. To understand the scale, imagine a reference situation in which every correct target gets probability1/4. Every loss is then $-\ln(1/4) = \ln 4$, and $\exp(\ln 4) = 4$. Our two unequal probabilities produce that same mean loss, so they produce PPL4 too.

For the actual two probabilities, their product is $(1/2)(1/8) = 1/16$. The equal probability that gives this same product across two targets is $1/4$, since $(1/4)(1/4) = 1/16$. This equal-per-target

probability is the geometric mean; its reciprocal is 4. PPL4 therefore does not claim that there were literally four candidates or that accuracy was25%. Average the losses first, then exponentiate; do not exponentiate the total, which would give16.

Third output: bits_per_byte uses source bytes as its denominator

Cross-entropy above used ln, so its unit is a nat. Binary information uses log base 2, whose unit is a bit. For a probability $1/2$ event, $-\ln(1/2) = \ln 2$ nats and $-\log_2(1/2) = 1$ bit. Thus $\ln 2$ nats **equals1 bit**. Convert the whole accumulated loss by dividing by $\ln 2$:

```
4ln2 nats / ln2 = 4 ideal bits
4 ideal bits / 4 original source bytes = 1 bit per byte
```

The source "abcd" still occupies $4 \times 8 = 32$ raw bits. The4 ideal bits describe the model's probability score in coding units; this function does not create a compressed file. utf8_bytes counts matching source text bytes, not the storage occupied by the token-ID tensor. For a whole scored text "你 a", for example, len(text.encode("utf-8")) is 4, whereas len(text) is 2.

All three calculations from the **same inputs** are now:

Output key	Calculation	Result
loss	nll_sum / tokens	$2 \ln 2 \approx 1.386294361$
ppl	$\exp(L)$	4
bits_per_byte	$S/(M \ln 2)$	1

There are two kinds of denominator because token counts depend on tokenization while source-byte counts describe the covered text. If a deliberately constructed second setup holds nll_sum=$4 \ln 2$ and utf8_bytes=4 fixed but has tokens=4, loss becomes $\ln 2$ and PPL2, while BPB stays 1. This is the second original check; it does not mean that retokenizing real text automatically preserves its score or improves the model. Compare PPL with the same tokenizer and scoring conditions.

Why keep totals? A separate batch example has one target with loss 1 in batchA and three targets with loss 3 each in batchB. The complete target list is [1,3,3,3], so its mean is $10/4 = 2.5$. Averaging the two batch means gives $(1 + 3)/2 = 2$, incorrectly giving the small batch the same weight as the large one. Keep each batch's sum and count, add them, then divide once; compute PPL only after this final mean. 07.02 prepares such totals.

Connect the scoring policy too. Your 06.06 training mask can include EOS targets. This 07.01 BPB example scores ordinary text only, excluding structural EOS and PAD from both the loss sum and target count. Do not combine an EOS-inclusive sum with ordinary-text bytes and assume it is this text-only metric. The full protocol discussion below explains alignment; this does not ask you to rewrite your accepted training code.

You now have the purpose, each input, a complete example and all outputs. The later sections retain illustrations, formal derivations and boundary cases for reference; the final implementation plan follows the same calculations.

Why another number after cross-entropy?

A language model assigns a probability to each possible next token. Cross-entropy asks how much probability it assigned to the **observed correct target**. An evaluation report must also say how many targets were scored and what unit was used. A total loss of 10 over two targets is different from 10 over a thousand targets.

This lesson turns three accumulated quantities into three reportable metrics. **Mean token loss** uses tokens as its denominator. **Perplexity (PPL)** exponentiates that mean. **Bits per byte (BPB)** converts the total to bits and divides by the corresponding original UTF-8 bytes. Their units explain when comparisons are meaningful.

Prerequisites: target probabilities, natural logarithms and cross-entropy from 03.09–03.11, plus UTF-8 bytes and frozen tokenization from Chapters 02/06. Read the book in order, but this small scalar helper can be implemented without any unfinished model, evaluator or data pipeline. math is already imported. No tensor shape, training loop, download or new environment is involved.

Connect cross-entropy, NLL and the correct-target probability

For position i, the model produces a vector of V logits z_i. Softmax turns it into probabilities, and the observed target ID t_i selects one component:

$$p_{i,v} = \frac{e^{z_{i,v}}}{\sum_{u=0}^{V-1} e^{z_{i,u}}}, \qquad q_{i,v} = \begin{cases} 1 & v = t_i \\ 0 & v \neq t_i, \end{cases} \qquad \ell_i = -\sum_v q_{i,v} \ln p_{i,v} = -\ln p_{i,t_i}.$$

Here v indexes vocabulary columns; i indexes scored target occurrences. q is a mathematical one-hot target distribution; the production API receives integer target IDs and need not build q explicitly. Ordinary hard-target cross-entropy is therefore the negative log-likelihood of the correct target. `F.cross_entropy` computes this stably from logits through log-softmax. The helper in this assignment starts after those operations and receives the accumulated scalar total.

```
logits: [B,T,V] -> select correct-target log-probabilities: [B,T]
               -> mask scored positions -> sum into scalar S, count into N
original byte spans for exactly those selected text targets -> scalar M
```

Bracketed entries above are tensor shapes, not token contents. With the main constructed example, selected losses have shape `[2]` and numerical values approximately `[0.693147,2.079442]`. The resulting S, N and M are scalars. The existing probability-to-metric figure below traces those same values.

The model is evaluated on the observed prefix. In the two-token example, it scores `ab` after a fixed preceding context and then scores `cd` after that context plus the observed `ab`. It does not need to generate or guess a replacement first token to calculate this score. The probability of that specified two-token continuation is $(1/2)(1/8) = 1/16$; the identity $-\ln\left(\prod_i p_i\right) = \sum_i -\ln p_i$ explains why per-target NLLs add.

At a single position, probabilities 1, $1/2$, $1/4$ and $1/8$ yield losses 0, $\ln 2$, $2 \ln 2$ and $3 \ln 2$. Increasing probability of the correct target lowers its loss. A confident incorrect prediction can still give the true target very low probability and a large loss. Argmax accuracy keeps only the winning ID, while NLL retains how much probability the correct ID received.

Start with the probability of each correct target

Let t_i be an observed target token and let p_i be the model's probability of that token given its allowed prefix/context. The subscript i indexes **scored targets**, not vocabulary entries. We accumulate:

$$p_i = p_\theta(t_i \mid \text{allowed context}), \qquad \ell_i = -\ln p_i, \qquad S = \sum_{i=1}^{N} \ell_i.$$

For positive probabilities at most 1, each loss is nonnegative. Probability 1 gives loss 0; a smaller correct-target probability gives a larger loss. Natural logarithms measure this information in **nats**. The helper receives the accumulated S; it does not compute probabilities or take their logarithms itself.

Symbol	Actual parameter	Type and meaning	Unit
S	nll_sum	float: finite, nonnegative **sum** of scored negative log-likelihoods	nats
N	tokens	int: positive count of those scored text-token targets	tokens
M	utf8_bytes	int: positive count of the original UTF-8 bytes covered by those targets	bytes
L	returned loss	float: S/N	nats/token
PPL	returned ppl	float: $\exp(L)$	Dimensionless, dependent on the token unit
BPB	returned bits_per_byte	float: $S/(M \ln 2)$	bits/byte

All six quantities are scalars. N is not vocabulary size; M is not an embedding dimension, character count or tensor-memory allocation. Inputs satisfy the stated contract; new validation branches are not part of this assignment.

Derive mean loss and perplexity before coding

First normalize the total by the number of scored targets:

$$L = \frac{S}{N} = \frac{1}{N} \sum_{i} -\ln p_i.$$

Then exponentiate. Using log-product identities gives an interpretation, not just a rule to memorize:

$$\text{PPL} = e^{L} = \exp\left(\frac{1}{N}\sum_i \ln\frac{1}{p_i}\right) = \left(\prod_i \frac{1}{p_i}\right)^{1/N} = \frac{1}{\left(\prod_i p_i\right)^{1/N}}.$$

The denominator on the right is the **geometric mean** correct-target probability. Thus PPL 4 means that geometric mean is 1/4. It does not literally mean the model kept exactly four candidates or got one quarter of the targets correct. For a uniform distribution over V classes, $p_i = 1/V$ gives $L = \ln V$ and PPL $= V$; that is one special distribution, not a general upper bound.

From correct-target probabilities to perplexity: log, average, then exponentiate

Constructed example: scored text abcd, split into byte chunks ab / cd. These are contents, not token IDs.

i	token byte contents	p_i (target probability)	$-\ln p_i$ (nats)
1	b"ab"	1/2	$\ln 2 \approx .693147$
2	b"cd"	1/8	$3 \ln 2 \approx 2.079442$

$$S = \sum_i -\ln p_i = 4\ln 2 \approx 2.772589 \text{ nats}, \quad N = 2$$

$L = S/N = 2\ln 2 \approx 1.386294$

nats / scored token

$\longrightarrow$

$PPL = e^{L} = e^{2\ln 2} = 4$

1 / geometric mean target probability

$$\sqrt{(1/2)(1/8)} = 1/4 \quad \Longrightarrow \quad PPL = 1/(1/4) = 4$$

Not the inverse arithmetic mean probability: 1 / .3125 = 3.2.

Not the arithmetic mean of inverses either: (2 + 8) / 2 = 5. The correct value is 4.

Every quantity here is scalar; there are no B / T / D tensor axes.

Figure 141: Two constructed target probabilities become summed NLL, mean token loss and perplexity

Read the figure from its probability rows down through the sum and the two boxes for mean loss and perplexity. The row contents b”ab” and b”cd” are illustrative **token byte chunks**, not numeric IDs

or tensor sizes. Count and unit labels sit outside them. The orange alternatives show two tempting but incorrect averages.

Walk through the complete original fixture

Use the self-authored scored text “abcd”, whose UTF-8 byte values are [97,98,99,100]. Assume its entire four-byte span is scored with a suitable fixed context, as two chunks b”ab” and b”cd”. These are constructed conditional probabilities, not observations from a trained model:

1. The correct first chunk has probability 1/2. Its loss is $-\ln(1/2) = \ln 2 \approx 0.693147$.
2. The correct second chunk, conditioned on the prefix, has probability 1/8. Its loss is $-\ln(1/8) = 3\ln 2 \approx 2.079442$.
3. The product of the conditional probabilities is 1/16. The total is $S = 4\ln 2 \approx 2.772588722$, with $N = 2$ and $M = 4$.
4. Mean token loss is $L = (4\ln 2)/2 = 2\ln 2 \approx 1.386294361$.
5. Perplexity is $\exp(2\ln 2) = 4$. Equivalently, the geometric mean probability is $\sqrt{(1/2)(1/8)} = 1/4$, then take its reciprocal.

Taking the inverse of the arithmetic mean probability gives $1/((0.5 + 0.125)/2) = 3.2$, which is wrong. Averaging the inverse probabilities gives $(2 + 8)/2 = 5$, also wrong. The logs are averaged **before** exponentiation.

Why divide by $\ln 2$ for bits per byte?


A bit uses a base 2 logarithm, whereas our cross-entropy uses the natural logarithm. The change-of-base identity is:

$$-\log_2 p = \frac{-\ln p}{\ln 2}, \qquad C_{\text{bits}} = \frac{S}{\ln 2}, \qquad \text{BPB} = \frac{C_{\text{bits}}}{M} = \frac{S}{M \ln 2}.$$

An event with probability $1/2$ costs $-\ln(1/2) = \ln 2$ nats, or exactly 1 bit. Therefore 1 nat is $1/\ln 2 \approx 1.442695$ bits. We divide by $\ln 2$; multiplying by it would convert in the opposite direction.

Convert the logarithm base, then normalize by source bytes: nats → bits → bits per byte

Continue abcd / two tokens / S=4 ln 2. The Unicode example below is a separate byte-count illustration.



abcd: M = len("abcd".encode("utf-8")) = 4

a	b	c	d
97	98	99	100

4 × 8 = 32 raw bits; distinct from the 4-bit ideal model code length.

Separate example: 你 a has two Unicode code points, but four UTF-8 bytes.

228	189	160	97
你: 3 bytes			a: 1 byte

len(text) = 2 ≠ M = 4

M counts only source bytes covered by S; exclude PAD storage and unscored prompt bytes.

BPB is an ideal model code-length statistic, not a compressed-file size; it has no upper bound of 8.

Figure 142: Natural-log total converted to ideal bits and normalized by source bytes, with a separate Unicode count

Read the top row left to right. For the original fixture, $4 \ln 2$ nats becomes 4 ideal bits. Divide by the four **source bytes** to obtain BPB 1. The source still occupies $4 \times 8 = 32$ raw bits before compression. BPB is an ideal model code-length statistic; the helper does not produce a compressed file, include coding overhead or promise a four-bit file.

The lower row is a **separate byte-count illustration**: "你 a" has two Unicode code points but four UTF-8 bytes, [228,189,160,97]. Use len(text.encode("utf-8")), not len(text), **when the entire text is scored**. This does not assign "你 a" the probabilities or NLL of the ASCII fixture. BPE can split a character's bytes among tokens; do not try to decode each token separately just to count bytes.

The first original driver call therefore returns, approximately:

```
language_metrics(4*math.log(2), 2, 4)
→ {'loss': 1.3862943611198906, 'ppl': 4.0, 'bits_per_byte': 1.0}
```

Floating-point results may have tiny rounding differences; use math.isclose in comparisons.

Classroom Q&A: what does BPB actually mean?

Clarification: M counts scored source UTF-8 bytes, not embedding width D, vocabulary size V, target count N or tensor memory. With unscored prefix b and scored target 你 a, a defined tokenizer can yield two targets covering $3+1 = 4$ bytes, so $M = 4$ even if an embedding lookup stores16 float32 values/64 bytes. See the complete source-byte/embedding Q&A for the tokenizer, mask and coverage trace.

Think of BPB as **average model-based surprise, in bits, per original byte of scored text**. A model that predicts the actual text well assigns it higher probability. Higher probability means fewer ideal coding bits. Dividing by the source-byte count tells us how much information is needed for the same amount of original text.

First connect a probability to bits. One fair yes/no choice has two equally likely outcomes: selecting the observed outcome costs 1 bit, because $-\log_2(1/2) = 1$. Selecting one of eight equally likely outcomes costs 3 bits, because $-\log_2(1/8) = 3$. These are coding interpretations of probability; the model need not literally have two or eight candidate tokens.

Use the **same** abcd fixture from the figure, with its fixed preceding context:

Scored token contents	Original bytes	Model probability of this target	Ideal contribution $-\log_2(p)$
b"ab"	2	$1/2$	1 bit
b"cd"	2	$1/8$	3 bits
Whole scored text	4	Product $1/16$ along this token path	4 bits

The source occupies 32 raw bits. Its model-based ideal score is 4 bits, so:

$$\text{BPB} = \frac{(1+3)\text{ ideal bits}}{(2+2)\text{ source bytes}} = 1\text{ bit/byte}, \qquad \text{ideal size / raw size} = \frac{4}{32} = \frac{\text{BPB}}{8} = 12.5\%.$$

Read "1 bit per byte" as an **average conditional information cost**. Every original byte still contains 8 physical bits; token IDs and embeddings do not become one-bit objects. The intuition is that a shared predictor lets an encoder and decoder exploit patterns instead of explicitly transmitting every raw bit. This interpretation assumes the model, tokenizer, conditioning context and coding rules are already shared. The ratio excludes transmitting those resources, finite coding overhead and file headers. Individual $-\log_2(p)$ terms can be fractional; actual coding works over sequences and need not assign that exact number of whole bits to each token. This metric calculation alone creates no compressed artifact.

What improves when BPB falls? Keep the same text, tokenization, coverage and allowed context. A hypothetical second predictor assigns $1/4$ and $1/16$ to these same two targets, costing $2+4=6$ ideal bits, or BPB 1.5. The original predictor costs 4 bits, or BPB 1. Its probability product $1/16$ is higher than the second predictor's $1/64$: it predicts this observed token path better overall. It need not give every individual target a higher probability to achieve a lower total score. On a fixed held-out corpus, lower BPB similarly means a better aggregate probability score under that protocol; it does not directly measure answer accuracy or reasoning ability.

Why divide by bytes rather than tokens? Different tokenizers can split the same text into different numbers of targets. A common source-byte denominator avoids changing the reporting unit solely because one tokenizer uses larger chunks. It does not remove differences in the assigned score, context availability, special-token policy or preprocessing; those conditions still need to be aligned. Across different languages or corpora, UTF-8 byte patterns and text difficulty can differ too, so an unaligned BPB comparison is not a clean model ranking.

For a separate scale example, 1000 scored source bytes costing 2000 ideal bits give BPB 2; 1500 ideal bits give BPB 1.5. The latter saves 500 ideal bits, a 25% reduction for that same text. Raw storage would be 8000 bits in either case. BPB can also exceed 8 if the model assigns sufficiently low probabilities; the raw 8-bit representation is a separate coding option, not an upper bound on this model's score.

Hold bytes and total score fixed, then change token count

Construct another hypothetical scoring setup for the **same** bytes "abcd": four chunks b"a", b"b", b"c", b"d", each with correct-target conditional probability 1/2. Their product is also $1/16$ and their total loss is also $4\ln 2$, but now $N=4$.

$$L_B = \frac{4\ln 2}{4} = \ln 2, \quad \mathrm{PPL}_B = 2, \quad \mathrm{BPB}_B = \frac{4\ln 2}{4\ln 2} = 1.$$

Same bytes and total NLL, different token counts: perplexity still changes

Two deliberately constructed equal-score examples; changing a real tokenizer does not guarantee equal NLL.

Scored bytes	a	b	c	d	**M = 4**
A: two byte chunks	b"ab"		b"cd"		N = 2

Product of target probabilities: $1/2 \times 1/8 = 1/16$

S = 4 ln 2 L = 2 ln 2 PPL = 4 BPB = 1

B: four byte chunks	b"a"	b"b"	b"c"	b"d"	N = 4

Product of target probabilities: $(1/2)^4 = 1/16$

S = 4 ln 2 L = ln 2 PPL = 2 BPB = 1

At fixed S and M: larger N → smaller S/N → smaller PPL; BPB is unchanged.

Vocabulary size alone determines no direction for PPL; these numbers are not a language-quality experiment.

Figure 143: Equal constructed total scores over the same bytes yield different token-normalized perplexities

Read the two segmentations against the same four byte cells. A reports PPL 4; B reports PPL 2. Both assign the chosen target path a probability product $1/16$ and both report BPB 1. The smaller PPL here follows from the different token denominator, not a better total score for those bytes. The second original call is language_metrics(4*math.log(2),4,4), returning loss≈0.693147181, ppl≈2 and bits_per_byte≈1.

Equal S is a deliberate assumption in this counterexample. Retokenizing real text does not guarantee the same NLL. At fixed S, increasing N lowers PPL; using fewer, longer tokens would raise PPL. Vocabulary size alone implies no direction. This corrects the earlier draft's misleading suggestion that a larger vocabulary inherently lowers perplexity.

Compare perplexity under the same tokenizer and scoring protocol. BPB can help across tokenizers because bytes supply a common denominator, but the text, scored coverage, preprocessing, context policy and boundary treatment must still match. Official Transformers perplexity guide explains tokenization and context-window sensitivity. The BPB definition using UTF-8 byte counts also appears in the primary Paloma evaluation paper, Appendix B.

A precision note for later study: S here scores the tokenizer's chosen token sequence. If several token sequences decode to the same bytes, their probabilities would need to be summed to obtain a marginal byte-string probability. Merely dividing the chosen path's score by bytes does not perform that marginalization. The toy example compares its explicitly specified paths. Further primary reading: Exact Byte-Level Probabilities.

Add totals before computing a corpus metric

Suppose two batches cover disjoint scored text spans:

Batch	NLL sum S	Scored tokens N	Source bytes M	Mean loss	PPL	BPB
A	$\ln 2$	1	1	$\ln 2$	2	1
B	$9 \ln 2$	3	3	$3 \ln 2 = \ln 8$	8	3
Combined	$10 \ln 2$	4	4	$2.5 \ln 2$	$\sqrt{32} \approx 5.656854$	2.5

Add numerators and counts before computing global metrics: do not average batch perplexities

Separate batch example; batches cover disjoint scored bytes and each target is counted once.

batch	S (nats)	N (tokens)	M (bytes)	PPL	BPB
A	ln 2	1	1	2	1
B	9 ln 2	3	3	8	3
A + B	10 ln 2	4	4	$\sqrt{32} \approx 5.657$	2.5

$$L = \frac{S_A + S_B}{N_A + N_B} = \frac{10 \ln 2}{4} = 2.5 \ln 2$$

$$PPL = e^{2.5 \ln 2} = 2^{2.5} = \sqrt{32} \approx 5.656854$$

$$BPB = \frac{10 \ln 2}{4 \ln 2} = 2.5$$

Wrong: mean PPL is (2+8)/2=5; a token-weighted linear mean gives (2+3×8)/4=6.5.

Correct PPL is the token-weighted geometric mean: exp((1 ln 2 + 3 ln 8)/4).

Weight losses by tokens and BPB by bytes; the clearest implementation accumulates S, N and M first.

Figure 144: Accumulate NLL, target counts and byte counts before normalization; contrast incorrect PPL averages

The combined PPL is $\exp((\ln 2 + 9 \ln 2)/(1+3)) = 2^{2.5} \approx 5.656854$. The plain mean of batch perplexities is 5; even a token-weighted **linear** mean gives 6.5. Neither is correct. An unweighted mean of batch losses would give 2 ln 2 and PPL 4, also wrong because the batches have different target counts.

For batches j, the correct identities are:

$$L = \frac{\sum_j S_j}{\sum_j N_j} = \frac{\sum_j N_j L_j}{\sum_j N_j}, \qquad \text{PPL} = \exp\left(\frac{\sum_j N_j \ln \text{PPL}_j}{\sum_j N_j}\right), \qquad \text{BPB} = \frac{\sum_j S_j}{(\sum_j M_j)\ln 2}.$$

Thus losses are token-weighted, PPL is a token-weighted **geometric** mean, and BPB is byte-weighted. The simplest reporting pipeline accumulates S, N, M, then calls this helper once. Accumulating these sufficient statistics is also useful when workers report different valid-target counts. The assigned helper receives totals; it does not implement that outer loop.

If F.cross_entropy returned a mean L over N selected targets, recover $S = LN$ using the **same selection**. Do not pass that mean directly as nll_sum, and do not multiply by the number of padded slots. Lesson 07.02's evaluator will provide accumulated NLL and selected-target count, but the caller must also preserve matching byte coverage and special-target policy.

Keep the numerator and denominator about the same text

This lesson uses a **text-only target protocol**. Exclude structural EOS/BOS/role targets and PAD from S and N consistently; count only the corresponding ordinary-text bytes in M. Literal text "<eos>" is ordinary text, unlike 06.04's appended structural EOS. A structural token can still be conditioning context without being a scored target.

This convention does not retroactively change 06.06's training objective or 06.05's mask. A later evaluator sums whatever targets its mask selects; if its mask includes EOS, its totals are not automatically this text-only metric. Specify a different protocol explicitly or align the mask before supplying totals. There is no universal special-token policy implicit in the three numbers.

Check these alignment cases before calling the helper:

- A prompt used only as context contributes no scored targets or bytes. If next-token shifting omits the first token, omit its byte coverage too; use the whole-string byte count only if the whole string is scored.
- Overlapping windows can supply repeated context. Count each intended target once for this protocol; do not score a target several times while dividing by unique bytes once. Repeated document occurrences are separate scored occurrences when the evaluation includes them.
- For partially scored strings, retain token-byte lengths or byte-span metadata from the fixed tokenizer. Summing the byte lengths of selected ordinary token chunks works when those chunks exactly cover the intended spans. Guessing M from character count or token count does not.
- Match normalization, document boundaries, allowed context, resets, window length and stride across compared runs. The same bytes with different conditioning contexts can have different NLLs.

The function trusts its inputs; a mathematically correct division cannot detect a mismatched scoring protocol. Report the tokenizer/data version, coverage policy and counts alongside the metrics. Keep actual infrastructure mappings in ignored local configuration.

Connect these metrics to an actual training report

A reported mean loss of approximately 3.27 nats per selected target corresponds to perplexity $\exp(3.27)$, approximately 26.31, for that same selection and context protocol. This transforms the probability score; it does not turn it into an accuracy percentage. A uniform reference distribution over V classes has PPL V, but a nonuniform model's PPL can exceed V if it assigns very small probability to the observed targets.

A report can keep EOS-inclusive loss and text-only loss/BPB as separate measurements: the first also scores document endings, while the second scores only ordinary text. Exponentiate each mean only for its own selected targets. This exercise's text-only `nll_sum`, `tokens` and `utf8_bytes` must all describe the same scored ordinary text. For BPB, compute total bits from total NLL; dividing an already token-averaged loss by bytes would normalize twice.

When tokenizers differ, a constructed same-text, same-total-NLL case can have different token PPLs solely because N differs. BPB supplies a common byte denominator, but comparable reports still need matching text, normalization, scored coverage and context policy. A lower score on the same held-out protocol means improved probability prediction there. Instruction following, factual accuracy and other capabilities require their own evaluations.

Translate the exact interface into your implementation

```
def language_metrics(nll_sum: float, tokens: int, utf8_bytes: int) -> dict:
```

Return a **new dictionary** with exactly the string keys 'loss', 'ppl' and 'bits_per_byte', each mapped to a float. Do not return a tuple, tensors, per-batch arrays or different key names. Python / is true division, so dividing a float by an int returns a float. math.log(2) is $\ln 2$, not log base 2; math.exp(value) computes e to that value. Python math reference

Edit only between the START/END LEARNER CODE markers in the shared exercise. These steps are also saved beside that region. Keep run_checks unchanged.

1. **Read the inputs as totals.** S=nll_sum, N=tokens and M=utf8_bytes are already scalars. For the original call they are $4\ln 2$, 2, 4. No encoding, tensor reshape or loop is needed.
2. **Compute loss.** At four spaces inside the function, use / to divide the total nll_sum by tokens and store the float in a local variable such as loss. Expected intermediate value:$2\ln 2 \approx 1.386294361$.
3. **Compute ppl from that mean.** At the same four-space indentation, call math.exp on loss and store the result. Expected value:4. Exponentiating nll_sum would instead give 16, the inverse probability product before taking the Nth root.
4. **Convert total nats to total bits.** Use math.log(2) as the conversion divisor. You may name a temporary total_bits; its original value is 4. This is still a total, not a per-token average.

5. **Normalize those bits by utf8_bytes.** Store bits_per_byte; the original value is $4/4 = 1$. Equivalently use one fraction with the parenthesized denominator utf8_bytes*math.log(2). Do not use loss here, which has already been divided by N.
6. **Build and return the named dictionary.** Use a dictionary literal, whose fields use the syntax 'key': value separated by commas. The keys match the three names above; values come from your local results. return exits the function with that dictionary. It belongs at four spaces, after the calculations; continuation lines inside braces may be indented further for readability.
7. **Remove only the placeholder raise.** raise NotImplementedError currently stops execution. Replace it with your own calculations; preserve imports, function signature, region markers and the supplied check driver. No new for, if, try or tensor operation is required.
8. **Trace all three original calls before running.** First predicts loss $2 \ln 2$/PPL 4/BPB1. Second keeps S, M but doubles N: loss $\ln 2$ / PPL 2 / BPB 1. Zero NLL predicts loss 0/PPL1/BPB0 even though its positive counts are 3 and 8. Then run the unchanged driver.

Boundaries worth understanding, without expanding the assignment

For valid nonnegative S, $L \geq 0$, PPL ≥ 1 and BPB ≥ 0. At $S = 0$, $\exp(0) = 1$; perplexity is not 0. tokens=0 or utf8_bytes=0 violates the precondition and has no defined result in this exercise; an outer evaluator must handle an empty scored set explicitly.

PPL is not generally bounded by vocabulary size. In a two-class model, a true target assigned probability $1/1024$ has loss $\ln 1024$ and PPL 1024. If that target covers one byte, its ideal length is 10 bits and BPB 10, greater than 8. An inaccurate model can assign much less probability than a uniform byte model; raw byte width does not cap surprise.

math.exp can overflow even for a finite mean loss: $\exp(1000)$ cannot fit an ordinary Python float. $\exp(700)$ is still representable. Retain log-perplexity, which equals loss, in real reports; do not clip the loss or silently substitute a finite PPL. The supplied exercise fixtures avoid overflow, and adding an exception handler is not part of the learner task. Stable accumulation and evaluator mode/no-gradient handling belong to 07.02.

Lower held-out NLL under a fixed protocol means a better probability score on those targets. It does not prove truthfulness, instruction following or general reasoning. Those need separate task evaluations. No training-quality claim follows from these arithmetic examples.

Run and distinguish check evidence from understanding

From the repository root:

```
python exercises/07_01_language_metrics.py
```

After your implementation, expect:

```
Lesson 07.01 checks passed.
```

The unchanged supplied driver checks PPL/BPB for both equal-score tokenizations and the complete

zero-NLL dictionary. It does not explicitly check nonzero 'loss', exact keys/types on those calls, Unicode coverage, aggregation or overflow. These scalar checks do not validate a caller's real-corpus byte coverage or overflow handling.

Before moving on, explain these in your own words: why convert nats by dividing by $\ln 2$; why PPL uses a geometric mean; why its value changes when only N changes; why len("你 a") is the wrong byte denominator; and why mean batch PPL is wrong. For a short prediction drill, double S, N, M together: all three metrics should stay unchanged. Keeping S, N fixed and doubling M halves only BPB.

Classroom reference: the document-type handoff

A common question is why document used to be a dictionary but now appears directly in stream.extend(document). The missing explanation was the **explicit caller-side conversion between stages**. A variable name does not fix an object's type, and a type annotation does not convert data.

Use this complete handoff, with the same frozen BPE rule and special IDs as the continuous Chapter 06 example:

```
records = [
    {"id": "A", "text": "abab"},
    {"id": "B", "text": "ac"},
]
texts = [record["text"] for record in records]
# texts == ["abab", "ac"]

merges = {(97, 98): 256}
token_documents = encode_documents(texts, merges, eos_id=257)
# token_documents == [[256, 256, 257], [97, 99, 257]]

x, y, mask = pack_tokens(token_documents, context_length=3, pad_id=258)
```

This is caller wiring for your existing functions, not a learner-core replacement. The list comprehension visits each record, reads its "text" field, and collects the strings. Then encode_documents turns each string into BPE IDs and appends EOS257. The rule merges bytes97,98 ("ab") into ID 256; "ac" remains97,99. Original dictionaries remain in records; token_documents is a new object.

Stage	One item	Type
Original record	{"id": "A", "text": "abab"}	dict
Extracted text	"abab"	str
Encoded document, including EOS	[256, 256, 257]	list[int]
Input to pack_tokens	[[256,256,257], [97,99,257]]	list[list[int]]

Inside pack_tokens, documents refers to that last outer list. In for document in documents, the first document is [256,256,257] and the second is [97,99,257]. stream.extend(document) adds each integer to one flat stream:

```
start:       []
```

```
iteration 1:  [256, 256, 257]
iteration 2:  [256, 256, 257, 97, 99, 257]
```

extend adds the contents; append would instead add the entire list as one nested element. If a record dictionary were passed directly, extend would iterate its keys, producing [“id”,“text”], not tokens. Do not change this valid packing loop to document[“text”]: its input has already been encoded. Read the 06.05 representation diagram and full handoff alongside this trace. The original packing check’s IDs 1,2,3,4 are a separate hand-written fixture, not the BPE IDs above.

07.02 Fixed evaluation protocols

Method sources

The fixed-corpus evaluation perspective is informed by Magnusson et al., 2024; R30; the distinction between a token-path score and exact byte probabilities is discussed in Phan et al., 2024; R31. Our masks, denominator and frozen fixture are specified locally, not inherited as a benchmark certification.

Ask a different question of the same model

In 06.06, you changed parameters to improve next-token prediction. Evaluation asks: **with these parameters held fixed, how much probability does the model assign to a specified set of observed targets?** The forward calculation and selected cross-entropy look familiar; the purpose and state handling change.

Training loss on one repeated batch describes that batch. A held-out evaluation uses documents excluded from fitting the model. A lower training loss alone does not establish that prediction improved on those other documents. Compare checkpoints using the same data, tokenizer, contexts, target-selection policy and aggregation, so changes in the score have an interpretable meaning.

This lesson implements evaluate_fixed, a masked next-token **loss evaluator**, not a text generator or complete capability benchmark. It does not select a checkpoint, load data, fit tokenization, update parameters or decide which split to use. The caller supplies the model and already prepared batches. Existing Python/PyTorch is sufficient; no new environment or download is required.

Connect the exact interfaces from Chapters06 and 07

Earlier work	Its output or role	What this lesson reuses
06.01–06.03	Records, fingerprints, document groups and cleaned splits	Caller fixes the evaluation documents and preprocessing
06.04	Extracted text strings become list[list[int]] with fixed BPE/EOS IDs	Same tokenizer artifact for training and held-out text
06.05	pack_tokens returns x, y, mask tensors	Same aligned target layout and mask semantics

Earlier work	Its output or role	What this lesson reuses
06.06	pretrain modifies the passed model; history contains pre-update training losses	Evaluate that existing model without another training update
07.01	Convert NLL totals and counts to loss/PPL/BPB under a stated protocol	Supply trustworthy summed NLL and selected-target count

A batch is a **tuple of three tensors**, not a source dictionary and not one token list. The batches parameter is a list of such tuples. For example, once the corresponding exercise functions are complete:

```
val_texts = [record["text"] for record in validation_records]
val_token_documents = encode_documents(val_texts, merges, eos_id)
vx, vy, vm = pack_tokens(val_token_documents, context_length, pad_id)
validation_batches = [(vx, vy, vm)]
report = evaluate_fixed(model, validation_batches)
```

This is caller wiring. validation_records contains cleaned held-out dictionaries; extracting text and encoding happen before this function. Its supplied driver provides tensors directly, so it does not call language_metrics or require a real corpus to run. Do not call pretrain inside evaluation.

The continuous BPE example from 06.06 also fits: x/y/mask have shape(2,3), EOS257/PAD258, and a compatible model has $V \geq 259$. It selects five targets and gives ln 259 under an explicitly zero-logit diagnostic. That fixture demonstrates interface continuity, not a held-out quality measurement. The original 07.02 driver below deliberately uses a different, smaller vocabulary.

Guided session: collect the numbers that 07.01 received

In 07.01, language_metrics received nll_sum, tokens and utf8_bytes as already known scalars. This lesson moves one step upstream: **run the existing model on evaluation batches to obtain the first two totals**. The K used below is the same target-occurrence count called N in 07.01. It is not vocabulary size. The byte count M still comes from matching source-text coverage outside this function.

```
07.02: model + [(x, y, mask), ...] → {'nll_sum': S, 'tokens': K, 'loss': S/K}
07.01: S + K + matching source bytes M → mean loss, PPL, BPB
```

06.06 uses forward → loss → backward → optimizer update. Here the path ends at forward → selected losses → report. Parameters stay fixed. The caller supplies held-out batches if the goal is held-out evaluation; the function cannot decide whether a tensor came from training or validation data. The list contains tuples of tensors, not the earlier source-record dictionaries. If batches=[(x, y, mask)], there is one batch containing $B = 2$ rows; its list length 1 does not mean $B = 1$.

Formula and exact inputs before the trace

Let Z=model(x) be raw logits of shape(B, T, V), with b indexing rows, t positions and c vocabulary classes. The aligned target y[b, t] selects one class. Softmax gives its probability; categorical cross-

entropy gives its negative log:

$$p_{b,t,c} = \frac{e^{Z_{b,t,c}}}{\sum_{j=0}^{V-1} e^{Z_{b,t,j}}}, \qquad \ell_{b,t} = -\ln p_{b,t,y_{b,t}} = \log\left(\sum_j e^{Z_{b,t,j}}\right) - Z_{b,t,y_{b,t}}.$$

F.cross_entropy performs this log-softmax/target-selection calculation from raw logits. Do not call softmax first. reduction='none' retains one loss per target so that the bool mask can choose which losses enter the sum. This loss mask does not remove inputs or replace the causal attention mask inside a decoder.

One complete nonuniform example using the actual driver layout

Use the original x=[[0,1],[1,2]], y=[[1,2],[2,0]], mask=[[True, False],[True, True]], all with shape(2,2). x and y have dtype torch.long; mask has dtype torch.bool. $B = 2$, $T = 2$ and $V = 3$. y is already shifted/aligned, so evaluation does not shift it again.

For calculable probabilities, use a **separate constructed predictor**: input 0 gives class probabilities [1/4,1/2,1/4]; inputs 1 and 2 give [1/2,1/4,1/4]. Each vector sums to 1. Raw logits equal to the elementwise natural logs of those vectors realize these probabilities exactly, because their exponentials sum to 1. This is a fixed lookup fixture, not a numerical prediction about the driver's randomly initialized embedding/dropout/linear model. Its per-position result is:

Flattened q	Original (b, t)	Input ID	Target ID	Correct-target probability	Loss	Selected?
0	(0,0)	0	1	$1/2$	$\ln 2$	True
1	(0,1)	1	2	$1/4$	$2 \ln 2$	False
2	(1,0)	1	2	$1/4$	$2 \ln 2$	True
3	(1,1)	2	0	$1/2$	$\ln 2$	True

07.02: turn target probabilities into the totals used by 07.01

Original driver inputs; probabilities are a separate constructed example, not measured random-model outputs.

x: shape=(2,2), long

0	1
1	2

Rows b=0,1; cols t=0,1

y: shape=(2,2), long

1	2
2	0

Rows b=0,1; cols t=0,1

mask: shape=(2,2), bool

True	False
True	True

Rows b=0,1; cols t=0,1

Z: (2,2,3) → (4,3) y: (2,2) → (4,) CE(none): (4,) → (2,2)

q	(b,t)	[p(class 0), p(class 1), p(class 2)]	y	−ln p(y)	mask
0	(0,0)	[1/4, 1/2, 1/4]	1	ln 2	True
1	(0,1)	[1/2, 1/4, 1/4]	2	2 ln 2	False
2	(1,0)	[1/2, 1/4, 1/4]	2	2 ln 2	True
3	(1,1)	[1/2, 1/4, 1/4]	0	ln 2	True

losses: shape=(2,2)

ln 2	2 ln 2
2 ln 2	ln 2

→

losses[mask]: shape=(3,)

[ln 2, 2 ln 2, ln 2]

$S = 4 \ln 2 \approx 2.772589, \quad K = 3, \quad L = S/K \approx 0.924196$

return {'nll_sum': S, 'tokens': K, 'loss': L}

07.01 reuses S and K: PPL=exp(L)≈2.519842; BPB also needs matching source-byte count M.

Green contributes; gray excludes scoring without deleting context. These synthetic IDs do not determine M.

Figure 145: Exact driver input contents, hypothetical probabilities, selected losses and the 07.01 reporting connection

Read the top matrices as contents, with shape/dtype labels outside their cells. In the middle, each probability-vector coordinate is an output class, not a sequence position. The target ID picks one coordinate. Green entries count toward S and K; the gray entry still has a legal computed loss but contributes to neither total. Target ID 0 is valid and selected in the final row.

Flatten only the position axes for the cross-entropy interface: logits(2,2,3)→(4,3), y(2,2)→(4,). The four resulting losses reshape back to (2,2), preserving $q = bT + t$:

```
losses contents = [[ln2, 2ln2],      shape=(2,2)
                   [2ln2, ln2]]
losses[mask]   = [ln2, 2ln2, ln2]   shape=(3,)
```

Therefore $S = 4 \ln 2 \approx 2.772588722$ nats, $K = 3$, and loss=$S/K \approx 0.924196241$ nats/target. The exact return keys are 'nll_sum', 'tokens', 'loss'; their values are a Python float, int and float respectively. torch.sum() produces a scalar tensor of shape(); .item() extracts its Python number. mask.sum().item() counts 3 True entries, not 4 allocated positions.

Now evaluate the same rows as two batches. Row 0 contributes $(S_0, K_0) = (\ln 2, 1)$; row 1 contributes $(S_1, K_1) = (3 \ln 2, 2)$. Running totals progress $(0, 0) \to (\ln 2, 1) \to (4 \ln 2, 3)$. Their mean losses are $\ln 2$ and $(3/2) \ln 2$. Equally averaging them gives $(5/4) \ln 2 \approx 0.866433976$, whereas the correct target-weighted result is $(4/3) \ln 2 \approx 0.924196241$. Keep sums/counts and divide only after every batch. A zero-selected batch contributes sum 0/count 0 to the totals; taking its own mean would be undefined.

Send the result back to 07.01

07.01 uses the returned `nll_sum` and `tokens`: loss remains $(4/3) \ln 2$ and PPL $= \exp(L) = 2^{4/3} \approx 2.519842100$. For text-only targets with matching source-byte coverage M, BPB would be $S/(M \ln 2) = 4/M$. These synthetic ID tensors have no source-byte mapping, so **no numeric M or BPB is inferred here**. Do not substitute `x.numel()`, tensor memory size or vocabulary size for M. An actual text-only caller can connect the completed helpers as follows:

```
evaluation = evaluate_fixed(model, batches)
metrics = language_metrics(
    evaluation["nll_sum"], evaluation["tokens"], utf8_bytes
)
```

The caller must already have aligned mask selection and utf8_bytes, excluding structural targets consistently with 07.01. That wiring is outside the exercise function; evaluate_fixed itself returns only its specified three keys. Its returned loss intentionally repeats the same mean that 07.01 can compute.

The implementation plan below supplies the control-flow syntax and indentation. Save the old module mode, enter temporary eval/no_grad controls, accumulate per-target sums/counts, restore the saved mode in finally, then return after successful evaluation. No optimizer, backward or clearing of existing gradients belongs in this helper.

Define the quantity before choosing code

Let k index batches. A batch may have its own B_k rows and T_k positions; the model's output vocabulary size is V. For each legal target y, define:

$$Z^{(k)} = f_\theta(x^{(k)}), \qquad p^{(k)}_{b,t,c} = \text{softmax}(Z^{(k)}_{b,t,:})_c, \qquad \ell^{(k)}_{b,t} = -\ln p^{(k)}_{b,t,y^{(k)}_{b,t}}.$$

The observed targets are already aligned with input positions, as in 06.05/06.06. Teacher forcing still uses the observed prefix; evaluation does not sample predictions and substitute them into x. The mask selects target losses, not input visibility or vocabulary columns.

For each batch, retain its selected **sum and count**:

$$S_k = \sum_{b,t:m^{(k)}_{b,t}=1} \ell^{(k)}_{b,t}, \qquad K_k = \sum_{b,t} m^{(k)}_{b,t}.$$

Across all batches, report:

$$S = \sum_k S_k, \qquad K = \sum_k K_k > 0, \qquad \boxed{\widehat{L} = \frac{S}{K}}.$$

Quantity	Meaning	Python result
S	Total selected negative log-likelihood, natural-log units/nats	'nll_sum': float
K	Number of selected target occurrences	'tokens': int
$\widehat{L}$	Mean selected loss, nats per target	'loss': float

K is not vocabulary size, number of documents, number of batches or allocated tensor slots. Count repeated scored occurrences when the protocol includes them. The evaluator implements the supplied selection; the caller must prevent unintended overlapping-window double counting.

Trace the exact original driver

The driver constructs nn. Sequential(Embedding(3,4), Dropout(.8), Linear(4,3)) and starts it in training mode. It supplies:

```
x    = [[0,1], [1,2]]
y    = [[1,2], [2,0]]
mask = [[True,False], [True,True]]
```

Here $B = 2, T = 2, V = 3$. The embedding width 4 is internal to the model; it is neither T nor V. The embedding produces(2,2,4), dropout preserves that shape, and the linear head produces raw logits(2,2,3).

Flattened $q = bT + t$	Original (b, t)	Input ID	Target ID	Selected?
0	(0,0)	0	1	True
1	(0,1)	1	2	False
2	(1,0)	1	2	True
3	(1,1)	2	0	True

The final target 0 is valid. The excluded target at (0,1) has the same ID 2 as the selected target at (1,0); selection depends on the mask, not on the ID value. These are hand-written synthetic IDs, not outputs of the BPE fixture. Do not give them EOS257/PAD258 meanings.

Reuse the aligned tensor interface: score three targets out of four positions

The original driver supplies x/y/mask by hand; these IDs are not BPE outputs. B=2,T=2,V=3.

x: shape=(2,2)

long

t=0	t=1
0	1
1	2

y: shape=(2,2)

long

t=0	t=1
1	2
2	0

mask: shape=(2,2)

bool

t=0	t=1
True	False
True	True

logits: (2,2,3) → (4,3) y: (2,2) → (4,) CE(none): (4,) → (2,2)

Analytic baseline: each position has logits [0,0,0], giving correct-target probability 1/3.

ln 3	ln 3
ln 3	ln 3

→ **selected: shape=(3,)**

[ln 3, ln 3, ln 3]

$S = 3\ln 3 \approx 3.295837, \quad K = 3, \quad L = S/K = \ln 3 \approx 1.098612$

True selects a target; False does not remove input context. y is aligned already; do not shift it again.

Actual random model scores need not be zero; do not confuse this baseline with measured driver output.

Figure 146: Original tensors, target selection and a clearly labeled uniform-logit baseline

Read the three upper tables as contents, with shapes/dtypes outside the cells. For a fully calculable **analytic baseline**, suppose all three logits at every position equal 0. Each correct-target probability is $1/3$ and each loss is $\ln 3$. Select three values:

$$S = 3\ln 3 \approx 3.295836866, \qquad K = 3, \qquad \widehat{L} = \ln 3 \approx 1.098612289.$$

The conceptual return is {'nll_sum':$3\ln 3$,'tokens':3,'loss':$\ln 3$}. Actual random model weights are not zero and the original driver does not prescribe a numeric score. Its main comparison evaluates the same rows once as a full batch and once as two one-row batches. In eval mode this particular model is independent across rows, so both ways must agree within floating-point tolerance.

Show why unequal batches require sums and counts

The uniform example cannot expose every aggregation error: averaging equal batch means gives the same answer accidentally. Use a separate two-class lookup diagnostic with deliberately different losses.

A fixed table W maps input IDs to raw logits; its columns are output classes 0 and 1:

$$W = \begin{bmatrix} -1 & \ln(1-e^{-1}) \\ \ln(1-e^{-2}) & -2 \end{bmatrix}, \qquad Z = W[x].$$

Each row's exponentials sum to 1. Therefore input 0 gives target 0 probability e^{-1}, with loss 1; input 1 gives target 1 probability e^{-2}, with loss 2. This table is an arithmetic fixture, not the original embedding/dropout model and not a trained checkpoint.

Use these synthetic batches, with all targets legal:

```
A: x=[[0,0,0]], y=[[0,0,1]], mask=[[True,True,False]]
B: x=[[1,1,1],[1,0,0]], y=[[1,1,1],[1,1,1]],
   mask=[[True,True,True],[True,False,False]]
```

The deliberately excluded labels need not have a particular ID. Their losses are computed before selection and then omitted. For input 0/target 1 those excluded losses are $-\ln(1-e^{-1}) \approx 0.458675$; their values do not affect S or K.

Batch	Selected losses	Selected sum	Count	Batch mean
A	[1,1]	2	2	1
B	[2,2,2,2]	8	4	2
Combined	Six values above	10	6	$10/6 = 5/3 \approx 1.666667$

Divide total NLL by total targets: batch means cannot be averaged equally

Separate two-class lookup: A correct-target probability is exp(−1), B is exp(−2); gray slots are excluded.

A: losses shape=(1,3), K_A**=2**

1	1	.458675⋯

S_A=1+1=2 L_A=1

B: losses shape=(2,3), K_B**=4**

2	2	2
2	.458675⋯	.458675⋯

S_B=2+2+2+2=8 L_B=2

$$S = S_A + S_B = 10, \qquad K = K_A + K_B = 6$$

$$L = \frac{S}{K} = \frac{10}{6} = \frac{5}{3} \approx 1.666667$$

$$L = \frac{2 \cdot 1 + 4 \cdot 2}{2 + 4} \neq \frac{1 + 2}{2} = 1.5$$

A zero-target batch contributes (S_k,K_k)=(0,0); never take the mean of an empty selection.

Regroup the same rows/prefixes/masks; changing context segmentation is not equivalent evaluation.

Figure 147: Nonuniform selected counts and the correct global denominator

The green cells contribute; gray cells do not. After A, running totals are $S = 2$, $K = 2$. After B, $S = 10$, $K = 6$. Divide once after all batches. The unweighted mean of batch means,$(1+2)/2 = 1.5$, gives the smaller batch too much weight. The equivalent weighted mean is:

$$\widehat{L} = \frac{\sum_k K_k L_k}{\sum_k K_k} = \frac{2 \cdot 1 + 4 \cdot 2}{6} = \frac{5}{3}.$$

An individual batch may select zero targets even though the complete list selects at least one. Its empty selection has sum 0 and count 0, so accumulation still works. Taking that batch's empty mean would give NaN. The exercise does not require a new special-case branch or a defined result for total $K = 0$.

Regrouping is equivalent only when it retains the same input rows, prefixes, positions and target mask under a row-independent evaluation model. Splitting along B, as the original driver does, retains each row's context. Cutting a causal sequence along T or repacking text changes context/position treatment and may change predictions. Accumulation-order rounding also means comparison should use a tolerance rather than bitwise equality.

Understand two independent controls

`model.eval()` sets the module and its children to evaluation mode, equivalent to train(False). It changes behavior of relevant modules such as ordinary dropout, which stops dropping/scaling activations. It does **not** disable autograd, clear gradients or update weights. Official Module.eval definition

`with torch.no_grad():` temporarily disables reverse-mode graph recording for ordinary new operations in its block. This avoids building the parameter-gradient graph we will not use during evaluation. It does **not** switch off dropout, clear existing .grad tensors or change parameter requires_grad flags. Leaving the block restores the caller's preceding grad-enabled/disabled context. Official no_grad definition

Two independent controls: eval changes module behavior; no_grad changes graph recording

Separate dropout example: h=[1,2,3,4], p=.5; illustrative training keep-mask=[1,0,1,0].

	Ordinary grad mode	**with torch.no_grad()**
train()	Output [2,0,6,0] **Allow graph recording: Yes** Dropout still samples a mask	Output [2,0,6,0] **Allow graph recording: No** Dropout still samples a mask
eval()	Output [1,2,3,4] **Allow graph recording: Yes** Ordinary dropout is identity	Output [1,2,3,4] **Allow graph recording: No** Ordinary dropout is identity

no_grad does not clear old .grad or change requires_grad; eval itself does not disable autograd.

This evaluator uses the lower-right combination: eval mode with no_grad.

Figure 148: Module mode and autograd recording are separate switches

Read rows as module mode and columns as grad mode. The numerical dropout example uses h=[1,2,3,4], p=.5 and an illustrative keep-mask[1,0,1,0]. In training, retained entries are divided by $1 - p$, giving [2,0,6,0]. In evaluation, dropout is the identity, giving [1,2,3,4]. The training keep-mask is an explicit illustration, not a promised random sample. The graph labels describe whether recording is permitted, not whether an identity operation necessarily creates a new graph.

Use both controls for this evaluator. Neither is a universal reproducibility switch: custom forward randomness, batch-coupled behavior or nondeterministic operations can still matter. For example, a custom model can call a random operation even in eval mode. This helper does not restore arbitrary RNG streams or enforce deterministic kernels. The supplied ordinary dropout model is deterministic in evaluation under the checked conditions.

Preserve state so evaluation can sit between training updates

06.06 leaves the model in training mode and may leave gradient tensors from its last backward call. This evaluator must leave those parameter values, parameter identities, gradient objects and gradient contents unchanged. Do not construct an optimizer, call backward/step/zero_grad, detach/replace parameters or set requires_grad=False. There is nothing to optimize here.

Save the Boolean model.training **before** changing it. At the end, model.train(old_mode) restores that root mode: True returns to training and False stays in evaluation. Calling model.train() unconditionally would incorrectly change a caller that was already evaluating. The method only sets mode; it does not run a training step.

The specified restoration is the model's original root flag. Standard train(mode) propagates the flag to child modules, so it does not reconstruct a pre-existing mixture of training/eval child flags. The supplied model begins uniformly train or eval. Supporting a heterogeneous per-module mode snapshot is a separate interface extension, not an unannounced learner requirement.


Ordinary eval-mode dropout/linear/embedding do not mutate weights; the helper is not a sandbox for an arbitrary custom forward that mutates its own parameters or buffers. Preserve the stated ordinary-model contract without claiming that no_grad prevents all Python side effects.

Learn try/finally before relying on it

Suppose a later batch raises an exception during forward or cross-entropy. A restoration statement placed only at the bottom of the successful path would be skipped. Python try/finally gives a cleanup path that runs on normal completion and exception propagation. No except block is needed to swallow or transform the error. Python cleanup explanation

Save the mode, evaluate temporarily, and restore it on success or failure

Example: enter with model.training=True and grad mode enabled; both return to their original states.



Success: return the metrics afterward. Error: propagate it; do not return a partial score.

If old_mode=False, restore eval. train(old_mode) sets a mode; it does not perform a training update.

Figure 149: Mode and grad context are restored on normal completion and failure

Follow the success and failure arrows into the same finally box. The no_grad context exits first and restores grad mode; finally restores module mode. After successful cleanup, return the final metrics. If evaluation fails, let the original exception propagate rather than returning a partial score. Do not put return inside finally, where it could suppress an error.

The implementation's indentation map is:

```
4 spaces: save old_mode; initialize float sum and integer count
4 spaces: try:
8 spaces:     model.eval()
8 spaces:     with torch.no_grad():
12 spaces:        for x, y, mask in batches:
16 spaces:            forward, per-position CE, selected sum/count accumulation
4 spaces: finally:
8 spaces:     model.train(old_mode)
4 spaces: return the complete result after successful evaluation
```

The colon introduces each block. for unpacks one supplied three-tensor tuple per iteration. with establishes a temporary context. finally belongs at the same indentation as try, not inside the batch loop. This is a map of responsibilities, not the exercise function.

Specify the exact assignment interface and shapes

```
def evaluate_fixed(
    model: nn.Module,
    batches: list[tuple[torch.Tensor, torch.Tensor, torch.Tensor]],
) -> dict:
```

model is an existing module returning floating logits(B, T, V). batches is a nonempty list of tuples(x, y, mask). x/y are torch.long(B, T), mask is torch.bool(B, T). Within a batch their shapes match; different batches may have different B/T compatible with the model. Inputs/devices and model capacity are compatible. All evaluated target IDs, including excluded ones, are legal classes $0 \ldots V-1$. A negative ignore label is not part of this lesson's mask contract. At least one target is selected across the whole list; individual zero-selection batches are valid. No additional input-validation task is assigned.

Return a new dictionary with exactly 'nll_sum' as float, 'tokens' as int and 'loss' as float. The first is a **sum**, the last is that sum divided by the total count. The function receives no utf8_bytes and cannot infer source-byte coverage from token IDs. It neither returns BPB/PPL nor calls language_metrics; these remain a caller reporting step.

Intermediate	General shape/type	Original one-batch fixture
model(x)	Floating(B, T, V)	(2,2,3)
Flattened logits	Floating(B*T, V)	(4,3)
Flattened y	long(B*T,)	(4,)
CE with reduction='none'	Floating(B*T,)	(4,)
Losses restored to y shape	Floating(B, T)	(2,2)

Intermediate	General shape/type	Original one-batch fixture
Mask-selected losses	Floating $(K_k,)$	(3,)
Selected .sum()	Scalar tensor, shape()	$3 \ln 3$ under zero logits
.sum().item()	Python float	Approximately 3.295837
mask.sum().item()	Python int	3

Use reshape rather than assuming contiguous storage for view. Read V from logits.shape[-1]. The vocabulary axis stays together when flattening positions. As in 06.06, F.cross_entropy accepts raw logits; do not softmax first. `.reshape_as(y)` uses y's shape, not its values. `.item()` is appropriate here because evaluation does not need parameter gradients and totals should be Python numbers. Official cross-entropy interface

Guided implementation in twelve steps

Edit only the START/END learner region in the actual exercise. Its comments repeat this guidance. Keep the original run_checks intact.

1. **Save and initialize at four spaces.** Save model.training in a local old_mode before changing it. Initialize a Python float total such as total_nll=0.0 and an integer total such as total_tokens=0. These describe the entire list, so create them outside the loop.
2. **Open try at four spaces.** Inside it at eight spaces call model.eval(). The saved old_mode remains available for cleanup. Do not replace the passed model with a new model or a training clone.
3. **Open the grad-disabled context at eight spaces.** Use with torch.no_grad():. Its body starts at twelve spaces. This temporarily controls graph recording independently of the module mode.
4. **Loop over batches at twelve spaces.** Use for x, y, mask in batches:. Each iteration unpacks one tuple. The repeated body uses sixteen spaces. Do not shift y, tokenize, generate or deduplicate positions.
5. **Compute raw logits at sixteen spaces.** Call model(x), then read V from its last dimension. The original fixture gives(2,2,3); after row splitting each call gives(1,2,3). The different B does not change the three classes.
6. **Preserve position alignment for CE.** At sixteen spaces reshape logits to(-1, V) and y to(-1), call F.cross_entropy with reduction='none', and restore the returned vector using reshape_as(y). The original shapes are(4,3),(4,), then(2,2). Keep every class column and individual position loss until selection.
7. **Accumulate the selected sum.** Select with the bool mask, call .sum(), then .item(), and add that float to total_nll using +=. Do not take a batch mean. In the separate nonuniform fixture, the running sum is 2 after A and 10 after B.
8. **Accumulate the corresponding count.** Add mask.sum().item() to total_tokens; it is an integer count. In that fixture the totals are 2 then 6. A batch with no selected targets contributes 0 to both sums naturally.
9. **Finish all iterations before dividing.** Keep both accumulation statements inside the loop. Ex-

iting for/with leaves the final Python totals available and restores the previous grad context. Do not return after the first batch or calculate a mean of an empty per-batch selection.

10. **Write finally at four spaces.** At eight spaces within it call model.train(old_mode). It runs after success or an evaluation exception. Restore the saved Boolean rather than always forcing train mode. Do not call zero_grad or return here.
11. **Return at four spaces after finally.** Build the exact three-key dictionary from the completed sum/count and their ratio. The nonuniform example expects nll_sum≈10.0, tokens=6, loss≈1.666667. This return executes only after successful evaluation; errors continue outward after cleanup.
12. **Replace the placeholder and check.** Remove raise NotImplementedError, preserve the signature/imports/markers/driver, and run the command below. No optimizer, backward call, exception-swallowing branch or new environment belongs in this implementation.

Connect the returned totals to 07.01 without changing the protocol

The evaluator sums **whatever mask selects**, including EOS if the caller includes EOS targets. It does not silently impose 07.01's text-only BPB protocol. To use language_metrics(S, K, M), select ordinary-text targets consistently and retain the corresponding original UTF-8 byte count M. Exclude unscored prompts/padding and structural targets from both numerator and denominators under that stated text-only convention. Repacking must not double-count target occurrences. A token count alone cannot recover M.

Classroom Q&A: what exactly is M? Is it embedding/token size?

Question: after completing 07.02, the learner asked whether BPB means bits per byte and whether M is the size of the whole embedding or its tokens.

Yes: **BPB = bits per byte**. M is the number of **original UTF-8 bytes covered by the scored ordinary-text targets**. It is not the vocabulary size V, target occurrence count N, embedding width D, embedding parameter count or tensor storage size. An embedding row contains learned numeric features, not a sequence of the token's UTF-8 bytes. The tokenizer supplies that separate byte mapping.

$$BPB = \frac{\sum_i -\log_2 p_i}{M} = \frac{S}{M \ln 2}.$$

The original three-ID synthetic driver still supplies no byte mapping, so its M is unknown. For a **new, explicit tokenizer example**, begin with 256 byte tokens and learn (228,189)→256, then (256,160)→257. ID 257 now covers the three UTF-8 bytes of "你"; ID 97 covers the one byte of "a". EOS 258 / PAD 259 give vocabulary size $V = 260$.

Use unscored prefix "b" and scored continuation "你 a". The aligned input/target IDs are x=[[98,257]], y=[[257,97]], mask=[[True, True]]:

Target ID	Token contents	Original byte values	Counted source bytes
257	你	[228,189,160]	3
97	a	[97]	1
Total	你 a	Four bytes above	$M = 4$

BPB counts source bytes: M is neither token count nor embedding width

Separate tokenizer fixture: (228,189)→256, then (256,160)→257; EOS258, PAD259, V=260.

Unscored prefix: b Scored target: 你 a

98	228	189	160	97

你: 3 bytes; token ID257 a: 1 byte; ID97

x = [[98,257]] y = [[257,97]] mask = [[True,True]]

x, y and mask each have shape (1,2); the entries above are contents, not dimensions.

M	Scored source bytes	3 + 1 = 4
N	Scored target occurrences	2
V	Vocabulary size	260
D	Embedding width	8

Embedding table E: shape=(260,8). Lookup E[x]: shape=(1,2,8).

The lookup has 16 floats: 64 bytes of float32 storage. M remains 4.

Score only a: M=1. Score only 你: M=3. Changing D does not change those byte counts.

Figure 150: Source byte accounting separated from target counts, vocabulary capacity and embedding dimensions

The prefix b is input context and contributes no scored bytes. The complete string b 你 a occupies 5 bytes, but this evaluation scores only "你 a", so $M = 4$. Here $N = 2$ target occurrences, $V = 260$ vocabulary entries, and choose $D = 8$ embedding features. The embedding table shape is(260,8);

the looked-up E[x] shape is(1,2,8), containing 16 floating numbers. Float32 storage for that lookup occupies 64 bytes. An int64 y tensor occupies 16 bytes and y.numel()=2. **None of 64,16,2,260,8 is the source-byte count 4.** Changing D to 16 changes lookup storage to 128 bytes while M remains 4.

If the loss mask selects only "a", $N = 1$ and $M = 1$; if it selects only "你", $N = 1$ and $M = 3$. The embedding shapes stay unchanged. Recompute the NLL numerator S with the same selection too. For these ordinary tokens, matching target-byte metadata is [[3,1]], which can be summed under the text-target mask. Byte-BPE token byte chunks can provide these lengths even if one chunk alone is not valid decoded text. Structural EOS/PAD have no ordinary-text byte contribution and are excluded from the text-only NLL/count policy as well.

Compute len(scored_text.encode('utf-8')) when the entire provided target text is scored. With partial spans/windows/masks, retain aligned byte coverage or derive it from the tokenizer's byte chunks under the exact scoring policy. The model's embedding weights alone cannot provide M. This also explains why evaluate_fixed returns NLL/counts but has no utf8_bytes field: its interface receives neither source text nor tokenizer/byte metadata.

For any fixed selected-token protocol, log-perplexity is the reported loss and PPL $= \exp(L)$, subject to representability. Across different tokenizers, token-normalized perplexities require care as explained in 07.01. Never average batch perplexities or pass a batch-mean loss as the summed NLL. This function supplies S and K specifically so reporting can aggregate correctly.

In a later experiment, evaluate the same frozen validation batches before and after a budgeted 06.06 training run. The evaluator's old-mode restoration lets it fit between training updates without clearing pending gradients or leaving dropout in the wrong mode. The existing integration lab additionally needs 07.04 inference components; preparing 07.02 does not fill those future learner regions or make the whole lab complete.

Freeze the protocol outside the helper

A function name cannot freeze an experiment by itself. Save a portable protocol record covering:

Protocol component	What must agree across compared checkpoints
Data and membership	Dataset revision, content fingerprints and fixed held-out document IDs/groups
Tokenization	Tokenizer artifact/hash, normalization, merge/special-ID meanings
Context and boundaries	Row construction, sequence length, context resets, EOS transitions and window/stride coverage
Target selection	Exact mask policy, special/PAD targets and any prompt exclusions
Aggregation and execution	Selected NLL sum/count, numerical precision, model eval/no_grad procedure and code revision
Artifacts and interpretation	Model checkpoint identifier/checksum, configuration, training budget, reported totals and limits

Keep train, validation and final test roles distinct. Training fits parameters; validation can guide choices among variants; a final test set should not become another tuning set. Exact content duplicates and normalization-equivalent or near-duplicate material can compromise a holdout despite correct score arithmetic. The source-grouping and cleaning discussion in 06.02/06.03 remains relevant.

A loss evaluator does not establish truthfulness, instruction following or reasoning ability. Such tasks additionally require fixed prompts, decoding/stopping settings, answer extraction and scoring rules. An exact-answer accuracy denominator should include failed generations among all attempted tasks; silently dropping failures changes the metric. This chapter does not implement those task evaluators.

Run, inspect the driver and record evidence honestly

```
python exercises/07_02_fixed_evaluation.py
```

After your implementation:

```
Lesson 07.02 checks passed.
```

The unchanged driver checks tokens=3, one-batch versus two-row-batch mean agreement, restoration from both starting train/eval modes, unchanged state_dict values and preservation of existing gradient object identities.

Numerical boundary: losses*mask is equivalent to selection for finite losses, but* $0 \cdot \infty$ *is NaN. A two-position finite-logit fixture gives losses [*$\ln 2$*, inf] with mask [True, False]; the selected sum is* $\ln 2$ *while multiplying before selection gives NaN. Boolean-index the losses before summing; preserve the loop and mode restoration. An infinite* selected* loss should still be reported as such rather than silently discarded. Returning loss=0 for total_tokens=0 would extend the positive-total contract; an empty mean is undefined.

Before coding, predict the A/B totals and explain why they cannot be averaged equally. Then explain why eval alone permits graphs, why no_grad alone leaves training dropout active, why existing gradients should remain untouched, and why cleanup needs finally.

07.03 KV cache and position alignment

Method sources

For ordinary incremental multi-head attention retaining past keys and values, see Shazeer, 2019; R19, Section 2.4; Hugging Face, v4.57.1; R37 provides an implementation-oriented explanation. This append-only cache is not the paper's multi-query proposal (Section 3) or the paged memory manager of Kwon et al., 2023; R20; those are distinct optimizations.

Reuse the unchanged prefix

07.01 reported probability scores. 07.02 measured observed targets with fixed model parameters. 07.03 asks: **when generation appends a token, which earlier calculations can we reuse?** It performs no training update or BPB calculation.

An uncached loop processes a 100-token prefix, then 101 tokens, then 102. Under causal attention, old positions cannot depend on later arrivals. With unchanged prefix, fixed weights and evaluation behavior, each old hidden state is unchanged; its projected key/value at each layer is unchanged too. A **key-value cache (KV cache)** retains those tensors. New queries still attend to past keys/values; caching avoids recomputing them. Each layer has its own cache because it projects different hidden states. Official cache explanation

Prefill processes the prompt, often many positions in one call with cache=None. **Decode** commonly processes one new token per call. This exercise also accepts several new positions, so it must preserve causality within that new chunk. It receives already projected q/k/values for one layer; 07.04 will connect it to the model/generation loop.

Follow the same tokens across three calls

Use the illustrative token labels `I`, `like`, `tea`, `.`; these labels do not assert how the real tokenizer splits those words.

1. The prompt contains `I like`. The model processes both positions, builds K/V at each layer, and the last position's logits let us select `tea`.
2. The next call processes only `tea`. Each layer computes its new Q/K/V at position 2, reuses positions 0 and 1 from its cache, and selects the following token `.`.
3. The following call processes only `.` at position 3. The old three positions remain cached.




Figure 151: Three calls with and without cached prefix work; position slots and vector shapes are labeled separately

The upper lane recomputes 2, then 3, then 4 rows. The lower lane computes 2, then 1, then 1 new rows. The small cache tiles label **positions covered by vectors**, rather than showing vector contents. Each layer has its own K/V tensors; actual contents appear in the next matrix figure.

The selected token is not processed until the next call. Attention produces a feature vector; the vocabulary head produces logits; selection produces a token ID. These are three different objects. Lesson 07.04 connects them into the generation loop.

Why the earlier vectors stay valid

At position 0, causal attention sees only position 0. Appending position 2 cannot change that information. At position 1, attention sees positions 0 and 1, so the appended position cannot change that result either.

Now follow this argument through the layers. The token embedding and positional transformation for an earlier position stay the same. Attention only reads its earlier-or-current positions. Our RMSNorm and FFN act on features within each position; the residual adds vectors at matching positions. Therefore unchanged past rows at one layer imply unchanged past rows at the next layer. Their projected K/V remain reusable. This relies on the same prefix, positions, weights and evaluation behavior.

Changing feature width or reshaping heads does not erase the position axis. The wrapper still knows which row is position 0, 1 or 2. Operations that actually mix/reorder positions differently would need a different cache argument; our decoder does not do that.

Why save K and V, rather than Q? The new query asks how to read all available keys and values. Earlier queries were needed to calculate earlier outputs; they are not arguments in the new query's attention calculation. Cache the past K/V, and calculate a new Q for each new position.

A nonzero example with unequal attention weights

The zero-Q/K fixture later in the worksheet is a useful arithmetic check, but every allowed weight becomes equal. It does not explain matching or position offsets. Start here instead.

For one layer/head, let $B = H = 1$ mean one batch row and one head. Keep $P = 2$ cached positions and process $S = 1$ new position, with query/key width $d = 2$ and value width $d_v = 2$. These are **post-RoPE** Q/K values, with their position transformation already applied. The first two rows of K/V are cached; the third row is new:

$$q_2 = [\sqrt{2}, 0], \qquad K_{\text{all}} = \begin{bmatrix} 0 & 1 \\ \ln 2 & 1 \\ \ln 3 & 1 \end{bmatrix}, \qquad V_{\text{all}} = \begin{bmatrix} 2 & 0 \\ 0 & 4 \\ 6 & 6 \end{bmatrix}.$$

Full tensor shapes are `q [1,1,1,2]`, `K_all [1,1,3,2]`, `V_all [1,1,3,2]`. The displayed matrices fix the batch/head indices. The integer 2 in $d = 2$ counts coordinates; a cell entry such as $\ln 2$ is a numeric value, approximately 0.693.

Scaled dot products give:

$$r_2 = \frac{q_2 K_{\text{all}}^{\mathsf{T}}}{\sqrt{2}} = [0, \ln 2, \ln 3].$$

Query position 2 can see all three available key positions, so nothing is masked in this one-query example. Applying softmax means exponentiating and normalizing:

$$\exp(r_2) = [1, 2, 3], \qquad a_2 = [1/6, 2/6, 3/6].$$

A score of zero still receives positive weight; a blocked score must instead become negative infinity. The output is a weighted **vector**, with two coordinates:

$$o_2 = \tfrac{1}{6}[2, 0] + \tfrac{2}{6}[0, 4] + \tfrac{3}{6}[6, 6] = [10/3, 13/3].$$




Figure 152: Nonzero Q/K, explicit transposition shapes, nonuniform softmax and a two-coordinate weighted output

Read this figure from the saved/new rows, through Q times transposed K, then through weights times V. Blue rows are retained; green rows are new. Shape labels sit outside numeric cells. The result has shape `[1,1,1,2]`; it is not a token ID or the entire layer cache.

For implementing the exercise, inputs are **before** RoPE. The raw new query for this particular figure can be chosen as `[sqrt(2)*cos(2), -sqrt(2)*sin(2)]`; applying position-2 rotation gives the displayed `[sqrt(2),0]`. Similarly, choose the raw new key as the inverse position-2 rotation of `[ln(3), 1]`. Existing cached keys already have their transformations. This distinction keeps the hand example consistent with the function contract.

Exact objects, axes and units

```
def cached_attention(q: torch.Tensor, k: torch.Tensor,
                     values: torch.Tensor, cache: dict | None
                     ) -> tuple[torch.Tensor, dict]:
```

Symbol	Meaning	Unit
B	Batch rows	Samples
H	Attention heads	Heads
P	Cached earlier positions	Token positions
S	New positions in this call	Token positions
d	Query/key matching width; positive and even	Feature coordinates per head
d_v	Value width; may differ from d	Feature coordinates per head

Here S is a position count, unrelated to 07.01's summed-NLL symbol S. BPB's source-byte count M is not an attention dimension.

Parameter	Shape/type	Meaning
q	Floating [B, H, S, d]	New projected queries, before RoPE
k	Floating [B, H, S, d]	New projected keys, before RoPE
values	Floating [B, H, S, dv]	New projected values, not rotated
cache	None or dictionary	Missing prefix state, or the tensors below
cache['keys']	Floating [B, H, P, d]	Old keys, already rotated at their positions
cache['values']	Floating [B, H, P, dv]	Old unrotated values

Sizes/devices/dtypes are compatible, and B, H, S, d, d_v are positive. Return output [B, H, S, dv] for **new queries only**, plus a **new dictionary** with keys [B, H, P+S, d] and values [B, H, P+S, dv]. Preserve inputs and old cache; inference outputs/cache should not retain autograd history. Cloning values inside no_grad on first use also gives independent storage.

The original driver uses float32. The existing 05.02 helper's half-dtype restoration follow-up remains open; this lesson's original/reference examples use float32/float64. The cache is not an embedding table, stored text, model weights or all layers combined.

Formulas first

New query index $i = 0, \dots, S-1$ corresponds to absolute sequence position:

$$p_i = P + i, \qquad p = [P, P+1, \dots, P+S-1].$$

Use the supplied 05.02 apply_rope(x, positions, base=10000.0) on new q/k:

$$\widetilde{Q} = \text{RoPE}(q, p), \qquad \widetilde{K}_{\text{new}} = \text{RoPE}(k, p),$$

$$K_{\text{all}} = K_{\text{past}} \|_{\text{time}} \widetilde{K}_{\text{new}}, \qquad V_{\text{all}} = V_{\text{past}} \|_{\text{time}} \text{values}.$$

The concatenation symbol means old rows followed by new rows. Without a cache, $P = 0$ and these are just the new tensors. **Do not rotate cached keys again or rotate values.** Compute scores R, weights A and outputs O:

$$R = \frac{\widetilde{Q} K_{\text{all}}^{\mathsf{T}}}{\sqrt{d}}, \qquad R^{\text{masked}}_{b,h,i,j} = \begin{cases} R_{b,h,i,j}, & j \le P + i, \\ -\infty, & j > P + i, \end{cases}$$

$$A_{b,h,i,:} = \text{softmax}(R^{\text{masked}}_{b,h,i,:}), \qquad O = A V_{\text{all}}.$$

Only the last two K axes transpose. The first product contracts d; the second contracts the full key-position count $P + S$:

```
Qrot       [B,H,S,d]
Kall.T     [B,H,d,P+S]
scores     [B,H,S,P+S]
weights    [B,H,S,P+S]
Vall       [B,H,P+S,dv]
output     [B,H,S,dv]
```

Softmax runs over the last/key axis. Blocking with $-\infty$ gives zero weight because $\exp(-\infty) = 0$. Replacing a blocked score with 0 still gives $\exp(0) = 1$, so it does not block attention.

Keep absolute RoPE positions

If $P = 2$, $S = 2$, new positions are [2,3], not [0,1]. Their integer vector has shape (2,), shared across batch/head axes. Cached keys already carry positions [0,1].

For a **separate nonzero illustration**, take $d = 2$ and raw [1,0]. The single feature-pair frequency is 1 radian/position, giving $[\cos p, \sin p]$:

Position	Status	Rotated contents
0	Cached	[1,0]

Position	Status	Rotated contents
1	Cached	[0.540302,0.841471]
2	New	[−0.416147,0.909297]
3	New	[−0.989992,0.141120]

New tokens continue the old position numbering: RoPE does not restart at zero

Separate nonzero RoPE illustration: d=2, raw row [1,0], frequency 1 rad/position; distinct from the zero-vector fixture.

position	status	raw [a,b]	rotated [cos(p),sin(p)]
0	cached	[1,0]	[1.000000, 0.000000]
1	cached	[1,0]	[0.540302, 0.841471]
2	new	[1,0]	[-0.416147, 0.909297]
3	new	[1,0]	[-0.989992, 0.141120]

P=2, S=2 → positions=[2,3], shape=(2,)

$$[a, b] \mapsto [a\cos p - b\sin p,\ \ a\sin p + b\cos p]$$

Wrong reset [0,1]: new position 2 would use [1,0], instead of [-0.416147,0.909297].

Cached keys are already rotated: do not rotate them twice. New q and k use the same positions.

This design rotates q/k, not values. Row order and each tensor's declared shape are preserved.

Figure 153: Nonzero RoPE position-offset illustration

Resetting position 2 to 0 gives the wrong [1,0]. Rotating the cached position 1 key again by angle 1 incorrectly changes its existing angle 1 to angle 2. Rotate each key once at its own position; new q and k share positions. This nonzero illustration is distinct from the zero-vector arithmetic example below.

A rectangular causal mask

For $P = 2$, $S = 2$, query rows are at absolute positions 2,3 and key columns at 0,1,2,3. Query 2 sees keys 0,1,2 but blocks 3; query 3 sees all four. Define future_mask[i, j]=(j>P+i):

```
key columns: 0      1      2      3
query p=2: [False, False, False, True ]
query p=3: [False, False, False, False]   shape=(2,4)
```




Figure 154: Allowed entries, future-mask values and broadcasting shapes

positions[:, None] has shape (S,1); key_positions[None,:] has (1, $P + S$). Comparing key>query broadcasts to (S, $P + S$), then masked_fill broadcasts over B/H. None inserts a size-one axis without

adding positions. A plain upper-left triangle incorrectly treats the first new query as position 0 and blocks keys 1,2. For $S = 1$, the latest query should see **all** $P + 1$ **keys**. Do not assume an API's default rectangular is_causal convention matches that alignment.

Boolean meaning follows the receiving operation:07.02's loss mask uses True to **score a target**; this future_mask uses True to **block attention**.

Optional uniform sanity check: the worksheet fixture

Set $B = H = 1$, $P = S = d = 2$, $d_v = 1$. An earlier call processed positions 0,1. Old/new q/k are zero, so all their RoPE results are zero:

```
old cache['keys']   [[[[0,0],[0,0]]]]  shape=(1,1,2,2)
old cache['values'] [[[[2],[4]]]]      shape=(1,1,2,1)
new q               [[[[0,0],[0,0]]]]  shape=(1,1,2,2)
new k               [[[[0,0],[0,0]]]]  shape=(1,1,2,2)
new values          [[[[8],[10]]]]     shape=(1,1,2,1)
```

1. Read $P = 2$ from the old key time axis and $S = 2$ from q. Build positions [2,3].
2. Rotate new q/k; zero stays zero. Append to get K_{all}(1,1,4,2) and V_{all}(1,1,4,1), whose value contents are [2,4,8,10].
3. Every $q \cdot k$ score is 0; division by $\sqrt{2}$ leaves 0. Scores have shape (1,1,2,4).
4. The displayed b=0, h=0 masked rows are [0,0,0,−inf] and [0,0,0,0].
5. Their exponentials [1,1,1,0] and [1,1,1,1] normalize to [1/3,1/3,1/3,0] and [1/4,1/4,1/4,1/4].
6. Multiply these weights by values:

$$o_2 = \frac{2+4+8}{3} = \frac{14}{3}, \qquad o_3 = \frac{2+4+8+10}{4} = 6.$$

Complete calculation: zero scores → causal softmax → weighted visible values

Main zero-q/k fixture: B=H=1, P=S=d=2, dv=1. Displayed slices fix batch b=0 and head h=0.

weights: shape=(1,1,2,4)

1/3	1/3	1/3	0
1/4	1/4	1/4	1/4

`all_values: (1,1,4,1)`

2
4
8
10

shapes : $(2,4)\ @\ (4,1)\ \longrightarrow\ (2,1)$

$$o_2 = \frac{1}{3}(2) + \frac{1}{3}(4) + \frac{1}{3}(8) + 0(10) = \frac{14}{3}$$

$$o_3 = \frac{1}{4}(2 + 4 + 8 + 10) = 6$$

output: shape=(1,1,2,1), contents [[[[14/3],[6]]]]

Past outputs [2,3] plus new outputs [14/3,6] match full-prefix outputs [2,3,14/3,6].

Return cache length 4; preserve old cache length 2. Feature width is separate from position count.

Figure 155: Complete weighted-value arithmetic with labeled matrix-product shapes

Return output contents [[[[14/3],[6]]]], shape (1,1,2,1), and a new four-position cache. Preserve the old two-position cache. Earlier prefill outputs [2,3] plus these new outputs [14/3,6] equal full-prefix outputs [2,3,14/3,6]. Caching preserves predictions rather than improving them.

Zero vectors make hand calculation easy but cannot expose an incorrect RoPE offset. The original randomized driver and separate nonzero illustration address that distinction; positions have not become optional.

Twelve guided implementation steps

The following hints refer to the separate uniform worksheet fixture. Edit only the learner region in 07_03_kv_cache.py. Its adjacent comments repeat these steps. Preserve imports/signature/markers and the supplied driver.

1. **Four spaces: enter with torch.no_grad():.** Its body uses eight spaces. Inputs are tensors, so this helper has no model.eval() call.
2. **Eight spaces: read S and d from q's last two axes.** Branch with if cache is None:; statements inside if/else use twelve spaces. None is the missing-state sentinel: $P = 0$. Otherwise read cache['keys'].shape[-2]. Testing is None does not test whether tensor entries are zero.
3. **Eight spaces: build positions.** torch.arange(P, P+S, device=q.device) gives integer positions [S]. The end is exclusive; expect [2,3] in the append example.
4. **Rotate only new q/k.** Call apply_rope separately on q and k with the same positions. Both retain [B, H, S, d]; leave values and cached keys unrotated by this call.
5. **Eight/twelve spaces: build all K/V.** Branch again on cache is None. First call: retain new rotated k and clone values inside no_grad. clone makes an independent tensor; simply returning an existing input inside no_grad would not remove its existing requires_grad flag. Later calls: torch.cat accepts a tuple/list of old then new tensors; use dim=-2 for keys and values. Do not assign into the passed cache.
6. **Eight spaces: scores.** Multiply rotated q by `all_keys.transpose(-2,-1)`, then divide by `math.sqrt(d)`. Contract d, not S or d_v. The toy scores have shape (1,1,2,4), all zero.
7. **Eight spaces: future mask.** Make key indices $0 \ldots P + S - 1$ on q.device. Compare `key_positions[None,:]>positions[:, None]`. Shapes(1,4) and(2,1) yield(2,4); the first row blocks only key 3.
8. **Mask, then softmax.** Use masked_fill with $-\infty$, then softmax(dim=-1). Keep B/H axes and normalize over keys. Expected toy weights are [1/3,1/3,1/3,0] and [1/4,1/4,1/4,1/4].
9. **Multiply by all_values.** Contract $P + S$ to obtain [B, H, S, dv]. The toy output contains $14/3$ then 6. No flattening across batches/heads is needed.
10. **Return a fresh state.** Return output and a new dictionary with exactly 'keys' and 'values'. Return at eight spaces inside with, or four spaces afterward; either exit restores the preceding grad mode. Cache K/V, not old Q or output O.
11. **Check cases.** $P = 0$ gives normal causal prefill; $P = 2$ appends positions [2,3]; $S = 1$ permits every available key. Preserve old state and avoid autograd history. No loop is required in this helper.

12. **Replace the placeholder and run below.** No optimizer, data download or new environment belongs in this task.

```
python exercises/07_03_kv_cache.py
```

Expected after implementation:

```
Lesson 07.03 checks passed.
```

The actual driver uses seed 33, $B = 2$, $H = 3$, total length 4, $d = 6$, $d_v = 5$. It compares full versus prefill 2 + append 2, checks cache lengths/contents, old-key preservation and output grad status. Random driver values differ from the toy. It does not cover every partition, value ownership, requires_grad input or generation policy.

Boundaries and understanding

One layer's cache stores $BHP(d + d_v)$ scalars. Multiply by layers and bytes per scalar for physical memory. The optional four-position float32 worksheet fixture stores $4(2 + 1) = 12$ scalars=48 bytes; this is unrelated to BPB's source-byte denominator M. Attention still reads old K/V; decode is not constant-cost as context grows.

This exercise is append-only. Reset state for a different request; do not reuse it after changing prefix/model weights/layer identity. It does not extend context limits, handle padding positions or implement window eviction. A generation or scoring interface must also define what happens at its context limit. If a sliding window changes the visible prefix or resets positions, rebuild the cache under that new policy; retained vectors may have depended on the removed context. Silently dropping cache rows does not establish equivalent context/position behavior. Section 07.04 returns to this limit when connecting the cache to a generation loop.

Explain why past states remain unchanged under causal attention, why query 2 sees key 2 but not 3, why d stays fixed while P grows, and why resetting RoPE is wrong.

07.04 will add the per-layer model loop, prompt prefill, subsequent-token input, stopping and sampling.

07.04 Turn a KV cache into a generation loop

Method sources

Incremental K/V reuse follows the ordinary attention algorithm in Shazeer, 2019; R19, Section 2.4. Cached RoPE positions must follow the construction in Su et al., 2021; R07; the state-dictionary interface and equality probes are specific to this book.

Connect one attention call to a complete answer

07.03 implemented **one layer's cached attention**: new Q/K/V arrive, old K/V are reused, and a new cache is returned. It did not select a token, loop until EOS or turn token IDs into text.

07.04 supplies a whole-model wrapper, `CachedModernLM`, and asks you to write only `generate_cached`. The wrapper calls your 07.03 function once per layer. Your function repeatedly calls that wrapper and selects one next token from its logits. The 07.03 no_grad block covers attention only; the embedding, FFN and head also need this lesson's outer no_grad context.

The essential order is:

```
process the current input + old cache
        ↓
receive logits + an updated cache
        ↓
select one next token and append it to the returned ID list
        ↓
if continuing, send that selected token into the NEXT model call
```

A newly selected token is not in the returned cache yet. The cache describes positions the model has actually processed. Choosing an ID does not compute that ID's embedding, hidden states or K/V vectors.

Formulas before implementation

Let s count generation iterations from zero. Let the prompt contain T_0 IDs. U_s is the sequence actually sent into the model on this iteration, and C_s is the cache before that call:

$$U_s = \begin{cases} [p_0, \dots, p_{T_0-1}], & s = 0, \\ [g_{s-1}], & s > 0, \end{cases} \qquad (Z_s, C_{s+1}) = \text{model}(U_s, C_s), \quad C_0 = \text{None}.$$

The first call is **prefill**. Subsequent calls are **incremental decoding**. Here g_{s-1} is the ID selected on the preceding iteration. Keep the entire generated ID list separately; do not resend it with an existing cache.

Take the last new-position logit vector:

$$z_s = Z_s[0, -1, :] \in \mathbb{R}^V.$$

Let τ be the `temperature` argument. If it is positive, define the probability of next ID j by:

$$\pi_{s,j} = \frac{\exp(z_{s,j}/\tau)}{\sum_{k=0}^{V-1} \exp(z_{s,k}/\tau)}, \qquad g_s \sim \text{Categorical}(\pi_s).$$

For `temperature=0`, use greedy selection instead:

$$g_s = \underset{j}{\text{argmax}}\, z_{s,j}.$$

There is no division by zero. Append g_s, then stop if it is the configured EOS. The budget counts newly selected IDs, including a selected EOS.

Read the supplied wrapper before writing the loop

The exercise already defines `CachedModernLM.forward(ids, cache=None)`. You do not implement this class. Its two returns are **logits and the next per-layer cache list**.

For the original driver, $V = 5$, model width $D = 8$, heads $H = 2$, per-head width $d = 4$, FFN width `16` and layers $L = 2$. Generation uses batch size $B = 1$.

Object	Prefill with two IDs	Later one-ID call
Input `ids`	`[1,2]`, contents `[[0,1]]`	`[1,1]`, e.g. `[[2]]`
Embedding / hidden states	`[1,2,8]`	`[1,1,8]`
Each layer's new Q/K/V	`[1,2,2,4]`	`[1,2,1,4]`
Returned logits	`[1,2,5]`	`[1,1,5]`
`logits[0,-1,:]`	`[5]`	`[5]`

These bracketed entries in the shape columns are **dimensions**. The separately labeled `[[0,1]]` and `[[2]]` are **tensor contents**.




Figure 156: New hidden states cross layers; each layer owns its K/V state

Inside each block, `n @ block.q/k/v` independently projects the normalized hidden state. Reshaping `[B,S,D]` to `[B,S,H,d]` and transposing gives `[B,H,S,d]`. Your 07.03 helper attends to that layer's old/new K/V. Merging heads returns `[B,S,D]`; the residual and FFN preserve the same new-position axis before the next layer.

The cache is a Python list:

```
cache[0] = {'keys': layer0_K, 'values': layer0_V}
cache[1] = {'keys': layer1_K, 'values': layer1_V}
```

After the two-position prefill, **each** layer's K and V has shape `[1,2,2,4]`. After processing one additional position, each has `[1,2,3,4]`. Layers have different vector contents even when their shapes match. Do not concatenate different layers along time. The final `nn.Linear(8,5)` stores `head.weight` with shape `[5,8]`; it applies the equivalent of `hidden @ head.weight.T`, mapping eight features to five vocabulary logits. The diagram labels the mapping as 8→5, rather than mislabeling the stored weight shape.

Why the last logit row? For prompt `[0,1]`, the row at input ID 0 predicts the next ID already supplied as ID 1. The row at input ID 1 predicts the first unknown next ID. Averaging the rows would combine different prediction problems.

A complete hand-worked generation trace

Use this explicitly defined **teaching vocabulary**, not the project's real byte-BPE tokenizer:

ID	Display label
0	I
1	like
2	tea
3	.
4	EOS

Set `prompt=[0,1]`, `budget=3`, `eos_id=4`, `temperature=0`. The logits below belong to a scripted teaching model. They are not claimed to be the actual random driver's logits.

Process the input, then choose the next token: the cache trails the returned list

Teaching vocabulary V=5: 0=I, 1=like, 2=tea, 3=., 4=EOS. Scripted logits, distinct from the random driver.

Call	ids sent into model	Past → returned cache length	logits[0,-1,:] · shape (5,)	Selected ID
0	0 1 shape (1,2)	**None → 2** K,V: [1,2,2,4] Separate state for each of 2 layers	0 ln2 ln4 ln2 0 argmax → 2	2 Not cached yet
	Returned list so far [0, 1, 2] ← includes the newly selected ID			
1	2 shape (1,1)	**2 → 3** K,V: [1,2,3,4] Separate state for each of 2 layers	ln2 0 0 ln4 0 argmax → 3	3 Not cached yet
	Returned list so far [0, 1, 2, 3] ← includes the newly selected ID			
2	3 shape (1,1)	**3 → 4** K,V: [1,2,4,4] Separate state for each of 2 layers	0 0 0 0 ln8 argmax → 4	4 EOS: stop; no forward
	Returned list so far [0, 1, 2, 3, 4] ← includes the newly selected ID			

Return [0,1,2,3,4]; the cache has processed only [0,1,2,3]. EOS ends the loop without another forward.

Caches contain per-position K/V vectors, not these ID numbers. Equal layer shapes do not imply equal contents.

Figure 157: Three calls: input tensor, per-layer cache length, logit values, selected ID and returned list

Iteration 0 — process the prompt. Start with `sequence=[0,1]`, `cache=None`. Send `[[0,1]]`, shape `[1,2]`. Each layer stores two processed positions. The wrapper returns logits `[1,2,5]`; choose the last row:

$$z_0 = [0, \ln 2, \ln 4, \ln 2, 0].$$

Its largest entry is at ID 2, so greedy selection chooses `2`. Append it: `sequence=[0,1,2]`. **The cache still covers only `[0,1]`**, because ID 2 has not been processed.

Iteration 1 — process the selected ID 2. Send only `[[2]]`, shape `[1,1]`, with the existing cache. Do not send `[[0,1,2]]`: the old positions already exist in the cache. This call extends each layer from two to three cached positions. Let its last logits be:

$$z_1 = [\ln 2, 0, 0, \ln 4, 0].$$

Greedy selection chooses ID 3. Append it: `sequence=[0,1,2,3]`. The cache now covers `[0,1,2]`; selected ID 3 waits for the next call.

Iteration 2 — process ID 3, then select EOS. Send only `[[3]]`. The cache grows from three to four positions. Let:

$$z_2 = [0, 0, 0, 0, \ln 8].$$

Choose ID 4. Append it **before** checking the stopping condition: `sequence=[0,1,2,3,4]`. It equals `eos_id`, so stop. There is no extra model call for EOS.

The three model input lengths were **2,1,1**. The final ID list has length five; the cache covers four processed positions. Those different lengths are expected.

Without caching, full-prefix calls would process lengths 2,3,4. The row totals 4 versus 9 describe newly processed positions per layer, not a promised wall-clock speed ratio. Each new query still reads the past K/V.

Temperature and the caller's random generator

For the first scripted logit row, temperature one gives:

$$\exp(z_0) = [1, 2, 4, 2, 1], \qquad \pi = [0.1, 0.2, 0.4, 0.2, 0.1].$$

At temperature `0.5`, the exponentials are `[1,4,16,4,1]`, with total 26. ID 2 gets probability $16/26$, about `0.615`. At temperature `2`, the distribution is flatter. A probability of `0.4` is not a guarantee that ID 2 will be sampled.




Figure 158: The same five logits at three temperatures

The supplied `generator` controls sampling randomness. Use it in `torch.multinomial`; do not recreate or reseed it inside the loop. In the checked CPU fixture, first-row sampling at temperature `0.7` with a fresh seed-4 generator selects ID 2. This is one seeded draw, not the definition of sampling.

Two **fresh generators with the same seed**, the same model, prompt and sampling protocol reproduce the fixture. Reusing an already advanced generator continues its random stream. Greedy selection does not need a random draw and should not consume it. For GPU sampling, generator and probability-tensor devices must match; this assignment's supplied fixture uses CPU.

Exact function contract

```
def generate_cached(
    model: nn.Module,
    prompt: list[int],
    budget: int,
    eos_id: int | None,
    temperature: float,
    generator: torch.Generator,
) -> list[int]:
```

- `model`: the supplied parameter-owning `CachedModernLM`; its forward takes new IDs and old cache, returning logits and a new list of layer states.
- `prompt`: a nonempty Python list of valid integer IDs. Preserve this caller-owned list.
- `budget`: a nonnegative count of newly selected IDs. It is not prompt length, vocabulary size or a token ID.
- `eos_id`: the selected stopping ID, or `None` to disable EOS stopping. ID 0 is a valid stopping value.
- `temperature`: nonnegative; zero chooses argmax, positive values sample from scaled logits.
- `generator`: the caller-owned CPU `torch.Generator` for this CPU fixture.
- Return: a **fresh Python list** containing the full original prompt and generated IDs. It includes a newly selected EOS. Its length lies between `len(prompt)` and `len(prompt)+budget`.

Keep model parameters and the prompt unchanged. Temporarily use eval mode and no_grad; restore the entry training flag even if a forward raises. This root-flag convention assumes an ordinarily uniform model mode; preserving arbitrary mixed child-module modes requires a more general per-module snapshot.

This function returns IDs rather than decoded text, including a newly selected EOS for inspection. A later text-decoding step must interpret that EOS as structure before decoding ordinary token bytes, following 06.04.

Fourteen guided implementation steps

Edit only the learner region in 07_04_inference_interface.py. The supplied wrapper and check driver stay intact. The file repeats these hints beside the TODO.

1. **Four spaces: copy and save.** Use `list(prompt)` for a local `sequence`, and save `model.`

`training` as `old_mode`. Copying prevents `.append()` from changing the caller's prompt.

2. **Four spaces: initialize state and find the device.** Set `cache=None`. `next(model.parameters())` retrieves the first registered parameter; `.device` identifies where to create IDs. Do not build a new model or optimizer.
3. **Four spaces: open `try:`.** At eight spaces call `model.eval()`. It controls evaluation behavior, while the separate no_grad context controls autograd recording.
4. **Eight spaces: enter `with torch.no_grad():`.** Its body uses twelve spaces. Open `for _ in range(budget):` there; the repeated body uses sixteen spaces. `_` is an unused loop index. `range(0)` performs no iterations.
5. **Sixteen spaces: choose the input IDs.** If `cache is None`, use the complete `sequence`. Otherwise use a one-item list containing `sequence[-1]`. Branch bodies use twenty spaces. The example gives `[0,1]`, then `[2]`, then `[3]`.
6. **Sixteen spaces: add the batch dimension.** Construct `torch.tensor([current_ids], dtype=torch.long, device=device)`. The outer brackets produce `[1,S]`; a scalar or flat `[S]` tensor is the wrong shape for this wrapper.
7. **Call and unpack both returns.** Use the new tensor and old cache in `model(...)`; retain both `logits` and the returned `cache`. Ignoring the returned state loses the optimization. Do not manually append layers or concatenate IDs into cached vector tensors.
8. **Select one vocabulary row.** `logits[0,-1,:]` has shape `[V]`. The first index selects the only batch row; `-1` selects the last new position; `:` retains all vocabulary candidates.
9. **Branch on temperature.** At temperature zero use the vocabulary row's `.argmax()`. In the positive branch, divide by `temperature` first, then softmax over `dim=-1`. Never divide by zero.
10. **Produce one Python integer.** Argmax gives a scalar tensor. `torch.multinomial(probabilities, num_samples=1, generator=generator)` gives a one-item tensor. `.item()` extracts the number; retain an ordinary integer ID. Do not reset the generator.
11. **Append, then test EOS.** `sequence.append(token)` stays inside the loop. Check `eos_id is not None` and equality with the selected integer. Testing just `if eos_id:` would mishandle EOS ID 0.
12. **Use `break` inside that EOS branch.** It exits the nearest loop immediately. The newly appended EOS remains in the result. Without EOS, the budget controls loop length. Do not return after the first ordinary token.
13. **Four spaces: write `finally:`.** Its eight-space body restores `model.train(old_mode)`. Cleanup runs on success or error. Do not return from finally: that could hide an exception.
14. **Four spaces after cleanup: return the sequence.** The return is outside the loop, so budget zero still returns a fresh prompt copy without calling the model or sampling. Replace the placeholder and run below.

Run the actual assignment

```
python exercises/07_04_inference_interface.py
```

Expected after your implementation:

```
Lesson 07.04 checks passed.
```

The original driver uses seed 34 and the real small random two-layer wrapper. It compares cached versus uncached logits and greedy IDs, checks prompt preservation, budget zero, early EOS, training-mode restoration and repeated-seed sampling. Its generated IDs need not match the scripted teaching trace. Additional checks can cover input lengths, cache handoff, fresh zero-budget results, EOS ID 0, no_grad, failure cleanup and RNG behavior.

Scope, the slow chat page and understanding

This loop handles one unpadded sequence. It does not add top-k, beam search, a web server, batched variable-length stopping, cross-user state or a cache-eviction policy. It starts a fresh cache for every generation request. Do not reuse state after changing model weights or the prefix.

The teaching wrapper does not enforce a trained context limit. A caller must still honor the model configuration. For example, a model limited to 512 positions cannot process a 500-ID prompt followed by 32 more input positions under the same bounded policy. One conversation policy reserves answer room by removing complete oldest turns before prefill, while preserving the latest question. A sliding-window policy instead changes the visible prefix during generation and may require recomputing that window, so cache reuse can become expensive. Choose and report the boundary and position policy explicitly; `generate_cached` does not implement either policy.

Before moving on, explain why ID 2 is in the returned sequence before it is in the cache; why the second model input is `[[2]]`; why every layer needs its own state; and why a returned EOS adds no further model call.

Looking back

Efficient generation makes a model usable, but pretraining alone does not define a useful conversational response. The next chapter treats conversation structure and response objectives as new data and learning contracts.

08 Teach responses and preferences

A conversation is more than several text strings placed next to each other. Roles, turn boundaries and end markers determine who said what and where the next answer begins. The target mask determines which part of that serialization directly contributes to the training objective.

We first build complete conversation examples, then distinguish learning a demonstrated answer from preferring one answer over another. A final section introduces a clipped policy objective and explains the additional machinery a reinforcement-learning system would need. These methods optimize supplied signals; their names do not certify factual correctness, good judgment or reliable conversation.

08.01 Give a conversation an exact token format

Method sources

Instruction-following training context is provided by Ouyang et al., 2022; R32. The role delimiters, serialization and assistant-target masks below are this book's format contract, not an official chat standard defined by that paper.

From generating IDs to answering a user

07.04 taught a model to continue a prompt using a KV cache. Its interface accepts a flat list of integer IDs. A chat interface, however, starts with an ordered list of messages: who spoke, and what they said. We now connect those two representations.

The model does not receive Python dictionaries or a chat-window layout. A **chat template** converts messages into one token sequence. Our two-role teaching format inserts a reserved role ID, encodes the ordinary content with your frozen 02.05 BPE encoder, and appends a terminator. It also records which tokens should be supervised when we later fine-tune the assistant.

This is data preparation, with no forward call, optimizer or parameter update. 08.02 will consume these outputs to calculate assistant-only supervised fine-tuning (SFT) loss. Formatting alone cannot make a pretrained completion model follow instructions.

This is a deliberately small local schema. Real models use different control tokens and templates; the official Hugging Face chat-template guide explains that messages are converted into token sequences and that generation prefixes must match the model's training format. Our exact IDs and mask policy below are this course's design, not a universal chat standard.

First understand the inputs

```
def format_chat(
    messages: list[dict],
    merges: dict,
    role_ids: dict[str, int],
    eos_id: int,
) -> tuple[list[int], list[bool]]:
```

Name	Type and meaning	Main example
`messages`	Ordered list of message dictionaries. Each has `role` and `content`.	See below
Each `message`	A dictionary, not a string or a token list	`{'role':'user','content':'a'}`
`role`	String, either `'user'` or `'assistant'`	`'assistant'`
`content`	Ordinary Python string to pass into `encode_bpe`	`'b'`
`merges`	Frozen pair-to-replacement-ID BPE rules from 02.05	`{}`: no merges
`role_ids`	Reserved structural IDs, supplied by the caller	`{'user':256,'assistant':257}`
`eos_id`	Reserved message terminator in this fixture	`258`
Returned `ids`	One fresh flat Python list of integer IDs	Length 6
Returned `learn_mask`	One fresh flat Python list of Boolean target flags, aligned with `ids`	Length 6

Use exactly these message fields. In `for message in messages:`, each `message` is a dictionary, so read `message['role']` and `message['content']`. Earlier packed documents were lists of IDs; the representation here is different and stated explicitly.

Caller preconditions: content is a string; roles are supported; structural IDs are distinct and do not collide with ordinary byte/BPE IDs. No mutation of messages, merges or role IDs is needed. This exercise is not a schema validator and does not add system, tools, padding, multimodal content or forced role alternation.

Serialization formula: one message at a time

Let message index be r. Its role is role_r, its text is content_r, and its encoded content has length n_r:

$$b_r = \text{encode_bpe}(\text{content}_r, \text{merges}), \qquad n_r = |b_r|.$$

Construct one complete message segment:

$$s^{(r)} = [\text{role_ids}[\text{role}_r]] \parallel b_r \parallel [\text{eos_id}].$$

The symbol $\parallel$ means list concatenation: put the elements of the right list after the left list. It does not add the numeric IDs. Preserve message order:

$$s = s^{(0)} \| s^{(1)} \| \cdots, \qquad T = \sum_r (n_r + 2).$$

Each message contributes one role ID, n_r content IDs, and one EOS ID. T is the resulting number of positions. It is not the vocabulary size and is not the largest token ID.

Role labels such as `USER` in a diagram are display names for IDs, not text sent to BPE. Only `content` enters `encode_bpe`; the formatter directly inserts structural IDs.




Figure 159: Message dictionaries become token IDs and aligned target flags

Read the position row separately from the numeric ID row. Every colored ID cell is one token occurrence. The Boolean row describes supervision, not causal attention visibility. Both returns are Python lists; after batching the main example, ID and mask tensors would have shape `[1,6]`.

What the learning mask means

Define a_r to be true exactly when $\text{role}_r = \text{assistant}$. For one message, the aligned target flags are:

$$m^{(r)} = [\text{False}] \parallel [a_r] \text{ repeated } (n_r + 1) \text{ times.}$$

The leading False belongs to the role marker. The remaining flags cover the content and terminator together. Concatenate these mask segments in the same order as the ID segments.

Our policy is:

- All role-marker IDs: False. The caller supplies the role at inference time.
- User content and user EOS: False. They provide context rather than demonstrated assistant outputs.
- Assistant content and assistant EOS: True. We train both what to say and when to end that answer.

A False flag does **not** remove the token, zero its embedding, or prevent later positions from attending to it. User context can influence assistant loss and parameter gradients through attention. Nor does False mean a particular parameter row can never change: the full model and vocabulary normalization share parameters. This policy selects direct target losses; it is distinct from a causal attention mask or a padding-validity mask.

Here `eos_id` terminates every message. We retain the exercise's name, while acknowledging that production formats may distinguish end-of-message, end-of-turn and end-of-sequence tokens. A terminator inside a prompt does not automatically stop 07.04; that loop checks newly selected IDs.

Complete worked example: user a, assistant b

Use:

```
messages = [
    {'role': 'user', 'content': 'a'},
    {'role': 'assistant', 'content': 'b'},
]
merges = {}
role_ids = {'user': 256, 'assistant': 257}
eos_id = 258
```

First message. Its role is user. Ordinary encoding gives `encode_bpe('a', {}) == [97]`. Construct `[256,97,258]`; its mask is `[False,False,False]`.

Second message. Its role is assistant. Encoding gives `[98]`. Construct `[257,98,258]`; its mask is `[False,True,True]`.

Concatenate without nesting:

```
position       0    1    2    3    4    5
ids          256   97  258  257   98  258
learn_mask     F    F    F    F    T    T
meaning     USER    a  EOS ASSISTANT b  EOS
```

Return these two lists as a tuple. There are six positions, but the highest ID is 258, so the model's vocabulary capacity must be **at least 259**. The mask has two True entries. No tensor computation or model training has occurred.

Connect the mask to next-token prediction

`format_chat` prepares the complete conversation as two lists: `ids` and `learn_mask`. Each token has a corresponding flag, and both lists keep the original token order. The caller batches these lists and passes the complete `ids` tensor to the model. The model returns one row of prediction scores (logits) per position. The loss function `assistant_loss`, introduced in Section 08.02, uses these scores and the complete `ids` and `learn_mask` tensors as follows.

The flag at position i describes whether **that token** is a target we want to learn. A causal model's logit row at position t predicts position $t + 1$. Therefore later loss computation aligns:

$$Z_{\text{used}} = Z[:, :-1, :], \quad Y = s[1:], \quad M = m[1:].$$

Here s is the full ID sequence and m contains its learning flags. In the six-ID example, the model returns Z with shape `[1,6,259]`. Its first five rows predict the tokens at positions 1–5. The final row has no next token within this example, so it is left out of the loss. Taking the first five logit rows and the last five IDs and flags gives these pairs:

```
logit position t       0      1      2      3      4
input ID             256     97    258    257     98
target ID             97    258    257     98    258
shifted mask           F      F      F      T      T
```

At logit position 3, the prefix ends with the assistant role marker. This row predicts `b` at position 4, so it uses `b`'s True flag. The marker's own False flag describes a different target: the marker itself. The figure follows this same prediction-to-target pairing.

Shift the target mask: logits at position 3 predict b at position 4
Same six-ID example. Full logits shape [1,6,259]; shifting leaves 5 prediction slots, with 2 selected.

logit position t	0	1	2	3	4
input ID s[t]	256	97	258	257	98
	↓	↓	↓	↓	↓
target s[t+1]	97	258	257	98	258
mask m[t+1]	False	False	False	True	True

Slot 3: given ... ASSISTANT, predict b. Slot 4: given ... b, predict EOS.

Illustrative probabilities: p(b)=1/2 and p(EOS)=1/4. Average only these two targets:

$$L = (-\ln(1/2) - \ln(1/4))/2 = 3\ln 2/2 \approx 1.039721$$

Pair each prediction with the next token and that token's learning flag.

Figure 160: Each prediction is paired with the next token and that token's learning flag

If the model assigns probabilities $p(\texttt{b}) = 1/2$ and $p(\text{EOS}) = 1/4$ at the two selected rows, the assistant-only mean loss is:

$$L = -\frac{1}{N}\sum_{t=0}^{T-2} m_{t+1} \log p_\theta(s_{t+1} \mid s_0, \ldots, s_t), \quad N = \sum_{i=1}^{T-1} m_i = 2,$$

$$L = \frac{-\ln(1/2) - \ln(1/4)}{2} = \frac{3\ln 2}{2} \approx 1.039721.$$

The denominator is two selected targets, not six tokens or five prediction slots. This equation describes mathematical selection; implementation should select valid losses rather than multiply excluded infinities by zero, as discussed in 07.02. Uniform logits across 259 candidates would instead give $\ln(259) \approx 5.556828$ for every selected target. These are illustrative probability fixtures, not results from a trained model.

BPE, Unicode and structural IDs

The main example deliberately uses no merges so its arithmetic is easy. Your implementation must still call the actual `encode_bpe` helper, rather than hard-code ASCII or byte conversion.

Consider a **separate** rule set with `(97,98) → 256`. ID 256 is now an ordinary BPE token meaning `ab`, so the main example's structural IDs would collide. Reserve user257, assistant258 and EOS259 for this separate fixture:

```
user content 'ab'      → [256]
assistant content 'aba'→ [256,97]
ids        = [257,256,259,258,256,97,259]
learn_mask = [F,  F,  F,  F,  T, T,  T]
```




Figure 161: BPE content and inserted structure use disjoint IDs

Do not infer token type from `id >= 256`: both ordinary merges and special IDs can satisfy that condition. Reserve IDs against the actual frozen vocabulary. A model with new IDs also needs sufficient embedding/output capacity and training; inserting an integer cannot create a meaningful trained embedding automatically.

For a Unicode example with the main no-merge vocabulary, replace assistant content `b` with `好`. Its UTF-8 bytes are `[229,165,189]`, so:

```
ids        = [256,97,258,257,229,165,189,258]
learn_mask = [F,  F,  F,  F,  T,  T,  T,  T]
```

The three content IDs all receive True. The mask counts tokens, not displayed characters or Unicode code points. A different frozen BPE may combine some bytes, changing the content length and the required number of flags.

Literal content such as `<|assistant|>` stays ordinary text. With no merges its IDs are `[60,124,97,115,115,105,115,116,97,110,116,124,62]`. Do not replace that substring with a reserved role ID. Explicit structural construction prevents accidental role-ID insertion by this encoder; it is not proof that the model resists malicious instructions written in ordinary content.

Connect completed training examples to the 07.04 inference prefix

For training, the complete example contains both the prompt and known answer:

```
[256,97,258,257,98,258]
```

For generation, the answer is not yet known. Format the completed user message, then append only the assistant role ID:

```
format_chat([user message], ...)[0] → [256,97,258]
append assistant role ID           → [256,97,258,257]
```

This prefix is what 07.04 accepts as `prompt`. Do not construct an empty completed assistant message as a shortcut: our formatter would produce `[257,258]`, ending that message before generation begins.




Figure 162: The full training sequence and unfinished assistant inference prefix

In an illustrative rollout, a prefill call with tensor shape `[1,4]` might select ID 98; feed only `[[98]]` next, then stop if ID 258 is selected. The selected token enters K/V only on its next forward call, exactly as in 07.04. This is a protocol example, not a claim that formatting makes the random model generate `b`.

Training and inference should agree on role IDs, content encoding, terminators and boundary conventions. This exercise returns complete messages and has no generation-prefix option; the prefix illustration is a separate caller operation, not a request to change its signature.

Nine guided implementation steps

Edit only the marked learner region in 08_01_chat_format.py. The numbered hints are also beside the TODO. Keep the existing imports, signature and original check driver.

1. **At four spaces**, initialize separate empty lists named `ids` and `learn_mask`. They must be newly created on every call.
2. **At four spaces**, write `for message in messages:`. Everything for that one message belongs at eight spaces. An empty input executes no iterations.
3. **At eight spaces**, read `role = message['role']` and `content = message['content']`. Bracket lookup reads dictionary values; you are not iterating over characters or dictionary keys.
4. Append `role_ids[role]` to `ids`, and append `False` to `learn_mask`. `.append(value)` adds one element. Do this for both supported roles.
5. Call the supplied `encode_bpe(content, merges)` and keep its returned list as `content_ids`. Do not train or change the merges. For `a` it is `[97]`; for empty content it is `[]`.
6. Use `ids.extend(content_ids)`, then append `eos_id`. `.extend(list)` adds its individual elements; `.append(content_ids)` would incorrectly nest a list.
7. Set `is_assistant = (role == 'assistant')`. Equality returns an actual Boolean, True or False. Do not use the role string itself as a flag.
8. Extend `learn_mask` with `[is_assistant] * (len(content_ids)+1)`. The `+1` covers EOS. Python list repetition repeats entries; here Boolean entries are immutable. With empty assistant content this adds one True for EOS. Check equal ID/mask lengths after each message in your reasoning.
9. **Return at four spaces, after the loop**, in order `ids, learn_mask`. The comma constructs the two-item tuple. Returning inside the loop would silently discard later messages; returning after the loop also handles `messages=[]` as `([],[])`. Replace the placeholder raise, not the supplied driver.

No `torch.tensor`, softmax, backward, causal mask or KV cache is required in this formatter. Those belong to the stages connected above.

Boundary cases and checks

Case	Expected result or rule
No messages	`([],[])`, newly owned lists
Assistant content empty	IDs `[257,258]`, flags `[False,True]` under the main vocabulary
User content empty	IDs `[256,258]`, flags `[False,False]`
Several turns	Concatenate all segments in original order; never return from the first iteration
Unicode / actual BPE rules	Derive mask length from `len(content_ids)`, not character length
Repeated calls	No leftover IDs, mutation or random-state changes
User-only output	Valid formatter result with no selected targets; not a valid positive-target batch for 08.02's mean loss

Run in your existing environment:

```
python exercises/08_01_chat_format.py
```

Expected after your implementation:

```
Lesson 08.01 checks passed.
```

The unchanged original driver checks the six-ID example, empty message list and empty assistant content.

Before the next lesson, explain which flags change if the first message's role changes; why `learn_mask[3]` can be False while logit row 3 still receives supervised loss; why EOS needs a flag even for empty content; and why a special ID must not collide with an ordinary BPE merge.

Read the shifted target mask again

Revisit the complete six-ID conversation to check this pairing:

```
ids          [256,97,258,257,98,258]
learn_mask   [F,  F, F,  F, T, T]
shifted mask [F,  F, F,  T, T]
```

The selected next-token targets are 98 and 258 at positions 4 and 5, predicted by logit rows 3 and 4. The assistant marker's False flag excludes the marker as a target; it does not exclude the marker's next-token prediction of 98. Empty assistant content still contributes one True for EOS. Chinese 好 encodes to three ordinary byte IDs in this fixture, so its content plus EOS need four True flags.

08.02 Assistant-only supervised fine-tuning

Method sources

Supervised instruction fine-tuning is one stage of the pipeline in Ouyang et al., 2022; R32. This exercise isolates assistant-target cross-entropy; it does not reproduce the full human-feedback pipeline or establish conversational adequacy.

Purpose and prerequisites

The serialized conversation in Section 08.01 contains both the question and the demonstrated answer. If we simply trained on every position, we would also teach the model to reproduce user questions. Supervised fine-tuning changes which predictions are rewarded: the conversation remains the context, while the assistant answers and their end markers selected by 08.01's mask supply the targets. In a conversation with several assistant turns, this policy supervises all of those turns.

This is a continuation of next-token learning, with a different data distribution and target mask. The pretrained weights are the starting point, rather than random parameters. The learning rate, validation prompts and stopping rule belong to this new stage. An improvement on demonstrations does not by itself establish improved factual knowledge or held-out conversation quality.

Formulas and principles

$$L_{\text{SFT}} = -\frac{\sum_{b=0}^{B-1}\sum_{t=1}^{T-1} m_{b,t}\log p_\theta(\text{ids}_{b,t} \mid \text{ids}_{b,<t})}{\sum_{b=0}^{B-1}\sum_{t=1}^{T-1} m_{b,t}}$$

Here ids has shape $[B, T]$, and the model returns logits $[B, T, V]$. The formula indexes **target positions** $t = 1, \ldots, T-1$: logits at position $t-1$ predict the ID at position t. The Boolean value $m_{b,t}$ says whether that target belongs to the response we want to learn. It does not say whether the input at that position may be read as context.

Define $K = \sum_{b,t} m_{b,t}$ over the target positions $t = 1, \ldots, T-1$ shown above, excluding position 0. The exercise assumes $K > 0$. The numerator is the sum of the selected negative log probabilities; dividing by K gives a mean per selected target. Padding must already be excluded from m. An EOS marker may have zero source-text bytes and still be a meaningful training target: learning when to stop is part of the demonstrated response.

For one selected class score z_c, the logit derivative is $(p_c - \mathbf{1}[c = y])/K$. For an unselected position it is zero. That last statement concerns a **direct output-loss term**. A user embedding can still affect a later assistant vector through causal attention, so the user embedding and shared model parameters may receive gradients. Detaching all prompt representations would change the learning problem.

Do not apply softmax before `F.cross_entropy`. That operation accepts logits and combines log-softmax with the target selection in a numerically stable calculation. The `assistant_loss` interface performs next-token alignment inside the loss: its caller supplies complete `ids` and `learn_mask` tensors

and the logits computed from those same positions. The caller therefore leaves these inputs unsliced, unlike Chapter 03's interface that constructs aligned input/target pairs before the model call.

Select targets without removing context

logit t	input ID	target ID	learn?
0	256	97	No
1	97	258	No
2	258	257	No
3	257	98	Yes
4	98	258	Yes

V=259; selected: b and EOS. Uniform mean loss = ln(259).

Figure 163: Assistant-only supervised fine-tuning: 08.02

Read each table row as one logit position, its input ID and its next-position target. The six-ID conversation produces five prediction rows. The two green rows select the assistant character and EOS for the mean; the other rows remain context even though their direct target losses are excluded.

Function contract

```
def assistant_loss(logits: torch.Tensor, ids: torch.Tensor, learn_mask: torch.Tensor) ->
↪  torch.Tensor:
```

logits: float [B, T, V] from full conversation; ids: long[B, T]; learn_mask: bool[B, T], at least one true entry after position 0. Return connected scalar mean over shifted assistant targets. Padding mask must already be combined into learn_mask.

A worked example

Use the six teaching IDs from 08.01: `[256,97,258,257,98,258]`. They denote a user marker, the byte `a`, EOS, an assistant marker, the byte `b`, and EOS. The vocabulary must therefore have **at least 259 entries**. This is a synthetic teaching vocabulary, not the project's frozen tokenizer.

Choose $V = 259$ for the uniform example. The full target mask is `[0,0,0,0,1,1]`. After the single next-token shift, the aligned rows are:

Logit position	Target ID	Target meaning	Selected
0	97	User text a	No
1	258	End of user turn	No
2	257	Assistant marker	No
3	98	Assistant text b	Yes
4	258	EOS	Yes

The logits at original position 5 have no next target within this example and are sliced away. Uniform scores give each class probability $1/259$, so the two selected losses sum to $2 \ln 259$ and their mean is $\ln 259 \approx 5.556828$. Logit rows0,1,2 and 5 have no direct gradient from this objective; rows3 and 4 do.

For a second probability assignment on the same positions, let $p(b) = 1/2$ and $p(EOS) = 1/4$. The selected mean becomes $(-\ln(1/2) - \ln(1/4))/2 \approx 1.039721$. This is the same target alignment with different predictions, not a changed tokenizer or an extra model output.

Guided implementation

Work in `assistant_loss` in the companion exercise. The caller owns the model and has already prepared the full conversation and its Boolean target mask.

1. Read `logits.shape` as `[B,T,V]`, and verify that `ids` and `learn_mask` describe the same first two axes. Keep the vocabulary axis intact.
2. Form the five-position views of the six-position example: logits exclude the last position, while IDs and mask exclude the first. Their time lengths are all `T-1`.
3. Flatten only the batch and time axes for cross-entropy. The score matrix has `[B*(T-1),V]`; the target vector has `[B*(T-1)]`.
4. Request one loss per target with `reduction="none"`, then restore `[B,T-1]`. Flattening must not change which mask entry belongs to which target.
5. Use the shifted Boolean mask to select losses, and average only those entries. The assumed positive selected count makes this mean defined.
6. Return the scalar tensor with its graph connected. Calling `.item()` here would return a Python number and prevent the caller from backpropagating.

Common pitfalls

Replacing a position's logits with zeros gives a uniform distribution and loss $\ln V$, so that position still contributes unless its loss is excluded. Select losses with the shifted target mask.

Run and check

```
python exercises/08_02_assistant_sft.py
```

An unfinished prerequisite reports learner TODO, not an installation failure. Once implementation and prerequisites pass, expect:

```
Lesson 08.02 checks passed.
```

The SUPPLIED CHECK DRIVER includes the fixture and relevant boundary/gradient/state assertions. Passing verifies those contracts, not real-data quality, hardware performance or independent mastery.

Further practice

Can user token embeddings still receive gradients with assistant-only target loss?

Fine-tune a saved base checkpoint on a small, licensed instruction dataset using this loss. Freeze a held-out prompt set and compare base versus SFT using the same seeds and decoding policy. Track answer correctness, format following, EOS behavior and regression on held-out base text.

08.03 Direct preference optimization

Method sources

Direct Preference Optimization (DPO) is introduced by Rafailov et al., 2023; R12. Our paired-response log-probability calculation isolates its objective; reference-policy, reduction and masking choices must remain explicit.

Purpose and prerequisites

Supervised fine-tuning tells the model which answer to imitate. A preference pair gives a different kind of observation: for the same prompt, a judge prefers one response to another. Direct preference optimization, or DPO, turns that comparison into a differentiable objective without training a separate reward model inside this exercise.

The comparison is relative to a frozen reference policy. The reference records how strongly the starting model already preferred one response. The trainable policy is asked to improve that relative preference. Keep the prompt, response boundaries and tokenization matched: subtracting probabilities from unrelated prompts does not describe the comparison the objective assumes.

Formulas and principles

Let x be one prompt, y_w its chosen response and y_l its rejected response. A policy π is the model's conditional probability distribution over responses; π_θ is trainable and π_{ref} is the frozen reference. Here $\sigma(z) = 1/(1 + e^{-z})$ is the logistic sigmoid, $\beta > 0$ is the `beta` scale, and $\mathbb{E}$ means averaging the pair losses over the batch.

$$L_{\text{DPO}} = -\mathbb{E}\log\sigma\left(\beta\left[(\log\pi_\theta(y_w|x) - \log\pi_\theta(y_l|x)) - (\log\pi_{\text{ref}}(y_w|x) - \log\pi_{\text{ref}}(y_l|x))\right]\right)$$

A response is a sequence, so its log probability is the sum of the next-token log probabilities of its selected answer tokens. The prompt is conditioning context. Both responses must use the same prompt, tokenizer and boundary convention, including a consistent EOS policy.

Let $a = \log\pi_\theta(y_w|x) - \log\pi_\theta(y_l|x)$ be the trainable policy's preference margin, and a_0 the corresponding frozen reference margin. The scaled improvement is $z = \beta(a - a_0)$. One pair contributes $-\log\sigma(z) = \log(1 + e^{-z})$. A stable `logsigmoid` or softplus formulation avoids explicitly taking the logarithm of a sigmoid that may round to zero.


At $z = 0$ the loss is $\ln 2$: the policy has not improved its margin over the reference. Increasing z lowers the loss. For one pair, $\partial L/\partial a = -\beta\sigma(-z)$, so gradient descent pushes the chosen-minus-rejected margin upward. It does not assert that every absolute chosen probability must increase after a shared-parameter model update.

The four inputs already contain sequence log probabilities and have shape $[B]$. They are not logits $[B, T, V]$, and this function does not compute their token sums. The reference inputs must be detached. In a real implementation, freeze the reference parameters and exclude them from the optimizer as well. Sequence sums are sensitive to length; replacing them with token means would define a different objective.

Improve a preference relative to a reference

Reference then improved policy

chosen	rejected	margin
-2	-3	1
-1	-3	2



beta=0.2: loss 0.693147 at z=0; 0.598139 at z=0.2.

Figure 164: Direct preference optimization: 08.03

Compare the policy margin and reference margin in the first panel, then follow their difference into

the logistic loss curve. The marked zero-margin point is $\ln 2$. A higher relative margin moves right and lowers the loss; the plotted values are analytic examples, not measured preference accuracy.

Function contract

```
def dpo_loss(chosen: torch.Tensor, rejected: torch.Tensor, ref_chosen: torch.Tensor,
 ↪  ref_rejected: torch.Tensor, beta: float) -> torch.Tensor:
```

four tensors: float[B] summed assistant-response log probabilities for matched prompts; chosen/rejected: trainable policy, reference tensors frozen; beta>0. Return scalar mean DPO loss; detach reference inputs. Sequence log probabilities are sums, not token means.

A worked example

For one prompt, policy and reference both assign chosen log probability -2 and rejected log probability -3. Both margins are 1, so their difference is zero. With $\beta = 0.2$, the scaled margin is still zero and the loss is 0.693147.

The derivatives with respect to the two policy log-probability inputs are -0.1 for chosen and $+0.1$ for rejected. Subtracting a small learning-rate multiple of these derivatives increases the chosen input and decreases the rejected input. The reference inputs receive no gradient.

Now change only the policy's chosen log probability to -1. Its margin becomes 2, the reference margin stays 1, and $z = 0.2$. The loss is $\log(1 + e^{-0.2}) \approx 0.598139$. This decrease expresses an improved relative preference on this pair. It does not establish correctness on an unseen question.

For two pairs, calculate one margin difference per pair and then average the two losses. Subtracting batch averages before the nonlinearity would mix examples and produce a different result.

Guided implementation

Implement the exact `dpo_loss` interface; the caller has already scored the responses.

1. Read all four tensors as one value per matched preference pair, shape `[B]`. Keep pair order aligned.
2. Subtract rejected from chosen for the trainable policy. The result remains `[B]` and retains its graph.
3. Detach the two reference tensors before forming the same difference. This blocks gradients even if an input was accidentally supplied with `requires_grad=True`.
4. Subtract the reference margin from the policy margin, then multiply by the positive `beta`.
5. Apply the stable negative log-sigmoid elementwise. At zero scaled margin every pair should contribute approximately0.693147.
6. Average across pairs and return the connected scalar tensor. Use the check driver to confirm signs and the absence of reference gradients.

Common pitfalls

A frozen reference must not be updated by the optimizer. Comparing responses from different prompts breaks the intended ratio.

Run and check

```
python exercises/08_03_direct_preference.py
```

An unfinished prerequisite reports learner TODO, not an installation failure. Once implementation and prerequisites pass, expect:

```
Lesson 08.03 checks passed.
```

The SUPPLIED CHECK DRIVER includes the fixture and relevant boundary/gradient/state assertions. Passing verifies those contracts, not real-data quality, hardware performance or independent mastery.

Further practice

Why is the reference difference subtracted instead of directly maximizing chosen probability?

After passing, change one example dimension or input, predict the result before running, and explain any mismatch. Record the check separately from your explanation. Continue in book order.

08.04 Rewards, advantages and clipped policy objectives

Method sources

The clipped policy-ratio surrogate is from PPO Schulman et al., 2017; R13. This scalar worksheet does not implement a complete PPO trainer: rollout collection, value estimation and the other training components require separate treatment.

Purpose and prerequisites

Preference training uses recorded comparisons. Reinforcement learning can instead sample an action, observe a reward and update the policy toward actions that performed better than a baseline. In a language model, an action may be a generated token, and a rollout is a sequence of such choices. A reward can judge a final answer, but its quality determines what behavior the optimizer is encouraged to learn.

We isolate the clipped policy term used in Proximal Policy Optimization (PPO). The exercise accepts already computed log probabilities and advantages. It does not collect rollouts, fit a value model, compute penalties based on Kullback–Leibler (KL) divergence from a reference policy, or define a reward.

KL divergence measures a difference between probability distributions; that separate term can discourage movement away from the reference. Separating those responsibilities lets us inspect the signs and clipping rule before building a larger system.

Formulas and principles

Let s denote the state, which for token generation is the prompt and tokens already observed, and a the sampled action. The policy $\pi_\theta(a \mid s)$ assigns that action a probability. J denotes the expected-reward objective and ∇ differentiates with respect to policy parameters θ. Here $\mathbb{E}$ is an expectation over sampled state/action observations, estimated by their batch mean, and ϵ is the positive clipping width supplied as `clip`.

$$\nabla J = \mathbb{E}[A \nabla \log \pi_\theta(a|s)]; \quad r = e^{\log \pi_{\text{new}} - \log \pi_{\text{old}}}; \quad L = -\mathbb{E} \min(rA, \text{clip}(r, 1-\epsilon, 1+\epsilon)A)$$

A reward R evaluates an outcome. An advantage A expresses how much better that outcome was than a baseline under the chosen estimator. Positive advantage favors the sampled action; negative advantage discourages it. In this policy term, the advantage is treated as fixed data rather than differentiated through.

The probability ratio is $r = \pi_{\text{new}}(a|s)/\pi_{\text{old}}(a|s)$ for the **same sampled action and state**. Subtracting the corresponding log probabilities and exponentiating computes this ratio. The old policy describes how the sample was collected; it is not the frozen DPO reference from 08.03. Both may appear in a real system for different purposes.

The surrogate compares rA with a version whose ratio is clipped to $[1-\epsilon, 1+\epsilon]$, then selects the smaller value. When $A > 0$, the upper cap prevents the objective from continuing to reward an excessive probability increase. When $A < 0$, the lower cap prevents continued reward for an excessive decrease. The minimum handles both cases because multiplying by a negative number reverses order.

The loss is the **negative** mean because the optimizer minimizes, whereas the surrogate is an objective to maximize. Clipping is not a hard constraint that every updated probability ratio remains inside the interval. Shared parameters and other losses can still move ratios outside it.




Figure 165: Rewards, advantages and clipped policy objectives： 08.04

Read the positive-advantage and negative-advantage curves separately. The horizontal part shows where further movement in the favorable direction no longer increases the clipped objective. The function returns the negative average of these objective values.

Function contract

```
def clipped_policy_loss(new_logp: torch.Tensor, old_logp: torch.Tensor, advantage: torch.Tensor,
↪  clip: float) -> torch.Tensor:
```

new_logp, old_logp, advantage: float[B] action log probabilities and precomputed advantages; clip in(0,1). Return scalar negative clipped surrogate mean. Detach old_logp and advantage; no reward-model gradient. This is the policy term only, not a complete PPO trainer.

A worked example

Take $\epsilon = 0.2$, ratios `[1.5,0.5]`, and advantages `[1,-1]`.

Sample	Ratio	Advantage	Unclipped rA	Clipped ratio	Clipped product	Selected minimum
0	1.5	1	1.5	1.2	1.2	1.2
1	0.5	-1	-0.5	0.8	-0.8	-0.8

The mean surrogate is $(1.2 - 0.8)/2 = 0.2$, so the returned loss is -0.2. A negative policy loss is valid: unlike a negative log likelihood, this surrogate is not required to be nonnegative.

The two examples above are beyond favorable clipping boundaries. For an unclipped example at $r = 1$ and $A = 1$, the loss derivative with respect to `new_logp` is -1 for a one-item batch. Gradient descent raises the sampled action's log probability. With $A = -1$, the sign reverses. Keep `old_logp` and `advantage` detached in both cases.

Guided implementation

Implement `clipped_policy_loss` as a calculation on matched shape `[B]` tensors.

1. Subtract detached `old_logp` from `new_logp`. Do not subtract a probability from a log probability.
2. Exponentiate to obtain positive ratios; equal new and old log probabilities must give ratio1.
3. Detach `advantage` and form the ordinary ratio-times-advantage vector.
4. Clamp the ratios, not the advantages, to `1-clip` and `1+clip`; multiply by the same detached advantages.
5. Use `torch.minimum` elementwise. Check both rows of the worked table before taking any mean.
6. Negate the mean and return the tensor. The supplied checks concern this policy term; an actual rollout system needs independent reward and stability evaluation.

Common pitfalls

Maximizing an unreliable reward can teach reward hacking. A complete algorithm also handles KL, value estimates and sampling mismatch; this small loss check certifies none of those systems.

Run and check

```
python exercises/08_04_policy_objective.py
```

An unfinished prerequisite reports learner TODO, not an installation failure. Once implementation and prerequisites pass, expect:

```
Lesson 08.04 checks passed.
```

The SUPPLIED CHECK DRIVER includes the fixture and relevant boundary/gradient/state assertions. Passing verifies those contracts, not real-data quality, hardware performance or independent mastery.

Further practice

Why does min, rather than max, work for both positive and negative advantages?

First implement a two-action bandit with known reward1 for one action and 0 for the other. Sample from an old policy, compute detached reward-minus-mean advantages and optimize this term; measure

probability and reward on independent samples. Only then design a language reward with held-out correctness checks.

Looking back

We can now specify what a conversational update tries to improve. Before scaling the workload, we must understand where memory and time go and which optimizations preserve the calculation.

09 Scale execution without losing meaning

A mathematically correct model can still use resources badly. A memory estimate may omit activations; a timer may stop before the accelerator finishes; a microbatch mean may give the wrong weight to a short final batch. Performance work begins by making those contracts measurable.

This chapter separates persistent state from temporary storage, derives target-weighted gradient accumulation, explains autocast and loss scaling, checks an efficient attention implementation against a reference, and models distributed gradient reduction. Each technique is tied to an equivalence condition before a speed or memory claim is made. Measurements belong to the actual backend and workload, not to a CPU arithmetic fixture.

09.01 Memory, compute and profiling

Method sources

The incremental attention bandwidth context is Shazeer, 2019; R19; serving-cache memory management is studied in Kwon et al., 2023; R20. Our byte and time accounting are local estimates, not a reproduction of either paper's measured throughput.

Purpose and prerequisites

A parameter count is a starting point for resource planning, not a measurement of peak memory. Training keeps weights, gradients and optimizer state, while the forward and backward passes create activations and temporary workspaces. Inference has a different inventory, including a cache whose size grows with sequence length.

We build a small accounting function before measuring a complete model. Its estimates make assumptions visible: one gradient buffer and two Adam moment buffers in float32, with a caller-specified storage width for parameters. Automatic operation-precision selection (autocast, introduced in 09.03), extra full-precision master copies, state partitioning across processes (sharding, introduced in 09.05), and temporary optimizer buffers can change the inventory. The estimate must be checked against the program that really runs.

Formulas and principles

Let P be `parameters`, b_θ be `parameter_bytes` (bytes per stored weight), N be the `tokens` processed during the measured work, and t be `seconds`. M_{state} counts stored-state bytes, and C_{train} estimates floating-point operations (FLOPs).

$$M_{\text{state}} \approx P(b_\theta + 4 + 8); \quad C_{\text{train}} \approx 6PN; \quad \text{throughput} = N/t$$

P counts parameters. A float32 number occupies four bytes; Adam's two moment buffers therefore use $8P$ bytes under this exercise's assumptions. The three reported state components are Pb_θ, $4P$ and $8P$. If weights also use float32, their sum is $16P$ bytes before activations. Bytes, decimal GB and binary GiB are different units: divide bytes by 10^9 for GB and by 2^{30} for GiB.

The rough dense-model work estimate $6PN$ counts approximately two operations per multiply-add, a forward pass and its backward work. It omits important details, including long-sequence attention and system overhead. Here N should describe processed positions for the work estimate. A valid-target throughput excludes masked padding and is a separate reporting convention; the no-padding arithmetic example lets those counts coincide.

A timer must surround completed work. Accelerator calls can return after scheduling operations, so an unsynchronized host timer can report only dispatch time. Warm up the actual shapes and backend, synchronize at the measured boundaries, and report several updates rather than one unusually fast iteration.

Optimization priorities follow the measured fractions. If data preparation uses30% of iteration time, eliminating it entirely leaves70%; the maximum speedup from that change alone is $1/0.7 \approx 1.43$. This is a bound for that workload, not a predicted speedup from adding workers.




Figure 166: Memory, compute and profiling: 09.01

The memory stack separates weights, gradients and two moment buffers, with activations explicitly outside the estimate. The timing panel uses a hypothetical one-second iteration; its fractions explain

the speedup bound without implying a hardware benchmark.

Function contract

```
def training_budget(parameters: int, tokens: int, seconds: float, parameter_bytes: int = 4) ->
↪ dict:
```

parameters, tokens: positive counts; seconds>0 measured synchronized training duration; parameter_bytes: positive bytes per parameter. Return parameter_memory, gradient_memory, optimizer_memory bytes, approximate_flops, tokens_per_second. Gradient/moment baseline uses float32.

A worked example

Take `parameters=1000`, `tokens=2000`, `seconds=2`, and `parameter_bytes=4`.

Component	Calculation	Bytes
Parameters	1000×4	4000
Gradients	1000×4	4000
Adam moments	$1000 \times 2 \times 4$	8000
State subtotal	$4000 + 4000 + 8000$	16000

Estimated work is $6 \times 1000 \times 2000 = 12{,}000{,}000$ FLOPs, and measured-count throughput is $2000/2 = 1000$ tokens per second. No activation or allocator overhead has been included.

Changing only `parameter_bytes` to 2 reduces the weight term to 2000 bytes; the function's float32 gradient and moment assumptions stay unchanged. Its subtotal becomes 14000 bytes. A real mixed-precision scheme that also keeps a float32 master copy would need an additional4000 bytes, which this interface does not report.

Guided implementation

Implement `training_budget` as explicit unit accounting.

1. Read `parameters` and `tokens` as counts and `seconds` as an already measured positive duration. This function does not time a model.
2. Compute the parameter-memory field using the caller's `parameter_bytes`.
3. Compute the gradient-memory field with four bytes per parameter and optimizer-memory field with eight. Keep the three named outputs separate.
4. Form the approximate FLOP count from the specified processed-token count. Retain it as an estimate, not a peak-memory or runtime prediction.
5. Divide tokens by seconds for throughput, and return the exact named fields expected by the driver.
6. In the follow-up lab, measure actual peak allocation and state which token count your throughput uses. Never replace a measurement with this arithmetic result.

Common pitfalls

A half-precision parameter scheme may need extra master weights; standard autocast often keeps parameters fp32. Estimated state memory is not peak memory.

Run and check

```
python exercises/09_01_budget_profiling.py
```

An unfinished prerequisite reports learner TODO, not an installation failure. Once implementation and prerequisites pass, expect:

```
Lesson 09.01 checks passed.
```

The SUPPLIED CHECK DRIVER includes the fixture and relevant boundary/gradient/state assertions. Passing verifies those contracts, not real-data quality, hardware performance or independent mastery.

Further practice

Why can asynchronous device timing overstate throughput?

Measure10 warmup and 30 timed updates using time.perf_counter, synchronizing accelerated devices at the timing boundaries. Record peak allocated memory, tokens/s, optimizer state bytes and profiler stage shares. Preserve summarized portable measurements, not raw infrastructure logs.

09.02 Position-weighted gradient accumulation

Method sources

For the interaction of gradient accumulation, effective batches and loss scaling, see the official examples in PyTorch, v2.0 AMP; R17. The CPU worksheet isolates weighted accumulation; its arithmetic does not establish a particular accelerator's speed or numerical behavior.

Purpose and prerequisites

If a desired batch does not fit in activation memory, split it into microbatches and accumulate their gradients before one parameter update. Each backward pass can release its own graph while the parameter gradient buffers retain the sum. The model still receives one optimizer step for the combined batch.

The subtle point is normalization. An equal mean over microbatch means weights microbatches equally, even when one contains fewer valid targets. To reproduce the global target-mean objective, each contribution must use the same total target denominator. This reconnects accumulation to the masked loss introduced in Chapter 06.

Formulas and principles

$$L = \frac{\sum_k n_k L_k}{N}; \quad \nabla L = \sum_k \frac{n_k}{N} \nabla L_k, \quad N = \sum_k n_k$$


Let microbatch k contain n_k valid targets with mean loss L_k. Its summed loss is $n_k L_k$. The complete batch mean is the sum of these numerators divided by $N = \sum_k n_k$. Differentiation is linear, so backward on each weighted contribution $n_k L_k / N$ accumulates the gradient of the same total objective.

This is an equivalence statement about an objective evaluated at one parameter state. Parameters must not change between microbatches. Zero gradients once before the loop, call backward for each contribution, then update once after the loop. Dividing by the number of microbatches is valid only when their selected counts are equal.

For a faithful deterministic comparison, disable stochastic dropout and avoid batch-dependent operations such as BatchNorm, which computes normalization statistics from each batch. Splitting a batch changes those statistics, while separate dropout calls can use different random masks. Even without those effects, floating-point reduction order can produce small numerical differences. An optimizer schedule counts combined updates rather than backward calls. If gradients are clipped, clip once after accumulation. Section 09.03 introduces loss scaling: multiplying loss before backward and removing that factor from gradients. Remove it before clipping so the threshold applies to the true accumulated gradient.

Weight microbatches by their target counts

Batch	Count	Mean	Sum
A	2	1	2
B	4	2	8



One update after both backward passes. Correct mean=5/3; naive mean=1.5.

Figure 167: Position-weighted gradient accumulation： 09.02

The table lists each microbatch's target count, mean loss and loss sum. The two bars show the weighted contributions $1/3$ and $4/3$ to the global mean, both using denominator 6. In the implemen-

tation, backpropagate those contributions into the same gradient buffers, then take one optimizer step after both microbatches.

Function contract

```
def accumulated_step(model: nn.Module, batches: list[tuple], optimizer: torch.optim.Optimizer) ->
↪ float:
```

batches: nonempty (X, Y, mask) list with at least one target total; model returns logits, dropout off for equality tests; optimizer owns model parameters. Return pre-update global target-mean loss float; zero grads once, backward per microbatch, step once.

A worked example

MicrobatchA has two valid targets and mean loss 1. MicrobatchB has four valid targets and mean loss 2. Their loss sums are 2 and 8, and the global count is 6. The correct mean is $(2+8)/6 = 5/3 \approx 1.666667$.

A contributes $(2/6) \times 1 = 1/3$ to the loss, and B contributes $(4/6) \times 2 = 4/3$. Adding the contributions before an update gives the global mean. Averaging the two local means gives 1.5, which overweights each target in the smaller microbatch.

The same rule applies to gradients. If the two local mean gradients were1 and 4 for a scalar parameter, the combined gradient would $(2\times1+4\times4)/6 = 3$, not2.5. This additional scalar illustration is separate from the check driver's actual model parameters.

Guided implementation

Implement `accumulated_step` on the supplied `(X,Y,mask)` list.

1. Count all selected Boolean entries before any forward pass, obtaining the positive global denominator `N`.
2. Call `optimizer.zero_grad` once at function indentation, before the microbatch loop.
3. For each microbatch, obtain logits $[B_k, T_k, V]$, form one cross-entropy value per aligned target and select its valid mask entries.
4. Sum those selected losses and divide by the global `N`. In the example, the two contributions must be $1/3$ and $4/3$.
5. Add a detached Python value to the reported loss, but call `.backward()` on the connected contribution tensor. Each pass adds to the same parameter gradient buffers.
6. Leave the loop before calling `optimizer.step()`. Return the accumulated pre-update loss. The return and step must not be indented inside the loop.

Common pitfalls

Accumulation does not make BatchNorm or stochastic dropout identical to a full batch. Clipping should follow all accumulation and AMP unscaling.

Run and check

```
python exercises/09_02_gradient_accumulation.py
```

An unfinished prerequisite reports learner TODO, not an installation failure. Once implementation and prerequisites pass, expect:

```
Lesson 09.02 checks passed.
```

The SUPPLIED CHECK DRIVER includes the fixture and relevant boundary/gradient/state assertions. Passing verifies those contracts, not real-data quality, hardware performance or independent mastery.

Further practice

Why does the optimizer step belong outside the microbatch loop?

After passing, change one example dimension or input, predict the result before running, and explain any mismatch. Record the check separately from your explanation. Continue in book order.

09.03 Autocast and gradient scaling

Method sources

Mixed-precision training is developed in Micikevicius et al., 2018; R14; the software usage baseline is PyTorch, v2.0 AMP; R17. The paper's FP16 discussion and loss-scaling recipe are not a blanket requirement for every BF16 backend; distinguish the formats and test the actual execution path.

Purpose and prerequisites

Precision controls which values a computation can represent and how much relative detail it keeps. A training system can use lower precision for selected matrix operations while retaining float32 parameters and safer reductions. This is automatic mixed precision, not a command to cast the entire model and every tensor to half precision.

FP16 (16-bit floating point) and BF16 (bfloat16) are two different 16-bit formats. The exercise supports two paths: CPU BF16 without a gradient scaler, and CUDA FP16 with a caller-owned scaler that manages the loss-scaling factor. Their operation order is the common subject. A passing CPU example does not test accelerator overflow detection, skipped updates or kernel speed.

Formulas and principles

$$\widetilde{L} = sL; \quad \tilde{g} = s\nabla L; \quad g = \tilde{g}/s \quad \text{before clipping and updating}$$

FP16 allocates five exponent bits and ten fraction bits; BF16 allocates eight exponent bits and seven fraction bits. BF16 therefore has a broadly float32-like exponent range but less relative precision. Range and precision are different properties: a format can represent very large magnitudes while rounding nearby values coarsely.

Loss scaling multiplies the loss by $s > 0$ before backward. By the chain rule the stored gradients are also multiplied by s. Before an ordinary optimizer update, unscale those gradients by dividing by s. The purpose is to keep small intermediate gradient values in a representable range, not to increase the mathematical learning rate.

Clipping must inspect the unscaled gradients. For norm threshold1, clipping a scaled norm first and then unscaling would impose an unintended threshold of roughly $1/s$ on the true gradient. The correct order is scale, backward, unscale, clip, optimizer step, then scaler update. The scaler may skip an update if it detects nonfinite gradients; it is state that must be saved for faithful recovery.

An autocast context chooses eligible operation dtypes. The original float32 parameter objects remain float32 in this exercise. Backward runs outside the autocast context. For accumulation, complete all scaled backward calls before one unscale/clip/step/update sequence.

Unscale before clipping

Quantity	Original	Scaled ×1024	Unscaled ÷1024
Loss	0.01	10.24	0.01
Gradient	0.000001	0.001024	0.000001
True norm	2	2048	2 → clip to 1

If scaled norm 2048 is clipped to 1 first, the unscaled norm is only 1/1024.

Figure 168: Autocast and gradient scaling：09.03

Read each table row from the original value through scaling by 1024 and division by 1024. The norm row then clips the restored norm 2 to 1; the footer shows why clipping 2048 first would leave an unintended norm of $1/1024$. These numbers illustrate the algebra, without claiming that the chosen unscaled gradient necessarily underflows in every backend.

Function contract

```
def mixed_precision_step(model: nn.Module, x: torch.Tensor, y: torch.Tensor, optimizer:
 ↪  torch.optim.Optimizer, scaler=None) -> float:
```

model: module; x, y: long[B, T]; optimizer: model optimizer; scaler: None for CPU BF16 or caller-owned CUDA GradScaler for CUDA FP16. Return pre-update loss float. Clip unscaled global grad norm to 1 before step. Existing fp32 model parameters remain fp32.

A worked example

Let the unscaled loss be0.01, a true scalar gradient be0.000001, and scale be1024. The scaled loss is 10.24 and the scaled gradient is 0.001024. Dividing that gradient by 1024 restores0.000001 before updating. This example demonstrates the algebra; whether an intermediate value underflows depends on its format and the operations that produced it.

For a separate clipping example, let the true gradient norm be2 and the scale1024. The stored norm is 2048. Correct unscaling restores norm 2, then clipping limits it to 1. Incorrectly clipping2048 down to 1 before unscaling leaves true norm $1/1024$, an excessively small update.

The supplied CPU model contains an embedding and a linear projection. Its parameter storage stays float32, while eligible forward operations may produce BF16 outputs. The returned Python loss reports the pre-update objective; the scalar tensor is used for backward before that conversion.

Guided implementation

Implement the two branches in `mixed_precision_step` without taking ownership of the caller's optimizer or scaler.

1. Clear gradients, determine the input device type, and choose BF16 for the CPU exercise or FP16 for the CUDA path.
2. Enter `torch.autocast` around forward and loss computation. Preserve logits/target alignment when flattening for cross-entropy.
3. Leave autocast before backward. If `scaler` is absent, use ordinary backward, then clip the global norm to 1 and step once.
4. If a scaler is supplied, call its scaling operation on the loss before backward, then unscale the optimizer's gradients exactly once.
5. Clip after unscale, let `scaler.step` perform or skip the optimizer update, and call `scaler.update`.
6. Return the pre-update loss as a Python float. A real continuation checkpoint must also preserve scaler state.

Common pitfalls

Do not cast all parameters to half just because autocast is used. For real CUDA accumulation unscale/step/update once per optimizer update.

Run and check

```
python exercises/09_03_mixed_precision.py
```

An unfinished prerequisite reports learner TODO, not an installation failure. Once implementation and prerequisites pass, expect:

```
Lesson 09.03 checks passed.
```

The SUPPLIED CHECK DRIVER includes the fixture and relevant boundary/gradient/state assertions. Passing verifies those contracts, not real-data quality, hardware performance or independent mastery.

Further practice

What breaks if clipping sees scaled gradients?

After passing, change one example dimension or input, predict the result before running, and explain any mismatch. Record the check separately from your explanation. Continue in book order.

09.04 Efficient attention with equivalence checks

Method sources

The mathematical attention target is Vaswani et al., 2017; R04; the IO-aware exact-attention algorithm is FlashAttention Dao et al., 2022; R15. Our scaled-dot-product-attention wrapper and parity fixture do not implement the FlashAttention GPU kernel, and backend selection remains environment-dependent.

Purpose and prerequisites

The reference attention calculation materializes scores and weights for every query-key pair. For a long sequence, those matrices can dominate memory even when the final output is much smaller. Efficient attention changes how intermediate values are stored and reused while preserving the mathematical attention operation.

PyTorch's `F.scaled_dot_product_attention`, abbreviated SDPA, selects a backend for scaled dot-product attention. A fused backend combines operations and manages their intermediate storage; it does not change which token positions may be read. Before timing it, compare its outputs and gradients with the explicit reference. The mask convention, scale and dropout policy must be identical in both paths.

Formulas and principles

$$O = \text{softmax}(QK^\top/\sqrt{d} + M)V; \quad \text{equivalence: } O_{\text{fast}} \approx O_{\text{reference}},\ \nabla O_{\text{fast}} \approx \nabla O_{\text{reference}}$$

Queries and keys share a matching width d, while values may have a different width d_v. In this interface the common layout is $Q : [B, H, T_q, d]$, $K : [B, H, T_k, d]$, $V : [B, H, T_k, d_v]$, with output $[B, H, T_q, d_v]$. The causal default assumes aligned self-attention positions. In the equation, M is an additive score mask: 0 for visible pairs and $-\infty$ for blocked pairs. It is the mathematical counterpart of the Boolean `allowed` argument, rather than that Boolean tensor added directly to the scores. The gradient comparison means applying the same scalar downstream loss to each output and comparing its gradients with respect to Q, K and V.

Tiled attention can maintain a running maximum, a rescaled exponential sum and a weighted value sum without keeping the complete probability matrix in device memory. That avoids a large stored intermediate; it does not make the dense pairwise arithmetic disappear. Backend eligibility depends on shape, dtype and device, so a dispatch call alone is not proof that a particular fast kernel ran.

The Boolean mask in PyTorch SDPA uses `True` for **allowed** entries. Section 04.05's `masked_fill` example used `True` for blocked entries. The names refer to different conventions; negating the wrong one can silently expose future positions.

For a cache with P past positions, a new query index i has absolute position $P + i$. Its allowed keys satisfy $j \leq P + i$. A rectangular `is_causal=True` interpretation may align at the upper left instead; provide the explicit absolute-position mask for this exercise's cached case. Set dropout to zero for the deterministic equivalence check.




Figure 169: Efficient attention with equivalence checks： 09.04

The left panel shows the 3-by 3 causal visibility matrix; the right panel separates a one-query, three-key cached case. White or colored cells must be read according to the explicit allowed-mask legend. Output values are compared with the original zero-score fixture.

Function contract

```
def efficient_attention(q: torch.Tensor, k: torch.Tensor, values: torch.Tensor, allowed:
↪  torch.Tensor | None = None) -> torch.Tensor:
```

`q`: float `[B,H,Tq,d]`; `k`: float `[B,H,Tk,d]`; `values`: float `[B,H,Tk,dv]`. The causal default assumes aligned self-attention with `Tq=Tk`; an explicit Boolean `allowed` mask supports the documented rectangular case and uses True for visible keys. Return `[B,H,Tq,dv]`, with dropout0 and the default inverse-square-root scale.

A worked example

With three zero query/key scores, a causal query averages only the visible values. Let values be2,4 and 8, with shape `[1,1,3,1]`. Query/key matching width can independently be2, giving their shape `[1,1,3,2]`.

The three outputs are 2, $(2+4)/2 = 3$, and $(2+4+8)/3 = 14/3$. The output shape is `[1,1,3,1]`, not the query/key shape. Equal scores produce uniform weights over the allowed keys, not all keys.

Now suppose two positions are already cached and one new query has absolute position 2. It must see keys0,1,2, so the explicit allowed mask `[True,True,True]` has shape `[1,3]`. Its output is $14/3$. A mistakenly upper-left mask would keep only key 0 and produce2, even though the operation would still return a tensor of the expected shape.

Guided implementation

Implement `efficient_attention` as a precise backend call, leaving the explicit reference in the supplied checks.

1. Read the last two axes of each input and distinguish query length, key length, matching width and value width.
2. When `allowed is None`, use the exercise's aligned causal self-attention default with `is_causal=True` and `dropout_p=0.0`.
3. When an explicit `allowed` mask is supplied, pass it as `attn_mask` and set `is_causal=False`. Its True entries mean visible keys.
4. Retain the backend's default inverse-square-root matching-width scale; do not divide scores a second time outside the call.
5. Return the output tensor. An optimized implementation need not return the full weights matrix.
6. Compare outputs and input gradients at a dtype-appropriate tolerance. Only then measure actual time and peak allocation on the intended backend.

Common pitfalls

Kernel numerical results can differ slightly; compare dtype-appropriate tolerances. Explicit masks and dropout semantics must be preserved in both implementations.

Run and check

```
python exercises/09_04_efficient_attention.py
```

An unfinished prerequisite reports learner TODO, not an installation failure. Once implementation and prerequisites pass, expect:

```
Lesson 09.04 checks passed.
```

The SUPPLIED CHECK DRIVER includes the fixture and relevant boundary/gradient/state assertions. Passing verifies those contracts, not real-data quality, hardware performance or independent mastery.

Further practice

Why can correct output checks still miss a backward bug?

After passing, change one example dimension or input, predict the result before running, and explain any mismatch. Record the check separately from your explanation. Continue in book order.

09.05 Distributed gradients and recovery

Method sources

For distributed data parallelism, see Li et al., 2020; R33 and the versioned design note PyTorch, v2.0 DDP; R18. Optimizer-state partitioning is developed in ZeRO Rajbhandari et al., 2020; R34. Our CPU recovery ledger models accounting invariants, not a complete implementation of DDP or ZeRO.

Purpose and prerequisites

Data parallelism keeps a model replica in each participating process and gives the processes different data. A rank is a process's numbered identity within this communication group; distributed data parallelism is abbreviated DDP. Before a common optimizer update, their gradients are synchronized. If every rank sees the same number of valid targets, averaging local mean gradients recovers the global target mean. Unequal masks or final batches break that shortcut.

The CPU function in this section models the reduction contract. It does not start processes or perform network collectives. This separation lets us establish the correct weighted gradient before introducing process groups, data partitioning and coordinated recovery.

Formulas and principles

$$g_{\text{global}} = \frac{\sum_r n_r g_r}{\sum_r n_r}; \quad \text{DDP mean reduction requires local loss scale } Rn_r/N$$

Rank r has n_r selected targets and local target-mean gradient g_r. Its loss-sum gradient is $n_r g_r$. The global target mean is therefore $\sum_r n_r g_r / \sum_r n_r$, exactly the same accounting rule used for micro-batches in09.02.

Ordinary DDP averages gradients across R ranks under the relevant default reduction behavior. To obtain the weighted global mean when local counts differ, a local mean loss can be scaled by Rn_r/N, where $N = \sum_r n_r$. DDP's subsequent factor $1/R$ cancels that extra rank count. This is a derivation for the stated reduction convention, not a rule to apply again if the framework has already performed the normalization.

Sharding is a different storage decision: parameters, gradients or optimizer state may be partitioned rather than fully replicated. It adds reconstruction and checkpoint requirements. For coordinated recovery, ranks must agree on one completed update boundary and restore optimizer state, rank-local randomness and data position consistently.

A collective is a communication operation in which every rank in the group participates, such as a gradient reduction combining their tensors. All ranks must enter matching collectives in the same order.

A rank that exits early while its peers wait for a gradient reduction can deadlock the program. Validation, exceptions and zero-target cases therefore require a coordinated policy in a real system.

A global target mean is a weighted reduction

Rank	Count	Local mean gradient	Weighted numerator
0	2	[1,3]	[2,6]
1	4	[4,0]	[16,0]
Sum	6		[18,6]

Global gradient=[18,6]/6=[3,1]. Unweighted rank mean=[2.5,1.5].

Figure 170: Distributed gradients and recovery：09.05

The table lists different target counts and local gradients for two ranks, then multiplies each gradient by its count. Add the weighted numerators and divide once by the total count. The footer contrasts that result with the incorrect unweighted rank mean. The DDP scaling expression above explains how an averaging collective can realize the same result; the CPU exercise performs no communication.

Function contract

```
def distributed_gradient(local_gradients: list[torch.Tensor], local_counts: list[int]) ->
↪  torch.Tensor:
```

local_gradients: nonempty same-shape float tensors, each a rank-local valid-target mean gradient; local_counts: matching positive target counts. Return global count-weighted mean gradient without modifying inputs. This CPU exercise models the reduction contract; supplied distributed_lab.py verifies actual DDP synchronization.

A worked example

Rank0 has two targets and mean gradient `[1,3]`; rank1 has four targets and mean gradient `[4,0]`. Multiply by counts to obtain `[2,6]` and `[16,0]`. Their sum is `[18,6]`, and division by six gives `[3,1]`.

The unweighted rank mean is `[2.5,1.5]`, a different update direction. With $R = 2$, scale the local mean losses by $2 \times 2/6 = 2/3$ and $2 \times 4/6 = 4/3$. Averaging the resulting gradients gives the intended `[3,1]`.

With equal counts, the weighted calculation reduces to an ordinary mean; with one rank, it returns that rank's gradient. Both are useful boundary checks, and neither permits modifying an input gradient in place.

Guided implementation

Implement `distributed_gradient` using the supplied lists, not a distributed runtime.

1. Read each `local_gradients[r]` as a same-shape floating tensor and `local_counts[r]` as its positive selected count.
2. Sum the counts for the global denominator.
3. Create a fresh zero tensor with `torch.zeros_like` using the first gradient's shape, dtype and device.
4. Iterate over matching gradient/count pairs with `zip`, accumulating each weighted numerator into the fresh result.
5. Divide by the global count and return. Compare with `[3,1]` and the equal-count boundary.
6. Check that all original gradients retain their values. Actual communication and kill/resume validation belong to the separate distributed laboratory.

Common pitfalls

All ranks must enter collectives in the same order. A successful CPU reduction does not establish multi-device throughput or sharded recovery; run the actual two-process lab and a kill/resume experiment before scaling.

Run and check

```
python exercises/09_05_distributed_recovery.py
```

An unfinished prerequisite reports learner TODO, not an installation failure. Once implementation and prerequisites pass, expect:

```
Lesson 09.05 checks passed.
```

The SUPPLIED CHECK DRIVER includes the fixture and relevant boundary/gradient/state assertions. Passing verifies those contracts, not real-data quality, hardware performance or independent mastery.

Further practice

Why is averaging rank means wrong when padding yields unequal valid target counts?

Run python scripts/distributed_lab.py for a real local two-process CPU/Gloo DDP update versus a global reference. Then follow the scaling runbook for accelerator DDP, accumulation with no_sync, atomic rank-aware checkpoint manifests, synchronized failure and resume. Real connection mappings belong only in ignored local configuration.

Looking back

An optimization has meaning only when its result can be compared with a preserved baseline. The final chapter turns that discipline into experiment records, budget models and tests of original ideas.

10 Make experiments explainable

An experiment is a chain of identities and decisions. Which code ran? Which data and tokenizer were fixed? How many targets were actually processed? Which validation rule selected the saved weights, and which independent test was reserved for the final comparison? A result becomes useful when another person can reconstruct that chain.

We finish by making a portable experiment snapshot, fitting a deliberately limited scaling model, and estimating a paired effect with a bootstrap interval. The objective is to make a claim precise enough to be challenged. A new architectural idea becomes evidence when controlled comparisons, ablations and failure cases show what it changes and under which conditions.

10.01 Reproducible experiment records

Method sources

Structured model reporting is motivated by Model Cards Mitchell et al., 2019; R40; byte fingerprints use NIST, 2015; R41. Our portable experiment manifest adds local provenance fields and does not claim to reproduce a model-card evaluation or certify a model's abilities.

Purpose and prerequisites

A loss number does not identify an experiment. It acquires meaning from the code, data, tokenizer, optimization budget and evaluation protocol that produced it. A record should preserve those identities even if a caller later edits the Python dictionaries used to configure the run.

This section builds a small immutable snapshot by convention: a deep copy that the caller cannot change indirectly through shared nested objects. The configuration receives a stable digest. Saved weights remain outside Git and receive their own artifact checksums; neither a configuration hash nor a code revision substitutes for those weights.

Formulas and principles

$$h_{\text{cfg}} = \text{SHA256}(\text{JSON}_{\text{sorted,compact,UTF8}}(\text{cfg}))$$

$$\text{Evidence} = (\text{commit}, \text{data}, \text{tokenizer}, \text{cfg}, \text{budget}, \text{protocol}, \text{results})$$

A dictionary's insertion order is not part of the experiment's intended identity. Serializing with sorted keys, compact separators and UTF-8 encoding produces the same bytes for equivalent key orderings

under this stated Python convention. SHA-256 then fingerprints those bytes. This is a reproducible serialization rule for the exercise, not a universal canonical-JSON standard across every language and numeric representation.

The `code_commit` argument identifies the code revision with a full 40-character hexadecimal Git identifier. A short label such as `main` can move; an abbreviated hash is insufficient for the supplied contract. The data and tokenizer IDs must resolve to preserved versions or checksums. A protocol ID fixes what is measured and how it is aggregated.

Deep copying matters because nested dictionaries remain shared after a shallow copy. If a saved record contains the caller's original `config['model']` dictionary, a later width edit would silently rewrite history. Construct and snapshot the full record before returning it.

A digest is not encryption or anonymization. Hashing a configuration that contains a personal hostname still leaves that hostname in the stored configuration. Use portable compute labels and keep actual private mappings outside the record. The conclusion should separate a measured difference from the next hypothesis it suggests.




Figure 171: Reproducible experiment records: 10.01

Read downward from two configuration insertion orders to their shared sorted serialization and SHA-256 digest. The figure shows only a digest prefix; the function returns the complete hexadecimal fingerprint. The final line describes a separate caller mutation: changing its nested width to 99 must leave the saved snapshot at 8.

Function contract

```
def experiment_record(code_commit: str, data_id: str, tokenizer_id: str, config: dict, budget:
↪  dict, protocol_id: str, results: dict, conclusion: str) -> dict:
```

code_commit: full40-character hexadecimal revision; data_id, tokenizer_id, protocol_id: versioned portable strings; config, budget, results: JSON-compatible dicts; conclusion: evidence-limited text. Return deep snapshot with config_sha256 from canonical JSON plus all supplied fields.

A worked example

Consider `{'width':8,'heads':2}` and the same entries inserted in reverse order. The specified serialization produces `{"heads":2,"width":8}` in both cases. Identical UTF-8 bytes must yield the same digest. Changing width to 16 changes the byte sequence and normally changes the digest.

For an ownership test, use `config={'model':{'width':8}}`, create the record, then set the caller's nested width to 99. The stored width must remain8, and its existing digest must still describe that original snapshot. Copying only the top dictionary would fail this test.

A complete real record also states how many updates and selected targets were consumed, which checkpoint selection rule was used and which artifact was evaluated. The exercise's placeholder-style data IDs teach structure; they must be replaced by real preserved identities in an actual run.

Guided implementation

Implement `experiment_record` while preserving the exact field names in its check driver.

1. Validate `code_commit` with a full-string40-hex-digit match and raise `ValueError` if it fails.
2. Serialize `config` with sorted keys, compact separators and `ensure_ascii=False`, then encode the resulting string as UTF-8.
3. Compute the hexadecimal SHA-256 digest of those bytes. Hash the configuration, not its Python `repr` or a path to a mutable file.
4. Assemble the supplied identity, configuration, budget, protocol, results and conclusion fields with `config_sha256`.
5. Deep-copy the complete record before returning, so nested caller-owned objects are no longer shared.
6. Test reordered keys, a changed value and a nested post-return mutation separately. None of these tests establishes the truth of a measured result; that requires the preserved experiment.

Common pitfalls

Hashing a config does not remove sensitive fields. Use neutral artifact IDs; actual compute mappings, logs and weights belong in ignored locations.

Run and check

```
python exercises/10_01_experiment_provenance.py
```

An unfinished prerequisite reports learner TODO, not an installation failure. Once implementation and prerequisites pass, expect:

```
Lesson 10.01 checks passed.
```

The SUPPLIED CHECK DRIVER includes the fixture and relevant boundary/gradient/state assertions. Passing verifies those contracts, not real-data quality, hardware performance or independent mastery.

Further practice

What evidence is missing from a screenshot showing only the final loss?

Use templates/experiment-record.json and templates/model-card.md for each real run and release candidate. Record full commit, data/tokenizer checksums, portable configuration, measured budget, fixed evaluation, artifact digest and limitations. Keep model/data weights outside Git.

10.02 Measured scaling and budget choices

Method sources

Empirical language-model scaling is studied by Kaplan et al., 2020; R35; compute-optimal data/parameter allocation is revisited by Hoffmann et al., 2022; R11. Our tiny log–log fit is a learning fixture, not evidence that those empirical laws hold for this model or outside the fitted range.

Purpose and prerequisites

A scaling curve is useful when it changes a budget decision: should the next run use more parameters, more training tokens or a different allocation of the same compute? A fitted curve is meaningful only if its measurements refer to comparable data, tokenization, objectives and evaluation. A smooth line through incomparable runs is not a scaling result.

We begin with a limited one-dimensional model whose loss floor is supplied rather than estimated. This makes the log-space fit transparent. It is a numerical exercise for learning how assumptions enter an extrapolation, not permission to project a handful of toy points into a large training commitment.

Formulas and principles

For measured run i, let C_i be its compute budget in one fixed unit and L_i its comparable held-out loss. L_∞ is the supplied `floor`, a the fitted coefficient, and b the fitted exponent. Define $x_i = \ln C_i$ and $y_i = \ln(L_i - L_\infty)$; the bars $\bar{x}$ and $\bar{y}$ denote arithmetic means over the observed runs.

$$\log(L - L_\infty) = \log a - b \log C; \quad b = -\frac{\sum_i (x_i - \bar{x})(y_i - \bar{y})}{\sum_i (x_i - \bar{x})^2}$$


Assume $L(C) = L_\infty + aC^{-b}$, with positive compute C and $L(C) > L_\infty$. Subtract the supplied floor before taking logs. With $x = \ln C$ and $y = \ln(L - L_\infty)$, the relation becomes the straight line $y = \alpha + sx$, where $\alpha = \ln a$ and $s = -b$.

Least squares chooses the slope s by dividing the centered cross-product sum by the centered squared-x sum. At least two distinct budgets are needed, or the denominator is zero. Recover $a = e^\alpha$ and $b = -s$. The exercise does not constrain the fitted exponent to be positive: noisy or worsening measurements could yield a different sign, which should be reported rather than silently repaired.

An assumed floor can strongly change the fitted curve. If a loss is at or below that floor, its logarithm is not defined in this model. Even a mathematically valid fit can be wrong outside the observed range because data quality, reuse, optimization and system efficiency may change.

Large-model scaling studies consider more than this one variable. The compute-optimal literature motivates balancing model size and tokens under a budget, but it does not certify that a particular small model has learned enough to chat. Keep unique corpus tokens separate from repeated training exposures and actual achieved throughput.

A transparent fit with an assumed loss floor



Filled points are synthetic observations. Hollow point is an untested extrapolation.

Figure 172: Measured scaling and budget choices： 10.02

The left plot shows the three hypothetical loss measurements and their fitted power law. The right plot shows the same points after logarithms: the slope is -0.5. The extrapolated $C = 64$ marker is a prediction to test, not an additional observation.

Function contract

```
def fit_scaling(compute: list[float], losses: list[float], floor: float = 0.) -> dict:
```

compute: at least 2 distinct positive budgets; losses: same-length measured held-out losses, each>floor; floor: assumed fixed irreducible-loss estimate. Return coefficient a, exponent b for $L(C) \approx L_\infty + aC^{-b}$ using log-space least squares. This is a toy fit, not a universal law.

A worked example

Use compute `[1,4,16]`, losses `[4,2,1]`, and floor0. Multiplying compute by 4 halves the loss. Therefore $4^{-b} = 1/2$, giving $b = 1/2$; the first point then gives $a = 4$.

C	L	$\ln C$	$\ln L$
1	4	0	1.386294
4	2	1.386294	0.693147
16	1	2.772589	0

The centered least-squares slope is-0.5 and intercept is $\ln 4$. At compute64, the model predicts $4/\sqrt{64} = 0.5$. That budget was not included in the fit, so a real experiment there would test the extrapolation.

For the separate floor1 fixture with losses `[5,3,2]`, subtracting1 yields the same residual losses `[4,2,1]`. The fitted a, b stay4 and 0.5, but the compute64 prediction is now1.5. Adding the floor back is part of the model, not an optional reporting choice.

Guided implementation

Implement `fit_scaling` with the supplied fixed floor.

1. Convert compute and loss lists to NumPy float64 arrays. Keep their paired order unchanged.
2. Compute `x=log(compute)` and `y=log(losses-floor)` under the contract's positive and distinct-budget assumptions.
3. Subtract the mean from each array. The centered covariance numerator and squared-x denominator produce the line slope.
4. Compute the intercept from the original means, not the centered means, which are zero.
5. Return the coefficient as the exponential of the intercept and the exponent as the negative slope, using the driver's exact field names.
6. Verify both the zero-floor and floor1 examples. Treat a future-budget prediction as a hypothesis requiring a new measurement.

Common pitfalls

Comparing models with different data quality or tokenizers confounds the fit. An estimated improvement must be checked at a new budget.

Run and check

```
python exercises/10_02_scaling_fit.py
```

An unfinished prerequisite reports learner TODO, not an installation failure. Once implementation and prerequisites pass, expect:

```
Lesson 10.02 checks passed.
```

The SUPPLIED CHECK DRIVER includes the fixture and relevant boundary/gradient/state assertions. Passing verifies those contracts, not real-data quality, hardware performance or independent mastery.

Further practice

Why can a wrong assumed loss floor radically change the fitted exponent?

After passing, change one example dimension or input, predict the result before running, and explain any mismatch. Record the check separately from your explanation. Continue in book order.

10.03 Original ideas, ablations and uncertainty

Method sources

The bootstrap resampling principle is introduced by Efron, 1979; R36. This paired-loss exercise resamples aligned units; its interval depends on sampling assumptions and does not guarantee coverage or conversational quality.

Purpose and prerequisites

A new component can improve one run for several reasons: its mechanism may help, its initialization may be lucky, its training budget may be larger, or the experimenter may have selected the best of many attempts. A controlled experiment separates those possibilities by preserving a baseline and stating the comparison before seeing the final test.

Use paired runs when a matched seed and data schedule can make baseline and variant comparable. An ablation removes the proposed component while retaining the rest of the system. Failure cases and negative results matter because they reveal what a favorable average hides. This final exercise summarizes paired loss differences and their empirical variability; it does not turn an idea into a research contribution by itself.

Formulas and principles

Let n be the number of original paired runs and i index those pairs. $L_{\text{base},i}$ and $L_{\text{var},i}$ are their baseline and variant losses. A star marks a bootstrap resample, so $\overline{d}^*$ is one resampled mean difference. Here CI denotes the confidence interval estimated by this procedure, and Q_q is the q quantile of the bootstrap mean distribution: the value at fraction q of its ordered mass.

$$d_i = L_{\text{base},i} - L_{\text{var},i}; \quad \Delta = \frac{1}{n}\sum_i d_i; \quad \text{CI} = [Q_{.025}(\overline{d}^*), Q_{.975}(\overline{d}^*)]$$

For pair i, define $d_i = L_{\text{base},i} - L_{\text{var},i}$. A positive difference means the variant has lower loss under this convention. The mean improvement is $\Delta = \sum_i d_i/n$. Pairing occurs before resampling: a bootstrap draw samples indices into the **differences**, keeping each baseline/variant pairing intact.

Each bootstrap replicate draws n indices with replacement from the n observed pairs and averages the selected differences. Quantiles0.025 and 0.975 give a percentile interval for this empirical resampling procedure. The local generator seed makes that numerical procedure repeatable without changing global NumPy randomness.

The interval reflects variation present in the observed pairs under the resampling assumptions. It does not account automatically for benchmark selection, correlated seeds, repeated model search or unmeasured data shifts. With only three runs, an interval can be misleadingly narrow. More bootstrap replicates reduce Monte Carlo noise; they do not create more independent training runs.

Before a real comparison, define the primary metric, the fixed evaluation split and the budget-matching rule. Use validation to develop the method and reserve an independent final evaluation. Report all planned variants and seeds, rather than only the best-looking checkpoint or task.




Figure 173: Original ideas, ablations and uncertainty： 10.03

The left panel plots baseline and variant losses for three paired runs; subtracting the variant from the baseline gives [1,1,1]. The right panel is a separate example: the exact resampling distribution of the mean of [-1,0,1]. A narrow toy interval is not independent evidence of generalization.

Function contract

```
def paired_effect(baseline: list[float], variant: list[float], seed: int, bootstrap: int = 1000)
 ↪  -> dict:
```

baseline, variant: equal nonempty paired held-out losses under matched seeds/budgets; seed: local bootstrap RNG seed; bootstrap: positive replicates. Return mean_improvement, ci_low, ci_high, count. Improvement=baseline-variant; percentile bootstrap interval95%, exploratory for small samples.

A worked example

Baseline losses `[3,4,5]` and variant losses `[2,3,4]` yield `[1,1,1]`. Their mean improvement is 1. Every resample also has mean1, so the percentile interval is `[1,1]`. That degeneracy comes from the identical observed differences; it does not establish zero uncertainty about future runs.

For differences `[-1,0,1]`, the observed mean is 0. Resampling three entries with replacement permits negative, zero and positive means. The exact27 ordered resamples range from-1 to 1, and a sufficiently populated empirical interval spans zero. This illustrates that the observed pairs do not isolate a consistently positive effect.

The supplied finite-bootstrap calculation uses its explicit seed and replicate count. Its returned `count` remains the number of original paired runs, not the number of bootstrap replicates. If one run is excluded, report the reason and apply a predefined exclusion policy rather than choosing whichever removal produces a favorable interval.

Guided implementation

Implement `paired_effect` without rerunning models or altering global RNG state.

1. Convert the equal-length nonempty loss lists to float64 arrays and form `baseline-variant` elementwise.
2. Save the actual mean difference and original pair count before resampling.
3. Create `np.random.default_rng(seed)`. Use this local generator for an integer index array of shape `[bootstrap,n]` with replacement.
4. Index the differences with that array, giving `[bootstrap,n]` values; average along the last axis to get one mean per replicate.
5. Compute the two requested quantiles, then return the mean, interval endpoints and original count under the exact named fields.
6. Check the constant-difference fixture and a sign-changing example. Follow the arithmetic check with a real baseline/variant/ablation plan; no unrun experiment may be described as a result.

Common pitfalls

Do not report only the best seed or claim significance from a tiny bootstrap. Predefine the primary metric; multiple variants require honest selection reporting and final independent evaluation.

Run and check

```
python exercises/10_03_ablations_uncertainty.py
```

An unfinished prerequisite reports learner TODO, not an installation failure. Once implementation and prerequisites pass, expect:

```
Lesson 10.03 checks passed.
```

The SUPPLIED CHECK DRIVER includes the fixture and relevant boundary/gradient/state assertions. Passing verifies those contracts, not real-data quality, hardware performance or independent mastery.

Further practice

What must stay fixed to attribute improvement to a new attention design?

Complete templates/research-proposal.md, run baseline/one variant/ablation with matched seeds and token budgets, freeze evaluation, record all runs and explain limitations. Assemble a versioned One-

Long model card and artifact checksums. A new name or altered block is an idea; reproducible evidence makes it a research result.

Looking back

The model is now something you can inspect, train, evaluate and change. Begin the next experiment with a question whose answer would alter a decision, then preserve enough evidence for that answer to survive a rerun.

Appendix A Glossary

Definitions follow the conventions used in this book. Method attributions appear in the relevant sections and References.

Text and tokenization

Unicode code point. An integer identifying a position in the Unicode codespace; it is distinct from a UTF-8 byte and a model token ID.

UTF-8. A variable-length encoding of Unicode scalar values using one to four bytes.

Byte. Eight bits; a byte value ranges from 0 to 255.

Token. One vocabulary unit emitted by a tokenizer; it may represent a byte, part of a word or several characters.

Token ID. The integer index assigned to a vocabulary entry, rather than the vocabulary size.

Vocabulary. The mapping between token units and their IDs, together with declared special entries.

Tokenizer. A procedure that maps text to tokens or IDs under a specified vocabulary and encoding policy.

Byte-pair encoding (BPE). An iterative merge method that learns larger units from frequent adjacent pairs.

Merge rule. A ranked instruction replacing an adjacent pair with its combined token.

Encoding and decoding. Mapping source text to its representation and reconstructing text from that representation; exact recovery depends on the declared codec.

End-of-sequence token (EOS). A reserved vocabulary entry used to mark an ending under the model's data and generation protocol.

Padding token. A reserved entry used to align sequence lengths; padding positions usually require explicit loss and attention masks.

Tensors and learning

Tensor shape. The ordered lengths of a tensor's axes, such as batch, position and feature axes.

Batch size. The number of examples processed together in one batch, distinct from token count.

Context length. The number of positions available to a model call; the supported limit and actual input length are different quantities.

Embedding table. A trainable matrix with one feature vector per vocabulary entry.

Embedding lookup. Selecting embedding rows using token IDs while preserving the input ID layout.

Broadcasting. Aligning compatible tensor shapes so an operation can act across axes without explicitly copying every value.

Trainable parameter. A model value whose gradient may be used by an optimizer to update it.

Loss function. A scalar objective measuring the specified prediction error, with its reduction and mask defined.

Gradient. The vector or tensor of partial derivatives of a scalar objective with respect to selected variables.

Chain rule. The derivative rule that composes local derivatives through intermediate variables.

Automatic differentiation. Computing derivatives by applying derivative rules to the executed program's operations.

Backpropagation. Reverse propagation of derivative contributions through a computation graph; parameter updates are a separate operation.

Logits. Real-valued model outputs before conversion into a probability distribution.

Softmax. Exponentiating scores and dividing by their sum along a declared axis to obtain probabilities.

Cross-entropy loss. For a one-hot observed target, the negative logarithm of its predicted probability, aggregated as specified.

Autoregressive generation. Repeatedly predicting a next token conditioned on the preceding tokens and appending the selected result.

Temperature. A positive divisor applied to logits before sampling; lower values sharpen the distribution.

Greedy decoding. Selecting the highest-scoring allowed next token at each step.

Attention and architecture

Query, key and value (Q/K/V). Projected features used to compute attention scores and the corresponding weighted content.

Scaled dot-product attention. Attention formed from query–key dot products divided by the square root of key width, followed by masking, softmax and value mixing.

Causal mask. A restriction preventing a query from attending to later positions under the declared position order.

Multi-head attention. Attention performed with multiple learned projection heads whose outputs are combined.

Positional encoding. A representation or transformation that makes token position available to the model.

Rotary position embedding (RoPE). Position-dependent pairwise rotations applied to query and key coordinates, making their dot product depend on relative position.

Residual connection. Adding a sublayer's result to a compatible input representation.

Layer normalization (LayerNorm). Normalizing features with their mean and variance along the declared feature axis, usually with a learned affine transform.

Root mean square normalization (RMSNorm). Rescaling features by their root mean square without subtracting the feature mean.

Feed-forward network (FFN). A position-wise feature transformation, commonly expanding width, applying a nonlinearity and projecting back.

GELU. An activation of the form x times the standard normal cumulative distribution at x, with common approximations.

SwiGLU. A gated FFN variant multiplying a Swish-activated projection by a separate value projection.

Decoder-only Transformer. A Transformer language model built from causal self-attention blocks without a separate encoder.

Weight tying. Using the same parameter storage for compatible input embeddings and output-vocabulary projections.

Key-value cache (KV cache). Stored past keys and values reused during incremental attention with unchanged prefix, weights and position conventions.

Prefill. Processing the prompt to produce initial hidden states and, when enabled, the initial KV cache.

Decode step. Processing newly appended positions using the existing generation state, commonly one token at a time.

PagedAttention. A serving technique that organizes KV-cache memory in blocks with mappings, distinct from merely retaining K/V tensors.

Optimization and execution

Learning rate. The step-size factor used in a parameter update; its effect also depends on the optimizer.

Adam. An adaptive optimizer using moving averages of gradients and squared gradients with bias correction.

AdamW. An Adam variant applying weight decay separately from the adaptive gradient term.

First and second moments. In Adam, estimates of the gradient mean and raw squared-gradient mean; the latter is not a second derivative.

Bias correction. Compensating for moving-average estimates initialized at zero during early updates.

Fan-in. The number of input features feeding one output coordinate, used when choosing initialization scale.

Warmup. An initial phase that increases learning rate according to a specified schedule.

Cosine decay. A learning-rate decrease following a cosine-shaped curve over a declared interval.

Gradient clipping. Limiting a declared gradient magnitude, such as the global norm, before an optimizer update.

Gradient accumulation. Combining gradient contributions across microbatches before one optimizer step, with consistent weighting.

Checkpoint. A saved state whose contents determine whether it supports inference only or complete training continuation.

Mixed precision. Using different numerical formats for selected computations or states, with explicit stability controls.

FP16 and BF16. Two 16-bit floating-point formats with different exponent and precision ranges; their stability needs can differ.

Loss scaling. Scaling a loss before backward and undoing the scale on gradients to help manage limited numerical range.

FlashAttention. An IO-aware exact-attention algorithm designed to reduce memory traffic through tiled computation.

Distributed data parallelism (DDP). Replicating model computation across workers processing different data and synchronizing gradients.

ZeRO. A family of distributed techniques partitioning optimizer states, gradients or parameters to reduce replicated memory.

Data, evaluation and alignment

Document-level split. Assigning complete documents to partitions before producing model examples to control overlap.

Deduplication. Removing repeated records under an explicitly defined matching rule; exact matching does not detect every semantic duplicate.

Target mask. An indicator or weight specifying which prediction positions contribute to the objective.

Perplexity. The exponential of mean token negative log-likelihood in natural-log units under the declared scoring protocol.

Bits per byte (BPB). Observed negative log-likelihood converted to bits and divided by the declared number of source bytes.

Supervised fine-tuning (SFT). Further training on supplied target responses using a supervised objective and specified target masks.

Direct preference optimization (DPO). A preference-learning objective comparing chosen and rejected responses relative to a reference policy.

Proximal policy optimization (PPO). A policy-optimization method with a commonly used clipped probability-ratio surrogate; the surrogate alone is not a full trainer.

Reference policy. A fixed comparison policy used by a declared alignment objective.

Scaling law. An empirical relationship between performance and quantities such as parameters, data or compute, valid only within justified scope.

Ablation. A controlled comparison changing a selected component while accounting for the other relevant conditions.

Bootstrap. Estimating sampling variability by repeatedly resampling observed units under a stated sampling design.

Confidence interval. An interval produced by a procedure with a stated repeated-sampling coverage target under its assumptions.

Provenance. The recorded origin and transformation history of code, data, configurations and results.

SHA-256 checksum. A 256-bit cryptographic digest used to check byte identity, not truth, licensing or model competence.

Appendix B Companion exercises

The reader edition assembles the shared lesson manuscripts, not a separate abridgment. Its 71 sections cover ten chapters and 70 companion exercises. Section 03.04 develops the chain rule conceptually without adding a separate assignment. The chapter/section filenames are stable so a printed section can be matched to the code.

Chapter	Sections	Companion exercises	Main subject
01	1	1	Text representation
02	7	7	Byte-pair encoding
03	24	23	Parameters and a learning baseline
04	10	10	Causal Transformer
05	7	7	Modern components and recovery
06	6	6	Corpus and pretraining
07	4	4	Evaluation and inference
08	4	4	Conversation and preference objectives
09	5	5	Efficient and distributed execution
10	3	3	Experiment design

Each assignment contains a function contract, a marked implementation region and a supplied check driver. Read the inputs and expected outputs, calculate the small example, then fill the marked region. The driver checks the cases listed in that section; use additional examples to investigate a different shape, boundary or numerical regime.

The larger laboratories connect the functions to data preparation, model training and evaluation. Keep a record of the code revision, data and tokenizer identities, configuration, budget and scoring protocol for each run. Compare experiments under a matching evaluation protocol.

The companion code provides marked exercises for you to implement. Use the book version and section number when reporting a correction, together with a small example that reproduces the issue.

For the code, begin with the repository README and the numbered file named in the section. Keep the code revision associated with the book, use the declared software baseline, and read an unfinished-prerequisite message as an assignment dependency rather than a package-installation error.

References

Author–year citations and reference IDs in each Method sources paragraph resolve to the entries below. Links lead to primary papers, standards or versioned official documentation. Publication years and first-preprint years are distinguished when they differ; software documentation is identified by version. The book's small examples and figures are original teaching material, not reproduced paper experiments.

R01. The Unicode Consortium (2024). The Unicode Standard, Version 16.0.0. Unicode Standard.

R02. Yergeau, F. (2003). UTF-8, a transformation format of ISO 10646. RFC 3629.

R03. Sennrich, R., Haddow, B., and Birch, A. (2016). Neural Machine Translation of Rare Words with Subword Units. ACL 2016; arXiv:1508.07909. First preprint: 2015.

R04. Vaswani, A., et al. (2017). Attention Is All You Need. NeurIPS 2017; arXiv:1706.03762.

R05. Ba, J. L., Kiros, J. R., and Hinton, G. E. (2016). Layer Normalization. arXiv:1607.06450.

R06. Zhang, B., and Sennrich, R. (2019). Root Mean Square Layer Normalization. NeurIPS 2019; arXiv:1910.07467.

R07. Su, J., et al. (2021). RoFormer: Enhanced Transformer with Rotary Position Embedding. arXiv:2104.09864. First preprint: 2021; revised v5 (2023) consulted, Sections 3.2 and 3.4.2.

R08. Shazeer, N. (2020). GLU Variants Improve Transformer. arXiv:2002.05202.

R09. Kingma, D. P., and Ba, J. (2015). Adam: A Method for Stochastic Optimization. ICLR 2015; arXiv:1412.6980. First preprint: 2014.

R10. Loshchilov, I., and Hutter, F. (2019). Decoupled Weight Decay Regularization. ICLR 2019; arXiv:1711.05101. First preprint: 2017.

R11. Hoffmann, J., et al. (2022). Training Compute-Optimal Large Language Models. NeurIPS 2022; arXiv:2203.15556.

R12. Rafailov, R., et al. (2023). Direct Preference Optimization: Your Language Model is Secretly a Reward Model. NeurIPS 2023; arXiv:2305.18290.

R13. Schulman, J., et al. (2017). Proximal Policy Optimization Algorithms. arXiv:1707.06347.

R14. Micikevicius, P., et al. (2018). Mixed Precision Training. ICLR 2018; arXiv:1710.03740. First preprint: 2017.

R15. Dao, T., et al. (2022). FlashAttention: Fast and Memory-Efficient Exact Attention with IO-Awareness. NeurIPS 2022; arXiv:2205.14135.

R16. PyTorch contributors (version 2.0). Autograd mechanics. Official software documentation.

R17. PyTorch contributors (version 2.0). Automatic mixed precision examples. Official software documentation.

R18. PyTorch contributors (version 2.0). Distributed Data Parallel. Official design note. The note describes the v1.4 design; it is not a guarantee about later backends.

R19. Shazeer, N. (2019). Fast Transformer Decoding: One Write-Head is All You Need. arXiv:1911.02150v1. Section 2.4 describes ordinary incremental multi-head attention with retained K/V. Section 3 proposes the distinct multi-query variant.

R20. Kwon, W., et al. (2023). Efficient Memory Management for Large Language Model Serving with PagedAttention. SOSP 2023; arXiv:2309.06180.

R21. Xiong, R., et al. (2020). On Layer Normalization in the Transformer Architecture. ICML 2020; PMLR 119:10524–10533.

R22. Hendrycks, D., and Gimpel, K. (2016). Gaussian Error Linear Units (GELUs). arXiv:1606.08415.

R23. He, K., Zhang, X., Ren, S., and Sun, J. (2016). Deep Residual Learning for Image Recognition. CVPR 2016; arXiv:1512.03385. First preprint: 2015.

R24. Bengio, Y., Ducharme, R., Vincent, P., and Jauvin, C. (2003). A Neural Probabilistic Language Model. JMLR 3:1137–1155.

R25. Radford, A., et al. (2019). Language Models are Unsupervised Multitask Learners. OpenAI technical report.

R26. Press, O., and Wolf, L. (2017). Using the Output Embedding to Improve Language Models. EACL 2017, short papers:157–163.

R27. Loshchilov, I., and Hutter, F. (2017). SGDR: Stochastic Gradient Descent with Warm Restarts. ICLR 2017; arXiv:1608.03983. First preprint: 2016.

R28. Pascanu, R., Mikolov, T., and Bengio, Y. (2013). On the difficulty of training recurrent neural networks. ICML 2013; PMLR 28(3):1310–1318.

R29. Kazemnejad, A., et al. (2023). The Impact of Positional Encoding on Length Generalization in Transformers. NeurIPS 2023; arXiv:2305.19466.

R30. Magnusson, I., et al. (2024). Paloma: A Benchmark for Evaluating Language Model Fit. NeurIPS 2024; arXiv:2312.10523. First preprint: 2023.

R31. Phan, B., et al. (2024). Exact Byte-Level Probabilities from Tokenized Language Models for FIM-Tasks and Model Ensembles. arXiv:2410.09303. First preprint: 2024; revised v2 (2025) consulted.

R32. Ouyang, L., et al. (2022). Training language models to follow instructions with human feedback. NeurIPS 2022; arXiv:2203.02155.

R33. Li, S., et al. (2020). PyTorch Distributed: Experiences on Accelerating Data Parallel Training. VLDB 2020; arXiv:2006.15704.

R34. Rajbhandari, S., Rasley, J., Ruwase, O., and He, Y. (2020). ZeRO: Memory Optimizations Toward Training Trillion Parameter Models. SC 2020; arXiv:1910.02054v3. First preprint: 2019. The revised v3 is cited, not the withdrawn v1.

R35. Kaplan, J., et al. (2020). Scaling Laws for Neural Language Models. arXiv:2001.08361.

R36. Efron, B. (1979). Bootstrap Methods: Another Look at the Jackknife. The Annals of Statistics 7(1):1–26; DOI:10.1214/aos/1176344552.

R37. Hugging Face (version 4.57.1). Caching. Transformers official documentation.

R38. Glorot, X., and Bengio, Y. (2010). Understanding the difficulty of training deep feedforward neural networks. AISTATS 2010; PMLR 9:249–256.

R39. Rumelhart, D. E., Hinton, G. E., and Williams, R. J. (1986). Learning representations by back-propagating errors. Nature 323:533–536; DOI:10.1038/323533a0.

R40. Mitchell, M., et al. (2019). Model Cards for Model Reporting. FAT* 2019; arXiv:1810.03993. First preprint: 2018.

R41. National Institute of Standards and Technology (2015). Secure Hash Standard (SHS). FIPS PUB 180-4, August 2015; DOI:10.6028/NIST.FIPS.180-4.

Edition and production

Author: Wanglong Lu (卢望龙).

The chapter numbers match the companion exercise files. The appendix lists the assignments and explains how to use their supplied checks. Each edition includes a source manifest identifying its chapter text, illustration assets and code revision.

Illustrations are prepared with reproducible vector drawing and numerical plotting. PNG files support ordinary reading; SVG sources preserve the diagrams for print and revision. Third-party assets retain their respective licenses.

AI tools assisted with drafting, revision, bilingual translation and language polishing.