

Get ready for rapid development. LooUQ's Circuit River LTE^m1 modem enables rapid IoT device design, development and deployment due to the LTE^m1's network carrier compatibility and approvals. Your device is ready when you are, requiring no additional network certification testing. LooUQ has done the work to enable your project to reach market opportunities as they appear. The LTE^m1 offers everything you need for remote sensing and control applications: small size, low power, easy host connectivity and cloud platform compatibility.

Features


- Approved on the Verizon and T-Mobile networks
- Tested with Hologram and other MVNOs
- Integrated GNSS receiver (standalone and assisted)
- Small size, 48mm x 40mm x 8mm
- Low-power, battery centric design
- SPI host interface
- USB for AT commands, firmware updates and diagnostics
- FOTA, Firmware-Over-the-Air upgrade support
- TCP/IP functionality support TCP/UDP/SSL/HTTP/MQTT
- SSL/TLS support for TCP/HTTP/MQTT
- File system available for application storage
- Powered by the industry recognized Quectel BG96 module
- Cross-industry applicability
- For anywhere, anytime communications

Benefits

- Works seamlessly with popular IoT development boards
- Open-sourced C99 driver supports rich abstraction for TCP/IP
- Secure communications with industry standard encryption
- Field serviceable OTA updates
- Fully integrated with LooUQ Cloud
- Easily integrates with major cloud platforms

Part Number: **CR-LTE^m1**





Contact LooUQ's Product Team
231/237-8860

Find Us Online
www.LooUQ.com

More Information
answers.LooUQ.com

Specifications

Physical

- 45mm x 40mm x 9.15mm board
- 48mm x 40mm overall with host connector.
- Detailed dimension information is available in the LooUQ Answers Center (answers.LooUQ.com)

Power

- Supply voltage 3.7-volts nominal (3.4v min, 4.3v max)
- Consumption @ LTE Cat M1 (typical)
 - Power Saving Mode: 10uA
 - LTE Connected Mode (average)
 - 124mA @ 0dBm
 - 130mA @ 10dBm
 - 190mA @ 23dBm

Communications

- LTE CAT-M1 and NB-IOT
- 300 Kbps (uplink) 375 Kbps (downlink)
- SPI host interface for efficient communications
- USB interface for AT, updates, NMEA sentences and diagnostics
- U.FL antenna connections
 - Main: cellular 700MHz, LTE Band 13
 - GNSS: passive or active (3v - 5v)
- UART output of GNSS NMEA sentences

Approvals

- Quectel BG-96 module FCC approved
- Verizon OD certified
- T-Mobile Registered

Support

LTEM1 support is available 7x24 via our online LooUQ Answers Center. Priority support is optionally available. LooUQ also offers data plans and LooUQ Cloud platform integrated service plans. Please contact us for more information.

<https://github.com/LooUQ/CircuitRiver-LTE1c>