SAPIENZA
UNIVERSITÀ DI ROMA
DIPARTIMENTO DI INGEGNERIA INFORMATICA
AUTOMATICA E GESTIONALE ANTONIO RUBERTI

Master in Artificial Intelligence and Robotics

Data-driven identification of a one-link robot with flexible joint

Lagrangian Neural Network applied to elastic robots

Course: Robotics 2

Professor: Alessandro De Luca

Tutor: Pietro Pustina

Students: Lorenzo Cirillo 1895955, Claudio Schiavella 1884561

INTRODUCTION

- Robot dynamic model
  - Relationship between applied forces and motion
  - D'Alembert, Hamilton,
- Euler-Lagrange equations
  - Modeling and control
  - Symbolic form equations of motions
- Modeling systems → Neural networks → Lagrangian NN



PARAMETRIC LAGRANGIAN

Lagrangian

$$L(q, \dot{q}) = T(q, \dot{q}) - U(q)$$

- Kinetic $T(q, \dot{q})$ and potential $U(q)$ energy
- Generalized coordinates $q \in \mathbb{R}^N$
  - N = robot DOF

Euler-Lagrange equations

$$\frac{d}{dt}\frac{\partial L}{\partial \dot{q}_i} - \frac{\partial L}{\partial q_i} = u_i \qquad i = 1, \dots, N$$

- Non-conservative forces u_i
  - Considered null in our application

PARAMETRIC LAGRANGIAN

Parametric Lagrangian

$$\ddot{q} = \left(\nabla_{\dot{q}} \nabla_{\dot{q}}^{T} L\right)^{-1} [\nabla_q L - (\nabla_q \nabla_{\dot{q}}^{T} L)\dot{q}]$$

- Lagrangian analytical expression not always known
- Alternative approach
  - Automatic differentiation

RIGID ROBOT

1R robot with y-axis agreeing with gravity

Model: $$(I + md^2)\ddot{q} + mg_0 d \sin(q) = 0$$

Acceleration: $$\ddot{q} = -\frac{1}{I + md^2} mg_0 d \sin(q)$$

- Coriolis and Centrifugal term not present
  - One single link
  - Contribute to the joint when it is moving is null

ELASTIC ROBOT

1R robot with y-axis agreeing with gravity

Model:

$$\begin{cases} (I + md^2)\ddot{q} + mg_0 d \sin(q) + k(q - \theta) = 0 \\ I_m \ddot{\theta} + k(\theta - q) = 0 \end{cases}$$

Accelerations:

$$\begin{cases} \ddot{q} = -\dfrac{1}{I + md^2}\left[mg_0 d \sin(q) + k(q - \theta)\right] \\ \ddot{\theta} = \dfrac{1}{I_m} k(q - \theta) \end{cases}$$

- Again Coriolis and Centrifugal term not present
  - Constant inertia matrix

BASELINE NN



- Classic feedforward neural network
  - Only fully connected layers
- Learn $\ddot{q}$ directly from $\dot{q}$ and q
  - Not considering Lagrangian and relative constraints
- Function of a comparison baseline
  - Same structure of Lagrangian NN to comparison reasons

LAGRANGIAN NN



- Same baseline structure, completely different approach
  - Very close to robot nature
- Learn Lagrangian
  - Functional programming context
  - Predictions benefit of the Lagrangian approach features
- $\ddot{q}$ obtained from parametric Lagrangian

SIMULATIONS

- **Type 1:** Observe behavior of the two networks
  - Trajectory tracking
  - Trajectory error
  - Energy conservation
- **Type 2:** Introduce noise
  - Same tests as in type 1
  - Highlight network robustness in not ideal context

SAPIENZA
UNIVERSITÀ DI ROMA

RIGID CASE

Robot parameters

Parameter	Measure
Length	$0.30\ [m]$
Base radius	$0.01\ [m]$
CoM distance	$0.15\ [m]$
Mass	$0.25\ [kg]$
Inertia	$0.01125\ [kg\ m^2]$

Network setup

Characteristic	Value
Layers	4
Neurons	500
Activation	Softplus
Loss	MSE
Regularization	L2 penalty
Train epochs	10 000

SAPIENZA
UNIVERSITÀ DI ROMA

RIGID CASE – NETWORK TRAINING

Train and test losses





SAPIENZA
UNIVERSITÀ DI ROMA

RIGID CASE – SIMULATION 1

Initial conditions:

$$q(0) = 1{,}33\, rad \quad \dot{q}(0) = 0{,}2\, \frac{rad}{s}$$



SAPIENZA
UNIVERSITÀ DI ROMA

RIGID CASE – SIMULATION 1





SAPIENZA
UNIVERSITÀ DI ROMA

RIGID CASE – SIMULATION 2

Initial conditions:

$$q(0) = 0\,rad \quad \dot{q}(0) = 4\frac{rad}{s}$$



SAPIENZA
UNIVERSITÀ DI ROMA

RIGID CASE – SIMULATION 2

Free evolution with noise







Free evolution without noise







RIGID CASE – SIMULATION 3

Initial conditions:

$$q(0) = 2{,}66\, rad \quad \dot{q}(0) = 0{,}5\, \frac{rad}{s}$$



SAPIENZA
UNIVERSITÀ DI ROMA

RIGID CASE – SIMULATION 3





RIGID CASE

Motor parameters

Parameter	Measure
Height	$0.04\ [m]$
Base radius	$0.02\ [m]$
Mass	$0.4\ [kg]$
Reduction ratio	160
Inertia	$0.0128\ [kg\ m^2]$
Stiffness constant	$50\ [Nm/rad]$

Network setup

Configuration	Units	Layers
A	300	2
B	500	4
C	700	5

SAPIENZA
UNIVERSITÀ DI ROMA

ELASTIC CASE

Robot parameters

Parameter	Measure
Length	$0.30\ [m]$
Base radius	$0.01\ [m]$
CoM distance	$0.15\ [m]$
Mass	$0.25\ [kg]$
Inertia	$0.01125\ [kg\ m^2]$

Network setup

Characteristic	Value
Layers	4
Neurons	500
Activation	Softplus
Loss	MSE
Regularization	L2 penalty
Train epochs	10 000

SAPIENZA
UNIVERSITÀ DI ROMA

ELASTIC CASE – CONFIGURATION A

Train and test losses





SAPIENZA
UNIVERSITÀ DI ROMA

ELASTIC CASE – SIMULATION 1

Initial conditions:

$$\begin{cases} q(0) = 2{,}66\, rad \quad \dot{q}(0) = 0{,}5 \dfrac{rad}{s} \\ \theta(0) = 3{,}06\, rad \quad \dot{\theta}(0) = 1 \dfrac{rad}{s} \end{cases}$$



SAPIENZA
UNIVERSITÀ DI ROMA

ELASTIC CASE – SIMULATION 1

Free evolution without noise











Free evolution with noise











ELASTIC CASE – SIMULATION 2

Initial conditions:

$$\begin{cases} q(0) = 1{,}33\, rad \quad \dot{q}(0) = 1\,\dfrac{rad}{s} \\ \theta(0) = 1{,}51\, rad \quad \dot{\theta}(0) = 0{,}5\,\dfrac{rad}{s} \end{cases}$$



SAPIENZA
UNIVERSITÀ DI ROMA

ELASTIC CASE – SIMULATION 2

Free evolution without noise



Free evolution with noise



ELASTIC CASE – CONFIGURATION B

Train and test losses





SAPIENZA
UNIVERSITÀ DI ROMA

ELASTIC CASE – SIMULATION 3

Free evolution without noise











Free evolution with noise











SAPIENZA
UNIVERSITÀ DI ROMA

ELASTIC CASE – SIMULATION 4

Free evolution without noise











Free evolution with noise











ELASTIC CASE – CONFIGURATION C

Train and test losses





SAPIENZA
UNIVERSITÀ DI ROMA

ELASTIC CASE – SIMULATION 5

Free evolution without noise



Free evolution with noise



SAPIENZA
UNIVERSITÀ DI ROMA

ELASTIC CASE – SIMULATION 6

Free evolution without noise











Free evolution with noise











SAPIENZA
UNIVERSITÀ DI ROMA

CONCLUSIONS

- At least in the rigid case, LNN performances are very good
  - Both in trajectory error and energy conservation
- Unfortunately, bad results in elastic case
- Elastic LNN seems to improve as network complexity increase
  - More wide/deep network and more initial conditions
  - High computational resources needed
- Paper LNN approach works on unitary configurations
  - We reject this in preference to real robot parameters

SAPIENZA
UNIVERSITÀ DI ROMA

THANK YOU