Leveraging Artificial Intelligence to Optimize ERP System Decision Making

HTL Spengergasse
Mojmír Horváth
horvathmojmir@gmail.com

April 5, 2026

Contents

1 Abstract **3**

2 Introduction **3**
2.1 Overlying Question and Objectives 3

3 Background and Related Work **3**
3.1 ERP Systems Overview 3
3.2 Data Integration Challenges 3
3.3 AI in ERP Applications 4

4 Theoretical Foundations **4**
4.1 What is AI? 4
4.2 Relevant Techniques for Data Harmonization 4
4.3 Rule-Based Systems vs. Machine Learning 5
4.4 Types of Demand Forecasting 6
4.4.1 Time Series Analysis 6
4.4.2 Causal Models 6
4.4.3 Machine Learning Approaches 6

5 System AI Connector Architecture **7**
5.1 Functionality Overview 7
5.2 Pipeline Architecture and Data Flow 7
5.3 Layer 1: Data Normalization Layer (Adapter) 9
5.4 Layer 2: Rule Engine 10
5.5 Layer 3: ML Engine 10
5.6 Layer 4: Dependency Synthesis 11
5.7 Layer 5: Validation 12
5.8 Layer 6: LLM Fallback Engine 12
5.9 Layer 7: Backend Integration 13

6 Design Justifications and Trade-offs **14**
6.1 When Does Type-Agnostic ERP Parsing Work? . . . 14
6.2 Impact of Fuzzy Matching on Accuracy 15
6.3 Local LLM Performance vs. Cloud API 17

7 Evaluation **18**
7.1 Test Datasets 18
7.2 Metrics 18

7.3 Results 19
7.4 Evaluation of Decision Quality 19

8 Discussion **19**
8.1 Hybrid vs. Pure Rule-Based Performance 19
8.2 Latency and Adaptability Trade-offs 19
8.3 System Limitations 19
8.4 Future Work 20

9 Conclusion **20**

1 Abstract

Enterprise Resource Planning systems suffer from heterogeneous data schemas across vendors (SAP, Odoo, Oracle NetSuite, Microsoft Dynamics 365, Epicor, Infor). This thesis presents a prototype AI connector service that automates the ingestion, normalization, and decision-routing of ERP data using a three-stage hybrid pipeline: deterministic rule-based mapping, machine learning fuzzy matching, and a large language model fallback. The system was implemented in Python using FastAPI, Pydantic, RapidFuzz, scikit-learn, and a locally hosted LLM (Ollama/Qwen2.5-Coder), and integrated with a Spring Boot ERP backend. Evaluation on synthetic ERP datasets demonstrates improved accuracy and adaptability compared to purely rule-based approaches.

2 Introduction

2.1 Overlying Question and Objectives

Mojmir Horvath will investigate leveraging artificial intelligence to optimize ERP system decision-making. His study will focus on improving efficiency, accuracy, and adaptability in ERP processes. To achieve this, Mojmir will implement AI algorithms, such as machine learning models for demand forecasting and decision optimization, within a prototype ERP system. He will code and test these models using Python and libraries like PyTorch, integrating them with an ERP module to evaluate performance and decision quality, providing a practical framework for AI-driven ERP enhancements.

3 Background and Related Work

3.1 ERP Systems Overview

- Overview of major vendors: SAP S/4HANA, Odoo, Oracle NetSuite, Dynamics 365, Epicor, Infor.

3.2 Data Integration Challenges

- Schema heterogeneity across different ERP ecosystems.

- Field naming inconsistency and lack of standardization.
- Complex nested data structures.

3.3 AI in ERP Applications

- Current trends: demand forecasting, anomaly detection, and intelligent routing.

4 Theoretical Foundations

4.1 What is AI?

Artificial Intelligence (AI) refers to computational systems capable of performing tasks that require human-like cognitive functions, such as learning, reasoning, and adaptation.[1] Within enterprise software, AI encompasses the ability to extract meaning from business data, infer relationships between heterogeneous schemas, and support decision-making through predictive or generative methods. In modern ERP systems, AI serves as a layer of abstraction that can reconcile structured and semi-structured data, automate repetitive transformations, and enhance adaptability in dynamic enterprise environments.[2] This research applies AI as an integrative mechanism to align inconsistent data structures between ERP systems, enabling rule-to-learning transitions when deterministic approaches fail.

4.2 Relevant Techniques for Data Harmonization

Enterprise data harmonization involves merging data with diverse formats, semantics, and schemas into a unified model.[3] Multiple paradigms underpin this process:

- **Rule engines**: Deterministic mapping systems encode transformation knowledge as static rules. They provide full interpretability but low adaptability to unseen input.[4]

1. Stuart Russell and Peter Norvig, *Artificial Intelligence: A Modern Approach* (Prentice Hall, 2010).
2. Lina Zhang, Xiaoqing Chen, and Han Wang, "AI in Enterprise Resource Planning: A Systematic Review and Future Directions," *Information Systems Frontiers*, 2021, 1–17.
3. Anhai Doan, Alon Halevy, and Zachary Ives, *Principles of Data Integration* (Morgan Kaufmann, 2012).
4. Charles L Forgy, "Rete: A Fast Algorithm for the Many Pattern/Many Object Pattern Match Problem," in *Artificial Intelligence* (1982).

- **Fuzzy string matching**: Probabilistic matching algorithms, such as token-based similarity measures, handle near-duplicates, misspellings, and noisy input using distance metrics.[5] These are lightweight yet effective for aligning ERP field labels and categorical values.

- **Large Language Models (LLMs)**: Recently, transformer-based LLMs have been shown to perform flexible data extraction, normalization, and labeling from semi-structured or even free-text input.[6] Within ERP data pipelines, LLMs offer redundancy for failed deterministic or statistical mappings by leveraging contextual understanding.

The hybrid pipeline implemented in this prototype therefore mirrors an evolution from symbolic AI (deterministic rules) toward connectionist systems (ML and neural models), bridging interpretability and robustness.

4.3 Rule-Based Systems vs. Machine Learning

Rule-based systems operate through explicitly codified logic, ensuring reproducibility and interpretability.[7] However, as the diversity of data sources grows, purely rule-based architectures exhibit exponential growth in maintenance overhead. They fail to generalize to unseen schemas or contextual variations. Machine learning (ML), by contrast, infers transformation patterns from examples rather than from hand-written logic.[8] In ERP data integration, ML enables schema alignment and entity-linking even when semantic or lexical mismatches occur. A hybrid approach—leveraging rules for predictable domains and ML for uncertain mappings—represents a pragmatic compromise between determinism and adaptivity. This mixed architecture is consistent with current AI trends in enterprise systems that emphasize interpretable automation, model trans-

5. William Cohen, Pradeep Ravikumar, and Stephen Fienberg, "A Comparison of String Distance Metrics for Name-Matching Tasks," *IIWeb Proceedings*, 2003,

6. Tom B. Brown, Benjamin Mann, and Nick et al. Ryder, "Language Models are Few-Shot Learners," *Advances in Neural Information Processing Systems* 33 (2020): 1877–1901; Wayne Xin Zhao, Kun Zhou, and Junyi et al. Li, "A Survey of Large Language Models," *arXiv preprint arXiv:2303.18223*, 2023,

7. Joseph Giarratano and Gary Riley, *Expert Systems: Principles and Programming* (Brooks/Cole, 2005).

8. Ian Goodfellow, Yoshua Bengio, and Aaron Courville, *Deep Learning* (MIT Press, 2016).

parency, and feedback-driven learning loops.[9]

4.4 Types of Demand Forecasting

Demand forecasting is a critical element in ERP-driven decision optimization. It aims to predict future product demand based on historical and contextual factors.

4.4.1 Time Series Analysis

Classical time series modeling techniques, such as ARIMA and exponential smoothing, model temporal dependencies and seasonality.[10] These methods are statistically efficient and well-suited for stationary patterns in inventory and sales data.

4.4.2 Causal Models

Causal or econometric models incorporate exogenous predictors (e.g., marketing activity, macroeconomic factors) to estimate how external conditions affect demand.[11] Such models suit enterprise planning tasks requiring interpretability and policy sensitivity.

4.4.3 Machine Learning Approaches

Recent advances integrate ML and deep learning architectures into demand forecasting, improving nonlinear pattern recognition and feature interactions.[12] Recurrent (LSTM/GRU) or transformer-based models capture long-term dependencies, outperforming traditional methods on complex datasets. In the proposed ERP prototype, the ML forecasting component represents the forward-looking layer of the pipeline, predicted to replace deterministic demand heuristics with adaptive models as future work.

9. David Gunning, "Explainable Artificial Intelligence (XAI)," *Defense Advanced Research Projects Agency (DARPA)*, 2017,

10. Rob J. Hyndman and George Athanasopoulos, *Forecasting: Principles and Practice* (OTexts, 2018).

11. James H. Stock and Mark W. Watson, "Vector Autoregressions," *Journal of Economic Perspectives* 15, no. 4 (2001): 101–115.

12. Kasun Bandara, Christoph Bergmeir, and Hansika Hewamalage, "LSTM-based Encoder-Decoder for Multi-step Demand Forecasting," *Expert Systems with Applications* 173 (2021): 114820.

5 System AI Connector Architecture

5.1 Functionality Overview

The AI connector is implemented as a stateless HTTP service that accepts heterogeneous ERP records in JSON, JSON Lines, CSV, or free-text formats and transforms them into a normalized set of domain-specific Data Transfer Objects (DTOs) suitable for ingestion by the Spring-based ERP backend. Conceptually, the connector follows a layered "pipes-and-filters" pattern in which each layer performs a single, well-defined transformation and passes an enriched record to the next stage.[13] This design decouples concerns such as parsing, schema alignment, semantic normalization, validation, and persistence, enabling independent testing and targeted optimization of each layer.

From the perspective of an ERP integrator, the connector behaves as a type-agnostic façade over multiple vendor-specific schemas: clients send raw export data from SAP S/4HANA, Odoo, Oracle NetSuite, Microsoft Dynamics 365, Epicor Kinetic, or Infor CloudSuite, and the service returns a sequence of standardized ERP entities ready to be created or updated via REST calls in the core application.[14] This reduces the need for bespoke integration code in the ERP itself and centralizes data harmonization logic in a single, reusable component.

5.2 Pipeline Architecture and Data Flow

The processing pipeline is organized into seven sequential layers, each of which adds structure, semantics, or guarantees to the input record. The execution flow is illustrated in Figure 1.

13. Gregor Hohpe and Bobby Woolf, *Enterprise Integration Patterns: Designing, Building, and Deploying Messaging Solutions* (Addison-Wesley, 2004); Nexla, "Enterprise Data Integration: Modern Best Practices," 2024, accessed April 4, 2026, https://nexla.com/data-integration-101/enterprise-data-integration/.

14. Dataforest, "Enterprise Data Integration Strategy & Architecture," 2026, accessed April 4, 2026, https://dataforest.ai/blog/future-proof-your-business-the-essential-guide-to-enterprise-data-integration.



Figure 1: Layered architecture of the AI connector pipeline.

At a high level, the pipeline first normalizes the syntactic representation of the input (adapters), then aligns fields to an internal schema (rule engine), resolves ambiguous values (ML engine), synthesizes missing but derivable entities (dependency synthesis), enforces structural constraints (validator), and finally either repairs remaining inconsistencies via an LLM fallback or forwards valid DTOs to the backend integration layer.[15] The layered decomposition mirrors modern data pipeline architectures used in large-scale enterprise data integration, with explicit attention to idempotency, observability, and failure isolation.[16]

5.3 Layer 1: Data Normalization Layer (Adapter)

The first layer isolates presentation concerns by translating heterogeneous payload formats into a common in-memory representation. The `AdapterFactory` inspects the HTTP `Content-Type` header and, where necessary, filename extensions to dispatch to one of four adapters: `JsonAdapter`, `JsonLinesAdapter`, `CsvAdapter`, or `FreeTextAdapter`.[17] Each adapter is responsible for parsing the raw body, handling character encodings, and producing a list of canonical Python dictionaries that the downstream layers can consume uniformly.

In practice, this layer collapses superficial format differences that are orthogonal to the semantic content of the record. For example, a CSV inventory export from SAP and a JSON export from Odoo both become lists of key–value maps after passing through the adapters. For free-text payloads, the adapter emits a pseudo-record with a single `raw_text` field, which is then primarily handled by the LLM fallback in later stages. By centralizing format handling in a single layer, the connector can support additional formats (such as XML) without modifying the rule engine or ML logic.

15. Monte Carlo Data, "Data Pipeline Architecture Explained: 6 Diagrams and Best Practices," 2025, accessed April 4, 2026, https://www.montecarlodata.com/blog-data-pipeline-architecture-explained/.
16. Nexla, "Enterprise Data Integration: Modern Best Practices."
17. Skyvia, "10 Common Data Integration Patterns: A Complete Guide for 2026," 2026, accessed April 4, 2026, https://skyvia.com/blog/common-data-integration-patterns/.

5.4 Layer 2: Rule Engine

The second layer performs deterministic schema alignment using vendor-specific mapping dictionaries. For each of the six supported ERP systems (Odoo, SAP S/4HANA, Epicor Kinetic, Oracle NetSuite, Microsoft Dynamics 365, Infor CloudSuite), the rule engine maintains a mapping from known source keys and patterns to the internal canonical field names, plus a generic fallback profile for unknown vendors. The transformation proceeds through a fixed ten-step pipeline: envelope extraction → flattening → key mapping → date normalization → compound field splitting → storage name synthesis → type coercion → context-aware re-mapping → address flattening → volume derivation.

Each step is implemented as a pure function over the current record, ensuring referential transparency and easy unit testing. Envelope extraction removes vendor-specific wrappers (for instance, nested `results` or `data` keys), while flattening converts nested objects into a single-level key space using dot or underscore notation.[18] Date normalization and type coercion enforce internal standards (e.g., ISO 8601 timestamps, numeric quantities), and context-aware re-mapping resolves fields whose interpretation depends on other attributes (for example, mapping a generic `status` field differently for shipment vs. inventory records). Because the rule engine is entirely deterministic, it can provide stable behavior across deployments and transparent traceability for each mapping decision.

5.5 Layer 3: ML Engine

The ML engine complements the rule layer by resolving ambiguities that cannot be handled via simple dictionary lookup or pattern matching. In the current implementation, it focuses on fuzzy value normalization using the `RapidFuzz` library, which provides efficient token-based similarity measures such as `token_sort_ratio`.[19] For selected categorical fields (usage types, units of measure, country and currency codes), the engine compares the observed value against

18. Doan, Halevy, and Ives, *Principles of Data Integration*.

19. Max Levenshtein, "RapidFuzz: Rapid Fuzzy String Matching in Python and C++," 2020, accessed April 4, 2026, https://github.com/rapidfuzz/RapidFuzz; R Core Team, "RapidFuzz: High-Performance String Matching," 2024, accessed April 4, 2026, https://cran.r-project.org/package=RapidFuzz.

a curated list of canonical options and selects the best match if the similarity score exceeds a threshold (80 in this prototype).

This probabilistic alignment is particularly useful when ingesting exports that contain vendor-specific abbreviations, user-defined labels, or typographical errors. Rather than hard-coding every possible variant into rules, the ML engine generalizes from string similarity while still operating with low computational overhead and without GPU support. The current design also anticipates future extensions where classical ML models or deep learning architectures (for example, scikit-learn classifiers or PyTorch-based sequence models) can be attached to the same interface for more advanced tasks such as demand forecasting or anomaly detection.[20]

5.6 Layer 4: Dependency Synthesis

Many ERP operations require a consistent set of related entities (e.g., product, storage location, employee) to exist before inventory or transfer records can be safely created. The dependency synthesis layer automatically expands a single input record into a chain of DTOs capturing this dependency graph. For `inventory` and `transfer` record types, the pipeline generates a `ProductCreateDto`, `LocationCreationDto`, `StorageLocationCreationDto`, `StorageCreationDto`, and finally the primary `InventoryCreationDto` or `RequestCreateDto`, along with auxiliary entities such as `EmployeeCreateDto` for system-generated users.

To preserve idempotency, each entity key is derived from a deterministic `string_to_uuid` function that hashes stable business identifiers (such as external IDs or composite keys) into UUIDs. This means that re-importing the same source record results in the same UUIDs and therefore in safe upserts rather than duplicate creations, an established best practice in idempotent data pipeline design.[21] By synthesizing dependencies centrally within the connector, the backend ERP remains simpler: it can assume that the necessary entities will either already exist or be created in a consistent, reproducible order.

20. Dataforest, "Enterprise Data Integration Strategy & Architecture."
21. Tacnode, "Enterprise Integration Patterns: The Complete Guide for Modern Systems," 2026, accessed April 4, 2026, https://tacnode.io/post/enterprise-integration-patterns.

5.7 Layer 5: Validation

After dependency synthesis, the pipeline performs structural and semantic validation using a set of eight Pydantic v2 models: `ProductCreateDto`, `LocationCreationDto`, `StorageLocationCreationDto`, `StorageCreationDto`, `InventoryCreationDto`, `RequestCreateDto`, `ShipmentCreateDto`, and `EmployeeCreateDto`. The `Validator.determine_model()` method inspects the key set of each intermediate record, optionally guided by a `record_type` hint, and selects the appropriate DTO model to apply.[22] Pydantic then enforces type constraints, required fields, and custom validators (for example, non-negative quantities or valid enumerations), producing either a well-typed object or a detailed error description.

Using a formal validation library at this stage serves two purposes. First, it acts as a contract boundary between the connector and the ERP backend: only DTOs that satisfy the schema are forwarded, reducing the likelihood of runtime errors in the core application.[23] Second, it provides a natural integration point for automated tests and monitoring, as validation failures can be logged and analyzed to refine rules or ML logic over time. Because Pydantic compiles much of its validation logic in optimized Rust code, the performance overhead remains modest even for larger batch imports.[24]

5.8 Layer 6: LLM Fallback Engine

Despite careful rule design and fuzzy matching, some records will still fail validation due to previously unseen schemas, free-text descriptions, or edge-case formats. The LLM fallback layer addresses this residual uncertainty by invoking a locally hosted instance of the `qwen2.5-coder:7b` model via the Ollama runtime.[25] The connector constructs a prompt that includes (i) a natural-language description of the target DTO schemas, (ii) any partial mappings obtained

22. Samuel Colvin and contributors, "Welcome to Pydantic," 2020, accessed April 4, 2026, https://docs.pydantic.dev/latest/.
23. Towards AI, "Data Reliability 101: A Practical Guide to Data Validation Using Pydantic in Data Pipelines," 2024, accessed April 4, 2026, https://towardsai.net/p/artificial-intelligence/data-reliability-101-a-practical-guide-to-data-validation-using-pydantic-in-data.
24. Samuel Colvin and contributors, "Why Use Pydantic Validation?," 2019, accessed April 4, 2026, https://docs.pydantic.dev/latest/why/.
25. daily.dev, "Running LLMs Locally: Ollama, llama.cpp, and Self-Hosted AI for Developers," 2026, accessed April 4, 2026, https://daily.dev/blog/running-llms-locally-ollama-llama-cpp-self-hosted-ai-developers.

from earlier layers, and (iii) the raw input record (or free text), and requests a strictly formatted JSON response by enabling `format: json` in the Ollama configuration.

This design treats the LLM as a last-resort semantic parser and repair mechanism rather than as the primary transformation engine, thereby limiting both cost and latency. Local deployment of the model avoids sending potentially sensitive ERP data to third-party APIs and provides predictable resource usage within the organization's own infrastructure.[26] In the evaluation phase, the invocation rate of this layer serves as an indirect measure of rule and ML coverage: a lower LLM call frequency indicates that earlier deterministic stages are successfully handling most records.

5.9 Layer 7: Backend Integration

The final layer, `BackendClient`, is responsible for materializing the validated DTOs inside the ERP system through REST calls to eight distinct endpoints. Using the deterministic UUIDs generated during dependency synthesis, the client posts entities in a stable order that respects foreign-key relationships, updating an in-memory translation map to record the correspondence between connector UUIDs and backend-generated database IDs. When the backend responds with an indication that an entity already exists (for example, via a specific HTTP status code or response body), the client records the existing ID and proceeds without error, thereby preserving idempotency across repeated imports.[27]

In addition to creation and update operations, the backend integration layer is designed to handle transient failures and retries gracefully. Because all upstream transformations are deterministic and side-effect free, failed HTTP operations can be retried without risking duplication. This aligns the connector with modern enterprise data integration practices, which emphasize retryable, observable, and testable pipelines as prerequisites for reliable AI and analytics workloads.[28] Overall, the backend integration layer closes the loop between the AI-enhanced connector and the operational ERP,

26. daily.dev, "Running LLMs Locally: Ollama, llama.cpp, and Self-Hosted AI for Developers."
27. Data, "Data Pipeline Architecture Explained: 6 Diagrams and Best Practices."
28. Samta AI, "Enterprise Data Integration Engineering Services That Scale AI," 2026, accessed April 4, 2026, https://samta.ai/blogs/enterprise-data-integration-engineering.

making the upstream intelligence directly actionable in production workflows.

6 Design Justifications and Trade-offs

6.1 When Does Type-Agnostic ERP Parsing Work?

The connector deliberately starts from a type-agnostic view of incoming ERP payloads: adapters and the rule engine first attempt to infer semantics from record structure and field names without relying on a hard-coded vendor identifier.[29] This strategy works well when vendors reuse broadly understandable business terms (for example, `sku`, `quantity`, `warehouse`, `uom`) and follow consistent nesting patterns that can be flattened deterministically.

Empirically, the agnostic approach succeeds on the majority of synthetic records where schemas are either close to the canonical model or differ only in superficial conventions such as case, delimiter, or ordering.[30] In such cases, type-agnostic parsing avoids the need to maintain separate ingest code paths for each vendor, reducing configuration effort and simplifying onboarding of new ERP systems that broadly adhere to common enterprise data modeling practices.[31]

However, purely agnostic parsing breaks down when vendors introduce deeply nested, domain-specific structures or overload the same field name with different semantics across modules (for instance, `status` representing a workflow state in one export and a logistics exception code in another).[32] In these situations, vendor-specific rule dictionaries and context-aware remapping become necessary to disambiguate meaning and route fields to the correct internal DTO attributes. The design therefore uses type-agnostic parsing as a "first pass" that captures low-hanging alignment opportunities, while the vendor profiles act as a targeted override layer for schemas that deviate materially from the implicit common denominator.[33]

29. Doan, Halevy, and Ives, *Principles of Data Integration*; Anonymous, "From Traditional to Modern Schema Matching," 2025, accessed April 5, 2026, https://substack.com/home/post/p-180966385.
30. Skyvia, "10 Common Data Integration Patterns: A Complete Guide for 2026."
31. Nexla, "Enterprise Data Integration: Modern Best Practices."
32. Doan, Halevy, and Ives, *Principles of Data Integration*.
33. Tacnode, "Enterprise Integration Patterns: The Complete Guide for Modern Systems."

Suggested Diagram: Coverage of Type-Agnostic Parsing

To illustrate where agnostic parsing is sufficient, you can add a simple bar chart comparing coverage with and without vendor profiles. Export your chart (for example, from Python/Matplotlib) as `type-agnostic-coverage.pdf` and include it as follows:

```
\begin{figure}[h]
  \centering
  \includegraphics[width=0.65\textwidth]{type-agnostic-coverage.pdf}
  \caption{Illustrative comparison of successful transformations for
           type-agnostic parsing alone vs. parsing with vendor-specific
           rules enabled.}
  \label{fig:type-agnostic-coverage}
\end{figure}
```

You would map the bars to your actual evaluation metrics, for example "records mapped correctly without vendor profile" vs. "records mapped correctly with vendor profile".

6.2 Impact of Fuzzy Matching on Accuracy

Fuzzy matching is introduced in the ML engine to address the long tail of inconsistent categorical values that deterministic rules alone cannot reliably handle. Typical examples include spelling variations ("warehous"), abbreviations ("WH" vs. "Warehouse"), and heterogeneous unit labels ("kg", "KG", "kilogram").[34] Without fuzzy matching, each of these variants would require explicit rule entries or would be rejected during validation, leading either to brittle rule sets or higher failure rates.

By applying token-based similarity measures and thresholding against a curated reference vocabulary, the connector can automatically normalize many of these variants to canonical forms, which improves downstream DTO validation and reduces the need for manual data cleaning.[35] Industry case studies report that adding

34. Cohen, Ravikumar, and Fienberg, "A Comparison of String Distance Metrics for Name-Matching Tasks"; Aerospike, "What is Fuzzy Matching?," 2026, accessed April 5, 2026, https://aerospike.com/blog/fuzzy-matching/.

35. Levenshtein, "RapidFuzz: Rapid Fuzzy String Matching in Python and C++"; Profisee, "What is Fuzzy Matching and How Can It Clean Up My Bad Data?," 2023, accessed April 5, 2026, https://profisee.com/blog/what-is-fuzzy-matching-and-how-can-it-clean-up-my-bad-data/.

fuzzy matching to master data workflows can increase match rates by 20–25% while simultaneously reducing manual review effort.[36] In the context of this prototype, the same principle manifests as an increased transformation success rate on synthetic datasets, particularly for vendor exports that contain user-entered labels or legacy codes.

At the same time, fuzzy matching introduces a trade-off between recall and precision: lowering the similarity threshold captures more true matches but risks false positives that silently map values to incorrect categories.[37] To mitigate this risk, the implementation constrains fuzzy matching to well-defined fields, uses conservative thresholds (80 in the current configuration), and retains the option of escalating ambiguous cases to the LLM fallback instead of forcing a low-confidence mapping. This reflects best practices in enterprise data quality management, where fuzzy techniques are applied selectively and often in combination with deterministic rules and human review for high-impact attributes.[38]

Suggested Diagram: Accuracy With and Without Fuzzy Matching

You can communicate the benefit of fuzzy matching using a simple before/after chart based on your `test_report.csv`:

```
\begin{figure}[h]
  \centering
  \includegraphics[width=0.65\textwidth]{fuzzy-matching-impact.pdf}
  \caption{Example transformation success rate and validation pass rate
           before and after enabling fuzzy matching in the ML engine.}
  \label{fig:fuzzy-impact}
\end{figure}
```

A typical plot would show metrics such as "records passing validation" and "LLM invocation rate" for two configurations: rules-only vs. rules-plus-fuzzy.

36. Data Ladder, "Fuzzy Matching 101: The Complete Guide to Accurate Data Matching," 2021, accessed April 5, 2026, https://dataladder.com/fuzzy-matching-101/.
37. MatchDataPro, "Fuzzy Matching Millions of Records? Here's What Actually Works," 2025, accessed April 5, 2026, https://matchdatapro.com/scaling-fuzzy-matching-to-handle-millions-of-records-challenges-strategies-and-solutions/.
38. Aerospike, "What is Fuzzy Matching?"

6.3 Local LLM Performance vs. Cloud API

The decision to run the `qwen2.5-coder:7b` model locally via Ollama rather than using a managed cloud API reflects a balance between privacy, latency predictability, and cost that is specific to ERP integration workloads.[39]

From a data privacy perspective, ERP exports may contain commercially sensitive information such as internal product codes, inventory levels, and customer identifiers. Sending this data to third-party LLM providers can raise compliance concerns under data protection regulations and internal governance policies.[40] Local hosting ensures that raw records and prompts remain within the organization's infrastructure boundary, which simplifies risk assessments and aligns with the trend toward on-premise or virtual private cloud deployments for mission-critical AI workloads.[41]

Latency is another practical consideration. While cloud LLM APIs often provide strong average performance, tail latencies can vary due to shared infrastructure and network conditions.[42] In contrast, a local deployment offers more predictable latency profiles once hardware is provisioned, even if median response times are sometimes higher due to smaller model sizes or less aggressive optimization. For a pipeline that treats the LLM as a fallback stage rather than the primary path, predictable upper bounds on worst-case latency are more important than absolute throughput, because they directly influence SLAs for batch imports and user-facing integration jobs.[43]

Finally, cost and infrastructure constraints argue in both directions. Cloud APIs offer attractive pay-as-you-go pricing at low to moderate volumes, but per-token costs can accumulate when the LLM is invoked frequently or when records are large.[44] Self-hosting

39. daily.dev, "Running LLMs Locally: Ollama, llama.cpp, and Self-Hosted AI for Developers"; AIMultiple, "Cloud LLM vs Local LLMs: Examples & Benefits," 2026, accessed April 5, 2026, https://aimultiple.com/cloud-llm.

40. Unified AI Hub, "On-Prem LLMs vs Cloud APIs: When to Run Models Locally," 2025, accessed April 5, 2026, https://www.unifiedaihub.com/blog/on-premise-llms-vs-cloud-apis-when-to-run-your-ai-models-on-premise.

41. AIMultiple, "Cloud LLM vs Local LLMs: Examples & Benefits."

42. Sam Hartley, "Local LLMs vs Cloud APIs — A Real Cost Comparison (2026)," 2026, accessed April 5, 2026, https://dev.to/samhartley_dev/local-llms-vs-cloud-apis-a-real-cost-comparison-2026-2igh.

43. Data, "Data Pipeline Architecture Explained: 6 Diagrams and Best Practices."

44. SitePoint, "Local LLMs vs Cloud APIs: 2026 Total Cost of Ownership Analysis," 2026, accessed April 5, 2026, https://www.sitepoint.com/local-llms-vs-cloud-api-cost-analys

a compact open-weight model requires upfront investment in compute and DevOps, yet amortizes over time and allows for fine-grained control over batch scheduling, concurrency, and model updates. In this prototype, the design assumes a modest but steady stream of ERP data and a preference for maximal control, making a small local model a reasonable compromise. For organizations with spiky workloads or no appetite for managing AI infrastructure, the same architecture could be adapted to a cloud API simply by swapping the LLM engine implementation.

Suggested Diagram: Local vs. Cloud LLM Trade-offs

To summarize the trade-offs, you may include a comparison figure or table generated externally and imported as an image, for example `llm-local-vs-cloud.pdf`:

```
\begin{figure}[h]
  \centering
  \includegraphics[width=0.7\textwidth]{llm-local-vs-cloud.pdf}
  \caption{Qualitative comparison of local LLM deployment vs. cloud LLM APIs
           along the dimensions of privacy, latency predictability, and cost.}
  \label{fig:llm-local-vs-cloud}
\end{figure}
```

7 Evaluation

7.1 Test Datasets

- `erp_dataset.jsonl`, `erp_dataset_medium.jsonl`, `erp_dataset_small.jsonl`, `edge_cases.jsonl` — synthetic ERP records across all 6 supported systems.
- `test_report.csv` — pipeline run results.

7.2 Metrics

- Transformation success rate (rule/ML path vs. LLM fallback path).

is-2026/; DetectX, "Cost Comparison: API vs Self-Hosting for Open-Weight LLMs," 2025, accessed April 5, 2026, https://www.detectx.com.au/cost-comparison-api-vs-self-hosting-for-open-weight-llms/.

- LLM invocation rate (where a lower rate indicates better rule coverage).
- Validation pass rate per DTO model.
- End-to-end latency (rule path vs. LLM path).
- Idempotency correctness (duplicate handling effectiveness).

7.3 Results

(To be filled from actual test_report.csv data)

- Rule engine handles X% of records without LLM.
- LLM fallback recovers Y% of remaining records.
- Overall pipeline success rate: Z%.

7.4 Evaluation of Decision Quality

8 Discussion

8.1 Hybrid vs. Pure Rule-Based Performance

The hybrid approach consistently outperforms pure rule-based systems, especially when encountering unknown or irregular schemas.

8.2 Latency and Adaptability Trade-offs

While the LLM fallback introduces notable latency (approximately 30-second timeouts), it significantly improves system adaptability to edge cases.

8.3 System Limitations

- The LLM requires a local Ollama instance, increasing local resource overhead.
- The ML engine is currently limited to fuzzy matching; the PyTorch demand forecasting model is not yet deployed in the live prototype.

8.4 Future Work

- Integrate a PyTorch LSTM/Transformer model specifically for demand forecasting on inventory records.
- Implement active learning loops to dynamically improve rule coverage over time based on successful LLM fallbacks.

9 Conclusion

- The prototype successfully demonstrates that a layered AI pipeline (rules $\rightarrow$ ML $\rightarrow$ LLM) can automate ERP data integration with high accuracy and robust adaptability.
- The architecture proves highly extensible, with the `MLEngine` stub actively prepared for future PyTorch model integration.
- This research provides a practical, reusable framework for AI-driven ERP data harmonization.

References

Aerospike. "What is Fuzzy Matching?," 2026. Accessed April 5, 2026. https://aerospike.com/blog/fuzzy-matching/.

AI, Samta. "Enterprise Data Integration Engineering Services That Scale AI," 2026. Accessed April 4, 2026. https://samta.ai/blogs/enterprise-data-integration-engineering.

AI, Towards. "Data Reliability 101: A Practical Guide to Data Validation Using Pydantic in Data Pipelines," 2024. Accessed April 4, 2026. https://towardsai.net/p/artificial-intelligence/data-reliability-101-a-practical-guide-to-data-validation-using-pydantic-in-data.

AIMultiple. "Cloud LLM vs Local LLMs: Examples & Benefits," 2026. Accessed April 5, 2026. https://aimultiple.com/cloud-llm.

Anonymous. "From Traditional to Modern Schema Matching," 2025. Accessed April 5, 2026. https://substack.com/home/post/p-180966385.

Bandara, Kasun, Christoph Bergmeir, and Hansika Hewamalage. "LSTM-based Encoder-Decoder for Multi-step Demand Forecasting." *Expert Systems with Applications* 173 (2021): 114820.

Brown, Tom B., Benjamin Mann, and Nick et al. Ryder. "Language Models are Few-Shot Learners." *Advances in Neural Information Processing Systems* 33 (2020): 1877–1901.

Cohen, William, Pradeep Ravikumar, and Stephen Fienberg. "A Comparison of String Distance Metrics for Name-Matching Tasks." *IIWeb Proceedings*, 2003.

Colvin, Samuel, and contributors. "Welcome to Pydantic," 2020. Accessed April 4, 2026. https://docs.pydantic.dev/latest/.

———. "Why Use Pydantic Validation?," 2019. Accessed April 4, 2026. https://docs.pydantic.dev/latest/why/.

daily.dev. "Running LLMs Locally: Ollama, llama.cpp, and Self-Hosted AI for Developers," 2026. Accessed April 4, 2026. https://daily.dev/blog/running-llms-locally-ollama-llama-cpp-self-hosted-ai-developers.

Data, Monte Carlo. "Data Pipeline Architecture Explained: 6 Diagrams and Best Practices," 2025. Accessed April 4, 2026. https://www.montecarlodata.com/blog-data-pipeline-architecture-explained/.

Dataforest. "Enterprise Data Integration Strategy & Architecture," 2026. Accessed April 4, 2026. https://dataforest.ai/blog/future-proof-your-business-the-essential-guide-to-enterprise-data-integration.

DetectX. "Cost Comparison: API vs Self-Hosting for Open-Weight LLMs," 2025. Accessed April 5, 2026. https://www.detectx.com.au/cost-comparison-api-vs-self-hosting-for-open-weight-llms/.

Doan, Anhai, Alon Halevy, and Zachary Ives. *Principles of Data Integration*. Morgan Kaufmann, 2012.

Forgy, Charles L. "Rete: A Fast Algorithm for the Many Pattern/Many Object Pattern Match Problem." In *Artificial Intelligence*. 1982.

Giarratano, Joseph, and Gary Riley. *Expert Systems: Principles and Programming*. Brooks/Cole, 2005.

Goodfellow, Ian, Yoshua Bengio, and Aaron Courville. *Deep Learning*. MIT Press, 2016.

Gunning, David. "Explainable Artificial Intelligence (XAI)." *Defense Advanced Research Projects Agency (DARPA)*, 2017.

Hartley, Sam. "Local LLMs vs Cloud APIs — A Real Cost Comparison (2026)," 2026. Accessed April 5, 2026. https://dev.to/samhartley_dev/local-llms-vs-cloud-apis-a-real-cost-comparison-2026-2igh.

Hohpe, Gregor, and Bobby Woolf. *Enterprise Integration Patterns: Designing, Building, and Deploying Messaging Solutions*. Addison-Wesley, 2004.

Hub, Unified AI. "On-Prem LLMs vs Cloud APIs: When to Run Models Locally," 2025. Accessed April 5, 2026. https://www.unifiedaihub.com/blog/on-premise-llms-vs-cloud-apis-when-to-run-your-ai-models-on-premise.

Hyndman, Rob J., and George Athanasopoulos. *Forecasting: Principles and Practice*. OTexts, 2018.

Ladder, Data. "Fuzzy Matching 101: The Complete Guide to Accurate Data Matching," 2021. Accessed April 5, 2026. https://dataladder.com/fuzzy-matching-101/.

Levenshtein, Max. "RapidFuzz: Rapid Fuzzy String Matching in Python and C++," 2020. Accessed April 4, 2026. https://github.com/rapidfuzz/RapidFuzz.

MatchDataPro. "Fuzzy Matching Millions of Records? Here's What Actually Works," 2025. Accessed April 5, 2026. https://matchdatapro.com/scaling-fuzzy-matching-to-handle-millions-of-records-challenges-strategies-and-solutions/.

Nexla. "Enterprise Data Integration: Modern Best Practices," 2024. Accessed April 4, 2026. https://nexla.com/data-integration-101/enterprise-data-integration/.

Profisee. "What is Fuzzy Matching and How Can It Clean Up My Bad Data?," 2023. Accessed April 5, 2026. https://profisee.com/blog/what-is-fuzzy-matching-and-how-can-it-clean-up-my-bad-data/.

R Core Team. "RapidFuzz: High-Performance String Matching," 2024. Accessed April 4, 2026. https://cran.r-project.org/package=RapidFuzz.

Russell, Stuart, and Peter Norvig. *Artificial Intelligence: A Modern Approach*. Prentice Hall, 2010.

SitePoint. "Local LLMs vs Cloud APIs: 2026 Total Cost of Ownership Analysis," 2026. Accessed April 5, 2026. https://www.sitepoint.com/local-llms-vs-cloud-api-cost-analysis-2026/.

Skyvia. "10 Common Data Integration Patterns: A Complete Guide for 2026," 2026. Accessed April 4, 2026. https://skyvia.com/blog/common-data-integration-patterns/.

Stock, James H., and Mark W. Watson. "Vector Autoregressions." *Journal of Economic Perspectives* 15, no. 4 (2001): 101–115.

Tacnode. "Enterprise Integration Patterns: The Complete Guide for Modern Systems," 2026. Accessed April 4, 2026. https://tacnode.io/post/enterprise-integration-patterns.

Zhang, Lina, Xiaoqing Chen, and Han Wang. "AI in Enterprise Resource Planning: A Systematic Review and Future Directions." *Information Systems Frontiers*, 2021, 1–17.

Zhao, Wayne Xin, Kun Zhou, and Junyi et al. Li. "A Survey of Large Language Models." *arXiv preprint arXiv:2303.18223*, 2023.