

# Object detection with Convolutional Neural Nets

**Falgayrac Jérôme, Hardouin Baptiste, Virel Guillaume,  
Voreiter Damien**

M2 - University of Bretagne Sud, Vannes

2019

# Table of contents

## Rappel

Convolutional Neural Networks (*CNN*)

Support Vector Machine (*SVM*)

## Object Detection

### Base

Histogram Oriented Gradient (*HOG*)

Region-Based Convolutional Neural Networks (*R-CNN*)

### Advanced Methods

Fast R-CNN

Faster R-CNN

YOLO

Mask R-CNN

## Results

## Practical session

## Source

# Table of contents

## Rappel

Convolutional Neural Networks (*CNN*)  
Support Vector Machine (*SVM*)

## Object Detection

## Results

## Practical session

## Source

# Convolutional Neural Networks (CNN)




Figure: Convolutional Network

# Support Vector Machine (*SVM*)

Figure: Working

# Table of contents

Rappel

## Object Detection

### Base

Histogram Oriented Gradient (*HOG*)

Region-Based Convolutional Neural Networks (*R-CNN*)

### Advanced Methods

Fast R-CNN

Faster R-CNN

YOLO

Mask R-CNN

Results

Practical session

Source

# Histogram Oriented Gradient (*HOG*)




Figure: 8x8 HOG

# Histogram Oriented Gradient (*HOG*)




Figure: Fill principle of the histogram

# Histogram Oriented Gradient (*HOG*)




Figure: Fill principle of the histogram

## HOG Normalization and result




Figure: 16x16 block for normalization

Figure: HOG Visualization

# Region-Based Convolutional Neural Networks (*R-CNN*)




Figure: Model R-CNN

# Selective Search

## Step 1:

Segmentation method by Felzenszwalb et Huttenlocher



Figure: Input image



Figure: Output image

# Selective Search

## Step 2:



Figure: Oversegmented images

# Similarity

- ▶ Color similarity
- ▶ Shape compatibility
- ▶ Size similarity
- ▶ Texture similarity
- ▶ Final similarity

# Selective Search

## Step 3:





Figure: Grouping similarity regions

# Bounding Box Regression



Before non-max suppression



After non-max suppression

**Figure:** Multiple bounding boxes detect the car in the image

# Advanced Methods

# Fast R-CNN




Figure: Fast-RCNN Principle

# Faster R-CNN




Figure: Faster-RCNN Principle

# Region Proposal Network (*RPN*)




Figure: RPN Principle

# Faster-RCNN Results




Figure: RPN Principle

# YOLO




Figure: Yolo Network  
(24 + 2 layers)

# Pascal VOC 2012 dataset



Figure: Base image

# YOLO




Figure: Image divided into grid ( $7 \times 7$ )

# YOLO





Figure: Exemple on one cell

# YOLO




Figure: Result of exemple

# Mask R-CNN



Figure: Base image

# Mask R-CNN




Figure: Segmentation masks

# Mask R-CNN




Figure: Mask Model

# COCO dataset

Figure: Example

*(COCO is only 330 000 images with 1.5 million object instances for 80 classes. . . )*

# Table of contents

Rappel

Object Detection

Results

Practical session

Source

# Results



Figure: Accuracy / Speed graph

## Results




Figure: Training time

## Results




Figure: Test time

# Results

Algorithm	Features	Limitations
R-CNN	Selective search for region identification  Extraction of CNN features from each region independently for classification	Training is expensive and slow  The process involves 3 separate models without much shared computation  Extracts around 2000 regions from each image  Cannot be implemented in real time (it takes ~47s for each image)
Fast R-CNN	Each image is passed only once to the CNN  Feature maps are used to detect objects  Uses a single R-CNN model  Much faster than R-CNN in both training and testing time	Selective search is slow and hence computation time is high  Region proposals are generated separately using a different model. This makes the process very expensive
Faster R-CNN	Uses a unified model composed of RPN (region proposal network) and fast R-CNN with shared convolutional feature layers	Object proposals with RPN are time-consuming  The performance of the previous system affects the performance of the current system
Mask R-CNN	Applies Faster R-CNN to pixel-level image segmentation  An additional branch is used in parallel with existing branches, to predict an object mask.  Improves the RoI pooling layer so that RoI can be more precisely mapped to regions of the original image	None

Figure: Comparative table

# Table of contents

Rappel

Object Detection

Results

Practical session

Source

# Practical session



Figure: Start image

# Practical session



Figure: Output image

# Practical session

Figure: Output Video

# Table of contents

Rappel

Object Detection

Results

Practical session

Source

## Source

S. Ren, K. He, R. B. Girshick, and J. Sun, "Faster R-CNN: towards real-time object detection with region proposal networks," *CoRR*, vol. abs/1506.01497, 2015. [Online]. Available: <http://arxiv.org/abs/1506.01497>

K. He, G. Gkioxari, P. Dollár, and R. B. Girshick, "Mask R-CNN," *CoRR*, vol. abs/1703.06870, 2017. [Online]. Available: <http://arxiv.org/abs/1703.06870>

R. B. Girshick, "Fast R-CNN," *CoRR*, vol. abs/1504.08083, 2015. [Online]. Available: <http://arxiv.org/abs/1504.08083>

J. Redmon, S. K. Divvala, R. B. Girshick, and A. Farhadi, "You only look once: Unified, real-time object detection," *CoRR*, vol. abs/1506.02640, 2015. [Online]. Available: <http://arxiv.org/abs/1506.02640>

V. S. Chandel, "Selective search for object detection," Sep 2017. [Online]. Available: <https://www.learnopencv.com/selective-search-for-object-detection-cpp-python/>

## Source (cont.)

- Geva, "Building faster r-cnn on tensorflow: Introduction and examples." [Online]. Available: <https://missinglink.ai/guides/tensorflow/building-faster-r-cnn-on-tensorflow-introduction-and-examples/>
- S. Mallick, "Histogram of oriented gradients," Dec 2016. [Online]. Available:  
<https://www.learnopencv.com/histogram-of-oriented-gradients/>
- A. SACHAN, "Zero to hero: Guide to object detection using deep learning: Faster r-cnn,yolo,ssd," Dec 2017. [Online]. Available:  
<https://cv-tricks.com/object-detection/faster-r-cnn-yolo-ssd/>
- P. Sharma, "Step-by-step implementation of mask r-cnn for image segmentation," Jul 2019. [Online]. Available:  
<https://www.analyticsvidhya.com/blog/2019/07/computer-vision-implementing-mask-r-cnn-image-segmentation/>