

## Apply filters to SQL queries

### Project description

The organization that I am working with requires me to review their security for security incidents and to update their systems as necessary. For this task, I used SQL to collect the pertinent information to fulfill this objective.

### Retrieve after hours failed login attempts

A security incident is believed to have occurred during the after-hours past **1800HRS**. To examine the incident further, I used the **FROM** and **WHERE** operators to look for unsuccessful login attempts for after **1800HRS**.

```
MariaDB [organization]> SELECT *
-> FROM log_in_attempts
-> WHERE login_time > '18:00' AND success = '0';
```

event_id	username	login_date	login_time	country	ip_address	success
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
18	pwashing	2022-05-11	19:28:50	US	192.168.66.142	0
20	tshah	2022-05-12	18:56:36	MEXICO	192.168.109.50	0
28	astrada	2022-05-09	19:28:12	MEXICO	192.168.27.57	0
34	drosas	2022-05-11	21:02:04	US	192.168.45.93	0
42	cgriffin	2022-05-09	23:04:05	US	192.168.4.157	0
52	cjackson	2022-05-10	22:07:07	CAN	192.168.58.57	0
69	wjaffrey	2022-05-11	19:55:15	USA	192.168.100.17	0
82	abernard	2022-05-12	23:38:46	MEX	192.168.234.49	0
87	apatel	2022-05-08	22:38:31	CANADA	192.168.132.153	0
96	ivelasco	2022-05-09	22:36:36	CAN	192.168.84.194	0
104	asundara	2022-05-11	18:38:07	US	192.168.96.200	0
107	bisles	2022-05-12	20:25:57	USA	192.168.116.187	0
111	astrada	2022-05-10	22:00:26	MEXICO	192.168.76.27	0
127	abellmas	2022-05-09	21:20:51	CANADA	192.168.70.122	0
131	bisles	2022-05-09	20:03:55	US	192.168.113.171	0
155	cgriffin	2022-05-12	22:18:42	USA	192.168.236.176	0
160	jclark	2022-05-10	20:49:00	CANADA	192.168.214.49	0
199	yappiah	2022-05-11	19:34:48	MEXICO	192.168.44.232	0

19 rows in set (0.156 sec)

Using the **SELECT** operator followed by an asterisk, I indicated that I am looking for any available information in the dataset. Using the **FROM** operator, I indicated that I am examining the **log\_in\_attempts** dataset. Finally, I used the **WHERE** operator to state the parameters for my SQL query which is that the **login\_time** is over **18:00**. Using the **AND** operator to identify a second parameter, I look for **success = 0** to indicate failed logins.

## Retrieve login attempts on specific dates

The security incident is believed to have occurred on May 9, 2025. As such, I examined all login attempts on the date of the incident and before, May 10, 2025.

```
MariaDB [organization]> SELECT *  
->  
-> FROM log_in_attempts  
->  
-> WHERE login_date = '2022-05-08' OR login_date = '2022-05-09';
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	1
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	1
4	dkot	2022-05-08	02:00:39	USA	192.168.178.71	0
8	bisles	2022-05-08	01:30:17	US	192.168.119.173	0
12	dkot	2022-05-08	09:11:34	USA	192.168.100.158	1
15	lyamamot	2022-05-09	17:17:26	USA	192.168.183.51	0
24	arusso	2022-05-09	06:49:39	MEXICO	192.168.171.192	1
25	sbaelish	2022-05-09	07:04:02	US	192.168.33.137	1
26	apatel	2022-05-08	17:27:00	CANADA	192.168.123.105	1
28	astrada	2022-05-09	19:28:12	MEXICO	192.168.27.57	0
30	yappiah	2022-05-09	03:22:22	MEX	192.168.124.48	1
32	acook	2022-05-09	02:52:02	CANADA	192.168.142.239	0
36	asundara	2022-05-08	09:00:42	US	192.168.78.151	1

Following from the same **SELECT** and **FROM** operators from the previous task, I used the **WHERE** operator again to look for entries where the login date is 2022-05-08 OR 2022-05-09.

## Retrieve login attempts outside of Mexico

The organization has determined that the suspicious login does not originate from **Mexico**. As such, I looked for login attempts for IPs in countries that are not **Mexico**.

```
MariaDB [organization]> SELECT *  
-> FROM log_in_attempts  
-> WHERE NOT country LIKE 'Mex%';
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	1
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	1
4	dkot	2022-05-08	02:00:39	USA	192.168.178.71	0
5	jrafael	2022-05-11	03:05:59	CANADA	192.168.86.232	0
7	eraab	2022-05-11	01:45:14	CAN	192.168.170.243	1
8	bisles	2022-05-08	01:30:17	US	192.168.119.173	0
10	jrafael	2022-05-12	09:33:19	CANADA	192.168.228.221	0
11	sgilmore	2022-05-11	10:16:29	CANADA	192.168.140.81	0
12	dkot	2022-05-08	09:11:34	USA	192.168.100.158	1
13	mrah	2022-05-11	09:29:34	USA	192.168.246.135	1
14	sbaelish	2022-05-10	10:20:18	US	192.168.16.99	1
15	lyamamot	2022-05-09	17:17:26	USA	192.168.183.51	0
16	mcouliba	2022-05-11	06:44:22	CAN	192.168.172.189	1
17	pwashing	2022-05-11	02:33:02	USA	192.168.81.89	1
18	pwashing	2022-05-11	19:28:50	US	192.168.66.142	0
19	jhill	2022-05-12	13:09:04	US	192.168.142.245	1
21	iuduike	2022-05-11	17:50:00	US	192.168.131.147	1
25	sbaelish	2022-05-09	07:04:02	US	192.168.33.137	1
26	apatel	2022-05-08	17:27:00	CANADA	192.168.123.105	1

I used the `WHERE NOT` operator to exclude entries where the country is `LIKE Mex%`. The `%` is used to include any character that follows "Mex". In this way, I can query for **Mexico**. As a result, the entries that will be returned will be from any country that is not **Mexico**.

## Retrieve employees in Marketing

The organization wants to update the systems for employees in the **Marketing** department that have an office from the **East Building**. I used an SQL query to look for employees that fit those parameters.

```
MariaDB [organization]> SELECT *
->
-> FROM employees
-> WHERE department LIKE "Marketing" AND office LIKE "East%"
-> ;
```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1052	a192b174c940	jdarosa	Marketing	East-195
1075	x573y883z772	fbautist	Marketing	East-267
1088	k865l965m233	rgosh	Marketing	East-157
1103	NULL	randerss	Marketing	East-460
1156	a184b775c707	dellery	Marketing	East-417
1163	h679i515j339	cwilliam	Marketing	East-216

```
7 rows in set (0.002 sec)
```

Using the `WHERE` operator, I looked for entries where the `department` is `LIKE "Marketing"` and the `office` is `LIKE "East%"` (the `%` is used to look for entries that include East followed by any character after it).

## Retrieve employees in Finance or Sales

Here, I looked at the list of employees in either the **finance** department or the **sales** department.

```
MariaDB [organization]> SELECT*
-> FROM employees
-> WHERE department = 'Finance' OR department = 'Sales';
```

employee_id	device_id	username	department	office
1003	d394e816f943	sgilmore	Finance	South-153
1007	h174i497j413	wjaffrey	Finance	North-406
1008	i858j583k571	abernard	Finance	South-170
1009	NULL	lrodriqu	Sales	South-134
1010	k242l212m542	jlsansky	Finance	South-109
1011	l748m120n401	drosas	Sales	South-292
1015	p611q262r945	jsoto	Finance	North-271
1017	r550s824t230	jclark	Finance	North-188
1018	s310t540u653	abellmas	Finance	North-403
1022	w237x430y567	arusso	Finance	West-465
1024	y976z753a267	iuduike	Sales	South-215
1025	z381a365b233	jhill	Sales	North-115
1029	d336e475f676	ivelasco	Finance	East-156
1035	j236k303l245	bisles	Sales	South-171
1039	n253o917p623	cjackson	Sales	East-378
1041	p929q222r778	cgriffin	Sales	North-208
1044	s429t157u159	tbarnes	Finance	West-415
1045	t567u844v434	pwashing	Finance	East-115
1046	u429v921w138	daquino	Finance	West-280
1047	v109w587x644	cward	Finance	West-373
1048	w167x592y375	tmitchel	Finance	South-288
1049	NULL	jreckley	Finance	Central-295
1050	y132z930a114	csimmons	Finance	North-468
1057	f370g535h632	mscott	Sales	South-270
1062	k367l639m697	redwards	Finance	North-180
1063	l686m140n569	lpope	Sales	East-226
1066	o678p794q957	ttyrell	Sales	Central-444
1069	NULL	jpark	Finance	East-110

I used the **WHERE** operator for the category, **department**, followed by an equal sign for both **Finance** OR **Sales** to look for entries for either departments.

## Retrieve all employees not in IT

Here I looked for employees who are not from the **Information Technology** department.

```

MariaDB [organization]> SELECT *
-> FROM employees
-> WHERE NOT department LIKE 'Information Technology';

```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1001	b239c825d303	bmoreno	Marketing	Central-276
1002	c116d593e558	tshah	Human Resources	North-434
1003	d394e816f943	sgilmore	Finance	South-153
1004	e218f877g788	eraab	Human Resources	South-127
1005	f551g340h864	gesparza	Human Resources	South-366
1007	h174i497j413	wjaffrey	Finance	North-406
1008	i858j583k571	abernard	Finance	South-170
1009	NULL	lrodriqu	Sales	South-134
1010	k242l212m542	jlansky	Finance	South-109
1011	l748m120n401	drosas	Sales	South-292
1015	p611q262r945	jsoto	Finance	North-271
1016	q793r736s288	sbaelish	Human Resources	North-229
1017	r550s824t230	jclark	Finance	North-188
1018	s310t540u653	abellmas	Finance	North-403
1020	u899v381w363	arutley	Marketing	South-351
1022	w237x430y567	arusso	Finance	West-465
1024	y976z753a267	iuduike	Sales	South-215
1025	z381a365b233	jhill	Sales	North-115
1026	a998b568c863	apatel	Human Resources	West-320
1027	b806c503d354	mrah	Marketing	West-246
1028	c603d749e374	aestrada	Human Resources	West-121
1029	d336e475f676	ivelasco	Finance	East-156
1030	e391f189g913	mabadi	Marketing	West-375
1031	f419g188h578	dkot	Marketing	West-408
1034	i679j565k940	bsand	Human Resources	East-484
1035	j236k303l245	bisles	Sales	South-171
1036	k550l533m205	rjensen	Marketing	Central-239
1038	m873n636o225	btang	Human Resources	Central-260
1039	n253o917p623	cjackson	Sales	East-378
1040	o783p832q294	dtarly	Human Resources	East-237
1041	p929q222r778	cgriffin	Sales	North-208
1042	q175r338s833	acook	Human Resources	West-381
1044	s429t157u159	tbarnes	Finance	West-415
1045	t567u844v434	pwashing	Finance	East-115
1046	u429v921w138	daquino	Finance	West-280
1047	v109w587x644	cward	Finance	West-373
1048	w167x592y375	tmitchel	Finance	South-288
1049	NULL	jreckley	Finance	Central-295
1050	y132z930a114	csimmons	Finance	North-468
1051	z451a308b518	itraora	Marketing	Central-134

Finally, I used the `WHERE NOT` operator to exclude department entries that are `LIKE` 'Information Technology'. This will return entries from any department apart from **Information Technology**.

## Summary

I used SQL queries to locate all failed login attempts made after 1800HRS. Then, I located login attempts on dates of 2022-05-08 and 2022-05-09. Finally, I looked for all login attempts that occurred outside of Mexico.

The organization then wanted to update the systems of certain departments. To fulfill this task, I used SQL queries to gather a list of employees from the Marketing department. Then, I did the same queries to gather a list of employees from both the Finance and Sales departments. Finally, I did a SQL query to identify all other employees that are not in the IT department as they already updated their systems.