

---

# **Data Science - A practical Approach**

**Lorenz Feyen**

**Oct 08, 2021**



# CONTENTS

|           |  |           |
|-----------|--|-----------|
| <b>I</b>  | <b>1. Introduction</b>                 | <b>3</b>  |
| <b>1</b>  | <b>Introduction</b>                    | <b>5</b>  |
| 1.1       | Structured vs Unstructured . . . . .   | 5         |
| 1.2       | Data Structures . . . . .              | 6         |
| 1.3       | OLTP and OLAP . . . . .                | 7         |
| <b>II</b> | <b>2. Data Preparation</b>             | <b>9</b>  |
| <b>2</b>  | <b>Introduction</b>                    | <b>11</b> |
| 2.1       | why Data Preparation? . . . . .        | 11        |
| 2.2       | Further reading . . . . .              | 14        |
| <b>3</b>  | <b>Missing Data</b>                    | <b>15</b> |
| 3.1       | Kamyr digester . . . . .               | 15        |
| 3.2       | Travel times . . . . .                 | 17        |
| 3.3       | Material properties . . . . .          | 22        |
| <b>4</b>  | <b>Concatenation and deduplication</b> | <b>25</b> |
| 4.1       | Concatenation . . . . .                | 25        |
| 4.2       | Deduplication . . . . .                | 26        |
| <b>5</b>  | <b>Outliers and validity</b>           | <b>31</b> |
| 5.1       | Silicon wafer thickness . . . . .      | 31        |
| 5.2       | Distillation column . . . . .          | 34        |
| <b>6</b>  | <b>String operations</b>               | <b>37</b> |
| <b>7</b>  | <b>Datetime operations</b>             | <b>39</b> |
| <b>8</b>  | <b>Categorical encoding</b>            | <b>49</b> |
| 8.1       | Raw Material Charaterization . . . . . | 49        |
| <b>9</b>  | <b>Restaurant tips</b>                 | <b>53</b> |
| <b>10</b> | <b>Scaling and Normalization</b>       | <b>59</b> |
| <b>11</b> | <b>Binning and ranking</b>             | <b>63</b> |
| 11.1      | Binning . . . . .                      | 65        |
| 11.2      | Ranking . . . . .                      | 68        |
| <b>12</b> | <b>Some practice</b>                   | <b>73</b> |

|                                  |            |
|----------------------------------|------------|
| <b>III 3. Data Preprocessing</b> | <b>75</b>  |
| 13 Data Preprocessing            | 77         |
| 14 Indexing and slicing          | 79         |
| 15 Merge                         | 83         |
| 16 Groupby                       | 87         |
| 17 Pivot                         | 91         |
| <b>IV 4. Data Exploration</b>    | <b>95</b>  |
| 18 Data Exploration              | 97         |
| <b>V 5. Data Visualisation</b>   | <b>99</b>  |
| 19 Data Visualisation            | 101        |
| <b>VI 6. Machine Learning</b>    | <b>103</b> |
| 20 Machine Learning              | 105        |

pdf version can be found [here](#).



## **Part I**

### **1. Introduction**





## INTRODUCTION

this is an introduction

### 1.1 Structured vs Unstructured

When performing data preparation an important aspect is to consider with the type of data we are working with. In general there are 2 types of data, but you could consider a third.

#### 1.1.1 Structured data

Structured data is data that adheres to a pre-defined data model and is therefore straightforward to analyze. This data model is the description of our data, each record has to be conform to the model. A table in a spreadsheet is a good example of the concept of structured data however often no data types are enforced, meaning a column can contain e.g. both numbers and text. Later we will see that a mixture of data types is often problematic therefor the need of a data model.

#### 1.1.2 Unstructured data

In contrast to structured data, there is no apparent data model but this does not mean the data is unusable or cluttered. Usually it means either no data model has yet been applied or we are dealing with data that is difficult to confine in a model. A great example of this would be images, or more general (binary) files. These obviously are hard to sort yet often data structures also contain metadata from these files, with data describing things as when the file was uploaded, what is shown in the file, ... In turn the metadata can be structured and a data model can be related to the unstructured data.

#### 1.1.3 Semi-structured data

As an intermediate option, we have what is called semi-structured data. The reasoning behind this is that the concept of tables is not always applicable, in some occasions e.g. data lakes there is no complex structure present compared to a database. In a data lake files are stored similar to the folder structure in your computer, with no fancy infrastructure behind it, thus reducing operation costs. This implies that a data model can not be enforced and the data is stored in generic files.

## 1.2 Data Structures

There are several structures in which data can be stored and accessed, here we cover the 3 most important.

### 1.2.1 Data Lake

As mentioned earlier a data lake would be the most cost efficient method as it relies on the least infrastructure and can be serverless. The concept behind a data lake is straight-forward, the data is stored in simple files with a specific notation e.g. parquet, csv, xml, ... What is important when designing a data lake would be partitioning, this can be achieved by using subfolders and saving parts of the data in different files. To make this more tangible, take a look at this symbolic [example](#) I provided. Instead of putting all data in one csv file, subfolder divide the data in Country, City and then the year. We could even further partition yet the data is here in daily frequency so that would create many small partitions. The difficulty for a data lake lies in the method of interacting, when adding new data one has to adhere to a agreed upon data model that is not enforced, meaning you could create incorrect data which then need to be cleaned. On the other hand efficiency of you data lake depends on good partitioning, as the order of divisioning of your folders. We could have also divided first on year and then on country and city. As a data scientist seeing the data lake might not be as common, as this is rather an engineering task, however using the concepts of a data lake in experimental projects can make a big difference.

### 1.2.2 Database

Another interesting data structure is the database, widely used for exceptional speeds and ease of use, yet costly in storage. Numerous implementations of servers using the SQL language are developed over the years with each their own dialect and advantages. The important take home message here is that you can easily perform queries on the database that pre-handles the data to retrieve the information you need. these operations include filtering, grouping categories, joining tables, ordering and much more, as SQL is a complete language on its own. As a data scientist these databases are much more common, so SQL is a good asset to learn!

### 1.2.3 Data Warehouse

A next step towards data analysis is the data warehouse, where a database is composed of the most pragmatic method of storing your data a data warehouse consist of multiple views on your data. Based upon the data of a dataset the data warehouse transforms this data into a new format that displays the data in a new way. Let me illustrate with with a simple example, we have a database with a table that contains the rentals of books from multiple libraries. This table has a few columns: a timestamp, the library, the action (rent, return, ...), the client\_id and the book\_id. If you would want to know if a book is available this database is perfect for your needs as you just have to find the last event for that book and if its a return the book is (or should be) there. Now imagine we would want to know how many books are being rented per month this database is insufficient, yet our data warehouse might contain such a view! It is up to the data engineer/scientist to create a computation that displays the amount of books rented per month. If they also would like to subdivided it per category of books, you would need to incorporate another table of the database where information of the books is stored. More on these operations of a data warehouse will be seen in the data preprocessing chapter. One last remark about data warehousing, it is important to optimize between memory and computation. Tables in our data warehouse compared to database can be computed in place reducing memory costs yet increasing computation costs. If a visualization tool often queries a table in your warehouse it is favorable to create it as a table in your database.

## 1.3 OLTP and OLAP

From the previous section you might have deduced that a database and Data Warehouse serve 2 different purposes. These are denoted as OnLine Transaction Processing and OnLine Analytical Processing, as the names suggest these are used for transactional and analytical processes.

### 1.3.1 OLTP

For this method the database structure is optimal, let us review the example where we have libraries renting out books. Renting out a book would send a message to our OLTP system creating a new record stating that specific book is at this moment rented out from our library. OLTP handles day-to-day operational data that can be both written and read from our database.

### 1.3.2 OLAP

In the case we would like to analyse data from the libraries we would use the OLAP method, creating multi-dimensional views from our transactional data. Our dimensions would be the date (aggregated per month), the library and the category of book, the chapter of data preprocessing will use these operations practically. I could write a whole chapter on OLAP operations however they are well described in [this wikipedia page](#).



## **Part II**

# **2. Data Preparation**



## INTRODUCTION

When performing data science, we often do not elaborate about the preparation that went into the dataset. It is considered tedious and irrelevant to the story of the analysis, however it is often the most important part of data analysis. Data Preparation is the metaphorical foundation of your construction, if you fail to prepare data, you prepare to fail your analysis.

Good data beats a fancy algorithm

If you would perform an analysis and insert unprepared data, you will mostly be disappointed with the result.

### 2.1 why Data Preparation?

Aside from metaphors let us make the reasoning behind this step more tangible, to explain the relevance of this step, we partitioned the answer into a few key points.


#### 2.1.1 Accuracy

There is no excuse for incorrect data and accuracy is the most important attribute. Let us assume that we have a dataset where for some reason the results are not accurate. This would lead us to an analysis where we conclude a result that contains a bias. An example would be a dataset of sold cars, where the listed price is that of the stock car without options. Options are not incorporated in the price and we are perhaps training an algorithm that predicts the stock price. If you as a data scientist fail to report/correct this, your predictions are making sense, but always underestimate!

#### 2.1.2 Consistency

They usually say something such as 'consistency is key' and with data preparation that is likewise true. A dataset where we do not have consistent results will never converge towards a particular answer. Note however that it might not be a problem of consistency but rather you are missing crucial information. If we would have a dataset where local temperatures are logged, we would like to see a consistency each 24 hours. However we do see there are day to day fluctuations, so perhaps we need to keep track of cloud and rain data to make the dataset more complete. We could then see that the results are more consistent yet the possibility of outliers is still present. Equally possible would be that our temperature sensor is not sensitive enough or has large fluctuations in readings, it is the task of the data scientist to figure this out.

To get a visual about accuracy and consistency this picture might help:



### 2.1.3 Completeness

As hinted in the previous point, completeness is something you have to be aware of. Having 'complete' data is crucial for your narrative to give a correct answer, as you might otherwise lose detail. Note that you never will know if your data is complete as there might always be more data to mine. Yet you have to make a consideration between collecting more data and the effort required. This collecting can happen in multiple methods, as an example we use a survey where we asked several people 10 different questions, we could:


- gather new data, here our data grows 'longer' by asking the 10 question to more people. It might be that our sample of people were only students at a campus, so our data was not complete.
- gather new feature, by asking more questions to the same people (in case we could still find them). By doing this we get a better understanding of their opinion, again making our data more complete.
- fill missing values, by imputing the abstained questions with answers of similar records. When someone answered they did not want to answer we could figure out what they would have answered by looking at what persons answered that reply in a similar way.



### 2.1.4 Timeliness

For some datasets we are dealing with data that is time related. It can happen that data at specific timepoints is missing or delayed, resulting in a failure to use machine learning algorithms. A well-organised data pipeline utilises techniques of data preparation to circumvent these outages, usually this would be to retain the last successful datapoint. However in hindsight we could use more complex strategies to fill in these gaps or correct datetimes in our dataset,

In this example the data stream is interrupted and data preparation is there to handle these outages before we can perform analysis.



### 2.1.5 Believability

You could collect the most intricate dataset possible, but if the narrative that you are conducting contradicts itself, you will end up nowhere. During the process of data analytics it is important to apply a critical mind to what your dataset is telling you. Obviously this is not a reason to mask or mold the data so it agrees with your opinion. Rather you should be wary when conflicts happen and act accordingly, unfortunately it is impossible to write a generic tactic for this. As a data scientist your experience of the underlying subject should help create understanding of the topic, remember, gathering information from experts in the field is crucial here!

### 2.1.6 Interpretability

Another problem that might arise when you are diving deep into the data might be that you have created something no human could ever interpret. The Machine Learning algorithms outputs plausible and believable results, but it is impossible to understand the reasoning behind. For some this is perfectly acceptable, for some this is undesirable. It is your task as a data scientist to cater the wishes of the product operator and if they desire understanding as they would like to learn from the data driven process you need to unfold the process. Usually this comes down to which data transformations are used as some do produce an output that only makes mathematical sense.

### 2.1.7 In conclusion

There are multiple ways to deteriorate the quality of your data and raw formats of data often contain multiple. Before we can do anything with it these problems need to be resolved, if you fail to do so, the final output fails too.

## 2.2 Further reading

Towards Data Science

## MISSING DATA

In this notebook we will look at a few datasets where values from columns are missing. It is crucial for data science and machine learning to have a dataset where no values are missing as algorithms are usually not able to handle data with information missing.

For python, we will be using the pandas library to handle our dataset.

```
import pandas as pd
```

### 3.1 Kamyr digester

The first dataset we will be looking at is taken from a physical device equipped with numerous sensors, each timepoint (1 hour) these sensors are read out and the data is collected. Let's have a look at the general structure

```
kamyr_df = pd.read_csv('https://raw.githubusercontent.com/LorenzF/data-science-
practical-approach/main/src/c2_data_preparation/data/kamyr-digester.csv')
kamyr_df.head()
```

| Observation   | Y-Kappa       | ChipRate      | BF-CMratio    | BlowFlow    | ChipLevel4  | \       |
|---------------|---------------|---------------|---------------|-------------|-------------|---------|
| 0             | 31-00:00      | 23.10         | 16.520        | 121.717     | 1177.607    | 169.805 |
| 1             | 31-01:00      | 27.60         | 16.810        | 79.022      | 1328.360    | 341.327 |
| 2             | 31-02:00      | 23.19         | 16.709        | 79.562      | 1329.407    | 239.161 |
| 3             | 31-03:00      | 23.60         | 16.478        | 81.011      | 1334.877    | 213.527 |
| 4             | 31-04:00      | 22.90         | 15.618        | 93.244      | 1334.168    | 243.131 |
|               |               |               |               |             |             |         |
| T-upperExt-2  | T-lowerExt-2  | UCZAA         | WhiteFlow-4   | ...         | SteamFlow-4 | \       |
| 0             | 358.282       | 329.545       | 1.443         | 599.253     | ...         | 67.122  |
| 1             | 351.050       | 329.067       | 1.549         | 537.201     | ...         | 60.012  |
| 2             | 350.022       | 329.260       | 1.600         | 549.611     | ...         | 61.304  |
| 3             | 350.938       | 331.142       | 1.604         | 623.362     | ...         | 68.496  |
| 4             | 351.640       | 332.709       | NaN           | 638.672     | ...         | 70.022  |
|               |               |               |               |             |             |         |
| Lower-HeatT-3 | Upper-HeatT-3 | ChipMass-4    | WeakLiquorF   | BlackFlow-2 | \           |         |
| 0             | 329.432       | 303.099       | 175.964       | 1127.197    | 1319.039    |         |
| 1             | 330.823       | 304.879       | 163.202       | 665.975     | 1297.317    |         |
| 2             | 329.140       | 303.383       | 164.013       | 677.534     | 1327.072    |         |
| 3             | 328.875       | 302.254       | 181.487       | 767.853     | 1324.461    |         |
| 4             | 328.352       | 300.954       | 183.929       | 888.448     | 1343.424    |         |
|               |               |               |               |             |             |         |
| WeakWashF     | SteamHeatF-3  | T-Top-Chips-4 | SulphidityL-4 |             |             |         |
| 0             | 257.325       | 54.612        | 252.077       | NaN         |             |         |
| 1             | 241.182       | 46.603        | 251.406       | 29.11       |             |         |

(continues on next page)

(continued from previous page)

|                       |         |        |         |       |
|-----------------------|---------|--------|---------|-------|
| 2                     | 237.272 | 51.795 | 251.335 | NaN   |
| 3                     | 239.478 | 54.846 | 250.312 | 29.02 |
| 4                     | 215.372 | 54.186 | 249.916 | 29.01 |
| [5 rows x 23 columns] |         |        |         |       |

Interesting, there seem to be 22 sensor values and 1 timestamp for each record. As mechanical devices are prone to noise and dropouts of sensors we would be foolish to assume no missing values are present.

```
kamyr_df.isna().sum().divide(len(kamyr_df)).round(4)*100
```

```
Observation      0.00
Y-Kappa          0.00
ChipRate         1.33
BF-CMratio       4.65
BlowFlow         4.32
ChipLevel4       0.33
T-upperExt-2     0.33
T-lowerExt-2     0.33
UCZAA           7.97
WhiteFlow-4      0.33
AAWhiteSt-4     46.84
AA-Wood-4        0.33
ChipMoisture-4   0.33
SteamFlow-4      0.33
Lower-HeatT-3    0.33
Upper-HeatT-3    0.33
ChipMass-4       0.33
WeakLiquorF      0.33
BlackFlow-2      0.33
WeakWashF        0.33
SteamHeatF-3     0.33
T-Top-Chips-4    0.33
SulphidityL-4    46.84
dtype: float64
```

As expected, the datapoint 'AAWhiteSt-4' even has 46% of data missing! It seems we only have 300 datapoints and presumably these missing values occur in different records our dataset will be decimated if we just drop all rows with missing values.

```
kamyr_df.shape
```

```
(301, 23)
```

```
kamyr_df.dropna().shape
```

```
(131, 23)
```

As we drop all rows with missing values, we are left with only 131 records. Whilst this might be good enough for some purposes, there are more viable options.

Perhaps we can first remove the column with the most missing values and then drop all remaining

```
kamyr_df.drop(columns=['AAWhiteSt-4 ', 'SulphidityL-4 ']).dropna().shape
```

```
(263, 21)
```

Significantly better, although we lost the information of 2 sensors we now have a complete dataset with 263 records. For purposes where those 2 sensors are irrelevant this is a viable option, keep in mind that this dataset is still 100% truthful, as we have not imputed any values.

Another option, where we retain all our records would be using the timely nature of our dataset, each record is a measurement with an interval of 1 hour. I have no knowledge of this dataset but one might make the assumption that the interval of 1 hour is taken as the state of the machine does not alter much in 1 hour. Therefore we could do what is called a forward fill, where we fill in the missing values with the same value of the sensor for the previous measurement.

This would solve nearly all nan values as there might be a problem where the first value is missing. This is shown below.

```
kamyr_df.fillna(method='ffill')['SulphidityL-4 ']
```

```
0      NaN
1    29.11
2    29.11
3    29.02
4    29.01
...
296   30.43
297   30.29
298   30.47
299   30.47
300   30.46
Name: SulphidityL-4 , Length: 301, dtype: float64
```

Although our dataset is not fully the truth, we can see that little to no changes occur in the sensor and using a forward fill is arguably the most suitable option.

## 3.2 Travel times

Another dataset from the same source contains a collection of recorded travel times and specific information about the travel itself as e.g.: the day of the week, where they were going, ...

```
travel_df = pd.read_csv('https://raw.githubusercontent.com/LorenzF/data-science-
practical-approach/main/src/c2_data_preparation/data/travel-times.csv')
travel_df
```

|   | Date      | StartTime | DayOfWeek | GoingTo | Distance | MaxSpeed | AvgSpeed | \ |
|---|-----------|-----------|-----------|---------|----------|----------|----------|---|
| 0   | 1/6/2012  | 16:37     | Friday    | Home    | 51.29    | 127.4    | 78.3     |   |
| 1   | 1/6/2012  | 08:20     | Friday    | GSK     | 51.63    | 130.3    | 81.8     |   |
| 2   | 1/4/2012  | 16:17     | Wednesday | Home    | 51.27    | 127.4    | 82.0     |   |
| 3   | 1/4/2012  | 07:53     | Wednesday | GSK     | 49.17    | 132.3    | 74.2     |   |
| 4   | 1/3/2012  | 18:57     | Tuesday   | Home    | 51.15    | 136.2    | 83.4     |   |
| ..  | ...       | ...       | ...       | ...     | ...      | ...      | ...      |   |
| 200   | 7/18/2011 | 08:09     | Monday    | GSK     | 54.52    | 125.6    | 49.9     |   |
| 201   | 7/14/2011 | 08:03     | Thursday  | GSK     | 50.90    | 123.7    | 76.2     |   |
| 202   | 7/13/2011 | 17:08     | Wednesday | Home    | 51.96    | 132.6    | 57.5     |   |
| 203   | 7/12/2011 | 17:51     | Tuesday   | Home    | 53.28    | 125.8    | 61.6     |   |
| 204   | 7/11/2011 | 16:56     | Monday    | Home    | 51.73    | 125.0    | 62.8     |   |
| AvgMovingSpeed FuelEconomy TotalTime MovingTime Take407All Comments |           |           |           |         |          |          |          |   |

(continues on next page)

(continued from previous page)

|                         |      |      |      |      |     |     |
|-------------------------|------|------|------|------|-----|-----|
| 0                       | 84.8 | NaN  | 39.3 | 36.3 | No  | NaN |
| 1                       | 88.9 | NaN  | 37.9 | 34.9 | No  | NaN |
| 2                       | 85.8 | NaN  | 37.5 | 35.9 | No  | NaN |
| 3                       | 82.9 | NaN  | 39.8 | 35.6 | No  | NaN |
| 4                       | 88.1 | NaN  | 36.8 | 34.8 | No  | NaN |
| ..                      | ...  | ...  | ...  | ...  | ... | ... |
| 200                     | 82.4 | 7.89 | 65.5 | 39.7 | No  | NaN |
| 201                     | 95.1 | 7.89 | 40.1 | 32.1 | Yes | NaN |
| 202                     | 76.7 | NaN  | 54.2 | 40.6 | Yes | NaN |
| 203                     | 87.6 | NaN  | 51.9 | 36.5 | Yes | NaN |
| 204                     | 92.5 | NaN  | 49.5 | 33.6 | Yes | NaN |
| [205 rows x 13 columns] |      |      |      |      |     |     |

we have a total of 205 records and we can already see that the FuelEconomy column seems pretty bad, let's quantify that.

```
travel_df.isna().sum().divide(len(travel_df)).round(4)*100
```

```
Date          0.00
StartTime      0.00
DayOfWeek      0.00
GoingTo        0.00
Distance       0.00
MaxSpeed       0.00
AvgSpeed       0.00
AvgMovingSpeed 0.00
FuelEconomy    8.29
TotalTime      0.00
MovingTime     0.00
Take407All     0.00
Comments      88.29
dtype: float64
```

In the end, it doesn't seem that bad, but there are comments and nearly none of them are filled in. Which in perspective is understandable. Let's see what the comments look like

```
travel_df[~travel_df.Comments.isna()].Comments
```

```
15          Put snow tires on
39          Heavy rain
49          Huge traffic backup
50    Pumped tires up: check fuel economy improved?
52          Backed up at Bronte
54          Backed up at Bronte
60          Rainy
78          Rain, rain, rain
91          Rain, rain, rain
92    Accident: backup from Hamilton to 407 ramp
110         Raining
132         Back to school traffic?
133    Took 407 all the way (to McMaster)
150         Heavy volume on Derry
156         Start early to run a batch
158    Accident at 403/highway 6; detour along Dundas
165         Detour taken
166         Must be Friday
```

(continues on next page)

(continued from previous page)

```

172             Medium amount of rain
174             New tires
182             Turn around on Derry
184             Empty roads
187             Police slowdown on 403
189             Accident blocked 407 exit
Name: Comments, dtype: object

```

As you would expect, these comments are text based. Now imagine we would like to run some Natural Language Processing (NLP) on these, it would be a pain to perform string operations on it when it is riddled with missing values.

Here a simple example where we select all records containing the word 'rain', with no avail.

```
travel_df[travel_df.Comments.str.lower().str.contains('rain')]
```

```

-----
ValueError                                Traceback (most recent call last)
/tmp/ipykernel_6376/1298831137.py in <module>
----> 1 travel_df[travel_df.Comments.str.lower().str.contains('rain')]

~/git/data-science-practical-approach/venv/lib/python3.8/site-packages/pandas/core/
frame.py in __getitem__(self, key)
   3446
   3447     # Do we have a (boolean) 1d indexer?
-> 3448     if com.is_bool_indexer(key):
   3449         return self._getitem_bool_array(key)
   3450

~/git/data-science-practical-approach/venv/lib/python3.8/site-packages/pandas/core/
common.py in is_bool_indexer(key)
   137         # Don't raise on e.g. ["A", "B", np.nan], see
   138         # test_loc_getitem_list_of_labels_categoricalindex_with_
-> na
-> 139         raise ValueError(na_msg)
   140         return False
   141         return True

ValueError: Cannot mask with non-boolean array containing NA / NaN values

```

The last line of the python error traceback gives us the reason it failed, because there were NaN values present.

Luckily the string variable has more or less it's on 'null' value, being an empty string, this way these operations are still possible, most of the comments will just contain nothing.

```
travel_df.Comments = travel_df.Comments.fillna('')
```

```
travel_df[travel_df.Comments.str.lower().str.contains('rain')]
```

|     | Date       | StartTime | DayOfWeek | GoingTo | Distance | MaxSpeed | AvgSpeed | \ |
|-----|------------|-----------|-----------|---------|----------|----------|----------|---|
| 39  | 11/29/2011 | 07:23     | Tuesday   | GSK     | 51.74    | 112.2    | 55.3     |   |
| 60  | 11/9/2011  | 16:15     | Wednesday | Home    | 51.28    | 121.4    | 65.9     |   |
| 78  | 10/25/2011 | 17:24     | Tuesday   | Home    | 52.87    | 123.5    | 65.1     |   |
| 91  | 10/12/2011 | 17:47     | Wednesday | Home    | 51.40    | 114.4    | 59.7     |   |
| 110 | 9/27/2011  | 07:36     | Tuesday   | GSK     | 50.65    | 128.1    | 86.3     |   |
| 172 | 8/9/2011   | 08:15     | Tuesday   | GSK     | 49.08    | 134.8    | 60.5     |   |

(continues on next page)

(continued from previous page)

|     | AvgMovingSpeed        | FuelEconomy | TotalTime | MovingTime | Take407All | \ |
|-----|-----------------------|-------------|-----------|------------|------------|---|
| 39  | 61.0                  | NaN         | 56.2      | 50.9       | No         |   |
| 60  | 71.8                  | 9.35        | 46.7      | 42.1       | No         |   |
| 78  | 72.4                  | 8.97        | 48.7      | 43.8       | No         |   |
| 91  | 65.8                  | 8.75        | 51.7      | 46.9       | No         |   |
| 110 | 88.6                  | 8.31        | 35.2      | 34.3       | Yes        |   |
| 172 | 67.2                  | 8.54        | 48.7      | 43.8       | No         |   |
|     | Comments              |             |           |            |            |   |
| 39  | Heavy rain            |             |           |            |            |   |
| 60  | Rainy                 |             |           |            |            |   |
| 78  | Rain, rain, rain      |             |           |            |            |   |
| 91  | Rain, rain, rain      |             |           |            |            |   |
| 110 | Raining               |             |           |            |            |   |
| 172 | Medium amount of rain |             |           |            |            |   |

Fixed! now we can use the comments for analysis.

We still have to fix the FuelEconomy, let us take a look at the non NaN values

```
travel_df[~travel_df.FuelEconomy.isna()]
```

|     | Date           | StartTime   | DayOfWeek | GoingTo    | Distance   | MaxSpeed | AvgSpeed | \ |
|-----|----------------|-------------|-----------|------------|------------|----------|----------|---|
| 6   | 1/2/2012       | 17:31       | Monday    | Home       | 51.37      | 123.2    | 82.9     |   |
| 7   | 1/2/2012       | 07:34       | Monday    | GSK        | 49.01      | 128.3    | 77.5     |   |
| 8   | 12/23/2011     | 08:01       | Friday    | GSK        | 52.91      | 130.3    | 80.9     |   |
| 9   | 12/22/2011     | 17:19       | Thursday  | Home       | 51.17      | 122.3    | 70.6     |   |
| 10  | 12/22/2011     | 08:16       | Thursday  | GSK        | 49.15      | 129.4    | 74.0     |   |
| ..  | ...            | ...         | ...       | ...        | ...        | ...      | ...      |   |
| 197 | 7/20/2011      | 08:24       | Wednesday | GSK        | 48.50      | 125.8    | 75.7     |   |
| 198 | 7/19/2011      | 17:17       | Tuesday   | Home       | 51.16      | 126.7    | 92.2     |   |
| 199 | 7/19/2011      | 08:11       | Tuesday   | GSK        | 50.96      | 124.3    | 82.3     |   |
| 200 | 7/18/2011      | 08:09       | Monday    | GSK        | 54.52      | 125.6    | 49.9     |   |
| 201 | 7/14/2011      | 08:03       | Thursday  | GSK        | 50.90      | 123.7    | 76.2     |   |
|     | AvgMovingSpeed | FuelEconomy | TotalTime | MovingTime | Take407All | Comments |          |   |
| 6   | 87.3           | -           | 37.2      | 35.3       | No         |          |          |   |
| 7   | 85.9           | -           | 37.9      | 34.3       | No         |          |          |   |
| 8   | 88.3           | 8.89        | 39.3      | 36.0       | No         |          |          |   |
| 9   | 78.1           | 8.89        | 43.5      | 39.3       | No         |          |          |   |
| 10  | 81.4           | 8.89        | 39.8      | 36.2       | No         |          |          |   |
| ..  | ...            | ...         | ...       | ...        | ...        | ...      |          |   |
| 197 | 87.3           | 7.89        | 38.5      | 33.3       | Yes        |          |          |   |
| 198 | 102.6          | 7.89        | 33.3      | 29.9       | Yes        |          |          |   |
| 199 | 96.4           | 7.89        | 37.2      | 31.7       | Yes        |          |          |   |
| 200 | 82.4           | 7.89        | 65.5      | 39.7       | No         |          |          |   |
| 201 | 95.1           | 7.89        | 40.1      | 32.1       | Yes        |          |          |   |

[188 rows x 13 columns]

It seems that aside NaN values there are also other intruders, a quick check on the data type (Dtype) reveals it is not recognised as a number!

```
travel_df.info()
```



```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 205 entries, 0 to 204
Data columns (total 13 columns):
#   Column                Non-Null Count  Dtype
---  ---
0   Date                  205 non-null   object
1   StartTime              205 non-null   object
2   DayOfWeek              205 non-null   object
3   GoingTo                205 non-null   object
4   Distance               205 non-null   float64
5   MaxSpeed               205 non-null   float64
6   AvgSpeed               205 non-null   float64
7   AvgMovingSpeed         205 non-null   float64
8   FuelEconomy            188 non-null   object
9   TotalTime              205 non-null   float64
10  MovingTime             205 non-null   float64
11  Take407All             205 non-null   object
12  Comments               205 non-null   object
dtypes: float64(6), object(7)
memory usage: 20.9+ KB
```

The column is noted as an object or string type, meaning that these numbers are given as '9.24' instead of 9.24 and numerical operations are not possible. We can cast them to numeric but have to warn pandas to coerce errors, meaning errors will be converted to NaN values. Later we'll handle the NaN's.

```
travel_df.FuelEconomy = pd.to_numeric(travel_df.FuelEconomy, errors='coerce')
travel_df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 205 entries, 0 to 204
Data columns (total 13 columns):
#   Column                Non-Null Count  Dtype
---  ---
0   Date                  205 non-null   object
1   StartTime              205 non-null   object
2   DayOfWeek              205 non-null   object
3   GoingTo                205 non-null   object
4   Distance               205 non-null   float64
5   MaxSpeed               205 non-null   float64
6   AvgSpeed               205 non-null   float64
7   AvgMovingSpeed         205 non-null   float64
8   FuelEconomy            186 non-null   float64
9   TotalTime              205 non-null   float64
10  MovingTime             205 non-null   float64
11  Take407All             205 non-null   object
12  Comments               205 non-null   object
dtypes: float64(7), object(6)
memory usage: 20.9+ KB
```

Wonderful, now the column is numerical and we can see 2 more missing values have popped up! We could easily drop these 19 records and have a complete dataset.

```
travel_df.dropna()
```

|   | Date       | StartTime | DayOfWeek | GoingTo | Distance | MaxSpeed | AvgSpeed | \ |
|---|------------|-----------|-----------|---------|----------|----------|----------|---|
| 8 | 12/23/2011 | 08:01     | Friday    | GSK     | 52.91    | 130.3    | 80.9     |   |

(continues on next page)

(continued from previous page)

|                         |                |             |           |            |            |          |      |
|-------------------------|----------------|-------------|-----------|------------|------------|----------|------|
| 9                       | 12/22/2011     | 17:19       | Thursday  | Home       | 51.17      | 122.3    | 70.6 |
| 10                      | 12/22/2011     | 08:16       | Thursday  | GSK        | 49.15      | 129.4    | 74.0 |
| 11                      | 12/21/2011     | 07:45       | Wednesday | GSK        | 51.77      | 124.8    | 71.7 |
| 12                      | 12/20/2011     | 16:05       | Tuesday   | Home       | 51.45      | 130.1    | 75.2 |
| ..                      | ...            | ...         | ...       | ...        | ...        | ...      | ...  |
| 197                     | 7/20/2011      | 08:24       | Wednesday | GSK        | 48.50      | 125.8    | 75.7 |
| 198                     | 7/19/2011      | 17:17       | Tuesday   | Home       | 51.16      | 126.7    | 92.2 |
| 199                     | 7/19/2011      | 08:11       | Tuesday   | GSK        | 50.96      | 124.3    | 82.3 |
| 200                     | 7/18/2011      | 08:09       | Monday    | GSK        | 54.52      | 125.6    | 49.9 |
| 201                     | 7/14/2011      | 08:03       | Thursday  | GSK        | 50.90      | 123.7    | 76.2 |
|                         |                |             |           |            |            |          |      |
|                         | AvgMovingSpeed | FuelEconomy | TotalTime | MovingTime | Take407All | Comments |      |
| 8                       | 88.3           | 8.89        | 39.3      | 36.0       | No         |          |      |
| 9                       | 78.1           | 8.89        | 43.5      | 39.3       | No         |          |      |
| 10                      | 81.4           | 8.89        | 39.8      | 36.2       | No         |          |      |
| 11                      | 78.9           | 8.89        | 43.3      | 39.4       | No         |          |      |
| 12                      | 82.7           | 8.89        | 41.1      | 37.3       | No         |          |      |
| ..                      | ...            | ...         | ...       | ...        | ...        | ...      | ...  |
| 197                     | 87.3           | 7.89        | 38.5      | 33.3       | Yes        |          |      |
| 198                     | 102.6          | 7.89        | 33.3      | 29.9       | Yes        |          |      |
| 199                     | 96.4           | 7.89        | 37.2      | 31.7       | Yes        |          |      |
| 200                     | 82.4           | 7.89        | 65.5      | 39.7       | No         |          |      |
| 201                     | 95.1           | 7.89        | 40.1      | 32.1       | Yes        |          |      |
|                         |                |             |           |            |            |          |      |
| [186 rows x 13 columns] |                |             |           |            |            |          |      |

However im leaving them as an excercise for you to apply a technique we will see in the next part

### 3.3 Material properties

Another dataset from the same source contains the material properties from 30 samples, this time there is not timestamp as the samples are not related in time with each other.

```
material_df = pd.read_csv('https://raw.githubusercontent.com/LorenzF/data-science-
practical-approach/main/src/c2_data_preparation/data/raw-material-properties.csv')
material_df
```

|    | Sample | size1 | size2 | size3 | density1 | density2 | density3 |
|----|--------|-------|-------|-------|----------|----------|----------|
| 0  | X12558 | 0.696 | 2.69  | 6.38  | 41.8     | 17.18    | 3.90     |
| 1  | X14728 | 0.636 | 2.30  | 5.14  | 38.1     | 12.73    | 3.89     |
| 2  | X15468 | 0.841 | 2.85  | 5.20  | 37.6     | 13.58    | 3.98     |
| 3  | X21364 | 0.609 | 2.13  | 4.62  | 34.2     | 11.12    | 4.02     |
| 4  | X23671 | 0.684 | 2.16  | 4.87  | 36.4     | 12.24    | 3.92     |
| 5  | X24055 | 0.762 | 2.81  | 6.36  | 38.1     | 13.28    | 3.89     |
| 6  | X24905 | 0.552 | 2.34  | 5.03  | 41.3     | 16.71    | 3.86     |
| 7  | X25917 | 0.501 | 2.17  | 5.09  | NaN      | NaN      | NaN      |
| 8  | X27871 | 0.619 | 2.11  | 5.13  | NaN      | NaN      | NaN      |
| 9  | X28690 | 0.610 | 2.10  | 4.18  | 35.0     | 12.15    | 3.86     |
| 10 | X31385 | 0.532 | 2.09  | 4.93  | NaN      | NaN      | NaN      |
| 11 | X31813 | 0.738 | 2.29  | 5.47  | NaN      | NaN      | NaN      |
| 12 | X32807 | 0.779 | 2.62  | 5.59  | NaN      | NaN      | NaN      |
| 13 | X33943 | 0.537 | 2.23  | 5.41  | 35.2     | 11.34    | 3.99     |
| 14 | X35035 | 0.702 | 2.05  | 5.10  | 34.2     | 10.54    | 4.02     |
| 15 | X39223 | 0.768 | 2.51  | 5.09  | 34.9     | 12.55    | 3.90     |

(continues on next page)

(continued from previous page)

|    |        |       |      |      |      |       |      |
|----|--------|-------|------|------|------|-------|------|
| 16 | X40503 | 0.714 | 2.56 | 6.03 | 35.6 | 12.20 | 4.02 |
| 17 | X41400 | 0.621 | 2.42 | 5.10 | 38.7 | 14.27 | 3.98 |
| 18 | X42988 | 0.726 | 2.11 | 4.69 | 37.1 | 13.14 | 3.98 |
| 19 | X44749 | 0.698 | 2.36 | 5.40 | 36.6 | 12.16 | 4.01 |
| 20 | X45295 | NaN   | NaN  | NaN  | 38.1 | 13.34 | 3.89 |
| 21 | X46965 | 0.759 | 2.47 | 4.83 | 38.7 | 14.83 | 3.89 |
| 22 | X49666 | 0.535 | 2.13 | 5.23 | NaN  | NaN   | NaN  |
| 23 | X50678 | 0.716 | 2.29 | 5.45 | 37.3 | 13.70 | 3.92 |
| 24 | X52894 | 0.635 | 2.08 | 4.94 | NaN  | NaN   | NaN  |
| 25 | X53925 | 0.598 | 2.12 | 4.69 | 37.9 | 13.45 | 3.78 |
| 26 | X54254 | 0.700 | 2.47 | 5.22 | 38.8 | 14.72 | 3.92 |
| 27 | X54272 | 0.957 | 2.96 | 7.37 | 36.2 | 13.38 | 4.20 |
| 28 | X54394 | 0.759 | 2.66 | 5.36 | 35.2 | 12.19 | 3.98 |
| 29 | X55408 | 0.661 | 2.10 | 4.27 | NaN  | NaN   | NaN  |
| 30 | X56952 | 0.646 | 2.38 | 4.51 | 40.1 | 15.68 | 3.86 |
| 31 | X57095 | 0.662 | 2.34 | 4.71 | 35.0 | 12.37 | 3.90 |
| 32 | X57128 | 0.749 | 2.43 | 5.16 | 37.3 | 13.04 | 3.92 |
| 33 | X61870 | 0.598 | 2.21 | 4.90 | NaN  | NaN   | NaN  |
| 34 | X61888 | 0.619 | 2.59 | 5.81 | NaN  | NaN   | NaN  |
| 35 | X72736 | 0.693 | 2.05 | 5.02 | 39.6 | 15.55 | 3.94 |

let us quantify the amount of missing data

```
material_df.isna().sum().divide(len(material_df)).round(4)*100
```

```
Sample      0.00
size1       2.78
size2       2.78
size3       2.78
density1    27.78
density2    27.78
density3    27.78
dtype: float64
```

Unfortunately that is a lot of missing data, covered in all records, dropping here seems almost impossible if we want to keep a healthy amount of records.

Here it would be wise to go for a more elaborate method of imputation, I opted for the K-nearest neighbours method, which looks at the K most similar records in the dataset to make an educated guess on what the missing value could be, this because we can assume that records with similar data are also similar over all the properties (columns).

Im using the sklearn library for this, which has more imputation techniques such as MICE. More info can be found [here](#)

```
from sklearn.impute import KNNImputer
```

im creating an imputer object and specify that i want to use the 5 most similar records and weigh them by distance from the to imputed record, meaning closer neighbours are more important.

```
imputer = KNNImputer(n_neighbors=5, weights="distance")
```

As the imputer only takes numerical values I had to do some pandas magic and drop the first column, which I then added again. The result is a fully filled dataset, you can recognise the new values as they are not rounded.

```
pd.DataFrame(
    imputer.fit_transform(material_df.drop(columns=['Sample'])),
    columns=material_df.columns.drop('Sample')
)
```

|    | size1    | size2    | size3    | density1  | density2  | density3 |
|----|----------|----------|----------|-----------|-----------|----------|
| 0  | 0.696000 | 2.690000 | 6.380000 | 41.800000 | 17.180000 | 3.900000 |
| 1  | 0.636000 | 2.300000 | 5.140000 | 38.100000 | 12.730000 | 3.890000 |
| 2  | 0.841000 | 2.850000 | 5.200000 | 37.600000 | 13.580000 | 3.980000 |
| 3  | 0.609000 | 2.130000 | 4.620000 | 34.200000 | 11.120000 | 4.020000 |
| 4  | 0.684000 | 2.160000 | 4.870000 | 36.400000 | 12.240000 | 3.920000 |
| 5  | 0.762000 | 2.810000 | 6.360000 | 38.100000 | 13.280000 | 3.890000 |
| 6  | 0.552000 | 2.340000 | 5.030000 | 41.300000 | 16.710000 | 3.860000 |
| 7  | 0.501000 | 2.170000 | 5.090000 | 38.495282 | 14.029399 | 3.931180 |
| 8  | 0.619000 | 2.110000 | 5.130000 | 37.405275 | 13.157346 | 3.943667 |
| 9  | 0.610000 | 2.100000 | 4.180000 | 35.000000 | 12.150000 | 3.860000 |
| 10 | 0.532000 | 2.090000 | 4.930000 | 37.811132 | 13.646072 | 3.908364 |
| 11 | 0.738000 | 2.290000 | 5.470000 | 37.088833 | 13.255412 | 3.941654 |
| 12 | 0.779000 | 2.620000 | 5.590000 | 36.540567 | 12.889902 | 3.970973 |
| 13 | 0.537000 | 2.230000 | 5.410000 | 35.200000 | 11.340000 | 3.990000 |
| 14 | 0.702000 | 2.050000 | 5.100000 | 34.200000 | 10.540000 | 4.020000 |
| 15 | 0.768000 | 2.510000 | 5.090000 | 34.900000 | 12.550000 | 3.900000 |
| 16 | 0.714000 | 2.560000 | 6.030000 | 35.600000 | 12.200000 | 4.020000 |
| 17 | 0.621000 | 2.420000 | 5.100000 | 38.700000 | 14.270000 | 3.980000 |
| 18 | 0.726000 | 2.110000 | 4.690000 | 37.100000 | 13.140000 | 3.980000 |
| 19 | 0.698000 | 2.360000 | 5.400000 | 36.600000 | 12.160000 | 4.010000 |
| 20 | 0.733097 | 2.653959 | 5.881504 | 38.100000 | 13.340000 | 3.890000 |
| 21 | 0.759000 | 2.470000 | 4.830000 | 38.700000 | 14.830000 | 3.890000 |
| 22 | 0.535000 | 2.130000 | 5.230000 | 37.391815 | 13.089536 | 3.944335 |
| 23 | 0.716000 | 2.290000 | 5.450000 | 37.300000 | 13.700000 | 3.920000 |
| 24 | 0.635000 | 2.080000 | 4.940000 | 37.254724 | 13.206262 | 3.933904 |
| 25 | 0.598000 | 2.120000 | 4.690000 | 37.900000 | 13.450000 | 3.780000 |
| 26 | 0.700000 | 2.470000 | 5.220000 | 38.800000 | 14.720000 | 3.920000 |
| 27 | 0.957000 | 2.960000 | 7.370000 | 36.200000 | 13.380000 | 4.200000 |
| 28 | 0.759000 | 2.660000 | 5.360000 | 35.200000 | 12.190000 | 3.980000 |
| 29 | 0.661000 | 2.100000 | 4.270000 | 36.172345 | 12.755632 | 3.887375 |
| 30 | 0.646000 | 2.380000 | 4.510000 | 40.100000 | 15.680000 | 3.860000 |
| 31 | 0.662000 | 2.340000 | 4.710000 | 35.000000 | 12.370000 | 3.900000 |
| 32 | 0.749000 | 2.430000 | 5.160000 | 37.300000 | 13.040000 | 3.920000 |
| 33 | 0.598000 | 2.210000 | 4.900000 | 37.865882 | 13.826029 | 3.887021 |
| 34 | 0.619000 | 2.590000 | 5.810000 | 35.932339 | 12.318210 | 3.989911 |
| 35 | 0.693000 | 2.050000 | 5.020000 | 39.600000 | 15.550000 | 3.940000 |

This concludes the part of missing values, perhaps you can try yourself and impute the missing values for the FuelEconomy using the SimpleImputer or even the IterativeImputer.

## CONCATENATION AND DEDUPLICATION

In this notebook we are going to investigate the concepts of stitching data files (concatenation) and verifying the integrity of our data concerning duplicates

### 4.1 Concatenation

When dealing with large amounts of data, fractioning is often the only solution. Not only does this tidy up your data space, but it also benefits computation. Aside from that, appending new data to your data lake is independent of the historical data. However if you want to perform historical analysis this means you will need to perform additional operations.

In this notebook we have a setup of a very small data lake containing daily minimal temperatures. If you would look closely in the url you would see the following structure.

data/temperature/australia/melbourne/1981.csv

This is a straight-forward but perfect example on how fragmentation works, in our data lake we have: temperatures data fractioned by country, city and year. As we are working with daily temperatures further fractioning would not be interesting, but you could fraction e.g. per month.

In the cells below, we read our both 1981 and 1982 data and concatenate them using python.

```
import pandas as pd
```

```
melbourne_1981_df = pd.read_csv('https://raw.githubusercontent.com/LorenzF/data-science-practical-approach/main/src/c2_data_preparation/data/temperatures/australia/melbourne/1981.csv')
```

```
melbourne_1982_df = pd.read_csv('https://raw.githubusercontent.com/LorenzF/data-science-practical-approach/main/src/c2_data_preparation/data/temperatures/australia/melbourne/1982.csv')
```

```
df = pd.concat([
    melbourne_1981_df,
    melbourne_1982_df,
])
```

```
df
```

```
      Date  Temp
0  1981-01-01  20.7
1  1981-01-02  17.9
2  1981-01-03  18.8
3  1981-01-04  14.6
4  1981-01-05  15.8
..      ...    ...
360 1982-12-27  15.3
361 1982-12-28  16.3
362 1982-12-29  15.8
363 1982-12-30  17.7
364 1982-12-31  16.3
```

```
[730 rows x 2 columns]
```

And there you have it! we now have a dataframe containing both data from 1981 as 1982. Can you figure out what I calculated in the next cell? Do you think there might be a more ‘clean’ solution?

```
df[df.Date.str[5:7]=='01'].Temp.mean()
```

```
17.140322580645158
```

As an exercise I would ask you now to create a small python script that given a begin and end year (between 1981 and 1990) can automatically concatenate all the necessary data

```
for i in range(1982,1987):
    print(i)
```

```
1982
1983
1984
1985
1986
```

## 4.2 Deduplication

Another important aspect of data cleaning is the removal of duplicates. Here we fragment of a dataset from activity on a popular games platform. We can see which user has either bought or played specific games and how often. Unfortunately for some reason, entries might have duplicates which we have to deal with as otherwise users might have e.g. bought a game twice.

```
df = pd.read_csv('https://raw.githubusercontent.com/LorenzF/data-science-practical-
->approach/main/src/c2_data_preparation/data/steam.csv')
df
```

```
   user_id      game      action  freq
0  11373749  Sid Meier's Civilization IV  purchase    1.0
1  11373749  Sid Meier's Civilization IV    play    0.1
2  11373749  Sid Meier's Civilization IV  purchase    1.0
3  11373749  Sid Meier's Civilization IV Beyond the Sword  purchase    1.0
4  11373749  Sid Meier's Civilization IV Beyond the Sword  purchase    1.0
...      ...      ...      ...    ...
1834 112845094      Arma 2  purchase    1.0
```

(continues on next page)

(continued from previous page)

|      |           |                              |          |     |
|------|-----------|------------------------------|----------|-----|
| 1835 | 112845094 | Grand Theft Auto San Andreas | purchase | 1.0 |
| 1836 | 112845094 | Grand Theft Auto Vice City   | purchase | 1.0 |
| 1837 | 112845094 | Grand Theft Auto Vice City   | purchase | 1.0 |
| 1838 | 112845094 | Grand Theft Auto III         | purchase | 1.0 |

[1839 rows x 4 columns]

We have a dataframe with 1839 interactions, you can see that the freq either notes the amount they bought (which always 1 as there is not use in buying it more) or the amount in hours they played.

Let us straightforward ask pandas to remove all rows that have an exact duplicate

```
df.drop_duplicates()
```

|      | user_id   | game   | action   | freq |
|------|-----------|--|----------|------|
| 0    | 11373749  | Sid Meier's Civilization IV                  | purchase | 1.0  |
| 1    | 11373749  | Sid Meier's Civilization IV                  | play     | 0.1  |
| 3    | 11373749  | Sid Meier's Civilization IV Beyond the Sword | purchase | 1.0  |
| 5    | 11373749  | Sid Meier's Civilization IV Warlords         | purchase | 1.0  |
| 7    | 56038151  | Tom Clancy's H.A.W.X. 2                      | purchase | 1.0  |
| ...  | ...       | ...  | ...      | ...  |
| 1831 | 112845094 | Grand Theft Auto San Andreas                 | purchase | 1.0  |
| 1832 | 112845094 | Grand Theft Auto San Andreas                 | play     | 0.2  |
| 1833 | 112845094 | Grand Theft Auto III                         | purchase | 1.0  |
| 1834 | 112845094 | Arma 2                                       | purchase | 1.0  |
| 1836 | 112845094 | Grand Theft Auto Vice City                   | purchase | 1.0  |

[1132 rows x 4 columns]

Alright! this seemed to have dropped 707 rows from our dataset, but we would like to know more about those. Let's ask which rows the algorithm has dropped:

```
df[df.duplicated()]
```

|      | user_id   | game   | action   | freq |
|------|-----------|--|----------|------|
| 2    | 11373749  | Sid Meier's Civilization IV                  | purchase | 1.0  |
| 4    | 11373749  | Sid Meier's Civilization IV Beyond the Sword | purchase | 1.0  |
| 6    | 11373749  | Sid Meier's Civilization IV Warlords         | purchase | 1.0  |
| 10   | 56038151  | Grand Theft Auto San Andreas                 | purchase | 1.0  |
| 12   | 56038151  | Grand Theft Auto Vice City                   | purchase | 1.0  |
| ...  | ...       | ...  | ...      | ...  |
| 1827 | 39146470  | Sid Meier's Civilization IV Warlords         | purchase | 1.0  |
| 1830 | 48666962  | Crysis 2                                     | purchase | 1.0  |
| 1835 | 112845094 | Grand Theft Auto San Andreas                 | purchase | 1.0  |
| 1837 | 112845094 | Grand Theft Auto Vice City                   | purchase | 1.0  |
| 1838 | 112845094 | Grand Theft Auto III                         | purchase | 1.0  |

[707 rows x 4 columns]

Here we can see the duplicates, no particular pattern seems to be present, we could just for curiosity count the games that are duplicated

```
df[df.duplicated()].game.value_counts()
```

|                              |     |
|------------------------------|-----|
| Grand Theft Auto San Andreas | 172 |
| Grand Theft Auto Vice City   | 103 |

(continues on next page)

(continued from previous page)

|  |    |
|--|----|
| Sid Meier's Civilization IV                  | 98 |
| Grand Theft Auto III                         | 90 |
| Sid Meier's Civilization IV Beyond the Sword | 80 |
| Sid Meier's Civilization IV Warlords         | 79 |
| Sid Meier's Civilization IV Colonization     | 75 |
| Crysis 2                                     | 7  |
| Arma 2                                       | 1  |
| Tom Clancy's H.A.W.X. 2                      | 1  |
| TERA   | 1  |
| Name: game, dtype: int64                     |    |

It seems there are some games which are very prone to being duplicated, at this point we could go and ask the IT department why these games are acting weird.

Another thing im interested about is the perspective of a single gamer, here we took a single user\_id and printed all his games

```
df[df.user_id == 11373749]
```

|   | user_id  | game   | action   | freq |
|---|----------|--|----------|------|
| 0 | 11373749 | Sid Meier's Civilization IV                  | purchase | 1.0  |
| 1 | 11373749 | Sid Meier's Civilization IV                  | play     | 0.1  |
| 2 | 11373749 | Sid Meier's Civilization IV                  | purchase | 1.0  |
| 3 | 11373749 | Sid Meier's Civilization IV Beyond the Sword | purchase | 1.0  |
| 4 | 11373749 | Sid Meier's Civilization IV Beyond the Sword | purchase | 1.0  |
| 5 | 11373749 | Sid Meier's Civilization IV Warlords         | purchase | 1.0  |
| 6 | 11373749 | Sid Meier's Civilization IV Warlords         | purchase | 1.0  |

Ah, you can see all of his three games are somehow duplicated in purchase, also it seems he only played one of them for only 0.1 hours. Looks like he fell to the bait of a tempting summer sale but didn't realise he had no time to actually play it.

Another thing I would like to mention here is that this dataset would make a fine recommender system as it contains user ids and hours played. Add game metadata (description) and reviews to the mix and your data preparation is done!

We can remove all duplicates now by overwriting our dataframe

```
df = df.drop_duplicates()
```

One thing still bothers me, as hours played can change over time it might be that different snapshots have produced different values, therefore more duplicates might be present with different hours\_played.

Time to investigate this by using a subset of columns in the drop\_duplicates algorithm

```
df.drop_duplicates(subset=['user_id', 'game', 'action'])
```

|      | user_id   | game   | action   | freq |
|------|-----------|--|----------|------|
| 0    | 11373749  | Sid Meier's Civilization IV                  | purchase | 1.0  |
| 1    | 11373749  | Sid Meier's Civilization IV                  | play     | 0.1  |
| 3    | 11373749  | Sid Meier's Civilization IV Beyond the Sword | purchase | 1.0  |
| 5    | 11373749  | Sid Meier's Civilization IV Warlords         | purchase | 1.0  |
| 7    | 56038151  | Tom Clancy's H.A.W.X. 2                      | purchase | 1.0  |
| ...  | ...       | ...  | ...      | ...  |
| 1831 | 112845094 | Grand Theft Auto San Andreas                 | purchase | 1.0  |
| 1832 | 112845094 | Grand Theft Auto San Andreas                 | play     | 0.2  |
| 1833 | 112845094 | Grand Theft Auto III                         | purchase | 1.0  |
| 1834 | 112845094 | Arma 2                                       | purchase | 1.0  |

(continues on next page)



(continued from previous page)

```
1836 112845094          Grand Theft Auto Vice City  purchase    1.0

[1120 rows x 4 columns]
```

Seems we have shaved off another 12 records, so our intuition was right, again lets see which the duplicates are:

```
df[df.duplicated(subset=['user_id', 'game', 'action'])]
```

|      | user_id   | game   | action | freq |
|------|-----------|--|--------|------|
| 118  | 118664413 | Grand Theft Auto San Andreas                 | play   | 0.2  |
| 458  | 50769696  | Grand Theft Auto San Andreas                 | play   | 3.1  |
| 521  | 71411882  | Grand Theft Auto III                         | play   | 0.2  |
| 607  | 33865373  | Sid Meier's Civilization IV                  | play   | 2.0  |
| 898  | 71510748  | Grand Theft Auto San Andreas                 | play   | 0.2  |
| 908  | 28472068  | Grand Theft Auto Vice City                   | play   | 0.4  |
| 910  | 28472068  | Grand Theft Auto San Andreas                 | play   | 0.2  |
| 912  | 28472068  | Grand Theft Auto III                         | play   | 0.1  |
| 1506 | 59925638  | Tom Clancy's H.A.W.X. 2                      | play   | 0.3  |
| 1553 | 148362155 | Grand Theft Auto San Andreas                 | play   | 12.5 |
| 1709 | 176261926 | Sid Meier's Civilization IV Beyond the Sword | play   | 0.4  |
| 1711 | 176261926 | Sid Meier's Civilization IV                  | play   | 0.2  |

As expected the duplicates are all in the 'play' action, to complete our view we extract the data of a single user

```
df[df.user_id==118664413]
```

|     | user_id   | game                         | action   | freq |
|-----|-----------|------------------------------|----------|------|
| 115 | 118664413 | Grand Theft Auto San Andreas | purchase | 1.0  |
| 116 | 118664413 | Grand Theft Auto San Andreas | play     | 1.9  |
| 118 | 118664413 | Grand Theft Auto San Andreas | play     | 0.2  |

It looks like we have a problem now, we know these are duplicates and should be removed, but which one? Personally I would argue here that we keep the highest value, as it is impossible to 'unplay' hours on the game. I will leave this as an exercise for you, but the solution is pretty tricky so i'll give a hint:

The algorithm always keeps the first record in case of duplicates, so you could sort the rows making sure the higher value is always encountered first, good luck!



## OUTLIERS AND VALIDITY

When preparing data we have to be cautious with the accuracy of our set. Outliers and invalid data points are difficult to detect but should be handled with caution.

we start out by importing our most important library.

```
import pandas as pd
```

### 5.1 Silicon wafer thickness

Our first dataset contains information about the production of silicon wafers, each wafers thickness is measure on 9 different spots. More information on the dataset can be found [here](#).

```
wafer_df = pd.read_csv('https://raw.githubusercontent.com/LorenzF/data-science-  
practical-approach/main/src/c2_data_preparation/data/silicon-wafer-thickness.csv')  
wafer_df.head()
```

|   | G1    | G2    | G3     | G4    | G5    | G6     | G7     | G8     | G9     |
|---|-------|-------|--------|-------|-------|--------|--------|--------|--------|
| 0 | 0.175 | 0.188 | -0.159 | 0.095 | 0.374 | -0.238 | -0.800 | 0.158  | -0.211 |
| 1 | 0.102 | 0.075 | 0.141  | 0.180 | 0.138 | -0.057 | -0.075 | 0.072  | 0.072  |
| 2 | 0.607 | 0.711 | 0.879  | 0.765 | 0.592 | 0.187  | 0.431  | 0.345  | 0.187  |
| 3 | 0.774 | 0.823 | 0.619  | 0.370 | 0.725 | 0.439  | -0.025 | -0.259 | 0.496  |
| 4 | 0.504 | 0.644 | 0.845  | 0.681 | 0.502 | 0.151  | 0.404  | 0.296  | 0.260  |

we would like to investigate the distribution of measurements here, as we are early in this course using visualisation techniques would be too soon. This does not mean we can't use simple mathematics, introducing the InterQuartile Range. A reason for using IQR over standard deviation is that with IQR we do not assume a normal distribution. The IQR calculates the range between the bottom 'quart' or 25% and the top 25%, giving us an indication of the spread of our results, we calculate this IQR for each of the 9 measurements independently. For more info about IQR you can visit [wikipedia](#).

```
iqr = wafer_df.quantile(0.75)-wafer_df.quantile(0.25)  
iqr
```

```
G1    0.54425  
G2    0.61000  
G3    0.54075  
G4    0.52475  
G5    0.61175  
G6    0.86750  
G7    0.76175
```

(continues on next page)

(continued from previous page)

```
G8    0.87225
G9    0.86300
dtype: float64
```

you can see that the IQR spread for each measurement lays between 0.5 and 1 unit indicating that the 9 measurements of the wafer have a similar spread. With these IQR's we could calculate for each point relative to the spread of the measurement how far it is from the median.

```
relative_spread_df = (wafer_df-wafer_df.median())/iqr
relative_spread_df.head()
```

```
      G1      G2      G3      G4      G5      G6      G7  \
0 -0.011024 -0.077869 -0.819233 -0.367794  0.176543 -0.352738 -1.029865
1 -0.145154 -0.263115 -0.264448 -0.205812 -0.209236 -0.144092 -0.078110
2  0.782729  0.779508  1.100324  0.909004  0.532897  0.137176  0.586150
3  1.089573  0.963115  0.619510  0.156265  0.750306  0.427666 -0.012471
4  0.593477  0.669672  1.037448  0.748928  0.385779  0.095677  0.550706

      G8      G9
0 -0.130696 -0.254925
1 -0.229292  0.073001
2  0.083692  0.206257
3 -0.608770  0.564311
4  0.027515  0.290846
```

You can now see that some points are close to the median, whilst others are much higher, both positive as negative. By defining a threshold, we quantify what deviation has to be there to flag a reading as an outlier. The high outliers are separated, note that only a single measurement of the 9 can trigger and render the total measurement as an outlier. Yet judging from the setup where we would want to find wafers with varying thickness that approach is desirable.

```
relative_spread_df[(relative_spread_df>2).any(axis='columns')]
```

```
      G1      G2      G3      G4      G5      G6  \
8    2.232430  2.009016  1.956542  1.589328  1.843890  1.544669
38   12.891135  12.827049  12.832178  13.913292  11.429506  9.500865
39    3.691318  3.981148  3.774387  4.081944  3.248059  3.729107
61    2.010106  2.153279  1.987980  1.863745  1.858602  1.274928
110   3.678457  2.841803  3.204808  3.180562  2.669391  0.518732
112   2.361047  2.086066  2.363384  2.107670  1.925623  1.238040
117   1.475425  1.043443  2.154415  2.582182  0.653862  1.823631
120   1.791456  1.484426  2.583449  1.440686  2.085819  0.990202
121   1.791456  1.484426  2.583449  1.440686  2.085819  0.990202
152   2.610932  2.102459  2.387425  2.549786  2.169187  1.730259
154  -0.529169 -0.538525 -0.404993 -0.331586 -0.552513  4.565994

      G7      G8      G9
8    1.233344  0.419604  1.582851
38   10.305875  9.927200  9.055620
39    3.304890  3.846374  3.149479
61    1.237283  0.825451  0.955968
110   0.700361  0.176555  0.727694
112   1.766328  0.890800  1.377752
117   1.581227  0.857552  1.188876
120   1.782081  1.034107  1.822711
121   1.782081  1.034107  1.822711
```

(continues on next page)

(continued from previous page)

```
152  2.241549  1.713958  1.592121
154  -0.051854 -0.382918 -0.536501
```

seems we have a few high outliers, you can clearly see the measurements are mostly all across the board high, but in some cases (e.g. id 154) only one measurement was an outlier. We can do the same for the low outliers.

```
relative_spread_df[(relative_spread_df<-2).any(axis='columns')]
```

```

      G1      G2      G3      G4      G5      G6      G7  \
54  -1.550758 -1.525410 -1.843736 -2.082897 -1.659174 -1.203458 -1.184772
56  -1.732660 -1.510656 -2.121128 -2.122916 -1.781774 -1.521614 -1.909419
59  -1.971520 -1.310656 -2.328248 -1.175798 -2.067838 -0.915274 -1.783394
64  -1.234727 -1.361475 -0.736015 -1.055741 -2.224765 -0.839193 -0.679357
65  -2.226918 -1.194262 -2.117429 -2.161029 -2.043318 -0.190202 -1.004923
102 -2.484153 -2.330328 -1.568192 -2.808957 -1.945239 -1.340634 -0.846078

      G8      G9
54  -1.650903 -1.245655
56  -1.782746 -1.159907
59  -1.304672 -1.514484
64  -0.865578 -0.663963
65  -0.270565 -0.794902
102 -1.691029 -0.887601
```

For a simple mathematical equation these result look promising, yet it can always be more sophisticated. Not going to deep into the subject we could perform some Machine Learning, using a unsupervised method. Here we use the sklearn library which contains the Isolation forest algorithm. More info about the algorithm [here](#).

```
from sklearn.ensemble import IsolationForest
```

We first create the classifier and train (fit) it with the generic wafer data. Then for each record of the wafer data we make a prediction, if it thinks its an outlier, we keep them

```
clf = IsolationForest(random_state=0).fit(wafer_df)
wafer_df[clf.predict(wafer_df)==-1]
```

```

      G1      G2      G3      G4      G5      G6      G7      G8      G9
8      1.396  1.461  1.342  1.122  1.394  1.408  0.924  0.638  1.375
20    -0.558 -0.705 -0.526 -0.412 -0.753 -0.998 -0.270  0.598 -1.416
38      7.197  8.060  7.223  7.589  7.258  8.310  7.835  8.931  7.824
39      2.190  2.664  2.325  2.430  2.253  3.303  2.502  3.627  2.727
54    -0.663 -0.695 -0.713 -0.805 -0.749 -0.976 -0.918 -1.168 -1.066
56    -0.762 -0.686 -0.863 -0.826 -0.824 -1.252 -1.470 -1.283 -0.992
59    -0.892 -0.564 -0.975 -0.329 -0.999 -0.726 -1.374 -0.866 -1.298
61      1.275  1.549  1.359  1.266  1.403  1.174  0.927  0.992  0.834
65    -1.031 -0.493 -0.861 -0.846 -0.984 -0.097 -0.781  0.036 -0.677
102   -1.171 -1.186 -0.564 -1.186 -0.924 -1.095 -0.660 -1.203 -0.757
106   -0.659 -0.451 -0.692 -0.708 -0.595 -0.726 -1.031 -0.877 -1.080
110    2.183  1.969  2.017  1.957  1.899  0.518  0.518  0.426  0.637
112    1.466  1.508  1.562  1.394  1.444  1.142  1.330  1.049  1.198
117    0.984  0.872  1.449  1.643  0.666  1.650  1.189  1.020  1.035
120    1.156  1.141  1.681  1.044  1.542  0.927  1.342  1.174  1.582
121    1.156  1.141  1.681  1.044  1.542  0.927  1.342  1.174  1.582
152    1.602  1.518  1.575  1.626  1.593  1.569  1.692  1.767  1.383
```

Comparing the results with our IQR approach we see a lot of similarities, here the id 154 record did not show up as we

already realised this was perhaps not a strong enough outlier. You could enhance our IQR technique by checking the amount of measurements that are above the threshold and respond accordingly, I will leave you a little hint.

```
(relative_spread_df>2).sum()
```

```
G1    7
G2    7
G3    8
G4    6
G5    6
G6    3
G7    3
G8    2
G9    2
dtype: int64
```

## 5.2 Distillation column

As an exercise you can try the same technique to this dataset and see what you would find, good luck! Be mindful that you do not incorporate the date as a variable in your outlier algorithm.

```
distil_df = pd.read_csv('https://raw.githubusercontent.com/LorenzF/data-science-
practical-approach/main/src/c2_data_preparation/data/distillation-tower.csv')
distil_df
```

|     | Date       | Temp1    | FlowC1     | Temp2    | TempC1       | Temp3          | TempC2   | \       |   |
|-----|------------|----------|------------|----------|--------------|----------------|----------|---------|---|
| 0   | 2000-08-21 | 139.9857 | 432.0636   | 377.8119 | 100.2204     | 492.1353       | 490.1459 |         |   |
| 1   | 2000-08-23 | 131.0470 | 487.4029   | 371.3060 | 100.2297     | 482.2100       | 480.3128 |         |   |
| 2   | 2000-08-26 | 118.2666 | 437.3516   | 378.4483 | 100.3084     | 488.7266       | 487.0040 |         |   |
| 3   | 2000-08-29 | 118.1769 | 481.8314   | 378.0028 | 95.5766      | 493.1481       | 491.1137 |         |   |
| 4   | 2000-08-30 | 120.7891 | 412.6471   | 377.8871 | 92.9052      | 490.2486       | 488.6641 |         |   |
| ..  | ...        | ...      | ...        | ...      | ...          | ...            | ...      |         |   |
| 248 | 2003-01-26 | 130.8138 | 212.6385   | 341.5964 | 121.4354     | 468.3401       | 467.0299 |         |   |
| 249 | 2003-01-28 | 128.9673 | 225.1412   | 349.8965 | 118.8604     | 479.7665       | 478.4652 |         |   |
| 250 | 2003-01-31 | 130.5328 | 223.5965   | 345.9366 | 120.4027     | 474.5378       | 473.1145 |         |   |
| 251 | 2003-02-03 | 128.5248 | 213.5613   | 343.4950 | 119.6989     | 469.3802       | 467.9954 |         |   |
| 252 | 2003-02-04 | 131.0491 | 217.4117   | 346.1960 | 119.0825     | 474.6599       | 473.0381 |         |   |
|     | TempC3     | Temp4    | PressureC1 | ...      | Temp10       | FlowC3         | FlowC4   | Temp11  | \ |
| 0   | 180.5578   | 187.4331 | 215.0627   | ...      | 513.9653     | 8.6279         | 10.5988  | 30.8983 |   |
| 1   | 172.6575   | 179.5089 | 205.0999   | ...      | 504.5145     | 8.7662         | 10.7560  | 31.9099 |   |
| 2   | 165.9400   | 172.9262 | 205.0304   | ...      | 508.9997     | 8.5319         | 10.5737  | 29.9165 |   |
| 3   | 167.2085   | 174.2338 | 205.2561   | ...      | 514.1794     | 8.6260         | 10.6695  | 30.6229 |   |
| 4   | 167.0326   | 173.9681 | 205.0883   | ...      | 511.0948     | 8.5939         | 10.4922  | 29.4977 |   |
| ..  | ...        | ...      | ...        | ...      | ...          | ...            | ...      | ...     |   |
| 248 | 174.7639   | 180.7649 | 229.7393   | ...      | 479.0290     | 5.5590         | 6.4470   | 16.4131 |   |
| 249 | 176.2176   | 182.3646 | 230.5049   | ...      | 491.2362     | 5.6342         | 6.4360   | 17.2385 |   |
| 250 | 176.3310   | 182.2578 | 230.6638   | ...      | 485.8786     | 5.4810         | 6.3575   | 16.9866 |   |
| 251 | 174.6435   | 180.5093 | 230.5226   | ...      | 480.2879     | 5.4727         | 6.4175   | 16.6778 |   |
| 252 | 177.1088   | 183.1810 | 225.6420   | ...      | 486.0253     | 5.4597         | 6.3291   | 16.8766 |   |
|     | Temp12     | InvTemp1 | InvTemp2   | InvTemp3 | InvPressure1 | VapourPressure |          |         |   |
| 0   | 489.9900   | 2.0409   | 2.6468     | 2.1681   | 4.3524       | 32.5026        |          |         |   |
| 1   | 480.2888   | 2.0821   | 2.6932     | 2.2207   | 4.5497       | 34.8598        |          |         |   |

(continues on next page)

(continued from previous page)

|                         |          |        |        |        |        |         |
|-------------------------|----------|--------|--------|--------|--------|---------|
| 2                       | 486.6190 | 2.0550 | 2.6424 | 2.1796 | 4.5511 | 32.1666 |
| 3                       | 491.1304 | 2.0361 | 2.6455 | 2.1620 | 4.5464 | 30.4064 |
| 4                       | 487.6475 | 2.0507 | 2.6463 | 2.1704 | 4.5499 | 30.9238 |
| ..                      | ...      | ...    | ...    | ...    | ...    | ...     |
| 248                     | 466.3347 | 2.1444 | 2.9274 | 2.2127 | 4.0911 | 38.8507 |
| 249                     | 477.8816 | 2.0926 | 2.8580 | 2.1620 | 4.0783 | 34.2653 |
| 250                     | 472.3176 | 2.1172 | 2.8907 | 2.1855 | 4.0756 | 36.5717 |
| 251                     | 467.0001 | 2.1413 | 2.9113 | 2.2090 | 4.0780 | 38.1054 |
| 252                     | 472.2701 | 2.1174 | 2.8885 | 2.1844 | 4.1608 | 35.6298 |
| [253 rows x 28 columns] |          |        |        |        |        |         |





## STRING OPERATIONS



## DATETIME OPERATIONS

When our dataset contains time-related data, datetime operations are a great asset to our data science toolkit. For this exercise we obtain a public covid dataset containing A LOT of information on infection cases, deaths, tests and vaccinations.

Let's start by importing the data, as the dataset is about 60MB at the time of writing, this might take some time. Perhaps you could think of a method to make this more efficient, do we always need all of the data?

More info about the data can be found [here](#)

```
import pandas as pd
```

```
covid_df = pd.read_csv('https://raw.githubusercontent.com/owid/covid-19-data/master/
public/data/owid-covid-data.csv', on_bad_lines='skip')
covid_df.head()
```

```

iso_code  continent  location  date  total_cases  new_cases  \
0        AFG        Asia  Afghanistan  2020-02-24         5.0         5.0
1        AFG        Asia  Afghanistan  2020-02-25         5.0         0.0
2        AFG        Asia  Afghanistan  2020-02-26         5.0         0.0
3        AFG        Asia  Afghanistan  2020-02-27         5.0         0.0
4        AFG        Asia  Afghanistan  2020-02-28         5.0         0.0

new_cases_smoothed  total_deaths  new_deaths  new_deaths_smoothed  ...  \
0                NaN            NaN          NaN                NaN  ...
1                NaN            NaN          NaN                NaN  ...
2                NaN            NaN          NaN                NaN  ...
3                NaN            NaN          NaN                NaN  ...
4                NaN            NaN          NaN                NaN  ...

female_smokers  male_smokers  handwashing_facilities  \
0            NaN          NaN                    37.746
1            NaN          NaN                    37.746
2            NaN          NaN                    37.746
3            NaN          NaN                    37.746
4            NaN          NaN                    37.746

hospital_beds_per_thousand  life_expectancy  human_development_index  \
0                        0.5             64.83                0.511
1                        0.5             64.83                0.511
2                        0.5             64.83                0.511
3                        0.5             64.83                0.511
4                        0.5             64.83                0.511

excess_mortality_cumulative_absolute  excess_mortality_cumulative  \

```

(continues on next page)

(continued from previous page)

```

0          NaN          NaN
1          NaN          NaN
2          NaN          NaN
3          NaN          NaN
4          NaN          NaN

   excess_mortality  excess_mortality_cumulative_per_million
0             NaN             NaN
1             NaN             NaN
2             NaN             NaN
3             NaN             NaN
4             NaN             NaN

[5 rows x 65 columns]

```

As mentioned a lot of information is present here, about 65 columns. yet for this exercise my main objective is the 'date' column. If we would print out the data types using the info method, we can see that the date is recognized as an 'object' stating that it is an ordinary string, not a datetime.

```
covid_df.info()
```

```

<class 'pandas.core.frame.DataFrame'>
RangeIndex: 121744 entries, 0 to 121743
Data columns (total 65 columns):
#   Column                                     Non-Null Count  Dtype
---  -
0   iso_code                                121744 non-null  object
1   continent                              116202 non-null  object
2   location                               121744 non-null  object
3   date                                  121744 non-null  object
4   total_cases                           115518 non-null  float64
5   new_cases                             115515 non-null  float64
6   new_cases_smoothed                    114500 non-null  float64
7   total_deaths                          104708 non-null  float64
8   new_deaths                            104863 non-null  float64
9   new_deaths_smoothed                   114500 non-null  float64
10  total_cases_per_million                114910 non-null  float64
11  new_cases_per_million                  114907 non-null  float64
12  new_cases_smoothed_per_million         113897 non-null  float64
13  total_deaths_per_million               104113 non-null  float64
14  new_deaths_per_million                 104268 non-null  float64
15  new_deaths_smoothed_per_million        113897 non-null  float64
16  reproduction_rate                      98318 non-null  float64
17  icu_patients                           14443 non-null  float64
18  icu_patients_per_million               14443 non-null  float64
19  hosp_patients                           16504 non-null  float64
20  hosp_patients_per_million              16504 non-null  float64
21  weekly_icu_admissions                  1268 non-null   float64
22  weekly_icu_admissions_per_million      1268 non-null   float64
23  weekly_hosp_admissions                 2088 non-null   float64
24  weekly_hosp_admissions_per_million     2088 non-null   float64
25  new_tests                              52248 non-null  float64
26  total_tests                            52352 non-null  float64
27  total_tests_per_thousand               52352 non-null  float64
28  new_tests_per_thousand                 52248 non-null  float64
29  new_tests_smoothed                     62816 non-null  float64

```

(continues on next page)

(continued from previous page)

```

30 new_tests_smoothed_per_thousand      62816 non-null float64
31 positive_rate                        58959 non-null float64
32 tests_per_case                       58319 non-null float64
33 tests_units                          64746 non-null object
34 total_vaccinations                   28115 non-null float64
35 people_vaccinated                    26746 non-null float64
36 people_fully_vaccinated              23714 non-null float64
37 total_boosters                       3057 non-null float64
38 new_vaccinations                     23298 non-null float64
39 new_vaccinations_smoothed            50221 non-null float64
40 total_vaccinations_per_hundred       28115 non-null float64
41 people_vaccinated_per_hundred        26746 non-null float64
42 people_fully_vaccinated_per_hundred  23714 non-null float64
43 total_boosters_per_hundred           3057 non-null float64
44 new_vaccinations_smoothed_per_million 50221 non-null float64
45 stringency_index                     101767 non-null float64
46 population                           120880 non-null float64
47 population_density                   112501 non-null float64
48 median_age                           107423 non-null float64
49 aged_65_older                       106229 non-null float64
50 aged_70_older                       106834 non-null float64
51 gdp_per_capita                       108055 non-null float64
52 extreme_poverty                      72482 non-null float64
53 cardiovascular_death_rate            107695 non-null float64
54 diabetes_prevalence                  111063 non-null float64
55 female_smokers                        84078 non-null float64
56 male_smokers                         82858 non-null float64
57 handwashing_facilities               54111 non-null float64
58 hospital_beds_per_thousand           97911 non-null float64
59 life_expectancy                       115458 non-null float64
60 human_development_index              107790 non-null float64
61 excess_mortality_cumulative_absolute  4317 non-null float64
62 excess_mortality_cumulative           4317 non-null float64
63 excess_mortality                     4317 non-null float64
64 excess_mortality_cumulative_per_million 4317 non-null float64
dtypes: float64(60), object(5)
memory usage: 60.4+ MB

```

We would like to change that, as we can only perform datetime operations if pandas recognises the datetime format used. Good for us, pandas has a method to automatically infer the date format, we do that now.

```

covid_df.date = pd.to_datetime(covid_df.date)
covid_df.info()

```

```

<class 'pandas.core.frame.DataFrame'>
RangeIndex: 121744 entries, 0 to 121743
Data columns (total 65 columns):
#   Column                                Non-Null Count  Dtype
---  -
0   iso_code                             121744 non-null object
1   continent                             116202 non-null object
2   location                             121744 non-null object
3   date                                 121744 non-null datetime64[ns]
4   total_cases                          115518 non-null float64
5   new_cases                            115515 non-null float64
6   new_cases_smoothed                   114500 non-null float64

```

(continues on next page)

(continued from previous page)

|    |                                       |        |          |         |
|----|---------------------------------------|--------|----------|---------|
| 7  | total_deaths                          | 104708 | non-null | float64 |
| 8  | new_deaths                            | 104863 | non-null | float64 |
| 9  | new_deaths_smoothed                   | 114500 | non-null | float64 |
| 10 | total_cases_per_million               | 114910 | non-null | float64 |
| 11 | new_cases_per_million                 | 114907 | non-null | float64 |
| 12 | new_cases_smoothed_per_million        | 113897 | non-null | float64 |
| 13 | total_deaths_per_million              | 104113 | non-null | float64 |
| 14 | new_deaths_per_million                | 104268 | non-null | float64 |
| 15 | new_deaths_smoothed_per_million       | 113897 | non-null | float64 |
| 16 | reproduction_rate                     | 98318  | non-null | float64 |
| 17 | icu_patients                          | 14443  | non-null | float64 |
| 18 | icu_patients_per_million              | 14443  | non-null | float64 |
| 19 | hosp_patients                         | 16504  | non-null | float64 |
| 20 | hosp_patients_per_million             | 16504  | non-null | float64 |
| 21 | weekly_icu_admissions                 | 1268   | non-null | float64 |
| 22 | weekly_icu_admissions_per_million     | 1268   | non-null | float64 |
| 23 | weekly_hosp_admissions                | 2088   | non-null | float64 |
| 24 | weekly_hosp_admissions_per_million    | 2088   | non-null | float64 |
| 25 | new_tests                             | 52248  | non-null | float64 |
| 26 | total_tests                           | 52352  | non-null | float64 |
| 27 | total_tests_per_thousand              | 52352  | non-null | float64 |
| 28 | new_tests_per_thousand                | 52248  | non-null | float64 |
| 29 | new_tests_smoothed                    | 62816  | non-null | float64 |
| 30 | new_tests_smoothed_per_thousand       | 62816  | non-null | float64 |
| 31 | positive_rate                         | 58959  | non-null | float64 |
| 32 | tests_per_case                        | 58319  | non-null | float64 |
| 33 | tests_units                           | 64746  | non-null | object  |
| 34 | total_vaccinations                    | 28115  | non-null | float64 |
| 35 | people_vaccinated                     | 26746  | non-null | float64 |
| 36 | people_fully_vaccinated               | 23714  | non-null | float64 |
| 37 | total_boosters                        | 3057   | non-null | float64 |
| 38 | new_vaccinations                      | 23298  | non-null | float64 |
| 39 | new_vaccinations_smoothed             | 50221  | non-null | float64 |
| 40 | total_vaccinations_per_hundred        | 28115  | non-null | float64 |
| 41 | people_vaccinated_per_hundred         | 26746  | non-null | float64 |
| 42 | people_fully_vaccinated_per_hundred   | 23714  | non-null | float64 |
| 43 | total_boosters_per_hundred            | 3057   | non-null | float64 |
| 44 | new_vaccinations_smoothed_per_million | 50221  | non-null | float64 |
| 45 | stringency_index                      | 101767 | non-null | float64 |
| 46 | population                            | 120880 | non-null | float64 |
| 47 | population_density                    | 112501 | non-null | float64 |
| 48 | median_age                            | 107423 | non-null | float64 |
| 49 | aged_65_older                         | 106229 | non-null | float64 |
| 50 | aged_70_older                         | 106834 | non-null | float64 |
| 51 | gdp_per_capita                        | 108055 | non-null | float64 |
| 52 | extreme_poverty                       | 72482  | non-null | float64 |
| 53 | cardiovasc_death_rate                 | 107695 | non-null | float64 |
| 54 | diabetes_prevalence                   | 111063 | non-null | float64 |
| 55 | female_smokers                        | 84078  | non-null | float64 |
| 56 | male_smokers                          | 82858  | non-null | float64 |
| 57 | handwashing_facilities                | 54111  | non-null | float64 |
| 58 | hospital_beds_per_thousand            | 97911  | non-null | float64 |
| 59 | life_expectancy                       | 115458 | non-null | float64 |
| 60 | human_development_index               | 107790 | non-null | float64 |
| 61 | excess_mortality_cumulative_absolute  | 4317   | non-null | float64 |
| 62 | excess_mortality_cumulative           | 4317   | non-null | float64 |
| 63 | excess_mortality                      | 4317   | non-null | float64 |

(continues on next page)

(continued from previous page)

```

64 excess_mortality_cumulative_per_million 4317 non-null    float64
dtypes: datetime64[ns](1), float64(60), object(4)
memory usage: 60.4+ MB

```

now we are ready to perform datetime operations, however we can see that dates are appearing multiple times, this because we have records for multiple countries. I live in Belgium, so decided to isolate that subsection of the data. If they had used a data lake and partitioned into countries, reading out the data would have been much more efficient, but efficiency is not something I would expect from government as a Belgian.

```

covid_belgium_df = covid_df[covid_df.location=='Belgium'].set_index('date')
covid_belgium_df.head()

```

```

      iso_code continent location  total_cases  new_cases  \
date
2020-02-04      BEL    Europe  Belgium         1.0         1.0
2020-02-05      BEL    Europe  Belgium         1.0         0.0
2020-02-06      BEL    Europe  Belgium         1.0         0.0
2020-02-07      BEL    Europe  Belgium         1.0         0.0
2020-02-08      BEL    Europe  Belgium         1.0         0.0

      new_cases_smoothed  total_deaths  new_deaths  new_deaths_smoothed  \
date
2020-02-04           NaN           NaN           NaN           NaN
2020-02-05           NaN           NaN           NaN           NaN
2020-02-06           NaN           NaN           NaN           NaN
2020-02-07           NaN           NaN           NaN           NaN
2020-02-08           NaN           NaN           NaN           NaN

      total_cases_per_million  ...  female_smokers  male_smokers  \
date
2020-02-04           0.086  ...           25.1           31.4
2020-02-05           0.086  ...           25.1           31.4
2020-02-06           0.086  ...           25.1           31.4
2020-02-07           0.086  ...           25.1           31.4
2020-02-08           0.086  ...           25.1           31.4

      handwashing_facilities  hospital_beds_per_thousand  \
date
2020-02-04           NaN           5.64
2020-02-05           NaN           5.64
2020-02-06           NaN           5.64
2020-02-07           NaN           5.64
2020-02-08           NaN           5.64

      life_expectancy  human_development_index  \
date
2020-02-04          81.63           0.931
2020-02-05          81.63           0.931
2020-02-06          81.63           0.931
2020-02-07          81.63           0.931
2020-02-08          81.63           0.931

      excess_mortality_cumulative_absolute  excess_mortality_cumulative  \
date
2020-02-04           NaN           NaN
2020-02-05           NaN           NaN

```

(continues on next page)

(continued from previous page)

|                       |                  |   |
|-----------------------|------------------|---|
| 2020-02-06            | NaN              | NaN                                     |
| 2020-02-07            | NaN              | NaN                                     |
| 2020-02-08            | NaN              | NaN                                     |
|                       |                  |   |
|                       | excess_mortality | excess_mortality_cumulative_per_million |
| date                  |                  |   |
| 2020-02-04            | NaN              | NaN                                     |
| 2020-02-05            | NaN              | NaN                                     |
| 2020-02-06            | NaN              | NaN                                     |
| 2020-02-07            | NaN              | NaN                                     |
| 2020-02-08            | NaN              | NaN                                     |
| [5 rows x 64 columns] |                  |   |

Now that we have our dataset containing only Belgium I would like to emphasize another aspect, for features such as population density we would not expect a 'head count' to differ each day, and as we can see this number is steady over the whole line (results may vary for those who execute this in the future).

```
covid_belgium_df.population.value_counts()
```

```
11632334.0    611
Name: population, dtype: int64
```

we only have a single value (in my case 11.6M) that is repeated over the whole dataset, would this look optimal to you? How would you perhaps approach this to improve data management? If you would like to go hands-on I left you a blank cell to experiment.


Optimalizations aside, we can not do that which we came for! Datetime operations, the first thing that I have in mind is that due to weekends, the cases might fluctuate a lot per day, so it is not optimal to view it on a daily basis.

First we create a simple line plot with the raw daily cases, then we perform a weekly sum to create a more smooth version of the new cases.

```
covid_belgium_df['new_cases'].plot(title='daily cases are fluctuating')
```


```
<AxesSubplot:title={'center':'daily cases are fluctuating'}, xlabel='date'>
```





```
weekly_cases_df = covid_belgium_df['new_cases'].resample('W').sum()  
weekly_cases_df.plot(title='weekly cases are smoother')
```

```
<AxesSubplot:title={'center':'weekly cases are smoother'}, xlabel='date'>
```



That looks great! Those who inspected carefully saw that the x-axis was correctly identified as datetimes and that the y-axis for weekly sums have a much higher range.

In a next example we would like to have the relative changes from week to week, this can be done using the shift operation.


```
weekly_cases_df.shift(1)
```

```
date
2020-02-09      NaN
2020-02-16       1.0
2020-02-23       0.0
2020-03-01       0.0
2020-03-08       1.0
...
2021-09-12    14099.0
2021-09-19    13508.0
2021-09-26    14298.0
2021-10-03    13909.0
2021-10-10    13474.0
Freq: W-SUN, Name: new_cases, Length: 88, dtype: float64
```

This method shifted our data by 1 week forwards, this way we can subtract these results from our original data creating a relative increase (this\_week\_cases - last\_week\_cases).

```
(weekly_cases_df-weekly_cases_df.shift(1)).plot(title='relative increase p week')
```

```
<AxesSubplot:title={'center':'relative increase p week'}, xlabel='date'>
```



Another powerful asset of datetimes is that we can utilize the concepts of days, weeks, months and years. In Belgium they speak about a phenomenon called ‘the weekend effect’ where a lot of reports are delayed and therefore Sundays have less cases whereas Mondays have more.

Do we see that in our data? let us separate the Sundays and Mondays and take a mean!

```
print('mean deaths on Monday')
covid_belgium_df.loc[covid_belgium_df.index.dayofweek==0, "new_deaths"].mean()
```

```
mean deaths on Monday
```

```
39.02439024390244
```

```
print('mean deaths on Sunday')
covid_belgium_df.loc[covid_belgium_df.index.dayofweek==6, "new_deaths"].mean()
```

```
mean deaths on Sunday
```

```
36.646341463414636
```

It seems indeed that more people are reported to pass away on a Monday than on a Sunday, it would be optimal to verify this with statistics, but for now we keep it simple.

As a last example I would like to use slicing of our dataset to demonstrate we can also take a subset of our data and handle this, here we took the months of dec2020-jan2021 for Belgium and calculated the total deaths.

```
covid_belgium_df.loc['2020-12-01':'2021-01-31'].new_deaths.sum()
```

4447.0

Now let's compare this to our neighbours, the Netherlands and France, we do exactly the same operations by selecting exactly the same time window.

```
covid_netherlands_df = covid_df[covid_df.location=='Netherlands'].set_index('date')
covid_netherlands_df.loc['2020-12-01':'2021-01-31'].new_deaths.sum()
```

4655.0

```
covid_france_df = covid_df[covid_df.location=='France'].set_index('date')
covid_france_df.loc['2020-12-01':'2021-01-31'].new_deaths.sum()
```

23382.0

You can see that Belgium has the lowest of total deaths in that time interval, so you could assume we performed the best! However this approach is a bit simplified as there are not as many Belgians as French and Dutch. Could you perhaps think if an improvement to create a better understanding?

## CATEGORICAL ENCODING

Often we deal with categorical data and this kind of data is something computer algorithms are not able to understand. On the other hand long categorical features might take up unnecessary memory in our dataset, so converting to a categorical feature is optimal.

```
import pandas as pd
```

### 8.1 Raw Material Characterization

In this dataset, we have a few numerical features describing characteristics of our material, next to that we also have an Outcome feature describing the state of our material in a category.

Let's have a look at the data

```
raw_material_df = pd.read_csv('./data/raw-material-characterization.csv')
raw_material_df.head()
```

|   | Lot number | Outcome  | Size5 | Size10 | Size15 | TGA   | DSC  | TMA  |
|---|------------|----------|-------|--------|--------|-------|------|------|
| 0 | B370       | Adequate | 13.8  | 9.2    | 41.2   | 787.3 | 18.0 | 65.0 |
| 1 | B880       | Adequate | 11.2  | 5.8    | 27.6   | 772.2 | 17.7 | 68.8 |
| 2 | B452       | Adequate | 9.9   | 5.8    | 28.3   | 602.3 | 18.3 | 50.7 |
| 3 | B287       | Adequate | 10.4  | 4.0    | 24.7   | 677.9 | 17.7 | 56.5 |
| 4 | B576       | Adequate | 12.3  | 9.3    | 22.0   | 593.5 | 19.5 | 52.0 |

So we can see that the outcome is indeed a text field with a human interpretable value. The different values are:

```
raw_material_df.Outcome.unique()
```

```
array(['Adequate', 'Poor'], dtype=object)
```

Imagine that we would like to get all records where the Outcome is less than adequate, using strings this is not possible as the computer does not understand relations of Adequate and Poor when they are denoted as text.

```
raw_material_df[raw_material_df.Outcome<'Adequate']
```

```
Empty DataFrame
Columns: [Lot number, Outcome, Size5, Size10, Size15, TGA, DSC, TMA]
Index: []
```

To overcome this we can change the type of the feature from 'object' (string) to 'category' let us look at the data types of our data

```
raw_material_df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 24 entries, 0 to 23
Data columns (total 8 columns):
#   Column      Non-Null Count  Dtype
---  -
0   Lot number   24 non-null    object
1   Outcome      24 non-null    object
2   Size5        24 non-null    float64
3   Size10       24 non-null    float64
4   Size15       24 non-null    float64
5   TGA          24 non-null    float64
6   DSC          24 non-null    float64
7   TMA          24 non-null    float64
dtypes: float64(6), object(2)
memory usage: 1.6+ KB
```

Now we can change that of Outcome to category using the astype method

```
raw_material_df.Outcome = raw_material_df.Outcome.astype('category')
raw_material_df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 24 entries, 0 to 23
Data columns (total 8 columns):
#   Column      Non-Null Count  Dtype
---  -
0   Lot number   24 non-null    object
1   Outcome      24 non-null    category
2   Size5        24 non-null    float64
3   Size10       24 non-null    float64
4   Size15       24 non-null    float64
5   TGA          24 non-null    float64
6   DSC          24 non-null    float64
7   TMA          24 non-null    float64
dtypes: category(1), float64(6), object(1)
memory usage: 1.6+ KB
```

Our feature might be of categorical nature now, however we still have to define it is an ordinal category and has an order.

```
raw_material_df.Outcome = raw_material_df.Outcome.cat.as_ordered().cat.reorder_
    categories(['Poor', 'Adequate'])
```

If we retry to effort to only take the records where the Outcome is less than Adequate, we now get an outcome! Since we only have 2 categories this is a bit unfortunate, but you should get the idea behind it.

```
raw_material_df[raw_material_df.Outcome<'Adequate']
```

|    | Lot number | Outcome | Size5 | Size10 | Size15 | TGA   | DSC  | TMA  |
|----|------------|---------|-------|--------|--------|-------|------|------|
| 5  | B914       | Poor    | 13.7  | 7.8    | 27.0   | 597.9 | 18.1 | 49.8 |
| 6  | B404       | Poor    | 15.5  | 10.7   | 34.3   | 668.5 | 19.6 | 55.7 |
| 7  | B694       | Poor    | 15.4  | 10.7   | 35.9   | 602.8 | 19.2 | 53.6 |
| 8  | B875       | Poor    | 14.9  | 11.3   | 41.0   | 614.6 | 18.5 | 50.0 |
| 10 | B517       | Poor    | 16.1  | 11.6   | 39.2   | 682.8 | 17.5 | 56.4 |

(continues on next page)

(continued from previous page)

|    |      |      |      |     |      |       |      |      |
|----|------|------|------|-----|------|-------|------|------|
| 13 | B430 | Poor | 12.9 | 9.7 | 36.3 | 642.4 | 19.1 | 55.0 |
| 21 | B745 | Poor | 10.2 | 5.8 | 24.7 | 575.9 | 18.5 | 46.2 |

Let's take this a step further, since computer algorithms still have no idea what the numerical relation is between Adequate and Poor, we could use a Label Encoder for that.

```
from sklearn.preprocessing import LabelEncoder
```

the label encoder is inputted with the Outcome feature and recognises 2 types, it chooses a numerical value for each while fitting.

```
le = LabelEncoder()
le.fit(raw_material_df.Outcome)
```

```
LabelEncoder()
```

After fitting we can use this encoder to transform our dataset!

```
raw_material_df['outcome_label'] = le.transform(raw_material_df.Outcome)
raw_material_df.head()
```

|   | Lot number | Outcome  | Size5 | Size10 | Size15 | TGA   | DSC  | TMA  | \ |
|---|------------|----------|-------|--------|--------|-------|------|------|---|
| 0 | B370       | Adequate | 13.8  | 9.2    | 41.2   | 787.3 | 18.0 | 65.0 |   |
| 1 | B880       | Adequate | 11.2  | 5.8    | 27.6   | 772.2 | 17.7 | 68.8 |   |
| 2 | B452       | Adequate | 9.9   | 5.8    | 28.3   | 602.3 | 18.3 | 50.7 |   |
| 3 | B287       | Adequate | 10.4  | 4.0    | 24.7   | 677.9 | 17.7 | 56.5 |   |
| 4 | B576       | Adequate | 12.3  | 9.3    | 22.0   | 593.5 | 19.5 | 52.0 |   |

|   | outcome_label |
|---|---------------|
| 0 | 0             |
| 1 | 0             |
| 2 | 0             |
| 3 | 0             |
| 4 | 0             |

It seems something unfortunate has happened, the encoder gave the Adequate an outcome label of 0, which is lower than the label of Poor (1), this might be bad if we would like to give a score as our outcome.

There is in pandas another method of mapping a label to a category albeit less automated, as you would have to know the categories in your feature.

```
raw_material_df.outcome_label = raw_material_df.Outcome.map({'Poor': 0, 'Adequate': 1})
raw_material_df.head()
```

|   | Lot number | Outcome  | Size5 | Size10 | Size15 | TGA   | DSC  | TMA  | outcome_label |
|---|------------|----------|-------|--------|--------|-------|------|------|---------------|
| 0 | B370       | Adequate | 13.8  | 9.2    | 41.2   | 787.3 | 18.0 | 65.0 | 1             |
| 1 | B880       | Adequate | 11.2  | 5.8    | 27.6   | 772.2 | 17.7 | 68.8 | 1             |
| 2 | B452       | Adequate | 9.9   | 5.8    | 28.3   | 602.3 | 18.3 | 50.7 | 1             |
| 3 | B287       | Adequate | 10.4  | 4.0    | 24.7   | 677.9 | 17.7 | 56.5 | 1             |
| 4 | B576       | Adequate | 12.3  | 9.3    | 22.0   | 593.5 | 19.5 | 52.0 | 1             |

Yes! This did the trick, now we can use that outcome label to predict an outcome for future samples.





## RESTAURANT TIPS

Now we are going to look at a dataset of tips, here a restaurant tracked the table bills and tips for a few days in the week whilst also noting the gender, smoking habit and time of day. This led to a small yet very interesting dataset, let's have a look!

```
tips_df = pd.read_csv('https://raw.githubusercontent.com/mwaskom/seaborn-data/master/tips.csv')
tips_df
```

```
   total_bill  tip  sex smoker  day  time  size
0      16.99  1.01 Female    No  Sun  Dinner     2
1      10.34  1.66   Male    No  Sun  Dinner     3
2      21.01  3.50   Male    No  Sun  Dinner     3
3      23.68  3.31   Male    No  Sun  Dinner     2
4      24.59  3.61 Female    No  Sun  Dinner     4
..         ...   ...   ...   ...   ...   ...   ...
239     29.03  5.92   Male    No  Sat  Dinner     3
240     27.18  2.00 Female   Yes  Sat  Dinner     2
241     22.67  2.00   Male   Yes  Sat  Dinner     2
242     17.82  1.75   Male    No  Sat  Dinner     2
243     18.78  3.00 Female    No  Thur Dinner     2

[244 rows x 7 columns]
```

We can see here that we have a lot of categorical variables: gender, smoker, the day and the time. In later sections we will see how we can aggregate on these categorical variables. Now however we would like to process them for a machine learning exercise, where we need numbers not text. For the features smoker and day, you could argue there is a clear numbering between them, smoking is 1 if the person was smoking and e.g. Sun relates to 7 as it is the seventh day of the week.

But for the gender this is different, we can't really say that women are 1 and Men are 0 or vice versa (although in this binary case it might work). The same theory applies for time, if we would say that breakfast, lunch and dinner equal to 0, 1 and 2 this would give our algorithm a bad impression as it would think dinner is twice lunch...

We use One Hot Encoding for this, the idea is that for each value of the feature we create a new column.

```
from sklearn.preprocessing import OneHotEncoder
```

First we create our encoder, then we give it the day column to learn and see which values of categories there are.

```
ohe = OneHotEncoder()
ohe.fit(tips_df[['day']])
```

```
OneHotEncoder()
```

Now we can perform an encoding, here we insert the day column and it returns a matrix with 4 columns corresponding to the 4 days in our feature.

```
ohe.transform(tips_df[['day']]).todense()
```

[illegible]

(continues on next page)

[illegible]

(continued from previous page)

[illegible]

(continues on next page)

[illegible]

(continued from previous page)

```
[1., 0., 0., 0.],
[1., 0., 0., 0.],
[1., 0., 0., 0.],
[0., 1., 0., 0.],
[0., 1., 0., 0.],
[0., 1., 0., 0.],
[0., 1., 0., 0.],
[0., 1., 0., 0.],
[0., 1., 0., 0.],
[0., 1., 0., 0.],
[0., 1., 0., 0.],
[0., 1., 0., 0.],
[0., 1., 0., 0.],
[0., 1., 0., 0.],
[0., 1., 0., 0.],
[0., 1., 0., 0.],
[0., 1., 0., 0.],
[0., 1., 0., 0.],
[0., 1., 0., 0.],
[0., 1., 0., 0.],
[0., 1., 0., 0.],
[0., 0., 0., 1.])
```

As this is a rather mathematical approach for this simple problem I prefer to use the pandas approach for this, which is the `get_dummies` method. The outcome is much more pleasing yet completely the same.

```
pd.get_dummies(tips_df.day)
```

```
   Fri  Sat  Sun  Thur
0     0   0    1     0
1     0   0    1     0
2     0   0    1     0
3     0   0    1     0
4     0   0    1     0
...   ...  ...  ...   ...
239   0    1    0     0
240   0    1    0     0
241   0    1    0     0
242   0    1    0     0
243   0    0    0     1

[244 rows x 4 columns]
```

As an exercise you could create a script that given a specific feature (e.g. day):

- extracts that feature
- creates dummies
- concatenates it to the dataframe

Good luck!

## SCALING AND NORMALIZATION

In this notebook we are going to look into 2 rather mathematical concepts, Scaling and Normalization. The idea is that we can scale the values and shape the distribution of feature in our dataset.

As an example we take a dataset containing samples from a low density polyethylene production process, containing several numerical features such as temperatures, Forces, Pressure,...

The idea is that by using Scaling and normalization, the 'range of motion' for these sensors is equal and we can compare the fluctuations not only inbetween records, but also inbetween sensors.

```
import pandas as pd
```

```
ldpe_df = pd.read_csv('https://openmv.net/file/LDPE.csv').drop(columns=['Unnamed: 0'])  
ldpe_df.head()
```

|   | Tin    | Tmax1  | Tout1  | Tmax2  | Tout2  | Tcin1  | Tcin2  | z1    | z2    | \ |
|---|--------|--------|--------|--------|--------|--------|--------|-------|-------|---|
| 0 | 208.17 | 296.35 | 233.81 | 283.41 | 239.05 | 117.14 | 117.20 | 0.029 | 0.581 |   |
| 1 | 207.26 | 298.26 | 230.88 | 287.55 | 242.55 | 116.39 | 117.23 | 0.028 | 0.574 |   |
| 2 | 205.30 | 296.57 | 235.38 | 284.35 | 245.19 | 117.33 | 118.42 | 0.031 | 0.578 |   |
| 3 | 209.29 | 294.11 | 225.61 | 283.31 | 242.04 | 116.15 | 117.94 | 0.030 | 0.581 |   |
| 4 | 206.76 | 295.13 | 230.26 | 283.74 | 244.92 | 116.75 | 118.49 | 0.030 | 0.579 |   |


  

|   | Fi1    | Fi2    | Fs1    | Fs2    | Press | Conv   | Mn    | Mw     | LCB   | SCB   |
|---|--------|--------|--------|--------|-------|--------|-------|--------|-------|-------|
| 0 | 0.4507 | 0.4518 | 666.42 | 248.95 | 3021  | 0.1322 | 27379 | 160326 | 0.781 | 26.11 |
| 1 | 0.4765 | 0.5091 | 658.61 | 246.36 | 3033  | 0.1365 | 27043 | 165044 | 0.819 | 26.29 |
| 2 | 0.4744 | 0.4505 | 666.51 | 244.65 | 3004  | 0.1335 | 27344 | 165621 | 0.801 | 26.13 |
| 3 | 0.4429 | 0.4516 | 667.31 | 242.28 | 2980  | 0.1300 | 27502 | 160497 | 0.778 | 25.92 |
| 4 | 0.4394 | 0.4414 | 670.83 | 244.31 | 2997  | 0.1316 | 27518 | 165713 | 0.786 | 26.02 |

We can see that our features clearly have different ranges, but lets try to visualise these ranges using a density plot

```
ldpe_df.plot(kind='density')
```

```
<AxesSubplot:ylabel='Density'>
```




Ouch, this is clearly not working! Because the 'Mw' feature is in the range of 150k-175k our plot is so diluted the rest are pinned to 0. We can use the sklearn library to perform a min max scaling, this scaling will shift the distribution of each feature between 0 and 1, but that can also be adjusted.

```
from sklearn.preprocessing import MinMaxScaler
```

```
scaler = MinMaxScaler()
scaler.fit(ldpe_df)
pd.DataFrame(scaler.transform(ldpe_df), columns=ldpe_df.columns).plot(kind='density')
```

```
<AxesSubplot:ylabel='Density'>
```






That makes a lot more sense, you can now see all of the distribution at once. Also there seems to be one (yellow) feature that has some outliers perhaps something weird is going on there...

Taking it a step further we could also alter the distributions by using a standard scaler instead of a min max scaler, redistributing the values mathematically into a normal distribution.

```
from sklearn.preprocessing import StandardScaler
```

```
scaler = StandardScaler()
scaler.fit(ldpe_df)
pd.DataFrame(scaler.transform(ldpe_df), columns=ldpe_df.columns).plot(kind='density')
```

```
<AxesSubplot:ylabel='Density'>
```



You can see it had some trouble fitting our special feature into the normal distribution but it did work out in the end. With this we are ready to perform machine learning algorithms on this data, but first why not try and figure out where those outliers are I mentioned earlier?

## BINNING AND RANKING

When dealing with numerical data the trouble can sometimes be that numbers can have a wide variety.

Here we apply 2 methods to deal with that, binning and ranking. With binning we change the numerical feature into a categorical/ordinal feature. Ranking is used when our numerical feature contains a non normal distribution that fails to be normalized.

For this example we use a food consumption dataset, where european countries are listed and the relative percentage of each country is given that consumes the type of food, e.g. a value of 67 means that 67% of that country eats that type of food.

```
import pandas as pd
pd.set_option('display.max_columns', None)
```

```
food_df = pd.read_csv('https://openmv.net/file/food-consumption.csv')
food_df
```

|    | Country     | Real coffee | Instant coffee | Tea | Sweetener | Biscuits | \ |
|----|-------------|-------------|----------------|-----|-----------|----------|---|
| 0  | Germany     | 90          | 49             | 88  | 19.0      | 57.0     |   |
| 1  | Italy       | 82          | 10             | 60  | 2.0       | 55.0     |   |
| 2  | France      | 88          | 42             | 63  | 4.0       | 76.0     |   |
| 3  | Holland     | 96          | 62             | 98  | 32.0      | 62.0     |   |
| 4  | Belgium     | 94          | 38             | 48  | 11.0      | 74.0     |   |
| 5  | Luxembourg  | 97          | 61             | 86  | 28.0      | 79.0     |   |
| 6  | England     | 27          | 86             | 99  | 22.0      | 91.0     |   |
| 7  | Portugal    | 72          | 26             | 77  | 2.0       | 22.0     |   |
| 8  | Austria     | 55          | 31             | 61  | 15.0      | 29.0     |   |
| 9  | Switzerland | 73          | 72             | 85  | 25.0      | 31.0     |   |
| 10 | Sweden      | 97          | 13             | 93  | 31.0      | NaN      |   |
| 11 | Denmark     | 96          | 17             | 92  | 35.0      | 66.0     |   |
| 12 | Norway      | 92          | 17             | 83  | 13.0      | 62.0     |   |
| 13 | Finland     | 98          | 12             | 84  | 20.0      | 64.0     |   |
| 14 | Spain       | 70          | 40             | 40  | NaN       | 62.0     |   |
| 15 | Ireland     | 30          | 52             | 99  | 11.0      | 80.0     |   |

|   | Powder soup | Tin soup | Potatoes | Frozen fish | Frozen veggies | Apples | \ |
|---|-------------|----------|----------|-------------|----------------|--------|---|
| 0 | 51          | 19       | 21       | 27          | 21             | 81     |   |
| 1 | 41          | 3        | 2        | 4           | 2              | 67     |   |
| 2 | 53          | 11       | 23       | 11          | 5              | 87     |   |
| 3 | 67          | 43       | 7        | 14          | 14             | 83     |   |
| 4 | 37          | 23       | 9        | 13          | 12             | 76     |   |
| 5 | 73          | 12       | 7        | 26          | 23             | 85     |   |
| 6 | 55          | 76       | 17       | 20          | 24             | 76     |   |
| 7 | 34          | 1        | 5        | 20          | 3              | 22     |   |

(continues on next page)

(continued from previous page)

|    |             |              |     |        |        |           |           |         |   |
|----|-------------|--------------|-----|--------|--------|-----------|-----------|---------|---|
| 8  | 33          | 1            | 5   | 15     | 11     | 49        |           |         |   |
| 9  | 69          | 10           | 17  | 19     | 15     | 79        |           |         |   |
| 10 | 43          | 43           | 39  | 54     | 45     | 56        |           |         |   |
| 11 | 32          | 17           | 11  | 51     | 42     | 81        |           |         |   |
| 12 | 51          | 4            | 17  | 30     | 15     | 61        |           |         |   |
| 13 | 27          | 10           | 8   | 18     | 12     | 50        |           |         |   |
| 14 | 43          | 2            | 14  | 23     | 7      | 59        |           |         |   |
| 15 | 75          | 18           | 2   | 5      | 3      | 57        |           |         |   |
|    |             |              |     |        |        |           |           |         |   |
|    | Oranges     | Tinned fruit | Jam | Garlic | Butter | Margarine | Olive oil | Yoghurt | \ |
| 0  | 75          | 44           | 71  | 22     | 91     | 85        | 74        | 30.0    |   |
| 1  | 71          | 9            | 46  | 80     | 66     | 24        | 94        | 5.0     |   |
| 2  | 84          | 40           | 45  | 88     | 94     | 47        | 36        | 57.0    |   |
| 3  | 89          | 61           | 81  | 15     | 31     | 97        | 13        | 53.0    |   |
| 4  | 76          | 42           | 57  | 29     | 84     | 80        | 83        | 20.0    |   |
| 5  | 94          | 83           | 20  | 91     | 94     | 94        | 84        | 31.0    |   |
| 6  | 68          | 89           | 91  | 11     | 95     | 94        | 57        | 11.0    |   |
| 7  | 51          | 8            | 16  | 89     | 65     | 78        | 92        | 6.0     |   |
| 8  | 42          | 14           | 41  | 51     | 51     | 72        | 28        | 13.0    |   |
| 9  | 70          | 46           | 61  | 64     | 82     | 48        | 61        | 48.0    |   |
| 10 | 78          | 53           | 75  | 9      | 68     | 32        | 48        | 2.0     |   |
| 11 | 72          | 50           | 64  | 11     | 92     | 91        | 30        | 11.0    |   |
| 12 | 72          | 34           | 51  | 11     | 63     | 94        | 28        | 2.0     |   |
| 13 | 57          | 22           | 37  | 15     | 96     | 94        | 17        | NaN     |   |
| 14 | 77          | 30           | 38  | 86     | 44     | 51        | 91        | 16.0    |   |
| 15 | 52          | 46           | 89  | 5      | 97     | 25        | 31        | 3.0     |   |
|    |             |              |     |        |        |           |           |         |   |
|    | Crisp bread |              |     |        |        |           |           |         |   |
| 0  | 26          |              |     |        |        |           |           |         |   |
| 1  | 18          |              |     |        |        |           |           |         |   |
| 2  | 3           |              |     |        |        |           |           |         |   |
| 3  | 15          |              |     |        |        |           |           |         |   |
| 4  | 5           |              |     |        |        |           |           |         |   |
| 5  | 24          |              |     |        |        |           |           |         |   |
| 6  | 28          |              |     |        |        |           |           |         |   |
| 7  | 9           |              |     |        |        |           |           |         |   |
| 8  | 11          |              |     |        |        |           |           |         |   |
| 9  | 30          |              |     |        |        |           |           |         |   |
| 10 | 93          |              |     |        |        |           |           |         |   |
| 11 | 34          |              |     |        |        |           |           |         |   |
| 12 | 62          |              |     |        |        |           |           |         |   |
| 13 | 64          |              |     |        |        |           |           |         |   |
| 14 | 13          |              |     |        |        |           |           |         |   |
| 15 | 9           |              |     |        |        |           |           |         |   |

Here you could do some data validity, where we check if all values are between 0 and 100, or we check for missing values. I will leave that up to you

## 11.1 Binning

the first thing we want to do is separate the countries based on their coffee consumption, instead of creating arbitrary values we can perform a quantitative cut. This means we create a number of equally sized groups using the qcut function, we give them the labels low, medium and high.

```
food_df['bin_coffee'] = pd.qcut(food_df['Real coffee'], q=3, labels=['low', 'medium',
↪ 'high'])
food_df
```

|    | Country     | Real coffee  | Instant coffee | Tea         | Sweetener      | Biscuits  | \         |         |   |
|----|-------------|--------------|----------------|-------------|----------------|-----------|-----------|---------|---|
| 0  | Germany     | 90           | 49             | 88          | 19.0           | 57.0      |           |         |   |
| 1  | Italy       | 82           | 10             | 60          | 2.0            | 55.0      |           |         |   |
| 2  | France      | 88           | 42             | 63          | 4.0            | 76.0      |           |         |   |
| 3  | Holland     | 96           | 62             | 98          | 32.0           | 62.0      |           |         |   |
| 4  | Belgium     | 94           | 38             | 48          | 11.0           | 74.0      |           |         |   |
| 5  | Luxembourg  | 97           | 61             | 86          | 28.0           | 79.0      |           |         |   |
| 6  | England     | 27           | 86             | 99          | 22.0           | 91.0      |           |         |   |
| 7  | Portugal    | 72           | 26             | 77          | 2.0            | 22.0      |           |         |   |
| 8  | Austria     | 55           | 31             | 61          | 15.0           | 29.0      |           |         |   |
| 9  | Switzerland | 73           | 72             | 85          | 25.0           | 31.0      |           |         |   |
| 10 | Sweden      | 97           | 13             | 93          | 31.0           | NaN       |           |         |   |
| 11 | Denmark     | 96           | 17             | 92          | 35.0           | 66.0      |           |         |   |
| 12 | Norway      | 92           | 17             | 83          | 13.0           | 62.0      |           |         |   |
| 13 | Finland     | 98           | 12             | 84          | 20.0           | 64.0      |           |         |   |
| 14 | Spain       | 70           | 40             | 40          | NaN            | 62.0      |           |         |   |
| 15 | Ireland     | 30           | 52             | 99          | 11.0           | 80.0      |           |         |   |
|    |             |              |                |             |                |           |           |         |   |
|    | Powder soup | Tin soup     | Potatoes       | Frozen fish | Frozen veggies | Apples    | \         |         |   |
| 0  | 51          | 19           | 21             | 27          | 21             | 81        |           |         |   |
| 1  | 41          | 3            | 2              | 4           | 2              | 67        |           |         |   |
| 2  | 53          | 11           | 23             | 11          | 5              | 87        |           |         |   |
| 3  | 67          | 43           | 7              | 14          | 14             | 83        |           |         |   |
| 4  | 37          | 23           | 9              | 13          | 12             | 76        |           |         |   |
| 5  | 73          | 12           | 7              | 26          | 23             | 85        |           |         |   |
| 6  | 55          | 76           | 17             | 20          | 24             | 76        |           |         |   |
| 7  | 34          | 1            | 5              | 20          | 3              | 22        |           |         |   |
| 8  | 33          | 1            | 5              | 15          | 11             | 49        |           |         |   |
| 9  | 69          | 10           | 17             | 19          | 15             | 79        |           |         |   |
| 10 | 43          | 43           | 39             | 54          | 45             | 56        |           |         |   |
| 11 | 32          | 17           | 11             | 51          | 42             | 81        |           |         |   |
| 12 | 51          | 4            | 17             | 30          | 15             | 61        |           |         |   |
| 13 | 27          | 10           | 8              | 18          | 12             | 50        |           |         |   |
| 14 | 43          | 2            | 14             | 23          | 7              | 59        |           |         |   |
| 15 | 75          | 18           | 2              | 5           | 3              | 57        |           |         |   |
|    |             |              |                |             |                |           |           |         |   |
|    | Oranges     | Tinned fruit | Jam            | Garlic      | Butter         | Margarine | Olive oil | Yoghurt | \ |
| 0  | 75          | 44           | 71             | 22          | 91             | 85        | 74        | 30.0    |   |
| 1  | 71          | 9            | 46             | 80          | 66             | 24        | 94        | 5.0     |   |
| 2  | 84          | 40           | 45             | 88          | 94             | 47        | 36        | 57.0    |   |
| 3  | 89          | 61           | 81             | 15          | 31             | 97        | 13        | 53.0    |   |
| 4  | 76          | 42           | 57             | 29          | 84             | 80        | 83        | 20.0    |   |
| 5  | 94          | 83           | 20             | 91          | 94             | 94        | 84        | 31.0    |   |
| 6  | 68          | 89           | 91             | 11          | 95             | 94        | 57        | 11.0    |   |
| 7  | 51          | 8            | 16             | 89          | 65             | 78        | 92        | 6.0     |   |
| 8  | 42          | 14           | 41             | 51          | 51             | 72        | 28        | 13.0    |   |
| 9  | 70          | 46           | 61             | 64          | 82             | 48        | 61        | 48.0    |   |

(continues on next page)

(continued from previous page)

|                        |    |        |    |    |    |    |    |      |
|------------------------|----|--------|----|----|----|----|----|------|
| 10                     | 78 | 53     | 75 | 9  | 68 | 32 | 48 | 2.0  |
| 11                     | 72 | 50     | 64 | 11 | 92 | 91 | 30 | 11.0 |
| 12                     | 72 | 34     | 51 | 11 | 63 | 94 | 28 | 2.0  |
| 13                     | 57 | 22     | 37 | 15 | 96 | 94 | 17 | NaN  |
| 14                     | 77 | 30     | 38 | 86 | 44 | 51 | 91 | 16.0 |
| 15                     | 52 | 46     | 89 | 5  | 97 | 25 | 31 | 3.0  |
| Crisp bread bin_coffee |    |        |    |    |    |    |    |      |
| 0                      | 26 | medium |    |    |    |    |    |      |
| 1                      | 18 | medium |    |    |    |    |    |      |
| 2                      | 3  | medium |    |    |    |    |    |      |
| 3                      | 15 | high   |    |    |    |    |    |      |
| 4                      | 5  | medium |    |    |    |    |    |      |
| 5                      | 24 | high   |    |    |    |    |    |      |
| 6                      | 28 | low    |    |    |    |    |    |      |
| 7                      | 9  | low    |    |    |    |    |    |      |
| 8                      | 11 | low    |    |    |    |    |    |      |
| 9                      | 30 | low    |    |    |    |    |    |      |
| 10                     | 93 | high   |    |    |    |    |    |      |
| 11                     | 34 | high   |    |    |    |    |    |      |
| 12                     | 62 | medium |    |    |    |    |    |      |
| 13                     | 64 | high   |    |    |    |    |    |      |
| 14                     | 13 | low    |    |    |    |    |    |      |
| 15                     | 9  | low    |    |    |    |    |    |      |

a new column has appeared at the end of our dataframe, containing the labels of our binning, countries with low coffee consumption are put in the low category and vice versa. Now we can separate the countries with low coffee consumption from the rest

```
food_df[food_df.bin_coffee == 'low']
```

|    |                        |              |                |             |                |           |           |           |
|----|------------------------|--------------|----------------|-------------|----------------|-----------|-----------|-----------|
|    | Country                | Real coffee  | Instant coffee | Tea         | Sweetener      | Biscuits  | \         |           |
| 6  | England                | 27           | 86             | 99          | 22.0           | 91.0      |           |           |
| 7  | Portugal               | 72           | 26             | 77          | 2.0            | 22.0      |           |           |
| 8  | Austria                | 55           | 31             | 61          | 15.0           | 29.0      |           |           |
| 9  | Switzerland            | 73           | 72             | 85          | 25.0           | 31.0      |           |           |
| 14 | Spain                  | 70           | 40             | 40          | NaN            | 62.0      |           |           |
| 15 | Ireland                | 30           | 52             | 99          | 11.0           | 80.0      |           |           |
|    | Powder soup            | Tin soup     | Potatoes       | Frozen fish | Frozen veggies | Apples    | \         |           |
| 6  | 55                     | 76           | 17             | 20          | 24             | 76        |           |           |
| 7  | 34                     | 1            | 5              | 20          | 3              | 22        |           |           |
| 8  | 33                     | 1            | 5              | 15          | 11             | 49        |           |           |
| 9  | 69                     | 10           | 17             | 19          | 15             | 79        |           |           |
| 14 | 43                     | 2            | 14             | 23          | 7              | 59        |           |           |
| 15 | 75                     | 18           | 2              | 5           | 3              | 57        |           |           |
|    | Oranges                | Tinned fruit | Jam            | Garlic      | Butter         | Margarine | Olive oil | Yoghurt \ |
| 6  | 68                     | 89           | 91             | 11          | 95             | 94        | 57        | 11.0      |
| 7  | 51                     | 8            | 16             | 89          | 65             | 78        | 92        | 6.0       |
| 8  | 42                     | 14           | 41             | 51          | 51             | 72        | 28        | 13.0      |
| 9  | 70                     | 46           | 61             | 64          | 82             | 48        | 61        | 48.0      |
| 14 | 77                     | 30           | 38             | 86          | 44             | 51        | 91        | 16.0      |
| 15 | 52                     | 46           | 89             | 5           | 97             | 25        | 31        | 3.0       |
|    | Crisp bread bin_coffee |              |                |             |                |           |           |           |

(continues on next page)

(continued from previous page)

|    |    |     |
|----|----|-----|
| 6  | 28 | low |
| 7  | 9  | low |
| 8  | 11 | low |
| 9  | 30 | low |
| 14 | 13 | low |
| 15 | 9  | low |

You can already see the England/Ireland stereotype here, note that those are the only 2 with really low coffee consumption, the others are only in this low binning because we requested equally spaced bins in our qcut function. using the cut function would result in a different outcome. Perhaps you could try that out?

I tried to think of some metric to quantify the status of coffee drinkers, since we also have the instant coffee consumption we could create a metric where we subtract the amount of instant coffee drinkers from the amount of real coffee drinkers. This way we can measure that difference between them, I already went ahead and made equal quantity bins for them with labels low, medium and high 'quality coffee'.

```
food_df['bin_qual_coffee'] = pd.qcut(food_df['Real coffee'] - food_df['Instant coffee'], q=3, labels=['low', 'medium', 'high'])
```

```
food_df[food_df.bin_qual_coffee=='high']
```

|    | Country | Real coffee | Instant coffee | Tea | Sweetener | Biscuits | \ |
|----|---------|-------------|----------------|-----|-----------|----------|---|
| 1  | Italy   | 82          | 10             | 60  | 2.0       | 55.0     |   |
| 10 | Sweden  | 97          | 13             | 93  | 31.0      | NaN      |   |
| 11 | Denmark | 96          | 17             | 92  | 35.0      | 66.0     |   |
| 12 | Norway  | 92          | 17             | 83  | 13.0      | 62.0     |   |
| 13 | Finland | 98          | 12             | 84  | 20.0      | 64.0     |   |

|    | Powder soup | Tin soup | Potatoes | Frozen fish | Frozen veggies | Apples | \ |
|----|-------------|----------|----------|-------------|----------------|--------|---|
| 1  | 41          | 3        | 2        | 4           | 2              | 67     |   |
| 10 | 43          | 43       | 39       | 54          | 45             | 56     |   |
| 11 | 32          | 17       | 11       | 51          | 42             | 81     |   |
| 12 | 51          | 4        | 17       | 30          | 15             | 61     |   |
| 13 | 27          | 10       | 8        | 18          | 12             | 50     |   |

|    | Oranges | Tinned fruit | Jam | Garlic | Butter | Margarine | Olive oil | Yoghurt | \ |
|----|---------|--------------|-----|--------|--------|-----------|-----------|---------|---|
| 1  | 71      | 9            | 46  | 80     | 66     | 24        | 94        | 5.0     |   |
| 10 | 78      | 53           | 75  | 9      | 68     | 32        | 48        | 2.0     |   |
| 11 | 72      | 50           | 64  | 11     | 92     | 91        | 30        | 11.0    |   |
| 12 | 72      | 34           | 51  | 11     | 63     | 94        | 28        | 2.0     |   |
| 13 | 57      | 22           | 37  | 15     | 96     | 94        | 17        | NaN     |   |

|    | Crisp bread | bin_coffee | bin_qual_coffee |
|----|-------------|------------|-----------------|
| 1  | 18          | medium     | high            |
| 10 | 93          | high       | high            |
| 11 | 34          | high       | high            |
| 12 | 62          | medium     | high            |
| 13 | 64          | high       | high            |

Aha! you can see here which countries prefer the real coffee over the instant version. It seems the scandinavian countries together with obviously Italy are the true Caffeine connoisseur of Europe. Another interesting thing we can do now is take the mean for each product for both group high and low and take the difference for high - low. We can see the result below

```
food_df[food_df.bin_qual_coffee=='high'].mean()-food_df[food_df.bin_qual_coffee=='low'].mean()
```

```
/tmp/ipykernel_16521/3908782487.py:1: FutureWarning: Dropping of nuisance columns in
↳ DataFrame reductions (with 'numeric_only=None') is deprecated; in a future version
↳ this will raise TypeError. Select only valid columns before calling the reduction.
  food_df[food_df.bin_qual_coffee=='high'].mean()-food_df[food_df.bin_qual_coffee==
↳ 'low'].mean()
```

```
Real coffee      34.500000
Instant coffee   -43.366667
Tea              2.066667
Sweetener        -0.800000
Biscuits         2.583333
Powder soup      -18.200000
Tin soup         -9.600000
Potatoes         5.066667
Frozen fish      15.400000
Frozen veggies   10.866667
Apples           -4.166667
Oranges          3.666667
Tinned fruit     -14.066667
Jam              -12.233333
Garlic           -13.466667
Butter           10.333333
Margarine        2.500000
Olive oil        -3.433333
Yoghurt          -19.000000
Crisp bread      36.533333
dtype: float64
```

It seems a preference for quality coffee also pairs with crisp bread, who knew? Do you think scaling/normalization might be interesting here? why (not)?

## 11.2 Ranking

In case normalization fails us and we are for some reason not able to get a normal distribution out of a feature, we can still resort to ranking. Note that non linear machine learning techniques often use a ranking functionality under the hood, therefore this technique is often not required, yet for educational purposes we are going to use it here anyway. Let's see how the distribution for Real coffee consumption looks like.

```
food_df.sort_values('Real coffee')
```

|    | Country     | Real coffee | Instant coffee | Tea | Sweetener | Biscuits | \ |
|----|-------------|-------------|----------------|-----|-----------|----------|---|
| 6  | England     | 27          | 86             | 99  | 22.0      | 91.0     |   |
| 15 | Ireland     | 30          | 52             | 99  | 11.0      | 80.0     |   |
| 8  | Austria     | 55          | 31             | 61  | 15.0      | 29.0     |   |
| 14 | Spain       | 70          | 40             | 40  | NaN       | 62.0     |   |
| 7  | Portugal    | 72          | 26             | 77  | 2.0       | 22.0     |   |
| 9  | Switzerland | 73          | 72             | 85  | 25.0      | 31.0     |   |
| 1  | Italy       | 82          | 10             | 60  | 2.0       | 55.0     |   |
| 2  | France      | 88          | 42             | 63  | 4.0       | 76.0     |   |
| 0  | Germany     | 90          | 49             | 88  | 19.0      | 57.0     |   |
| 12 | Norway      | 92          | 17             | 83  | 13.0      | 62.0     |   |
| 4  | Belgium     | 94          | 38             | 48  | 11.0      | 74.0     |   |
| 3  | Holland     | 96          | 62             | 98  | 32.0      | 62.0     |   |
| 11 | Denmark     | 96          | 17             | 92  | 35.0      | 66.0     |   |

(continues on next page)




(continued from previous page)

|    |             |              |                 |             |                |           |           |           |
|----|-------------|--------------|-----------------|-------------|----------------|-----------|-----------|-----------|
| 5  | Luxembourg  | 97           | 61              | 86          | 28.0           | 79.0      |           |           |
| 10 | Sweden      | 97           | 13              | 93          | 31.0           | NaN       |           |           |
| 13 | Finland     | 98           | 12              | 84          | 20.0           | 64.0      |           |           |
|    | Powder soup | Tin soup     | Potatoes        | Frozen fish | Frozen veggies | Apples \  |           |           |
| 6  | 55          | 76           | 17              | 20          | 24             | 76        |           |           |
| 15 | 75          | 18           | 2               | 5           | 3              | 57        |           |           |
| 8  | 33          | 1            | 5               | 15          | 11             | 49        |           |           |
| 14 | 43          | 2            | 14              | 23          | 7              | 59        |           |           |
| 7  | 34          | 1            | 5               | 20          | 3              | 22        |           |           |
| 9  | 69          | 10           | 17              | 19          | 15             | 79        |           |           |
| 1  | 41          | 3            | 2               | 4           | 2              | 67        |           |           |
| 2  | 53          | 11           | 23              | 11          | 5              | 87        |           |           |
| 0  | 51          | 19           | 21              | 27          | 21             | 81        |           |           |
| 12 | 51          | 4            | 17              | 30          | 15             | 61        |           |           |
| 4  | 37          | 23           | 9               | 13          | 12             | 76        |           |           |
| 3  | 67          | 43           | 7               | 14          | 14             | 83        |           |           |
| 11 | 32          | 17           | 11              | 51          | 42             | 81        |           |           |
| 5  | 73          | 12           | 7               | 26          | 23             | 85        |           |           |
| 10 | 43          | 43           | 39              | 54          | 45             | 56        |           |           |
| 13 | 27          | 10           | 8               | 18          | 12             | 50        |           |           |
|    | Oranges     | Tinned fruit | Jam             | Garlic      | Butter         | Margarine | Olive oil | Yoghurt \ |
| 6  | 68          | 89           | 91              | 11          | 95             | 94        | 57        | 11.0      |
| 15 | 52          | 46           | 89              | 5           | 97             | 25        | 31        | 3.0       |
| 8  | 42          | 14           | 41              | 51          | 51             | 72        | 28        | 13.0      |
| 14 | 77          | 30           | 38              | 86          | 44             | 51        | 91        | 16.0      |
| 7  | 51          | 8            | 16              | 89          | 65             | 78        | 92        | 6.0       |
| 9  | 70          | 46           | 61              | 64          | 82             | 48        | 61        | 48.0      |
| 1  | 71          | 9            | 46              | 80          | 66             | 24        | 94        | 5.0       |
| 2  | 84          | 40           | 45              | 88          | 94             | 47        | 36        | 57.0      |
| 0  | 75          | 44           | 71              | 22          | 91             | 85        | 74        | 30.0      |
| 12 | 72          | 34           | 51              | 11          | 63             | 94        | 28        | 2.0       |
| 4  | 76          | 42           | 57              | 29          | 84             | 80        | 83        | 20.0      |
| 3  | 89          | 61           | 81              | 15          | 31             | 97        | 13        | 53.0      |
| 11 | 72          | 50           | 64              | 11          | 92             | 91        | 30        | 11.0      |
| 5  | 94          | 83           | 20              | 91          | 94             | 94        | 84        | 31.0      |
| 10 | 78          | 53           | 75              | 9           | 68             | 32        | 48        | 2.0       |
| 13 | 57          | 22           | 37              | 15          | 96             | 94        | 17        | NaN       |
|    | Crisp bread | bin_coffee   | bin_qual_coffee |             |                |           |           |           |
| 6  | 28          | low          | low             |             |                |           |           |           |
| 15 | 9           | low          | low             |             |                |           |           |           |
| 8  | 11          | low          | low             |             |                |           |           |           |
| 14 | 13          | low          | low             |             |                |           |           |           |
| 7  | 9           | low          | medium          |             |                |           |           |           |
| 9  | 30          | low          | low             |             |                |           |           |           |
| 1  | 18          | medium       | high            |             |                |           |           |           |
| 2  | 3           | medium       | medium          |             |                |           |           |           |
| 0  | 26          | medium       | medium          |             |                |           |           |           |
| 12 | 62          | medium       | high            |             |                |           |           |           |
| 4  | 5           | medium       | medium          |             |                |           |           |           |
| 3  | 15          | high         | low             |             |                |           |           |           |
| 11 | 34          | high         | high            |             |                |           |           |           |
| 5  | 24          | high         | medium          |             |                |           |           |           |
| 10 | 93          | high         | high            |             |                |           |           |           |
| 13 | 64          | high         | high            |             |                |           |           |           |

Ah yes, about half of the values are 90 or higher, not really optimal as the range is between 0 and 100! We can also view this in a visual way using a density plot.

```
food_df['Real coffee'].plot(kind='density', title='Real coffee (raw)')
```

```
<AxesSubplot:title={'center':'Real coffee (raw)'}, ylabel='Density'>
```



For larger datasets this would be more useful as we cannot see our whole dataset, it is clear we have to do something about this, now imagine we can not use regular normalization techniques. The rank method now comes in handy!

```
food_df['rank_coffee'] = food_df['Real coffee'].rank()
food_df
```

|    | Country     | Real coffee | Instant coffee | Tea         | Sweetener      | Biscuits | \ |
|----|-------------|-------------|----------------|-------------|----------------|----------|---|
| 0  | Germany     | 90          | 49             | 88          | 19.0           | 57.0     |   |
| 1  | Italy       | 82          | 10             | 60          | 2.0            | 55.0     |   |
| 2  | France      | 88          | 42             | 63          | 4.0            | 76.0     |   |
| 3  | Holland     | 96          | 62             | 98          | 32.0           | 62.0     |   |
| 4  | Belgium     | 94          | 38             | 48          | 11.0           | 74.0     |   |
| 5  | Luxembourg  | 97          | 61             | 86          | 28.0           | 79.0     |   |
| 6  | England     | 27          | 86             | 99          | 22.0           | 91.0     |   |
| 7  | Portugal    | 72          | 26             | 77          | 2.0            | 22.0     |   |
| 8  | Austria     | 55          | 31             | 61          | 15.0           | 29.0     |   |
| 9  | Switzerland | 73          | 72             | 85          | 25.0           | 31.0     |   |
| 10 | Sweden      | 97          | 13             | 93          | 31.0           | NaN      |   |
| 11 | Denmark     | 96          | 17             | 92          | 35.0           | 66.0     |   |
| 12 | Norway      | 92          | 17             | 83          | 13.0           | 62.0     |   |
| 13 | Finland     | 98          | 12             | 84          | 20.0           | 64.0     |   |
| 14 | Spain       | 70          | 40             | 40          | NaN            | 62.0     |   |
| 15 | Ireland     | 30          | 52             | 99          | 11.0           | 80.0     |   |
|    | Powder soup | Tin soup    | Potatoes       | Frozen fish | Frozen veggies | Apples   | \ |

(continues on next page)


(continued from previous page)

|    |             |              |                 |             |        |           |           |         |   |
|----|-------------|--------------|-----------------|-------------|--------|-----------|-----------|---------|---|
| 0  | 51          | 19           | 21              | 27          | 21     | 81        |           |         |   |
| 1  | 41          | 3            | 2               | 4           | 2      | 67        |           |         |   |
| 2  | 53          | 11           | 23              | 11          | 5      | 87        |           |         |   |
| 3  | 67          | 43           | 7               | 14          | 14     | 83        |           |         |   |
| 4  | 37          | 23           | 9               | 13          | 12     | 76        |           |         |   |
| 5  | 73          | 12           | 7               | 26          | 23     | 85        |           |         |   |
| 6  | 55          | 76           | 17              | 20          | 24     | 76        |           |         |   |
| 7  | 34          | 1            | 5               | 20          | 3      | 22        |           |         |   |
| 8  | 33          | 1            | 5               | 15          | 11     | 49        |           |         |   |
| 9  | 69          | 10           | 17              | 19          | 15     | 79        |           |         |   |
| 10 | 43          | 43           | 39              | 54          | 45     | 56        |           |         |   |
| 11 | 32          | 17           | 11              | 51          | 42     | 81        |           |         |   |
| 12 | 51          | 4            | 17              | 30          | 15     | 61        |           |         |   |
| 13 | 27          | 10           | 8               | 18          | 12     | 50        |           |         |   |
| 14 | 43          | 2            | 14              | 23          | 7      | 59        |           |         |   |
| 15 | 75          | 18           | 2               | 5           | 3      | 57        |           |         |   |
|    |             |              |                 |             |        |           |           |         |   |
|    | Oranges     | Tinned fruit | Jam             | Garlic      | Butter | Margarine | Olive oil | Yoghurt | \ |
| 0  | 75          | 44           | 71              | 22          | 91     | 85        | 74        | 30.0    |   |
| 1  | 71          | 9            | 46              | 80          | 66     | 24        | 94        | 5.0     |   |
| 2  | 84          | 40           | 45              | 88          | 94     | 47        | 36        | 57.0    |   |
| 3  | 89          | 61           | 81              | 15          | 31     | 97        | 13        | 53.0    |   |
| 4  | 76          | 42           | 57              | 29          | 84     | 80        | 83        | 20.0    |   |
| 5  | 94          | 83           | 20              | 91          | 94     | 94        | 84        | 31.0    |   |
| 6  | 68          | 89           | 91              | 11          | 95     | 94        | 57        | 11.0    |   |
| 7  | 51          | 8            | 16              | 89          | 65     | 78        | 92        | 6.0     |   |
| 8  | 42          | 14           | 41              | 51          | 51     | 72        | 28        | 13.0    |   |
| 9  | 70          | 46           | 61              | 64          | 82     | 48        | 61        | 48.0    |   |
| 10 | 78          | 53           | 75              | 9           | 68     | 32        | 48        | 2.0     |   |
| 11 | 72          | 50           | 64              | 11          | 92     | 91        | 30        | 11.0    |   |
| 12 | 72          | 34           | 51              | 11          | 63     | 94        | 28        | 2.0     |   |
| 13 | 57          | 22           | 37              | 15          | 96     | 94        | 17        | NaN     |   |
| 14 | 77          | 30           | 38              | 86          | 44     | 51        | 91        | 16.0    |   |
| 15 | 52          | 46           | 89              | 5           | 97     | 25        | 31        | 3.0     |   |
|    |             |              |                 |             |        |           |           |         |   |
|    | Crisp bread | bin_coffee   | bin_qual_coffee | rank_coffee |        |           |           |         |   |
| 0  | 26          | medium       | medium          | 9.0         |        |           |           |         |   |
| 1  | 18          | medium       | high            | 7.0         |        |           |           |         |   |
| 2  | 3           | medium       | medium          | 8.0         |        |           |           |         |   |
| 3  | 15          | high         | low             | 12.5        |        |           |           |         |   |
| 4  | 5           | medium       | medium          | 11.0        |        |           |           |         |   |
| 5  | 24          | high         | medium          | 14.5        |        |           |           |         |   |
| 6  | 28          | low          | low             | 1.0         |        |           |           |         |   |
| 7  | 9           | low          | medium          | 5.0         |        |           |           |         |   |
| 8  | 11          | low          | low             | 3.0         |        |           |           |         |   |
| 9  | 30          | low          | low             | 6.0         |        |           |           |         |   |
| 10 | 93          | high         | high            | 14.5        |        |           |           |         |   |
| 11 | 34          | high         | high            | 12.5        |        |           |           |         |   |
| 12 | 62          | medium       | high            | 10.0        |        |           |           |         |   |
| 13 | 64          | high         | high            | 16.0        |        |           |           |         |   |
| 14 | 13          | low          | low             | 4.0         |        |           |           |         |   |
| 15 | 9           | low          | low             | 2.0         |        |           |           |         |   |

At the end of our data a new column was appended, containing the ranking of each country with the lowest being 1 and the highest equal to the amount of countries. When we visualise this distribution we get a uniform distribution, not normal but still better than before!

```
food_df['rank_coffee'].plot(kind='density', title='Real coffee (ranked)')
```

```
<AxesSubplot:title={'center':'Real coffee (ranked)'}, ylabel='Density'>
```



## SOME PRACTICE

Now that you have learned techniques in data preparation, why don't you put them to use in this wonderfully horrifying dataset. Good luck!

```
import os
import json

import pandas as pd
```

```
kaggle_dir = os.path.expanduser("~/kaggle")
if not os.path.exists(kaggle_dir):
    os.mkdir(kaggle_dir)

with open(f'{kaggle_dir}/kaggle.json', 'w') as f:
    json.dump(
        {
            "username": "lorenzof",
            "key": "7a44a9e99b27e796177d793a3d85b8cf"
        }, f)
```

```
import kaggle
kaggle.api.dataset_download_files(dataset='PromptCloudHQ/us-jobs-on-monstercom', path=
↳ './data', unzip=True)
```

```
-----
ModuleNotFoundError                                Traceback (most recent call last)
/tmp/ipykernel_25600/39646943.py in <module>
----> 1 import kaggle
      2 kaggle.api.dataset_download_files(dataset='PromptCloudHQ/us-jobs-on-monstercom
↳ ', path='./data', unzip=True)

ModuleNotFoundError: No module named 'kaggle'
```

```
df = pd.read_csv('./data/monster_com-job_sample.csv')
```

```
df.head()
```

|   | country                  | country_code | date_added | has_expired | \ |
|---|--------------------------|--------------|------------|-------------|---|
| 0 | United States of America | US           | NaN        | No          |   |
| 1 | United States of America | US           | NaN        | No          |   |
| 2 | United States of America | US           | NaN        | No          |   |

(continues on next page)

(continued from previous page)

|   |   |   |                     |    |
|---|---|---|---------------------|----|
| 3 | United States of America                          | US  | NaN                 | No |
| 4 | United States of America                          | US  | NaN                 | No |
|   | job_board   |   | job_description     | \  |
| 0 | jobs.monster.com                                  | TeamSoft is seeing an IT Support Specialist to... |                     |    |
| 1 | jobs.monster.com                                  | The Wisconsin State Journal is seeking a flexi... |                     |    |
| 2 | jobs.monster.com                                  | Report this job About the Job DePuy Synthes Co... |                     |    |
| 3 | jobs.monster.com                                  | Why Join Altec? If you're considering a career... |                     |    |
| 4 | jobs.monster.com                                  | Position ID# 76162 # Positions 1 State CT C...    |                     |    |
|   | job_title   |   | job_type            | \  |
| 0 | IT Support Technician Job in Madison              |   | Full Time Employee  |    |
| 1 | Business Reporter/Editor Job in Madison           |   | Full Time           |    |
| 2 | Johnson & Johnson Family of Companies Job Appl... |   | Full Time, Employee |    |
| 3 | Engineer - Quality Job in Dixon                   |   | Full Time           |    |
| 4 | Shift Supervisor - Part-Time Job in Camphill      |   | Full Time Employee  |    |
|   | location  |   |                     | \  |
| 0 | Madison, WI 53702                                 |   |                     |    |
| 1 | Madison, WI 53708                                 |   |                     |    |
| 2 | DePuy Synthes Companies is a member of Johnson... |   |                     |    |
| 3 | Dixon, CA   |   |                     |    |
| 4 | Camphill, PA                                      |   |                     |    |
|   | organization                                      |   |                     | \  |
| 0 | NaN   |   |                     |    |
| 1 | Printing and Publishing                           |   |                     |    |
| 2 | Personal and Household Services                   |   |                     |    |
| 3 | Altec Industries                                  |   |                     |    |
| 4 | Retail  |   |                     |    |
|   | page_url  | salary  |                     | \  |
| 0 | http://jobview.monster.com/it-support-technici... | NaN   |                     |    |
| 1 | http://jobview.monster.com/business-reporter-e... | NaN   |                     |    |
| 2 | http://jobview.monster.com/senior-training-lea... | NaN   |                     |    |
| 3 | http://jobview.monster.com/engineer-quality-jo... | NaN   |                     |    |
| 4 | http://jobview.monster.com/shift-supervisor-pa... | NaN   |                     |    |
|   | sector  |   | uniq_id             |    |
| 0 | IT/Software Development                           | 11d599f229a80023d2f40e7c52cd941e                  |                     |    |
| 1 | NaN   | e4cbb126dabf22159aff90223243ff2a                  |                     |    |
| 2 | NaN   | 839106b353877fa3d896ffb9c1fe01c0                  |                     |    |
| 3 | Experienced (Non-Manager)                         | 58435fcab804439efdcaa7ecca0fd783                  |                     |    |
| 4 | Project/Program Management                        | 64d0272dc8496abfd9523a8df63c184c                  |                     |    |

Need some inspiration? perhaps [this](#) might help!

## **Part III**

# **3. Data Preprocessing**





## **DATA PREPROCESSING**

this is an introduction



## INDEXING AND SLICING

In

```
import pandas as pd
```

```
min_temp_df = pd.read_csv('https://raw.githubusercontent.com/LorenzF/data-science-  
practical-approach/main/src/c2_data_preparation/data/temperatures/australia/  
melbourne/1981.csv')  
min_temp_df
```

```
      Date  Temp  
0  1981-01-01  20.7  
1  1981-01-02  17.9  
2  1981-01-03  18.8  
3  1981-01-04  14.6  
4  1981-01-05  15.8  
..      ...   ...  
360 1981-12-27  15.5  
361 1981-12-28  13.3  
362 1981-12-29  15.6  
363 1981-12-30  15.2  
364 1981-12-31  17.4
```

```
[365 rows x 2 columns]
```

```
min_temp_df.Date = pd.to_datetime(min_temp_df.Date)
```

```
min_temp_df = min_temp_df.set_index('Date')
```

```
min_temp_df.loc['1981-06-01':'1981-06-30']
```

```
      Date  Temp  
1981-06-01  11.6  
1981-06-02  10.6  
1981-06-03   9.8  
1981-06-04  11.2  
1981-06-05   5.7  
1981-06-06   7.1  
1981-06-07   2.5  
1981-06-08   3.5  
1981-06-09   4.6
```

(continues on next page)

(continued from previous page)

```
1981-06-10    11.0
1981-06-11     5.7
1981-06-12     7.7
1981-06-13    10.4
1981-06-14    11.4
1981-06-15     9.2
1981-06-16     6.1
1981-06-17     2.7
1981-06-18     4.3
1981-06-19     6.3
1981-06-20     3.8
1981-06-21     4.4
1981-06-22     7.1
1981-06-23     4.8
1981-06-24     5.8
1981-06-25     6.2
1981-06-26     7.3
1981-06-27     9.2
1981-06-28    10.2
1981-06-29     9.5
1981-06-30     9.5
```

```
min_temp_df.loc['1989-06-01':'1989-06-30'].mean()
```

```
Temp      NaN
dtype: float64
```

```
min_temp_df.resample('MS').mean()
```

```

              Temp
Date
1981-01-01  17.712903
1981-02-01  17.678571
1981-03-01  13.500000
1981-04-01  12.356667
1981-05-01   9.490323
1981-06-01   7.306667
1981-07-01   7.577419
1981-08-01   7.238710
1981-09-01  10.143333
1981-10-01  10.087097
1981-11-01  11.890000
1981-12-01  13.680645
```

```
import seaborn as sns
```

```
tip_df = sns.load_dataset('tips')
tip_df.head()
```

```

   total_bill  tip  sex  smoker  day  time  size
0      16.99  1.01  Female    No  Sun  Dinner     2
1      10.34  1.66   Male    No  Sun  Dinner     3
2      21.01  3.50   Male    No  Sun  Dinner     3
3      23.68  3.31   Male    No  Sun  Dinner     2
```

(continues on next page)

(continued from previous page)

```
4      24.59  3.61  Female    No  Sun  Dinner    4
```

```
tip_index_df = tip_df.set_index('day')
```

```
tip_index_df.loc['Sun']
```

```

      total_bill  tip    sex smoker  time  size
day
Sun      16.99  1.01  Female    No  Dinner    2
Sun      10.34  1.66    Male    No  Dinner    3
Sun      21.01  3.50    Male    No  Dinner    3
Sun      23.68  3.31    Male    No  Dinner    2
Sun      24.59  3.61  Female    No  Dinner    4
..          ...   ...     ...   ...   ...   ...
Sun      20.90  3.50  Female   Yes  Dinner    3
Sun      30.46  2.00    Male   Yes  Dinner    5
Sun      18.15  3.50  Female   Yes  Dinner    3
Sun      23.10  4.00    Male   Yes  Dinner    3
Sun      15.69  1.50    Male   Yes  Dinner    2

```

```
[76 rows x 6 columns]
```

```
tip_index_df = tip_df.set_index(['day', 'time'])
```

```
tip_index_df.loc[('Thur', 'Lunch')].tip.mean()
```

```

/tmp/ipykernel_25625/2537502835.py:1: PerformanceWarning: indexing past lexsort depth
may impact performance.
  tip_index_df.loc[('Thur', 'Lunch')].tip.mean()

```

```
2.767704918032786
```

```
pd.pivot_table(tip_df, values='total_bill', index='day', columns='time', aggfunc=
↳ 'median')
```

```

time  Lunch  Dinner
day
Thur   16.00  18.780
Fri    13.42  18.665
Sat      NaN  18.240
Sun      NaN  19.630

```

```
tip_df.set_index(['sex', 'time', 'smoker']).loc[('Male', 'Dinner', 'Yes')]['tip'].mean()
```

```

/tmp/ipykernel_25625/3467525553.py:1: PerformanceWarning: indexing past lexsort depth
may impact performance.
  tip_df.set_index(['sex', 'time', 'smoker']).loc[('Male', 'Dinner', 'Yes')]['tip'].
  ↳ mean()

```

```
3.123191489361702
```



**MERGE**

<https://www.kaggle.com/uciml/restaurant-data-with-consumer-ratings>

```
import pandas as pd
```

```
rating_df = pd.read_csv('./data/cuisine/rating_final.csv')
```

```
rating_df
```

|      | userID | placeID | rating | food_rating | service_rating |
|------|--------|---------|--------|-------------|----------------|
| 0    | U1077  | 135085  | 2      | 2           | 2              |
| 1    | U1077  | 135038  | 2      | 2           | 1              |
| 2    | U1077  | 132825  | 2      | 2           | 2              |
| 3    | U1077  | 135060  | 1      | 2           | 2              |
| 4    | U1068  | 135104  | 1      | 1           | 2              |
| ...  | ...    | ...     | ...    | ...         | ...            |
| 1156 | U1043  | 132630  | 1      | 1           | 1              |
| 1157 | U1011  | 132715  | 1      | 1           | 0              |
| 1158 | U1068  | 132733  | 1      | 1           | 0              |
| 1159 | U1068  | 132594  | 1      | 1           | 1              |
| 1160 | U1068  | 132660  | 0      | 0           | 0              |

```
[1161 rows x 5 columns]
```

```
cuisine_df = pd.read_csv('./data/cuisine/chefmozcuisine.csv')  
cuisine_df
```

|     | placeID | Rcuisine       |
|-----|---------|----------------|
| 0   | 135110  | Spanish        |
| 1   | 135109  | Italian        |
| 2   | 135107  | Latin_American |
| 3   | 135106  | Mexican        |
| 4   | 135105  | Fast_Food      |
| ..  | ...     | ...            |
| 911 | 132005  | Seafood        |
| 912 | 132004  | Seafood        |
| 913 | 132003  | International  |
| 914 | 132002  | Seafood        |
| 915 | 132001  | Dutch-Belgian  |

```
[916 rows x 2 columns]
```

```
merged_df = pd.merge(rating_df, cuisine_df, on='placeID', how='inner')
merged_df
```

```
   userID  placeID  rating  food_rating  service_rating  Rcuisine
0    U1077   135085      2           2             2  Fast_Food
1    U1108   135085      1           2             1  Fast_Food
2    U1081   135085      1           2             1  Fast_Food
3    U1056   135085      2           2             2  Fast_Food
4    U1134   135085      2           1             2  Fast_Food
...     ...     ...     ...         ...         ...     ...
1038  U1061   132958      2           2             2  American
1039  U1025   132958      1           0             0  American
1040  U1097   132958      2           1             1  American
1041  U1096   132958      1           2             2  American
1042  U1136   132958      2           2             2  American

[1043 rows x 6 columns]
```

```
merged_df[merged_df.Rcuisine.isna()]
```

```
Empty DataFrame
Columns: [userID, placeID, rating, food_rating, service_rating, Rcuisine]
Index: []
```

```
merged_df.Rcuisine.unique()
```

```
array(['Fast_Food', 'Mexican', 'Seafood', 'Pizzeria', 'Regional',
       'Armenian', 'Cafeteria', 'American', 'Bar', 'Bar_Pub_Brewery',
       'Italian', 'Japanese', 'Contemporary', 'Burgers', 'Mediterranean',
       'International', 'Vietnamese', 'Family', 'Chinese',
       'Cafe-Coffee_Shop', 'Game', 'Bakery', 'Breakfast-Brunch'],
      dtype=object)
```

```
merged_df[merged_df.Rcuisine=='Bar_Pub_Brewery'][['rating', 'food_rating', 'service_
↪rating']].mean()
```

```
rating          1.305085
food_rating      1.169492
service_rating   1.203390
dtype: float64
```

```
merged_df[merged_df.Rcuisine=='Bar'][['rating', 'food_rating', 'service_rating']].
↪mean()
```

```
rating          1.200000
food_rating      1.135714
service_rating   1.085714
dtype: float64
```

```
merged_df[merged_df.Rcuisine=='Cafeteria'][['rating', 'food_rating', 'service_rating
↪']].mean()
```



```
rating          1.205882
food_rating     1.127451
service_rating  1.078431
dtype: float64
```

```
merged_df[merged_df.Rcuisine=='Cafe-Coffee_Shop'][['rating', 'food_rating', 'service_
↪rating']].mean()
```

```
rating          1.583333
food_rating     1.333333
service_rating  1.416667
dtype: float64
```

```
user_payment_df = pd.read_csv('./data/cuisine/userpayment.csv')
```

```
payment_df = pd.merge(rating_df, user_payment_df, how='inner')
```

```
payment_df.Upayment.unique()
```

```
array(['VISA', 'cash', 'bank_debit_cards', 'MasterCard-Eurocard',
      'American_Express'], dtype=object)
```

```
payment_df[payment_df.Upayment=='cash'][['rating', 'food_rating', 'service_rating']].
↪mean()
```

```
rating          1.182815
food_rating     1.200183
service_rating  1.080439
dtype: float64
```

```
payment_df[payment_df.Upayment=='bank_debit_cards'][['rating', 'food_rating',
↪'service_rating']].mean()
```

```
rating          1.437908
food_rating     1.562092
service_rating  1.398693
dtype: float64
```



## GROUPBY

```
import pandas as pd
```

```
rating_df = pd.read_csv('./data/cuisine/rating_final.csv')
```

```
grouped_rating_df = rating_df.groupby('placeID').mean().sort_values('rating')
grouped_rating_df
```

```
      rating  food_rating  service_rating
placeID
132654    0.250000         0.25         0.250000
135040    0.250000         0.25         0.250000
132560    0.500000         1.00         0.250000
132663    0.500000         0.50         0.666667
135069    0.500000         0.50         0.750000
...         ...         ...         ...
132755    1.800000         2.00         1.600000
132922    1.833333         1.50         1.833333
134986    2.000000         2.00         2.000000
135034    2.000000         2.00         1.600000
132955    2.000000         1.80         1.800000
```

```
[130 rows x 3 columns]
```

```
geo_df = pd.read_csv('./data/cuisine/geoplaces2.csv').set_index('placeID')
```

```
merged_rating_df = pd.merge(grouped_rating_df, geo_df, left_index=True, right_
↪ index=True)
merged_rating_df
```

```
      rating  food_rating  service_rating  latitude  longitude \
placeID
132654    0.250000         0.25         0.250000  23.735523  -99.129588
135040    0.250000         0.25         0.250000  22.135617 -100.969709
132560    0.500000         1.00         0.250000  23.752304  -99.166913
132663    0.500000         0.50         0.666667  23.752511  -99.166954
135069    0.500000         0.50         0.750000  22.140129 -100.944872
...         ...         ...         ...         ...         ...
132755    1.800000         2.00         1.600000  22.153324 -101.019546
132922    1.833333         1.50         1.833333  22.151135 -100.982311
134986    2.000000         2.00         2.000000  18.928798  -99.239513
135034    2.000000         2.00         1.600000  22.140517 -101.021422
```

(continues on next page)

(continued from previous page)

|   |   |      |                   |           |                 |
|---|---|------|-------------------|-----------|-----------------|
| 132955                                      | 2.000000  | 1.80 | 1.800000          | 22.147622 | -101.010275     |
| the_geom_meter \                            |   |      |                   |           |                 |
| placeID                                     |   |      |                   |           |                 |
| 132654                                      | 0101000020957F000040E8F628488557C18224E8B94845... |      |                   |           |                 |
| 135040                                      | 0101000020957F00001B552189B84A58C15A2AAEFD2CA2... |      |                   |           |                 |
| 132560                                      | 0101000020957F0000FC60BDA8E88157C1B2C357D6DA4E... |      |                   |           |                 |
| 132663                                      | 0101000020957F0000FDF8D26EE08157C1FEDB6A1FDB4E... |      |                   |           |                 |
| 135069                                      | 0101000020957F000038E5D546B74A58C18FD29AD0D29A... |      |                   |           |                 |
| ...   | ...   |      |                   |           |                 |
| 132755                                      | 0101000020957F000026CADE45A14658C1F011EBCA55AF... |      |                   |           |                 |
| 132922                                      | 0101000020957F000060A98A38FF4758C146718E41D9A4... |      |                   |           |                 |
| 134986                                      | 0101000020957F00002A0D05E2D96D5AC1AB058CB1EC56... |      |                   |           |                 |
| 135034                                      | 0101000020957F000026D92BB4894858C161A7552DA2B0... |      |                   |           |                 |
| 132955                                      | 0101000020957F000068BE7C87C24758C1920A360A08AD... |      |                   |           |                 |
| name \                                      |   |      |                   |           |                 |
| placeID                                     |   |      |                   |           |                 |
| 132654                                      | Carnitas Mata Calle 16 de Septiembre              |      |                   |           |                 |
| 135040                                      | Restaurant los Compadres                          |      |                   |           |                 |
| 132560                                      | puesto de gorditas                                |      |                   |           |                 |
| 132663                                      | tacos abi   |      |                   |           |                 |
| 135069                                      | Abondance Restaurante Bar                         |      |                   |           |                 |
| ...   | ...   |      |                   |           |                 |
| 132755                                      | La Estrella de Dimas                              |      |                   |           |                 |
| 132922                                      | cafe punta del cielo                              |      |                   |           |                 |
| 134986                                      | Restaurant Las Mananitas                          |      |                   |           |                 |
| 135034                                      | Michiko Restaurant Japones                        |      |                   |           |                 |
| 132955                                      | emilianos   |      |                   |           |                 |
| address city \                              |   |      |                   |           |                 |
| placeID                                     |   |      |                   |           |                 |
| 132654                                      | 16 de Septiembre                                  |      |                   |           | victoria        |
| 135040                                      | Camino a Simon Diaz 155 Centro                    |      |                   |           | San Luis Potosi |
| 132560                                      | frente al tecnologico                             |      |                   |           | victoria        |
| 132663                                      | ?   |      |                   |           | victoria        |
| 135069                                      | Industrias 908 Valle Dorado                       |      |                   |           | San Luis Potosi |
| ...   | ...   |      |                   |           | ...             |
| 132755                                      | Av. de los Pintores                               |      |                   |           | San Luis Potosi |
| 132922                                      | ?   |      |                   |           | ?               |
| 134986                                      | Ricardo Linares 107                               |      |                   |           | Cuernavaca      |
| 135034                                      | Cordillera de Los Alpes 160 Lomas 2 Seccion       |      |                   |           | San Luis Potosi |
| 132955                                      | venustiano carranza                               |      |                   |           | san luis potos  |
| state ... alcohol smoking_area dress_code \ |   |      |                   |           |                 |
| placeID                                     |   |      |                   |           |                 |
| 132654                                      | tamaulipas  | ...  | No_Alcohol_Served | none      | informal        |
| 135040                                      | SLP   | ...  | Wine-Beer         | none      | informal        |
| 132560                                      | tamaulipas  | ...  | No_Alcohol_Served | permitted | informal        |
| 132663                                      | tamaulipas  | ...  | No_Alcohol_Served | none      | informal        |
| 135069                                      | SLP   | ...  | Wine-Beer         | none      | informal        |
| ...   | ...   | ...  | ...               | ...       | ...             |
| 132755                                      | S.L.P.  | ...  | No_Alcohol_Served | none      | informal        |
| 132922                                      | ?   | ...  | No_Alcohol_Served | permitted | formal          |
| 134986                                      | Morelos   | ...  | Wine-Beer         | none      | formal          |
| 135034                                      | SLP   | ...  | No_Alcohol_Served | none      | informal        |
| 132955                                      | mexico  | ...  | Wine-Beer         | none      | informal        |

(continues on next page)

(continued from previous page)

```

        accessibility  price          url Rambience franchise \
placeID
132654      completely      low          ?  familiar          f
135040  no_accessibility    high          ?  familiar          f
132560  no_accessibility    low           ?  familiar          f
132663      completely      low          ?  familiar          f
135069  no_accessibility    low           ?  familiar          f
...
132755      partially    medium          ?  familiar          f
132922      completely    medium          ?  familiar          f
134986  no_accessibility    high  lasmananitas.com.mx  familiar          f
135034  no_accessibility    medium          ?  familiar          f
132955      completely      low          ?  familiar          t

        area other_services
placeID
132654  closed          none
135040  closed          none
132560   open          none
132663  closed          none
135069  closed          none
...
132755  closed    variety
132922  closed          none
134986  closed          none
135034  closed          none
132955  closed    variety

[130 rows x 23 columns]

```

```
merged_rating_df.columns
```

```

Index(['rating', 'food_rating', 'service_rating', 'latitude', 'longitude',
      'the_geom_meter', 'name', 'address', 'city', 'state', 'country', 'fax',
      'zip', 'alcohol', 'smoking_area', 'dress_code', 'accessibility',
      'price', 'url', 'Rambience', 'franchise', 'area', 'other_services'],
      dtype='object')

```

```
merged_rating_df.groupby('country')[['rating', 'food_rating', 'service_rating']].
    .mean()
```

```

        rating  food_rating  service_rating
country
?      1.166045      1.232946      1.069169
Mexico  1.200977      1.229093      1.118162
mexico  1.062660      1.069006      0.900064

```

```
can you fix this string problem?
```

```
Object `problem` not found.
```

```
merged_rating_df.groupby('alcohol')[['rating', 'food_rating', 'service_rating']].
    .mean()
```

|                   | rating   | food_rating | service_rating |
|-------------------|----------|-------------|----------------|
| alcohol           |          |             |                |
| Full_Bar          | 1.287124 | 1.218315    | 1.170311       |
| No_Alcohol_Served | 1.148075 | 1.194730    | 1.042417       |
| Wine-Beer         | 1.231887 | 1.261840    | 1.174437       |

```
merged_rating_df.groupby('accessibility')[['rating', 'food_rating', 'service_rating']\n↪].mean()
```

|                  | rating   | food_rating | service_rating |
|------------------|----------|-------------|----------------|
| accessibility    |          |             |                |
| completely       | 1.132494 | 1.203597    | 1.049709       |
| no_accessibility | 1.196189 | 1.206242    | 1.091278       |
| partially        | 1.275356 | 1.330294    | 1.219991       |

```
merged_rating_df.accessibility.value_counts()
```

```
no_accessibility    76
completely          45
partially           9
Name: accessibility, dtype: int64
```

```
merged_rating_df.groupby('price')[['rating', 'food_rating', 'service_rating']].mean()
```

|        | rating   | food_rating | service_rating |
|--------|----------|-------------|----------------|
| price  |          |             |                |
| high   | 1.258106 | 1.253816    | 1.174754       |
| low    | 1.063059 | 1.135805    | 0.935632       |
| medium | 1.234342 | 1.255871    | 1.161361       |

```
can you solve the mean-mean problem?
```

```
Object `problem` not found.
```

```
in the merge example we added the cuisine type, could you perform a groupby analysis\
↪on this?
```

```
Object `this` not found.
```

PIVOT

```
import pandas as pd
```

```
rating_df = pd.read_csv('./data/cuisine/rating_final.csv')
```

```
rating_df
```

```
   userID  placeID  rating  food_rating  service_rating
0    U1077   135085      2           2             2
1    U1077   135038      2           2             1
2    U1077   132825      2           2             2
3    U1077   135060      1           2             2
4    U1068   135104      1           1             2
...     ...     ...     ...         ...           ...
1156  U1043   132630      1           1             1
1157  U1011   132715      1           1             0
1158  U1068   132733      1           1             0
1159  U1068   132594      1           1             1
1160  U1068   132660      0           0             0

[1161 rows x 5 columns]
```

```
geo_df = pd.read_csv('./data/cuisine/geoplaces2.csv').set_index('placeID')
```

```
merged_rating_df = pd.merge(rating_df, geo_df, on='placeID')
merged_rating_df
```

```
   userID  placeID  rating  food_rating  service_rating  latitude \
0    U1077   135085      2           2             2  22.150802
1    U1108   135085      1           2             1  22.150802
2    U1081   135085      1           2             1  22.150802
3    U1056   135085      2           2             2  22.150802
4    U1134   135085      2           1             2  22.150802
...     ...     ...     ...         ...           ...     ...
1156  U1061   132958      2           2             2  22.144979
1157  U1025   132958      1           0             0  22.144979
1158  U1097   132958      2           1             1  22.144979
1159  U1096   132958      1           2             2  22.144979
1160  U1136   132958      2           2             2  22.144979

   longitude  the_geom_meter \
0   -100.982680  0101000020957F00009F823DA6094858C18A2D4D37F9A4...
```

(continues on next page)

(continued from previous page)

```

1    -100.982680  0101000020957F00009F823DA6094858C18A2D4D37F9A4...
2    -100.982680  0101000020957F00009F823DA6094858C18A2D4D37F9A4...
3    -100.982680  0101000020957F00009F823DA6094858C18A2D4D37F9A4...
4    -100.982680  0101000020957F00009F823DA6094858C18A2D4D37F9A4...
...
1156 -101.005683  0101000020957F000049095EB34A4858C15CB4BD1EE1AB...
1157 -101.005683  0101000020957F000049095EB34A4858C15CB4BD1EE1AB...
1158 -101.005683  0101000020957F000049095EB34A4858C15CB4BD1EE1AB...
1159 -101.005683  0101000020957F000049095EB34A4858C15CB4BD1EE1AB...
1160 -101.005683  0101000020957F000049095EB34A4858C15CB4BD1EE1AB...

      name                      address ... \
0    Tortas Locas Hipocampo  Venustiano Carranza 719 Centro ...
1    Tortas Locas Hipocampo  Venustiano Carranza 719 Centro ...
2    Tortas Locas Hipocampo  Venustiano Carranza 719 Centro ...
3    Tortas Locas Hipocampo  Venustiano Carranza 719 Centro ...
4    Tortas Locas Hipocampo  Venustiano Carranza 719 Centro ...
...
1156    tacos los volcanes          avenida hivno nacional ...
1157    tacos los volcanes          avenida hivno nacional ...
1158    tacos los volcanes          avenida hivno nacional ...
1159    tacos los volcanes          avenida hivno nacional ...
1160    tacos los volcanes          avenida hivno nacional ...

      alcohol  smoking_area  dress_code  accessibility  price \
0    No_Alcohol_Served  not permitted  informal  no_accessibility  medium
1    No_Alcohol_Served  not permitted  informal  no_accessibility  medium
2    No_Alcohol_Served  not permitted  informal  no_accessibility  medium
3    No_Alcohol_Served  not permitted  informal  no_accessibility  medium
4    No_Alcohol_Served  not permitted  informal  no_accessibility  medium
...
1156 No_Alcohol_Served          none  informal  completely  low
1157 No_Alcohol_Served          none  informal  completely  low
1158 No_Alcohol_Served          none  informal  completely  low
1159 No_Alcohol_Served          none  informal  completely  low
1160 No_Alcohol_Served          none  informal  completely  low

      url Rambience franchise  area other_services
0    ? familiar  f closed  none
1    ? familiar  f closed  none
2    ? familiar  f closed  none
3    ? familiar  f closed  none
4    ? familiar  f closed  none
...
1156 ? quiet  t closed  none
1157 ? quiet  t closed  none
1158 ? quiet  t closed  none
1159 ? quiet  t closed  none
1160 ? quiet  t closed  none

[1161 rows x 25 columns]

```

```
merged_rating_df.pivot(index='alcohol', columns='smoking_area', values='rating')
```

```
-----
ValueError
```

```
Traceback (most recent call last)
```

(continues on next page)



(continued from previous page)

```

/tmp/ipykernel_5491/1397663245.py in <module>
----> 1 merged_rating_df.pivot(index='alcohol', columns='smoking_area', values='rating
↳')

~/git/data-science-practical-approach/venv/lib/python3.8/site-packages/pandas/core/
↳frame.py in pivot(self, index, columns, values)
    7791         from pandas.core.reshape.pivot import pivot
    7792
-> 7793         return pivot(self, index=index, columns=columns, values=values)
    7794
    7795     _shared_docs[

~/git/data-science-practical-approach/venv/lib/python3.8/site-packages/pandas/core/
↳reshape/pivot.py in pivot(data, index, columns, values)
    515         else:
    516             indexed = data._constructor_sliced(data[values]._values,
↳index=multiindex)
-> 517         return indexed.unstack(columns_listlike)
    518
    519

~/git/data-science-practical-approach/venv/lib/python3.8/site-packages/pandas/core/
↳series.py in unstack(self, level, fill_value)
    4079         from pandas.core.reshape.reshape import unstack
    4080
-> 4081         return unstack(self, level, fill_value)
    4082
    4083         # -----

~/git/data-science-practical-approach/venv/lib/python3.8/site-packages/pandas/core/
↳reshape/reshape.py in unstack(obj, level, fill_value)
    458         if is_1d_only_ea_dtype(obj.dtype):
    459             return _unstack_extension_series(obj, level, fill_value)
-> 460         unstacker = _Unstacker(
    461             obj.index, level=level, constructor=obj._constructor_expanddim
    462         )

~/git/data-science-practical-approach/venv/lib/python3.8/site-packages/pandas/core/
↳reshape/reshape.py in __init__(self, index, level, constructor)
    131         raise ValueError("Unstacked DataFrame is too big, causing int32_
↳overflow")
    132
-> 133         self._make_selectors()
    134
    135         @cache_readonly

~/git/data-science-practical-approach/venv/lib/python3.8/site-packages/pandas/core/
↳reshape/reshape.py in _make_selectors(self)
    183
    184         if mask.sum() < len(self.index):
-> 185             raise ValueError("Index contains duplicate entries, cannot reshape
↳")
    186
    187         self.group_index = comp_index

ValueError: Index contains duplicate entries, cannot reshape

```

```
merged_rating_df.groupby(['alcohol', 'smoking_area']).mean().reset_index().pivot(index=
↳ 'alcohol', columns='smoking_area', values='rating')
```

| smoking_area      | none     | not permitted | only at bar | permitted | section  |
|-------------------|----------|---------------|-------------|-----------|----------|
| alcohol           |          |               |             |           |          |
| Full_Bar          | 1.305556 | 0.857143      | NaN         | 1.500000  | 1.272727 |
| No_Alcohol_Served | 1.186788 | 1.124402      | NaN         | 1.114286  | 1.265823 |
| Wine-Beer         | 1.217391 | 1.000000      | 1.368421    | 1.300000  | 1.275000 |

```
merged_rating_df.groupby(['alcohol', 'smoking_area']).count().reset_index().
↳ pivot(index='alcohol', columns='smoking_area', values='rating')
```

| smoking_area      | none  | not permitted | only at bar | permitted | section |
|-------------------|-------|---------------|-------------|-----------|---------|
| alcohol           |       |               |             |           |         |
| Full_Bar          | 36.0  | 7.0           | NaN         | 4.0       | 33.0    |
| No_Alcohol_Served | 439.0 | 209.0         | NaN         | 35.0      | 79.0    |
| Wine-Beer         | 161.0 | 9.0           | 19.0        | 10.0      | 120.0   |

```
geo_df.columns
```

```
Index(['latitude', 'longitude', 'the_geom_meter', 'name', 'address', 'city',
      'state', 'country', 'fax', 'zip', 'alcohol', 'smoking_area',
      'dress_code', 'accessibility', 'price', 'url', 'Rambience', 'franchise',
      'area', 'other_services'],
      dtype='object')
```

```
merged_rating_df.groupby(['city', 'smoking_area']).mean().reset_index().pivot(index=
↳ 'city', columns='smoking_area', values='rating')
```

| smoking_area    | none     | not permitted | only at bar | permitted | section  |
|-----------------|----------|---------------|-------------|-----------|----------|
| city            |          |               |             |           |          |
| ?               | 1.052632 | 1.000000      | NaN         | 1.833333  | 1.300000 |
| Cd Victoria     | 0.625000 | NaN           | NaN         | NaN       | NaN      |
| Cd. Victoria    | NaN      | 0.750000      | NaN         | NaN       | NaN      |
| Ciudad Victoria | NaN      | 1.300000      | NaN         | 0.750000  | NaN      |
| Cuernavaca      | 1.411765 | 1.157895      | 1.555556    | 1.500000  | 1.000000 |
| Jiutepec        | 1.461538 | NaN           | NaN         | 1.166667  | NaN      |
| San Luis Potosi | 1.211494 | 1.168317      | 1.200000    | NaN       | 1.273743 |
| Soledad         | 1.058824 | NaN           | NaN         | NaN       | NaN      |
| cuernavaca      | NaN      | 1.600000      | NaN         | NaN       | NaN      |
| s.l.p           | NaN      | 0.916667      | NaN         | NaN       | NaN      |
| s.l.p.          | 1.281250 | NaN           | NaN         | NaN       | NaN      |
| san luis potos  | 2.000000 | NaN           | NaN         | NaN       | NaN      |
| san luis potosi | 1.272727 | 1.000000      | NaN         | NaN       | 1.500000 |
| san luis potosi | NaN      | NaN           | NaN         | 1.400000  | NaN      |
| slp             | 1.166667 | NaN           | NaN         | NaN       | NaN      |
| victoria        | 1.000000 | 0.600000      | NaN         | 0.937500  | NaN      |
| victoria        | 0.750000 | NaN           | NaN         | NaN       | NaN      |

## **Part IV**

# **4. Data Exploration**



## DATA EXPLORATION

this is an introduction



## **Part V**

# **5. Data Visualisation**





## DATA VISUALISATION

this is an introduction



## **Part VI**

# **6. Machine Learning**



## **MACHINE LEARNING**

this is an introduction