```
import os
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
import numpy as np
from matplotlib import rcParams
from matplotlib.ticker import FuncFormatter
import matplotlib.ticker as mtick
import statsmodels.api as sm
from scipy import stats
from statsmodels.stats.outliers_influence import variance_inflation_factor
from statsmodels.tools.tools import add_constant
from statsmodels.stats.diagnostic import het_breuschpagan
from statsmodels.stats.stattools import durbin_watson
from statsmodels.stats.multicomp import pairwise_tukeyhsd
from statsmodels.stats.anova import AnovaRM
from statsmodels.formula.api import ols
from statsmodels.stats.multicomp import MultiComparison
from statsmodels.stats.power import TTestIndPower

final_data_path = "/Users/jessicaruan/Desktop/Panel Data Project/Financial Environment/Data"
os.chdir("/Users/jessicaruan/Desktop/Panel Data Project/Financial Environment/Data")

df_regular = pd.read_csv('Financial_Environment_Regular.csv')

df_final = df_final.sort_values(['Country', 'Year'])
df_final['lag_labor_productivity'] = df_final.groupby('Country')['labor_productivity'].shift(1)
df_final['labor_productivity_growth'] = (df_final['labor_productivity'] - df_final['lag_labor_productivity']) / df_final['lag_labor_productivity'] * 100

# Create GDP per capita growth rate
df_final['GDP_growth'] = df_final.groupby('Country')['GDP_per_capita'].pct_change() * 100
df_final['lag_GDP_growth'] = df_final.groupby('Country')['GDP_growth'].shift(1)
df_final['lag_GDP_per_capita'] = df_final.groupby('Country')['GDP_per_capita'].shift(1)

# Create the interaction variable between capital labor productivity growth
df_final['Capital_labor_productivity_growth'] = df_final['Capital_productivity'] * df_final['labor_productivity_growth']
df_final['lag_Capital_labor_productivity_growth'] = df_final.groupby('Country')['Capital_labor_productivity_growth'].shift(1)
df_final['lag_Capital_labor_productivity'] = df_final.groupby('Country')['Capital_productivity'] * df_final['lag_labor_productivity_lag']

# Saving the regression-ready dataset
df_final.to_csv('Financial_Environment_Regular.csv', index=False)

variables = ['lag_GDP_per_capita', 'lag_labor_productivity', 'lag_age', 'lag_trade_openness', 'lag_financial_freedom', 'lag_inflation', 'lag_GDP_growth', 'lag_gdp_growth_lag', 'lag_labor_productivity_growth_lag']

# Drop rows with missing values in these variables
df_final = df_final.dropna(subset=['lag_GDP_per_capita', 'lag_labor_productivity', 'lag_age', 'lag_trade_openness', 'lag_financial_freedom', 'lag_inflation', 'lag_GDP_growth', 'lag_gdp_growth_lag', 'lag_labor_productivity_growth_lag'])

# Verifying the data into the separate regimes + pre 2020, 2020-2021, post 2021

df_regular = df_final.copy()

conditions = [
    (df_final['Year'] < 2020),
    (df_final['Year'] >= 2020) & (df_final['Year'] <= 2021),
    (df_final['Year'] > 2021)
]
regimes = ['Stable Standard', 'Stricter Abuse', 'Transformative']

regime_map = {1: 'Stable Standard', 2: 'Stricter Abuse', 3: 'Transformative'}
df_final['Regime'] = np.select(conditions, [1, 2, 3], default=0)
df_final['Regime'] = df_final['Regime'].map(regime_map)
df_final['Regime'] = pd.Categorical(df_final['Regime'], categories=regimes, ordered=True)
df_final = df_final[df_final['Regime'] != 'Unknown']

import statsmodels.api as sm
from statsmodels.stats.outliers_influence import variance_inflation_factor

# Define dependent and independent variables
dependent_variable = 'labor_productivity'
independent_variables = [
    'Capital_productivity',
    'lag_GDP_per_capita',
    'lag_age',
    'lag_trade_openness',
    'lag_financial_freedom',
    'lag_inflation',
    'lag_GDP_growth',
    'lag_gdp_growth_lag',
    'lag_labor_productivity_growth_lag',
    'Capital_labor_productivity_growth',
    'lag_Capital_labor_productivity_growth',
    'lag_Capital_labor_productivity'
]

# Create the regression dataset
df_regression = df_final[[dependent_variable] + independent_variables + ['Regime']].dropna()

# Add constant term for regression
X = sm.add_constant(df_regression[independent_variables])
y = df_regression[dependent_variable]

# Calculate VIF for each variable
vif_data = pd.DataFrame()
vif_data["Variable"] = X.columns
vif_data["VIF"] = [variance_inflation_factor(X.values, i) for i in range(X.shape[1])]

print("Variance Inflation Factors:")
print(vif_data)

# Identify variables with high VIF (typically > 5 or 10)
high_vif = vif_data[vif_data["VIF"] > 5]
if not high_vif.empty:
    print("\nVariables with high multicollinearity (VIF > 5):")
    print(high_vif)
else:
    print("\nNo variables with high multicollinearity (VIF > 5)")

# Fit the regression model
model = sm.OLS(y, X).fit()

# Print regression results
print("\nRegression Results:")
print(model.summary())

# Calculate and print adjusted R-squared
print(f"\nAdjusted R-squared: {model.rsquared_adj:.4f}")

# Calculate and print number of observations
print(f"Number of observations: {model.nobs}")

# Calculate and print number of regressors (including constant)
print(f"Number of regressors: {model.df_model + 1}")

# Calculate and print degrees of freedom
print(f"Degrees of freedom: {model.df_resid}")

# Calculate and print F-statistic and its p-value
print(f"F-statistic: {model.fvalue:.4f}")
print(f"Prob (F-statistic): {model.f_pvalue:.4e}")

# Calculate and print AIC and BIC
print(f"AIC: {model.aic:.4f}")
print(f"BIC: {model.bic:.4f}")

# Check for heteroscedasticity using Breusch-Pagan test
from statsmodels.stats.diagnostic import het_breuschpagan
bp_test = het_breuschpagan(model.resid, model.model.exog)
print("\nBreusch-Pagan test for heteroscedasticity:")
print(f"LM Statistic: {bp_test[0]:.4f}")
print(f"LM-Test p-value: {bp_test[1]:.4f}")
print(f"F-Statistic: {bp_test[2]:.4f}")
print(f"F-Test p-value: {bp_test[3]:.4f}")

# Check for autocorrelation using Durbin-Watson test
from statsmodels.stats.stattools import durbin_watson
dw = durbin_watson(model.resid)
print("\nDurbin-Watson statistic:")
print(dw)

# Check for normality of residuals using Jarque-Bera test
from statsmodels.stats.stattools import jarque_bera
jb = jarque_bera(model.resid)
print("\nJarque-Bera test for normality of residuals:")
print(f"JB Statistic: {jb[0]:.4f}")
print(f"JB-Test p-value: {jb[1]:.4f}")

# Check for normality of residuals using Shapiro-Wilk test
from scipy.stats import shapiro
sw = shapiro(model.resid)
print("\nShapiro-Wilk test for normality of residuals:")
print(f"SW Statistic: {sw[0]:.4f}")
print(f"SW-Test p-value: {sw[1]:.4f}")

# Check for normality of residuals using Kolmogorov-Smirnov test
from scipy.stats import kstest
ks = kstest(model.resid, 'norm')
print("\nKolmogorov-Smirnov test for normality of residuals:")
print(f"KS Statistic: {ks[0]:.4f}")
print(f"KS-Test p-value: {ks[1]:.4f}")

# Check for normality of residuals using Anderson-Darling test
from statsmodels.stats.diagnostic import normal_ad
ad = normal_ad(model.resid)
print("\nAnderson-Darling test for normality of residuals:")
print(f"AD Statistic: {ad[0]:.4f}")
print(f"AD-Test p-value: {ad[1]:.4f}")

# Check for normality of residuals using Lilliefors test
from statsmodels.stats.diagnostic import lilliefors
lf = lilliefors(model.resid)
print("\nLilliefors test for normality of residuals:")
print(f"LF Statistic: {lf[0]:.4f}")
print(f"LF-Test p-value: {lf[1]:.4f}")

# Check for normality of residuals using Cramer-von Mises test
from statsmodels.stats.diagnostic import cramervonmises
cvm = cramervonmises(model.resid, 'norm')
print("\nCramer-von Mises test for normality of residuals:")
print(f"CVM Statistic: {cvm.statistic:.4f}")
print(f"CVM-Test p-value: {cvm.pvalue:.4f}")

# Check for normality of residuals using Anderson-Darling test
from statsmodels.stats.diagnostic import normal_ad
ad = normal_ad(model.resid)
print("\nAnderson-Darling test for normality of residuals:")
print(f"AD Statistic: {ad[0]:.4f}")
print(f"AD-Test p-value: {ad[1]:.4f}")

# Check for normality of residuals using Lilliefors test
from statsmodels.stats.diagnostic import lilliefors
lf = lilliefors(model.resid)
print("\nLilliefors test for normality of residuals:")
print(f"LF Statistic: {lf[0]:.4f}")
print(f"LF-Test p-value: {lf[1]:.4f}")

# Check for normality of residuals using Cramer-von Mises test
from statsmodels.stats.diagnostic import cramervonmises
cvm = cramervonmises(model.resid, 'norm')
print("\nCramer-von Mises test for normality of residuals:")
print(f"CVM Statistic: {cvm.statistic:.4f}")
print(f"CVM-Test p-value: {cvm.pvalue:.4f}")

# Add fixed effects (dummy variables)
df = pd.get_dummies(df_regression, columns=['Regime'], drop_first=True)

# Define dependent and independent variables
dependent_variable = 'labor_productivity'
independent_variables = [
    'Capital_productivity',
    'lag_GDP_per_capita',
    'lag_age',
    'lag_trade_openness',
    'lag_financial_freedom',
    'lag_inflation',
    'lag_GDP_growth',
    'lag_gdp_growth_lag',
    'lag_labor_productivity_growth_lag',
    'Capital_labor_productivity_growth',
    'lag_Capital_labor_productivity_growth',
    'lag_Capital_labor_productivity',
    'Regime_Stricter Abuse',
    'Regime_Transformative'
]

# Add constant term for regression
X = sm.add_constant(df[independent_variables])
y = df[dependent_variable]

# Fit the regression model
model = sm.OLS(y, X).fit()

# Print regression results
print("\nRegression Results:")
print(model.summary())

# Calculate and print adjusted R-squared
print(f"\nAdjusted R-squared: {model.rsquared_adj:.4f}")

# Calculate and print number of observations
print(f"Number of observations: {model.nobs}")

# Calculate and print number of regressors (including constant)
print(f"Number of regressors: {model.df_model + 1}")

# Calculate and print degrees of freedom
print(f"Degrees of freedom: {model.df_resid}")

# Calculate and print F-statistic and its p-value
print(f"F-statistic: {model.fvalue:.4f}")
print(f"Prob (F-statistic): {model.f_pvalue:.4e}")

# Calculate and print AIC and BIC
print(f"AIC: {model.aic:.4f}")
print(f"BIC: {model.bic:.4f}")

# Check for heteroscedasticity using Breusch-Pagan test
from statsmodels.stats.diagnostic import het_breuschpagan
bp_test = het_breuschpagan(model.resid, model.model.exog)
print("\nBreusch-Pagan test for heteroscedasticity:")
print(f"LM Statistic: {bp_test[0]:.4f}")
print(f"LM-Test p-value: {bp_test[1]:.4f}")
print(f"F-Statistic: {bp_test[2]:.4f}")
print(f"F-Test p-value: {bp_test[3]:.4f}")

# Check for autocorrelation using Durbin-Watson test
from statsmodels.stats.stattools import durbin_watson
dw = durbin_watson(model.resid)
print("\nDurbin-Watson statistic:")
print(dw)

# Check for normality of residuals using Jarque-Bera test
from statsmodels.stats.stattools import jarque_bera
jb = jarque_bera(model.resid)
print("\nJarque-Bera test for normality of residuals:")
print(f"JB Statistic: {jb[0]:.4f}")
print(f"JB-Test p-value: {jb[1]:.4f}")

# Check for normality of residuals using Shapiro-Wilk test
from scipy.stats import shapiro
sw = shapiro(model.resid)
print("\nShapiro-Wilk test for normality of residuals:")
print(f"SW Statistic: {sw[0]:.4f}")
print(f"SW-Test p-value: {sw[1]:.4f}")

# Check for normality of residuals using Kolmogorov-Smirnov test
from scipy.stats import kstest
ks = kstest(model.resid, 'norm')
print("\nKolmogorov-Smirnov test for normality of residuals:")
print(f"KS Statistic: {ks[0]:.4f}")
print(f"KS-Test p-value: {ks[1]:.4f}")

# Check for normality of residuals using Anderson-Darling test
from statsmodels.stats.diagnostic import normal_ad
ad = normal_ad(model.resid)
print("\nAnderson-Darling test for normality of residuals:")
print(f"AD Statistic: {ad[0]:.4f}")
print(f"AD-Test p-value: {ad[1]:.4f}")

# Check for normality of residuals using Lilliefors test
from statsmodels.stats.diagnostic import lilliefors
lf = lilliefors(model.resid)
print("\nLilliefors test for normality of residuals:")
print(f"LF Statistic: {lf[0]:.4f}")
print(f"LF-Test p-value: {lf[1]:.4f}")

# Check for normality of residuals using Cramer-von Mises test
from statsmodels.stats.diagnostic import cramervonmises
cvm = cramervonmises(model.resid, 'norm')
print("\nCramer-von Mises test for normality of residuals:")
print(f"CVM Statistic: {cvm.statistic:.4f}")
print(f"CVM-Test p-value: {cvm.pvalue
```

```
18       False
22       False
13       False
15       False
20       False
19       False
12       False
14       False
21       False
16       False
34       False
35       False
30       False
32       False
39       False
31       False
37       False
38       False
```