

FinalProject Peer2Peer Systems and blockchains  
Development of a DAPP for Smart Auctions

Lorenzo Bellomo, 531423

## Project Structure

The project is organized as follows:

- *Root folder*: It contains only the report file and a folder DAPP, all the code is in this folder.
- *DAPP folder*: It contains the configurations files needed (*bs-config.json* for lite-server, *package.json* for node, *truffle-config.json* for truffle). It additionally holds file *ropsten.json*, which contains the private credentials for ropsten deployment. Then other folders are explained just in the next points.
- *contracts, migrations, test and build*: Truffle related folders. They are compulsory when dealing with truffle projects. Also, at this level, the build folder is generated.
- *node\_modules and src*: Folders related to node and the front-end part. The *src* folder contains some *.css* files (bootstrap).
- *index.html*: It only contains the view for the top navbar in the web page, and the two buttons used to choose the auction to render.
- *views folder*: It contains *vickrey.html* and *dutch.html*, which are the files needed to render the auctions.
- *js/app.js*: This is the file that contains the logic for the initialization of web3, the rendering of the two auctions, the handling of all the callbacks and it also manages the interface towards the contracts. All the contract calls to the contracts (setters, getters and events for both the auctions), are handled in this file. The file structure is organized in three parts. The top part contains the web3 initialization, which is common to both auctions. The middle part is the Vickrey auction related one. It contains a method (*listenForEventsV()*) for setting up the callbacks for this type of auction, another one for all the calls to the main methods (*callerV()*), another one for the getters (*getterV()*) and some other small utility ones. The third and last part is identical to the former one, but related to the Dutch auction.

## Contracts ChangeLog

This section contains all the modifications applied to the delivered Final Term smart contracts. All the modifications have a motivation assigned.

- *Vickrey - Removed file Util.sol*: the only method that was provided in this file (computation of the nonce and amount hash for the Vickrey auction) has been moved to the file Vickrey auction.
- *Both - Added auctioneer role*: the text of the project explicitly asks for an auctioneer role. The owner decides which account is the auctioneer when he calls the newly added method *createAuction*. If he does not decide an auctioneer, he becomes the one to take the role. As a note, in the Vickrey auction, the role of the auctioneer doesn't have a clear purpose. The way

it will be used during the tests is to take care of the phase switches (at his expenses).

- *Both - Moved start time:* Both auctions, in the provided FinalTerm implementation, started in the moment the constructor was called. This was split in two phases. Phase one starts when the constructor is called, and it is the phase in which the auction is on the blockchain, but is not yet active (note, grace period is considered active). The secondPhase starts when the owner calls the method createAuction. In this method, the grace period begins and an event is emitted.
- *Dutch - Added auctionPhase:* In order to better implement the previous point, the boolean variable ended has been changed to a phase enum in the Dutch Auction. The phases are NEW, ALIVE and ENDED.
- *Dutch - Changed assert to require:* In order to better respect the require-assert definition, the assert in the constructor has been changed to a require.
- *Both - Added some getters:* In order to improve clarity and respect the previous changes in the contracts, some getters have been added.
- *Both - Added suicide operation:* The auction suicides whenever the owner of this auction presses on the red button in the UI.

## Main Project Choices

Below are listed the main project choices, together with an explanation regarding the reasoning behind those ones.

- *One HTML view:* The main choice is the one to collapse the three views (auctioneer, owner and bidder) in one HTML page. Technically this is incorrect (because of course every role should have its own customized web view), but this strongly simplifies testing and gives a broader view of the auction as a whole. This choice was taken mainly due to the fact that the setup code is identical for all the roles.
- *address management:* The first choice (collapsing the html views) strongly implies that it is not possible to fetch the MetaMask address while in initialization phase, and then use the same one for the whole interaction. This means that, for each operation that needs to have an address specified, it has to be fetched from MetaMask, resulting in a (very low) delay. The operations affected are only the main contract ones, as getter methods do not need to specify the address they come from.
- *HTML view organization:* The web index prompts to the choice between the two implemented auctions (Dutch and Vickrey). After deciding which one to view, the web3 initialization process begins, which ends with the rendering of the appropriate view for the two auctions. The web page is organized in three areas:
  - *Top area:* Provides all the operations for the three roles of the auction.

- *Bottom Left area*: Provides an interface to call some getter methods from the contract and shows the result of both the main methods from the top area and the getters.
- *Bottom Right area*: Area with some live information about the auction, together with all the events generated from the smart contract.
- *Vickrey Auction bids*: The Vickrey auction interface provides the ability to bid and open a commitment. The interface does not provide an input field for the nonce and for the hash, but handles those transparently. In addition to that, the only input to be provided for making a bid is the bidding value, and it is provided directly in the bidding phase (in opposition with the contract, where the payment of that amount is delayed to the opening phase). The DAPP will handle the contract payment delay, together with the handling of the hashes and nonces transparently for the user.

## Testing and Setup

In order to test locally the project those action are going to be needed:

1. *Run Ganache*: The default port varies. The one that has been set in the project configuration file is 7545. If this is not the case, then just change property *port* of *development* in the *truffle-config.json* file.
2. *Migrate*: Do *truffle migrate --reset* in order to compile the project and deploy them on the Ropsten test net. The account that pays the deployment price is the first one in Ganache. This also generates the build folder. The parameters passed to the contract constructors are specified in the file *1\_initial\_migration.js*. In order to change them, just edit this file.
3. *Run the server*: Just do *npm run dev*. This starts the lite server.
4. *Browser*: At this point, two things are going to be needed: *MetaMask* and the *web view*. Just open on the browser *localhost:3000*. Now login with your MetaMask with an account and connect it to Ganache. Import the needed amount of accounts from Ganache through their private key and the setup should be complete.

## Migration on Ropsten