x86 Crash Course

With a focus on Linux and a glance to x86_64

Mario Polino, Marcello Pogliani

March 19, 2019

DEIB, Politecnico di Milano

Credits — contributors as of March 19, 2019

- Main contributor: Andrea Mambretti (wrote the first version)
- Mario Polino
- Marcello Pogliani
- Stefano Zanero
- Federico Maggi

**Instruction Set Architecture (ISA)**

- "Logical" specification of a computer architecture
- Concerned with programming concepts
    - instructions, registers, interrupts, memory architecture, . . .
- May differ (widely) from the actual microarchitecture
- Examples:
    - x86 (IA-32 and x86_64)
    - ARM (mobile devices)
    - MIPS (embedded devices, e.g., consumer routers)
    - AVR, SPARC, Power, RISC-V, . . .

The x86 ISA

- Born in 1978, 16-bit ISA (Intel 8086)
- Evolved in a 32-bit ISA (1985, Intel 80386) and a 64-bit ISA (2003, AMD Opteron)
- CISC design (e.g., string operations)
- Many "legacy" features (e..g, segmentation)
- We'll see the "basic" ISA — there are various processor-specific features and extensions, such as SIMD (MMX, SSE, . . .) with their own instructions and registers[1]

---

[1]Complete reference: Intel Software Developer's Manual, about 5,000 pages
(https://software.intel.com/en-us/articles/intel-sdm)

IA-32: Registers

- General-purpose registers
    - EAX, EBX, ECX, EDX
    - ESI, EDI (source and destination index for string operations)
    - EBP (base pointer)
    - ESP (stack pointer)
- Instruction pointer: EIP
    - No explicit access
    - Modified by `jmp`, `call`, `ret`
    - Read through the stack (saved IP)
- Program status and control: EFLAGS
- (segment registers)

IA-32: `EFLAGS` register

X ID Flag (ID)
X Virtual Interrupt Pending (VIP)
X Virtual Interrupt Flag (VIF)
X Alignment Check / Access Control (AC)
X Virtual-8086 Mode (VM)
X Resume Flag (RF)
X Nested Task (NT)
X I/O Privilege Level (IOPL)
S Overflow Flag (OF)
C Direction Flag (DF)
X Interrupt Enable Flag (IF)
X Trap Flag (TF)
S Sign Flag (SF)
S Zero Flag (ZF)
S Auxiliary Carry Flag (AF)
S Parity Flag (PF)
S Carry Flag (CF)

S Indicates a Status Flag
C Indicates a Control Flag
X Indicates a System Flag

Reserved bit positions. DO NOT USE.
Always set to values previously read.

IA-32: EFLAGS register

- 32-bits register, boolean flags
- **Program status**: overflow, sign, zero, auxiliary carry (BCD), parity, carry
    - Indicate the result of arithmetic instructions
    - Extremely important for control flow
- **Program control**: direction flag
    - controls string instructions (auto-increment or auto-decrement)
- **System**: control operating-system operations

Fundamental data types

byte 8 bits

word 2 bytes

dword Doubleword, 4 bytes (32 bits)

qword Quadword, 8 bytes (64 bits)

Assembly language: specific to each ISA, mapped to binary code

For simplicitly, we don't deal with the *linking* process.

Assembly: Syntax

Two main syntaxes:

- **Intel**: default in most Windows programs (e.g., IDA)
- **AT&T**: default in most UNIX tools (e.g., gdb, objdump)

Beware: The order of the operands is **different**

We will use the Intel syntax

Assembly: Syntax

move the value 0 to EAX

Intel

mov eax, 0h

AT&T

movl $0x0,%eax

move the value 0 to the address contained in EBX+4

Intel

mov [ebx+4h],0h

AT&T

movl $0x0,0x4(%ebx)

x86: data movement

Examples

Immediate to register:

```
mov eax, 4h                     EAX = 4
```

Register to register:

```
mov eax, ebx                    EAX = EBX
```

Memory to register (and register to memory):

```
mov eax, [ebx]                  EAX = *EBX
mov eax, [ebx + 4h]             EAX = *(EBC + 4)
mov eax, [edx + ebx*4 + 8]      EAX = *(EDX + EBX * 4 + 8)
```

Note: memory to memory is an **invalid** combination[2]

---

[2]Except in some instructions, such as movs (move from string to string).

x86 Assembly and Machine Code

Instruction = opcode + operand

Example

	mov r/m r	ebp, esp
`mov ebp, esp`	89	E5 10
	mov bl	
`mov bl, 10`	B3	0A
	size prefix	
`mov bx, 10`	66 BB	0A 00
	mov ebx	
`mov ebx, 10`	BB	0A 00 00 00
	opcode (1-2 bytes)	*operands*

Beware: in x86, instructions have **variable length**.

Basic instructions

- **Data Transfer**: mov, push, pop, xchg, lea
- **Integer Arithmetic**: add, sub, mul, imul, div, idiv, inc, dec
- **Logical**: and, or, not, xor
- **Control Transfer**: jmp, jne, call, ret
- and lots more...

Data Transfer: `mov`

- `mov` **destination**, **source**
  source: immediate, register, memory location
  destination: register or memory location
- Basic load/store operations
    - Register to register, register to memory, immediate to register, immediate to memory
    - Memory to memory is INVALID (in every instruction)

Examples

MOV eax, ebx	MOV eax, FFFFFFFFh	MOV ax, bx
MOV [eax],ecx	MOV [eax],[ecx] NO!!!	MOV al, FFh

Integer Arithmetics: `add` and `sub`

add **destination**, **source**	sub **destination**, **source**
dest ← dest + source	dest ← dest − source

- Addressing:
  source: immediate, register, memory location
  destination: register or memory location
  (the destination has to be at least as large as the source)
- Negate a value: neg [op]
- Bitwise operations: and, or, xor, not work similarly

Examples

add esp, 44h	add edx, cx	add al, dh
sub esp, 33h	sub eax, ebx	sub [eax], 1h

Integer Arithmetics: unsigned multiply (`mul`)

- `mul` **source**

  source: register or memory location
- dest $\leftarrow$ implied_op $\times$ source
- **Implied operands** according to the size of **source**
  - First operand: `AL`, `AX`, or `EAX`
  - Destination: `AX`, `DX:AX`, `EDX:EAX` (double the size of **source**)
- Signed multiply: `imul`

Example

- `mul ebx`: `EDX:EAX` $\leftarrow$ `EAX * EBX`
  - most significant bits of the result in `EDX`
  - least significant bits of the result in `EAX`

- `mul cx`: `DX:AX` $\leftarrow$ `AX * CX`

- `mul cl`: `AX` $\leftarrow$ `AL * CL`

Integer Arithmetics: unsigned divide (div)

- div **source**

  source: register or a memory location
- Computes quotient and remainder
- Implied operand: EDX:EAX (according to the size of **source**)
- Signed divide: idiv

Examples

- div ebx (4 bytes)
    - EAX ← EDX:EAX / EBX
    - EDX ← EDX:EAX % EBX
- div bx (2 bytes)
    - AX ← DX:AX / BX   DX = DX:AX % BX
- div bl (1 byte)
    - AL ← AX / BX   AH = AX % BX

Integer Arithmetics: `cmp` and `test`

`cmp` **op1**, **op2**	`test` **op1**, **op2**
Computes op1 − op2	Computes op1 & op2

- Sets the flags (`ZF`,`CF`, `OF`, . . .)
- Discards the result

Examples

`cmp eax, ebx`	`cmp eax, 44BBCCDDh`	`cmp al, dh`
`cmp al, 44h`	`cmp ax,FFFFh`	`cmp [eax],4h`

Control-Flow Instructions: unconditional jump `jmp`

0x080483a0	Program Instruction
	↓
0x080483a1	jmp 0x080483ad
0x080483a3	Instruction never executed

0x080483ad	Other Block Instruction

- jmp **address** or **offset**
- Unconditional jump: just set the EIP to **address**
- Can be also *relative*: increment or decrement EIP by an offset

Control-Flow Instructions: conditional jumps

j<cc> **address** or **offset**

Jump to **address** if and only if a certain condition is verified

<cc>: condition

- O,NO,S,NS,E,Z,NE, . . .
- based on one or more status flags of EFLAGS

Examples:

- jz = jump if zero
- jg = jump if greater than
- jlt = jump if less than

Reference: http://www.unixwiz.net/techtips/x86-jumps.html

A very simple example (what does it do?)

Assume that the input is in registers: ECX and EDX; output: EAX

```
       mov eax, ecx
       mov ebx, edx
       cmp ebx, 0
       jz label
loop:
       cmp ebx, 1
       jle ret
       xor edx, edx
       mul ecx
       sub ebx, 1
       jmp loop
label:
       mov eax, 1
ret:
       ...
```

Load effective address (`lea`)

- `lea` **destination**, **source**
  source: memory location
  destination: register
- Like a mov, but it is storing the pointer, not the value
- It does NOT access memory

Example

	Registers		Memory	

Registers   Memory

EAX `0x00000000`

`0x7C81776F` `0x00403A40`
`0x7C911000` `0x00403A44`

EBX `0x00403A40`

`0x0012C140` `0x00403A48`
`0x7FFDB000` `0x00403A4C`

...

`lea eax, [ebx + 8]` $\rightarrow$ `EAX = 0x00403A48`

N.B.: with `mov eax, [ebx+8]` $\rightarrow$ `EAX = 0x0012C140`

23

- nop = **No Operation**. Just move to next instruction.
- The opcode is pretty famous and is 0x90
- Really useful in exploitation (we will see!)

Interrupts and Syscalls

- int **value**
    - **value**: software interrupt number to generate (0-255)
    - Every OS has its set of interrupt numbers (e.g., 80h for Linux system calls)
- syscall used for Linux 64-bit
- sysenter used by Microsoft Windows

8 new general purpose registers

Endianness

Endianness: convention that specifies in which order the bytes of a data word are lined up sequentially in memory.

Big-endian (left)

Systems in which the *most significant byte* of the word is stored in the *smallest address* given.

Little-endian

Systems in which the *least significant* byte is stored in the *smallest address*. IA-32 is "little endian".

Program Layout and Functions

Binary File Formats

- **PE (Portable Executable):** used by Microsoft binary executables
- **ELF:** common binary format for Unix, Linux, FreeBSD and others
- In both cases, we are interested in how each executable is mapped into memory, rather than how it is organized on disk.

## How an executable is mapped to memory in Linux (ELF)

Executable	Description
.bss	This section holds uninitialized data that contributes to the program's memory image. By definition, the system initializes the data with zeros when the program begins to run.
.comment	This section holds version control information.
.data/.data1	These sections hold initialized data that contribute to the program's memory image
.debug	This section holds information symbolic debugging.
.text	This section holds the "text," or executable instructions, of a program.
.init	This section holds executable instructions that contribute to the process initialization code. That is, when a program starts to run, the system arranges to execute the code in this section before calling the main program entry point (called main for C programs).
.got	This section holds the global offset table.

How an executable is mapped to memory in Windows (PE)

Executable	Description
.text	Contains the executable code
.rdata	Holds read-only data that is globally accessible within the program
.data	Stores global data accessed throughout the program
.idata	stores the import function information;
.edata	stores the export function information;
.pdata	Present only in 64-bit executables and stores execption-handling information
.rsrc	Stores resources needed by the executable
.reloc	Contains information for relocation of library files

Simplified program memory layout

Low addresses (0x80000000)

Shared libraries
`.text`
`.bss`
Heap (grows ↓)
...
Stack (grows ↑)
`env`
`argv`

High addresses (0xbfffffff)

The stack

- LIFO (last in first out) data structure
- Used to manage functions
  - local variables
  - return addresses
  - ...
- Handled through the register ESP (stack pointer)
- Remember: the stack grows **toward lower addresses** (downward the address space)

Stack Management Instructions: push

<div style="text-align:center">

push **immediate** or **register**

</div>

Stores the immediate or register value at the top of the stack and decrements the ESP of the operand size

Example

Initial condition: EAX $= 30$

push eax

is equivalent to:

sub esp, 4
mov DWORD PTR [esp], eax

Low addresses (0x80000000)

| ... |
| |
| |
| 100 | ← ESP |
| ... |

High addresses (0xbfffffff)

Stack Management Instructions: push

<center>push **immediate** or **register**</center>

Stores the immediate or register value at the top of the stack and
decrements the ESP of the operand size

### Example

Initial condition: EAX = 30

push eax

is equivalent to:

sub esp, 4
mov DWORD PTR [esp], eax

Low addresses (0x80000000)

...	
	← ESP
100	
...	

High addresses (0xbfffffff)

Stack Management Instructions: `push`

<div align="center">

push **immediate** or **register**

</div>

Stores the immediate or register value at the top of the stack and decrements the `ESP` of the operand size

Example

Final condition: `EAX = 30`

```
push eax
```

is equivalent to:

```
sub esp, 4
mov DWORD PTR [esp], eax
```

Low addresses (0x80000000)

...
30	← ESP
100
...

High addresses (0xbfffffff)

Stack Management Instructions: pop

pop **destination**

Loads to the destination a word off the top of the stack, then it increases ESP of the operand's size.

**Example**

Initial condition: EAX = ???

pop eax

is equivalent to:

mov eax, DWORD PTR [esp]
add esp, 4

Low addresses (0x80000000)

...
30	← ESP
100
...

High addresses (0xbfffffff)

<p align="center">pop <u>destination</u></p>

Loads to the destination a word off the top of the stack, then it increases ESP of the operand's size.

Example

Low addresses (0x80000000)

Initial condition: EAX = 30

pop eax

is equivalent to:

```
mov eax, DWORD PTR [esp]
add esp, 4
```

...
30	← ESP
100
...

High addresses (0xbfffffff)

34

Stack Management Instructions: `pop`

pop **destination**

Loads to the destination a word off the top of the stack, then it increases ESP of the operand's size.

Example

Low addresses (0x80000000)

Final condition: `EAX = 30`

`pop eax`

is equivalent to:

`mov eax, DWORD PTR [esp]`
`add esp, 4`

...	
30	
100	← ESP
...	

High addresses (0xbfffffff)

Calling a function

Instruction `call`:

- Push to the stack the address of the next instruction
- Move the address of the first instruction of the callee into EIP

Example: Let's call `func`, located at 0x800bff00

Low addresses (0x80000000)

Equivalent to:

- push eip
- jmp func

(reminder: we can't read or
set EIP directly!)

High addresses (0xbfffffff)

EIP = 0x8001020

Calling a function

Instruction `call`:

- Push to the stack the address of the next instruction
- Move the address of the first instruction of the callee into EIP

Example: Let's call `func`, located at 0x800bff00

Low addresses (0x80000000)

Equivalent to:

- push eip
- jmp func

(reminder: we can't read or set EIP directly!)

...
0x8001020	← ESP
Stack top
...

High addresses (0xbfffffff)

EIP = 0x8001020

35

Calling a function

Instruction `call`:

- Push to the stack the address of the next instruction
- Move the address of the first instruction of the callee into EIP

Example: Let's call `func`, located at 0x800bff00

Equivalent to:

- push eip
- jmp func

(reminder: we can't read or
set EIP directly!)

Low addresses (0x80000000)

...	
0x8001020	← ESP
Stack top	
...	

High addresses (0xbfffffff)

EIP = 0x800bff00

Returning from a function

Instruction `ret`:

- Restores the return address saved by `call` from the top of the stack

Example: let's return from `func`

Equivalent to:

- `pop eip`

(reminde: we can't read or set EIP directly!)

Low addresses (0x80000000)

...
0x8001020 ← ESP
Stack top
...

High addresses (0xbfffffff)

$EIP = 0x800bff00$

Returning from a function

Instruction `ret`:

- Restores the return address saved by `call` from the top of the stack

Example: let's return from `func`

Low addresses (0x80000000)

...
Stack top	← ESP
...

Equivalent to:

- pop eip

(reminde: we can't read or set EIP directly!)

High addresses (0xbfffffff)

EIP = 0x8001020

Functions and Stack Frames

- Stack frame = stack area allocated to a function
- EBP register: pointer to the beginning (base) of a function's frame
- At the beginning of a function:
  - Save EBP to stack
  - Set EBP to the address of the function's frame

Low addresses (0x80000000)


High addresses (0xbfffffff)

37

Entering a function

Example: We've just called `func`, **located at 0x800bff00**

Low addresses (0x80000000)

...	
0x8001020	← ESP
...	
caller's sEBP	← EBP
...	

func's frame encompasses the top three rows (... , empty, 0x8001020)

Setup the stack frame

- `push ebp`
- `mov ebp, esp`

High addresses (0xbfffffff)

Entering a function

Example: We've just called `func`, located at 0x800bff00

Low addresses (0x80000000)

Setup the stack frame

- push ebp

- mov ebp, esp

func's frame:
- ...
- Saved EBP   ← ESP
- 0x8001020
- ...
- caller's sEBP   ← EBP
- ...

High addresses (0xbfffffff)

Entering a function

Example: We've just called `func`, **located at 0x800bff00**

Low addresses (0x80000000)

func's frame

...
Saved EBP
0x8001020
...
caller's sEBP
...

← EBP
← ESP

Setup the stack frame

- `push ebp`
- `mov ebp, esp`

High addresses (0xbfffffff)

Leaving a function

Instruction `leave`: restores the caller's base pointer

Example: We're about to return from `func`

Low addresses (0x80000000)

func's frame	...	
	(... locals ...)	← ESP
	Saved EBP	← EBP
	0x8001020	
	...	
	caller's sEBP	
	...	

Equivalent to:

- `mov esp, ebp`
- `pop ebp`

High addresses (0xbfffffff)

39

Leaving a function

Instruction `leave`: restores the caller's base pointer

Example: We're about to return from `func`

Low addresses (0x80000000)

Equivalent to:

- `mov esp, ebp`

- `pop ebp`

High addresses (0xbfffffff)

Leaving a function

Instruction `leave`: restores the caller's base pointer

Example: We're about to return from `func`

Low addresses (0x80000000)

Equivalent to:

- `mov esp, ebp`
- `pop ebp`

High addresses (0xbfffffff)

Calling Conventions

- Defines
    - how to pass parameters (stack, registers or both, and who is responsible to clean them up)
    - how to return values
    - caller-saved or callee-saved registers
- The high-level language, the compiler, the OS, and the target architecture all together "implement" and "agree upon" a certain calling convention
    - it's part of the ABI, the Application Binary Interface

Calling Conventions: cdecl (C declaration)

- Default calling convention used by most x86 C compilers
  - Can be forced with the modifier `_cdecl`
- Arguments: passed **through the stack**, right to left order
- Cleanup: the **caller removes** the parameters from the stack *after* the called function completes
- Return: register RAX
- Caller-saved registers: EAX, ECX, EDX (other are callee-saved)

cdecl: **Example**

```c
void demo_cdecl(int a, int b, int c, int z);

//...

demo_cdecl(1, 2, 3, 4); //calling
```

```asm
; ...
push 4 ; push last parameter value
push 3 ; push third parameter value
push 2 ; ...
push 1
call demo_cdecl ; call the subroutine
add esp, 16 ; clean up the stack
```

Calling Conventions: `stdcall`

- Microsoft's Win32 API standard calling convention (modifier: `_stdcall`
- Parameters: passed using the stack (as in _cdecl)
- Main difference: the callee is responsible for clearing the function parameters from the stack before returning
  - To do this, the function needs to know the right number of parameter passed $\rightarrow$ can be used only with functions having a fixed number of parameters (e.g., no `printf`).

```
void _stdcall demo_stdcall(int a, int b, int c);
demo_stdcall(1, 2, 3);
```

```
ret 12 ; return and clear 12 bytes from the stack
```

Low addresses (0x80000000)

...
array[0]
...
array[4]
Saved EBP
Return address
1
2
...

High addresses (0xbfffffff)

```
void function (int a, int b) {
  int array [5];
}

int main (int argc, char** argv) {
  function(1, 2);
  printf("This is where the ret
       address points");
}
```

Assembler-level View of the Same Example

```
public main
main proc near
push ebp
mov ebp, esp ; create stack
and esp,0FFFFFFF0h
sub esp,10h ; make room for vars
mov dword ptr[esp+4],2 ; push 2
mov dword ptr[esp],1 ; push 1
call function
mov dword ptr [esp], offset format; "This is..."
call _printf
leave
ret
main endp

public function
function proc near
push ebp
mov ebp,esp ; create stack
sub esp,20h ; make room for array
leave
retn 8 ; remove 2 dwords
function endp
```

Low addresses (0x80000000)

...
array[0]
...
array[4]
Saved EBP
Return address
1
2
...

High addresses (0xbfffffff)

- Modifier: _fastcall
- Up to 2 parameters passed via registers: ECX and EDX
- Other parameters pushed to the stack (right to left order, stack cleanup by callee as in stdcall)

```
; demo_fastcall(1, 2, 3, 4);
push 4 ; push 4th parameter
push 3 ; push 3rd parameter
mov edx, 2 ; move 2nd parameter in EDX
mov ecx, 1 ; move 1st parameter in ECX
call demo_fastcall
add esp, 8 ; clean up the stack
```

Calling Conventions: Linux x86-64 (System V ABI)

- Parameters passed **in registers**: rdi, rsi, rdx, rcx, r8, r9, subsequent ones on the stack (reverse order, caller cleanup)
- Callee-saved registers: rbx, rsp, rbp, r12, r13, r14, and r15
- Caller-saved registers (scratch): rax, rdi, rsi, rdx, rcx, r8, r9, r10, r11
- Return value: rax (if 128-bit: rax and rdx)

Linux x86-64 calling convention: Example

```
main:
  push rbp
  mov rbp, rsp
  sub rsp, 16
  mov DWORD PTR [rbp-4], edi
  mov QWORD PTR [rbp-16], rsi
  mov esi, 2 ; Second parameter
  mov edi, 1 ; First parameter
  call function
  mov esi, eax ; Return value -> first param
  mov edi, OFFSET FLAT:.LC0 ; "The return ...
  mov eax, 0
  call printf
  leave
  ret

function:
  push rbp
  mov rbp, rsp
  mov DWORD PTR [rbp-4], edi
  mov DWORD PTR [rbp-8], esi
  mov edx, DWORD PTR [rbp-4]
  mov eax, DWORD PTR [rbp-8]
  add eax, edx
  pop rbp
  ret
```

```
int function (int a, int b) {
    return a + b;
}

int main (int argc, char** argv) {
    return printf("The return value is %d\n",
        function(1,2));
}
```

Low addresses

...
2
1
Saved RBP
Return address
...

High addresses

48

Tooling

objdump

- `man objdump`
  objdump **displays information** about one or more **object files**.
- `-x` all-headers
- `-d` disassemble
- `-M intel` intel syntax (default is att)

- **What is GDB?**
  GDB is GNU Project's Debugger: allows to follow, step by step, at assembler-level granularity, a running program, or what a program was doing right before it crashed.[3]

---

[3]http://www.gnu.org/software/gdb/

Start, break and navigate the execution with gdb

- Suppose you have an executable binary and want run it
  - **gdb /path/to/executable** loads the binary in gdb
- Now you decide to start the program with two parameters
  - **run 1 "abc"** passes 1 via argv[1] and "abc" as argv[2]
  - **run `printf "AAAAAAAAAAAA"`** (with the back ticks) we're passing the output of the print (very useful when you need to pass non printable characters such as raw bytes)
- Suppose you want to stop the execution at the address of a certain instruction
  - **break *0xDEADBEAF** places a break point at that address
  - **break *main+1** with debugging symbols this can be less painful
  - **catch syscall** block the execution when a syscall happens

51

Start, break and navigate the execution with gdb

- Now the execution stops at our break point. Here we can do several things
- Examples:
  - **ni** allows to procede instruction per instruction
  - **next 4** moves 4 lines ahead (if you have the line-numbers information in the binary)
  - **si** step into function
  - **finish** run until the end of current function
  - **continue** runs until the next break point (if any)
- To see info about the execution state:
  - **info registers** to inspect the content of the registers
  - **info frame** to see the values of the stack frame related to the function where we are in
  - **info file** print the information about the sections of the binary

Navigate the stack

- Suppose we're stopped somewhere in the code and want to inspect the stack
- Some useful view of the stack is achievable with:
  - **x/100wx $esp** prints 100 words of memory from the address found in the ESP to ESP+100 (x = hexadecimal formatting)
  - **x/10wo $ebp-100** prints 10 words of memory from EBP-100 to EBP-100+10 (o = octal formatting)
  - **x/s $eax** prints the elements pointed by EAX (s = string formatting)
- Do you have debug symbols? (i.e., gcc -ggdb)
  - **print args** prints info about the main parameters
  - **print a** prints the content of variable 'a'
  - **print *b** prints the value pointed by 'b'

Our friend gdb

- **The '~/.gdbinit' file**
  Gdb is a command line tool and it supports the configuration script as almost all the *nix software.
  Some options that you may want to tune are:
  - **set history save on**
    To have the lastest commands always available also when we re-open gdb
  - **set follow-fork-mode child**
    Allows you, if the process spawns children, to follow them and not only wait their end.
  - **set disassembly-flavor [intel | att]**
    This option sets in which predefined syntax your disassembled will be showed up. The default one is at&t
- Highly recommended to install pwndbg
  https://github.com/pwndbg/pwndbg

Layout in gdb

- Text-based interface for GDB
    - **layout asm** turn the interface to the assembly view always visible during debugging
    - **layout src** if your binary has the dubugging symbols you will have your c source view visible
    - **layout reg** add to the interface the register status view. It could be used in combination with one of the view described above
    - **gdb -tui ./mybin** runs gdb directly in this Text User Interface
- Use **CTRL+X A** to go back to standard interface.

strace

- Intercepts and records system calls and signals
- Dumps to standard error name, argument and return value of each system call

Useful options

- `-p <pid>` attach to existing process
- `-f` trace child process
- `-o <filename>` output to file
- `-e <expr>` modifies which events to trace (see manpage)

- Intercepts and records dynamic library calls
- Similar to strace, but at a different layer

Thank you!

(time for more questions)