Automatic Dependent Surveillance - Broadcast

Alberto Rolando

Department of Aerospace Science and Technology
Politecnico di Milano

Version 1.3.y

Introduction

The system developed for Mode S transponder has enabled a new form of communication directly between aircraft, which is not based on interrogation and response but on **unsolicited broadcasts** from aircraft known as **squitters**.

Since any aircraft flying under Instrumental Flight Rules (IFR) will have a sophisticated navigation system, it can report its position more precisely than can be obtained by primary radar and it does this by broadcasting frequent squitters.

Squitters come in various forms: the simplest is a preamble followed by a 56-bit data block coded using Pulse Position Modulation (PPM), which is an identical format to the Mode S reply.

This type of broadcast, known as a **Mode S acquisition squitter**, is sent once per second and contains just the aircraft 24-bit address plus control and parity bits giving a simple *"I am here"* message.

Extended Squitter

The capability of the system has been enhanced by extending squitters to contain 112 bits in the data block and the extra 56 bits is used to send additional positional and flight information.

The **Extended Squitter (ES)** illustrate a new method to provide traffic information referred to as the **Automatic Dependent Surveillance - Broadcast (ADS-B)**.

- **Automatic**: information is sent without any operator intervention.
- **Dependent**: information is derived from other onboard systems such as Global Navigation Satellite System (GNSS).
- **Surveillance**: it provides radar-type information though with higher precision.
- **Broadcast**: information is continuously sent and can be received by any suitably equipped aircraft or ground station.

Basic and Extended Squitter format



ADS-B message payloads and transmission rates

There are four types of ES wich contain different information and have different broadcast rate.

The code is highly compacted to pack as much information as possible into 56 bits and requires further processing to extract usable data.

Information in ADS-B message

Airborne position squitter

No. bits	Information
5	Format type code
2	Surveillance status
1	Single antenna flag
12	Altitude
1	Timeflag (UTC)
1	CPR format flag
17	CPR encoded latitude
17	CPR encoded latitude
56	Total

Broadcast rate = 2/second
Accuracy ~ 5 m

Surface position squitter

No. bits	Information
5	Format type code
7	Movement
1	Status
7	Ground track
1	Time flag (UTC)
1	CPR format flag
17	CPR encoded latitude
17	CPR encoded latitude
56	Total

Broadcast rate = 1/second
Accuracy ~ 1.2 m

Airborne velocity squitter

No. bits	Information
5	Format type code
3	Subtype
1	Intent change flag
1	IFR capability flag
3	Velocity uncertainty
10+1	East-West velocity + sign
10+1	North-South velocity + sign
9+1+1	Vertical rate + sign + source
2	Turn indicator
7+1	Height diff. from barometric + sign
56	Total

Broadcast rate = 2/second
Accuracy ~ 1.2 m

Aircraft identification squitter

No. bits	Information
5	Format type code
3	Aircraft category
6	Callsign character 1
6	Callsign character 2
6	Callsign character 3
6	Callsign character 4
6	Callsign character 5
6	Callsign character 6
6	Callsign character 7
6	Callsign character 8
56	Total

Broadcast rate = 0.2/second

ADS-B and Primary Radar

The ADS-B system enables comprehensive data about any flight to be obtained by a simple ADS-B receiver and it is expected that it will eventually replace primary radar as the main surveillance method for commercial air traffic.

The main advantage is its much higher precision of position reporting, which is down to around 5 m for airborne aircraft.

Additionally, position reporting precision is independent from aircraft position, whereas for primary radar it decreases with the distance from the radar antenna.

Note

Primary radar will continue to play an important role due to its ability to monitor all traffic regardless its capabilities and/or its will to co-operate, in particular for **security-related** surveillance activities.

ADS-B and Universal Access Transceiver

Having established the power of ADS-B as a method for the surveillance and control of air traffic the development of a new datalink system that is independent of mode S began in 1995, that is, the **Universal Access Transceiver (UAT)**.

International Civil Aviation Organization (ICAO) set up the Standards and Recommended Practices for the new system in 2007 and it has been assigned the frequency 978 MHz and digital data modulation rate of 1 Mbits s^{-1}

UAT is intended to support:

- ADS-B.
- Flight Information Service - Broadcast (FIS-B).
- Traffic Information Service - Broadcast (TIS-B).

ADS-B data over UAT

The information within the basic 128-bit message reports the ICAO 24-bit address of the aircraft along with its position, altitude, airspeed, and vertical speed.

Also included is the Navigational Uncertainty Category (NUC) for the position and speed, which is a measure of the estimated error.

The entire 128-bit message is known as the state vector component and is part of every ADS-B message.



TIS-B data over UAT

Traffic Information Service - Broadcast supplements ADS-B's air-to-air services to provide complete situational awareness in the cockpit of all traffic known to the Air Traffic Control (ATC) system.

TIS-B is an important service for an ADS-B link in airspace where not all aircraft are transmitting ADS-B information. The ground TIS-B station transmits surveillance target information on the ADS-B data link for unequipped targets or targets transmitting only on another ADS-B link.

TIS-B uplinks are derived from the best available ground surveillance sources:

- Ground radars for primary and secondary targets.
- Multilateration systems for targets on the airport surface.
- ADS-B systems for targets equipped with a different ADS-B link.

FIS-B data over UAT

Flight Information Service - Broadcast provides

- Weather text.
- Weather graphics.
- Notice To Airmens (NOTAMs).
- Automatic Terminal Information Service (ATIS).

FIS-B is inherently different from ADS-B in that it requires sources of data external to the aircraft or broadcasting unit, and has different performance requirements such as periodicity of broadcast.

FIS-B services are generally provided over the UAT link in areas that have a ground surveillance infrastructure.

ADS-B over Mode S ES vs. over UAT

There is some overlap between the ADS-B information from Mode S ES and UATs.

However, the latter also provides additional information such as FIS-B.

Another important fundamental difference is that a UAT-based system is essentially **bidirectional** and ground stations collate aircraft information and rebroadcast it to provide TIS-B.

In addition to the 128-bit state vector message, which is part of every ADS-B message, a longer version containing 256 bits in the data block is available over UAT to broadcast additional information including the aircraft call sign and the next trajectory change point.

Note

The full capability to send and receive messages is known as **ADS-B in** and **ADS-B out**.

ADS-R

Automatic Dependent Surveillance - Rebroadcast (ADS-R) is a service that rebroadcasts positions of aircraft that have a UAT *ADS-B out* equipment on 1090 MHz and vice versa, that is to say:

- It takes position information received on the ground from UAT equipped aircraft and rebroadcasts it on 1090 MHz.
- It rebroadcasts 1090 MHz data to UAT users.

This is done using Federal Aviation Administration (FAA) ground stations and the purpose is that aircraft with *ADS-B in* on only 1090 MHz should be able to also see UAT aircraft (and vice versa).

Note

In concert with TIS-B, ADS-R provides all ADS-B in equipped aircraft with comprehensive airspace and airport surface traffic picture.

Scenario


ADS-B in and
ADS-B out
ADS-B in and
ADS-B out
ADS-B air to air
ADS-B air to air
TIS-B FIS-B
ADS-B air to ground
ADS-B air to air
ADS-B air to ground
TIS-B FIS-B
No ADS-B
ADS-B out only
ADS-B air
to ground
Primary
surveillance
radar
Track
merger
Air traffic
control
ADS-B ground
transceiver
(978 and 1090 MHz)
with ADS-R
Weather
station

TIS-B Human Machine Interface (HMI)



FIS-B HMI


GARMIN
HOME
COM
127.65
HOUSTON ACC
STBY
133.15
APPROACH+
Com Vol
Psh Sq
Audio Panel
Intercom
MIC
1
MON
1
XPDR
IDENT
1200
ALT R
NAV GPT
109.00
GPT VOR
STBY
115.30
SJI VOR
NORTH UP
NXRD
SiriusXM
NEXRAD:US
Age: 5min
METAR:US
Age: 5min
METAR:CN
Age: 5min
TFR
Age: 5min
AIRMET
06/03 20:42z
SIGMET
06/03 20:42z
Lightning
Age: 5min
County
06/03 20:42z
PIREPS
Age: 5min
AIREPS
Age: 5min
FRZ LVL
KNEW
022° 68.3 NM
40 NM
Back
Menu
In
Out
ENR
GPS
Com Freq / Psh Nav

List of Acronyms

ADS-B	Automatic Dependent Surveillance - Broadcast
ADS-R	Automatic Dependent Surveillance - Rebroadcast
ATC	Air Traffic Control
ATIS	Automatic Terminal Information Service
ES	Extended Squitter
FAA	Federal Aviation Administration
FIS-B	Flight Information Service - Broadcast
GNSS	Global Navigation Satellite System
HMI	Human Machine Interface
ICAO	International Civil Aviation Organization
IFR	Instrumental Flight Rules
NOTAM	Notice To Airmen
NUC	Navigational Uncertainty Category
PPM	Pulse Position Modulation
TIS-B	Traffic Information Service - Broadcast
UAT	Universal Access Transceiver