

Exercise 10.1

Let $|\psi\rangle = a|0\rangle + b|1\rangle$ and the initial state be $|\psi_0\rangle = a|000\rangle + b|100\rangle$.

Applying a CNOT to the first two qubits we get,

$$|\psi_1\rangle = a|000\rangle + b|110\rangle$$

Applying a CNOT to the first and last qubits we get,

$$|\psi_2\rangle = a|000\rangle + b|111\rangle$$

Exercise 10.2

$$P_{\pm} = \frac{1}{2}(|0\rangle \pm |1\rangle)(\langle 0| \pm \langle 1|) = \frac{1}{2}(|0\rangle\langle 0| + |1\rangle\langle 1| \pm |1\rangle\langle 0| \pm |0\rangle\langle 1|) = \frac{1}{2}(I \pm X)$$

Therefore,

$$\mathcal{E}(\rho) = (1-2p)\rho + 2pP_+\rho P_+ + 2pP_-\rho P_- = (1-2p)\rho + \frac{1}{2}p(I+X)\rho(I+X) + \frac{1}{2}p(I-X)\rho(I-X) = (1-2p)\rho + p\rho + pX\rho X = (1-p)\rho + pX\rho X$$

Exercise 10.3

$$\begin{aligned} Z_2 Z_3 Z_1 Z_2 &= [I \otimes (|00\rangle\langle 00| + |11\rangle\langle 11|) - I \otimes (|01\rangle\langle 01| + |10\rangle\langle 10|)][(|00\rangle\langle 00| + |11\rangle\langle 11|) \otimes \\ &I - (|01\rangle\langle 01| + |10\rangle\langle 10|) \otimes I] = \underbrace{|000\rangle\langle 000| + |111\rangle\langle 111|}_{P_0} - \underbrace{(|100\rangle\langle 100| + |011\rangle\langle 011|)}_{P_1} \\ &+ \underbrace{|010\rangle\langle 010| + |101\rangle\langle 101|}_{P_2} - \underbrace{(|001\rangle\langle 001| + |110\rangle\langle 110|)}_{P_3} \end{aligned}$$

Exercise 10.4

$|000\rangle\langle 000|, |111\rangle\langle 111|$: no bit flip

$|100\rangle\langle 100|, |011\rangle\langle 011|$: first bit flipped

$|010\rangle\langle 010|, |101\rangle\langle 101|$: second bit flipped

$|001\rangle\langle 001|, |110\rangle\langle 110|$: third bit flipped

2) If our state is $|\psi\rangle = a|000\rangle + b|111\rangle$, then the measurement will collapse the state into $|000\rangle$ or $|111\rangle$ with probabilities $|a|^2$ or $|b|^2$, respectively. Hence, only the computational basis states $|000\rangle$ and $|111\rangle$ can be corrected.

3) Assuming the initial state is $|000\rangle$ the probability that one or fewer bit flips occur is $(1-p)^3 + p(1-p)^2$, hence $F \geq \sqrt{(1-p)^3 + p(1-p)^2}$.

Exercise 10.5

Assuming no more than one error has occurred, $X_1 X_2 X_3 X_4 X_5 X_6$ will be 1 if no phase flip occurred and -1 if one occurred on the first or second block. Identically for $X_4 X_5 X_6 X_7 X_8 X_9$. Hence, if both give -1 the error is on the second block, otherwise it's on the first block if $X_1 X_2 X_3 X_4 X_5 X_6$ gives -1 and on the third block if $X_4 X_5 X_6 X_7 X_8 X_9$ gives -1 . If both give 1 then no error has occurred.

Exercise 10.6

The eigenvalues of Z are ± 1 , hence

$$Z_1 Z_2 Z_3 (|000\rangle - |111\rangle) = |000\rangle - (-1)^3 |111\rangle = |000\rangle + |111\rangle$$

Exercise 10.7

Need to prove that $PE_i^\dagger E_j P = \alpha_{ij} P$. I and X are Hermitian, hence suffices to show for IX_1, II, X_1X_1 and X_1X_2 .

$$\begin{aligned} P\sqrt{(1-p)^3}I\sqrt{p(1-p)^2}X_1P &= (1-p)^2\sqrt{p(1-p)}(|000\rangle\langle 000| + |111\rangle\langle 111|)X_1(|000\rangle\langle 000| + |111\rangle\langle 111|) = (1-p)^2\sqrt{p(1-p)}(|000\rangle\langle 000| + |111\rangle\langle 111|)(|100\rangle\langle 000| + |011\rangle\langle 111|) = 0 \\ P\sqrt{(1-p)^3}I\sqrt{(1-p)^3}IP &= (1-p)^3PP = (1-p)^3P \\ P\sqrt{p(1-p)^2}X_1\sqrt{p(1-p)^2}X_1P &= p(1-p)^2PIP = p(1-p)^2P \\ P\sqrt{p(1-p)^2}X_1\sqrt{p(1-p)^2}X_2 &= p(1-p)^2(|000\rangle\langle 000| + |111\rangle\langle 111|)(|110\rangle\langle 000| + |001\rangle\langle 111|) = 0 \end{aligned}$$

Hence, the quantum error-correction conditions are satisfied.

Exercise 10.8

$P = |+++\rangle\langle +++| + |--\rangle\langle --|$, hence like in the previous exercise.

$$PE_i^\dagger E_j P = 0, i \neq j$$

$$PE_i^\dagger E_j P = P, i = j$$

Hence, the quantum error-correction conditions are satisfied.

Exercise 10.9

$$PIIP = P$$

$$\begin{aligned} PIP_1P &= (|+++\rangle\langle +++| + |--\rangle\langle --|)(|0\rangle\langle 0| \otimes I \otimes I)(|+++\rangle\langle +++| + |--\rangle\langle --|) = \\ &= (|+++\rangle\langle +++| + |--\rangle\langle --|)\frac{1}{\sqrt{2}}(|0++\rangle\langle +++| + |0--\rangle\langle --|) = \frac{1}{2}(|+++\rangle\langle +++| + |--\rangle\langle --|) = \frac{1}{2}P \end{aligned}$$

Identically,

$$PIQ_1P = \frac{1}{2}P$$

$$PP_1Q_1 = 0$$

$$PP_1P_1P = PP_1P = \frac{1}{2}P$$

$$PQ_1Q_1P = PQ_1P = \frac{1}{2}P$$

$$\begin{aligned} PP_1P_2P &= (|+++\rangle\langle +++| + |--\rangle\langle --|)(|0\rangle\langle 0| \otimes |0\rangle\langle 0| \otimes I)(|+++\rangle\langle +++| + |--\rangle\langle --|) = \\ &= (|+++\rangle\langle +++| + |--\rangle\langle --|)\frac{1}{2}(|00+\rangle\langle +++| + |00-\rangle\langle --|) = \frac{1}{4}(|+++\rangle\langle +++| + |--\rangle\langle --|) = \frac{1}{4}P \end{aligned}$$

$$\begin{aligned} PP_1Q_2P &= (|+++\rangle\langle +++| + |--\rangle\langle --|)(|0\rangle\langle 0| \otimes |1\rangle\langle 1| \otimes I)(|+++\rangle\langle +++| + |--\rangle\langle --|) = \\ &= (|+++\rangle\langle +++| + |--\rangle\langle --|)\frac{1}{2}(|01+\rangle\langle +++| + |01-\rangle\langle --|) = \frac{1}{4}(|+++\rangle\langle +++| + |--\rangle\langle --|) = \frac{1}{4}P \end{aligned}$$

Hence, the quantum error-correction conditions are satisfied.

Exercise 10.10

$$P = |0_L\rangle\langle 0_L| + |1_L\rangle\langle 1_L|$$

Due to phase and bit flips,

$$PIX_iP = PIY_iP = PIZ_iP = 0$$

$$PIIP = PX_iX_iP = PY_iY_iP = PZ_iZ_iP = P$$

The X_i and Y_i change the individual qubits, hence if $i \neq j$ $PX_iY_jP = 0$, e.g. for PX_1Y_2P looking at the first triplet, we have

$$(|000\rangle + |111\rangle)(|110\rangle - |001\rangle) = 0$$

$$X_iY_i = iZ_i, \text{ hence } PX_iY_iP = 0$$

For Z_iZ_j if i and j belong to different triplets then we have a phase flip on 2 separate triplets,

hence $PZ_iZ_jP = 0$.

However, if i and j are in the same triplet, then we apply 2 phase shifts to the triplet which is equivalent to no change, hence $PZ_iZ_jP = P$.

For X_iZ_j and Y_iZ_j we perform a bit and phase flip, hence for all i and j $PX_iZ_jP = PY_iZ_jP = 0$.

Exercise 10.11

$$\mathcal{E}(\rho) = \frac{I}{2}$$

Consider the operation elements found for the general depolarizing channel in Exercise 8.19 $\{\sqrt{\frac{p}{d}}|i\rangle\langle j|\}$. Taking $p = 1$ and $d = 2$, we get $\{\frac{1}{2}|0\rangle\langle 0|, \frac{1}{2}|1\rangle\langle 1|, \frac{1}{2}|0\rangle\langle 1|, \frac{1}{2}|1\rangle\langle 0|\}$.

Exercise 10.12

$$F(|0\rangle, \mathcal{E}(|0\rangle\langle 0|)) = \sqrt{\langle 0| \mathcal{E}(|0\rangle\langle 0|) |0\rangle}$$

$$= \sqrt{\langle 0| ((1-p)|0\rangle\langle 0| + \frac{p}{3}(X|0\rangle\langle 0|X + Y|0\rangle\langle 0|Y + Z|0\rangle\langle 0|Z)) |0\rangle} = \sqrt{1-p+\frac{p}{3}} = \sqrt{1-\frac{2p}{3}}$$

As the depolarizing channel is symmetric, for any pure state $|\psi\rangle$,

$$F(|\psi\rangle, \mathcal{E}(|\psi\rangle\langle\psi|)) = \sqrt{1-\frac{2p}{3}}.$$

As fidelity is jointly concave, for any ρ and some $|\psi\rangle$ we have,

$$F(\rho, \mathcal{E}(\rho)) \geq F(|\psi\rangle, \mathcal{E}(|\psi\rangle\langle\psi|)) = \sqrt{1-\frac{2p}{3}}$$

Exercise 10.13

Let $|\psi\rangle = a|0\rangle + b|1\rangle$

$$F(|\psi\rangle, \mathcal{E}(|\psi\rangle\langle\psi|)) = \sqrt{\langle\psi| \mathcal{E}(|\psi\rangle\langle\psi|) |\psi\rangle}$$

$$\sqrt{|\langle\psi|E_0|\psi\rangle|^2 + |\langle\psi|E_1|\psi\rangle|^2} = \sqrt{|a|^2 + |b|^2\sqrt{1-\gamma}|^2 + |a|b|^2\sqrt{\gamma}|^2}$$

Minimum will occur when $a = 0$ and $b = 1$, hence

$$F_{min}(|\psi\rangle, \mathcal{E}(|\psi\rangle\langle\psi|)) = F(|1\rangle, \mathcal{E}(|1\rangle\langle 1|)) = \sqrt{1-\gamma}$$

Exercise 10.14

$$G = rk \underbrace{\left\{ \begin{bmatrix} 1 & 0 & \dots & 0 \\ \vdots & \vdots & \vdots & \vdots \\ 1 & 0 & \dots & 0 \\ 0 & 1 & \dots & 0 \\ \vdots & \vdots & \vdots & \vdots \\ 0 & 1 & \dots & 0 \\ \vdots & \vdots & \vdots & \vdots \\ 0 & 0 & \dots & 1 \\ \vdots & \vdots & \vdots & \vdots \\ 0 & 0 & \dots & 1 \end{bmatrix} \right\}}_k$$

Exercise 10.15

Let c_1 and c_2 be columns of G . Then

$$G = [c_1 | c_2 | G']$$

$$G'' = [c_1 | c_1 + c_2 | G']$$

Let $x = (x_1, x_2, \dots, x_n)$.

$$Gx = c_1x_1 + c_2x_2 + \dots$$

$$G''x = c_1x_1 + (c_1 + c_2)x_2 + \dots$$

$$G''x - Gx = c_1x_2 \in C$$

Therefore, as C is linear with G as generator, G'' is a generator for C as well, as the difference of the two codes is still in C .

Exercise 10.16

Let r_1 and r_2 be rows of H . Then

$$H = \begin{bmatrix} r_1 \\ r_2 \\ H' \end{bmatrix}$$

$$H'' = \begin{bmatrix} r_1 \\ r_1 + r_2 \\ H' \end{bmatrix}$$

Let $x = (x_1, x_2, \dots, x_n)$.

$$Hx = \begin{bmatrix} r_1x \\ r_2x \\ \vdots \end{bmatrix} = 0$$

Therefore, $r_1x = r_2x = 0$. Hence,

$$H''x = \begin{bmatrix} r_1x \\ r_1x + r_2x \\ \vdots \end{bmatrix} = 0$$

Hence, H'' is a parity check matrix for the same code.

Exercise 10.17

$y_1 = (1, 1, 1, 0, 0, 0)$, $y_2 = (0, 0, 0, 1, 1, 1)$, hence we can take y_3 to y_6 as,

$$y_3 = (1, 1, 0, 0, 0, 0)$$

$$y_4 = (1, 0, 1, 0, 0, 0)$$

$$y_5 = (0, 0, 0, 0, 1, 1)$$

$$y_6 = (0, 0, 0, 1, 0, 1)$$

Therefore,

$$H = \begin{bmatrix} 1 & 1 & 0 & 0 & 0 & 0 \\ 1 & 0 & 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & 1 \\ 0 & 0 & 0 & 1 & 0 & 1 \end{bmatrix}$$

Exercise 10.18

Let x be an arbitrary message to be encoded. Then,

$$y = Gx \in C$$

Hence, $HGx = Hy = 0$ for $\forall x$

Hence, $HG = 0$

Exercise 10.19

Using that $HG = 0$ we have,

$$HG = \begin{bmatrix} a_{11} & a_{12} & \dots & a_{1k} & 1 & \dots & 0 \\ \vdots & \vdots & \vdots & \vdots & & \ddots & \\ a_{(n-k)1} & a_{(n-k)2} & \dots & a_{(n-k)k} & 0 & \dots & 1 \end{bmatrix} \begin{bmatrix} b_{11} & b_{12} & \dots & b_{1k} \\ \vdots & \vdots & \vdots & \vdots \\ b_{n1} & b_{n2} & \dots & b_{nk} \end{bmatrix} = 0$$

Hence,

$$\sum_{i \leq k} a_{1i} b_{i1} + b_{(k+1)1} = 0 \dots \sum_{i \leq k} a_{(n-k)i} b_{i1} + b_{n1} = 0$$

\vdots

$$\sum_{i \leq k} a_{1i} b_{ik} + b_{(k+1)k} = 0 \dots \sum_{i \leq k} a_{(n-k)i} b_{ik} + b_{nk} = 0$$

We see that for example, taking for $2 \leq i \leq k$ $b_{i1} = 0$, $b_{11} = 1$ and $b_{(k+1)1} = -a_{11}$ gives a solution.

Therefore for $i, j \leq k$ $b_{ij} = \delta_{ij}$ and for $i, j > k$ $b_{ij} = -a_{(i-k)j}$, i.e.

$$G = \begin{bmatrix} I_k \\ -A \end{bmatrix}$$

Exercise 10.20

Let x be a codeword such that $\text{wt}(x) \leq d - 1$. Let $H = c_1 | c_2 \dots c_n$ for code C . Consider Hx ,

$Hx = \sum_i c_i x_i$ for $d - 1$ columns. Therefore, as any $d - 1$ columns are linearly independent,

this sum cannot equal 0. Hence, $d(C) \geq d$. However, as any d columns are linearly dependant there exists a codeword y with $\text{wt}(y) = d$ such that $Hy = 0$. Therefore, $d(C) = d$.

Exercise 10.21

The parity check matrix is a $n - k$ by n matrix, hence the maximum number of linearly independent columns is $n - k$. Therefore, from Exercise 10.20 $n - k \geq d - 1$.

Exercise 10.22

The Hamming parity check matrix is constructed from columns which are all the possible $n - k$ bit strings, of which there are $2^r - 1$ of excluding the 0 string. Hence, any two columns will be linearly independent as all are different, however there always will be 3 linearly dependant columns, e.g. $(1, 0, 0, \dots)$, $(0, 1, 0, \dots)$ and $(1, 1, 0, \dots)$. Therefore, as per exercise 10.20 the code will have distance 3.

Exercise 10.23

Exercise 10.24

Exercise 10.25

Exercise 10.26