

XReview: **addalign** and **remalign**

If removing or adding a whole **align** environment is desired, *xreview* offers a the **addalign** and **remalign** environments (as well as **addalign*** and **remalign***).

L^AT_EX Code	\showchanges	\showclean
New equations:	New equations:	New equations:
\begin{addalign}		
& a+b = d\\	$a + b = d$ (1)	$a + b = d$ (1)
& b+c=3d	$b + c = 3d$ (2)	$b + c = 3d$ (2)
\end{addalign}		
Removed equations:	Removed equations:	Removed equations:
\begin{remalign}		
& a+b = d\\	$a + b = d$ (R1)	
& b+c=3d	$b + c = 3d$ (R2)	
\end{remalign}		

While **addalign** and **addalign*** works almost indistinguishably from marking each line as a **\addedeqline**, this is quite clearly not the same for **remalign**. The reason is simple: *amsmath* does *not* provide an easy way to **\sout** through alignment tabs and newlines. Therefore, we pull a simple trick to “*sout*” diagonally across. Not *as* pretty, but it is a drop-in replacement for a to-be-removed **align**! If an author cares very much about every single line being *beautifully* stricken-through, they unfortunately must use **\removedeqline** and friends explicitly. Because of these limitations, **remalign** and **remalign*** try to be as customizable as possible. Please refer to the full documentation in *xreview.pdf* for more details.