

Ref:

<https://www.atlassian.com/git/tutorials/saving-changes/gitignore>

<https://git-scm.com/docs/gitignore>

Git ignore patterns

.gitignore uses [globbing patterns](#) to match against file names. You can construct your patterns using various symbols:

Pattern	Example matches	Explanation*
<code>**/logs</code>	logs/debug.log logs/monday/ foo.bar build/logs/ debug.log	You can prepend a pattern with a double asterisk to match directories anywhere in the repository.
<code>**/logs/ debug.log</code>	logs/debug.log build/logs/ debug.log <i>but not</i> logs/build/ debug.log	You can also use a double asterisk to match files based on their name and the name of their parent directory.
<code>*.log</code>	debug.log foo.log .log logs/debug.log	An asterisk is a wildcard that matches zero or more characters.
<code>*.log !important.log</code>	debug.log <i>but not</i> logs/debug.log	Prepending an exclamation mark to a pattern negates it. If a file matches a pattern, but <i>also</i> matches a negating pattern defined later in the file, it will not be ignored.
<code>/debug.log</code>	debug.log <i>but not</i> logs/debug.log	Patterns defined after a negating pattern will re-ignore any previously negated files.

<code>debug.log</code>	<code>debug.log</code> <code>logs/debug.log</code>	Prepending a slash matches files only in the repository root.
<code>debug?.log</code>	<code>debug0.log</code> <code>debugg.log</code> <i>but not</i> <code>debug10.log</code>	A question mark matches exactly one character.
<code>debug[0-9].log</code>	<code>debug0.log</code> <code>debug1.log</code> <i>but not</i> <code>debug10.log</code>	Square brackets can also be used to match a single character from a specified range.
<code>debug[01].log</code>	<code>debug0.log</code> <code>debug1.log</code> <i>but not</i> <code>debug2.log</code> <code>debug01.log</code>	Square brackets match a single character from the specified set.
<code>debug[!01].log</code>	<code>debug2.log</code> <i>but not</i> <code>debug0.log</code> <code>debug1.log</code> <code>debug01.log</code>	An exclamation mark can be used to match any character except one from the specified set.
<code>debug[a-z].log</code>	<code>debuga.log</code> <code>debugb.log</code> <i>but not</i> <code>debug1.log</code>	Ranges can be numeric or alphabetic.

logs	logs logs/debug.log logs/latest/ foo.bar build/logs build/logs/ debug.log	If you don't append a slash, the pattern will match both files and the contents of directories with that name. In the example matches on the left, both directories and files named <i>logs</i> are ignored
logs/	logs/debug.log logs/latest/ foo.bar build/logs/ foo.bar build/logs/ latest/ debug.log	Appending a slash indicates the pattern is a directory. The entire contents of any directory in the repository matching that name – including all of its files and subdirectories – will be ignored
logs/ !logs/ important.log	logs/debug.log logs/ important.log	Wait a minute! Shouldn't logs/important.log be negated in the example on the left Nope! Due to a performance-related quirk in Git, you can not negate a file that is ignored due to a pattern matching a directory
logs/**/ debug.log	logs/debug.log logs/monday/ debug.log logs/monday/ pm/debug.log	A double asterisk matches zero or more directories.
logs/*day/ debug.log	logs/monday/ debug.log logs/tuesday/ debug.log <i>but not</i> logs/latest/ debug.log	Wildcards can be used in directory names as well.

<code>logs/</code> <code>debug.log</code>	<code>logs/debug.log</code> <i>but not</i> <code>debug.log</code> <code>build/logs/</code> <code>debug.log</code>	Patterns specifying a file in a particular directory are relative to the repository root. (You can prepend a slash if you like, but it doesn't do anything special.)
--	---	--