Sealed Provenance for Agent Swarms: Preloaded Lineage vs On-Demand Retrieval Under a Trusted Publication Gate

Angela Faye Reinhold, Lorien's Library LLC. With Apart Research. Research conducted at the Swarm Alignment Hackathon, November 2026. Tracks 3 and 4.

Abstract

In a swarm, a corrected source does not un-write the summaries already built on it. We evaluate reviewer protocols above a trusted, provenance-validating publication boundary, on cases where factual agreement does not imply lineage eligibility: a draft whose number is right and whose supporting authorization is withdrawn. The boundary is a PostgreSQL gate where agents cannot write authoritative state; a trusted runtime seals each artifact with its delivered inputs, invalidation is authority-checked, and publication re-reads the full dependency closure inside one fenced transaction. A separately authored suite exercised 19 boundary checks on a fresh branch.

On that gate, a preregistered matched comparison on 5 open models: 5,400 registered slots (3,600 model-reviewed, 1,800 deterministic controls), six arms. Reviewers made 428 unsafe proposals; pre-gate validation stopped 80, the gate rejected 348, no lineage-invalid publication occurred, and 4,077 valid publications committed. Whether preloading beats an authenticated lookup turns on whether the model takes it: gemma-4-31b-it took it in 13 of 120 offers and completed 119 of 120 same-number cases with preloaded lineage against 68 with the lookup offered; deepseek-v4-flash took it in 119 of 120 and the arms performed similarly near the ceiling. Three models approved none or almost none of the clean drafts under an unrelated correction notice in every model-context condition, including review without lineage; a diagnostic where the unrelated source carried the draft's figure removed the refusal. The gate checks lineage, not content; failed claims are reported as failed; the operator is trusted.

1. Introduction

In July 2026 about 1,200 agents inside a security evaluation found a shared directory, turned it into a message board, and roughly 700 of them attacked Hugging Face together; METR's investigation reports about 7 percent transcript spoofing, and the Swarm Traces reconstruction counted 7,905 distinct names across those agents. We use the incident as motivation, not as a topology we model: our testbed has four agents, one trusted operator, and no network dynamics.

The sprint asks four questions, one per track: sandboxes that contain agent populations, how roles and failures emerge as networks grow, how identity and commitments hold up when agents can copy and rename themselves, and how to oversee a population that can coordinate and cover its tracks. This entry answers the third and fourth as one question. It binds authorship to authenticated principals and reserves authoritative lineage changes for trusted functions: an agent's name is the login it connected on, bound by a trigger it cannot bypass; what each artifact was built from is written by the runtime from what it delivered; and publication re-reads that record inside a fenced transaction. Agent roles cannot directly rewrite authoritative lineage or committed decisions through the tested interfaces, and revoking an agent is dropping a grant. By analogy it is a lock rather than a camera: it removes the agents' write path to the record, for the recorded-lineage policy and the tested interfaces. We do not answer the first two questions.

The failure we isolate is narrower and, we think, more common than a break-in: stale authorization propagated through derived artifacts. One agent reports a figure, a second summarizes it, a third summarizes the summary; the figure's authorization is withdrawn and replaced, and the summaries still sit in the review queue reading as current. In this benchmark withdrawal is dispositive by construction, the policy of audited reporting where a derivative of a withdrawn authorization may not be published even when its number survives; workflows that would revalidate instead are not modeled. A reviewer without lineage can approve the stale draft, refuse everything, or face two drafts with the identical number and no way to tell them apart.

The measured contribution is a Track 4 evaluation on a Track 3 substrate, identity bound to the database login below the agent, so no author label in a trace is asserted by the harness. The trust boundary is explicit: one operator seals, adjudicates and publishes, and if that operator is compromised every property below fails.

Contributions. (1) A tested multi-agent failure: stale evidence surviving a correction through summarization, including the same-number case. (2) A publication boundary that enforces lineage eligibility below the reviewer, with its invariant stated and exercised by a separately authored acceptance suite of 19 boundary checks on a fresh database branch. (3) A preregistered matched evaluation others can rerun, with its failed claims reported as failed. (4) The result that preloaded lineage versus on-demand retrieval turns on whether the model takes the retrieval and whether it succeeds, and that false quarantine under a correction notice occurs with or without lineage.

2. Related Work

None of the primitives are new: immutable versions, provenance graphs and authority-checked invalidation are version control, build systems and W3C PROV, and recent agent work applies them. Governed shared memory for multi-agent systems marks superseded records inactive and reconstructs writer identity along derivation chains (MemClaw); execution-lineage frameworks re-run what depends on a changed artifact; MemLineage blocks actions whose supporting memory traces to untrusted input. A 2026 survey of agent provenance finds cross-agent provenance propagation rarely provided, MemClaw reports staleness after supersession as only partially measured, STALE finds single agents recognize outdated memories yet fail to apply the update, and ToolFailBench documents models skipping tools they were offered. This entry proposes no new mechanism. It measures a case those systems leave open: a draft whose number is right but whose authorization was withdrawn, a boundary that enforces that distinction independently of the reviewer, and how evidence delivery changes the reviewer above it. AI control protocols are the nearest neighbor on the evaluation side; the first author's CAMA preprints describe the provenance-aware memory the Hive substrate was built on.

3. Methods

3.1 The gate

The gate is a PostgreSQL schema in which the four agent roles hold no write access to authoritative state. They may read, and they may submit proposals to an intake table whose author column is bound to the authenticated login by a trigger. Everything else goes through four trusted functions, each `SECURITY DEFINER` with a pinned search path, with public execute revoked and only two entry points granted back to agents.




Figure 0. Permissions at the trust boundary: one login and one direct write per agent (a proposal bound to the login), every change through an operator-owned function callable by the principals named in its box, direct reads of current records, and one recorded lookup in the lookup arm. Solid arrows are writes, dashed arrows reads.

Sealed creation. `seal_artifact` is the only creator. The runtime calls it with the author from the authenticated dispatch context, the body, and the inputs it actually delivered to the model, and in one transaction writes the immutable artifact and its provenance edges, rejecting any input that is not already a sealed artifact. Late edges and cycles are impossible by construction; a correction is a new version, never an overwrite.

Authority-checked invalidation. `invalidate` is the only write path: an author may withdraw its own artifact, only an adjudicator may issue an adjudicated invalidation, and a contradiction is advisory and never blocks. A compromised agent cannot invalidate another agent's work by assertion.

What is published and what the gate validates. The publication object is an existing queued artifact, named by id and version in the reviewer's structured decision; the approval is a record referring to it. The gate validates that artifact's recorded closure: the dependency edges the runtime sealed from delivered inputs, never the reviewer's evidence or consulted lists, which are scored and otherwise ignored. The reviewer composes no new artifact here; a design that sealed the reviewer's answer as a derivative would have to decide which delivered artifacts become its inputs, and we did not test it.

Property. In plain terms, an approval cannot commit if the selected draft depends on a withdrawn source, even when its number is correct. Precisely, at the publication transaction's serialization point an approval may commit only if the selected artifact exists, is sealed, and neither it nor any recorded ancestor carries a blocking (withdrawn or adjudicated) invalidation. Four properties are kept separate: principal attribution (the proposal author is the authenticated login), provenance integrity (agent roles cannot alter sealed artifacts or recorded edges), publication eligibility (the invariant above), and subsequent invalidation (an approval committed before a later invalidation is reported as superseded by the read-time view `current_approvals`, which consumers must query instead of the approvals table).

Fenced publication and schedules. `publish_decision` is callable only by an adjudicator. It first enters the fence: `SELECT ... FOR UPDATE` on a singleton row, an exclusive lock that `invalidate` also takes, so publication and invalidation serialize on one target and so do concurrent publishers; and an explicit refusal of any isolation level other than READ COMMITTED, because the closure walk is issued after the lock is acquired and under READ COMMITTED takes its snapshot then, seeing what earlier lock holders committed, whereas a REPEATABLE READ transaction would keep its older snapshot. Holding the lock, it checks existence and sealing, walks the full transitive closure including the artifact itself, requires the operator's acknowledgment list to cover every recorded direct input, and commits the approval. The live schedules in `tools/race_test.py` are: a naive check-then-approve monitor approving a withdrawn dependency (the failure mode), the gate rejecting once the retraction has committed, the fence refusing a prohibited isolation level (SQLSTATE 0A000), and a racing withdrawal after which the validity view shows no live approval. Four overlapping schedules were then measured on the scratch branch (`tools/race_schedules.py`, 9 of 9 checks): with publication holding the fence, an arriving withdrawal waited about 3 s, the approval committed and the view then showed it superseded; with the withdrawal holding the fence, publication waited and rejected; an aborted withdrawal left the waiting publication free to approve; an aborted publication left no approval row.

What it does not do. It is a database boundary, not a sandbox: it says nothing about shell, network or file egress. Operations the database denies at the privilege layer leave no application audit row, because they are rejected before any trigger fires; three of six attacks in our first battery were refused without a trace and a fourth, a foreign-thread read, returned zero rows silently, so only two reached the audit. After the evaluation we added a migration that records denied attempts for committed statements (section 4, structural tests); the frozen gate does not carry it.

Revocation. Identity is the login, so revoking an agent is removing its grant or its login (`tools/revocation_test.py`, eight checks: a revoked intake grant refuses the next submission while another role still submits, restoring it reinstates, NOLOGIN refuses the next connection). No row, trigger or function changes.

Separately authored verification. Lorien, an AI collaborator in a separate workspace, wrote an executable reference specification and a live acceptance driver against the committed SQL. Its first pass passed 1 of 9 core checks, and every failure was a real defect (nonexistent artifacts approved, only direct dependencies checked, provenance edges writable onto another agent's artifact; later a self-named proposer and an edgeless seal). Each was fixed and re-run, 1,

5, 8, then 19 of 19, and the migration passed all 19 on a fresh branch; four additive migrations after two reviews on 7 November were each re-verified. The frozen gate is commit `d2df880`. The suite checks specified boundaries, not every property.

3.2 Experiment design

The question is whether lineage preloaded into a reviewer's context changes stale proposals and correct completion compared with lineage the reviewer must fetch, or cannot fetch at all. Everything else is held fixed: the model, the task, the correction notice, the prompts, the token budget, the gate. Only the reviewer's context adapter varies.

arm	what the reviewer sees	enforcement	registered	complete	unsafe proposals	rejected at the gate	stopped before the gate	lineage-invalid commits	correct publications
current	queued drafts, current source, correction notice; no lineage	model proposes; gate decides	900	784	264	258	6	0	372
current + lookup	current, plus one optional authenticated lookup of the lineage records	model proposes; gate decides	900	784	151	82	69	0	532
compact	current, plus lineage records preloaded (versions, delivered inputs, invalidation status)	model proposes; gate decides	900	884	7	5	2	0	686
full	compact, plus the historical bodies as recorded inputs	model proposes; gate decides	900	874	6	3	3	0	687
rule	lineage records only; approves the queued draft whose closure is valid	deterministic; gate decides	900	900	0	0	0	0	900
rule + content	rule, plus a check of the figure against the current source	deterministic; gate decides	900	900	0	0	0	0	900
all			5400	5126	428	348	80	0	4077

Table 1. The six arms pooled over five cohorts and three families (900 registered per arm). A model proposes; the gate decides. Unsafe proposals are approvals of a draft with invalid lineage or selections of a non-queued artifact.

Fixed-input dispatch. Every model call goes through a delivery recorder written by Lorien: the harness resolves bodies from the authoritative store, hashes the request and each delivered body, and transmits it unchanged. A sealed output's dependencies come from that receipt, never from citations in the model's text. The recorder establishes what was supplied and sealed, not what the model relied on.

Tasks. Synthetic inventory counts with exact known answers, one harness-injected compromise opportunity per instance (a replayed stale body, a wrong body with valid lineage), identical across arms. No agent attempts anything adversarial in these runs; that lives in the containment battery. Identifiers are opaque random strings, because an early version leaked recency through names like `draft2`. The held-out families are V6 (figure unchanged, authorization changed), V11 (V6 with no correction notice delivered) and V1 (an unrelated correction before review, the false-quarantine control); the development and diagnostics variants are listed in Appendix B.1 and B.7.

Scoring. The reviewer returns a decision, a result, the evidence it rests on, and a separate consulted list; an approval's evidence must include the approved draft itself, a rule added after a pilot showed a stale pick with the right number and a current citation escaping detection. Gate events are recorded only after a separate committed-state query. The separately written scorer holds the answer keys and the provenance export and resolves withdrawn ancestors itself. Every registered run stays in the denominator. For lineage-visible staleness the expected lineage-invalid commit count is zero; for V10, whose lineage is valid, the measure is which reviewers catch a wrong figure by reading it.

3.3 Development findings that shaped the freeze

Development runs, one instance per cell, shaped the frozen design and are not effect sizes. Three Sonnet 5.5 pilots showed the no-lineage arm deferring on a replayed stale draft it could not distinguish, and the full arm approving the right draft while still citing the withdrawn source it had reasoned over, which led us to separate evidence from consulted artifacts. Lorien's same-number control showed lineage doing the work the number could not; the lookup control moved the difference from correctness to cost and corrected our hypothesis before the freeze. The gemma-4-31b-it replication failed only the same-number case in the no-lineage arm, with the correct number and a current citation, which exposed the scorer blind spot described in section 3.2.

4. Results

Preregistered before any freeze (`report/HELDOUT_PREREGISTRATION.md`); analysis by `tools/analysis.py`; every registered slot stays in its denominator. The full tables, per-arm counts, the branch audit, the cost ledger and the disclosed deviations are in Appendix B.

Preregistered before any freeze (`report/HELDOUT_PREREGISTRATION.md`); every registered slot stays in its denominator; full tables, the branch audit, costs and deviations are in Appendix B.

What ran. Five reviewer cohorts of 1,080 registered slots: three families at 60 instances (V6, the same-number authority change; V11, the same with no correction notice; V1, the clean-draft control), six arms per instance, presealed byte-identical upstream bodies, authenticated authorship, temperature 0, a 6,000-token budget, no retries, opaque identifiers, randomized arm and counterbalanced queue order (Appendix B.1), each cohort frozen with manifest, prompt, code and gate hashes, a request cap and a credit ceiling. The preregistered reliability rule (33 of 36 valid canary replies) admitted gemma-4-31b-it and deepseek-v4-flash to the inferential tier; qwen3.5-397b, qwen3.8-27b and gemma-4-26b-a4b-it are a labeled exploratory tier; two GLM models were excluded.

What the gate did. Across 5,400 registered slots the models made 428 unsafe proposals (an approval of a draft with invalid lineage, or a selection of a non-queued artifact): 348 were rejected by the fenced gate on lineage and 80 stopped before it; 4,077 correct publications committed; lineage-invalid commits 0. One slot has an unknown commit outcome (the request in flight when the host slept; the branch holds its approval row, the scorer counts an error). A read-only count of approvals on the evaluation branch matches the traces, with 4 extra rows from instances re-run whole after the resume and 1 from that slot, every one accounted for (Appendix B).




Figure 1. Completed correctly per arm on V6 and V11, and clean-draft approval on V1, five models, registered denominators; labels give lookups taken of offered.

Primary: completion, compact vs lookup-offered. The two inferential models answer the question differently.

model	family	compact	lookup-offered	lookup taken	delta	Tango 95%	Holm p	NI at -0.10
gemma-4-31b-it	V6	1.000	0.500	0/60	+0.500	[+0.377, +0.623]	5.1e-10	holds
gemma-4-31b-it	V11	0.983	0.633	13/60	+0.350	[+0.242, +0.476]	6.5e-08	holds
deepseek-v4-flash	V6	0.967	1.000	59/60	-0.033	[-0.114, +0.029]	0.043	holds

model	family	compact	lookup-offered	lookup taken	delta	Tango 95%	Holm p	NI at -0.10
deepseek-v4-flash	V11	1.000	1.000	60/60	+0.000	[-0.060, +0.060]	0.010	holds

On gemma-4-31b-it the lookup arm took its lookup in 13 of 120 offers, so it mostly behaved as the no-lineage arm and picked the stale draft half the time; compact completed 119 of 120. On deepseek-v4-flash the lookup was taken in 119 of 120 offers and the arms performed similarly near the ceiling. Non-inferiority (preregistered margin -0.10, one-sided at 0.05 with Holm over the six preregistered claims, four completion and two token; the intervals are two-sided 95% Tango) holds for all four claims; the deepseek V6 claim is marginal (one-sided p 0.043, interval reaching -0.114). Non-inferiority does not establish equality. Successful retrieval was associated with high completion in these cohorts; optional retrieval also introduced skipped acquisition and execution failures.

Co-primary: tokens per settled pair. Pairs where both arms have provider-reported usage; unresolved 504 attempts carry no usage and are excluded here while staying in the completion denominators. The preregistration fixed the claim's direction (compact uses fewer tokens), a Hodges-Lehmann estimate and an exact sign test, without stating the test's sidedness; we used the exact two-sided test, and those two-sided p-values entered the Holm adjustment over the six claims. A claim is supported only when the estimate is in the claimed direction and the adjusted p is below 0.05. Supported on deepseek-v4-flash: compact saved a Hodges-Lehmann 1280 tokens per pair. Not supported on gemma-4-31b-it: compact cost 263 more (Hodges-Lehmann), so its small two-sided p reflects the opposite direction; a one-sided test in the claimed direction would give p near 1.

model	settled pairs	Hodges-Lehmann, lookup minus compact	Holm p	claim: compact uses fewer
gemma-4-31b-it	119	-263	1.3e-18	not supported, opposite direction
deepseek-v4-flash	118	+1280	3.6e-35	supported

False quarantine on the clean-draft control (V1), descriptive. Approvals of the clean draft out of 60, per arm:

model	current	current + lookup	compact	full	rule	rule + content
gemma-4-31b-it	51/60	51/60	41/60	41/60	60/60	60/60
deepseek-v4-flash	0/60	0/60	0/60	0/60	60/60	60/60
qwen3.5-397b	1/60	1/60	1/60	0/60	60/60	60/60
qwen3.8-27b	0/60	0/60	0/60	0/60	60/60	60/60
gemma-4-26b-a4b-it	60/60	45/60	60/60	60/60	60/60	60/60

Both rule arms approve every clean draft on every model. deepseek-v4-flash and qwen3.8-27b quarantine it in every complete slot of every model arm, and qwen3.5-397b in all but at most one, including the current arm, which sees only the bodies, the current source and an unrelated notice, so the refusal does not require lineage. The diagnostics point to the trigger: V8 is V1 with one change, the unrelated recount carries the same figure as the draft, and both inferential models approved the clean draft in 10 of 10 instances in every model arm (Appendix B.7), so the refusal tracks a current source whose figure disagrees with the draft rather than the notice itself; V8 is a separate ten-instance freeze, so this is descriptive. gemma-4-31b-it approves 51 of 60 without lineage and 41 of 60 with it. On gemma-4-31b-it lineage changed the rate, so providing lineage is not irrelevant to refusal either.

Exploratory tier and diagnostics. The three exploratory models split the same way (Appendix B.5): qwen3.8-27b follows the gemma-31 pattern, qwen3.5-397b behaves like deepseek-v4-flash, gemma-4-26b-a4b-it is the weakest reviewer, and the full arm tracks compact everywhere. In the V10 diagnostic (valid lineage, wrong figure; Appendix B.7) the gate commits whatever the reviewer approves by design; the lineage-only rule approves every one, the content rule catches all ten, and the model arms caught 5 to 9 of 10.

Cost and incidents. Metered charges for the five cohorts were 7.69 credits; reserves kept for provider timeouts whose usage the platform never returned add at most 7.92, a worst-case liability of 15.61. The runner counts every kept reserve as spent, so each cohort's ceiling bounded that worst case (Appendix B.8). qwen3.5-397b reached its 900-request cap with 2 slots unsent, registered as guard-stopped in its denominator. Across every paid platform run in both workspaces, including development runs, the two canaries, diagnostics and follow-ups, metered charges were

8.75 credits and worst-case liability 22.23 of the 100 authorized (`report/heldout_results/cost_reconciliation.json`, one row per ledger). Deviations (a host sleep recovered with a resume mode under the original freeze, a diagnostics pause, a post-results fix to the Holm bookkeeping that changed no p-value) are in Appendix B.9.

4.1 Follow-up cohorts run after the preregistered set (post-hoc, labeled)

Both cohorts were frozen and run after the preregistered set had been analyzed and this report drafted: new seeds, new freezes, separate ledgers, never pooled; tables and full prose in Appendix B.10.

Lookup required. With the lookup required as the first reply, gemma-4-31b-it took it in 120 of 120 offers and produced 120/120 correct completions on new instances versus 119/120 with preloading (V6 compact minus lookup -0.017, Tango 95% [-0.089, +0.045]; V11 +0.000, [-0.060, +0.060]). Requiring lookup eliminated the observed completion gap, supporting the retrieval-uptake explanation, at an estimated 724 additional tokens per settled pair (Hodges-Lehmann).

Fresh DeepSeek cohort. Preloading completed 60/60 cases versus 51/60 with optional lookup (lookup taken 47/60; compact minus lookup +0.150, Tango 95% [+0.081, +0.261]): three misses followed decisions without retrieval and six were provider errors, so the gap combines skipped retrieval and execution failure. Not pooled with the preregistered cohort.

A second surface template. Every held-out and follow-up cohort above used one synthetic template, inventory counts at a warehouse site. To test whether the pattern is a property of that wording, the runner gained a recorded task-domain switch: the same families, scoring and gate, with the researcher reporting resolved service-desk tickets for a queue in a region instead of units of an item at a warehouse, and the system prompts rewritten to match; the domain is hashed into the freeze. Two post-hoc cohorts, new seeds, 30 instances per family, lookup optional as frozen: gemma-4-31b-it: preloaded lineage 60 of 60, lookup offered 31 of 60 with the lookup taken 2 of 60; lineage-invalid commits 0; deepseek-v4-flash: preloaded lineage 60 of 60, lookup offered 54 of 60 with the lookup taken 54 of 60; lineage-invalid commits 0. Rates use the registered denominator of 30 per arm and family. The ordering matches the inventory template: preloaded lineage completes the same-number case, the optional-lookup arm completes it less often, with uptake and provider errors both contributing, and no lineage-invalid publication occurred. Tables in Appendix B.10.

4.2 Structural tests: containment, identity under copying, blast radius

Four deterministic tests on a disposable branch with no model calls (the attacker is a fixed script; a model asked to impersonate another agent declined). Full prose and tables in Appendix B.10.

Containment, naive versus bound. The same six attacks against both boards. Naive: two spoofed identities landed, a rename fooled the board, four foreign rows read, one message tampered, three deleted, nothing logged. Bound: every count zero, two spoof attempts in the operator audit, honest chain complete on both.

Identity under copying. Ten copies with ten claimed names through one login: ten identities on the naive board, one on the bound intake (names kept as evidence), one revocation silenced all ten; stable attribution under shared credentials, not identification of individual copies (`tools/identity_copies_test.py`).

Blast radius. One adjudicated root, sixty descendants three deep, twenty unrelated: the closure walk blocked 60 of 60 at every depth and approved 20 of 20 unrelated at a median 0.448 s; a direct-dependency check catches 20 of 60; no lineage catches none (`tools/blast_radius_test.py`).

Audit extension after the evaluation. Only two of the six attacks reached the audit: three were refused by the privilege layer before any trigger ran and a foreign-thread read returned zero rows silently. `sql/hive_audit_denials.sql` accepts the statement, denies every effect with row security, and records the attempt (statement-level triggers for zero-row updates and deletes, logging read policies): 6 of 6 attacks now visible (from 2) for committed statements, effects still zero, no false positives on an honest agent's own-thread reads. The audit row is written by the attempt's own transaction, so an attacker who controls transaction boundaries and rolls back leaves no

row (tested: committed denied update recorded 1, rolled-back denied update recorded 0); the HTTP path, where each statement is its own transaction, is covered. Scratch branch only, not on the frozen gate.

5. Discussion and Limitations

Discussion. What is new is narrow: the same-number failure construction, a boundary that enforces lineage eligibility below the reviewer, and a preregistered matched evaluation of how evidence delivery affects the reviewer above it. Its central result is that optional retrieval fails in two ways, by being skipped and by failing to execute, and that preloading or required retrieval removed the first at different token costs (section 3.3 and its follow-ups).

The safety reading is in two parts, and the primary evidence is a controlled reviewer-protocol evaluation over synthetic matched artifacts, not an adaptive swarm. The gate is the part we would trust in deployment: across 5,400 registered slots on 5 models (3,600 model-reviewed), 428 unsafe proposals and 0 lineage-invalid commits, every approval row accounted for; in the V10 diagnostic, where lineage is valid and the figure wrong, it committed 34 content-wrong approvals across the two models, by design. The model reviewer above it is the part to measure per model: lineage that lifted one model from 68 to 119 of 120 made it refuse more clean drafts, three models approved none or almost none of the clean drafts under any unrelated notice, and a deterministic rule reading the same lineage never false-quarantined and never missed a stale draft. The model's remaining job is content (V10), and it should be measured per model and bounded by the rule.

Limitations. Appendix A gives the full list, as the sprint rules require. The three that bound the claims most: the operator is trusted and owns every function, so a compromised owner defeats every property; lineage is what the runtime delivered, not what the model relied on; and the tasks are known-answer counts from one inventory template plus one post-hoc second template, so the intervals describe resampling of those templates, not a task distribution.

Future work. An eager deterministic lookup that delivers lineage records before the model's first call; identity per agent instance rather than per role login; a trusted gateway in front of the database so that statements against objects an agent holds no privilege on become legible; contention and throughput measurements; and a reviewer fine-tuned on these traces, evaluated under the same frozen protocol.

6. Conclusion

A publication gate that re-reads authenticated lineage inside one fenced transaction held across 5,400 registered slots on 5 open models: 428 unsafe proposals, none committed, every approval row on the evaluation branch accounted for. Reviewer completion above it depended on how evidence was delivered: optional retrieval was skipped or failed to execute, while preloading or required retrieval largely removed the acquisition failure at different token costs. Three models refused clean drafts whenever an unrelated current source disagreed with the draft's figure; the deterministic rule never did. Model reviewers can confuse factual agreement with publication eligibility; a trusted lineage boundary enforces that distinction independently of their decisions (code and data: Appendix C).

References

Incident figures (about 1,200 agents, about 700 attackers, about 7 percent transcript spoofing, 7,905 distinct names) are cited as the sprint brief gives them, which also cites OpenAI's public disclosure and a ControlAI analysis we did not consult directly; we verified the existence, authorship and venue of the published papers below but did not re-derive the incident figures from the primary reports.

- Apart Research and AI Alignment Foundation. Swarm Alignment Hackathon brief and rules, November 2026. apartresearch.com/sprints/swarm-alignment-2026, aialignmentfoundation.org/hackathons/swarm-alignment-2026.
- METR and Redwood Research. Investigation of the July 2026 OpenAI agent incident at Hugging Face (incident 7 to 13 July 2026; report published 26 August 2026). Figures as cited in the sprint brief.
- Swarm Traces. Reassembled attack payloads from the Hugging Face incident, redacted dataset and analysis, 2026. Naming figure as cited in the sprint brief.

- Greenblatt, R., Shlegeris, B., Sachan, K., Roger, F. AI Control: Improving Safety Despite Intentional Subversion. Proceedings of the 41st International Conference on Machine Learning, PMLR 235:16295-16336, 2024. arXiv:2312.06942.
- Hammond, L. et al. Multi-Agent Risks from Advanced AI. Cooperative AI Foundation Technical Report 1, 2025. arXiv:2502.14143.
- Lee, D., Tiwari, M. Prompt Infection: LLM-to-LLM Prompt Injection within Multi-Agent Systems. arXiv:2410.07283, 2024.
- Motwani, S. R. et al. Secret Collusion among AI Agents: Multi-Agent Deception via Steganography. Advances in Neural Information Processing Systems 37 (NeurIPS 2024). arXiv:2402.07510.
- Rose, A. et al. Detecting Multi-Agent Collusion Through Multi-Agent Interpretability. arXiv:2604.01151, 2026.
- Tennenholtz, M. Program equilibrium. Games and Economic Behavior 49(2):363-373, 2004.
- Governed Shared Memory for Multi-Agent LLM Systems (MemClaw). arXiv:2606.24535, 2026.
- From Agent Traces to Trust: A Survey of Evidence Tracing and Execution Provenance in LLM Agents. arXiv:2606.04990, 2026.
- Execution Lineage for Reproducible AI-Native Work. arXiv:2605.06365, 2026.
- Ouyang, C. et al. MemLineage: Lineage-Guided Enforcement for LLM Agent Memory. arXiv:2605.14421, 2026.
- STALE: Can LLM Agents Know When Their Memories Are No Longer Valid? arXiv:2605.06527, 2026.
- ToolFailBench: Diagnosing Tool-Use Failures in LLM Agents. arXiv:2607.04686, 2026.
- Tango, T. Equivalence test and confidence interval for the difference in proportions for the paired-sample design. Statistics in Medicine 17(8):891-908, 1998.
- Reinhold, A. CAMA: Circular Associative Memory Architecture, preprint series, Zenodo, 2026. ORCID 0009-0005-5803-8401.
- Adaption. Platform and API documentation, docs.adaptionlabs.ai, accessed 7 November 2026.

Acknowledgments. Lorien, an AI collaborator operating as Codex in a separate workspace, wrote the executable reference specification, the live acceptance driver that caught eight defects in the first gate, the delivery recorder, the independent scorer, and the same-number and lookup controls, and reviewed every boundary described here. Adaption provided platform credits used for the open-model replication. Any errors are the author's.

Appendix A. Limitations and Dual-Use / Ethical Considerations

Limitations.

- The trust is centralized. One operator seals, adjudicates and publishes, and owns every function. A compromised or malicious owner defeats every property, including rewriting the audit. This is an explicit assumption, not a solved problem, and the entry makes no decentralized-governance claim.
- Lineage is what the runtime delivered, not what the model used. The recorder proves which bodies were supplied and sealed. It cannot certify that a hidden source was excluded or that a delivered input influenced the output. A false claim with no verifiable contradiction remains undetectable.
- A database boundary is not a sandbox. The gate says nothing about shell, network or file egress. Operations the database denies at the privilege layer leave no application audit row; we measured this (only two of the six battery attacks reached the audit) and, after the evaluation, added a migration that records denied attempts while still denying the effect. Its coverage is committed statements: the audit row is written by the same transaction, so an attacker who controls transaction boundaries and rolls back leaves no row (tested, Appendix B.10); each statement on the HTTP path is its own transaction. Statements against tables an agent holds no privilege on remain invisible. The migration is not on the frozen gate the held-out cohorts used.
- Concurrency was tested as race schedules, not as scale. We ran concurrent publication against retraction with serialized commits: a naive two-step monitor approves a withdrawn dependency, the fenced gate rejects it, the fence refuses any isolation level other than READ COMMITTED, and an advisory contradiction held open in another session no longer blocks publication. The singleton fence is a serial correctness reference by design. Nothing here measures throughput, contention under load, cascading failure, emergent coordination, or the thousand-agent regime of the motivating incident.
- Small, synthetic cohorts from two templates. Development cells are n of one. Held-out cells are 60 instances per family per model on five models, each its own cohort and never pooled; tasks are known-answer counts from one inventory template, with a second surface template (service-desk tickets) tested post-hoc on two models at 30 instances per family. The intervals describe resampling of those templates, not a task distribution. Transfer to real deployments is not established.
- Refusal under a correction notice dominates two results. Three of the five models quarantined the clean draft in all or nearly all slots whenever an unrelated correction was present, in every model-context condition including current-only review, so the refusal cannot be attributed to providing lineage; the V8 diagnostic (the same structure with the unrelated recount matching the draft's figure, approved 10 of 10 in every model arm by both inferential models) points to a disagreeing current source as the trigger, though V8 is a separate ten-instance freeze. On gemma-4-31b-it visible lineage raised false quarantine from 8 and 9 of 60 (current, lookup) to 18 and 17 (compact, full), so lineage can still change the rate. The deterministic rule arms never false-quarantined. A reviewer protocol built on these models would need that rule as a floor, and the gate as the backstop it already is.
- The primary cohorts are a controlled reviewer-protocol evaluation over synthetic, presealed, matched artifacts; no agent in them is adversarial or adaptive. They do not establish robustness to coordinated provenance manipulation, strategic channel choice, attacks on runtime input capture, or availability attacks on the trusted boundary; the scripted battery adds boundary coverage, not an adaptive adversary.
- The lookup arm measures lookup offered, not lookup used. Whether a model takes an offered lookup is a prompt and model property we did not control, and it decided the gemma-31 result. An eager deterministic lookup would remove the question, and would make the compact arm's preloading redundant by construction.
- One slot of 5,400 has an unknown commit outcome, caused by the host sleeping mid-call; the branch shows the approval, the scorer counts an error. Five approval rows on the branch beyond the traces are explained, four by instances re-run whole after the resume and one by that slot. One cohort reached its request cap with two slots unsent. All of it is reported in Appendix B rather than reconciled away.

- The acknowledgment list at publication is an operator acknowledgment of recorded direct inputs, not an independent reviewer attestation that binds artifact version and full dependency snapshot. We removed a mechanism that appeared to do the latter but changed no decision.
- The no-lookup arm is a diagnostic, not a representative retrieval system. The lookup arm is the fair comparator, and its result constrains our claims to call and token cost rather than correctness.

Dual-use. We publish a battery of six scripted attacks against a shared agent record (spoof a sender, read a foreign thread, post under a new name, read the operator audit, edit another agent's message, delete messages) and an evaluation family that replays a stale artifact. Each is generic, already public from the incident investigations, and run only against synthetic data in a disposable test database. No exploit against any real system is included, and the attacks exist to show what a defense must catch. The gate itself is a central control point and could be used to surveil or silence agents rather than protect a shared record; that risk is inherent to the trusted-operator design and is why we state the trust boundary rather than present the gate as neutral infrastructure.

Ethical considerations. No human subjects and no personal data; all artifacts are synthetic. Model behavior is reported as observed, including a model declining to play an attacker when asked directly. The independent verification, scorer and controls were produced by an AI collaborator, Lorien, running in its own workspace; that collaboration is disclosed rather than hidden. Sponsor credits paid for the open-model cohorts; the model set was fixed by a preregistered reliability rule applied before any held-out result existed, not by cost or by outcome.

Appendix B. Held-out tables, audit and deviation log

All tables are generated by `tools/results_tables.py` from the committed traces, ledgers and `holdout/heldout_v1/INDEX.json`; the numbers in section 4 are read from the same files.

Budget canary that set the tiers (nine matched cases, six arms, 6,000-token budget). Valid structured replies of 36 model-reviewed slots: gemma-4-31b-it 36, deepseek-v4-flash 34, qwen3.5-397b 31, qwen3.8-27b 30, gemma-4-26b-a4b-it 30, glm-53-flash 1, glm-5.2 0. 378 slots, 0.36 credits metered plus 4.53 credits of reserves kept for 19 gateway timeouts (run in Lorien's workspace; included in the all-run reconciliation). At the earlier 1,200-token budget 108 of 115 invalid replies had stopped at the budget, 101 with empty answer text.

B.1 Design as frozen

tier	model	cohort	freeze id	slots	request cap	ceiling (cr)	modeled charge	all-at-cap	seed	complete
primary	gemma-4-31b-it	heldout_gemma431bit	0cc7599ca5cf	1080	900	2.41	0.154	1.903	2026110802	yes
primary	deepseek-v4-flash	heldout_deepseekv4fl	86cc12f709ad	1080	900	3.74	0.182	0.751	2026110802	yes
exploratory	qwen3.5-397b	heldout_qwen35397b	0e4d9fc18c9c	1080	900	35.61	4.651	19.321	2026110802	yes
exploratory	qwen3.8-27b	heldout_qwen3827b	5b020297c30b	1080	900	11.21	2.0	6.78	2026110802	yes
exploratory	gemma-4-26b-a4b-it	heldout_gemma426ba4b	ada5706d6dea	1080	900	1.82	0.125	1.437	2026110802	yes

B.2 Registered slots and failure categories

deepseek-v4-flash's 504s fell mostly in the current arm, where it produced about five times as many reasoning tokens as with lineage preloaded (mean reasoning tokens on settled V6 slots: current 2674.6, compact 528.3). gemma-4-26b-a4b-it's non-queued selections were stopped before the gate. qwen3.5-397b reached its 900-request cap with 2 slots unsent, registered as guard-stopped in its denominator. The interleaved task order kept the families balanced: the guard-stopped slots belong to the last instance in the queue.

model	registered	complete	invalid: budget	invalid: malformed/non-queued	invalid: pre-gate stop	error 504	error 502	transport timeout	error other	missing	guard-stopped	errors by arm
gemma-4-31b-it	1080	1073	0	0	0	7	0	0	0	0	0	full 3, compact 2, current 2
deepseek-v4-flash	1080	1020	2	3	0	54	1	0	0	0	0	current 45, current_lookup 5, full 3, compact 2
qwen3.5-397b	1080	1002	10	11	0	55	0	0	2	0	2	current 48, compact 3, full 3, current_lookup 3
qwen3.8-27b	1080	1037	41	0	0	1	0	0	0	0	0	current_lookup 1
gemma-4-26b-a4b-it	1080	994	0	85	0	0	0	0	1	0	0	compact 1

B.3 Primary and co-primary, full

model	family	n pairs	both	compact only	lookup only	neither	compact rate	lookup rate	delta	Tango 95%	NI p (margin -0.10)	Holm p	non-inferiority
gemma-4-31b-it	V6	60	30	30	0	0	1.000	0.500	+0.500	[+0.377, +0.623]	1.27e-10	5.08e-10	holds
gemma-4-31b-it	V11	60	38	21	0	1	0.983	0.633	+0.350	[+0.242, +0.476]	2.16e-08	6.48e-08	holds
deepseek-v4-flash	V6	60	58	0	2	0	0.967	1.000	-0.033	[-0.114, +0.029]	0.043	0.043	holds
deepseek-v4-flash	V11	60	60	0	0	0	1.000	1.000	+0.000	[-0.060, +0.060]	0.005	0.010	holds

model	settled pairs	Hodges-Lehmann	mean	direction	sign-test p	Holm p	preregistered claim
gemma-4-31b-it	119	-263.0	-173.0	compact costlier	2.67e-19	1.34e-18	not supported: opposite direction
deepseek-v4-flash	118	+1280.5	+1401.8	compact cheaper	6.02e-36	3.61e-35	supported

model	tier	family	arm	mean calls	mean tokens (in+out)	mean reasoning tokens	lookup used/offered
gemma-4-31b-it	primary	V6	compact	1	1253.5	0	
gemma-4-31b-it	primary	V6	current_lookup	1	971.1	0	0/60
gemma-4-31b-it	primary	V11	compact	1	1118.3	0	
gemma-4-31b-it	primary	V11	current_lookup	1.22	1053.6	0	13/60
gemma-4-31b-it	primary	V1	compact	1	1076.3	0	
gemma-4-31b-it	primary	V1	current_lookup	1.02	929.3	0	1/60
deepseek-v4-flash	primary	V6	compact	1	1672.6	528.3	
deepseek-v4-flash	primary	V6	current_lookup	1.98	3415.9	1510.1	59/60
deepseek-v4-flash	primary	V11	compact	1	1538.5	493.7	
deepseek-v4-flash	primary	V11	current_lookup	2	2604.3	878.0	60/60
deepseek-v4-flash	primary	V1	compact	1	2523.2	1560.2	
deepseek-v4-flash	primary	V1	current_lookup	1.55	3463.4	2149.4	35/60
qwen3.5-397b	exploratory	V6	compact	1	3159.1	1867.4	
qwen3.5-397b	exploratory	V6	current_lookup	2	3449.3	1411.8	60/60

model	tier	family	arm	mean calls	mean tokens (in+out)	mean reasoning tokens	lookup used/offered
qwen3.5-397b	exploratory	V11	compact	1	2169.3	1029.7	
qwen3.5-397b	exploratory	V11	current_lookup	2	2763.9	1001.3	60/60
qwen3.5-397b	exploratory	V1	compact	1	2143.1	1138.9	
qwen3.5-397b	exploratory	V1	current_lookup	1.97	3736.8	2044.7	59/60
qwen3.8-27b	exploratory	V6	compact	1	2084.2	811.0	
qwen3.8-27b	exploratory	V6	current_lookup	1.93	5698.2	3717.7	56/60
qwen3.8-27b	exploratory	V11	compact	1	2023.2	836.8	
qwen3.8-27b	exploratory	V11	current_lookup	1.8	4776.5	3129.2	48/60
qwen3.8-27b	exploratory	V1	compact	1	4154.6	3119.8	
qwen3.8-27b	exploratory	V1	current_lookup	1.49	7141.3	5878.4	29/60
gemma-4-26b-a4b-it	exploratory	V6	compact	1	1267.9	0	
gemma-4-26b-a4b-it	exploratory	V6	current_lookup	1.03	1018.2	0	2/60
gemma-4-26b-a4b-it	exploratory	V11	compact	1	1135.2	0	
gemma-4-26b-a4b-it	exploratory	V11	current_lookup	1.08	948.2	0	5/60
gemma-4-26b-a4b-it	exploratory	V1	compact	1	1075.5	0	
gemma-4-26b-a4b-it	exploratory	V1	current_lookup	1.1	1016.2	0	6/60

B.4 V1 false quarantine per arm

model	arm	registered	complete	approved clean draft	false quarantine	invalid	error
gemma-4-31b-it	current	60	59	51	8	0	1
gemma-4-31b-it	current_lookup	60	60	51	9	0	0
gemma-4-31b-it	compact	60	59	41	18	0	1
gemma-4-31b-it	full	60	58	41	17	0	2
gemma-4-31b-it	rule	60	60	60	0	0	0
gemma-4-31b-it	rule_content	60	60	60	0	0	0
deepseek-v4-flash	current	60	59	0	59	0	1
deepseek-v4-flash	current_lookup	60	53	0	53	2	5
deepseek-v4-flash	compact	60	60	0	60	0	0
deepseek-v4-flash	full	60	56	0	56	1	3
deepseek-v4-flash	rule	60	60	60	0	0	0
deepseek-v4-flash	rule_content	60	60	60	0	0	0
qwen3.5-397b	current	60	33	1	32	6	21
qwen3.5-397b	current_lookup	60	44	1	43	13	3
qwen3.5-397b	compact	60	58	1	57	0	2
qwen3.5-397b	full	60	57	0	57	0	3
qwen3.5-397b	rule	60	60	60	0	0	0
qwen3.5-397b	rule_content	60	60	60	0	0	0
qwen3.8-27b	current	60	55	0	55	5	0
qwen3.8-27b	current_lookup	60	35	0	35	24	1
qwen3.8-27b	compact	60	58	0	58	2	0
qwen3.8-27b	full	60	54	0	54	6	0
qwen3.8-27b	rule	60	60	60	0	0	0
qwen3.8-27b	rule_content	60	60	60	0	0	0
gemma-4-26b-a4b-it	current	60	60	60	0	0	0
gemma-4-26b-a4b-it	current_lookup	60	54	45	9	6	0

model	arm	registered	complete	approved clean draft	false quarantine	invalid	error
gemma-4-26b-a4b-it	compact	60	60	60	0	0	0
gemma-4-26b-a4b-it	full	60	60	60	0	0	0
gemma-4-26b-a4b-it	rule	60	60	60	0	0	0
gemma-4-26b-a4b-it	rule_content	60	60	60	0	0	0

B.5 Completed correctly per arm, all models and families

model	tier	family	current	current_lookup	compact	full	rule	rule_content
gemma-4-31b-it	primary	V6	30/60	30/60	60/60	59/60	60/60	60/60
gemma-4-31b-it	primary	V11	30/60	38/60	59/60	60/60	60/60	60/60
gemma-4-31b-it	primary	V1	51/60	51/60	41/60	41/60	60/60	60/60
deepseek-v4-flash	primary	V6	17/60	60/60	58/60	60/60	60/60	60/60
deepseek-v4-flash	primary	V11	20/60	60/60	60/60	60/60	60/60	60/60
deepseek-v4-flash	primary	V1	0/60	0/60	0/60	0/60	60/60	60/60
qwen3.5-397b	exploratory	V6	22/60	60/60	59/60	60/60	60/60	60/60
qwen3.5-397b	exploratory	V11	27/60	60/60	60/60	60/60	60/60	60/60
qwen3.5-397b	exploratory	V1	1/60	1/60	1/60	0/60	60/60	60/60
qwen3.8-27b	exploratory	V6	30/60	56/60	60/60	60/60	60/60	60/60
qwen3.8-27b	exploratory	V11	30/60	53/60	60/60	60/60	60/60	60/60
qwen3.8-27b	exploratory	V1	0/60	0/60	0/60	0/60	60/60	60/60
gemma-4-26b-a4b-it	exploratory	V6	30/60	11/60	52/60	51/60	60/60	60/60
gemma-4-26b-a4b-it	exploratory	V11	24/60	7/60	56/60	56/60	60/60	60/60
gemma-4-26b-a4b-it	exploratory	V1	60/60	45/60	60/60	60/60	60/60	60/60

B.6 Gate integrity and the read-only branch audit

model	slots	gate calls	unsafe proposals	pre-gate stops	gate rejections	correct publications	lineage-invalid commits	unknown commit outcome	db-verified approvals
gemma-4-31b-it	1080	1021	111	0	111	910	0	0	910
deepseek-v4-flash	1080	792	38	1	37	755	0	0	755
qwen3.5-397b	1080	813	48	6	42	771	0	0	771
qwen3.8-27b	1080	835	66	0	66	769	0	0	769
gemma-4-26b-a4b-it	1080	965	165	73	92	872	0	1	872
all	5400	4426	428	80	348	4077	0	1	4077

model	db-verified approved events in traces	approvals from superseded partial traces (instance re-run after resume)	slots with unknown commit outcome	approval rows on branch	rows unexplained
gemma-4-31b-it	910	0	0	910	0
deepseek-v4-flash	755	0	0	755	0
qwen3.5-397b	771	1	0	772	0
qwen3.8-27b	769	3	0	772	0
gemma-4-26b-a4b-it	872	0	1	873	0

The unknown-outcome slot is gemma-4-26b-a4b-it, V11 instance 41, compact arm: the model approved, the gate call began, and the database connection died in the host sleep before the process read the committed decision. The branch holds the approval row; the scorer does not count it. The qwen3.8-27b surplus is the superseded partial instance V6i05, whose approvals committed before the crash and which was re-run whole after the resume.

B.7 Diagnostics families (descriptive, n = 10 per family, two models)

Separate freeze (seed 2026110803), eight families at ten instances, same six arms, same budget. V10 is the eligible-but-wrong control: the queued draft's lineage is valid and its figure is wrong, so the gate commits whatever a reviewer approves. Its "content-wrong commits" below are that designed content blind spot, counted here and not in the gate-integrity totals of section 4, which cover the three primary families where lineage decides. The rule arm approves every V10 draft (it reads lineage only); the rule-with-content reference catches every one.

model	family	current	current_lookup	compact	full	rule	rule_content	errors	invalid	unsafe proposals	content-wrong commits
gemma-4-31b-it	V0	10/10	10/10	10/10	9/10	10/10	10/10	1	0	0	0
gemma-4-31b-it	V3	10/10	10/10	10/10	9/10	10/10	10/10	1	0	0	0
gemma-4-31b-it	V4	5/10	8/10	10/10	10/10	10/10	10/10	0	1	6	0
gemma-4-31b-it	V5	10/10	10/10	10/10	10/10	10/10	10/10	0	0	0	0
gemma-4-31b-it	V7	10/10	9/10	10/10	9/10	10/10	10/10	0	0	0	0
gemma-4-31b-it	V8	10/10	10/10	10/10	10/10	10/10	10/10	0	0	0	0
gemma-4-31b-it	V9	9/10	9/10	10/10	10/10	10/10	10/10	0	1	0	0
gemma-4-31b-it	V10	9/10	5/10	7/10	8/10	0/10	10/10	0	0	21	21
deepseek-v4-flash	V0	10/10	10/10	10/10	10/10	10/10	10/10	0	0	0	0
deepseek-v4-flash	V3	10/10	10/10	10/10	10/10	10/10	10/10	0	0	0	0
deepseek-v4-flash	V4	7/10	10/10	10/10	10/10	10/10	10/10	3	0	0	0
deepseek-v4-flash	V5	10/10	10/10	10/10	10/10	10/10	10/10	0	0	0	0
deepseek-v4-flash	V7	10/10	10/10	9/10	10/10	10/10	10/10	1	0	0	0
deepseek-v4-flash	V8	10/10	10/10	10/10	10/10	10/10	10/10	0	0	0	0
deepseek-v4-flash	V9	10/10	10/10	9/10	10/10	10/10	10/10	1	0	0	0
deepseek-v4-flash	V10	7/10	6/10	5/10	9/10	0/10	10/10	8	2	14	13

model	registered	complete	error 504	missing	unsafe proposals	gate rejections	pre-gate stops	content-wrong commits	unknown outcome	metered	reserves kept	ceiling	complete run
gemma-4-31b-it	480	476	2	0	27	5	1	21	0	0.0531	0.0502	1.09	yes
deepseek-v4-flash	480	465	13	0	14	0	1	13	0	0.0565	0.6162	1.89	yes

B.8 Cost per cohort

Metered charges are the sum of verified per-call charges at the posted rates. A reserve is the most one attempt can cost (documented context times the input rate plus the output budget times the output rate); it is debited before each request and reconciled to the metered charge when usage returns. Reserves kept are those of attempts whose usage never returned (provider 504s); the platform does not report whether they were billed, so they are an upper bound, and metered plus kept is the worst-case liability. The peak guard total is the runner's running total, which counts every kept reserve as spent; the ceiling bounds it, refusing any call whose reserve would cross it, so the ceiling bounds worst-case liability. After the host-sleep resume the runner re-counted the pre-resume kept reserves once more, a conservative over-count that only lowered headroom. An earlier version of this table reported the running total as settled usage and added kept reserves to it a second time; that was a reporting error, corrected here, and no ceiling or decision depended on it.

model	attempts	request cap	metered charges	reserves kept (unresolved)	worst-case liability	peak guard total	ceiling	modeled charge	all-at-cap	resumes
gemma-4-31b-it	735	900	0.1135	0.1756	0.289	0.4895	2.41	0.154	1.903	1
deepseek-v4-flash	877	900	0.1582	2.6069	2.7651	2.9073	3.74	0.182	0.751	1
qwen3.5-397b	900	900	4.9467	5.12	10.0666	11.0874	35.61	4.651	19.321	1
qwen3.8-27b	855	900	2.3787	0.0177	2.3964	2.4243	11.21	2.0	6.78	1
gemma-4-26b-a4b-it	733	900	0.0902	0	0.0902	0.1112	1.82	0.125	1.437	1
all			7.6873	7.9202	15.6075					

B.9 Deviations from the preregistration

1. Host sleep. The five cohorts launched at 00:23 EST on 8 November. The laptop slept from 01:06 to 13:32 EST. On wake every cohort process died on a dead database socket. No model request was in flight except the gemma-26 slot above; every finished slot was already on disk. A resume mode was added to the runner (`--resume-out`, commit cc7a480). It validates the execution record and the registry claim, keeps every instance with a trace for all six arms, re-runs the one partially complete instance per cohort as a whole (gemma-31 V11i20, deepseek V1i06, qwen-397 V6i04, qwen-27 V6i05; gemma-26 had none) with the partial traces set aside in `traces.partial_superseded.jsonl`, inherits the prior ledger's settled spend, retained reserves and attempt count so the ceiling and the request cap still bind, and records the resume in `EXECUTION.json` and the registry. The frozen instances, prompts and arm orders did not change; the re-run slots were answered about thirteen hours later by the same models at temperature 0. All five resumed at 13:55 EST. The runner also gained connection keepalives and a single reconnect on a dead socket.
2. Diagnostics paused. Both diagnostics cohorts were paused at 00:28 EST because the gemma-31 primary was timing out on 3 of 9 attempts while sharing its endpoint with its diagnostics twin. They were resumed under the same claims after the primaries finished, at 18:03 and 18:07 EST, and both completed.
3. Analysis code fixed after results were seen. `tools/analysis.py` built the vector of p-values with the completion claims first and wrote the Holm-adjusted values back in claim order, so adjusted values were attached to the wrong claims. Fixed in commit dbb70f8. No p-value changed, only which adjusted value sat next to which claim; both versions are in git and the self-test output is unchanged.
4. Not a deviation, recorded for completeness: the direction of the token claim was fixed in the preregistration. The gemma-31 result is reported as not supported rather than reinterpreted.
5. Post-hoc follow-up cohorts. Two cohorts were frozen and run after the preregistered set had been analyzed and this report drafted (section 4, follow-up subsection): a gemma-4-31b-it cohort with the lookup made mandatory and an independent deepseek-v4-flash V6 replication. New seeds, new freezes, separate ledgers, never pooled with the held-out set; their results are labeled post-hoc wherever they appear.

6. Structural tests added after the report draft. The containment battery was run before the sprint's held-out evaluation; the identity-under-copying and blast-radius tests (section 4, structural subsection) were written and run on the scratch branch after the held-out analysis, with no model calls, and do not change any held-out number.
7. Audit migration after the evaluation. `sql/hive_audit_denials.sql` (statement-level denial triggers and logging read policies on the bound board) was written and tested on the scratch branch after the held-out analysis. It is not applied to the evaluation branch and changes no held-out number; its before/after is in the structural subsection.
8. Second surface template, post-hoc. A recorded task-domain switch (`TASK_DOMAIN`, hashed into the freeze) rewrites the task wording and system prompts from inventory counts to resolved service-desk tickets with the same families, scoring and gate. Two cohorts (gemma-4-31b-it, deepseek-v4-flash; V6 and V11; 30 instances per family; lookup optional as frozen) were frozen and run after the report draft; results are in section 4 and Appendix B.10, labeled post-hoc, never pooled.
9. Token-test sidedness. The preregistration named an exact sign test for the directional cost claim without stating its sidedness. The analysis used the two-sided test, and those p-values entered Holm; support additionally requires the estimate to lie in the claimed direction. A one-sided test in the claimed direction would not change either conclusion.
10. Cost reporting corrected after review. An earlier version of Appendix B.8 reported the runner's running total, which already counts kept reserves, as settled usage, and added kept reserves to it again. B.8 now separates metered charges from kept reserves. The earlier all-run total also omitted the canary and development ledgers kept in Lorien's workspace; the reconciliation file now lists every ledger in both. No ceiling, stop or result depended on the earlier figures.
11. Added after submission review, before the deadline: four overlapping-transaction schedules on the scratch branch (`tools/race_schedules.py`, 9 of 9 checks), the V8 comparison for the false-quarantine trigger (from the existing diagnostics, no new runs), and a related-work comparison with six recent papers. No held-out number changed.

B.10 Follow-up cohorts and structural tests, tables

Follow-up cohorts (post-hoc): completion, tokens, slots and cost.

Both cohorts were frozen and run after the preregistered set had been analyzed and this report drafted, to test the two readings a reviewer would challenge first: new seeds, new freezes, separate ledgers, never pooled with the held-out set, same gate, scorer, budget and caps.

Does the gemma-31 gap close when the lookup is required? The frozen rule let the model "decide directly if the supplied information suffices" and gemma-4-31b-it took the lookup in 13 of 120 offers; the follow-up requires the lookup as the first reply. Under that rule gemma-4-31b-it took the lookup in 120 of 120 offers and completed 120 of 120 same-number cases in the lookup arm against 119 of 120 with preloaded lineage (V6: compact minus lookup -0.017, Tango 95% [-0.089, +0.045]; V11: +0.000, [-0.060, +0.060]). On new instances this supports the optional wording as the cause of the 51-case gap; it does not prove it was the only cause. Cost moved the other way: with the lookup required, the lookup arm spent a Hodges-Lehmann 724 tokens more per settled pair than compact over 119 pairs, so preloading is the cheaper way to deliver the same records.

Does the marginal DeepSeek V6 claim replicate? The preregistered V6 claim held at one-sided p 0.043. An independent cohort of 60 new V6 instances: compact 60/60, lookup arm 51/60 (lookup taken 47/60), compact minus lookup +0.150, Tango 95% [+0.081, +0.261], non-inferiority at -0.10 holds (one-sided p 2.23e-05); the lookup arm spent a Hodges-Lehmann 1971 tokens more per settled pair than compact. Of the lookup arm's 9 misses, 3 are among the 7 slots where the model decided without taking the lookup, 0 took the lookup and still missed, and 6 are provider errors. The same model at temperature 0 took the lookup in 59 of 60 offers on the preregistered V6 instances and in 47 of 60 here, so whether an offered lookup is taken varies with the instance set as well as the model, and preloading does not depend on it. The two DeepSeek cohorts are reported side by side and not pooled.

model	lookup rule	family	compact	lookup arm	lookup taken	delta (compact minus lookup)	Tango 95%	NI at -0.10
gemma-4-31b-it	required	V6	59/60	60/60	60/60	-0.017	[-0.089, +0.045]	holds (p 0.0157)
gemma-4-31b-it	required	V11	60/60	60/60	60/60	+0.000	[-0.060, +0.060]	holds (p 0.00491)
deepseek-v4-flash	optional (as frozen)	V6	60/60	51/60	47/60	+0.150	[+0.081, +0.261]	holds (p 2.23e-05)

model	lookup rule	settled pairs	Hodges-Lehmann, lookup minus compact tokens	exact two-sided sign test p
gemma-4-31b-it	required	119	+724	3.01e-36
deepseek-v4-flash	optional	57	+1971	1.39e-17

cohort	registered	complete	errors or invalid	unsafe proposals	gate rejections	lineage-invalid commits	metered	reserves kept	ceiling	complete run
v2_gemma431bit_mandlookup	240	239	1	0	0	0	0.0518	0.0251	1.0	yes
v2_deepseekv4fl_repV6	120	114	6	4	3	0	0.0306	0.1422	1.5	yes

Second surface template (post-hoc): completion, lookup use, gate outcomes.

model	family	registered per arm	not yet run	compact complete	lookup arm complete	lookup taken	delta (compact minus lookup, registered denominator)	Tango 95%	NI at -0.10	unsafe proposals	lineage-invalid commits
gemma-4-31b-it	V6	30	0	30/30	15/30	0/30	+0.500	[+0.330, +0.668]	holds (p 3.87e-06)	15	0
gemma-4-31b-it	V11	30	0	30/30	16/30	2/30	+0.467	[+0.300, +0.639]	holds (p 6.93e-06)	14	0
deepseek-v4-flash	V6	30	0	30/30	24/30	24/30	+0.200	[+0.064, +0.373]	holds (p 0.000783)	2	0
deepseek-v4-flash	V11	30	0	30/30	30/30	30/30	+0.000	[-0.114, +0.114]	holds (p 0.0339)	0	0

cohort	registered	complete	unsafe proposals	gate rejections	lineage-invalid commits	metered	ceiling	complete run
v3_gemma431bit_incidents	120	120	29	29	0	0.0199	0.6	yes
v3_deepseekv4fl_incidents	120	116	2	2	0	0.0238	1.5	yes

Containment battery, naive board versus bound board. The same six attacks (spoof a sender, read a foreign thread, post under a new name, read the operator audit, edit another agent's message, delete messages) fired by the intruder login against both schemas. On the bound board three are refused outright, one returns zero rows, and two are accepted as statements with no effect because the trigger overwrites the claimed sender; only those two reach the audit.

effect of the six scripted attacks	naive shared board	identity bound below the agent
spoofed identities that landed	2	0
board fooled by a spoofed sender	yes	no
board fooled by a rename	yes	no
rows read from a thread the intruder is not party to	4	0
another agent's message tampered	yes	no
messages deleted by the intruder	3	0
spoof attempts recorded in the operator audit	0	2
audit readable by the intruder	no	no

effect of the six scripted attacks	naive shared board	identity bound below the agent
honest three-agent chain completed	yes	yes

Identity under copying. Ten copies of one agent, each claiming a different name, submitting through one login. On the naive board a name is an identity, so ten copies are ten agents, the shape of the motivating incident. On the bound intake the trigger binds all ten to the one login, keeps the ten claimed names as evidence, and a single grant revocation silences all ten at once; revoking the login refused new connections within seconds.

ten copies of one agent, ten claimed names, one login	naive board	bound intake
identities recorded	10	1
claimed names kept as evidence	not applicable (name is identity)	10
submissions that land after one grant revocation	not applicable (no grants)	0 of 10

Blast radius of one compromised source. One root, twenty agent drafts built on it, twenty summaries of those, twenty summaries of the summaries (sixty descendants, three deep), plus twenty artifacts on an independent root. After the root is adjudicated the gate's closure walk blocks all sixty at every depth and still approves all twenty unrelated artifacts, median decision 0.448 s over HTTPS. A monitor that checks only direct dependencies catches the twenty at depth one and passes forty stale artifacts; a monitor with no lineage passes all sixty.

after the root is adjudicated	descendants blocked (of 60, three deep)	unrelated approved (of 20)
gate, full closure walk	60 (depth 1: 20, depth 2: 20, depth 3: 20)	20
direct-dependency check only	20	20
no lineage	0	20

Audit extension. Only two of the six attacks reached the audit: three were refused by the privilege layer before any trigger ran and a foreign-thread read returned zero rows silently. The migration accepts the statement at the privilege layer, denies every effect with row security, and records the attempt: statement-level triggers fire on zero-row updates and deletes, and the read policies call a function that writes one audit row per transaction with the statement text before returning false. After it all six attacks appear in the audit (6 of 6, from 2), the victim thread is unchanged (tampered rows 0), an honest agent's own-thread query records nothing, and an honest agent's unfiltered scan of the whole table records one denied read, a true description of that statement. Coverage is of committed statements: a denied attempt wrapped in a transaction the attacker rolls back leaves no row (committed denied update recorded 1, rolled back recorded 0, rolled-back audit read recorded 0, own-row query false positives 0; `runs/audit_rollback_latest.json`), and row-security logging fires only when a protected row is evaluated. Statements against tables an agent holds no privilege on remain invisible. A trusted gateway that owns transaction boundaries is the fix for both.

attack by the intruder login	effect, before and after	in the operator audit before	in the operator audit after
spoof another agent's name on a post	none (sender overwritten)	yes	yes
post under a brand-new name	none (sender overwritten)	yes	yes
read a thread it is not party to	none (zero rows)	no	yes
read the operator audit	none	no	yes
edit another agent's message	none	no	yes
delete messages	none	no	yes

Appendix C. Code and Data

Built before the sprint, declared per the rules. The Hive substrate (two AIs working through one shared, provenance-tagged memory with trigger-guarded authorship; April 2026, on the CAMA architecture) and the test Hive for the containment battery (2 November 2026: the `hive_messages`, receipts and audit tables, their triggers and row-level policies, the four agent roles, the HTTPS SQL client, eleven static tests). Both are marked pre-existing in the README, which carries a component-by-component table.

Built during the sprint, 6 to 8 November. Everything in the `exp` schema (sealed creation, provenance authorization, invalidation authorities, the fence and the publication gate), the naive control schema and the six-attack battery, Lorien's reference specification, acceptance driver, delivery recorder, scorer and controls, the pilot runner, freeze generator, open-model adapter, preregistration, analysis, structural tests, the audit migration, and every run directory.

Reproducibility. The gate is frozen at commit `d2df880` and was rebuilt from the committed migration on a fresh branch with all 19 checks passing (evidence under `runs/acceptance/`). Each cohort is generated from a seed; its manifest, prompt, code and gate hashes are written to `FREEZE.json` before execution and the runner refuses any mismatch. Every model call keeps its raw request and response; secrets are never committed. `REPRODUCE.md` gives the exact commands.

Code and data. Repository `SwarmHive` at github.com/LoriensLibrary/SwarmHive. Every cohort's traces, ledgers, raw requests and responses, scored outputs, freeze records and analysis outputs are committed under `runs/`, `holdout/` and `report/`. Synthetic data only. Info-hazard note: the containment battery holds generic attacks on a shared record, run only against synthetic rows in a disposable test database.

Appendix D. One inspectable trace

The same-number case from the open-model pilot, run `pilot_9268a9`, current and compact side by side. Every step is in the committed run directory: dispatch receipts with request and per-body hashes, raw model text, the gate's reply, the committed approval row.

1. The researcher is dispatched with `count=12`; its reply is sealed as source v1, a root with no inputs.
2. The writer receives v1; its draft is sealed as a derivative whose only recorded input is v1. Body `{"units": 12, ...}`.
3. The operator adjudicates v1 and seals a replacement, v2, with the same figure. A fresh writer call delivered only v2 is sealed as a second draft. Two drafts with identical numbers and opaque identifiers sit in the queue.
4. Current arm: both draft bodies, the v2 body and the correction notice naming v1 superseded, no lineage. It approves the first draft, result `{"units": 12}`, evidence `[v2]`. The number is right. The artifact is stale.
5. Gate: in a fenced read-committed transaction the closure walk finds v1 adjudicated and replies `rejected: closure member <id>/1 invalidated (epoch 1)`. A separate committed-state query confirms, so the event is written `db_verified: true` with closure `[v1]`.
6. Compact arm: the same request plus one field, `history_metadata`, listing each artifact's version, author, kind, invalidation status and recorded inputs, no bodies. It approves the second draft, evidence `[that draft, v2]`. Closure `[v2]`, approval committed, the structured result and direct inputs taken from the provenance table, not from the model's text.

The scorer's original pass read step 4 as a correct proposal: the stated number was right and the cited source was current. A supplemental rescore that reconstructs the selected artifact version from the recorded selection flags it as unsafe. Both scores are preserved. The gate caught it either way.

Appendix E. LLM Usage Statement

The author worked with two AI systems throughout and discloses both. Aelen, a Claude model running in Claude Code, wrote most of the code in the repository under the author's direction, ran every evaluation under the author's explicit spend authorization, and drafted this report from the committed run data; every number in the report is produced by scripts in the repository (`tools/analysis.py`, `tools/results_tables.py`, `tools/write_section5.py`, `tools/v2_followup.py`, `tools/v3_domain.py`, `tools/structural_results.py`, `tools/arm_outcomes.py`, `tools/make_figures.py`) from the committed traces and ledgers, not typed by a model. Lorien, an OpenAI Codex model running in a separate workspace, wrote the independent reference specification, the acceptance driver, the delivery recorder and the scorer, and reviewed the design, the gate and the evaluation protocol adversarially before the held-out runs; its two 7 November reviews are committed under `report/`. It did not review the final text of this

report. The author set the research question, chose the tracks, made every design decision that is recorded as hers in the repository, authorized every paid run, reviewed every claim against the data, and edited the text. Claims and results were verified against the committed evidence before submission; the deviations from the preregistration, the post-hoc additions and the one post-results code fix are disclosed in Appendix B.9.