

# ActiveJwk

No description

```
type ActiveJwk {  
  iss: String!  
  kid: String!  
  kty: String!  
  e: String!  
  n: String!  
  alg: String!  
  epoch: Epoch  
}
```

## Fields

`ActiveJwk.iss` • `String!` **non-null** **scalar**

The string (Issuing Authority) that identifies the OIDC provider.

`ActiveJwk.kid` • `String!` **non-null** **scalar**

The string (Key ID) that identifies the JWK among a set of JWKs, (RFC 7517, Section 4.5).

`ActiveJwk.kty` • `String!` **non-null** **scalar**

The JWK key type parameter, (RFC 7517, Section 4.1).

`ActiveJwk.e` • `String!` **non-null** **scalar**

The JWK RSA public exponent, (RFC 7517, Section 9.3).

`ActiveJwk.n` • `String!` **non-null** **scalar**

The JWK RSA modulus, (RFC 7517, Section 9.3).

`ActiveJwk.alg` • `String!` **non-null** **scalar**

The JWK algorithm parameter, (RFC 7517, Section 4.4).

`ActiveJwk.epoch` • `Epoch` **object**

The most recent epoch in which the JWK was validated.

Member Of

ActiveJwkConnection object . ActiveJwkEdge object

 [Edit this page](#)

