

# **MCD4710**

Introduction to algorithms  
and programming

## **Lecture 10**

Invariants

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

WARNING

This material has been reproduced and communicated to you by or on behalf of Monash University pursuant to Part VB of the Copyright Act 1968 (the Act).

The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act.

Do not remove this notice.

# Overview

- Formulate **assertions** about program states
- Demonstrate that truth of certain assertions is unchanged (**invariant**) by program (specifically by a loop)
- Relate invariants to computational problem to demonstrate **correctness** of algorithm

# Programs with simple flow are easy to recognise as correct

```
def number_of_days(month, year):  
    if month == 2:  
        if is_leap_year(year):  
            return 29  
        else:  
            return 28  
    elif month in THIRTY_DAYS_MONTH:  
        return 30  
    else:  
        return 31
```

```
def valid_date(day, month, year):  
    if month not in VALID_MONTHS:  
        return False  
    elif day not in range(1, number_of_days(month, year)):  
        return False  
    else:  
        return True
```

# ...but is this really computing a spanning tree?

```
def spanning_tree(graph):  
    """Input : adjacency matrix of graph  
    Output: adj. mat. of spanning tree of graph"""  
    n = len(graph)  
    tree = empty_graph(n)  
    conn = {0}  
    while len(conn) < n:  
        found = False  
        for i in conn:  
            for j in range(n):  
                if j not in conn and graph[i][j]==1:  
                    tree[i][j] = 1  
                    tree[j][i] = 1  
                    conn = conn.add(j)  
                    found = True  
                    break  
        if found:  
            break  
    return tree
```

# Decomposition helps but loops with *re-assignments/mutation* remain tricky

```
def extension(c, g):  
    """I: connec. vertices (c), graph  
    (g)  
    O: extension edge (i, j)"""  
    n = len(g)  
    for i in vertices:  
        for j in range(n):  
            if j not in c and g[i][j]:  
                return i, j  
  
def spanning_tree(graph):  
    """input: graph given as adj. matrix  
    output: spanning tree of graph"""  
    tree = empty_graph(len(graph))  
    conn = {0}  
    while len(conn) < n:  
        i, j = extension(conn, graph)  
        tree[i][j], tree[j][i] = 1, 1  
        conn = conn.add{j}  
    return tree
```

values behind  
names change  
all the time

# Outline

- Assertions and invariants
- Analysing Insertion Sort
- Analysing Min Index Selection
- Analysing Prim's Algorithm

# Cutting the Chocolate Block



A chocolate block is divided into squares by horizontal and vertical grooves. The object is to cut the chocolate block into individual pieces.

Assume each cut is made on a **single piece** along a groove. How many cuts are needed?



# How many cuts does it take to divide the following block into squares?



- A. 8
- B. 3
- C. 24
- D. 23
- E. None of the above


1. Visit <https://flux.qa>
2. Log in using your Authcate details (not required if you're already logged in to Monash)
3. Touch the + symbol and enter the code: UF7BD9
4. Answer questions when they pop up.

How many cuts does it take to divide a 100 X 50 block of chocolate?


- A. 5000
- B. 4999
- C. 4900
- D. 4950
- E. None of the above

1. Visit <https://flux.qa>
2. Log in using your Authcate details (not required if you're already logged in to Monash)
3. Touch the + symbol and enter the code: UF7BD9
4. Answer questions when they pop up.


# What is the relationship between cuts and number of pieces?




# What is the relationship between cuts and number of pieces?




1 cut  
2 pieces



# What is the relationship between cuts and number of pieces?



2 cuts  
3 pieces



**Statement**


***“number of pieces equals number of cuts plus one”***

...holds throughout cutting process

# Let's bring this concept into the world of programs

```
cut = ... #some arbitrary cutting strategy
pieces = [(m, n)]
num_cuts = 0
while len(pieces) < n*m:
    cut(pieces)
    num_cuts += 1
```

Example cutting strategy  
(we know it doesn't matter)




```
def cut_first_possible(pieces):
    for i in range(pieces):
        m, n = pieces[i]
        m, n = max(m, n), min(m, n)
        if m > 1:
            pieces.pop(i)
            pieces.append((m-1, n), (1, n))
            break
```

# Let's analyse this program by stating *assertions*

```
cut = ... #some arbitrary cutting strategy
pieces = [(m, n)]
num_cuts = 0
while len(pieces) < n*m:
    cut(pieces)
    num_cuts += 1
```

<https://goo.gl/Mkvzjm>

An **assertion** is a logical statement on a *program (execution) state*.



# Let's analyse this program by stating *assertions*


```

cut = ... #some arbitrary cutting strategy
pieces = [(m, n)]
num_cuts = 0
#PRC: len(pieces)==num_cuts+1
while len(pieces)<n*m:
    cut(pieces)
    num_cuts += 1

```

Example:  
loop precondition

An **assertion** is a logical statement on a *program (execution) state*.






# What happens during the loop?

```
cut = ... #some arbitrary cutting strategy
pieces = [(m, n)]
num_cuts = 0
#PRC: len(pieces)==num_cuts+1
while len(pieces)<n*m:
    #len(pieces)==num_cuts+1
    cut(pieces)
    num_cuts += 1
```

An **assertion** is a logical statement on a *program (execution) state*.




# What happens during the loop?

```

cut = ... #some arbitrary cutting strategy
pieces = [(m, n)]
num_cuts = 0
#PRC: len(pieces)==num_cuts+1
while len(pieces)<n*m:
    #len(pieces)==num_cuts+1
    cut(pieces)
    num_cuts += 1

```

after this step, assertion  
is (temporarily) violated




An **assertion** is a logical statement on a *program (execution) state*.

Instruction pointer

```

10 cut = cut_first_best
11 m, n = 6, 4
12 pieces = [(m, n)]
13 num_cuts = 0
→ 14 while len(pieces)<n*m:
15     cut(pieces)
→ 16     num_cuts += 1

```




# What happens during the loop?


```

cut = ... #some arbitrary cutting strategy
pieces = [(m, n)]
num_cuts = 0
#PRC: len(pieces)==num_cuts+1
while len(pieces)<n*m:
    #len(pieces)==num_cuts+1
    cut(pieces)
    num_cuts += 1 ← after this step
                    it is restored

```



An **assertion** is a logical statement on a *program (execution) state*.




# What happens during the loop?

```

cut = ... #some arbitrary cutting strategy
pieces = [(m, n)]
num_cuts = 0
#PRC: len(pieces)==num_cuts+1
while len(pieces)<n*m:
    #len(pieces)==num cuts+1
    cut(pieces)
    num cuts += 1
    #len(pieces)==num cuts+1

```

*maintained by  
loop body*




An **assertion** is a logical statement on a *program (execution) state*.

Instruction pointer

```


10 cut = cut_first_best
11 m, n = 6, 4
12 pieces = [(m, n)]
13 num_cuts = 0
→ 14 while len(pieces)<n*m:
15     cut(pieces)
→ 16     num_cuts += 1

```



# Loop invariant is an assertion maintained by loop body

```
cut = ... #some arbitrary cutting strategy
pieces = [(m, n)]
num_cuts = 0
#PRC: len(pieces)==num_cuts+1
while len(pieces)<n*m:
    #INV: len(pieces)==num_cuts+1
    cut(pieces)
    num_cuts += 1
    #INV: len(pieces)==num_cuts+1
```




An **assertion** is a logical statement on a *program (execution) state*.

A **loop invariant** is an assertion inside a loop that is true every time it is reached by the program execution.

# What are useful loop invariants?

```
cut = ... #some arbitrary cutting strategy
pieces = [(m, n)]
num_cuts = 0
#PRC: len(pieces)==num_cuts+1
while len(pieces)<n*m:
    cut(pieces)
    num_cuts += 1
    #INV: len(pieces)==num_cuts+1
```




An **assertion** is a logical statement on a *program (execution) state*.

A **loop invariant** is an assertion inside a loop that is true every time it is reached by the program execution.

We want invariants at *end of loop* that together with **loop exit condition** “turn into” desired **post-condition**.

# What are useful loop invariants?

```
cut = ... #some arbitrary cutting strategy
pieces = [(m, n)]
num_cuts = 0
#PRC: len(pieces)==num_cuts+1
while len(pieces)<n*m:
    cut(pieces)
    num_cuts += 1
    #INV: len(pieces)==num_cuts+1
    #EXC: len(pieces) == n*m
```




An **assertion** is a logical statement on a *program (execution) state*.

A **loop invariant** is an assertion inside a loop that is true every time it is reached by the program execution.

We want invariants at end of loop that together with **loop exit condition** “turn into” desired **post-condition**.

# What are useful loop invariants?

```
cut = ... #some arbitrary cutting strategy
pieces = [(m, n)]
num_cuts = 0
#PRC: len(pieces)==num_cuts+1
while len(pieces)<n*m:
    cut(pieces)
    num_cuts += 1
    #INV: len(pieces)==num_cuts+1
    #EXC: len(pieces) == n*m
    #POC: num cuts == n*m - 1
```




An **assertion** is a logical statement on a *program (execution) state*.

A **loop invariant** is an assertion inside a loop that is true every time it is reached by the program execution.

We want invariants at end of loop that together with **loop exit condition** “turn into” desired **post-condition**.



# What are useful loop invariants?



Source: [Furia et al., 2014]

We are interested in loop invariants that together with **loop exit condition** “turn into” desired **post-condition**.

[Furia et al., 2014: Loop invariants: analysis, classification, and examples ]

# Outline

- Assertions and invariants
- **Analysing Insertion Sort**
- Analysing Min Index Selection
- Analysing Prim's Algorithm

# Does Insertion Sort always result in a sorted list?

```
def insert(i, lst):  
    """accepts: int i and list lst of length n>i>0  
              of comp. elements with lst[:i] is sorted  
              postcon: lst[:i+1] is sorted"""  
    temp = lst[i]  
    j = i-1  
    while j >= 0 and lst[j] > temp:  
        lst[j+1] = lst[j]  
        j = j - 1  
    lst[j+1] = temp
```

```
def insertion_sort(lst):  
    """accepts: list lst of length n of comp. elements  
              postcon: lst has same elements as on call but  
                      is sorted"""  
    for i in range(1, len(lst)):  
        insert(i, lst)
```

# Situation at the start of execution

lst

?	?	?	?	...													...	?
0	1	2	3	...													...	n-1

```
def insertion_sort(lst):  
    """accepts: list lst of length n of comp. elements  
       postcon: lst has same elements as on call but  
                is sorted                                     """  
    for i in range(1, len(lst)):  
        insert(i, lst)
```

# Loop initialisation

lst

?	?	?	?	...												...	?
0	i=1	2	3	...												...	n-1

```
def insertion_sort(lst):  
    """accepts: list lst of length n of comp. elements  
       postcon: lst has same elements as on call but  
                is sorted                                     """  
    for i in range(1, len(lst)):  
        insert(i, lst)
```

# What is true at this point?

lst

?	?	?	?	...													...	?
0	i=1	2	3	...													...	n-1

```
def insertion_sort(lst):  
    """accepts: list lst of length n of comp. elements  
       postcon: lst has same elements as on call but  
                is sorted                                     """  
    for i in range(1, len(lst)):  
        # lst[:i] is sorted  
        insert(i, lst)
```

# Insertion procedure extends sorted range by one

lst

?	?	?	?	...													...	?
0	i=1	2	3	...													...	n-1

`insert(1, lst)`



?	?	?	?	...													...	?
0	i=1	2	3	...													...	n-1

```
def insertion_sort(lst):
    """accepts: list lst of length n of comp. elements
       postcon: lst has same elements as on call but
                is sorted                                     """
    for i in range(1, len(lst)):
        # lst[:i] is sorted
        insert(i, lst)
```

# Insertion procedure extends sorted range by one

lst

?	?	?	?	...													...	?
0	i=1	2	3	...													...	n-1

`insert(1, lst)`



?	?	?	?	...													...	?
0	i=1	2	3	...													...	n-1

```
def insertion_sort(lst):
    """accepts: list lst of length n of comp. elements
       postcon: lst has same elements as on call but
                is sorted"""
    for i in range(1, len(lst)):
        # lst[:1] is sorted
        insert(i, lst)
        # lst[:2] is sorted
```

Hold in first iteration  
(and further), but not enough  
do demonstrate post  
condition

Idea: generalise assertions so that they become stronger every iteration!



# These general assertions seem much more useful

lst

?	?	?	?	...													...	?
0	i=1	2	3	...													...	n-1

`insert(1, lst)`



?	?	?	?	...													...	?
0	i=1	2	3	...													...	n-1

```
def insertion_sort(lst):
    """accepts: list lst of length n of comp. elements
       postcon: lst has same elements as on call but
                is sorted                                     """
    for i in range(1, len(lst)):
        # lst[:i] is sorted
        insert(i, lst)
        # lst[:i+1] is sorted
```

# But are they preserved by general loop iteration?

lst

?	?	?	?	...													...	?
0	i=1	2	3	...													...	n-1

```
def insertion_sort(lst):  
    """accepts: list lst of length n of comp. elements  
       postcon: lst has same elements as on call but  
                is sorted                                     """  
    for i in range(1, len(lst)):  
        # lst[:i] sorted  
        insert(i, lst)  
        # lst[:i+1] sorted
```


# Let's assume first assertion is true

lst

?	?	?	?	...					...	?	?	...					...	?
0	1	2	3	...					...	i-1	i	...					...	n-1

```
def insertion_sort(lst):  
    """accepts: list lst of length n of comp. elements  
       postcon: lst has same elements as on call but  
                is sorted                                     """  
    for i in range(1, len(lst)):  
        # lst[:i] sorted  
        insert(i, lst)  
        # lst[:i+1] sorted
```

# Then loop body ensures second assertion




`insert(i, lst)`




```
def insertion_sort(lst):
    """accepts: list lst of length n of comp. elements
       postcon: lst has same elements as on call but
                is sorted"""
    for i in range(1, len(lst)):
        # lst[:i] sorted
        insert(i, lst)
        # lst[:i+1] sorted
```

# Which in turn implies first assertion in next iteration!




```
def insertion_sort(lst):
    """accepts: list lst of length n of comp. elements
       postcon: lst has same elements as on call but
                is sorted"""
    for i in range(1, len(lst)):
        # lst[:i] sorted
        insert(i, lst)
        # lst[:i+1] sorted
```

# Thus these assertions are loop invariants!




```
def insertion_sort(lst):
    """accepts: list lst of length n of comp. elements
       postcon: lst has same elements as on call but
                is sorted"""
    for i in range(1, len(lst)):
        #I: lst[:i] sorted
        insert(i, lst)
        #I': lst[:i+1] sorted
```

# What happens at end of loop?



```
def insertion_sort(lst):
    """accepts: list lst of length n of comp. elements
       postcon: lst has same elements as on call but
                is sorted"""
    for i in range(1, len(lst)):
        #I: lst[:i] sorted
        insert(i, lst)
        #I': lst[:i+1] sorted
    #EXC: i = n-1
```

# Loop exit condition and invariant imply desired post condition



```
def insertion_sort(lst):
    """accepts: list lst of length n of comp. elements
       postcon: lst has same elements as on call but
                is sorted"""
    for i in range(1, len(lst)):
        #I: lst[i] sorted
        insert(i, lst)
        #I': lst[i+1] sorted
    #EXC: i = n-1
    #POC: lst[:n] sorted
```



# Outline

- Assertions and invariants
- Analysing Insertion Sort
- **Analysing Min Index Selection**
- Analysing Prim's Algorithm

# Recap: what is min\_index trying to do (formally)?

```
def min_index(lst):  
    """accepts: list of length n>0 of comp. elements  
       returns: ?  
    """  
  
    k = 0  
    for i in range(1, len(lst)):  
        if lst[i] < lst[k]:  
            k = i  
    return k
```

1. Visit <https://flux.qa>
2. Log in using your Authcate details (not required if you're already logged in to Monash)
3. Touch the + symbol and enter the code: UF7BD9
4. Answer questions when they pop up.

# Recap: what is min\_index trying to do (formally)?

```
def min_index(lst):
    """accepts: list of length n>0 of comp. elements
       returns: index k in range(n) such that
               for all j in range(n), lst[k]<=lst[j]
    """
    k = 0
    for i in range(1, len(lst)):
        if lst[i] < lst[k]:
            k = i
    return k
```



# Does min\_index function always yield index of minimum value?

```
def min_index(lst):
    """accepts: list of length n>0 of comp. elements
       returns: index k in range(n) such that
               for all j in range(n), lst[k]<=lst[j]"""
    k = 0
    for i in range(1, len(lst)):
        if lst[i] < lst[k]:
            k = i
    return k
```

1st

[illegible]

# Situation before reaching loop statement

```
def min_index(lst):
    """accepts: list of length n>0 of comp. elements
       returns: index k in range(n) such that
                for all j in range(n), lst[k]<=lst[j]"""
    k = 0
    for i in range(1, len(lst)):
        if lst[i] < lst[k]:
            k = i
    return k
```

1st

[illegible]

# First iteration of loop

```
def min_index(lst):
    """accepts: list of length n>0 of comp. elements
       returns: index k in range(n) such that
               for all j in range(n), lst[k]<=lst[j]"""
    k = 0
    for i in range(1, len(lst)):
        if lst[i] < lst[k]:
            k = i
    return k
```

1st

[illegible]

# What is true at this point?

```
def min_index(lst):
    """accepts: list of length n>0 of comp. elements
       returns: index k in range(n) such that
                for all j in range(n), lst[k]<=lst[j]"""
    k = 0
    for i in range(1, len(lst)):
        # ?
        if lst[i] < lst[k]:
            k = i
    return k
```

1st

[illegible]

# Effect of conditional statement

```
def min_index(lst):
    """accepts: list of length n>0 of comp. elements
       returns: index k in range(n) such that
                for all j in range(n), lst[k]<=lst[j]"""
    k = 0
    for i in range(1, len(lst)):
        # ?
        if lst[i] < lst[k]:
            k = i
    return k
```

1st

[illegible]

```
if lst[1] < lst[k]:  
    k = 1
```



## 1<sup>st</sup> scenario

[illegible]



# Effect of conditional statement

```
def min_index(lst):
    """accepts: list of length n>0 of comp. elements
       returns: index k in range(n) such that
                for all j in range(n), lst[k]<=lst[j]"""
    k = 0
    for i in range(1, len(lst)):
        # ?
        if lst[i] < lst[k]:
            k = i
    return k
```

1st

[illegible]

```
if lst[1] < lst[k]:
    k = 1
```



## 2<sup>nd</sup> scenario

[illegible]

1st

```
if lst[1] < lst[k]:  
    k = 1
```

[illegible]

This suggests general pattern

```
def min_index(lst):
    """accepts: list of length n>0 of comp. elements
       returns: index k in range(n) such that
                for all j in range(n), lst[k]<=lst[j]"""
    k = 0
    for i in range(1, len(lst)):
        # lst[k] <= lst[0]
        if lst[i] < lst[k]:
            k = i
        # lst[k] <= lst[0] and lst[k]<=lst[1]
    return k
```

1st

[illegible]

```
if lst[1] < lst[k]:  
    k = 1
```



## 2<sup>nd</sup> scenario

[illegible]

This suggests general pattern

```
def min_index(lst):
    """accepts: list of length n>0 of comp. elements
       returns: index k in range(n) such that
               for all j in range(n), lst[k]<=lst[j]"""
    k = 0
    for i in range(1, len(lst)):
        # for all j in range(i): lst[k]<=lst[j]
        if lst[i] < lst[k]:
            k = i
        # for all j in range(i+1): lst[k]<=lst[j]
    return k
```

1st

[illegible]

```
if lst[1] < lst[k]:  
    k = 1
```



## 2<sup>nd</sup> scenario

[illegible]

# Let's consider general loop iteration


```
def min_index(lst):  
    """accepts: list of length n>0 of comp. elements  
    returns: index k in range(n) such that  
           for all j in range(n), lst[k]<=lst[j]"""  
    k = 0  
    for i in range(1, len(lst)):  
        # for all j in range(i): lst[k]<=lst[j]  
        if lst[i] < lst[k]:  
            k = i  
        # for all j in range(i+1): lst[k]<=lst[j]  
    return k
```

lst

?	?	?	...							...	?	...					...	?
0	1	2	...							...	i	...					...	n-1


# Assume first assertion is true

```
def min_index(lst):
    """accepts: list of length n>0 of comp. elements
       returns: index k in range(n) such that
               for all j in range(n), lst[k]<=lst[j]"""
    k = 0
    for i in range(1, len(lst)):
        # for all j in range(i): lst[k]<=lst[j]
        if lst[i] < lst[k]:
            k = i
        # for all j in range(i+1): lst[k]<=lst[j]
    return k
```




# Effect of conditional statement

```
def min_index(lst):
    """accepts: list of length n>0 of comp. elements
       returns: index k in range(n) such that
               for all j in range(n), lst[k]<=lst[j]"""
    k = 0
    for i in range(1, len(lst)):
        # for all j in range(i): lst[k]<=lst[j]
        if lst[i] < lst[k]: k = i
        # for all j in range(i+1): lst[k]<=lst[j]
    return k
```



# Conditional statement ensures second assertion


```
def min_index(lst):
    """accepts: list of length n>0 of comp. elements
    returns: index k in range(n) such that
           for all j in range(n), lst[k]<=lst[j]"""
    k = 0
    for i in range(1, len(lst)):
        # for all j in range(i): lst[k]<=lst[j]
        if lst[i] < lst[k]: k = i
        # for all j in range(i+1): lst[k]<=lst[j]
    return k
```






# Which in turn assures first assertion in next iteration

```
def min_index(lst):
    """accepts: list of length n>0 of comp. elements
       returns: index k in range(n) such that
               for all j in range(n), lst[k]<=lst[j]"""
    k = 0
    for i in range(1, len(lst)):
        #I: for all j in range(i): lst[k]<=lst[j]
        if lst[i] < lst[k]: k = i
        #I': for all j in range(i+1): lst[k]<=lst[j]
    return k
```




# What happens at the end of the loop?

```
def min_index(lst):
    """accepts: list of length n>0 of comp. elements
       returns: index k in range(n) such that
               for all j in range(n), lst[k]<=lst[j]"""
    k = 0
    for i in range(1, len(lst)):
        #I: for all j in range(i): lst[k]<=lst[j]
        if lst[i] < lst[k]: k = i
        #I': for all j in range(i+1): lst[k]<=lst[j]
    #EXC: i = n-1
    return k
```



# Again loop exit condition and invariants imply desired post cond.

```
def min_index(lst):
    """accepts: list of length n>0 of comp. elements
       returns: index k in range(n) such that
               for all j in range(n), lst[k]<=lst[j]"""
    k = 0
    for i in range(1, len(lst)):
        #I: for all j in range(i): lst[k]<=lst[j]
        if lst[i] < lst[k]: k = i
        #I': for all j in range(i+1): lst[k]<=lst[j]
    #EXC: i = n-1,
    #POC: for j in range(n): lst[k]<=lst[j]
    return k
```



# Selection Sort – The invariants...

```
def selectionSort(aList):  
    for k in range(len(aList)-1):  
        #INVARIANT: aList[:k] is sorted and represents  
        #the k smallest elements in the whole list  
        minPos = k  
        for current in range(k+1, len(aList)): # Find minimum index  
            if aList[current] < aList[minPos]:  
                minPos = current # Update new minimum index  
        aList[minPos], aList[k] = aList[k], aList[minPos] # Swap  
        #INVARIANT: aList[:k+1] is sorted and represents  
        #the k+1 smallest elements in the whole list
```

# Loop invariants

- Provide a useful invariant in terms of  $k$ .

```
k = 0
while k < len(my_list):
    #my_list[:k] will be replaced with a 1
    my_list[k] = 1
    k += 1
    #my_list[:k] will be replaced with a 1
```

Still  $k$  because  
unlike in the FOR  
loop,  $k$  is already  
changed in the  
While loop

- at the  $k^{\text{th}}$  iteration, the first  $k$  elements of the list have been replaced with a 1 i.e. `my_list[:k]` will be replaced with a 1

# Loop invariants

- Provide a useful invariant in terms of  $k$ .

```
ct = [0] * len(aList)
for k in range(len(aList)):
    for j in range(k):
        if aList[k] == aList[j]:
            ct[k] += 1
```

- After the  $k^{\text{th}}$  iteration,  $\text{ct}[k]$  holds the count of the number of times  $\text{aList}[k]$  occurred in  $\text{aList}[0:k]$

# Loop invariants

- Provide a useful invariant in terms of  $k$ .

```
ct = [0] * len(aList)
for k in range(len(aList)) :
    #ct[k] holds the value of 0
    for j in range(k) :
        if aList[k] == aList[j] :
            ct[k] += 1
    #ct[k] holds the count of the number of times aList[k] occurred in aList[0:k]
```

- After the  $k^{\text{th}}$  iteration,  $\text{ct}[k]$  holds the count of the number of times  $\text{aList}[k]$  occurred in  $\text{aList}[0:k]$

# Outline

- Assertions and invariants
- Analysing Insertion Sort
- Analysing Min Index Selection
- **Analysing Prim's Algorithm**




# Prim's algorithm: does it always produce a spanning tree?

```
def extension(con, g):  
    """input: vertices con connected in  
    g  
    output: edge (i,j) of g with i in  
    con and j not in con"""  
    for i in con:  
        for j in range(len(g)):  
            if j not in con and g[i][j]:  
                return i, j  
  
def spanning_tree(graph):  
    """input: graph given as adj. matrix  
    output: spanning tree of graph"""  
    tree = empty_graph(len(graph))  
    con = {0}  
    while len(con) < len(graph):  
        i, j = extension(con, graph)  
        tree[i][j], tree[j][i] = 1, 1  
        con.add{j}  
    return tree
```

# Let us visualise generic input

```
def extension(con, g):
    """input: vertices con connected in
    g
    output: edge (i,j) of g with i in
    con and j not in con"""
    ...


def spanning_tree(graph):
    """input: graph given as adj. matrix
    output: spanning tree of graph"""
    tree = empty_graph(len(graph))
    con = {0}
    while len(con) < len(graph):
        i, j = extension(con, graph)
        tree[i][j], tree[j][i] = 1, 1
        con.add{j}
    return tree
```



# ...and analyse what happens during computation

```
def extension(con, g):
    """input: vertices con connected in
    g
    output: edge (i,j) of g with i in
    con and j not in con"""
    ...


def spanning_tree(graph):
    """input: graph given as adj. matrix
    output: spanning tree of graph"""
    tree = empty_graph(len(graph))
    con = {0}
    while len(con) < len(graph):
        i, j = extension(con, graph)
        tree[i][j], tree[j][i] = 1, 1
        con.add{j}
    return tree
```



# ...and analyse what happens during computation

```
def extension(con, g):
    """input: vertices con connected in
    g
    output: edge (i,j) of g with i in
    con and j not in con"""
    ...


def spanning_tree(graph):
    """input: graph given as adj. matrix
    output: spanning tree of graph"""
    tree = empty_graph(len(graph))
    con = {0}
    while len(con) < len(graph):
        i, j = extension(con, graph)
        tree[i][j], tree[j][i] = 1, 1
        con.add{j}
    return tree
```



# ...and analyse what happens during computation

```
def extension(con, g):
    """input: vertices con connected in
    g
    output: edge (i,j) of g with i in
    con and j not in con"""
    ...


def spanning_tree(graph):
    """input: graph given as adj. matrix
    output: spanning tree of graph"""
    tree = empty_graph(len(graph))
    con = {0}
    while len(con) < len(graph):
        i, j = extension(con, graph)
        tree[i][j], tree[j][i] = 1, 1
        con.add{j}
    return tree
```



# ...and analyse what happens during computation

```
def extension(con, g):
    """input: vertices con connected in g
       output: edge (i,j) of g with i in
              con and j not in con"""
    ...


def spanning_tree(graph):
    """input: graph given as adj. matrix
       output: spanning tree of graph"""
    tree = empty_graph(len(graph))
    con = {0}
    while len(con) < len(graph):
        # vertices in con are connected in tree
        i, j = extension(con, graph)
        tree[i][j], tree[j][i] = 1, 1
        con.add{j}
    return tree
```



# ...and analyse what happens during computation

```
def extension(con, g):
    """input: vertices con connected in g
       output: edge (i,j) of g with i in
              con and j not in con"""
    ...


def spanning_tree(graph):
    """input: graph given as adj. matrix
       output: spanning tree of graph"""
    tree = empty_graph(len(graph))
    con = {0}
    while len(con) < len(graph):
        # vertices in con are connected in tree
        i, j = extension(con, graph)
        tree[i][j], tree[j][i] = 1, 1
        con.add{j}
    return tree
```



# ...and analyse what happens during computation

```
def extension(con, g):
    """input: vertices con connected in g
       output: edge (i,j) of g with i in
              con and j not in con"""
    ...

def spanning_tree(graph):
    """input: graph given as adj. matrix
       output: spanning tree of graph"""
    tree = empty_graph(len(graph))
    con = {0}
    while len(con) < len(graph):
        # vertices in con are connected in tree
        i, j = extension(con, graph)
        tree[i][j], tree[j][i] = 1, 1
        con.add{j}
    return tree
```






# ...and analyse what happens during computation

```
def extension(con, g):
    """input: vertices con connected in g
    output: edge (i,j) of g with i in
           con and j not in con"""
    ...


def spanning_tree(graph):
    """input: graph given as adj. matrix
    output: spanning tree of graph"""
    tree = empty_graph(len(graph))
    con = {0}
    while len(con) < len(graph):
        # vertices in con are connected in tree
        i, j = extension(con, graph)
        tree[i][j], tree[j][i] = 1, 1
        con.add{j}
    return tree
```



# ...and analyse what happens during computation

```
def extension(con, g):
    """input: vertices con connected in g
    output: edge (i,j) of g with i in
           con and j not in con"""
    ...


def spanning_tree(graph):
    """input: graph given as adj. matrix
    output: spanning tree of graph"""
    tree = empty_graph(len(graph))
    con = {0}
    while len(con) < len(graph):
        # vertices in con are connected in tree
        i, j = extension(con, graph)
        tree[i][j], tree[j][i] = 1, 1
        con.add{j}
        # vertices in con are connected in tree
    return tree
```



# Assume con is connected at start of arbitrary loop iteration

```
def extension(con, g):
    """input: vertices con connected in g
    output: edge (i,j) of g with i in
           con and j not in con"""
    ...


def spanning_tree(graph):
    """input: graph given as adj. matrix
    output: spanning tree of graph"""
    tree = empty_graph(len(graph))
    con = {0}
    while len(con) < len(graph):
        # vertices in con are connected in tree
        i, j = extension(con, graph)
        tree[i][j], tree[j][i] = 1, 1
        con.add{j}
        # vertices in con are connected in tree
    return tree
```



# Extension edge bridges connected to not yet connected

```
def extension(con, g):
    """input: vertices con connected in g
    output: edge (i,j) of g with i in
           con and j not in con"""
    ...


def spanning_tree(graph):
    """input: graph given as adj. matrix
    output: spanning tree of graph"""
    tree = empty_graph(len(graph))
    con = {0}
    while len(con) < len(graph):
        # vertices in con are connected in tree
        i, j = extension(con, graph)
        tree[i][j], tree[j][i] = 1, 1
        con.add{j}
        # vertices in con are connected in tree
    return tree
```



# Extension edge bridges connected to not yet connected

```
def extension(con, g):
    """input: vertices con connected in g
       output: edge (i,j) of g with i in
              con and j not in con"""
    ...


def spanning_tree(graph):
    """input: graph given as adj. matrix
       output: spanning tree of graph"""
    tree = empty_graph(len(graph))
    con = {0}
    while len(con) < len(graph):
        # vertices in con are connected in tree
        i, j = extension(con, graph)
        tree[i][j], tree[j][i] = 1, 1
        con.add{j}
        # vertices in con are connected in tree
    return tree
```



# After adding extension edge to tree j is also connected

```
def extension(con, g):
    """input: vertices con connected in g
       output: edge (i,j) of g with i in
              con and j not in con"""
    ...


def spanning_tree(graph):
    """input: graph given as adj. matrix
       output: spanning tree of graph"""
    tree = empty_graph(len(graph))
    con = {0}
    while len(con) < len(graph):
        # vertices in con are connected in tree
        i, j = extension(con, graph)
        tree[i][j], tree[j][i] = 1, 1
        con.add{j}
        # vertices in con are connected in tree
    return tree
```



# Invariant: con is connected

```
def extension(con, g):
    """input: vertices con connected in g
       output: edge (i,j) of g with i in
              con and j not in con"""
    ...


def spanning_tree(graph):
    """input: graph given as adj. matrix
       output: spanning tree of graph"""
    tree = empty_graph(len(graph))
    con = {0}
    while len(con) < len(graph):
        #I: vertices in con are connected in tree
        i, j = extension(con, graph)
        tree[i][j], tree[j][i] = 1, 1
        con.add{j}
        #I: vertices in con are connected in tree
    return tree
```



# Is this enough to conclude desired post condition?

```
def extension(con, g):
    """input: vertices con connected in g
       output: edge (i,j) of g with i in
              con and j not in con"""
    ...

def spanning_tree(graph):
    """input: graph given as adj. matrix
       output: spanning tree of graph"""
    tree = empty_graph(len(graph))
    con = {0}
    while len(con) < len(graph):
        i, j = extension(con, graph)
        tree[i][j], tree[j][i] = 1, 1
        con.add{j}
        #I: vertices in con are connected in tree
    #EXC: len(con) == len(graph)
    return tree
```






# No. Can conclude that the tree is connected, but could contain a cycle

```
def extension(con, g):
    """input: vertices con connected in g
       output: edge (i,j) of g with i in
              con and j not in con"""
    ...


def spanning_tree(graph):
    """input: graph given as adj. matrix
       output: spanning tree of graph"""
    tree = empty_graph(len(graph))
    con = {0}
    while len(con) < len(graph):
        i, j = extension(con, graph)
        tree[i][j], tree[j][i] = 1, 1
        con.add{j}
        #I: vertices in con are connected in tree
        #EXC: len(con) == len(graph)
        #POC: all vertices are connected to the tree
    return tree
```



# What should the second invariant be?

```
def extension(con, g):
    """input: vertices con connected in g
       output: edge (i,j) of g with i in
              con and j not in con"""
    ...


def spanning_tree(graph):
    """input: graph given as adj. matrix
       output: spanning tree of graph"""
    tree = empty_graph(len(graph))
    con = {0}
    while len(con) < len(graph):
        i, j = extension(con, graph)
        tree[i][j], tree[j][i] = 1, 1
        con.add{j}
        #I1: vertices in con are connected in tree
        #I2: ?
    return tree
```



# Need to guarantee that we never add a cycle to tree

```
def extension(con, g):
    """input: vertices con connected in g
    output: edge (i,j) of g with i in
           con and j not in con"""
    ...


def spanning_tree(graph):
    """input: graph given as adj. matrix
    output: spanning tree of graph"""
    tree = empty_graph(len(graph))
    con = {0}
    while len(con) < len(graph):
        i, j = extension(con, graph)
        tree[i][j], tree[j][i] = 1, 1
        con.add{j}
        #I: vertices in con are connected in tree
        # tree does not contain cycle
    return tree
```



# Observation: extension edge never creates a cycle with edges in the tree

```
def extension(con, g):
    """input: vertices con connected in g
    output: edge (i,j) of g with i in
           con and j not in con"""
    ...


def spanning_tree(graph):
    """input: graph given as adj. matrix
    output: spanning tree of graph"""
    tree = empty_graph(len(graph))
    con = {0}
    while len(con) < len(graph):
        # tree does not contain a cycle
        i, j = extension(con, graph)
        tree[i][j], tree[j][i] = 1, 1
        con.add{j}
        #I1: vertices in con are connected in tree
        # tree does not contain a cycle
    return tree
```



# Invariant 2: tree does not contain a cycle

```
def extension(con, g):
    """input: vertices con connected in g
       output: edge (i,j) of g with i in
              con and j not in con"""
    ...


def spanning_tree(graph):
    """input: graph given as adj. matrix
       output: spanning tree of graph"""
    tree = empty_graph(len(graph))
    con = {0}
    while len(con) < len(graph):
        i, j = extension(con, graph)
        tree[i][j], tree[j][i] = 1, 1
        con.add{j}
        #I1: vertices in con are connected in tree
        #I2: tree does not contain cycle
    return tree
```



# Now we know the tree is connected and without a cycle at loop exit

```
def extension(con, g):
    """input: vertices con connected in g
       output: edge (i,j) of g with i in
              con and j not in con"""
    ...


def spanning_tree(graph):
    """input: graph given as adj. matrix
       output: spanning tree of graph"""
    tree = empty_graph(len(graph))
    con = {0}
    while len(con) < len(graph):
        i, j = extension(con, graph)
        tree[i][j], tree[j][i] = 1, 1
        con.add{j}
        #I1: vertices in con are connected in tree
        #I2: tree does not contain cycle
        #EXC: len(con)==len(graph)
    return tree
```



# ...in other words: the tree must be a spanning tree!!

```
def extension(con, g):
    """input: vertices con connected in g
       output: edge (i,j) of g with i in
              con and j not in con"""
    ...

def spanning_tree(graph):
    """input: graph given as adj. matrix
       output: spanning tree of graph"""
    tree = empty_graph(len(graph))
    con = {0}
    while len(con) < len(graph):
        i, j = extension(con, graph)
        tree[i][j], tree[j][i] = 1, 1
        con.add{j}
        #I1: vertices in con are connected in tree
        #I2: tree does not contain cycle
        #EXC: len(con)==len(graph)
        #POC: tree is spanning tree of graph
    return tree
```



# What have we learnt?

- Use **assertions** about execution state to reason about programs
- Loop **invariants** can be used to analyse behaviour of loopy control flows
- Look for invariants that turn into desired **post-condition** when loop exit condition is true