

Grundlagen der künstlichen Intelligenz

Los Del DGIIM, losdeldgiim.github.io

Doble Grado en Ingeniería Informática y Matemáticas
Universidad de Granada

Esta obra está bajo una [Licencia Creative Commons Atribución-NoComercial-SinDerivadas 4.0 Internacional](https://creativecommons.org/licenses/by-nc-nd/4.0/) (CC BY-NC-ND 4.0).

Eres libre de compartir y redistribuir el contenido de esta obra en cualquier medio o formato, siempre y cuando des el crédito adecuado a los autores originales y no persigas fines comerciales.

Grundlagen der künstlichen Intelligenz

Los Del DGIIM, losdeldgiim.github.io

Arturo Olivares Martos

Granada, 2026

Índice general

1. Introduction	5
1.1. Intelligence Tests	5
1.2. Initial Definitions	6
2. Data Science	7
2.1. Statistics	7
2.2. Data	9
2.2.1. Data Collection	9
2.2.2. Data Preprocessing	10
2.2.3. Data Usage	12
3. Search Algorithms	13
3.1. Graph Theory	13
3.1.1. PageRank	14
3.2. Sorting Algorithms	15
3.2.1. Insertion Sort	15
3.2.2. Bubble Sort	16
3.2.3. Shaker Sort	16
3.2.4. Quick Sort	16
3.2.5. Topological Sorting: Kahn's Algorithm	17
3.3. Uninformed Search	17
3.3.1. Breadth-First Search	17
3.3.2. Depth-First Search	17
3.3.3. Depth-Limited Search	18
3.3.4. Iterative Deepening Search	18
3.3.5. Bidirectional Search	18
3.3.6. Uniform Cost Search	18
3.3.7. Dijkstra's Algorithm	19
3.4. Informed Search	20
3.4.1. Greedy Best First Search	20
3.4.2. A* Search	20
3.5. Local Search	21
3.5.1. Hill Climbing	21
3.5.2. Simulated Annealing	22

4. Machine Learning Methodic	23
4.1. Classification	24
4.1.1. Evaluation Metrics	24
4.2. Error and Uncertainty	28
4.3. Overfitting and Underfitting	30
4.3.1. No Free Lunch Theorem	31
4.4. Resampling Methods	31
4.4.1. Data Augmentation	31
4.4.2. Cross-Validation	31
4.5. K-Nearest Neighbors (KNN)	33
5. Genetic Algorithms	35
5.1. Crossover	36
5.2. Mutation	37
5.3. Selection	39
6. Exercises	41
6.0. Introduction	41
6.1. Data Processing / Cleaning	43
6.2. Search Algorithms	47
6.3. Machine Learning Algorithms	55
6.4. Genetic Algorithms	60

1. Introduction

Artificial Intelligence (AI) is a field that is rapidly evolving and has the potential to revolutionize various industries. Before delving into the technical aspects of AI, it is important to understand the concept of intelligence and how it can be measured.

1.1. Intelligence Tests

Scientists have tried to decide what differentiates AI from computer algorithms; i.e. what is the essence of intelligence? This question has been debated for decades, and there are different tests that have been proposed to determine whether a machine can be considered intelligent or not. The importance of these tests is shown in the Chinese Room thought experiment.

- Chinese Room Experiment:

The Chinese Room thought experiment involves a person who does not understand Chinese sitting in a room with a set of instructions for how to respond to Chinese characters. The person receives Chinese characters as input and uses the instructions to produce appropriate responses, which are then sent back out of the room.

From the outside, it may appear that the person in the room understands Chinese, but in reality, they are simply following a set of rules without any comprehension of the language. This thought experiment raises questions about whether a machine can truly understand language or if it is simply following a set of instructions.

Some of the most well-known tests include:

- Turing Test:

In the Turing Test, a human evaluator interacts with both a machine and a human without knowing which is which. If the evaluator cannot reliably distinguish between the machine and the human, then the machine is said to have passed the Turing Test and is considered to be intelligent.

It only tests for the ability to mimic human behavior, not for true understanding or consciousness.

- Winograd Test:

The test involves a series of sentences known as “Winograd Schemas”. They include ambiguous pronouns that require common sense and contextual understanding to resolve.

This test is not about factual knowledge but rather about understanding context.

- Lovelace Test:

The Lovelace Test is designed to evaluate a machine's ability to create something original and surprising.

This test is extremely difficult for machines to pass, as they often just combine existing ideas rather than creating something truly new.

- Metzinger Test:

The Metzinger Test is designed to evaluate a machine's ability to have a subjective experience, a sense of “self, I”, and consciousness. There is no definitive method for conducting the test in practice, since subjective experience cannot be observed from the outside.

1.2. Initial Definitions

From more general concepts to more specific ones, where each one builds upon the previous, some important terms in the field of AI include:

- Data Science: Field that turns data into knowledge and decisions.
- Artificial Intelligence: Field that aims to create machines that can perform tasks that typically require human intelligence.
- Machine Learning: Subfield of AI that focuses on training machines to learn from data and improve their performance over time without being explicitly programmed.
- Neural Networks: A type of (usually supervised) machine learning model inspired by the structure and function of the human brain. They consist of layers of interconnected nodes (neurons) that process and transmit information.
- Deep Learning: Neural networks with multiple layers. Deep learning has been particularly successful in tasks such as image recognition, natural language processing, and speech recognition.

2. Data Science

Data Science is a multidisciplinary field that combines statistical analysis, machine learning, and domain expertise to extract insights and knowledge from data.

2.1. Statistics

Data science involves, in a large scale, a lot of statistics, which is the branch of mathematics that deals with the collection, analysis, interpretation, presentation, and organization of data. Some of the most important concepts in statistics include:

- Outlier: A data point that is significantly different from the other data points in the dataset. Outliers can be caused by errors in data collection or by natural variability in the data. They can have a significant impact on the results of statistical analysis, so it is important to identify and handle them appropriately.
- Mean: The average of a set of numbers. It represents the central tendency of the data.

$$\text{Mean} = E[X] = \mu := \frac{1}{n} \sum_{i=1}^n x_i$$

- Median: The middle value of a set of numbers when they are arranged in order. It is less affected by outliers than the mean. Other terms as percentiles and quartiles are also used to describe the distribution of the data. The p -th percentile is the value below which $p\%$ of the data falls. The first quartile (Q1) is the 25th percentile, the second quartile (Q2) is the 50th percentile (which is also the median), and the third quartile (Q3) is the 75th percentile.
- Mode: The value that appears most frequently in a dataset. It is useful for categorical data.
- Variance: A measure of how much the data varies from the mean. It is calculated as the average of the squared differences from the mean.

$$\text{Variance} = E[(X - \mu)^2] = \sigma^2 := \frac{1}{n} \sum_{i=1}^n (x_i - \mu)^2$$

It can be however calculated using the Bessel correction, which divides by $n - 1$ instead of n to provide an unbiased estimator of the population variance when working with a sample. This is because when we calculate the sample mean,

we are using the same data points that we are trying to estimate the variance for, which can lead to an underestimation of the true population variance. By dividing by $n - 1$, we are effectively increasing the variance estimate to account for this bias.

$$\text{Sample Variance} = \frac{1}{n-1} \sum_{i=1}^n (x_i - \mu)^2$$

- Standard Deviation: The square root of the variance. It is a measure of how much the data varies from the mean, but it is in the same units as the data.

$$\text{Standard Deviation} = \sqrt{\text{Variance}} = \sigma$$

- Skewness: A measure of the asymmetry of the distribution of the data. A positive skew indicates that the data is skewed to the right, which means that the mean is greater than the median, meaning that there are more values on the right side of the distribution than on the left. A negative skew indicates that the data is skewed to the left, which means that the mean is less than the median, meaning that there are more values on the left side of the distribution than on the right. A skewness of zero indicates that the data is perfectly symmetrical.
- Kurtosis: A measure of the "tailedness" of the distribution of the data. A high kurtosis indicates that the data has heavy tails, which means that there are more extreme values in the data than would be expected in a normal distribution. A low kurtosis indicates that the data has light tails, which means that there are fewer extreme values in the data than would be expected in a normal distribution. A kurtosis of zero indicates that the data has the same tailedness as a normal distribution.
- Covariance: A measure of how much two random variables change together. It is calculated as:

$$\text{Cov}(X, Y) = E[(X - E[X])(Y - E[Y])]$$

A positive covariance indicates that the two variables tend to increase or decrease together, while a negative covariance indicates that one variable tends to increase when the other decreases. A covariance of zero indicates that there is no linear relationship between the two variables.

- Correlation: A measure of the strength and direction of the linear relationship between two random variables. It is calculated as:

$$\text{Correlation}(X, Y) = r_{X,Y} = \frac{\text{Cov}(X, Y)}{\sigma_X \sigma_Y}$$

where σ_X and σ_Y are the standard deviations of X and Y , respectively. The correlation coefficient ranges from -1 to 1, where a value of 1 indicates a perfect positive linear relationship, a value of -1 indicates a perfect negative linear relationship, and a value of 0 indicates no linear relationship between the two variables.

It should be noted that correlation does not imply causation. Just because two variables are correlated does not mean that one variable causes the other to change. There may be other factors at play that are influencing both variables, or the correlation may be purely coincidental.

2.2. Data

Data is the raw material that fuels the development of AI systems, and understanding how to work with data is crucial for anyone interested in the field of AI. Two main people work on it:

- Data Engineer: Responsible for building and maintaining the infrastructure that allows for the collection, storage, and processing of data.
- Data Scientist: Responsible for analyzing and interpreting data to extract insights and knowledge.

When working with data, the PPDAC Data Cycle is often used as a framework to guide the process. The PPDAC Data Cycle consists of five stages:

- Problem: Defining the problem that needs to be solved, stating the objectives and questions that need to be answered.
- Plan: Developing a plan for how to answer the questions and achieve the objectives. This includes deciding on which data to collect, how to collect it, and how to analyze it.
- Data: Collecting the data according to the plan. This can involve gathering data from various sources, such as databases, APIs, or web scraping. It also involves preparing the data for analysis, which may include cleaning, transforming, and encoding the data.
- Analysis: Analyzing the data to extract insights and knowledge. This can involve using various statistical and machine learning techniques to identify patterns and relationships in the data.
- Conclusion: Drawing conclusions from the analysis and communicating the results. This can involve creating visualizations, writing reports, or presenting the findings to stakeholders.

2.2.1. Data Collection

Regarding data collection, there are some aspects that must be taken into account:

- Data Quality: The quality of the data is crucial for the success of any AI project.
- Data Integrity: Ensuring that the data is accurate and reliable.
- Data Consistency: Ensuring that the data is consistent across different sources and formats.

2.2.2. Data Preprocessing

Once the data has been collected, it must be preprocessed before it can be used for training AI models. This involves:

- Data Validation: Checking the data for errors and inconsistencies. Depending on the source and type of data, some rules can be applied to validate it.
- Data Sorting: Organizing the data in a way that makes it easier to work with. This can involve sorting the data by a specific column.
- Data Aggregation: Combining data from multiple sources or records into a single record. This can involve calculating summary statistics, such as the mean or median, for a group of records. This is often used to reduce the size of the data and to make it easier to analyze. However, it can also lead to loss of information, so it should be used with caution.
- Data Cleaning: Removing or correcting any errors or inconsistencies in the data.
- Data Transformation: Converting the data into a format that can be used for training AI models.

Data preprocessing also involves data scaling, which is the process of normalizing or standardizing the data to ensure that it is on the same scale. This is important because many AI algorithms are sensitive to the scale of the data and can perform poorly if the data is not scaled properly. Some common scalers include:

- Binarizer: Converts categorical data into binary data. A threshold is set, and values above the threshold are converted to 1, while values below the threshold are converted to 0.

$$X' = \begin{cases} 0 & \text{if } X \leq \text{threshold} \\ 1 & \text{if } X > \text{threshold} \end{cases}$$

- MaxAbsScaler: Scales the data to the range $[-1, 1]$ by dividing each value by the maximum absolute value in the data.

$$X' = \frac{X}{\max(|X|)}$$

- MinMaxScaler: Scales the data to a specified range, let's say $[\text{mín}, \text{máx}]$. First the data is scaled to the range $[0, 1]$ (X_{std}), and then it is scaled to the specified range.

$$X_{\text{std}} = \frac{X - \text{mín}(X)}{\text{máx}(X) - \text{mín}(X)} \quad X' = X_{\text{std}} \cdot (\text{máx} - \text{mín}) + \text{mín}$$

- Normalizer: Scales the data to have a unit norm. This is done by dividing each value by the norm of the data. Usually, the L2 norm is used.

$$X' = \frac{X}{\|X\|}$$

- **PowerTransformer**: Applies a power transformation to the data to make it more Gaussian-like. This is useful for data that is not normally distributed.
- **RobustScaler**: Scales the data using statistics that are robust to outliers. This is useful for data that contains outliers.

$$X' = \frac{X - \text{median}(X)}{\text{IQR}(X)}$$

where $\text{IQR}(X)$ is the interquartile range of X .

- **StandardScaler**: Scales the data to have a mean of 0 and a standard deviation of 1.

$$X' = \frac{X - \mu}{\sigma}$$

where μ is the mean of X and σ is the standard deviation of X .

One important aspect of data preprocessing is *encoding* the data. This is the process of converting categorical data into numerical data that can be used for training AI models. There are several techniques for encoding data, such as:

- **Ordinal Encoding**: Assigning a unique integer to each category in the data. The order of the integers is important, as it implies a relationship between the categories.

$$\{\text{small, medium, large}\} \rightarrow \{0, 1, 2\}$$

- **Label Encoding**: Similar to ordinal encoding, but it does not imply any relationship between the categories. Each category is assigned a unique integer, but the order of the integers does not matter.

$$\{\text{red, green, blue}\} \rightarrow \{0, 1, 2\}$$

- **One-Hot Encoding**: Creating a binary column for each category in the data.

$$\{\text{red, green, blue}\} \rightarrow \begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

- **Dummy Encoding (Leave out the last)**: Similar to one-hot encoding, but it leaves out the last category to avoid multicollinearity.

$$\{\text{red, green, blue}\} \rightarrow \begin{bmatrix} 1 & 0 \\ 0 & 1 \\ 0 & 0 \end{bmatrix}$$

- **Absolute Frequency Encoding**: Assigning a unique integer to each category based on the absolute frequency of the category in the data. One drawback of this technique is that, if two categories have the same frequency, they will be assigned the same integer, which can lead to confusion.

$$\begin{aligned} &\{\text{red, red, red, green, blue, blue}\} \\ &\{\text{red, green, blue}\} \rightarrow \{3, 1, 2\} \end{aligned}$$

- Relative Frequency Encoding: Assigning a unique integer to each category based on the relative frequency of the category in the data.

$$\{\text{red, red, red, green, blue, blue}\}$$
$$\{\text{red, green, blue}\} \rightarrow \{3/6, 1/6, 2/6\}$$

- Feature Hash Encoding: Hashing the categories into a fixed number of columns. This is useful for data with a large number of categories.

2.2.3. Data Usage

Once the data has been preprocessed, they can be used. There are two main destinations for the data:

- Data Visualization: The process of creating visual representations of data to help understand and communicate insights. This is used by people.

The Gestalt Principles of Perception are a set of principles that describe how people perceive and organize visual information, and they can be applied to data visualization to create more effective and engaging visualizations.

- Data Modeling: The process of using data to train AI models. This is used by machines.

3. Search Algorithms

In our current world, plenty of algorithms are used to search for information. From the most basic ones, such as sorting algorithms, to the most complex ones, such as search engines. In this chapter, we will explore some of the most common search algorithms and their applications.

3.1. Graph Theory

Search algorithms are often used in graphs, as they provide a way to represent complex relationships between data. A graph $G = (V, E)$ is defined as a pair of sets, where V is called the set of vertices and E is called the set of edges. The vertices represent the data points, while the edges represent the relationships between them. There are different types of graphs, such as directed and undirected graphs, weighted and unweighted graphs, or cyclic and acyclic graphs. Each type of graph has its own properties and algorithms that can be applied to it. An example graph is shown in Figure 3.1.

A graph is usually represented as an *adjacency matrix*. Where the rows represent the origin vertices, the columns represent the destination vertices¹, and the values a_{ij} represent:

- If the graph is unweighted, a_{ij} represents the number of edges from vertex i to vertex j .
- If the graph is weighted, a_{ij} represents the weight of the edge from vertex i to vertex j . If there is no edge, a_{ij} is usually set to infinity or an invalid value.

If there are a lot of vertices that are not connected to each other, the adjacency matrix can be very sparse, meaning that it contains a lot of zeros. In this case, it is

¹This could also be the opposite: the origin vertices could be the columns and the destination vertices, the rows.




Figura 3.1: Example of a directed graph.

```

1 adjacency_list = {
    'A': ['B', 'D', 'E'],
    'B': ['A', 'C', 'D'],
    'C': ['B', 'E'],
5    'D': ['A', 'B', 'E'],
    'E': ['A', 'C', 'D']
}

```

Código fuente 1: Adjacency list for the graph in Figure 3.1.

more efficient to use an *adjacency list* to represent the graph, where each vertex is represented as a list of its neighboring vertices. This can save a lot of space, especially for large graphs with few edges. For example, the adjacency matrix for the graph in Figure 3.1 is shown in Equation 3.1, while the adjacency list is Listing 1.

$$A = \begin{bmatrix} 0 & 1 & 0 & 1 & 1 \\ 1 & 0 & 1 & 1 & 0 \\ 0 & 0 & 0 & 0 & 1 \\ 1 & 1 & 0 & 0 & 1 \\ 1 & 0 & 1 & 1 & 0 \end{bmatrix} \quad (3.1)$$

This matrix is also called “next-neighbor” matrix, as the neighboring vertices of a vertex i can be found by looking at the i -th row of the matrix. The “next-next-neighbor” matrix, on the other hand, is obtained by multiplying the adjacency matrix by itself. This matrix can be used to find the vertices that are two steps away from a given vertex.

Lastly, the *transition matrix* is obtained by normalizing the adjacency matrix. This is done by dividing each entry a_{ij} by the sum of the entries in the i -th row. The transition matrix can be used to find the probability of transitioning from one vertex to another in a random decision process.

3.1.1. PageRank

PageRank is an algorithm used to determine the importance of nodes in a graph. It is well-known for being used by Google Search to rank web pages in their search engine results. It works by counting the number and quality of links to a page to determine a rough estimate of how important the website is. The underlying assumption is that more important websites are likely to receive more links from other websites. Everything is represented as a directed graph, where the vertices represent web pages and the edges represent hyperlinks between them. There are certain parameters that can be adjusted in the PageRank algorithm, such as:

- The teleportation probability vector. It’s n -th entry represents the probability of jumping to the n -th page when a random surfer decides to teleport (going to a random page instead of following a link). It is usually set to a uniform distribution, meaning that the random surfer has an equal probability of jumping to any page.

- The damping factor α , which represents the probability that a random surfer will continue following links rather than teleporting.
- The convergence threshold, which determines when the algorithm should stop iterating and return the PageRank values.

The algorithm returns the PageRank vector, whose n -th entry represents the PageRank of the n -th page. The PageRank values decide in which order the pages are shown in the search results, with higher PageRank values indicating more important pages. The PageRank algorithm works as follows:

1. Initialize the PageRank vector with the teleportation probability vector.
2. Update the old PageRank vector (PR) by adding the transition matrix multiplied by the old PageRank vector (weighted by the damping factor α) and the teleportation probability vector (weighted by $1 - \alpha$):

$$PR = \alpha \cdot M \cdot PR + (1 - \alpha) \cdot v$$

Where M is the transition matrix and v is the teleportation probability vector.

3. Repeat the process until the change in the PageRank vector is less than the convergence threshold (or a maximum number of iterations is reached).

Once the algorithm converges, the PageRank values can be used to rank the web pages in search results. The higher the PageRank value, the more important the page is considered to be, and therefore, it will be ranked higher in the search results.

3.2. Sorting Algorithms

Sorting algorithms are a fundamental part of computer science, as they allow us to organize data in a specific order. In addition, they are used in many search algorithms, as they can help to reduce the search space and improve the efficiency of the search.

3.2.1. Insertion Sort

This algorithm works by dividing the array into a sorted and an unsorted part. The sorted part is initially empty, and the unsorted part contains all the elements.

1. Start with the first element of the unsorted part and compare it with the last element of the sorted part.
2. Move all the elements of the sorted part that are greater than the current element to the right.
3. Insert the current element into its correct position in the sorted part.
4. Repeat the process for all the elements in the unsorted part until it is empty.

It has a time complexity of $O(n^2)$.

3.2.2. Bubble Sort

This algorithm works by repeatedly swapping adjacent elements if they are in the wrong order. The process is repeated until the array is sorted.

1. Compare each pair of adjacent elements in the array.
2. If the elements are in the wrong order, swap them.
3. Repeat the process for all the elements in the array until it is sorted.

It has a time complexity of $O(n^2)$.

3.2.3. Shaker Sort

This algorithm is a variation of Bubble Sort that sorts in both directions on each pass through the list. It works by comparing adjacent elements and swapping them if they are in the wrong order, similar to Bubble Sort. However, it also compares elements in the opposite direction, which can help to reduce the number of passes needed to sort the array.

1. Start at the beginning of the array and compare each pair of adjacent elements.
2. If the elements are in the wrong order, swap them.
3. After reaching the end of the array, reverse the direction and compare each pair of adjacent elements again.
4. Repeat the process until the array is sorted.

It has a time complexity of $O(n^2)$, but with lower constant factors than Bubble Sort.

3.2.4. Quick Sort

This divide-and-conquer algorithm works by selecting a pivot element from the array and partitioning the other elements into two sub-arrays, according to whether they are less than or greater than the pivot. The sub-arrays are then sorted recursively. This process continues until the base case of an empty array or an array with a single element is reached.

1. Choose a pivot element from the array.
2. Partition the array into two sub-arrays: one with elements less than the pivot and one with elements greater than the pivot.
3. At this point, the pivot is in its final position.
4. Recursively apply the above steps to the sub-arrays until the base case is reached.

The efficiency of Quick Sort depends on the choice of the pivot. The complexity depends on the partitioning of the array. If the pivot divides the array into two equal halves, the time complexity is $O(n \log n)$. However, if the pivot is consistently the smallest or largest element, the time complexity degrades to $O(n^2)$.

3.2.5. Topological Sorting: Kahn's Algorithm

This algorithm is used to sort the vertices of a directed acyclic graph (DAG) in a linear order. If there is a directed edge from vertex u to vertex v , then u comes before v in the ordering. It is used in several applications, such as scheduling tasks, resolving dependencies, and determining the order of compilation in programming languages. The algorithm works as follows:

1. The result is going to be stored in a list called L .
2. Find all vertices with no incoming edges and add them to a set S .
3. While S is not empty:
 - a) Remove a vertex n from S and add it to L .
 - b) For each vertex m with an edge from n to m :
 - 1) Remove the edge from n to m .
 - 2) If m has no other incoming edges, add m to S .
4. If there are still edges in the graph, it means that there is a cycle, and therefore, a topological sort is not possible. Otherwise, the list L contains the vertices in topologically sorted order.

3.3. Uninformed Search

Uninformed search algorithms are those that do not have any additional information about the search space. They explore the search space in a systematic way, without any guidance or heuristics.

3.3.1. Breadth-First Search

This algorithm explores the search space level by level, starting from the root node and expanding all the nodes at the present depth before moving on to the nodes at the next depth level. It uses a queue (FIFO) to keep track of the nodes to be explored. It is guaranteed to find the shortest path, but it can be memory intensive, as it needs to store all the nodes at the current depth level.

3.3.2. Depth-First Search

This algorithm explores the search space by going as deep as possible along each branch before backtracking. It uses a stack (LIFO) to keep track of the nodes to be explored. It is not guaranteed to find the shortest path, but it can be more memory efficient than breadth-first search.

3.3.3. Depth-Limited Search

This algorithm is a variation of depth-first search that limits the depth of the search. It is used to avoid infinite loops in cases where the search space is infinite or has cycles. It uses a stack (LIFO) to keep track of the nodes to be explored, and it keeps track of the current depth of the search. If the depth limit is reached, it backtracks and explores other branches. It is not guaranteed to find the searched node, but it can be more memory efficient than depth-first search. The choice of the depth limit is crucial, as it can affect the completeness and optimality of the search.

3.3.4. Iterative Deepening Search

This algorithm combines the benefits of both breadth-first and depth-first search. It performs a depth-limited search with increasing depth limits until a solution is found.

1. Start with a depth limit of 0.
2. Perform a depth-limited search with the current depth limit.
3. If a solution is found, return it. Otherwise, increase the depth limit and repeat the process.

A stack (LIFO) is used to keep track of the nodes to be explored in the depth-limited search. It is guaranteed to find the shortest path, and it can be more memory efficient than breadth-first search.

3.3.5. Bidirectional Search

This algorithm is used to find the shortest path between two nodes in a graph. It works by simultaneously searching (typically BFS) from both the start node and the goal node until the two searches meet in the middle. It uses two data structures to keep track of the nodes to be explored from both directions. It is guaranteed to find the shortest path, and it can be more efficient than unidirectional search, especially in cases where the search space is large.

3.3.6. Uniform Cost Search

This algorithm is used in weighted graphs (where the edges have positive costs) to find the least costly path from the root node to a goal node. It is similar to breadth-first search, but it takes into account the cost of the path. It uses a priority queue to keep track of the nodes to be explored, where the priority is determined by the cost of the path from the root node to the current node. It is guaranteed to find the least costly path, but it can be memory intensive, as it needs to store all the nodes in the search space.

1. Start with the root node and add it to the priority queue with a cost of 0.
2. While the priority queue is not empty:
 - a) Remove the node with the lowest cost from the priority queue.

- b) If the node is a goal node, return the path to it.
- c) Otherwise, expand the node and add its children to the priority queue with their respective cumulative costs.

Local Uniform Cost Search

This algorithm is a variation of uniform cost search that is used to find the least costly path from a given node to a goal node, but just considering the local neighborhood of the given node. For each selected node, the next selected node is the one with the lowest cost among its neighbors. It is not guaranteed to find the least costly path, but it can be more efficient than uniform cost search in cases where the search space is large and the goal node is close to the given node.

1. Start with the given node.
2. While the goal node has not been reached, or a maximum number of iterations has not been reached:
 - a) Evaluate the neighbors of the current node and select the one with the lowest cost.
 - b) Move to the selected neighbor and repeat the process.

3.3.7. Dijkstra's Algorithm

This algorithm is a specific implementation of uniform cost search that is used to find the shortest path from a source node to all other nodes in a weighted graph. It works by maintaining a priority queue of nodes to be explored, where the priority is determined by the cumulative cost from the source node to the current node. The algorithm iteratively expands the node with the lowest cumulative cost and updates the costs of its neighbors until all nodes have been explored. It is guaranteed to find the shortest path from the source node to all other nodes, but it can be memory intensive, as it needs to store all the nodes in the search space.

1. Start with the source node and add it to the priority queue with a cost of 0. Every other node is added to the priority queue with a cost of infinity.
2. While the priority queue is not empty (it is not empty until all nodes have been explored):
 - a) Remove the node with the lowest cumulative cost from the priority queue.
 - b) For each neighbor of the current node:
 - 1) Calculate the cumulative cost to reach the neighbor through the current node.
 - 2) If this cumulative cost is less than the previously known cost for that neighbor, update the cost and modify it in the priority queue.

It should be noted that Dijkstra's algorithm is the same as UCS, but it simply does not stop when it finds a goal node, but rather continues to explore until all nodes have been explored. This is because Dijkstra's algorithm is designed to find

the shortest path from a source node to all other nodes in the graph, while UCS is designed to find the least costly path from a root node to a specific goal node. Therefore, Dijkstra's algorithm is more general than UCS, but also more computationally intensive.

3.4. Informed Search

Informed search algorithms are those that have additional information about the search space. They use this information to guide the search and improve its efficiency. The additional information is usually in the form of a heuristic function, which estimates the cost of reaching the goal from a given node.

3.4.1. Greedy Best First Search

This algorithm uses a priority queue to keep track of the nodes to be explored, where the priority is determined by the heuristic function. It always expands the node that is estimated to be closest to the goal.

1. Start with the root node and add it to the priority queue with a priority determined by the heuristic function.
2. While the priority queue is not empty:
 - a) Remove the node with the lowest heuristic value from the priority queue.
 - b) If the node is a goal node, return the path to it.
 - c) Otherwise, expand the node and add its children to the priority queue with their respective heuristic values.

The efficiency of Greedy Best First Search depends on the quality of the heuristic function. The main drawback of this algorithm is that it is not guaranteed to find the optimal solution, as it does not consider the actual cost of the path, but only its estimated cost to the goal.

3.4.2. A* Search

This algorithm is a combination of uniform cost search and greedy best first search. It uses a priority queue to keep track of the nodes to be explored, where the priority is determined by:

$$f(n) = g(n) + h(n)$$

Where $g(n)$ is the actual cost from the root node to the current node n , and $h(n)$ is the heuristic estimate of the cost from n to the goal. Two important properties of the heuristic function are:

- Admissible: It never overestimates the cost to reach the goal. It can be expressed as:

$$h(n) \leq h^*(n) \quad \forall n \in V$$

where $h^*(n)$ is the true cost from node n to the goal. If the heuristic is admissible, A* Search is guaranteed to find the optimal solution.

- Consistent (or monotonic): For every node n and every successor n' of n , the estimated cost of reaching the goal from n is no greater than the cost of getting from n to n' plus the estimated cost of reaching the goal from n' . Formally, this can be expressed as:

$$h(n) \leq c(n, n') + h(n')$$

where $c(n, n')$ is the actual cost of moving from node n to node n' . If the heuristic is consistent, it is also admissible, and A* Search is guaranteed to find the optimal solution. In addition, if the heuristic is consistent, A* Search is more efficient, as it does not need to revisit nodes that have already been explored.

Therefore, the A* Search algorithm is:

1. Start with the root node and add it to the priority queue with a priority determined by $f(n) = g(n) + h(n)$. All other nodes are added to the priority queue with a priority of infinity.
2. While the priority queue is not empty:
 - a) Remove the node with the lowest $f(n)$ value from the priority queue.
 - b) If the node is a goal node, return the path to it.
 - c) Otherwise, expand the node. For each child of the current node:
 - 1) Calculate $g(n')$ as $g(n) + c(n, n')$, where $c(n, n')$ is the actual cost of moving from node n to node n' . If that new $g(n')$ value is less than the previously known $g(n')$ value for that child, update $g(n')$ and calculate $f(n') = g(n') + h(n')$.

3.5. Local Search

Local search algorithms are those that operate on a single solution and try to find a better solution by making small changes to it. They are often used in optimization problems. Therefore, the aim is finding a local optimum, not necessarily a global one.

3.5.1. Hill Climbing

This algorithm starts with an arbitrary solution and iteratively makes small changes to it, accepting the change if it results in a better solution. The process continues until no further improvements can be made (or a maximum number of iterations is reached).

1. Start with an arbitrary solution.
2. Generate the neighbors of the current solution by making small changes to it.
3. Evaluate the neighbors and select the one with the best value.
4. If the best neighbor is better than the current solution, move to that neighbor and repeat the process. Otherwise (if no neighbor is better), return the current solution as a local optimum.

3.5.2. Simulated Annealing

This algorithm is a variation of hill climbing that allows for occasional moves to worse solutions in order to escape local optima. It is inspired by the annealing process in metallurgy, where a material is heated and then slowly cooled to remove defects and improve its properties. The algorithm works as follows:

1. Start with an arbitrary solution, an initial temperature $T \geq 0$, and a cooling rate α (where $0 < \alpha < 1$).
2. Generate a neighbor of the current solution by making a small change to it.
3. Evaluate the neighbor and calculate the change in the objective function ΔE (difference between the neighbor's value and the current solution's value).
4. If $\Delta E < 0$ (the neighbor is better), move to that neighbor. Otherwise, move to the neighbor with a probability of $e^{-\Delta E/T}$. Initially, with a high temperature, the algorithm is more likely to accept worse solutions, allowing it to explore the search space more broadly. As the temperature decreases, the algorithm becomes less likely to accept worse solutions, focusing more on local improvements.
5. Update the temperature by multiplying it by the cooling rate: $T = \alpha T$.
6. Repeat the process until a stopping criterion is met (e.g., a maximum number of iterations, a minimum temperature, or a satisfactory solution).

This algorithm doesn't necessarily find the optimal solution, but it can avoid being stuck in local optima, especially if the cooling schedule is well-designed.

4. Machine Learning Methodic

Once data has been collected, preprocessed and analyzed, the next step is to apply a machine learning model to it, in order to extract useful information and make predictions. Models are trained and, afterwards, they are evaluated to check their performance. Therefore, the whole dataset is usually split into three subsets:

- *Training set* (70-90 %): the subset of data used to train the model. The model learns from this data by adjusting its parameters to minimize the error between its predictions and the actual values.
- *Validation set* (10-15 %): the subset of data used to tune the hyperparameters of the model. Hyperparameters are parameters that are not learned from the data, but rather set by the user.
- *Test set* (10-30 %): the subset of data used to evaluate the performance of the trained model. The model makes predictions on this data, and its performance is measured using various metrics, such as accuracy, precision, recall, F1 score, etc.

There are three main types of machine learning: There are three main types of machine learning:

- Unsupervised Learning: The machine is trained on unlabeled data, where it must find patterns and relationships on its own.

It usually does not perform well on complex tasks, but it is perfect for outlier detection, as it can identify data points that do not fit the general pattern of the data.

- Supervised Learning: The machine is trained on labeled data, where the correct output is provided for each input.

Labelling data can be time-consuming and expensive, and enterprises often use CAPTCHAs (Completely Automated Public Turing test to tell Computers and Humans Apart) to outsource this task to humans. While detecting if you are a human or a bot by analyzing how you click on images, you are actually helping to label data for machine learning models.

- Reinforcement Learning: The machine learns by interacting with an environment and receiving feedback in the form of rewards or penalties based on its actions.

4.1. Classification

Classification is a supervised learning task where the goal is to assign a label to an input based on its features. For example, given an email, the task is to classify it as spam or not spam. A really common classifier is the *Binary Classifier*, which is used to classify data into two classes, whether yes or no, true or false, spam or not spam, etc. A *threshold* is used to determine the decision boundary between the two classes. If the predicted probability of an input belonging to a certain class is above the threshold, it is classified as that class; otherwise, it is classified as the other class.

When working with a binary classifier, it is important to distinguish between the actual class and the predicted class. This leads to four possible outcomes:

- True Positive (TP): The model correctly predicts the positive class.
- True Negative (TN): The model correctly predicts the negative class.
- False Positive (FP): The model incorrectly predicts the positive class when it is actually negative.
- False Negative (FN): The model incorrectly predicts the negative class when it is actually positive.

This results in the following terms:

- Actual Positive (AP): The actual class is positive. $AP = TP + FN$.
- Actual Negative (AN): The actual class is negative. $AN = TN + FP$.
- Predicted Positive (PP): The predicted class is positive. $PP = TP + FP$.
- Predicted Negative (PN): The predicted class is negative. $PN = TN + FN$.

For a classifier with n classes, this is all summarized in the *confusion matrix*, which is a $n \times n$ matrix where the rows represent the predicted classes and the columns represent the actual classes¹, and the (i, j) -th entry represents the number/percentage of instances where the predicted class is i and the actual class is j . Therefore, the diagonal entries represent the correct predictions, while the off-diagonal entries represent the incorrect predictions. For a binary classifier, the confusion matrix is represented in the Table 4.1.

4.1.1. Evaluation Metrics

The first metric that comes to mind to evaluate the performance of a classifier is *accuracy*:

- Accuracy: the proportion of *correct predictions* out of the total number of *predictions*. The question is: *How many predictions were correct?*

$$\text{Accuracy} = \frac{TP + TN}{TP + TN + FP + FN} \quad (4.1)$$

¹This is the most common way to represent the confusion matrix, but it can also be represented with the rows and columns swapped.

Tabla 4.1: Confusion Matrix for a Binary Classifier.

		Actual Values		
		Positive	Negative	
Predicted Values	Positive	TP	FP	PP
	Negative	FN	TN	PN
		AP	AN	

This metric can however be misleading when the classes are imbalanced, meaning that one class is much more frequent than the other. For example, if 95 % of the data belongs to the negative class and only 5 % belongs to the positive class, a model that always predicts negative will have an accuracy of 95 %, which seems good, but it is actually a terrible model because it never predicts the positive class correctly. Therefore, in cases of imbalanced classes, it is better to use other metrics, as the following.

- **Precision:** the proportion of *true positive predictions* out of the total number of *positive predictions*. Also called *positive predictive value*. The question is: *If predicted positive, how likely is it to be actually positive?*

$$\text{Precision} = PPV = P(AP | PP) = \frac{TP}{TP + FP} \quad (4.2)$$

- **Recall:** the proportion of *true positive predictions* out of the total number of *actual positives*. Also called *sensitivity* or *true positive rate*. The question is: *If actually positive, how likely is it to be predicted positive?*

$$\text{Recall} = TPR = P(TP | AP) = \frac{TP}{TP + FN} \quad (4.3)$$

Even though a theoretically perfect model would have both precision and recall equal to 1, this is in practice very difficult to achieve, and there is usually a trade-off between them. For example, if we set a very low threshold for a binary classifier, it will predict positive for almost all instances, which will result in a high recall but a low precision. On the other hand, if we set a very high threshold, it will predict positive for very few instances, which will result in a high precision but a low recall. Therefore, it is important to find the right balance between precision and recall depending on the specific problem and the costs associated with false positives and false negatives:

- In medical diagnosis, a false negative (failing to detect a disease) can be much more costly than a false positive (incorrectly diagnosing a healthy person), so we would want to prioritize recall over precision.
- In email spam detection, a false positive (marking a legitimate email as spam) can be more costly than a false negative (failing to detect a spam email), so we would want to prioritize precision over recall.

As precision and recall are important metrics for the positive class, they also have their opposite metrics for the negative class, which are also important to evaluate the performance of a classifier

- Negative Predictive Value (NPV): the proportion of *true negative predictions* out of the total number of *negative predictions*. The question is: *If predicted negative, how likely is it to be actually negative?*

$$NPV = P(AN | PN) = \frac{TN}{TN + FN} \quad (4.4)$$

- Specificity: the proportion of *true negative predictions* out of the total number of *actual negatives*. Also called *true negative rate*. The question is: *If actually negative, how likely is it to be predicted negative?*

$$\text{Specificity} = TNR = P(TN | AN) = \frac{TN}{TN + FP} \quad (4.5)$$

Out of this four metrics (precision, recall, NPV and specificity), we can derive their four complementary metrics:

- False Positive Rate (FPR): the proportion of *false positive predictions* out of the total number of *actual negatives*. Also called *false alarm rate*.

$$FPR = P(PF | AN) = \frac{FP}{FP + TN} = 1 - TNR \quad (4.6)$$

- False Discovery Rate (FDR): the proportion of *false positive predictions* out of the total number of *positive predictions*.

$$FDR = P(PF | PP) = \frac{FP}{TP + FP} = 1 - PPV \quad (4.7)$$

- False Omission Rate (FOR): the proportion of *false negative predictions* out of the total number of *negative predictions*.

$$FOR = P(PN | PN) = \frac{FN}{TN + FN} = 1 - NPV \quad (4.8)$$

- False Negative Rate (FNR): the proportion of *false negative predictions* out of the total number of *actual positives*. Also called *miss rate*.

$$FNR = P(PN | AP) = \frac{FN}{TP + FN} = 1 - TPR \quad (4.9)$$

Given that trade-offs between precision and recall exist, it is important to have single metrics that combines both of them. The following are some of the most common metrics that combine the metrics we have seen so far:

- F1 Score: the harmonic mean of precision and recall.

$$F1 = \frac{2}{\frac{1}{PPV} + \frac{1}{TPR}} = \frac{2 \cdot PPV \cdot TPR}{PPV + TPR} \quad (4.10)$$

- Fowlkes-Mallows index: the geometric mean of precision and recall.

$$FM = \sqrt{PPV \cdot TPR} \quad (4.11)$$

- Matthews Correlation Coefficient (MCC): a correlation coefficient between the actual and predicted classes.

$$MCC = \sqrt{TPR \cdot TNR \cdot PPV \cdot NPV} - \sqrt{FNR \cdot FPR \cdot FDR \cdot FOR} \quad (4.12)$$

It is the geometric mean of the basic metrics (TPR, TNR, PPV and NPV) minus the geometric mean of the complementary metrics (FNR, FPR, FDR and FOR). It ranges from -1 to 1 , where:

- 1 indicates a perfect classifier.
- 0 indicates a random classifier.
- -1 indicates a completely wrong classifier.

It is the most informative metric for evaluating the performance of a binary classifier, especially when the classes are imbalanced, as it the only one that takes into account the whole confusion matrix.

Other metrics that are commonly used to evaluate the performance of a classifier are:

- Prevalence: the proportion of actual positives in the dataset.

$$\text{Prevalence} = P(AP) = \frac{AP}{AP + AN} \quad (4.13)$$

- Balanced Accuracy: the average of the true positive rate and the true negative rate.

$$\text{Balanced Accuracy} = \frac{TPR + TNR}{2} \quad (4.14)$$

It is a better metric than accuracy when the classes are imbalanced, as it takes into account both the true positive rate and the true negative rate.

- Positive Likelihood Ratio (LR_+): the ratio of the true positive rate to the false positive rate.

$$LR_+ = \frac{TPR}{FPR} \quad (4.15)$$

It indicates how much more likely a positive test result is to be found in an actual positive case than in an actual negative case. The higher the LR_+ , the better the test is at identifying actual positives.

- Negative Likelihood Ratio (LR_-): the ratio of the false negative rate to the true negative rate.

$$LR_- = \frac{FNR}{TNR} \quad (4.16)$$

It indicates how much more likely a negative test result is to be found in an actual positive case than in an actual negative case. The lower the LR_- , the better the test is at identifying actual negatives.

- Diagnostic Odds Ratio (DOR): the ratio of the positive likelihood ratio to the negative likelihood ratio.

$$DOR = \frac{LR_+}{LR_-} \quad (4.17)$$

The higher the DOR, the better the test is at discriminating between actual positives and actual negatives.

- Informedness: the difference between the true positive rate and the false positive rate.

$$\text{Informedness} = \text{TPR} - \text{FPR} = \text{TPR} + \text{TNR} - 1 \quad (4.18)$$

- Markedness: the difference between the positive predictive value and the false discovery rate.

$$\text{Markedness} = \text{PPV} - \text{FDR} = \text{PPV} + \text{NPV} - 1 \quad (4.19)$$

- Prevalence Threshold (PT): the prevalence at which the positive likelihood ratio equals the negative likelihood ratio.

$$PT = \frac{\sqrt{\text{TPR} \cdot \text{FPR}} - \text{FPR}}{\text{TPR} - \text{FPR}} \quad (4.20)$$

Lastly, an important curve used to evaluate the performance of a binary classifier is the *Receiver Operating Characteristic (ROC) curve*, which plots the true positive rate (TPR) against the false positive rate (FPR) at various threshold settings using the same dataset. The area under the ROC curve (AUC) is a common metric used to summarize the performance of a binary classifier, where a higher AUC indicates a better performance.

- An ideal classifier would have all the points in the ROC curve at the top-left corner, which corresponds to a TPR of 1 and a FPR of 0, resulting in an AUC of 1.
- The bigger the AUC, the better the performance of the classifier.

4.2. Error and Uncertainty

When evaluating the performance of a machine learning model, it is important to take into account the error and uncertainty associated with the predictions. The different types of errors are:

- Blunders: errors caused by human carelessness, such as accidentally deleting data, mislabeling data, or using the wrong algorithm. These errors can be easily avoided by being careful and double-checking the work.
- Random Errors: uncontrollable errors that occur due to fluctuations in variables. They can be:
 - *Environmental*: caused by changes in the environment, such as temperature, humidity, etc.

- *Observational*: when the observer's judgment leads to random inaccuracies.
- Systematic Errors: errors that are identifiable and can be corrected. They can be:
 - *Instrumental*: caused by a flaw in the measurement instrument, such as a miscalibrated sensor.
 - *Theoretical*: caused by a flaw in the theoretical model, such as an incorrect assumption.
 - *Environmental*: caused by a consistent change in the environment, such as a change in the temperature that affects the measurements.
 - *Observational*: when the observer does not read the measurement instrument correctly, such as reading the wrong value on a scale.

However, an important trade-off is that no model is perfect, and there will always be some error associated with the predictions, as the data themselves are not perfect, and the model is just an approximation of reality. Therefore, it is important to evaluate the performance of a model using appropriate metrics that take into account the error and uncertainty associated with the predictions. Depending on the task, different metrics are used to evaluate the performance of a model.

- In classification tasks (prediction of discrete labels), the error measurement has already been covered in the previous section, where we have seen various metrics to evaluate the performance of a classifier.
- In regression tasks (prediction of continuous values), the error is usually measured using the following metrics, where the predicted values are denoted by $\hat{y}_i$ and the actual values are denoted by y_i :
 - Mean Absolute Error (MAE): the average of the absolute differences between the predicted values and the actual values.

$$MAE = \frac{1}{n} \sum_{i=1}^n |y_i - \hat{y}_i| \quad (4.21)$$

As an advantage, it is less sensitive to outliers than the mean squared error.

- Mean Squared Error (MSE): the average of the squared differences between the predicted values and the actual values.

$$MSE = \frac{1}{n} \sum_{i=1}^n (y_i - \hat{y}_i)^2 \quad (4.22)$$

As an disadvantage, it is more sensitive to outliers than the MAE, and it can be difficult to interpret the error in the original units of the data, as it is in squared units.

- Root Mean Squared Error (RMSE):

$$RMSE = \sqrt{MSE} \quad (4.23)$$

- Mean Absolute Percentage Error (MAPE): the average of the absolute percentage differences between the predicted values and the actual values.

$$MAPE = \frac{1}{n} \left(\sum_{i=1}^n \left| \frac{y_i - \hat{y}_i}{y_i} \right| \right) \cdot 100 \% \quad (4.24)$$

As an advantage, it is easy to interpret the error in terms of percentage, which can be more meaningful in some contexts. As a disadvantage, it can be undefined when any of the actual values are zero, and it can be heavily influenced by small actual values, leading to very large percentage errors.

4.3. Overfitting and Underfitting

Two common problems that can occur when training a machine learning model are overfitting and underfitting:

- Overfitting: occurs when a model learns the training data too well, *including the noise and outliers*, which results in a model that performs extremely well on the training data but poorly on unseen data, as it has lost the ability to generalize to new data.

Some common techniques to prevent overfitting are resampling methods (which will be covered later), early stopping or increasing the complexity of the model.

- Underfitting: occurs when a model is too simple to capture the underlying patterns in the data, which results in a model that performs poorly on both the training data and unseen data.

Some common techniques to prevent underfitting are increasing the complexity of the model, increasing the training duration or resampling methods.

Both overfitting and underfitting are directly related to the bias-variance trade-off, which is a fundamental concept in machine learning.

- Bias: the error introduced by approximating a real-world problem making incorrect assumptions. An algorithm with high bias may think that it is correctly modeling the data, but it is actually oversimplifying the problem.

A machine learning model with high bias pays very little attention to the training data and oversimplifies the model, which can lead to underfitting.

- Variance: the error introduced by the model's sensitivity to small fluctuations in the training data. An algorithm with high variance may fit the training data very well, but it may not generalize well to unseen data, as it has learned the noise and outliers in the training data.

A machine learning model with high variance pays a lot of attention to the training data and does not generalize well, which can lead to overfitting.

The bias-variance trade-off states that minimizing one of these two sources of error typically increases the other. In other words, as we increase the complexity of a model, its bias decreases but its variance increases, and vice versa. Therefore, it is important to find the right balance between bias and variance to achieve good generalization performance on unseen data.

4.3.1. No Free Lunch Theorem

In order to find that correct balance between bias and variance, we need to choose the right model for our data. However, the *No Free Lunch Theorem* states that there is no one model (or parameter setting) that works best for all problems. In other words, the performance of a model is highly dependent on the specific problem and the data it is applied to. Therefore, it is important to try different models and parameter settings to find the one that works best for our specific problem and data.

In order to find the best model and parameter settings, we can use a brute-force approach, where we try all possible combinations of models and parameters. However, the *curse of dimensionality* makes this approach infeasible, as the number of combinations grows exponentially with the number of models and parameters. Therefore, a more practical approach is to use a *trial and error* method, where we try a subset of models and parameter settings based on our intuition and experience, and then evaluate their performance using appropriate metrics to find the best one for our specific problem and data.

4.4. Resampling Methods

Resampling methods are techniques used to, from the available data, create new samples that can be used to train and evaluate machine learning models. These methods are particularly useful when the dataset is small, as they allow us to make the most out of the available data.

4.4.1. Data Augmentation

Data augmentation is a technique used to increase the size of the training dataset by creating new samples from the existing data. This can be done by applying various transformations to the data, such as rotation, scaling, flipping, etc. Data augmentation is commonly used in image classification tasks, where it can help to improve the performance of the model by providing it with more diverse examples to learn from.

4.4.2. Cross-Validation

Cross-validation is a technique used to evaluate the performance of a machine learning model by partitioning the data into multiple subsets, training the model on some of the subsets and evaluating it on the remaining subsets. Multiple techniques have been developed for cross-validation, which can be broadly categorized into two types: exhaustive and non-exhaustive cross-validation techniques.

Exhaustive Cross-Validation

Exhaustive cross-validation techniques involve evaluating the model on all possible combinations of training and test sets. These techniques include:

- Leave-One-Out: the model is trained on all the data except for one instance, which is used as the test set. This process is repeated for each instance in the dataset, and the performance of the model is averaged over all iterations.

If there are n instances in the dataset, this technique requires training the model n times, which can be computationally expensive for large datasets.

- Leave-P-Out: the model is trained on all the data except for p instances, which are used as the test set. This process is repeated for all possible combinations of p instances, and the performance of the model is averaged over all iterations.

If there are n instances in the dataset, this technique requires training the model $\binom{n}{p}$ times, which can be computationally expensive for large datasets and large values of p .

Since exhaustive cross-validation techniques can be computationally expensive, especially for large datasets, more practical approaches have been developed.

Non-Exhaustive Cross-Validation

Non-exhaustive cross-validation techniques involve evaluating the model on a subset of all possible combinations of training and test sets. These techniques include:

- K-Fold Cross-Validation: the data is partitioned into k subsets (or folds), where the model is trained on $k - 1$ folds and evaluated on the remaining fold. This process is repeated k times, with each fold used as the test set once, and the performance of the model is averaged over all iterations.

With k folds, this technique requires training the model k times, which is more computationally efficient than exhaustive cross-validation techniques, especially for large datasets.

- Holdout Method: the data is randomly split into a training set and a test set, where the model is trained on the training set and evaluated on the test set. This method is simple and computationally efficient, but it can be sensitive to how the data is split, as it may not be representative of the overall dataset.
- Repeated Random Subsampling: the data is randomly split into a training set and a test set multiple times, where the model is trained on the training set and evaluated on the test set for each split, and the performance of the model is averaged over all iterations. This repetition helps to mitigate the problems of the holdout method.
- Bootstrapping: the data is randomly sampled *with replacement* to create multiple training sets, where the model is trained on each training set and evaluated on the remaining data (called the out-of-bag samples), and the performance of the model is averaged over all iterations.

4.5. K-Nearest Neighbors (KNN)

KNN is a simple and intuitive machine learning algorithm used for different tasks, such as classification and regression. Its main idea is that, given a new data point, it will behave similarly to the data points that are closest to it in the feature space. The process is:

- Choosing a k value, which represents the number of nearest neighbors to consider.
- Calculating the distance between the new data point and all the data points in the training set, using a distance metric such as Euclidean distance, Manhattan distance, etc.
- Sort the distances and select the k nearest neighbors.
- Depending on the task, different strategies are used to make the prediction:
 - Classification: the predicted class is the majority class among the k nearest neighbors.
It is true that other approaches would also make sense, such as just stating the probability of the new data point belonging to each class based on the proportion of neighbors belonging to each class, or weighting the contribution of each neighbor based on their distance to the new data point, giving more weight to closer neighbors. However, they are not used.
 - Regression: the predicted value is the average of the values of the k nearest neighbors.
 - Outliers Detection: in order to detect if a value is an outlier, we can calculate the distance between the new data point and its k nearest neighbors, and if the average distance (weighted or not) is above a certain threshold, we can classify it as an outlier.

5. Genetic Algorithms

Genetic algorithms are a class of optimization algorithms inspired by the process of natural selection. They are used to find approximate solutions to optimization and search problems. The parallelism between the process of natural selection and the genetic algorithm is described in the following concepts:

- Chromosome: A representation of a solution to the problem. It is a data structure that encodes all the parameters of the solution.

They are often represented as strings of bits, but they can also be represented as arrays of numbers or other data structures depending on the problem being solved.

- Gene: A part of a chromosome that represents a specific parameter or feature of the solution.
- Alele: A specific value of a gene. They can be binary (0 or 1), discrete (a finite set of values), or continuous (a range of values).

A genetic algorithm typically consists of the following steps:

1. Initialization: A population of chromosomes is generated randomly or based on some heuristic. The size of the population will be constant throughout the algorithm.
2. Selection: The fitness of each chromosome is evaluated using a fitness function that measures how well the solution represented by the chromosome solves the problem. Chromosomes with higher fitness are more likely to be selected for reproduction.
3. Crossover: Pairs of selected chromosomes are combined to create offspring. This is done by exchanging parts of the chromosomes between the pairs.
4. Mutation: With a small probability, random changes are made to the genes of the offspring to introduce variation into the population.
5. Replacement: The new generation of chromosomes (offspring) replaces the old generation, and the process repeats from the selection step until a stopping criterion is met:
 - A solution with a satisfactory fitness level is found.
 - A maximum number of generations is reached.

- The population has converged (i.e., there is little variation in the chromosomes).

During the following sections, we will explore some of these steps in more detail.

5.1. Crossover

Crossover is a genetic operator used to combine the genetic information of two parent chromosomes to generate a new offspring chromosome. There are several types of crossover methods, including:

- Order-Based Crossover (OX2): Fixed positions are selected from the first parent, their values are copied to the offspring in the same positions, and the holes are filled with the corresponding values from the second parent.

Parent 1	A	A	B	B	A	A	C	C	A	A
Parent 2	C	C	A	B	A	B	B	A	A	A
Offspring	A	A	A	B	A	B	B	A	A	A

Tabla 5.1: Example of Order-Based Crossover (OX2), where the fixed positions are 0-1, 3-4 and 8.

- Position-Based Crossover (POS): Fixed positions are selected from the first parent. The values in those positions are copied at the start of the offspring, and the remaining values are filled with the start of the second parent.

Parent 1	A	A	B	B	A	A	C	C	A	A
Parent 2	C	C	A	B	A	B	B	A	A	A
Offspring	A	A	B	A	A	C	C	A	B	A

Tabla 5.2: Example of Position-Based Crossover (POS), where the fixed positions are 0-1, 3-4 and 8.

- Voting Crossover (VX):

For each gene, the value that appears most frequently among the parents is selected for the offspring. In case of a tie, one of the values is randomly selected.

This makes it a more general crossover method that can be applied to more than two parents, as it can take into account the values of all the parents when determining the value of each gene in the offspring.

Parent 1	A	A	B	B	A	A	C	C	A	A
Parent 2	C	C	A	B	A	B	B	A	A	A
Parent 3	A	A	A	B	A	A	C	C	A	A
Offspring	A	A	A	B	A	A	C	C	A	A

Tabla 5.3: Example of Voting Crossover (VX) with three parents.

■ Maximal Preservative Crossover (MPX):

An interval of genes is selected from the first parent and copied to the offspring (in the same positions). The remaining genes are filled with the values from the second parent, starting from the start of the interval.

Parent 1	A	A	B	B	A	A	C	C	A	A
Parent 2	C	C	A	B	A	B	B	A	A	A
Offspring	A	B	B	B	A	A	C	C	A	B

Tabla 5.4: Example of Maximal Preservative Crossover (MPX), where the selected interval is 2-7.

It should be noted that, if the interval selected in the first parent is too short, there may not be enough genes to fill the offspring. This should be controlled, as in some cases, chromosomes should not vary in length.

■ Alternating Positions Crossover (AP):

The offspring is created by alternating the genes of the two parents, but with two important constraints:

- Positions should be kept. If a gene is in the position i in offspring, it should be in the same position i in the parent from which it was taken.
- Genes can't be repeated in a chromosome.

This results in the following procedure to create the offspring:

1. The first gene of the offspring is taken from the first position of the first parent.
2. For every gene in the offspring, the next gene is taken from the other parent. If that gene is already in the offspring, the order of the parents is switched, and the next gene for that position is chosen from the other parent.
 - If that gene is also already in the offspring (which is not likely), then a mutation has to be performed, as there is no way to fill that position with a gene from the parents without repeating genes. This mutation can be done by randomly selecting a gene that is not already in the offspring and placing it in that position.
3. This process is repeated until the offspring is complete.

It should be noted that, if the parents are very similar, there may not be enough genes to fill the offspring without repeating genes. This should be controlled, as in some cases, chromosomes should not vary in length.

5.2. Mutation

Mutation is a genetic operator used to maintain genetic diversity within a population of chromosomes. It introduces random changes to the genes of offspring

chromosomes, which can help prevent premature convergence to local optima. There are several types of mutation types, as:

- Silent Mutation: A mutation that does not change the genotype of the chromosome. For example, if a gene is represented as a binary string, a silent mutation would be changing a 0 to another 0 or a 1 to another 1.
- Neutral Mutation: A mutation that changes the genotype of the chromosome but does not affect the phenotype (the observable characteristics of the solution).
- Conditional Mutation: A mutation that also changes the phenotype, but is still considered a valid solution to the problem.
- Letal Mutation: A mutation that results in a non-viable solution (e.g., a solution that violates constraints of the problem).

Depending on the problem being solved, different mutation methods will result in letal mutations, which should be avoided since they do not contribute to the search for optimal solutions. The choice of mutation method and the mutation rate (the probability of mutation occurring) can have a significant impact on the performance of a genetic algorithm. A high mutation rate can lead to excessive randomness and slow convergence, while a low mutation rate may not introduce enough diversity into the population, leading to premature convergence. There are different basic methods to perform mutation, such as:

- Deletion: A segment of the chromosome is removed.
- Insertion: A segment of the chromosome is selected and inserted into another position in the chromosome.
- Duplication: A segment of the chromosome is duplicated and inserted into another position in the chromosome.
- Inversion: A segment of the chromosome is reversed.

Using those, we can create more complex mutation methods, such as:

- Scramble Mutation: A segment of the chromosome is selected and its genes are randomly shuffled.
- Swap Mutation: Two genes in the chromosome are selected and their positions are swapped.

It is true that some of these mutation methods can change the length of the chromosome, which may not be desirable in certain problems where a fixed-length representation is required. This should be taken into account, as they could end up being letal mutations if the resulting chromosome is not a valid solution to the problem.

5.3. Selection

Selection is the process of choosing which chromosomes from the current population will be used to create the next generation. The selection process is based on the fitness of each chromosome, which is determined by a fitness function that evaluates how well the solution represented by the chromosome solves the problem. A correct balance between exploration and exploitation is crucial for the success of a genetic algorithm:

- Exploration: The ability of the algorithm to search through a wide range of solutions in the solution space. This is important to avoid getting stuck in local optima and to find the global optimum.
- Exploitation: The ability of the algorithm to focus on promising areas of the solution space that have already been explored. This is important to refine and improve solutions that are already good.

Two important concepts in selection are:

- Selection Pressure: The degree to which the selection process favors fitter chromosomes over less fit ones. High selection pressure can lead to faster convergence but may also increase the risk of premature convergence to local optima.
- Diversity: The variety of different chromosomes in the population. Maintaining diversity is important to ensure that the algorithm explores a wide range of solutions and does not get stuck in local optima.

There are several selection methods, including:

- Elitist Selection: The best (for instance, 10 %) chromosome(s) from the current population are directly copied to the next generation (without being subject to crossover or mutation), ensuring that the best solution is preserved.
- Steady State Selection: Only a small number of chromosomes (e.g., 30 %) are replaced in each generation, while the rest of the population remains unchanged. This allows for a gradual evolution of the population over time.

It should be noted that this approach is just a variation of elitist selection, where the portion of the “elite” is much larger than in the standard elitist selection.

- Tournament Selection: Fixed k chromosomes are randomly selected from the population, and the one with the highest fitness is chosen for reproduction. This process is repeated until the desired number of chromosomes is selected.
- Roulette Wheel Selection: Each chromosome is assigned a probability of selection proportional to its fitness. If f_i is the fitness of chromosome i , then:

$$P(i) = \frac{f_i}{\sum_{j=1}^N f_j}$$

where N is the total number of chromosomes in the population. It is seen as a roulette wheel where each chromosome occupies a portion of the wheel proportional to its fitness, and the wheel is spun to select chromosomes for reproduction. The process is repeated until the desired number of chromosomes is selected.

- Rank-Based Selection: Chromosomes are ranked based on their fitness, and selection probabilities are assigned based on their rank rather than their absolute fitness values. The roulette wheel selection method is then applied to these new probabilities. This can help to maintain diversity in the population and prevent premature convergence.

It should however be noted that the selection process may combine different methods, such as using elitist selection to preserve the best solutions while also applying tournament selection to select the remaining chromosomes needed for reproduction and reaching the desired population size for the next generation.

6. Exercises

6.0. Introduction

The Python part of this exercise is available in [this Jupyter Notebook](#).

Intelligence Tests

Ejercicio 1. Turing Test vs. Lovelace Test: Which test focuses on creativity and which on simulating conversation? How do these two tests work?

The Turing Test focuses on simulating conversation. It works by having a human evaluator engage in a natural language conversation with both a machine and a human without knowing which is which. If the evaluator cannot reliably distinguish the machine from the human, the machine is considered to have passed the Turing Test.

The Lovelace Test, on the other hand, focuses on creativity. It requires an AI to create something original (like a piece of art, music, or a story) that cannot be attributed to any human creator. The AI must be able to explain how it created the work and why it is original, demonstrating a level of creativity that goes beyond mere imitation.

Ejercicio 2. Why do many simple chatbots fail the Winograd Schema?

Many simple chatbots fail the Winograd Schema because they lack the necessary contextual understanding and common sense reasoning required to correctly interpret the ambiguous sentences used in the test. The Winograd Schema consists of sentences that have a pronoun with an ambiguous antecedent, and the correct interpretation depends on understanding the context and the relationships between the entities involved. Simple chatbots often rely on pattern matching or statistical methods rather than true comprehension, which leads to incorrect answers when faced with such nuanced language challenges.

Ejercicio 3. What is the main idea behind the Metzinger test for checking if an AI is self-aware, in simple terms? What is one thing that might make this test difficult to use for all types of AI?

The main idea behind the Metzinger test is to check if an AI can understand and describe its own internal processes and experiences, which would indicate self-awareness. One difficulty with this test is that it relies on the AI's ability to communicate its thoughts and feelings, which may not be possible for all types of AI,

especially those that do not have a natural language processing capability or a way to express their internal states effectively. Therefore, there is no universally applicable method to determine if an AI is self-aware, as it may depend on the specific design and capabilities of the AI in question.

6.1. Data Processing / Cleaning

The Python part of this exercise is available in [this Jupyter Notebook](#).

Data Filtering and Transforming

Ejercicio 6.1.1. Imagine you have a list of all the students in a school. You only want to look at the students in the 5th grade (data filtering). Then, you want to calculate the average age of those 5th graders (data transforming). Explain why you need both steps.

We first need to filter the data to focus only on the students in the 5th grade, as we are specifically interested in that group. This step allows us to narrow down our dataset to the relevant subset of students. After filtering, we need to transform the data by calculating the average age of those 5th graders. This transformation step is necessary to derive meaningful insights from the filtered data, as it provides us with a summary statistic (the average age) that can help us understand the characteristics of the 5th-grade students. Without filtering, we would be calculating the average age of all students, which would not give us the specific information we are looking for about the 5th graders.

Ejercicio 6.1.2. You have a list of toys that were sold in a store, including the toy's name and the price it sold for.

1. Give an example of a question you could answer by only looking at toys that cost more than 20 (data filtering).

A question that could be answered by data filtering would be: "Which toys that cost more than 20 euros were sold in the last month?" (Here, we filter the data by price greater than 20 euros and potentially by the sales date).

2. Give an example of something you could calculate or change about the toy prices (data transforming).

An example of data transformation would be calculating the average selling price of all toys or converting all prices from euros to another currency (e.g., US dollars) based on a specific exchange rate. Another transformation could be creating a new column indicating whether a toy is classified as "cheap" (e.g., < 15 euros), "mid-priced" (e.g., 15 euros – 30 euros), or "expensive" (> 30 euros) based on the selling price.

Data Understanding

Ejercicio 6.1.3. What is the difference between quantitative (numerical) and qualitative (categorical) data?

Quantitative data refers to numerical values that can be measured and quantified, such as height, weight, or age. Qualitative data, on the other hand, refers to categorical values that describe characteristics or attributes, such as color or gender. Quantitative data can be analyzed using mathematical operations, while qualitative data is typically analyzed using descriptive statistics or categorization.

Ejercicio 6.1.4. What does the abbreviation **NaN** mean in a dataset?

NaN stands for “Not a Number” and is used in datasets to represent missing or undefined values. It is also used to indicate that a value is not a valid number, such as the result of an undefined mathematical operation (e.g., division by zero). In data analysis, **NaN** values need to be handled appropriately, either by filling them with a specific value or dropping them.

Ejercicio 6.1.5. Briefly explain the difference between the mean and the median. Which value is more sensitive to outliers?

The mean is the average of a set of numbers, calculated by summing all the values and dividing by the count of values. The median is the middle value in a sorted list of numbers. The mean is more sensitive to outliers because it can be significantly affected by extremely high or low values, while the median is less affected as it only considers the middle value(s) and not the magnitude of all values.

Ejercicio 6.1.6. Calculate the quartiles for the following dataset: [10, 9, 1, 4, 3, 2, 5, 6, 6, 6, 3, 9].

First, we need to sort the dataset:

[1, 2, 3, 3, 4, 5, 6, 6, 6, 9, 9, 10]

The quartiles are then:

$$Q2 = \frac{6 + 5}{2} = 5,5$$
$$Q1 = \frac{3 + 3}{2} = 3$$
$$Q3 = \frac{6 + 9}{2} = 7,5$$

Data Cleaning

Ejercicio 6.1.7. Name two reasons why data is often dirty in the real world.

Data can be dirty due to:

- Human error during data entry, which can lead to typos, incorrect values, or missing data.
- Inconsistent data formats or structures, such as different date formats or varying units of measurement across datasets.

Ejercicio 6.1.8. What happens when you apply the `dropna()` function to a DataFrame?

The `dropna()` function removes any rows (or columns, if specified with the `axis=1` parameter) that contain missing values (**NaN**) from the DataFrame. The original DataFrame is not modified unless the `inplace=True` parameter is used.

This is a common data cleaning step to ensure that the dataset does not contain incomplete records that could affect analysis or modeling.

Ejercicio 6.1.9. Why do you scale (normalize) numerical data before feeding it into a machine learning model?

Scaling (normalizing) numerical data is important because many machine learning algorithms are sensitive to the scale of the input features. If the features have different ranges, the algorithm may give more weight to those with larger values, leading to biased results. Scaling helps to ensure that all features contribute equally to the model's learning process and can improve the convergence speed and performance of the model.

Ejercicio 6.1.10. Name two possible encodings and explain them using an example.

They are explained in the page 11.

Ejercicio 6.1.11. Describe three common challenges encountered during data preparation and explain a technique to mitigate each challenge.

- **Missing Data:** This can be mitigated by using techniques such as imputation (filling in missing values with the mean, median, or mode) or by dropping rows/columns with a high percentage of missing values.
- **Outliers:** Outliers can skew the results of analysis and modeling. They can be mitigated by using methods such as IQR to identify and either remove or transform outliers.
- **Inconsistent Data:** Inconsistent data can arise from different formats or units. This can be mitigated by standardizing the data format (e.g., converting all dates to a common format) and ensuring that all measurements are in the same units (e.g., converting all weights to kilograms).

Ejercicio 6.1.12. Explain the difference between data cleaning and data transformation. Provide an example of each.

Data Cleaning Data cleaning involves identifying and correcting errors or inconsistencies in the dataset to ensure that it is accurate and reliable. For example, removing duplicate entries from a customer database or filling in missing values in a sales dataset.

Data Transformation Data transformation involves converting data from one format or structure to another to make it suitable for analysis or modeling. For example, normalizing numerical features to a common scale or encoding categorical variables into numerical format using one-hot encoding.

Ejercicio 6.1.13. Why is it important to handle missing data appropriately? Discuss three different strategies for dealing with missing values and their potential drawbacks.

Handling missing data appropriately is crucial because it can significantly impact the results of analysis and modeling. If not addressed, missing data can lead to biased estimates, reduced statistical power, and inaccurate predictions. Three strategies for dealing with missing values are:

- Imputation: Filling in missing values with a specific value (e.g., mean, median, mode) can help maintain the dataset's size and structure. However, it can introduce bias if the imputed values do not accurately reflect the underlying distribution of the data.
- Deletion: Removing rows or columns with missing values can be simple but may lead to loss of information and reduced sample size.
- Model-based Imputation: Using statistical models to predict and fill in missing values based on other available data. This approach can be more accurate but is computationally intensive and may introduce additional complexity in model interpretation.

Ejercicio 6.1.14. What are outliers in a dataset and why can they be problematic? Describe three methods for detecting outliers.

Outliers are data points that significantly differ from the majority of the data. They can be problematic because they can skew the results of analysis and modeling, leading to inaccurate conclusions. Three methods for detecting outliers are:

- Z-score: This method identifies outliers by calculating the number of standard deviations a data point is from the mean. A common threshold is a Z-score of 3 or -3.
- Interquartile Range (IQR): This method identifies outliers by calculating the IQR (the difference between the third quartile and the first quartile) and defining outliers as data points that fall below $Q1 - 1,5 \cdot IQR$ or above $Q3 + 1,5 \cdot IQR$.
- Visual Methods: Box plots and scatter plots can visually reveal outliers in the data, allowing for easy identification of data points that deviate from the overall pattern.

Ejercicio 6.1.15. Explain the concept of data normalization or standardization. When would you prefer one over the other, and why is this a crucial step in many machine learning workflows?

Data normalization (scaling to a range) and standardization (scaling to have a mean of 0 and a standard deviation of 1) are techniques used to rescale numerical features. Normalization is preferred when the data does not follow a Gaussian distribution and when the algorithm does not assume any distribution. Standardization is preferred when the data follows a Gaussian distribution or when the algorithm assumes that the data is normally distributed. This step is crucial in machine learning workflows because it ensures that all features contribute equally to the model's learning process and can improve the convergence speed and performance of the model.




Figura 6.1: Directed graph representing the dependencies between lectures.

6.2. Search Algorithms

The Python part of this exercise is available in [this Jupyter Notebook](#).

Kahn's Algorithm (Topological Sorting)

You are responsible for the course planning at a university. For a specific module, there are several lectures that partially build upon each other. Your task is to find an order in which all lectures can be attended without attending a lecture before one of its prerequisites.

Lectures (Nodes): Math 1, Math 2, Computer Science 1, Computer Science 2, Databases, Algorithms, Software Development

Dependencies (directed edges “must be attended before”):

- Math 1 $\rightarrow$ Math 2
- Computer Science 1 $\rightarrow$ Computer Science 2
- Computer Science 1 $\rightarrow$ Algorithms
- Math 2 $\rightarrow$ Algorithms
- Computer Science 2 $\rightarrow$ Databases
- Algorithms $\rightarrow$ Software Development

Ejercicio 6.2.1. Create the graph. Represent the directed graph as an adjacency list, and for each node, note the in-degree (number of incoming edges).

The graph is depicted in Figure 6.1. The adjacency list and in-degrees are as follows:

- Math 1: Adjacent to [Math 2], In-degree = 0
- Math 2: Adjacent to [Algorithms], In-degree = 1
- Computer Science 1: Adjacent to [CS 2, Algorithms], In-degree = 0
- Computer Science 2: Adjacent to [Databases], In-degree = 1

- Databases: Adjacent to [], In-degree = 1
- Algorithms: Adjacent to [Software Development], In-degree = 2
- Software Development: Adjacent to [], In-degree = 1

Ejercicio 6.2.2. Apply Kahn’s Algorithm. Perform Kahn’s algorithm manually (or implement it in a programming language of your choice) to find a topological sorting of the lectures. Document each step:

1. Start with all nodes whose in-degree = 0.
2. Remove one of these nodes, add it to the order, and reduce the in-degrees of its neighbors.
3. Repeat until all nodes are processed.

The algorithm can be seen in the Table 6.1.

Ejercicio 6.2.3. Interpret the result. State the calculated order of the lectures, and determine if this order is unique. Justify your answer.

The calculated order of the lectures is:

Math 1 → Math 2 → Computer Science 1 → Computer Science 2 → Databases → Algorithms → Software Development

This order is not unique. For example, Computer Science 1 and Math 1 both have an in-degree of 0 at the start, so we could have chosen Computer Science 1 before Math 1, which would lead to a different valid topological order. The presence of multiple nodes with in-degree 0 at various steps allows for multiple valid topological sorts.

BFS vs DFS

Ejercicio 6.2.4. What are the key differences between BFS and DFS in terms of traversal strategy, data structures used, and typical applications?

Traversal Strategy: BFS explores all neighbors at the present depth before moving on to the nodes at the next depth level, while DFS explores as far as possible along each branch before backtracking.

Data Structures: BFS typically uses a queue to keep track of the next nodes to visit, while DFS uses a stack (either explicitly or via recursion).

Applications: BFS is often used for finding the shortest path in unweighted graphs, while DFS is useful for tasks like topological sorting, cycle detection, and solving puzzles that require exploring all possibilities (e.g., mazes).

Ejercicio 6.2.5. In what scenarios would you prefer BFS over DFS, and vice versa?

Prefer BFS: When you need to find the shortest path in an unweighted graph, when you want to explore all nodes at a certain depth before going deeper, or when the solution is likely to be found close to the root.

Tabla 6.1: Steps of Kahn's Algorithm for topological sorting of the lectures.

Step	Final Order	New In-degrees
0	[]	Math 1: 0 Math 2: 1 Computer Science 1: 0 Computer Science 2: 1 Databases: 1 Algorithms: 2 Software Development: 1
1	[Math 1]	Math 2: 0 Computer Science 1: 0 Computer Science 2: 1 Databases: 1 Algorithms: 2 Software Development: 1
2	[Math 1, Math 2]	Computer Science 1: 0 Computer Science 2: 1 Databases: 1 Algorithms: 1 Software Development: 1
3	[Math 1, Math 2, Computer Science 1]	Computer Science 2: 0 Databases: 1 Algorithms: 0 Software Development: 1
4	[M1, M2, CS1, CS2]	Databases: 0 Algorithms: 0 Software Development: 1
5	[M1, M2, CS1, CS2, Databases]	Algorithms: 0 Software Development: 1
6	[M1, M2, CS1, CS2, Databases, Algorithms]	Software Development: 0
7	[M1, M2, CS1, CS2, Databases, Algorithms, SD]	




Figura 6.2: Graph for Exercise 6.2.6.

Prefer DFS: When you want to explore all possible paths (e.g., backtracking problems), when the solution is likely to be found far from the root, or when you want to use less memory (DFS can be more memory-efficient than BFS in certain cases).

Ejercicio 6.2.6. Create a small graph as an example to practice this task (feel free to include a few intersections and cafés).

The graph is depicted in Figure 6.2.

Ejercicio 6.2.7 (Approach). Explain how you would find the café if you first searched all directly adjacent intersections (BFS), compared to simply walking straight down a street until you can go no further (DFS).

BFS Approach: Starting at the house (A), you would first check all the adjacent intersections (B and C). If you find the café at either of these intersections, you are done. If not, you would then check the neighbors of B (D) and C (E). If you find the café at D or E, you are done. If not, you would check the neighbors of D (E, which you wouldn't visit as you have already visited it) and E (F), where you would find the café at F.

DFS Approach: Starting at the house (A), you would choose one adjacent intersection to explore first (e.g., B). From B, you would go to D, and from D to E, and finally from E to F, where you would find the café. You would not check C at all in this approach, and you would only find the café after exploring a path with more intersections.

Ejercicio 6.2.8. Why does a queue help you search systematically in a circle around your starting point, while a stack tends to push you deeper into the structure?

A queue helps you search systematically in a circle around your starting point because it processes nodes in the order they were added. When you add all adjacent nodes to the queue, you will explore all nodes at the current depth before moving on to the next level. This ensures that you are exploring nodes in a breadth-first manner, which naturally expands outwards from the starting point.

In contrast, a stack processes nodes in a last-in, first-out (LIFO) order. When you add an adjacent node to the stack, it will be the next node you explore. This

means that you will go deeper into the structure along one path before backtracking to explore other paths. This depth-first approach can lead you to explore a long path before checking other adjacent nodes, which is why it tends to push you deeper into the structure.

Uniform Cost Search (UCS)

Ejercicio 6.2.9. Explain the concept of Uniform Cost Search. How does it differ from BFS and DFS?

Uniform Cost Search (UCS) is a search algorithm that expands the node with the lowest cumulative cost from the start node. It differs from BFS and DFS in that it takes into account the cost of reaching each node, rather than just the depth (BFS) or the path taken (DFS). UCS uses a priority queue to manage the nodes based on their cumulative cost, ensuring that it always expands the least costly path first. This makes UCS suitable for finding the optimal solution in weighted graphs, whereas BFS and DFS do not guarantee optimality in such cases.

Ejercicio 6.2.10. What data structure does Uniform Cost Search typically use to manage the search process?

Uniform Cost Search typically uses a priority queue to manage the search process. The priority queue allows UCS to always expand the node with the lowest cumulative cost first, ensuring that it finds the optimal solution in weighted graphs.

Ejercicio 6.2.11. When is Uniform Cost Search most appropriate?

Uniform Cost Search is most appropriate when the graph has weighted edges and you need to find the path with the minimum total cost from the start node to a goal node.

Ejercicio 6.2.12 (Approach). Suppose each street takes a different amount of time (traffic lights, inclines). In UCS, how do you decide which turn to take next?

In Uniform Cost Search, you would calculate the cumulative cost (time) to reach each adjacent intersection from your current location. You would then add these costs to a priority queue, which will allow you to always expand the node with the lowest cumulative cost next. This way, you ensure that you are always taking the path that has cost you the least effort so far, leading you towards the optimal route to your destination.

Ejercicio 6.2.13. How do you ensure that you always continue along the path that has cost you the least effort so far?

To ensure that you always continue along the path that has cost you the least effort so far, you would use a priority queue to manage the nodes based on their cumulative cost. Whenever you expand a node, you would calculate the cumulative cost to reach its neighbors and add them to the priority queue. The priority queue will automatically sort the nodes based on their cumulative cost, allowing you to always expand the node with the lowest cost next. This way, you are guaranteed to follow the path that has cost you the least effort at each step, leading you towards the optimal solution.

Dijkstra's Algorithm

Ejercicio 6.2.14. Describe Dijkstra's algorithm. What problem does it solve?

Dijkstra's algorithm is a graph search algorithm that finds the shortest path from a starting node to all other nodes in a weighted graph. It solves the problem of finding the minimum cumulative cost (or distance) from the start node to each of the other nodes in the graph. The algorithm uses a priority queue to keep track of the nodes to be explored, always expanding the node with the lowest cumulative cost first. This ensures that once a node's shortest path is determined, it will not change, allowing Dijkstra's algorithm to efficiently find the optimal paths in weighted graphs.

Ejercicio 6.2.15. How does Dijkstra's algorithm handle weighted graphs?

Dijkstra's algorithm handles weighted graphs by maintaining a priority queue that keeps track of the cumulative cost to reach each node from the starting node. When the algorithm expands a node, it calculates the cumulative cost to reach its neighbors by adding the weight of the edge connecting them to the cumulative cost of the current node. If this new cumulative cost is less than the previously recorded cost for that neighbor, the algorithm updates the cost and adds the neighbor to the priority queue for further exploration. This process ensures that Dijkstra's algorithm efficiently finds the shortest paths in weighted graphs.

Ejercicio 6.2.16. Compare and contrast Dijkstra's algorithm with Uniform Cost Search.

Dijkstra's algorithm and Uniform Cost Search (UCS) are the same algorithm, but UCS stops when it reaches the goal node, while Dijkstra's algorithm continues until it has found the shortest path to all nodes in the graph.

Ejercicio 6.2.17 (Procedure). Describe the step-by-step process Dijkstra uses to determine the distance from the starting point to each intersection.

Dijkstra's algorithm starts by initializing the distance to the starting point as 0 and the distances to all other nodes as infinity. It uses a priority queue to keep track of the nodes to explore, starting with the initial node. At each step, it expands the node with the lowest cumulative cost (distance) from the start node. For each of its neighbors, it calculates the cumulative cost to reach that neighbor by adding the weight of the edge connecting them to the cumulative cost of the current node. If this new cumulative cost is less than the previously recorded cost for that neighbor, it updates the cost and adds the neighbor to the priority queue for further exploration. This process continues until all nodes have been explored, resulting in the shortest distance from the starting point to each intersection.

Ejercicio 6.2.18. What do you do if you discover a shortcut to an intersection that you previously knew only via a longer route?

If you discover a shortcut to an intersection that you previously knew only via a longer route, you would update the cumulative cost (distance) for that intersection in the priority queue. This involves checking if the new cumulative cost is less than the previously recorded cost for that intersection. If it is, you would update the cost and add the intersection back into the priority queue for further exploration. This way, Dijkstra's algorithm ensures that it always finds the shortest path to each node, even if a shorter path is discovered after initially exploring a longer route.

A* Search

Ejercicio 6.2.19. Explain the A* search algorithm. What is the role of the heuristic function in A*?

A* search algorithm is an informed search algorithm that combines the features of Uniform Cost Search and a heuristic to efficiently find the shortest path from a start node to a goal node in a weighted graph. The role of the heuristic function in A* is to estimate the cost from the current node to the goal node. This heuristic helps guide the search process by prioritizing nodes that are likely to lead to the goal more quickly, thus reducing the number of nodes explored and improving efficiency compared to uninformed search algorithms like Uniform Cost Search.

Ejercicio 6.2.20. How does A* differ from Dijkstra's algorithm and Uniform Cost Search?

A* differs from Dijkstra's algorithm and Uniform Cost Search in that it incorporates a heuristic function to estimate the cost from the current node to the goal node. While Dijkstra's algorithm and Uniform Cost Search only consider the cumulative cost from the start node to the current node, A* combines this cumulative cost with the heuristic estimate to prioritize nodes that are more likely to lead to the goal. This allows A* to find the optimal path more efficiently in many cases, especially when the heuristic is well-designed.

Ejercicio 6.2.21. What are the conditions for a heuristic to be admissible and consistent in A*?

- Admissible: A heuristic is admissible if it never overestimates the true cost to reach the goal. In other words, for any node n , the heuristic value $h(n)$ must be less than or equal to the actual cost from n to the goal node.
- Consistent (Monotonic): A heuristic is consistent if for every node n and every successor n' of n , the estimated cost to reach the goal from n is less than or equal to the cost of reaching n' plus the estimated cost from n' to the goal, which is basically the triangle inequality. Consistency implies admissibility, but not vice versa.

Ejercicio 6.2.22 (Procedure). You see the church tower in the distance near the café. How does A* combine the distance already traveled with this straight-line estimate to shorten the route?

A* combines the distance already traveled (the cumulative cost from the start node to the current node) with the straight-line estimate (the heuristic value from the current node to the goal node) by calculating a total cost function $f(n) = g(n) + h(n)$, where $g(n)$ is the cumulative cost to reach node n and $h(n)$ is the heuristic estimate to reach the goal from node n . The algorithm prioritizes nodes with the lowest $f(n)$ value, which means it will explore paths that are both cost-effective so far and have a promising estimate to reach the goal. This allows A* to efficiently find a shorter route to the café by guiding the search towards nodes that are likely to lead to the goal more quickly.

Ejercicio 6.2.23. Why can't your guess (I think it's still 5 minutes) be longer than the actual distance, so that you're guaranteed to find the café via the fastest route?

Your guess (the heuristic estimate) cannot be longer than the actual distance because if it were, it would overestimate the cost to reach the goal. This would lead A^* to prioritize nodes that are actually farther from the goal, potentially causing it to explore less optimal paths and miss the fastest route. By ensuring that the heuristic is admissible (never overestimates), A^* guarantees that it will find the optimal path to the café, as it will always consider paths that are truly closer to the goal as more promising.

Tabla 6.2: Confusion matrix for the spam filter model.

	Actual: Spam	Actual: Not Spam
Model says: Spam	30 (TP)	10 (FP)
Model says: Not Spam	20 (FN)	40 (TN)

6.3. Machine Learning Algorithms

The Python part of this exercise is available in [this Jupyter Notebook](#).

The Intelligent Spam Filter

Imagine you have trained a model to distinguish important emails from annoying advertisements. To evaluate the quality of your filter, you ran a test on 100 emails and obtained the results shown in Table 6.2.

Confusion Matrix

Ejercicio 6.3.1. State the formulas for Accuracy, Precision, Recall, and F1-Score using TP , FP , TN , FN , and specify their respective ranges.

- Accuracy: It is ranged in $[0, 1]$.

$$\text{Accuracy} = \frac{TP + TN}{TP + FP + TN + FN}$$

- Precision: It is ranged in $[0, 1]$.

$$\text{Precision} = \frac{TP}{TP + FP}$$

- Recall: It is ranged in $[0, 1]$.

$$\text{Recall} = \frac{TP}{TP + FN}$$

- F1-Score: It is ranged in $[0, 1]$.

$$\text{F1-Score} = 2 \cdot \frac{\text{Precision} \cdot \text{Recall}}{\text{Precision} + \text{Recall}}$$

Ejercicio 6.3.2. Calculate the values using the table above. What do these values specifically say about the reliability of your filter in everyday use?

- Accuracy: $\frac{30 + 40}{30 + 10 + 40 + 20} = \frac{70}{100} = 0,7$.
- Precision: $\frac{30}{30 + 10} = \frac{30}{40} = 0,75$.
- Recall: $\frac{30}{30 + 20} = \frac{30}{50} = 0,6$.

$$\blacksquare \text{ F1-Score: } 2 \cdot \frac{0,75 \cdot 0,6}{0,75 + 0,6} = 2 \cdot \frac{0,45}{1,35} = 2 \cdot \frac{1}{3} = \frac{2}{3} \approx 0,67.$$

These values indicate that while the filter is reasonably accurate (70 %), it has a moderate precision (75 %) and a lower recall (60 %). This means that while most of the emails it identifies as spam are indeed spam, it misses a significant portion (40 %) of actual spam emails, which could lead to important emails being overlooked. In addition, the F1-Score of approximately 0.67 suggests that there is room for improvement in balancing precision and recall for better overall performance in everyday use.

Ejercicio 6.3.3. To get a complete picture, we will also use the Fowlkes-Mallows Index (FMI). What is the formula, and calculate the value.

$$\text{FMI} = \sqrt{\text{Precision} \cdot \text{Recall}} = \sqrt{0,75 \cdot 0,6} \approx 0,67$$

Ejercicio 6.3.4. Which value is more sensitive to the missed spam emails (FN) in your example?

The Recall is more sensitive to the missed spam emails (FN) because it directly measures the proportion of actual spam emails that were correctly identified by the model. A high number of false negatives (missed spam emails) will significantly decrease the Recall, indicating that the model is not effectively capturing all the spam emails in the dataset.

Ejercicio 6.3.5. Suppose your filter has an accuracy of 100 % on the training data, but only 70 % in the test table above. What phenomenon is at play here? Briefly explain why memorized emails hinder generalization.

The phenomenon at play here is called *overfitting*. Overfitting occurs when a model learns the training data too well, including its noise and outliers, to the point that it performs exceptionally on the training data but poorly on unseen test data. Memorized emails hinder generalization because the model has essentially “memorized” specific examples from the training set rather than learning the underlying patterns that can be applied to new, unseen data. As a result, when the model encounters new emails in the test set, it fails to generalize and correctly classify them, leading to a significant drop in accuracy.

Ejercicio 6.3.6. Explain the variance-bias dilemma: Which of these two factors predominates when the model begins to learn the noise in the data (overfitting), and which predominates when the model is oversimplified (underfitting)?

The variance-bias dilemma refers to the trade-off between two sources of error in machine learning models: bias and variance.

- **Bias:** Bias is the error introduced by approximating a real-world problem, which may be complex, by a simplified model. High bias can lead to underfitting, where the model is too simple to capture the underlying patterns in the data.
- **Variance:** Variance is the error introduced by the model’s sensitivity to small fluctuations in the training data. High variance can lead to overfitting, where the model learns not only the underlying patterns but also the noise in the training data.

Ejercicio 6.3.7. How does the complexity of the model change when you try to reduce the bias?

When you try to reduce the bias, you typically increase the complexity of the model. This is because reducing bias often involves adding more parameters or using a more flexible model that can capture more complex patterns in the data. However, increasing the complexity of the model can also lead to higher variance, which may result in overfitting if not managed properly.

Data Imbalance (Resampling)

Ejercicio 6.3.8. The needle-in-a-haystack problem: Your dataset contains 9900 normal emails and only 100 spam emails. Explain why a model without resampling tends to simply always predict Not Spam. What would the recall value be in this extreme case?

In this extreme case, a model without resampling would likely learn to predict Not Spam for all emails because it would achieve a high accuracy of 99% by doing so (9900 out of 10000 emails are Not Spam). However, this approach completely ignores the minority class (Spam), leading to a recall value of 0% for the Spam class. This is because the model would fail to identify any of the actual spam emails, resulting in zero true positives (TP) and thus a recall of:

$$\text{Recall} = \frac{TP}{TP + FN} = \frac{0}{0 + 100} = 0$$

Resampling techniques are crucial to address this imbalance and allow the model to learn to identify spam emails effectively. Some options include oversampling the minority class or undersampling the majority class to create a more balanced dataset for training.

Ejercicio 6.3.9. Why is it crucial to apply resampling to the training data and not to the test data? What would happen to the validity of your metrics if the test table were artificially balanced?

It is crucial to apply resampling only to the training data because the test data should reflect the real-world distribution of classes to provide an accurate evaluation of the model's performance. If the test table were artificially balanced, it would not represent the actual conditions under which the model will operate, leading to misleading metrics. For instance, if the test set is balanced, the model might appear to perform well in terms of recall and precision for both classes, but in reality, it may struggle to identify spam emails in a real-world scenario where they are much less frequent. This would compromise the validity of the metrics and give a false sense of confidence in the model's performance.

Automatic Fruit Sorting (kNN)

You are using a sensor that classifies fruit based on two features: weight (x_1) and hardness (x_2).

The k-Nearest-Neighbors Algorithm

Ejercicio 6.3.10. An unknown piece of fruit lands on the conveyor belt. Briefly describe the three algorithmic steps that kNN now performs to determine whether it is an apple or a pear.

- Step 1: Calculate Distances: The algorithm calculates the distance between the unknown fruit and all the known fruits in the training dataset using a distance metric.
- Step 2: Identify Neighbors: The algorithm identifies the k nearest neighbors (the k closest known fruits) based on the calculated distances.
- Step 3: Make a Prediction: The algorithm makes a prediction for the unknown fruit by taking a majority vote among the k nearest neighbors. The class (apple or pear) that appears most frequently among the neighbors is assigned to the unknown fruit.

Ejercicio 6.3.11. What are the formulas for the Euclidean distance and the Manhattan distance between two points $P(x_1, x_2)$ and $Q(y_1, y_2)$?

The formulas for the distances are as follows:

- Euclidean Distance:

$$d_{\text{Euclidean}}(P, Q) = \sqrt{(x_1 - y_1)^2 + (x_2 - y_2)^2}$$

- Manhattan Distance:

$$d_{\text{Manhattan}}(P, Q) = |x_1 - y_1| + |x_2 - y_2|$$

Ejercicio 6.3.12. The new fruit has the coordinates $(5, 2)$. A known reference apple is located at $(10, 5)$. Calculate the distance using both of the above-mentioned distance methods.

- Euclidean Distance:

$$d_{\text{Euclidean}}((5, 2), (10, 5)) = \sqrt{(5 - 10)^2 + (2 - 5)^2} = \sqrt{25 + 9} = \sqrt{34} \approx 5,83$$

- Manhattan Distance:

$$d_{\text{Manhattan}}((5, 2), (10, 5)) = |5 - 10| + |2 - 5| = 5 + 3 = 8$$

k-Nearest Neighbors

Ejercicio 6.3.13. What are the fundamental differences in the operating principles of kNN, k-Means, and k-Medians, and what types of tasks are they typically used for (classification, regression, clustering)?

Ejercicio 6.3.14. How exactly does kNN work step by step?

1. Distance Calculation: For a given new data point, the algorithm calculates the distance between this point and all the points in the training dataset using a chosen distance metric (e.g., Euclidean, Manhattan).

2. Neighbor Identification: The algorithm identifies the k nearest neighbors to the new data point based on the calculated distances.
3. Prediction: The algorithm makes a prediction for the new data point depending on the task:
 - For classification tasks, it assigns the class that is most common among the k nearest neighbors.
 - For regression tasks, it calculates the average (or median) of the target values of the k nearest neighbors and assigns this value to the new data point.

Ejercicio 6.3.15. What distance metrics do you know, and provide their mathematical forms?

- Euclidean Distance:

$$d_{\text{Euclidean}}(P, Q) = \sqrt{\sum_{i=1}^n (x_i - y_i)^2}$$

- Manhattan Distance:

$$d_{\text{Manhattan}}(P, Q) = \sum_{i=1}^n |x_i - y_i|$$

- Minkowski Distance:

$$d_{\text{Minkowski}}(P, Q) = \sqrt[p]{\sum_{i=1}^n |x_i - y_i|^p}$$

where p is a parameter that can be adjusted to obtain different distance metrics (e.g., $p = 1$ for Manhattan, $p = 2$ for Euclidean).

Ejercicio 6.3.16. What are the advantages and disadvantages of kNN, k-Means, and k-Medians in terms of robustness to outliers, computational effort, and interpretability of results?

Ejercicio 6.3.17. How do you choose the optimal value for “k” in kNN, k-Means, and k-Medians, and what methods are there to evaluate the performance of the models?

Ejercicio 6.3.18. In what scenarios would k-Medians be preferable to k-Means, and what specific challenges arise in the implementation and application of k-Medians?

6.4. Genetic Algorithms

The Python part of this exercise is available in [this Jupyter Notebook](#).

Imagine a delivery driver who needs to visit a set of cities and return to the starting city. The goal is to find the shortest possible route that visits each city exactly once. This is a classic optimization problem known as the Traveling Salesperson Problem (TSP).

Genetic Algorithm Concepts

Ejercicio 6.4.1. Explain the fundamental concepts of genetic algorithms, including population, fitness function, selection, crossover, and mutation.

Genetic algorithms are a type of optimization algorithm inspired by the process of natural selection. They work by maintaining a population of candidate solutions, which evolve over time through selection, crossover, and mutation.

- Population: A set of candidate solutions to the optimization problem. Each solution is often represented as a chromosome (e.g., a string of bits, a permutation, etc.).
- Fitness Function: A function that evaluates the quality of each candidate solution. It assigns a fitness score based on how well the solution solves the problem.
- Selection: The process of choosing candidate solutions from the population to create offspring for the next generation. Common selection methods include roulette wheel selection, tournament selection, and rank-based selection.
- Crossover: A genetic operator that combines two parent solutions to produce one or more offspring. The crossover operator is designed to exchange information between the parents, potentially creating better solutions.
- Mutation: A genetic operator that introduces random changes to a candidate solution. Mutation helps maintain genetic diversity in the population and allows the algorithm to explore new areas of the solution space.

Ejercicio 6.4.2. How do genetic algorithms differ from traditional optimization algorithms?

While traditional optimization algorithms (like gradient descent, linear programming, etc.) often work with a single solution and improve it iteratively, genetic algorithms maintain a population of solutions and use stochastic processes to explore the solution space.

Ejercicio 6.4.3. What are the advantages and disadvantages of using genetic algorithms for optimization problems?

- Advantages:
 - Can handle complex, non-linear, and multi-modal optimization problems.

- Does not require gradient information, making it suitable for problems where the fitness function is not differentiable.
- Can escape local optima due to its stochastic nature.
- Disadvantages:
 - Can be computationally expensive, especially for large populations and many generations.
 - May require careful tuning of parameters (population size, mutation rate, etc.) for good performance.
 - No guarantee of finding the global optimum.

TSP Representation

Ejercicio 6.4.4. Explain how to define a fitness function for the TSP that evaluates the quality of a route.

A suitable fitness function for the TSP can be defined as the inverse of the total distance of the route. For example, if the total distance of a route is D , the fitness can be calculated as:

$$\text{Fitness} = \frac{1}{D}$$

This way, shorter routes will have higher fitness values, and the genetic algorithm will be incentivized to evolve towards shorter routes.

Genetic Operators for TSP

Ejercicio 6.4.5. Describe suitable crossover and mutation operators for the TSP. Explain why standard crossover and mutation operators might not be effective.

For the TSP, standard crossover and mutation operators (like one-point crossover or bit-flip mutation) are not effective because they can produce invalid routes (e.g., duplicate cities or missing cities). Instead, specialized operators that preserve the permutation structure of the solution are needed. Examples of crossover operators suitable for TSP include:

- Variant of Ordered Crossover (OX): A subrange of the first parent is copied to the child (in the same positions), and the remaining positions are filled with values from the second parent. The variant considers that if a value from the second parent is already in the child, it is skipped until a non-duplicate value is found.

Examples of mutation operators suitable for TSP include:

- Swap Mutation: Two cities in the route are selected and their positions are swapped.
- Inversion Mutation: A segment of the route is selected and reversed.

Ejercicio 6.4.6. Discuss the importance of maintaining valid routes (permutations) during crossover and mutation.

In the TSP, each candidate solution is a permutation of cities. It is crucial to maintain valid routes during crossover and mutation to ensure that each city is visited exactly once. Standard crossover and mutation operators might produce invalid routes (e.g., duplicate cities or missing cities), which would not be meaningful solutions to the TSP. Therefore, specialized operators that preserve the permutation structure are necessary to ensure the integrity of the solutions. Invalid routes would lead to incorrect fitness evaluations and hinder the convergence of the genetic algorithm towards optimal solutions.

Ejercicio 6.4.7. Perform the Maximum Preservative Crossover (MPX) for the two chromosomes **bcabbbbc** and **acabccbb** using the obtained segment: 1 - 4 (0 is the first position), and use the deletion mutation operator.

The Maximum Preservative Crossover (MPX) involves selecting a segment from the first parent and preserving it in the child, while filling the remaining positions with genes from the second parent from the selected segment. For the given chromosomes **bcabbbbc** and **acabccbb**, we select the segment from position 1 to 4 (inclusive) from the first parent, which gives us the segment **cabb**. We then fill the remaining positions with genes from the second parent. The process is shown in Table 6.3.

Parent 1	B	C	A	B	B	B	B	C
Parent 2	A	C	A	B	C	C	B	B
Offspring	C	C	A	B	B	A	B	C

Tabla 6.3: MPX crossover for the given chromosomes and segment 1 - 4.

After performing the MPX crossover, we obtain the offspring **ccabbabc**. Next, we apply the deletion mutation operator, which involves randomly deleting a gene from the offspring. For example, if we randomly select the gene at position 1 (the second “c”), we would delete it, resulting in the mutated offspring **cabbabc**. It should be noted that this mutation may not be valid for some problems, as the resulting chromosome does not have the same length as the original chromosomes.