行星关节模组 / INTEGRATED PLANETARY JOINT MODULE

型号Model	LZ4610N（非中空）Non-hollow	LZ4605N（非中空）Non-hollow	LZ5710N（非中空）Non-hollow	LZ5740N（非中空）Non-hollow	LZ5735N / NP（非中空）Non-hollow	LZ807.75N（非中空）Non-hollow	LZ8025CN（非中空）Non-hollow	LZ10028CH（中空）Hollow-shaft	LZ12028CH（中空）Hollow-shaft	LZ10028CHB（中空带刹车）Hollow-shaft brakes	LZ12028CHB（中空带刹车）Hollow-shaft brakes
减速器类型Reducer Type	行星Planetary	行星Planetary	行星Planetary	行星Planetary	行星Planetary	行星Planetary	行星Planetary	行星Planetary	行星Planetary	行星Planetary	行星Planetary
尺寸Dimensions 直径X高度(mm)	⌀46X38	⌀46X38	⌀57X46	⌀57X53	⌀57X59.5 / ⌀57X65.5	⌀78.5X49.5	⌀80X61	⌀100X68	⌀120X78	⌀100X94.2	⌀120X87
减速比Gear Ratio	10	5	10	40	35	7.75	25	28	28	28	28
额定扭矩Rated Torque(N·m)	0.85Nm	0.43Nm	2.75Nm	9Nm	12Nm / 25Nm	6Nm	25Nm	60Nm	120Nm	60Nm	120Nm
峰值扭矩peak torque(N·m)	2.55Nm	1.4Nm	10Nm	28Nm	36Nm / 75Nm	18Nm	75Nm	200Nm	360Nm	200Nm	360Nm
磁编码器Magnetic Encoder	磁编/双编Dual Encoder	磁编/双编Dual Encoder	磁编/双编Dual Encoder	磁编/双编Dual Encoder	磁编/双编Dual Encoder	磁编/双编Dual Encoder	磁编/双编Dual Encoder	磁编/双编Dual Encoder	磁编/双编Dual Encoder	磁编/双编Dual Encoder	磁编/双编Dual Encoder
额定功率rated power（W）	17	4.5	40	30	50 / 210	226	314	471	1005	471	1005
额定电压Rated Voltage (V)	DC48V	DC48V	DC48V	DC48V	DC48V	DC48V	DC48V	DC48V	DC48V	DC48V	DC48V
通讯方式Communication Mode	CANFD	CANFD	CANFD	CANFD	CANFD	CANFD	CANFD	CANFD/Ether CAT	CANFD/Ether CAT	CANFD/Ether CAT	CANFD/Ether CAT
使用温度范围 Operating Temperature Range(°C)	-20 ~ 60℃	-20 ~ 60℃	-20 ~ 60℃	-20 ~ 60℃	-20 ~ 60℃	-20 ~70℃	-20 ~70℃	-20 ~ 80℃	-20 ~ 80℃	-20 ~ 80℃	-20 ~ 80℃
*防护等级Protection level	IP54	IP54	IP64	IP54	IP54	IP54	IP54	IP54	IP54	IP54	IP54
空载转速No-load Speed (rpm)	300	200	280	72	102	410	150	110	105	110	105
额定转速Rated Speed (rpm)	180	100	140	36	80	360	120	75	80	75	80
额定电流 Rated Current(Apk)	0.95	0.95	3	3	6	5.6	10.7	19.5	29.7	19.5	29.7
峰值电流Peak Current (Apk)	3.2	3.2	9	9	18	20.8	30	63	105	63	105
背隙 Backlash(arcmin)	≤8arcmin	≤8arcmin	≤8arcmin	≤15arcmin	≤15arcmin	≤8arcmin	≤15arcmin	≤15arcmin	≤15arcmin	≤15arcmin	≤15arcmin
电机反电势 / 反电动势常数Back-EMF Constant	6.4V/krpm	6.4V/krpm	7.1V/krpm	7.1V/krpm	7.5V/krpm / 9.35V/krpm	12.2Vrms/krpm	8.8Vrms/krpm	9Vrms/krpm	10.6V/krpm	9Vrms/krpm	10.6V/krpm
转矩常数Torque Constant	0.106Nm/A	0.106Nm/A	0.1Nm/A	0.1Nm/A	0.124Nm/A / 0.15Nm/A	0.157Nm/A	0.14Nm/A	0.15Nm/A	0.17Nm/A	0.15Nm/A	0.17Nm/A
极数Stage Count	14	14	28	28	20	28	20	42	42	42	42
工作噪音Working Noise(dB) 1m测试	≤55	≤55	≤55	≤58	≤60	≤65	≤65	≤68	≤70	≤68	≤70
重量Weight（g）	170	170	300	360	450 / 480	560	815	1600	2270	2200	2900
*刹车brake (N.m)	不带刹车（No brakes）									4.5	4.5

备注：*带刹车长度重量可能有变化，具体以出图为准The length and weight with brakes may vary; the exact dimensions are subject to the final drawing

*防护等级可选长度略有变化，具体以出图为准The optional length of the protection level may vary slightly, please refer to the diagram for details