

CS 228 : Logic in Computer Science

S. Krishna

First-Order Logic : Syntax

First Order Logic

- ▶ A formalism to specify properties of mathematical structures like graphs, partial orders, words, groups, rings, . . . , and the world at large!

First Order Logic

- ▶ A formalism to specify properties of mathematical structures like graphs, partial orders, words, groups, rings, . . . , and the world at large!
- ▶ Every dad is older than his child

First Order Logic

- ▶ A formalism to specify properties of mathematical structures like graphs, partial orders, words, groups, rings, . . . , and the world at large!
- ▶ Every dad is older than his child
- ▶ Every vertex has atleast two outgoing edges

First Order Logic

- ▶ A formalism to specify properties of mathematical structures like graphs, partial orders, words, groups, rings, . . . , and the world at large!
- ▶ Every dad is older than his child
- ▶ Every vertex has atleast two outgoing edges
- ▶ There is exactly one vertex with 3 outgoing edges

First Order Logic

- ▶ A formalism to specify properties of mathematical structures like graphs, partial orders, words, groups, rings, . . . , and the world at large!
- ▶ Every dad is older than his child
- ▶ Every vertex has atleast two outgoing edges
- ▶ There is exactly one vertex with 3 outgoing edges
- ▶ Atleast 5 students scored more than 90 marks in a class of 50

First Order Logic

- ▶ A formalism to specify properties of mathematical structures like graphs, partial orders, words, groups, rings, . . . , and the world at large!
- ▶ Every dad is older than his child
- ▶ Every vertex has atleast two outgoing edges
- ▶ There is exactly one vertex with 3 outgoing edges
- ▶ Atleast 5 students scored more than 90 marks in a class of 50
- ▶ All words starting with the letter a , ending with the letter b , have even length

Signatures

- ▶ A **vocabulary** or **signature** τ is a set consisting of
 - ▶ constants c_1, c_2, \dots
 - ▶ Relation symbols R_1, R_2, \dots , each with some arity k , denoted R_i^k
- ▶ We look at finite signatures
- ▶ $\tau = (E^2, F^3)$ is a finite signature with two relations, E with arity 2 and F with arity 3

Symbols in First Order Logic

Formulae of FO, over signature τ , are sequences of symbols, where each symbol is one of the following:

Symbols in First Order Logic

Formulae of FO, over signature τ , are sequences of symbols, where each symbol is one of the following:

- ▶ The symbol \perp called **false**

Symbols in First Order Logic

Formulae of FO, over signature τ , are sequences of symbols, where each symbol is one of the following:

- ▶ The symbol \perp called **false**
- ▶ An element of the infinite set $\mathcal{V} = \{x_1, x_2, \dots\}$ of **variables**

Symbols in First Order Logic

Formulae of FO, over signature τ , are sequences of symbols, where each symbol is one of the following:

- ▶ The symbol \perp called **false**
- ▶ An element of the infinite set $\mathcal{V} = \{x_1, x_2, \dots\}$ of **variables**
- ▶ Constants and relations from τ

Symbols in First Order Logic

Formulae of FO, over signature τ , are sequences of symbols, where each symbol is one of the following:

- ▶ The symbol \perp called **false**
- ▶ An element of the infinite set $\mathcal{V} = \{x_1, x_2, \dots\}$ of **variables**
- ▶ Constants and relations from τ
- ▶ The symbol \rightarrow called **implication**

Symbols in First Order Logic

Formulae of FO, over signature τ , are sequences of symbols, where each symbol is one of the following:

- ▶ The symbol \perp called **false**
- ▶ An element of the infinite set $\mathcal{V} = \{x_1, x_2, \dots\}$ of **variables**
- ▶ Constants and relations from τ
- ▶ The symbol \rightarrow called **implication**
- ▶ The symbol \forall called the **universal quantifier**

Symbols in First Order Logic

Formulae of FO, over signature τ , are sequences of symbols, where each symbol is one of the following:

- ▶ The symbol \perp called **false**
- ▶ An element of the infinite set $\mathcal{V} = \{x_1, x_2, \dots\}$ of **variables**
- ▶ Constants and relations from τ
- ▶ The symbol \rightarrow called **implication**
- ▶ The symbol \forall called the **universal quantifier**
- ▶ The symbols (and) called **paranthesis**

Well formed Formulae

A well-formed formula (wff) over a signature τ is inductively defined as follows:

Well formed Formulae

A well-formed formula (wff) over a signature τ is inductively defined as follows:

- ▶ \perp is a wff

Well formed Formulae

A well-formed formula (wff) over a signature τ is inductively defined as follows:

- ▶ \perp is a wff
- ▶ If t_1, t_2 are either variables or constants in τ , then $t_1 = t_2$ is a wff

Well formed Formulae

A well-formed formula (wff) over a signature τ is inductively defined as follows:

- ▶ \perp is a wff
- ▶ If t_1, t_2 are either variables or constants in τ , then $t_1 = t_2$ is a wff
- ▶ If t_i is either a variable or a constant, for $1 \leq i \leq k$ and R is a k -ary relation symbol in τ , then $R(t_1, \dots, t_k)$ is a wff

Well formed Formulae

A well-formed formula (wff) over a signature τ is inductively defined as follows:

- ▶ \perp is a wff
- ▶ If t_1, t_2 are either variables or constants in τ , then $t_1 = t_2$ is a wff
- ▶ If t_i is either a variable or a constant, for $1 \leq i \leq k$ and R is a k -ary relation symbol in τ , then $R(t_1, \dots, t_k)$ is a wff
- ▶ If φ and ψ are wff, then $\varphi \rightarrow \psi$ is a wff

Well formed Formulae

A well-formed formula (wff) over a signature τ is inductively defined as follows:

- ▶ \perp is a wff
- ▶ If t_1, t_2 are either variables or constants in τ , then $t_1 = t_2$ is a wff
- ▶ If t_i is either a variable or a constant, for $1 \leq i \leq k$ and R is a k -ary relation symbol in τ , then $R(t_1, \dots, t_k)$ is a wff
- ▶ If φ and ψ are wff, then $\varphi \rightarrow \psi$ is a wff
- ▶ If φ is a wff and x is a variable, then $(\forall x)\varphi$ is a wff

Logical Abbreviations : Boolean Connectives

- ▶ $\neg\varphi = \varphi \rightarrow \perp$
- ▶ $\top = \neg\perp$
- ▶ $\varphi \vee \psi = \neg\varphi \rightarrow \psi$
- ▶ $\varphi \wedge \psi = \neg(\neg\varphi \vee \neg\psi)$
- ▶ $\exists x.\varphi = \neg(\forall x.\neg\varphi)$
- ▶ Precedence of operators : $\neg > \wedge > \vee > \rightarrow > \forall$

An Example

Consider the signature $\tau = \{R\}$ where R is a binary relation. The following are FO formulae over this signature.

An Example

Consider the signature $\tau = \{R\}$ where R is a binary relation. The following are FO formulae over this signature.

- ▶ $\forall x R(x, x)$

An Example

Consider the signature $\tau = \{R\}$ where R is a binary relation. The following are FO formulae over this signature.

- ▶ $\forall x R(x, x)$ Reflexivity

An Example

Consider the signature $\tau = \{R\}$ where R is a binary relation. The following are FO formulae over this signature.

- ▶ $\forall x R(x, x)$ Reflexivity
- ▶ $\forall x (R(x, x) \rightarrow \perp)$

An Example

Consider the signature $\tau = \{R\}$ where R is a binary relation. The following are FO formulae over this signature.

- ▶ $\forall x R(x, x)$ Reflexivity
- ▶ $\forall x (R(x, x) \rightarrow \perp)$ Irreflexivity

An Example

Consider the signature $\tau = \{R\}$ where R is a binary relation. The following are FO formulae over this signature.

- ▶ $\forall x R(x, x)$ Reflexivity
- ▶ $\forall x (R(x, x) \rightarrow \perp)$ Irreflexivity
- ▶ $\forall x \forall y (R(x, y) \rightarrow R(y, x))$

An Example

Consider the signature $\tau = \{R\}$ where R is a binary relation. The following are FO formulae over this signature.

- ▶ $\forall x R(x, x)$ Reflexivity
- ▶ $\forall x (R(x, x) \rightarrow \perp)$ Irreflexivity
- ▶ $\forall x \forall y (R(x, y) \rightarrow R(y, x))$ Symmetry

An Example

Consider the signature $\tau = \{R\}$ where R is a binary relation. The following are FO formulae over this signature.

- ▶ $\forall x R(x, x)$ Reflexivity
- ▶ $\forall x (R(x, x) \rightarrow \perp)$ Irreflexivity
- ▶ $\forall x \forall y (R(x, y) \rightarrow R(y, x))$ Symmetry
- ▶ $\forall x \forall y (R(x, y) \rightarrow (R(y, x) \rightarrow (x = y)))$

An Example

Consider the signature $\tau = \{R\}$ where R is a binary relation. The following are FO formulae over this signature.

- ▶ $\forall x R(x, x)$ Reflexivity
- ▶ $\forall x (R(x, x) \rightarrow \perp)$ Irreflexivity
- ▶ $\forall x \forall y (R(x, y) \rightarrow R(y, x))$ Symmetry
- ▶ $\forall x \forall y (R(x, y) \rightarrow (R(y, x) \rightarrow (x = y)))$ Anti-symmetry

An Example

Consider the signature $\tau = \{R\}$ where R is a binary relation. The following are FO formulae over this signature.

- ▶ $\forall x R(x, x)$ Reflexivity
- ▶ $\forall x (R(x, x) \rightarrow \perp)$ Irreflexivity
- ▶ $\forall x \forall y (R(x, y) \rightarrow R(y, x))$ Symmetry
- ▶ $\forall x \forall y (R(x, y) \rightarrow (R(y, x) \rightarrow (x = y)))$ Anti-symmetry
- ▶ $\forall x \forall y \forall z (R(x, y) \rightarrow (R(y, z) \rightarrow R(x, z)))$

An Example

Consider the signature $\tau = \{R\}$ where R is a binary relation. The following are FO formulae over this signature.

- ▶ $\forall x R(x, x)$ Reflexivity
- ▶ $\forall x (R(x, x) \rightarrow \perp)$ Irreflexivity
- ▶ $\forall x \forall y (R(x, y) \rightarrow R(y, x))$ Symmetry
- ▶ $\forall x \forall y (R(x, y) \rightarrow (R(y, x) \rightarrow (x = y)))$ Anti-symmetry
- ▶ $\forall x \forall y \forall z (R(x, y) \rightarrow (R(y, z) \rightarrow R(x, z)))$ Transitivity

First-Order Logic : Semantics

Structures

- ▶ A structure \mathcal{A} of signature τ consists of

Structures

- ▶ A structure \mathcal{A} of signature τ consists of
 - ▶ A non-empty set A or $u(\mathcal{A})$ called the **universe**

Structures

- ▶ A structure \mathcal{A} of signature τ consists of
 - ▶ A non-empty set A or $u(\mathcal{A})$ called the **universe**
 - ▶ For each constant c in the signature τ , a fixed element $c_{\mathcal{A}}$ is assigned from the universe A

Structures

- ▶ A structure \mathcal{A} of signature τ consists of
 - ▶ A non-empty set A or $u(\mathcal{A})$ called the **universe**
 - ▶ For each constant c in the signature τ , a fixed element $c_{\mathcal{A}}$ is assigned from the universe A
 - ▶ For each k -ary relation R^k in the signature τ , a set of k -tuples from A^k is assigned to $R^{\mathcal{A}}$



Structures

- ▶ A structure \mathcal{A} of signature τ consists of
 - ▶ A non-empty set A or $u(\mathcal{A})$ called the **universe**
 - ▶ For each constant c in the signature τ , a fixed element $c_{\mathcal{A}}$ is assigned from the universe A
 - ▶ For each k -ary relation R^k in the signature τ , a set of k -tuples from A^k is assigned to $R^{\mathcal{A}}$
 - ▶ The structure \mathcal{A} is finite if A (or $u(\mathcal{A})$) is finite

Examples of Structures

A Graph

- ▶ A set V of vertices
- ▶ A set $E \subseteq V \times V$ of edges



A Graph Structure

- ▶ $\tau = \{E\}$, with E binary.

A Graph Structure

- ▶ $\tau = \{E\}$, with E binary.
 - ▶ A graph structure over τ is $\mathcal{G} = (V, E^{\mathcal{G}})$,
 - ▶ The **universe** $u(\mathcal{G})$ is the set of vertices V
 - ▶ The relation E is the edge relation

A Graph Structure

- ▶ $\tau = \{E\}$, with E binary.
 - ▶ A graph structure over τ is $\mathcal{G} = (V, E^{\mathcal{G}})$,
 - ▶ The **universe** $u(\mathcal{G})$ is the set of vertices V
 - ▶ The relation E is the edge relation
 - ▶ $\mathcal{G} = (V = \{1, 2, 3, 4\}, E^{\mathcal{G}} = \{(1, 2), (2, 3), (3, 4), (1, 1)\})$. We could just as well draw the graph for convenience.
 - ▶ $\forall x \exists y (E(x, y))$

A totally ordered set

- ▶ A set S with an order relation
- ▶ Relates any two elements of S
- ▶ Examples : $(\mathbb{N}, <)$, $(\mathbb{R}, <)$

A Total Order Structure

- ▶ $\tau = \{<, S\}$ with $<, S$ binary.

A Total Order Structure

- ▶ $\tau = \{<, S\}$ with $<$, S binary.
 - ▶ A finite order structure over τ is $\mathcal{O} = (O, <^{\mathcal{O}}, S^{\mathcal{O}})$
 - ▶ The universe $u(\mathcal{O})$ is the finite ordered set O
 - ▶ $<^{\mathcal{O}}$ is the ordering on O and $S^{\mathcal{O}}$ is the successor on O

A Total Order Structure

- ▶ $\tau = \{<, S\}$ with $<$, S binary.
 - ▶ A finite order structure over τ is $\mathcal{O} = (O, <^{\mathcal{O}}, S^{\mathcal{O}})$
 - ▶ The universe $u(\mathcal{O})$ is the finite ordered set O
 - ▶ $<^{\mathcal{O}}$ is the ordering on O and $S^{\mathcal{O}}$ is the successor on O
 - ▶ $\mathcal{O} = (O = \{1, 2, 4\}, <^{\mathcal{O}} = \{(1, 2), (1, 4), (2, 4)\}, S^{\mathcal{O}} = \{(1, 2)\})$
 - ▶ $\exists x \neg \exists y (S(x, y))$
- ▶ Can you write a **Partial Order** as a structure, where the universe consists of all subsets of a given finite set?

Words

- ▶ A word is a sequence of symbols over a (finite) alphabet
- ▶ Alphabet $\Sigma = \{a, b, c\}$
- ▶ Some words over Σ : *b, aaa, abababa, cacbccc*
- ▶ The length of a word is the number of symbols in it

A Word Structure

- ▶ $\tau = \{<, S, Q_a, Q_b\}$, where $<, S$ are binary, Q_a, Q_b are unary relations.

A Word Structure

- ▶ $\tau = \{<, S, Q_a, Q_b\}$, where $<, S$ are binary, Q_a, Q_b are unary relations.
 - ▶ A word structure $\mathcal{W} = (u(\mathcal{W}), <^{\mathcal{W}}, S^{\mathcal{W}}, Q_a^{\mathcal{W}}, Q_b^{\mathcal{W}})$

A Word Structure

- ▶ $\tau = \{<, S, Q_a, Q_b\}$, where $<, S$ are binary, Q_a, Q_b are unary relations.
 - ▶ A word structure $\mathcal{W} = (u(\mathcal{W}), <^{\mathcal{W}}, S^{\mathcal{W}}, Q_a^{\mathcal{W}}, Q_b^{\mathcal{W}})$
 - ▶ The universe $u(\mathcal{W})$ consists of the positions in a word W over symbols a, b

A Word Structure

- ▶ $\tau = \{<, S, Q_a, Q_b\}$, where $<, S$ are binary, Q_a, Q_b are unary relations.
 - ▶ A word structure $\mathcal{W} = (u(\mathcal{W}), <^{\mathcal{W}}, S^{\mathcal{W}}, Q_a^{\mathcal{W}}, Q_b^{\mathcal{W}})$
 - ▶ The universe $u(\mathcal{W})$ consists of the positions in a word W over symbols a, b
 - ▶ $<^{\mathcal{W}}$ is the ordering relation on the positions of W

A Word Structure

- ▶ $\tau = \{<, S, Q_a, Q_b\}$, where $<, S$ are binary, Q_a, Q_b are unary relations.
 - ▶ A word structure $\mathcal{W} = (u(\mathcal{W}), <^{\mathcal{W}}, S^{\mathcal{W}}, Q_a^{\mathcal{W}}, Q_b^{\mathcal{W}})$
 - ▶ The universe $u(\mathcal{W})$ consists of the positions in a word W over symbols a, b
 - ▶ $<^{\mathcal{W}}$ is the ordering relation on the positions of W
 - ▶ $S^{\mathcal{W}}$ is the successor relation on the positions of W

A Word Structure

- ▶ $\tau = \{<, S, Q_a, Q_b\}$, where $<, S$ are binary, Q_a, Q_b are unary relations.
 - ▶ A word structure $\mathcal{W} = (u(\mathcal{W}), <^{\mathcal{W}}, S^{\mathcal{W}}, Q_a^{\mathcal{W}}, Q_b^{\mathcal{W}})$
 - ▶ The universe $u(\mathcal{W})$ consists of the positions in a word W over symbols a, b
 - ▶ $<^{\mathcal{W}}$ is the ordering relation on the positions of W
 - ▶ $S^{\mathcal{W}}$ is the successor relation on the positions of W
 - ▶ $Q_a^{\mathcal{W}}$ is the set of positions labeled a in W

A Word Structure

- ▶ $\tau = \{<, S, Q_a, Q_b\}$, where $<, S$ are binary, Q_a, Q_b are unary relations.
 - ▶ A word structure $\mathcal{W} = (u(\mathcal{W}), <^{\mathcal{W}}, S^{\mathcal{W}}, Q_a^{\mathcal{W}}, Q_b^{\mathcal{W}})$
 - ▶ The universe $u(\mathcal{W})$ consists of the positions in a word W over symbols a, b
 - ▶ $<^{\mathcal{W}}$ is the ordering relation on the positions of W
 - ▶ $S^{\mathcal{W}}$ is the successor relation on the positions of W
 - ▶ $Q_a^{\mathcal{W}}$ is the set of positions labeled a in W
 - ▶ $Q_b^{\mathcal{W}}$ is the set of positions labeled b in W

A Word Structure

- ▶ $\tau = \{<, S, Q_a, Q_b\}$, where $<, S$ are binary, Q_a, Q_b are unary relations.
 - ▶ A word structure $\mathcal{W} = (u(\mathcal{W}), <^{\mathcal{W}}, S^{\mathcal{W}}, Q_a^{\mathcal{W}}, Q_b^{\mathcal{W}})$
 - ▶ The universe $u(\mathcal{W})$ consists of the positions in a word W over symbols a, b
 - ▶ $<^{\mathcal{W}}$ is the ordering relation on the positions of W
 - ▶ $S^{\mathcal{W}}$ is the successor relation on the positions of W
 - ▶ $Q_a^{\mathcal{W}}$ is the set of positions labeled a in W
 - ▶ $Q_b^{\mathcal{W}}$ is the set of positions labeled b in W
 - ▶ The structure with $u(\mathcal{W}) = \{0, 1, 2, \dots, 8\}$,
 $Q_a^{\mathcal{W}} = \{0, 1, 4, 6, 8\}$, $Q_b^{\mathcal{W}} = \{2, 3, 5, 7\}$,
 - ▶ $<^{\mathcal{W}} = \{(0, 1), (0, 2), \dots, (7, 8)\}$, $S^{\mathcal{W}} = \{(0, 1), (1, 2), \dots, (7, 8)\}$ uniquely defines the word $W = \text{aabbababa}$.
 - ▶ $\forall x(Q_b(x) \rightarrow \exists y(x < y \wedge Q_a(y)))$