

# CS-226: Digital Logic Design Logic

---

Virendra Singh

Professor

Computer Architecture and Dependable Systems Lab

Department of Electrical Engineering

Indian Institute of Technology Bombay

<http://www.ee.iitb.ac.in/~viren/>

E-mail: [viren@ee.iitb.ac.in](mailto:viren@ee.iitb.ac.in)



11 January 2021

CADSL

# System Realization Process

---

**Customer's need**

**Determine requirements**

**Write specifications**

**Design synthesis and Verification**

**Test development**

**Fabrication**

**Manufacturing test**

**System to customer**



# What is Engineering

---

- ✓ “**Design under constraint**. Engineers design solutions to problems. However there are a set of constraints that we have to satisfy -- size, weight, reliability, safety, economic factors, environmental impact, manufacturability, and a whole list of “--bilities” (Wulf)
- ✓ the profession in which a knowledge of the mathematical and natural sciences gained by study, experience, and practices are **applied with judgments** to develop ways to utilize economically the materials and **forces of nature for the benefit of mankind**.  
(Accreditation Board for Engineering and Technology (ABET, 2002))



# Digital System



# LOGIC



# What is logic?

---

- Logic is the study of valid reasoning.
- That is, logic tries to establish criteria to decide whether some piece of reasoning is valid or invalid.



# Valid Reasoning

---

- While in every piece of reasoning certain statements are *claimed to* follow from others, this may in fact not be the case.
- Example: “If I win the lottery, then I’m happy. However, I did not win the lottery. Therefore, I am not happy.”
- A piece of reasoning is *valid* if the statements that are claimed to follow from previous ones do *indeed* follow from those. Otherwise, the reasoning is said to be *invalid*.



# Logic

---

- Crucial for mathematical reasoning
- Used for designing electronic circuitry
- Logic is a system based on **propositions**.
- A proposition is a statement that is either **true** or **false** (not both).





# The Statement/Proposition

---

- “Elephants are bigger than mice.”

Is this a statement? *yes*

Is this a proposition? *yes*

What is the truth value  
of the proposition? *true*



# Introduction: PL

---

- In Propositional Logic (a.k.a Propositional Calculus or Sentential Logic), the objects are called **propositions**
- **Definition:** A proposition is a statement that is either **true** or **false**, but not both
- We usually denote a proposition by a letter:  $p$ ,  $q$ ,  $r$ ,  $s$ , ...



# Introduction: Proposition

---

- **Definition:** The value of a proposition is called its **truth value**; denoted by
  - $T$  or 1 if it is true or
  - $F$  or 0 if it is false
- Opinions, interrogative, and imperative are not propositions
- **Truth table**

$p$
0
1



# Propositions: Examples

---

- The following are propositions
  - Today is Thursday     $M$
  - The floor is wet     $W$
  - It is raining     $R$
- The following are not propositions
  - Python is the best language    *Opinion*
  - When will be the next class?    *Interrogative*
  - Do your homework    *Imperative*



# Are these propositions?

---

- $2+2=7$  Yes, False
- Every integer is divisible by 10 Yes
- Google is an excellent company No



# Logical Operators

---

- Operators/Connectives are used to create a compound proposition from two or more propositions
  - Negation (denote  $\neg$  or ! Or  $\sim$ )
  - And or logical conjunction (denoted  $\wedge$  or . ) – logical AND
  - Or or logical disjunction (denoted  $\vee$  or +) – logical OR
  - XOR or exclusive or (denoted  $\oplus$ )
  - Implication (denoted  $\Rightarrow$  or  $\rightarrow$ )
  - Biconditional (denoted  $\Leftrightarrow$  or  $\leftrightarrow$ )

We define the meaning (semantics) of the logical operators/connectives using **truth tables**



# Logical Operator: Negation

---

- $\neg p$ , the negation of a proposition  $p$ , is also a proposition
- Examples:
  - Today is not Monday.
- **Truth table**

$p$	$\neg p$
0	1
1	0



# Logical Operator: Logical And

- The logical operator **And** is true only when both of the propositions are true. It is also called a conjunction
- Examples
  - It is raining and it is cold
  - $(2+3=5)$  and  $(1<2)$
  - Ramesh's cow is dead and Ramesh's is not dead.
- Truth table

$p$	$q$	$p \wedge q$
0	0	
0	1	
1	0	
1	1	





# Logical Operator: Logical Or

- The logical disjunction, or logical Or, is true if one or both of the propositions are true.
- Examples
  - It is raining or it is the second lecture
  - $(2+2=5) \vee (1<2)$
  - You may have cake or ice cream

- **Truth table**

$p$	$q$	$p \wedge q$	$p \vee q$
0	0	0	
0	1	0	
1	0	0	
1	1	1	



# Logical Operator: Exclusive Or

- The exclusive Or, or XOR, of two propositions is true when exactly one of the propositions is true and the other one is false
- Example
  - The circuit is either ON or OFF but not both
  - Let  $ab < 0$ , then either  $a < 0$  or  $b < 0$  but not both
  - You may have cake or ice cream, but not both
- Truth table

$p$	$q$	$p \wedge q$	$p \vee q$	$p \oplus q$
0	0	0	0	
0	1	0	1	
1	0	0	1	
1	1	1	1	



# Logical Operator: Implication

- **Definition:** Let  $p$  and  $q$  be two propositions. The implication  $p \rightarrow q$  is the proposition that is false when  $p$  is true and  $q$  is false and true otherwise
  - $p$  is called the hypothesis, antecedent, premise
  - $q$  is called the conclusion, consequence
- **Truth table**

$p$	$q$	$p \wedge q$	$p \vee q$	$p \oplus q$	$p \Rightarrow q$
0	0	0	0	0	
0	1	0	1	1	
1	0	0	1	1	
1	1	1	1	0	



# Logical Operator: Implication

---

- The implication of  $p \rightarrow q$  can be also read as
  - If  $p$  then  $q$
  - $p$  implies  $q$
  - If  $p, q$
  - $p$  **only** if  $q$
  - $q$  if  $p$
  - $q$  when  $p$
  - $q$  whenever  $p$
  - $q$  follows from  $p$
  - $p$  is a **sufficient** condition for  $q$  ( $p$  is sufficient for  $q$ )
  - $q$  is a **necessary** condition for  $p$  ( $q$  is necessary for  $p$ )



# Logical Operator: Implication

---

- Examples
  - If you buy you air ticket in advance, it is cheaper.
  - If  $x$  is an integer, then  $x^2 \geq 0$ .
  - If it rains, the grass gets wet.
  - If the sprinklers operate, the grass gets wet.



# Exercise: Which of the following implications is true?

---

- If -1 is a positive number, then  $2+2=5$   $\top$
- If -1 is a positive number, then  $2+2=4$   $\top$
- If  $\sin x = 0$ , then  $x = 0$   $\top$



# Logical Operator: Equivalence

- **Definition:** The equivalence/biconditional  $p \leftrightarrow q$  is the proposition that is true when  $p$  and  $q$  have the same truth values. It is false otherwise.
- Note that it is equivalent to  $(p \rightarrow q) \wedge (q \rightarrow p)$
- **Truth table**

$p$	$q$	$p \wedge q$	$p \vee q$	$p \oplus q$	$p \rightarrow q$	$p \leftrightarrow q$
0	0	0	0	0	1	
0	1	0	1	1	1	
1	0	0	1	1	0	
1	1	1	1	0	1	



# Logical Operator: Equivalence

---

- The biconditional  $p \leftrightarrow q$  can be equivalently read as
  - $p$  if **and only** if  $q$
  - $p$  is a **necessary and sufficient** condition for  $q$
  - if  $p$  then  $q$ , and **conversely**
  - $p$  iff  $q$
- Examples
  - $x > 0$  if and only if  $x^2$  is positive
  - You may have pudding iff you eat your meal





# Which of the following equivalence/biconditionals is true?

---

•  $x^2 + y^2 = 0$  if and only if  $x=0$  and  $y=0$   $\top$

•  $2 + 2 = 4$  if and only if  $\sqrt{2} < 2$   $\top$

•  $x^2 \geq 0$  if and only if  $x \geq 0$   $\text{F}$



# Truth Tables

- Truth tables are used to show/define the relationships between the truth values of
  - the individual propositions and
  - the compound propositions based on them

$p$	$q$	$p \wedge q$	$p \vee q$	$p \oplus q$	$p \Rightarrow q$	$p \Leftrightarrow q$
0	0	0	0	0	1	1
0	1	0	1	1	1	0
1	0	0	1	1	0	0
1	1	1	1	0	1	1



# Constructing Truth Tables

- Construct the truth table for the following compound proposition

$$((p \wedge q) \vee \neg q)$$

$p$	$q$	$p \wedge q$	$\neg q$	$((p \wedge q) \vee \neg q)$
0	0	0	1	1
0	1	0	0	0
1	0	0	1	1
1	1	1	0	1



# How to Specify Arithmetic Operations?



# Number System



# Why Binary Arithmetic?

---

$$3 + 5$$



$$= 8$$

$$0011 + 0101$$



$$= 1000$$

# Number Systems – Representation

- Positive radix, positional number systems
- A number with *radix*  $r$  is represented by a string of digits:

$$A_{n-1}A_{n-2} \dots A_1A_0 \cdot A_{-1}A_{-2} \dots A_{-m+1}A_{-m}$$

in which  $0 \leq A_i < r$  and  $.$  is the *radix point*.

- The string of digits represents the power series:

$$\begin{aligned} (\text{Number})_r &= \left( \sum_{i=0}^{i=n-1} A_i \cdot r^i \right) + \left( \sum_{j=-m}^{j=-1} A_j \cdot r^j \right) \\ &\quad \text{(Integer Portion)} \quad \quad \quad + \quad \quad \quad \text{(Fraction Portion)} \end{aligned}$$



# Number Systems – Examples

	General	Decimal	Binary
Radix (Base)	$r$	10	2
Digits	$0 \Rightarrow r - 1$	$0 \Rightarrow 9$	$0 \Rightarrow 1$
Powers of Radix	0	$r^0$	1
	1	$r^1$	2
	2	$r^2$	4
	3	$r^3$	8
	4	$r^4$	16
	5	$r^5$	32
	-1	$r^{-1}$	0.5
	-2	$r^{-2}$	0.25
	-3	$r^{-3}$	0.125
	-4	$r^{-4}$	0.0625
	-5	$r^{-5}$	0.03125





# Special Powers of 2

---

$2^{10}$  (1024) is Kilo, denoted "K"

$2^{20}$  (1,048,576) is Mega, denoted "M"

$2^{30}$  (1,073, 741,824) is Giga, denoted "G"



# Positive Powers of 2

---

- Useful for Base Conversion

Exponent	Value
0	1
1	2
2	4
3	8
4	16
5	32
6	64
7	128
8	256
9	512
10	1024

Exponent	Value
11	2,048
12	4,096
13	8,192
14	16,384
15	32,768
16	65,536
17	131,072
18	262,144
19	524,288
20	1,048,576
21	2,097,152



# Converting Binary to Decimal

- To convert to decimal, use decimal arithmetic to form S (digit  $\times$  respective power of 2).
- Example: Convert  $11010_2$  to  $N_{10}$ :

Powers of 2:      43210

11010

$$\Rightarrow 1 \times 2^4 = 16$$

$$\Rightarrow 1 \times 2^3 = 8$$

$$\Rightarrow 0 \times 2^2 = 0$$

$$\Rightarrow 1 \times 2^1 = 2$$

$$\Rightarrow 0 \times 2^0 = 0$$

$$\text{Sum} \quad \Rightarrow = 26_{10}$$



# Converting Decimal to Binary

---

- Method 1
  - Subtract the largest power of 2 that gives a positive remainder and record the power.
  - Repeat, subtracting from the prior remainder and recording the power, until the remainder is zero.
  - Place 1's in the positions in the binary result corresponding to the powers recorded; in all other positions place 0's.
- Example: Convert  $625_{10}$  to  $N_2$



# Converting Decimal to Binary

- Subtract the largest power of 2 (see slide 14) that gives a positive remainder and record the power.
- Repeat, subtracting from the prior remainder and recording the power, until the remainder is zero.
- Place 1's in the positions in the binary result corresponding to the powers recorded; in all other positions place 0's.
- Example: Convert  $625_{10}$  to  $N_2$

→	625 - 512	= 113	⇒9
→	113 - 64	= 49	⇒6
→	49 - 32	= 17	⇒5
→	17 - 16	= 1	⇒4
→	1 - 1	= 0	⇒0
→	Placing 1's in the result for the positions recorded and 0's elsewhere:		
	9876543210		
→	1001110001		



# Commonly Occurring Bases

---

Name	Radix	Digits
Binary	2	0,1
Octal	8	0,1,2,3,4,5,6,7
Decimal	10	0,1,2,3,4,5,6,7,8,9
Hexadecimal	16	0,1,2,3,4,5,6,7,8,9,A,B,C,D,E,F

The six letters (in addition to the 10 integers) in hexadecimal represent:

10, 11, 12, 13, 14, 15



# Signed Magnitude?

---

- Use fixed length binary representation
- Use left-most bit (called *most significant bit* or MSB) for sign:

0 for positive

1 for negative



- Example:  $+18_{\text{ten}} = 00010010_{\text{two}}$   
 $-18_{\text{ten}} = 10010010_{\text{two}}$



# Difficulties with Signed Magnitude

---

- Sign and magnitude bits should be differently treated in arithmetic operations.
- Addition and subtraction require different logic circuits.
- Overflow is difficult to detect.
- “Zero” has two representations:
$$+ 0_{\text{ten}} = 00000000_{\text{two}}$$
$$- 0_{\text{ten}} = 10000000_{\text{two}}$$
- *Signed-integers are not used in modern computers.*





# Thank You

