







NCHC Open Hackathon

Final Presentation Plantmen

2024/12/4









Mentor

Members

Jay Chen & Cliff Chiu







機器學習與機器視覺實驗室 Lab of Machine Learning and Machine Vision








Plantman

Introduction

Plantman is an AI system that combines image recognition and natural language generation to provide automated disease, pest, and disorder (DPD) identification and real-time consultation services for farmers.







Programming language Python

Library usedPytorch, ONNX, CUDA, TensorRT

Algorithmic motifs Neural Network Embedo

Neural Network, Embedding matching, Attention mechanism










Plantman | System architecture







Problem to be solved

- 1. High user volume causes long query-response delays
- 2. LINE platform limits streaming, reducing user experience
- 3. Majority of time consumed by RAG processing





(Speed up 4x)







End-to-end inference time before acceleration

Time Cost of RAG Processing 100 Queries Simultaneously

	RAG	
	Reranker	LLM
Model	BAAI/bge-reranker-v2-m3	Breeze-7B-Instruct-v1_0
Framework	PyTorch (FP32)	Ollama (FP32)
Time cost	1389 sec.	
Speed	13.89 sec./query	







End-to-end inference time after acceleration

Time Cost of RAG Processing 100 Queries Simultaneously

	RAG	
	Reranker	LLM
Model	BAAI/bge-reranker-v2-m3	Breeze-7B-Instruct-v1_0
Framework	TensorRT (FP16)	TensorRT-LLM (INT8)
Time cost	104.47 sec.	
Speed	1.04 sec./query	


Speed up 10x








End-to-end inference time










Acceleration process



Reranker



LLM







Reranker Acceleration

- 1. Switch framework from PyTorch to **TensorRT**
- 2. Deploy inference process on Triton Server
- 3. Performance metric: sec./query (time to compare one query with 512 passages)

Time Cost of Reranker Processing 100 Queries Simultaneously

	Throughput (sec./query)	Computing time (sec.)
PyTorch (FP32)	13.78	1378
TensorRT (FP16)	1.17	117
Speedup	11.78x	11.78x





LLM Acceleration

- 1. Switch platform from Ollama to TensorRT-LLM
- 2. Deploy inference process on **Triton Server**
- 3. Performance metric: tokens/sec.

Time Cost of LLM Processing 100 Queries Simultaneously

	Throughput (token/sec.)	Computing time (sec.)
Ollama (FP32)	150.05	880.07
TensorRT-LLM (FP16)	7532.69	17.53
TensorRT-LLM (INT8)	8217.17	15.97
Speedup	55x	55x






LINE user experience optimization

Segment LLM outputs for step-by-step delivery

→ The time it takes for the user to receive the first reply was reduces from 22.94 seconds to 3.98 seconds.









What do we learn

- 1. Deployed on Triton Server for efficiency.
- 2. Converted LLM and reranker weights to TensorRT-LLM and TensorRT.
- 3. Used Nsight NVTX for performance profiling.









Future Work

- 1. Migrate entire workflow back to the lab
- 2. Integrate Embedding model to reduce passage comparisons in RAG







Conclusion

- Transformed models into TensorRT inference engines.
- 2. Deployed inference models on Triton Server.
- 3. Achieved 10x speed-up in E2E inference time.
- 4. Users now receive replies in just 3 seconds.

